

## **Oracle9i Application Server**

Release Notes

Release 2 (9.0.2.0.1) for AIX-Based Systems, Compaq Tru64  
UNIX, HP 9000 Series HP-UX, and Linux Intel

**Part No. B10056-02**

January 2003

Oracle9i Application Server Release Notes, Release 2 (9.0.2.0.1) for AIX-Based Systems, Compaq Tru64 UNIX, HP 9000 Series HP-UX, and Linux Intel

Part No. B10056-02

Copyright © 2002, 2003 Oracle Corporation. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information of Oracle Corporation; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent and other intellectual and industrial property laws. Reverse engineering, disassembly or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. Oracle Corporation does not warrant that this document is error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Oracle Corporation.

If the Programs are delivered to the U.S. Government or anyone licensing or using the programs on behalf of the U.S. Government, the following notice is applicable:

**Restricted Rights Notice** Programs delivered subject to the DOD FAR Supplement are "commercial computer software" and use, duplication, and disclosure of the Programs, including documentation, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement. Otherwise, Programs delivered subject to the Federal Acquisition Regulations are "restricted computer software" and use, duplication, and disclosure of the Programs shall be subject to the restrictions in FAR 52.227-19, Commercial Computer Software - Restricted Rights (June, 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and Oracle Corporation disclaims liability for any damages caused by such use of the Programs.

Oracle is a registered trademark, and Oracle*MetaLink*, Oracle Store, Oracle9i, Oracle9iAS Discoverer, SQL\*Plus, and PL/SQL are trademarks or registered trademarks of Oracle Corporation. Other names may be trademarks of their respective owners.

---

---

# Contents

<b>Send Us Your Comments</b> .....	ix
<b>Preface</b> .....	xi
Intended Audience .....	xi
Documentation Accessibility .....	xi
Organization.....	xii
Related Documentation .....	xii
Conventions.....	xiii
<b>1 Summary of Changes</b>	
1.1 Purpose of this Document.....	1-2
1.2 Component Release Notes .....	1-2
1.3 Operating System Requirements .....	1-3
1.4 Certification Information.....	1-8
1.5 Licensing Information.....	1-8
1.6 Deprecated Features .....	1-9
<b>2 Installation and Migration Issues</b>	
2.1 Installation Issues .....	2-2
2.1.1 Oracle9iAS Installation and Multiple Operating System Users.....	2-2
2.1.2 Multiple Infrastructure-based Deployment .....	2-2
2.1.3 Start Dependencies When Installing Against Oracle9iAS Infrastructure.....	2-3
2.1.4 Prompt for Database Files Location During Install.....	2-4
2.1.5 Modification in init.ora for Oracle9iAS Metadata Repository.....	2-4

2.1.6	Multiple Install Types into the Same Infrastructure Instance Overwrites Portal.	2-4
2.1.7	Oracle9iAS Wireless Installation Requires Oracle9iAS Portal.....	2-5
2.1.8	Oracle HTTP Server Does Not Start if SSO/mod_osso Registration Failed.....	2-5
2.1.9	Enabling Oracle9iAS Web Cache and mod_osso .....	2-5
2.1.10	Report Configuration Assistant Fails During Installation .....	2-6
2.1.11	Service Errors and NoClassDefFound Exceptions .....	2-7
2.1.12	Ulimit and Swap File Settings .....	2-8
2.1.13	Preinstallation Packages for Linux Intel .....	2-8
2.1.14	Installing on Red Hat Linux.....	2-9
2.1.15	Using Oracle Internet File System on Red Hat Linux.....	2-9
2.1.16	Default Port Number for Oracle Internet Directory on Linux.....	2-9
2.1.17	Oracle Universal Installer on Linux.....	2-9
2.1.18	Installing on HP 9000 Series HP-UX.....	2-10
2.2	Postinstallation Issues.....	2-11
2.2.1	DISPLAY Environment Variable is Set to localhost:0.....	2-11
2.3	Deinstallation Issues.....	2-11
2.4	Reinstallation Issues.....	2-11
2.5	Migration Issues.....	2-11
2.5.1	Kernel Mode Restriction on IBM AIX 5L-based Systems.....	2-11

### 3 Management and Security Issues

3.1	Management Issues.....	3-2
3.1.1	Run dcmctl to Update Configuration for Manual Configuration Changes.....	3-3
3.1.2	Using emctl to Change the ias_admin Password .....	3-3
3.1.3	OPMN Cannot Start OC4J Instance with Multibyte .....	3-3
3.1.4	Clock Synchronization.....	3-4
3.1.5	Use Port Option to Configure Loading Application.....	3-4
3.1.6	Oracle Enterprise Manager Does Not Display OC4J Metrics in the Home Page..	3-4
3.1.7	Changing the ias_admin Password in Translated Versions of OEM .....	3-4
3.1.8	“opmnctl restart” Displays Harmless “Unavailable Hostname” Message.....	3-4
3.1.9	Attributes Containing Paths Break Cluster Model.....	3-5
3.1.10	Oracle Enterprise Manager Does Not Support Multiple Locales.....	3-5
3.1.11	Operating System Patches for Host Metrics.....	3-5
3.1.12	Deploying BC4J JSP, UIX JSP and UIX XML Applications Using OEM .....	3-6
3.1.13	Restart OC4J When User Manager is Changed From JAZN LDAP To XML.....	3-6

3.1.14	Incorrect Indication of Oracle Internet Directory Status .....	3-6
3.1.15	Configuring JAAS with Oracle Enterprise Manager Web Site.....	3-7
3.1.16	Oracle9iAS Wireless Status Incorrectly Displayed as Down on Oracle Enterprise Manager Page	3-8
3.1.17	OEM Intelligent Agent May Work Incorrectly in Non-English Environment.....	3-9
3.1.18	Concurrent Administrative Operations on a Cluster Not Supported.....	3-10
3.2	Security Issues.....	3-11
3.2.1	Avoid Adding User Certificates to Trustpoints or Trusted Certificate Lists .....	3-11
3.2.2	Restrict Root Privileges to Oracle9iAS Web Cache Users .....	3-11
3.2.3	JAZN Demo Data Needs to be Loaded into LDAP if JAZN LDAP is Global User Manager	3-12

## 4 Component Issues

4.1	Oracle HTTP Server Issues.....	4-2
4.1.1	Running More than 1024 Oracle HTTP Server Processes .....	4-2
4.1.2	Ignore FASTCGI Error Messages After Installation .....	4-2
4.2	Oracle9i XML Developer Kit Issues.....	4-3
4.2.1	Certification and System Requirements .....	4-3
4.2.2	General Issues and Workarounds.....	4-3
4.3	Oracle9iAS Portal Issues.....	4-4
4.3.1	Problems Logging In When Two Oracle HTTP Servers are on the Same Host and are Using Internet Explorer with SSL Configuration	4-4
4.3.2	Creating Non-English PL/SQL Functions and Procedures.....	4-5
4.3.3	Link to Portal Monitoring Services Not Working .....	4-5
4.3.4	NLS Cannot Be Authenticated By Oracle9iAS Single Sign-On if Username Contains Non-ASCII Characters	4-7
4.4	Oracle9iAS Wireless Issues .....	4-8
4.4.1	Cannot Create a Quicklink for a Module.....	4-8
4.4.2	Running Oracle9iAS Wireless Against an upgraded OID .....	4-8
4.5	Oracle9iAS Web Cache Issues .....	4-9
4.5.1	Variations in Host Names of Client Request URLs Should be Defined.....	4-9
4.5.2	DAVOrWebCacheReadOnly Parameter Does Not Work .....	4-9
4.5.3	Cannot Change Wallet Directory in Web Cache Manager .....	4-10
4.5.4	Internet Explorer Limitation with Keep-Alive Setting .....	4-10
4.5.5	Using newgrp Command on Linux Intel.....	4-10
4.6	Oracle9iAS Reports Services Issues .....	4-11

4.6.1	Graph not Generating Oracle6i Graphics .....	4-11
4.6.2	Configuration of Reports Server with Oracle Enterprise Manager .....	4-12
4.6.3	Shutting Down the Reports Server from Oracle Enterprise Manager.....	4-12
4.7	Oracle9iAS Clickstream Intelligence Issues.....	4-13
4.7.1	Configuring Clickstream After Installing Oracle9iAS Using Oracle Universal Installer 4-13	
4.7.2	Error Displaying Clickstream Runtime Administrator .....	4-14
4.8	Oracle9iAS Single Sign-On Issues.....	4-16
4.8.1	Logging Out from Oracle9iAS Single Sign-On Enabled Applications Leaves Non-Oracle9iAS Single Sign-On Enabled Applications Open and Vice Versa	4-16
4.9	Oracle9iAS Unified Messaging.....	4-16
4.10	Oracle9iAS Proxy Plug-in.....	4-17

## 5 Documentation Errata

5.1	<i>Oracle9i Application Server Installation Guide</i> .....	5-2
5.1.1	InterConnect Software .....	5-2
5.2	Oracle9i Application Server Concepts.....	5-2
5.2.1	Characterization of New iPlanet Connector.....	5-2
5.3	<i>Oracle9i Application Server Administrator's Guide</i> .....	5-3
5.3.1	Association Middle-Tier Installations with an Infrastructure .....	5-3
5.4	Oracle9i Application Server Security Guide.....	5-4
5.4.1	SSLPassPhraseDialog Not Valid in Virtual Host Context.....	5-4
5.4.2	Remove PLSqlEnableConnectionPooling from Configured dads.conf File.....	5-4
5.4.3	Updated Information Regarding Oracle9iAS Portal Default User Accounts.....	5-4
5.4.4	Updated Information for Default User Password Policy .....	5-5
5.5	Oracle9i Application Server Globalization Support Guide.....	5-6
5.5.1	Multilingual Support for Oracle9iAS Single Sign-On.....	5-6
5.5.2	Updated Instructions for Deploying World-of-Books Demo .....	5-6
5.6	Oracle9i Application Server: Migrating from Oracle Application Server.....	5-8
5.6.1	Updated ossoconvert or ssl2ossl Migration Tool Information .....	5-8
5.7	Oracle Syndication Server User's and Administrator's Guide .....	5-9
5.7.1	Using Oracle9iAS Single Sign-On with Oracle9iAS Syndication Server.....	5-9
5.8	<i>Oracle9i Application Developer's Guide - XML</i> .....	5-10
5.9	Online Help .....	5-10
5.9.1	Broken Links to DAS Online Help.....	5-11

5.9.2 Online Help May Not Display Correct Language..... 5-11



---

---

# Send Us Your Comments

**Oracle9i Application Server Release Notes, Release 2 (9.0.2.0.1) for AIX-Based Systems, Compaq Tru64 UNIX, HP 9000 Series HP-UX, and Linux Intel**

**Part No. B10056-02**

Oracle Corporation welcomes your comments and suggestions on the quality and usefulness of this document. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most?

If you find any errors or have any other suggestions for improvement, please indicate the document title and part number, and the chapter, section, and page number (if available). You can send comments to us in the following ways:

- Email: [osdwrite\\_us@oracle.com](mailto:osdwrite_us@oracle.com)
- Postal service:  
Oracle Corporation  
Oracle9i Application Server Documentation  
Attn: Michael Boyarski  
500 Oracle Parkway  
Redwood Shores, CA 94065  
USA

If you would like a reply, please give your name, address, telephone number, and (optionally) electronic mail address.

If you have problems with the software, please contact your local Oracle Support Services.



---

# Preface

This preface contains the following topics:

- [Intended Audience](#)
- [Documentation Accessibility](#)
- [Organization](#)
- [Related Documentation](#)
- [Conventions](#)

## Intended Audience

The Oracle9i Application Server Release Notes is intended for anyone interested in Oracle9i Application Server.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Standards will continue to evolve over time, and Oracle Corporation is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For additional information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

### **Accessibility of Links to External Web Sites in Documentation**

This documentation may contain links to Web sites of other companies or organizations that Oracle Corporation does not own or control. Oracle Corporation neither evaluates nor makes any representations regarding the accessibility of these Web sites.

## **Organization**

This document contains:

### **Chapter 1, "Summary of Changes"**

This chapter provides the latest information about operating system requirements, deprecated features, licensing information, and provides links to component release notes.

### **Chapter 2, "Installation and Migration Issues"**

This chapter contains the latest information for installation, deinstallation, reinstallation, and migration.

### **Chapter 3, "Management and Security Issues"**

This chapter summarizes management and security issues associated with Oracle9i Application Server.

### **Chapter 4, "Component Issues"**

This chapter summarizes component issues associated with Oracle9i Application Server.

### **Chapter 5, "Documentation Errata"**

This chapter presents documentation errata for Oracle9i Application Server documentation set.

## **Related Documentation**

For more information, see these Oracle resources:

- Oracle9i Application Server Documentation Library
- Oracle9i Application Server Platform-Specific Documentation on Oracle9i Application Server Disk 1

In North America, printed documentation is available for sale in the Oracle Store at <http://oraclestore.oracle.com/>

Customers in Europe, the Middle East, and Africa (EMEA) can purchase documentation from

<http://www.oraclebookshop.com/>

Other customers can contact their Oracle representative to purchase printed documentation.

To download free release notes, installation documentation, white papers, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

<http://otn.oracle.com/admin/account/membership.html>

If you already have a username and password for OTN, then you can go directly to the documentation section of the OTN Web site at

<http://otn.oracle.com/docs/index.htm>

## Conventions

This section describes the conventions used in the text and code examples of this documentation set. It describes:

- [Conventions in Text](#)
- [Conventions in Code Examples](#)
- [Conventions for Microsoft Windows Operating Systems](#)

### Conventions in Text

We use various conventions in text to help you more quickly identify special terms. The following table describes those conventions and provides examples of their use.

Convention	Meaning	Example
<b>Bold</b>	Bold typeface indicates terms that are defined in the text or terms that appear in a glossary, or both. Bold also indicate a GUI element.	When you specify this clause, you create an <b>index-organized table</b> .

Convention	Meaning	Example
<i>Italics</i>	Italic typeface indicates book titles or emphasis.	<i>Oracle9i Database Concepts</i> Ensure that the recovery catalog and target database do <i>not</i> reside on the same disk.
UPPERCASE monospace (fixed-width) font	Uppercase monospace typeface indicates elements supplied by the system. Such elements include parameters, privileges, datatypes, RMAN keywords, SQL keywords, SQL*Plus or utility commands, packages and methods, as well as system-supplied column names, database objects and structures, usernames, and roles.	You can specify this clause only for a NUMBER column. You can back up the database by using the BACKUP command. Query the TABLE_NAME column in the USER_TABLES data dictionary view. Use the DBMS_STATS.GENERATE_STATS procedure.
lowercase monospace (fixed-width) font	Lowercase monospace typeface indicates executables, filenames, directory names, and sample user-supplied elements. Such elements include computer and database names, net service names, and connect identifiers, as well as user-supplied database objects and structures, column names, packages and classes, usernames and roles, program units, and parameter values.  <b>Note:</b> Some programmatic elements use a mixture of UPPERCASE and lowercase. Enter these elements as shown.	Enter sqlplus to open SQL*Plus. The password is specified in the orapwd file. Back up the datafiles and control files in the /disk1/oracle/dbs directory. The department_id, department_name, and location_id columns are in the hr.departments table. Set the QUERY_REWRITE_ENABLED initialization parameter to true. Connect as oe user. The JRepUtil class implements these methods.
lowercase italic monospace (fixed-width) font	Lowercase italic monospace font represents placeholders or variables.	You can specify the <i>parallel_clause</i> . Run <i>Uold_release</i> .SQL where <i>old_release</i> refers to the release you installed prior to upgrading.

## Conventions in Code Examples

Code examples illustrate SQL, PL/SQL, SQL\*Plus, or other command-line statements. They are displayed in a monospace (fixed-width) font and separated from normal text as shown in this example:

```
SELECT username FROM dba_users WHERE username = 'MIGRATE';
```

The following table describes typographic conventions used in code examples and provides examples of their use.

Convention	Meaning	Example
[ ]	Brackets enclose one or more optional items. Do not enter the brackets.	DECIMAL ( <i>digits</i> [ , <i>precision</i> ])
{ }	Braces enclose two or more items, one of which is required. Do not enter the braces.	{ENABLE   DISABLE}
	A vertical bar represents a choice of two or more options within brackets or braces. Enter one of the options. Do not enter the vertical bar.	{ENABLE   DISABLE} [COMPRESS   NOCOMPRESS]
...	Horizontal ellipsis points indicate either: <ul style="list-style-type: none"> <li>■ That we have omitted parts of the code that are not directly related to the example</li> <li>■ That you can repeat a portion of the code</li> </ul>	CREATE TABLE ... AS <i>subquery</i> ;  SELECT <i>col1, col2, ... , coln</i> FROM employees;
.	Vertical ellipsis points indicate that we have omitted several lines of code not directly related to the example.	
Other notation	You must enter symbols other than brackets, braces, vertical bars, and ellipsis points as shown.	acctbal NUMBER(11,2); acct CONSTANT NUMBER(4) := 3;
<i>Italics</i>	Italicized text indicates placeholders or variables for which you must supply particular values.	CONNECT SYSTEM/ <i>system_password</i> DB_NAME = <i>database_name</i>
UPPERCASE	Uppercase typeface indicates elements supplied by the system. We show these terms in uppercase in order to distinguish them from terms you define. Unless terms appear in brackets, enter them in the order and with the spelling shown. However, because these terms are not case sensitive, you can enter them in lowercase.	SELECT last_name, employee_id FROM employees; SELECT * FROM USER_TABLES; DROP TABLE hr.employees;

Convention	Meaning	Example
lowercase	<p>Lowercase typeface indicates programmatic elements that you supply. For example, lowercase indicates names of tables, columns, or files.</p> <p><b>Note:</b> Some programmatic elements use a mixture of UPPERCASE and lowercase. Enter these elements as shown.</p>	<pre>SELECT last_name, employee_id FROM employees;  sqlplus hr/hr  CREATE USER mjones IDENTIFIED BY ty3MU9;</pre>

## Conventions for Microsoft Windows Operating Systems

The following table describes conventions for Microsoft Windows operating systems and provides examples of their use.

Convention	Meaning	Example
Choose Start >	How to start a program.	To start the Oracle Database Configuration Assistant, choose Start > Programs > Oracle - <i>HOME_NAME</i> > Configuration and Migration Tools > Database Configuration Assistant.
File and directory names	File and directory names are not case sensitive. The following special characters are not allowed: left angle bracket (<), right angle bracket (>), colon (:), double quotation marks ("), slash (/), pipe ( ), and dash (-). The special character backslash (\) is treated as an element separator, even when it appears in quotes. If the file name begins with \\, then Windows assumes it uses the Universal Naming Convention.	<pre>c:\winnt"\"system32 is the same as C:\WINNT\SYSTEM32</pre>
C:\>	Represents the Windows command prompt of the current hard disk drive. The escape character in a command prompt is the caret (^). Your prompt reflects the subdirectory in which you are working. Referred to as the <i>command prompt</i> in this manual.	C:\oracle\oradata>

Convention	Meaning	Example
	<p>The backslash (\) special character is sometimes required as an escape character for the double quotation mark (") special character at the Windows command prompt. Parentheses and the single quotation mark (') do not require an escape character. Refer to your Windows operating system documentation for more information on escape and special characters.</p>	<pre>C:\&gt;exp scott/tiger TABLES=emp QUERY=\ "WHERE job='SALESMAN' and sal&lt;1600\" C:\&gt;imp SYSTEM/password FROMUSER=scott TABLES=(emp, dept)</pre>
<i>HOME_NAME</i>	<p>Represents the Oracle home name. The home name can be up to 16 alphanumeric characters. The only special character allowed in the home name is the underscore.</p>	<pre>C:\&gt; net start OracleHOME_ NAMETNSListener</pre>

Convention	Meaning	Example
<i>ORACLE_HOME</i> and <i>ORACLE_BASE</i>	<p>In releases prior to Oracle8i release 8.1.3, when you installed Oracle components, all subdirectories were located under a top level <i>ORACLE_HOME</i> directory that by default used one of the following names:</p> <ul style="list-style-type: none"> <li>■ C:\orant for Windows NT</li> <li>■ C:\orawin95 for Windows 95</li> <li>■ C:\orawin98 for Windows 98</li> </ul> <p>This release complies with Optimal Flexible Architecture (OFA) guidelines. All subdirectories are not under a top level <i>ORACLE_HOME</i> directory. There is a top level directory called <i>ORACLE_BASE</i> that by default is C:\oracle. If you install Oracle9i release 1 (9.0.1) on a computer with no other Oracle software installed, then the default setting for the first Oracle home directory is C:\oracle\ora90. The Oracle home directory is located directly under <i>ORACLE_BASE</i>.</p> <p>All directory path examples in this guide follow OFA conventions.</p> <p>Refer to <i>Oracle9i Database Getting Starting for Windows</i> for additional information about OFA compliances and for information about installing Oracle products in non-OFA compliant directories.</p>	Go to the <i>ORACLE_BASE\ORACLE_HOME\rdms\admin</i> directory.

---

---

# Summary of Changes

This release notes document contains information on Oracle9i Application Server Release 2 (9.0.2.0.1) that did not make it into the documentation set. Although this document is accurate at the time of publication, you can access the latest information and additions to these release notes on the Oracle Technology Network at

<http://otn.oracle.com/products/ias>

Topics in this chapter include:

- [Purpose of this Document](#)
- [Component Release Notes](#)
- [Operating System Requirements](#)
- [Certification Information](#)
- [Licensing Information](#)
- [Deprecated Features](#)

## 1.1 Purpose of this Document

This document describes differences between Oracle9i Application Server Release 2 (9.0.2.0.1) for AIX-Based Systems, Compaq Tru64 UNIX, HP 9000 Series HP-UX, and Linux Intel and its documented functionality.

This document contains the following:

- operating system patches required for running Oracle9i Application Server
- installation and migration issues and workarounds
- general management and security issues and workarounds
- updates to books in the documentation library

This is the main release notes document for the product, and Oracle Corporation recommends you review its contents before reading the component release notes listed in the next section.

## 1.2 Component Release Notes

For latest information about specific Oracle9iAS components, refer to the component-specific release notes from the links below.

**Table 1–1 Component Release Notes**

Solution Area	Component Release Notes
J2EE and Internet Applications Install Type	<ul style="list-style-type: none"> <li>■ <i>Oracle HTTP Server Release Notes</i></li> <li>■ <i>Oracle9iAS Containers for J2EE Release Notes</i></li> <li>■ <i>Oracle9iAS Web Services Release Notes</i></li> <li>■ <i>Oracle9iAS Web Cache Release Notes</i></li> <li>■ <i>Oracle Enterprise Manager Web Site Release Notes</i></li> </ul>
Portal and Wireless Install Type	<ul style="list-style-type: none"> <li>■ <i>Oracle9iAS Portal Release Notes</i></li> <li>■ <i>Oracle Ultra Search Release Notes</i></li> <li>■ <i>Oracle9iAS Wireless Release Notes</i></li> </ul>
Business Intelligence and Forms Install Type	<ul style="list-style-type: none"> <li>■ <i>Oracle9iAS Discoverer Release Notes</i></li> <li>■ <i>Oracle9iAS Forms Developer and Forms Services Release Notes</i></li> <li>■ <i>Oracle9iAS Personalization Release Notes</i></li> <li>■ <i>Oracle9iAS Reports Services Release Notes</i></li> </ul>

**Table 1–1 (Cont.) Component Release Notes**

Solution Area	Component Release Notes
Infrastructure Install Type	<ul style="list-style-type: none"> <li>■ <i>Oracle Enterprise Manager Release Notes</i></li> <li>■ <i>Oracle Internet Directory Release Notes</i></li> <li>■ <i>Oracle9iAS Single Sign-On Release Notes</i></li> </ul>
Integration and Client Components	<ul style="list-style-type: none"> <li>■ <i>Oracle9iAS InterConnect Release Notes</i></li> <li>■ <i>Oracle Workflow Release Notes</i></li> <li>■ <i>Oracle9i Application Server Client Release Notes</i></li> </ul>

## 1.3 Operating System Requirements

The following tables contains the software requirements for Oracle9iAS.

- [Table 1–2](#) and [Table 1–3](#) list the software requirements for AIX-Based Systems.
- [Table 1–4](#) lists the software requirements for HP 9000 Series HP-UX.
- [Table 1–5](#) lists the software requirements for Linux Intel.
- [Table 1–6](#) lists the software requirements for Compaq Tru64.

For the latest information, refer to *OracleMetaLink*:

<http://metalink.oracle.com>

---



---

**Note:** Download the operating system patches for AIX-Based Systems, Compaq Tru64 UNIX, HP 9000 Series HP-UX, and Linux Intel from the vendor web sites.

---



---



---



---

**Note:** The current JDK 1.3.1 production version is required. For Linux, this JDK is included on the Oracle9iAS CD-ROM

---



---

**Table 1–2 Software Requirements for AIX 4.3.3 Systems**

Item	Requirement
Operating System	AIX 4.3.3 (64-bit only)
Software	JDK 1.3.1
Operating System patches for AIX 4.3.3	ML9 IY05995 IY07276 IY01050 IY17528 IY25282
	Clusterware Patches PSSP 3.2 IY04109 IY04149 IY04767 HACMP/ES 4.4 IY03478 IY04109 IY06749 IY20220 IY17439 IY15677 IY14572 IY13935
Window Manager	Use any supported IBM AIX window manager that supports Motif, such as <code>dtwm</code> , <code>twm</code> , and <code>olwm</code> .

**Table 1–3 Software Requirements for AIX 5L Systems**

<b>Item</b>	<b>Requirement</b>
Operating System	AIX 5L (5.1 or higher) 32-bit or 64-bit kernel mode
Software	IBM JAVA 131 SR-3(32 bit) or higher VAC 5.0 runtime or higher
Operating System patches for AIX 5L	ML02 or higher Filesets: <code>bos.adt.libm</code> , <code>bos.perf.libperfstat</code> Patches: IY30150, IY39508
Window Manager	Use any supported IBM AIX window manager that supports Motif, such as <code>dtwm</code> , <code>twm</code> , and <code>olwm</code> .
Required Executables	The following executables must be present: <code>make</code> , <code>ar</code> , <code>ld</code> , and <code>nm</code> .

**Table 1–4 Software Requirements for HP 9000 Series HP-UX**

Item	Requirement
Operating System	HP-UX 11.0 (64-bit)
Software	JDK 1.3.1
Operating System Patches	<p>HP-UX 11.00 PA-RISC Patches:</p> <p>You must install any prerequisite patches for JDK. These patches are available from the HP website.</p> <p>NOTE: Several of the patches listed below have dependency patches that must be installed as well. When you navigate to the download web page for an individual patch, click the <i>dependency</i> link and make sure you install the dependency patches if required.</p> <p>Dec 2000 Patch Bundle</p> <p>PHSS_23377            PHCO_23770            PHKL_23226            PHCO_23092            PHCO_23792            PHCO_23963            PHCO_24148            PHKL_18543            PHKL_23226            PHKL_23409            PHKL_24826            PHKL_24943            PHKL_24971            PHNE_21731            PHNE_23456            PHNE_23833            PHSS_23440            PHSS_17535            PHSS_23546            PHSS_23800            PHKL_25188            PHSS_23823</p> <p>Clusterware:            MC/ServiceGuard            11.09 OPS Edition            PHCO_23919</p>
Required Executables	<p>The following executables must be present in the /usr/ccs/bin directory: make, ar, ld, nm, and cc.</p>

**Table 1–5 Software Requirements for Linux Intel**

<b>Item</b>	<b>Requirement</b>
Operating System	SuSE SLES7 or Red Hat Advanced Server 2.1 Distribution
Software	JDK 1.3.1 XFree86 Development 3.3.3.1 or later Open Motif 2.1.30 For SuSE SLES7 the following is also required: <ul style="list-style-type: none"><li>■ kernel 2.4.7</li><li>■ glibc 2.2.2-55</li></ul> For Red Hat Advanced Server 2.1 the following is also required: <ul style="list-style-type: none"><li>■ kernel 2.4.9</li><li>■ glibc 2.2.4-25</li></ul>

**Table 1–6 Software Requirements for Compaq Tru64 UNIX**

Item	Requirement
Operating System	Compaq Tru64 UNIX 5.1 or 5.1a
Software	JDK 1.3.1
Operating System Patches	5.1 patchkit 2 or higher 5.1a patchkit 1 or higher Bugfix HPAQ217F Clusterware: TruClusters 5.1a (CFS aware)
Operating System Packages	The OSFLIBA, OSFPGMR, and OSFCMPLRS subsets. These subsets are part of the Compaq Tru64 UNIX operating system distribution.
Window Manager	X Windows must be installed on the system from where the Installer is run. Use any Compaq-supported X Windows server with support for Motif, such as <code>dtwm</code> , <code>twm</code> , and <code>mwm</code> .  Character mode installations are not supported for Oracle9iAS Release 2 (9.0.2.0.1)  The X environments, Basic X-environments (OSF11), and X Servers (OSFSER) are required to run graphical products.
Required Executables	The following executables must be present in the <code>/usr/ccs/bin</code> directory: <code>make</code> , <code>ar</code> , <code>ld</code> , and <code>nm</code> .

## 1.4 Certification Information

Latest certification information for Oracle9iAS, Release 2 (9.0.2.0.1), is available at:

<http://metalink.oracle.com>

## 1.5 Licensing Information

Licensing information for Oracle9iAS, Release 2 (9.0.2.0.1), is available at:

[http://esource.oraclecorp.com/webdbprd-dad/webdb/esrc/esr\\_main.home](http://esource.oraclecorp.com/webdbprd-dad/webdb/esrc/esr_main.home)

## 1.6 Deprecated Features

The following features have been officially deprecated in Oracle9i Application Server Release 2 (9.0.2.0.1):

- Oracle9iAS Database Cache
- Enterprise Java Engine
- IIS Plugin
- `mod_ssl` based on `openssl`. This has been replaced by `mod_oss1`.
- Jserv environment. This has been replaced by Oracle9iAS Containers for J2EE (OC4J).

A complete list of deprecated features and migration details is also available on OTN and Oracle*Metalink* under the title “Oracle9iAS Release 2 (9.0.2.0.1) Deprecated Features”:

<http://otn.oracle.com/products/ias>  
<http://metalink.oracle.com>



---

---

# Installation and Migration Issues

This chapter describes installation and migration issues and their workarounds. Topics include:

- [Installation Issues](#)
- [Postinstallation Issues](#)
- [Deinstallation Issues](#)
- [Reinstallation Issues](#)
- [Migration Issues](#)

## 2.1 Installation Issues

This section covers these installation issues:

- [Oracle9iAS Installation and Multiple Operating System Users](#)
- [Multiple Infrastructure-based Deployment](#)
- [Start Dependencies When Installing Against Oracle9iAS Infrastructure](#)
- [Prompt for Database Files Location During Install](#)
- [Modification in init.ora for Oracle9iAS Metadata Repository](#)
- [Multiple Install Types into the Same Infrastructure Instance Overwrites Portal](#)
- [Oracle9iAS Wireless Installation Requires Oracle9iAS Portal](#)
- [Oracle HTTP Server Does Not Start if SSO/mod\\_osso Registration Failed](#)
- [Enabling Oracle9iAS Web Cache and mod\\_osso](#)
- [Report Configuration Assistant Fails During Installation](#)
- [Service Errors and NoClassDefFound Exceptions](#)
- [Ulimit and Swap File Settings](#)
- [Preinstallation Packages for Linux Intel](#)
- [Installing on Red Hat Linux](#)
- [Using Oracle Internet File System on Red Hat Linux](#)
- [Default Port Number for Oracle Internet Directory on Linux](#)
- [Oracle Universal Installer on Linux](#)
- [Installing on HP 9000 Series HP-UX](#)

### 2.1.1 Oracle9iAS Installation and Multiple Operating System Users

If you are installing more than one Oracle9i Application Server instance on a single computer, then you must perform all of the installations as the same operating system user.

### 2.1.2 Multiple Infrastructure-based Deployment

Oracle9iAS supports multiple infrastructure installations. The first (or primary) infrastructure installation must contain SSO, Oracle Internet Directory, a Metadata

Repository, and, optionally, Oracle Management Server. Any subsequent (or secondary) infrastructure installations:

- must point to the SSO in the primary installation.
- must point to the Oracle Internet Directory in the primary installation.
- must contain their own Metadata Repository.
- may optionally contain Oracle Management Server.

The purpose of a secondary installation is to provide an additional Metadata Repository in case the load on the primary Metadata Repository is excessive.

You can install a secondary infrastructure by choosing a custom installation and selecting Metadata Repository and optionally Oracle Management Server. You will be prompted for SSO and Oracle Internet Directory information, at which time you should supply the information for the primary infrastructure.

The middle tier application server installations that are installed after a secondary infrastructure can use that secondary infrastructure. This means that you cannot change existing middle tier application server installations to use the secondary infrastructure.

If you want a middle tier installation to use the secondary infrastructure, specify the SSO and Oracle Internet Directory from the primary infrastructure at install time. When you are prompted to specify which infrastructure's Metadata Repository you would like to use, choose the Metadata Repository from the secondary installation.

### 2.1.3 Start Dependencies When Installing Against Oracle9iAS Infrastructure

When installing Oracle9iAS against an existing Oracle9iAS Infrastructure, ensure that the following infrastructure components are running:

- Oracle9iAS Metadata Repository
- Oracle Internet Directory
- Oracle9iAS Single Sign-On
- Oracle HTTP Server
- Oracle9iAS Containers for J2EE

If you are installing an Oracle9iAS Infrastructure component, then ensure that its dependencies are running before starting the installation process. For example, before installing Oracle9iAS Single Sign-On, start Oracle9iAS Metadata Repository, Oracle Internet Directory, and Oracle HTTP Server.

If Oracle HTTP Server is not running on the Infrastructure, then you might get the following error message when you try to use the Infrastructure during installation:

An error occurred while attempting to verify your host and port. Please verify your host and port values and that you can connect to this host, or enter new values. User Output Stringlist is: <infra\_host>:<port>.  
Return value from SSORunning function is INVALID.

## 2.1.4 Prompt for Database Files Location During Install

If your computer does not have enough space in the Oracle home directory to create the database files required by the Oracle9iAS Metadata Repository, then you will be prompted to select another location to install them.

## 2.1.5 Modification in init.ora for Oracle9iAS Metadata Repository

If you are using Oracle9iAS Metadata Repository, edit the `init.ora` file to remove the following entry:

```
_optim_peek_user_binds=FALSE
```

## 2.1.6 Multiple Install Types into the Same Infrastructure Instance Overwrites Portal

Multiple Oracle9iAS Portal & Wireless installations pointing to a single Portal instance in the metadata repository would override the existing entries. Entries related to Web Cache would get overwritten in the Portal instance each time you run the mid-tier installation.

As a workaround, disable Web Cache for Portal in all the Oracle9iAS instances with the following procedure:

1. Log on to Portal runtime.
2. Click **Builder** to get the Portal design time home page.
3. Click **Administer**.
4. Click **Global Settings** within the services portlet.
5. Click **cache**.
6. Deselect the **Enable Web Cache** for caching portal content checkbox.
7. Click **Apply** and **OK**.

Note that each time you install the mid-tier, you drop and recreate the Portal users from Oracle Internet Directory. The password for the Portal lightweight user is the mid-tier instance name from the most recent installation.

### 2.1.7 Oracle9iAS Wireless Installation Requires Oracle9iAS Portal

During the installation process, when the component configuration screen appears, if you select to install Wireless, ensure that Portal is also selected. The configuration tool for Wireless requires Portal to work.

### 2.1.8 Oracle HTTP Server Does Not Start if SSO/mod\_osso Registration Failed

If the Oracle9iAS Infrastructure Configuration Assistant fails to register Oracle9iAS Single Sign-On Server /mod\_osso during installation, Oracle HTTP Server will not start. There are two options to correct this problem.

- If you do not have installed applications that use Oracle9iAS Single Sign-On Server, you can comment out the following line in the file `ORACLE_HOME/Apache/Apache/conf/httpd.conf`. Add a # character in front of the line to comment out the line.

```
# include ORACLE_HOME/Apache/Apache/conf/httpd.conf/mod_osso.conf
```

Note that you should use Oracle Enterprise Manager to edit the file.

- If you have installed applications that use Oracle9iAS Single Sign-On Server, manually run the `SSOregistrar` tool to generate a valid `osso.conf` file.

If `SSOregistrar` returns a non-zero status or throws an exception indicating some errors occurred, then you should not use `mod_osso`. To disable `mod_osso`, comment the line that includes `mod_osso` by adding a # character in front of the line, as shown in the first option.

### 2.1.9 Enabling Oracle9iAS Web Cache and mod\_osso

When the Oracle9iAS installer initially registers `mod_osso` with the Oracle9iAS Single Sign-On, it passes the registration URLs containing the port number of the Oracle HTTP Server, instead of the port number of Oracle9iAS Web Cache. Since the installer passes the incorrect port number, it bypasses Oracle9iAS Web Cache.

For `mod_osso` to work correctly, manually re-register `mod_osso` using URLs that have the Oracle9iAS Web Cache port.

**See Also:** “Component Configuration Dependencies” chapter in the *Oracle9i Application Server Administrator’s Guide* for detailed information on how changes in hostname and port affect Oracle9i Application Server, and, specifically, how `mod_ossso` and Oracle9iAS Single Sign-On may be affected,

Another alternative workaround is to shutdown Oracle9iAS Web Cache instead of re-registering the SSO partner. Since the entry point is now Oracle HTTP Server instead of Oracle9iAS Web Cache, the error would not show up.

---

---

**Note:** You can use the above mentioned workaround before re-registering using the Oracle9iAS Web Cache port. Also, when you use this workaround, you have to enter with the Oracle HTTP Server port. For example, if Oracle HTTP Server is running on 7779 and Oracle9iAS Web Cache is running on 7778, then you need to enter the following URL: `http://<host.domain>:7779`.

---

---

On Microsoft Internet Explorer, refresh the page once the changes are made. Otherwise, you might encounter the following error:

```
Forbidden
You don't have permission to access /osso_login_success on this server.
```

## 2.1.10 Report Configuration Assistant Fails During Installation

During installation, if the Reports Configuration Assistant fails and give the following message:

```
Process destroyed exception (in the installer configuration palette)
```

then perform the following steps:

1. Log on to Oracle Internet Directory and obtain the Portal user database password.
2. Log on to the metadata repository as Portal user and run the following script:

```
ORACLE_HOME/portal/admin/plsql/wwd/rwaddpag.sql
```

This creates the Reports portlet.

Alternatively, you can create a `tnsnames` entry and execute the script as Portal user with the Portal user password obtained from the Oracle Internet Directory, as described in Step 1.

## 2.1.11 Service Errors and NoClassDefFound Exceptions

After accessing a large number of different module services or HTTP adapter-based services (with JSP-based content sources hosted on the same Java VM), some of the services fail with a 'service error'. Accessing the target JSPs results in a 'NoClassDefFound' exception. Restarting the server corrects the problem.

When an application is loaded for the first time, the OC4J classloaders read the class bytes in the library jars into memory; it does so even without the classes being instantiated (because the application instantiates classes from an in-memory array).

Class files resulting from compiling JSP files are loaded dynamically. With time, the heap gets filled up and newer classes from compiled JSPs cannot be read into the memory array(s), nor instantiated on the heap. Hence the top-level classloaders fail with a 'NoClassDefFound' exception. In subsequent lookups, the 'OutOfMemoryError' is not thrown since the JDK classloader `loadClass( )` implementation semantics prescribe NOT reloading classes that could not deterministically be loaded earlier.

To determine if this is the case, check the number of `OutOfMemoryErrors` in `sys_panama.log`. That number should be the same as the number of times the server has been restarted.

If it is the case, increase the heap-size for the VM by modifying the Java option subelement of the OC4J element corresponding to the `instanceName` `OC4J_Wireless`.

1. From your browser, point to Oracle Enterprise Manager at `http://<host>:1810`.
2. Log in to Enterprise Manager as `ias_admin/<password supplied at install time>`.
3. Select your middle tier instance.
4. Select `OC4J_Wireless`. The `OC4J_Wireless` screen appears.
5. Select "Server Properties" (located under Instance Properties at the bottom of the `OC4J_Wireless` page) to invoke the Server Properties page. A page with command-line options appears which includes an editable field for Java Options which you use to set the heap size.

6. Use the Java Options field to set the heap size.
7. Remove the option `-noclassgc`.
8. Click **Apply**.

**See Also:** “Setting the JVM Heap Size for OC4J Processes” section in the *Oracle9i Application Server Performance Guide*.

## 2.1.12 Ulimit and Swap File Settings

Oracle Corporation recommends setting the following ulimit parameters before installation:

Parameter	Recommended Value
time	unlimited
file	unlimited
data	1048576
stack	32768
memory	2045680
coredump	unlimited
nofiles	4096
vmemory	4194304

On Linux, Oracle Corporation recommends setting the swap file size to 3 times the size of RAM before installation.

## 2.1.13 Preinstallation Packages for Linux Intel

Install the `ksh` package if you have not already installed it on your machine. Oracle Corporation recommends installing one of the following `ksh` packages:

Operating System	Recommended Package
SuSE SLES7	pdksh-5.2.14-206
Red Hat AS	pdksh-5.2.14-13

## 2.1.14 Installing on Red Hat Linux

If you are installing Oracle9iAS on Red Hat Linux, make sure to

- Install the binutils-2.11.90.0.8-13 patch. This patch can be downloaded from <http://metalink.oracle.com>, search for Patch number 2389349.
- Include the `/usr/bin` directory as the first entry of the PATH environment variable.

If either of these requirements above are not satisfied, relinking will fail.

Also, create a link from the `/sbin/fuser` file to `/bin/fuser`. This is required to successfully detect whether Oracle Enterprise Manager is running during second and subsequent installations on the same machine.

## 2.1.15 Using Oracle Internet File System on Red Hat Linux

For Oracle 9iFS release 9.0.2 to work on Red Hat AS, you need to apply the patch for bug 2037255 to the backend database. This patch is available at:

<http://metalink.oracle.com>

## 2.1.16 Default Port Number for Oracle Internet Directory on Linux

On Linux, port number 389 is reserved in the `/etc/services` file. If you want Oracle9iAS to install using the default port number for Oracle Internet Directory, delete the entries in the `/etc/services` file.

---

---

**Note:** You must *remove* all lines containing the port number 389 from the `/etc/services` file if you want to use that port number. Attempting to *comment out* lines containing 389 does not free the port.

---

---

## 2.1.17 Oracle Universal Installer on Linux

The Oracle Universal Installer fails on Linux if you try to perform multiple installations or deinstallations from the same Oracle Universal Installer session. If you encounter this problem, restart Oracle Universal Installer.

## 2.1.18 Installing on HP 9000 Series HP-UX

If you are installing on HP 9000 Series HP-UX, you must manually create some symbolic links before performing the installation. This is due to a known HP-UX problem, Doc. ID. KBRC00003627. To create the required links:

1. Log in as `root`.
2. Change to the `/usr/lib` directory:

```
# cd /usr/lib
```

3. Create the required links:

```
# ln -s /usr/lib/libX11.3 libX11.sl
# ln -s /usr/lib/libXIE.2 libXIE.sl
# ln -s /usr/lib/libXext.3 libXext.sl
# ln -s /usr/lib/libXhp11.3 libXhp11.sl
# ln -s /usr/lib/libXi.3 libXi.sl
# ln -s /usr/lib/libXm.4 libXm.sl
# ln -s /usr/lib/libXp.2 libXp.sl
# ln -s /usr/lib/libXt.3 libXt.sl
# ln -s /usr/lib/libXtst.2 libXtst.sl
```

---

## 2.2 Postinstallation Issues

This section covers the following postinstallation issues:

- [DISPLAY Environment Variable is Set to localhost:0](#)

### 2.2.1 DISPLAY Environment Variable is Set to localhost:0

The installation sets the `DISPLAY` variable in `opmn.xml` to `localhost:0` by default. If your machine is not equipped with a graphics card, you need to set the variable in `opmn.xml` to point to a virtual frame buffer such as X Virtual Frame Buffer (XVFB) or Virtual Network Computing (VNC). Refer to Chapter 3 of the Oracle9i Application Server Installation Guide for instructions.

---

---

**Note:** This information supersedes similar information in the component release notes.

---

---

## 2.3 Deinstallation Issues

There are no known issues associated with deinstallation.

## 2.4 Reinstallation Issues

There are no known issues associated with reinstallation.

## 2.5 Migration Issues

This section covers the following migration issues:

- [Kernel Mode Restriction on IBM AIX 5L-based Systems](#)

### 2.5.1 Kernel Mode Restriction on IBM AIX 5L-based Systems

If you are migrating from Oracle9i Application Server Release 1 (1.0.2.2.x) to Release 2 (9.0.2.0.1) on IBM AIX 5L, install Release 2 (9.0.2.0.1) in 32-bit kernel mode. You may change the kernel mode to 64-bit after the migration is complete.

Release 1 (1.0.2.2.x) is supported only in 32-bit kernel mode, whereas Release 2 (9.0.2.0.1) is supported both in the 32-bit and 64-bit kernel mode of IBM AIX 5L-based systems.



---

---

# Management and Security Issues

This chapter summarizes management and security issues associated with Oracle9i Application Server. Topics include:

- [Management Issues](#)
- [Security Issues](#)

## 3.1 Management Issues

This section contains the following topics:

- [Run dcmctl to Update Configuration for Manual Configuration Changes](#)
- [Using emctl to Change the ias\\_admin Password](#)
- [OPMN Cannot Start OC4J Instance with Multibyte](#)
- [Clock Synchronization](#)
- [Use Port Option to Configure Loading Application](#)
- [Oracle Enterprise Manager Does Not Display OC4J Metrics in the Home Page](#)
- [Changing the ias\\_admin Password in Translated Versions of OEM](#)
- [“opmnctl restart” Displays Harmless “Unavailable Hostname” Message](#)
- [Attributes Containing Paths Break Cluster Model](#)
- [Oracle Enterprise Manager Does Not Support Multiple Locales](#)
- [Operating System Patches for Host Metrics](#)
- [Deploying BC4J JSP, UIX JSP and UIX XML Applications Using OEM](#)
- [Restart OC4J When User Manager is Changed From JAZN LDAP To XML](#)
- [Incorrect Indication of Oracle Internet Directory Status](#)
- [Configuring JAAS with Oracle Enterprise Manager Web Site](#)
- [Oracle9iAS Wireless Status Incorrectly Displayed as Down on Oracle Enterprise Manager Page](#)
- [OEM Intelligent Agent May Work Incorrectly in Non-English Environment](#)

### 3.1.1 Run dcmctl to Update Configuration for Manual Configuration Changes

If you make manual changes to the configuration files for these components:

- Oracle HTTP Server
- OC4J

your changes will not be reflected in the DCM repository.

To propagate your manual edits back to the DCM repository, run the following command after making any edits, either manually or through the Oracle Enterprise Manager.

```
dcmctl updateconfig ohs
dcmctl updateconfig oc4j
```

This is also the case if you created, modified, or deleted DADs or modified the `mod_plsql` cache setting using the Oracle Enterprise Manager.

See the Oracle9i Application Server Administrator's Guide for details.

### 3.1.2 Using emctl to Change the ias\_admin Password

If you change the `ias_admin` password using `emctl`, then you must restart the Oracle Enterprise Manager Web Site with the following commands:

```
> emctl stop
> emctl start
```

### 3.1.3 OPMN Cannot Start OC4J Instance with Multibyte

The configuration file for OPMN, `opmn.xml`, is in UTF-8 encoding. The code that parses `opmn.xml` is written in C, and the data in `opmn.xml` is handled as UTF-8 bytes. This causes problems when the data is not converted to the right encoding. For example, if the default encoding of your operation system is EUC-JP, the directory is created using UTF-8 data. The multibyte instance name then becomes inaccessible.

As a workaround, avoid using multibyte characters for contents such as instance names and environment variables in `opmn.xml`.

### 3.1.4 Clock Synchronization

Several Oracle9iAS components require the clocks on the machines on which they run to be synchronized. You can synchronize the clocks by running the Network Time Protocol (NTP) daemon on these machines. You do this by starting `xntpd` or a similar daemon process.

### 3.1.5 Use Port Option to Configure Loading Application

There are several ways to configure how to load an application.

- One is to load it dynamically when the first request comes in. This approach uses named pipes for communication.
- Another approach is to load the application at startup. With this approach, you can configure it to use the port option or the named pipe option (where you do not have to specify the port). This release supports the port option only.

### 3.1.6 Oracle Enterprise Manager Does Not Display OC4J Metrics in the Home Page

When the Oracle Enterprise Manager Home Page is opened, the OC4J metrics are not displayed. Refresh the page in order to see the metrics.

### 3.1.7 Changing the `ias_admin` Password in Translated Versions of OEM

You cannot change the `ias_admin` password using a translated version of the Enterprise Manager Web site. This is because the **Preferences** link on the Instance Home Page is disabled.

You can change the `ias_admin` password using the following command:

```
ORACLE_HOME/bin/emctl set password new_password
```

### 3.1.8 “`opmnctl restart`” Displays Harmless “Unavailable Hostname” Message

If you run `opmnctl restart` or restart OC4J by other means, and EMD is running, you might see the following error messages in the

*ORACLE\_HOME*/Apache/Apache/error\_log file:

```
[Wed Apr 3 12:09:50 2002] [error] MOD_OC4J_0082: Failed to call  
gethostbyname() for host name: UNAVAILABLE.  
[Wed Apr 3 12:09:50 2002] [error] MOD_OC4J_0019: Failed to resolve network  
address of worker: home_15's host: UNAVAILABLE and port: 3003.  
[Wed Apr 3 12:09:50 2002] [error] [client 130.35.92.190] MOD_OC4J_0138:
```

```
Failed to validate network worker: home_15 with host: UNAVAILABLE and port:
3003.
[Wed Apr 3 12:09:50 2002] [error] [client 130.35.92.190] MOD_OC4J_0141:
Failed to validate host: UNAVAILABLE and port 3003 for network worker:
home_15.
```

You can ignore these error messages; they will not cause any problems.

### 3.1.9 Attributes Containing Paths Break Cluster Model

In attributes that specify paths, make sure that the paths are relative to Oracle home. Otherwise, your cluster members may not run properly.

### 3.1.10 Oracle Enterprise Manager Does Not Support Multiple Locales

Oracle Enterprise Manager does not support multiple locales. The following components use the browser's locale when displaying pages in Oracle Enterprise Manager:

- Oracle9iAS Discoverer
- Oracle9iAS Forms Services
- Oracle9iAS Portal
- Oracle9iAS Single Sign-On
- PL/SQL properties
- Oracle9iAS Unified Messaging

All other management pages use the Java default locale when displaying pages.

### 3.1.11 Operating System Patches for Host Metrics

You must install the systat package for the host metrics to work correctly on Linux Intel.

### 3.1.12 Deploying BC4J JSP, UIX JSP and UIX XML Applications Using OEM

BC4J JSP, UIX JSP, and UIX XML applications from JDeveloper deployed to Oracle9iAS through the Enterprise Manager deployment functionality runtime will result in a runtime rendering data access error. This happens only if data source information is added subsequently through Enterprise Manager and not pre-packaged already in the EAR file from JDeveloper.

If the EAR file generated from JDeveloper doesn't package the data source information or the "deploy to EAR files" option is chosen instead of "deploy to connection," and if that information is subsequently added through the Enterprise Manager through the edit data sources functionality, then the UIX/JSP and UIX/XML applications cannot run successfully due to runtime rendering error.

To avoid the error, do not add the data sources information after deployment through EM. Instead, package the EAR file with the data sources information from JDeveloper prior to deployment through EM. While creating the UIX/JSP or the UIX/XML application from JDeveloper, instead of just deploying to an EAR file, deploy to any existing connection, including dummy connections. That process will create an EAR file with the data sources information packaged.

If deploying to a dummy connection, although the process will result in deployment errors in JDeveloper, it will create an EAR file that includes the data source information that can be successfully deployed to Oracle9iAS.

### 3.1.13 Restart OC4J When User Manager is Changed From JAZN LDAP To XML

If the user manager for OC4J is changed from JAZN LDAP to JAZN XML, the change is not picked up dynamically. OC4J continues to use JAZN LDAP as the user manager.

In order to effect the change to JAZN XML, restart the OC4J instance.

### 3.1.14 Incorrect Indication of Oracle Internet Directory Status

Oracle Enterprise Manager web pages may show an incorrect status of Oracle Internet Directory (OID). The status may show that OID is down when it is actually up and running. This problem is caused by the Perl executable not being in the `/usr/local/bin` directory. It can be solved as follows:

1. Find the location of the Perl executable in your system by using the which command. For example:

```
> which perl
```

A full path name is displayed. Assume `/perl_path/perl` for this discussion

2. Set a soft link to the displayed path at `/usr/local/bin/perl` as follows:

```
> ln -s /perl_path/perl /usr/local/bin/perl
```

3. Restart the Oracle Enterprise Manager administration GUI.

### 3.1.15 Configuring JAAS with Oracle Enterprise Manager Web Site

---

---

**Note:** This information supersedes Section 8.1, "Configuring JAAS" in the *Oracle Enterprise Manager Web Site Release Notes*

---

---

To configure JAAS, perform the following tasks:

1. Open `ORACLE_HOME/sysman/j2ee/config/jazn.xml` in a text editor.
2. Uncomment the following properties in the `jazn.xml` file:

```
<property name="ldap.service" value="ldap://localhost:389"/>  
<property name="ldap.user" value="cn=oracladmin"/>  
<property name="policymgr.provider" value="LDAP"/>
```

If "localhost" does not work in your environment, you may need to replace it with the actual name of your Oracle Internet Directory (OID) server. Similarly, you may need to replace the port number if your OID server does not use the default port of 389.

3. Modify the `ldap.password` property by entering the password you used for OID server login. Be sure to include an exclamation point (!) before the password encrypt it. For example:

```
<property name="ldap.password" value="!manager1234"/>
```

4. Save the modified `jazn.xml` file and restart the Enterprise Manager Web site.

---

---

**Note:** By default, the OID server will recognize your `ias_admin` password. If you later change this password for OID administration, you must re-enter it using the `ldap.password` property in the `jazn.xml` file and then restart the Enterprise Manager Web site in order to manage JAAS using OID.

---

---

### 3.1.16 Oracle9iAS Wireless Status Incorrectly Displayed as Down on Oracle Enterprise Manager Page

A condition has been discovered that will cause the Wireless status to be displayed (in Oracle Enterprise Manager) as *Down*, even though it is in fact *Up*. This occurs when more than one Oracle home directory exists on a single machine.

If you have more than one Oracle Home directory on a single machine, make the following changes to the Oracle9iAS Middle Tier (including Oracle9iAS Wireless) installation:

- (UNIX only) Add the following line to the start of `ORACLE_HOME/Wireless/sample/runpanamaserver.sh`, just after the first line (“`#!/bin/sh`”):

```
ORACLE_HOME=${1}
```

- (Windows only) Add the following line to the beginning of `ORACLE_HOME\Wireless\samplerunpanamaserver.bat`:

```
set ORACLE_HOME=%1
```

### 3.1.17 OEM Intelligent Agent May Work Incorrectly in Non-English Environment

If the language environment is non-English, and the `/usr/local/lib/tcl8.2/encoding/*.enc` Tcl interpreter encoding definition files are installed on the node, OEM Intelligent Agent may not work properly with non-English characters. As a result, OEM jobs may fail to execute or return corrupted strings. If the above encoding definition files are not present, this problem should not occur.

The solution to this problem is to create empty Tcl interpreter encoding definition files at the following location:

```
$ORACLE_HOME/lib/tcl8.2/encoding/*.enc
```

To do so, perform the following steps:

1. Execute the following commands:

```
% cd $ORACLE_HOME/lib
% mkdir tcl8.2
% cp -pr /usr/local/lib/tcl8.2/encoding tcl8.2
% cd tcl8.2/encoding
```

2. Additionally, execute the following commands depending on which shell you are running:

- If you are using C-shell or T C-shell:

```
% foreach file (*.enc)
foreach? cp /dev/null $file
foreach? end
```

- If you are using Korn-shell or B-shell:

```
% for file in *.enc; do
> cp /dev/null $file
> done
```

3. Once the empty encoding definition files have been created, restart Oracle Intelligent Agent as follows:

```
% agentctl stop
% agentctl start
```

Note that the `NLS_LANG` and `LANG` environment variables must be defined with appropriate values before Oracle Intelligent Agent is restarted.

### **3.1.18 Concurrent Administrative Operations on a Cluster Not Supported**

Concurrent administrative operations on a cluster are not supported in Oracle9iAS Release 2 (9.0.2). Configuration information for clusters is stored in a central repository. All members of the cluster have access to this repository. This keeps configuration consistent across the cluster. Since the objects in the repository are shared across the cluster, concurrent write access to these objects is not allowed.

## 3.2 Security Issues

The following are known issues associated with Oracle9iAS security.

- [Avoid Adding User Certificates to Trustpoints or Trusted Certificate Lists](#)
- [Restrict Root Privileges to Oracle9iAS Web Cache Users](#)
- [JAZN Demo Data Needs to be Loaded into LDAP if JAZN LDAP is Global User Manager](#)

### 3.2.1 Avoid Adding User Certificates to Trustpoints or Trusted Certificate Lists

If a wallet contains a user certificate as a trustpoint for a server, then a core dump occurs when the user connects to the server.

Oracle Corporation recommends not adding user certificates to trustpoints or trusted certificate lists in the Oracle wallet. Instead, install the certificate authority (CA) signers' certificate as a trustpoint.

### 3.2.2 Restrict Root Privileges to Oracle9iAS Web Cache Users

Users that install Oracle9iAS Web Cache may gain root privileges by running the `root.sh` because the `webcachectl` executable triggers the `setuid` to obtain root access.

To restrict root privileges, remove `setuid` from the `webcachectl` executable. Note that `setuid` is required in the following cases:

- Privileged port numbers less than 1,024 are being used for Oracle9iAS Web Cache listening ports.
- More than 1,024 file descriptors are being used for connections to Oracle9iAS Web Cache.
- The current `webcachectl` user does not match the configured user in the Process Identity page (Cache-Specific Configuration > Process Identity) of Oracle9iAS Web Cache Manager.

### 3.2.3 JAZN Demo Data Needs to be Loaded into LDAP if JAZN LDAP is Global User Manager

If the user manager for the default application for an OC4J instance is changed to JAZN LDAP, the JAZN demo data needs to be loaded into the specified LDAP database. (This is documented in the README file in `$ORACLE_HOME/j2ee/home/jazn/install`.) Additionally, the default @ realm needs to be specified as "jazn.com".

If the above is not done, deployment of the demos through EM or `dcmctl` will fail with an error in looking up `java:comp/ServerAdministrator`.

---

---

## Component Issues

This chapter summarizes issues associated with Oracle9i Application Server. Topics include:

- [Oracle HTTP Server Issues](#)
- [Oracle9i XML Developer Kit Issues](#)
- [Oracle9iAS Portal Issues](#)
- [Oracle9iAS Wireless Issues](#)
- [Oracle9iAS Web Cache Issues](#)
- [Oracle9iAS Reports Services Issues](#)
- [Oracle9iAS Clickstream Intelligence Issues](#)
- [Oracle9iAS Single Sign-On Issues](#)
- [Oracle9iAS Unified Messaging](#)
- [Oracle9iAS Proxy Plug-in](#)

## 4.1 Oracle HTTP Server Issues

The following are known issues associated with Oracle HTTP Server:

- [Running More than 1024 Oracle HTTP Server Processes](#)
- [Ignore FASTCGI Error Messages After Installation](#)

### 4.1.1 Running More than 1024 Oracle HTTP Server Processes

If running more than 1024 Oracle HTTP Server processes in the same box that are accessing OC4J instances, set the `Oc4jCacheSize` directive in `mod_oc4j.conf` to 0. This disables the use of persistent connections between `mod_oc4j` and OC4J instances and improves performance.

### 4.1.2 Ignore FASTCGI Error Messages After Installation

After installation of Oracle9iAS, the following error messages may appear in the `error_log` file in `$ORACLE_HOME/Apache/Apache/logs`:

```
[Fri Apr 5 15:17:50 2002] [error] (2)No such file or directory: FastCGI: access
for server (uid -1, gid 10) failed: read not allowed by group
[Fri Apr 5 15:17:50 2002] [error] (2)No such file or directory: FastCGI: can't
create dynamic directory "/tmp/fcgi_10258/dynamic": access for server (uid -1,
gid 10) failed: read not allowed by group
```

These error messages are harmless and will not affect the operation of FastCGI. They are caused by a re-ordering of directives in `httpd.conf` during installation. To eliminate these messages, the directives `User` and `Group` should be moved from their location at the end of the file to be located before the FastCGI server directives in `httpd.conf`.

## 4.2 Oracle9i XML Developer Kit Issues

The following are known issues with Oracle9i XML Developer Kit:

- [Certification and System Requirements](#)
- [General Issues and Workarounds](#)

### 4.2.1 Certification and System Requirements

The following is additional support provided by Oracle9i XML Developer Kits (XDKs):

- Oracle Schema Processor now supports the official W3C Schema Recommendation.
- XSQL Servlet now provides support for Apache FOP 0.18.

### 4.2.2 General Issues and Workarounds

This following lists additional support and options provided by Oracle9i XML Developer Kits (XDKs):

- SourceViewer Bean now supports internal DTDs.
- XSQL Servlet:
  - Now supports the setting of multiple parameter values with a single SQL statement.
  - Provides a new performance improvement option for `<xsql:include-owa>`.
  - Has a new Airport SOAP Service demo.
  - Now supports the simplified inclusion of XML from CLOB and VARCHAR2 columns.

- XSQL Processor

XSLT Processor for Java is now threadsafe.

## 4.3 Oracle9iAS Portal Issues

The following are known issues with Oracle9iAS Portal:

- [Problems Logging In When Two Oracle HTTP Servers are on the Same Host and are Using Internet Explorer with SSL Configuration](#)
- [Creating Non-English PL/SQL Functions and Procedures](#)
- [Link to Portal Monitoring Services Not Working](#)
- [NLS Cannot Be Authenticated By Oracle9iAS Single Sign-On if Username Contains Non-ASCII Characters](#)

### 4.3.1 Problems Logging In When Two Oracle HTTP Servers are on the Same Host and are Using Internet Explorer with SSL Configuration

When two Oracle9iAS Oracle HTTP Servers are running on a single machine, such as when an infrastructure install and a Portal and Wireless middle tier install are both installed on a single machine, login to the Portal is not possible when using a Microsoft Internet Explorer (MSIE) Browser. This has been verified with versions 5.5 and 6.0 of MSIE. The problem occurs when a browser redirect is issued from one port used by the Oracle9iAS Single Sign-On server to the port used by Oracle9iAS Web Cache, which is fronting Oracle9iAS Portal. When MSIE receives the redirect, it erroneously sets the Host: header with the first port rather than the destination port. This behavior is not exhibited by Netscape Navigator (versions 4.6, 4.7). When this error occurs with MSIE, one of the following messages may be shown after an attempt to log in:

```
Error: Unexpected error encountered in wwsec_app_priv.process_signon  
(ORA-06502: PL/SQL: numeric or value error: character string buffer too small)  
(WWC-41417)
```

or

```
Error: The decryption of the authentication information was unsuccessful. This  
may be caused by corruption of the data, an incorrect encryption key in this  
application's configuration, or an illegal access attempt. Please notify your  
administrator. (WWC-41454)
```

Although MSIE sets the Host: header incorrectly in either SSL or non-SSL mode, the problem only shows up in SSL mode because Oracle9iAS Web Cache is setup to map ports to a catch-all default HTTP port in non-SSL mode. The workaround is to use two separate machines, with the two install types.

### 4.3.2 Creating Non-English PL/SQL Functions and Procedures

You cannot create PL/SQL functions and procedures in languages other than English when using Oracle9iAS Portal from a browser. You must create them using SQL\*Plus.

### 4.3.3 Link to Portal Monitoring Services Not Working

The link to Portal Monitoring Services does not work, i.e. the link displayed on the Administer tab.

A workaround is to cut and paste the block below into a SQLPLUS session that is connected as **sys** or **portal** on the same database as the PORTAL schema. If the portal schema name is not PORTAL the script will need updating accordingly, see text highlighted in **bold** below:

```

/*
*
* This patch script inspects and updates the Portal Service Monitoring
* link (to the Oracle Enterprise Manager Portal Target) on the
* Portal Administer Tab. It strips the link of redundant extra host
* entries, if necessary i.e. the URL on 9.0.2 incorrectly has the
* following parameters:
*
$target=<iASName>.<host>%5F<host>%5FPortal%3Aportal%3A7778$ctxName1=<iASName>.<host>%5F<ho
st>

* it should be of the form:
* $target=<iASName>.<host>%5FPortal%3Aportal%3A7778$ctxName1=<iASName>.<host>

*
* There is logic in the script to prevent it running twice.
* NOTE: if running against a PORTAL schema named something other than
* PORTAL please update the two PORTAL schema references accordingly
*/
DECLARE
CURSOR c1 is
        SELECT url FROM PORTAL.wwptl_other_services_link$
        where NAME='MONITORING';
workerURL VARCHAR2(2000);
newURL VARCHAR2(2000);
host VARCHAR2(1000);
testIndex NUMBER;
indexOfStartClip NUMBER;
indexOfEndClip NUMBER;
urlLength NUMBER;
BEGIN

```

```
OPEN c1;
FETCH c1 INTO workerURL;
  indexOfEndClip:= INSTR (workerURL,'%5Fportal%3',1,1) ;
  urlLength := LENGTH(workerURL);
  newURL := SUBSTR (workerURL, 0, indexOfEndClip-1);
  indexOfStartClip:= INSTR (newURL,'%5F',-1,1) ;
  /*****
  * Test to see if the patch has already been run
  * and if so don't do anything
  * if the ias$ string is present the extra host has
  * already been clipped
  *****/
  host := SUBSTR (newURL, indexOfStartClip+3, indexOfEndClip);
  testIndex := INSTR (host,'ias$',1,1);
IF testIndex = 0
THEN
  newURL := SUBSTR (newURL, 0, indexOfStartClip);
  workerURL := SUBSTR(workerURL,
indexOfEndClip+1,urlLength-indexOfEndClip);
  indexOfStartClip:= INSTR (workerURL,'%5F',-1,1) ;
  workerURL := SUBSTR(workerURL, 0,indexOfStartClip-1);
  newURL := newURL||workerURL||'?event=doLoad';
  update PORTAL.wwptl_other_services_link$ set URL = newURL where NAME =
'MONITORING';
  COMMIT;
END IF;
CLOSE c1;
END;
/
```

Next you need to clear the mod\_plsql cache and re-start Oracle9iAS Web Cache to flush out existing pages with the incorrect link. To do this:

1. Empty the mod\_plsql cache by deleting the contents of the plsql directory:

---

---

**Warning: Only delete the contents of the plsql directory.**

---

---

```
rm -fr ORACLE_HOME/Apache/modplsql/cache/plsql/*
```

2. Re-start the Web Cache:

```
cd ORACLE_HOME/webcache/bin
./webcachectl restart
```

---

---

**Note:** An alternative workaround is to go to the Oracle Enterprise Manager interface directly, navigate to the portal instance by selecting the appropriate Application Server that contains the Portal Targets and then select the Portal Target from the Application Server Page's list of components. The URL being:

`http://host.domain:1810/emd/console/targets`

---

---

#### 4.3.4 NLS Cannot Be Authenticated By Oracle9iAS Single Sign-On if Username Contains Non-ASCII Characters

For non-ASCII usernames to work, the default encoding of the OC4J Java VM running the Oracle9iAS Syndication Server should be compatible with the character set of the Oracle9iAS Single Sign-On Login Server. The Java VM default encoding is determined by the locale on which OC4J is started. The character set of the Oracle9iAS Single Sign-On Login Server is the character set of the database on which the Oracle9iAS Single Sign-On Login Server is deployed.

For example, when OC4J is deployed on a Japanese locale environment with Shift-JIS as the character set of the locale, the default encoding of the Java VM is SJIS (Java encoding name for the Shift-JIS character set). In this case, the database character set of the Oracle9iAS Single Sign-On Login Server should also be JA16SJIS (Oracle's character set for SJIS) in order to use Japanese multibyte usernames.

## 4.4 Oracle9iAS Wireless Issues

The following are known issues with Oracle9iAS Wireless:

- [Cannot Create a Quicklink for a Module](#)
- [Running Oracle9iAS Wireless Against an upgraded OID](#)

### 4.4.1 Cannot Create a Quicklink for a Module

In this release, it is not possible to create a quicklink for a module.

### 4.4.2 Running Oracle9iAS Wireless Against an upgraded OID

This version of Oracle9iAS Wireless requires a user with the distinguished name:

```
cn=orcladmin, cn=Users, default_subscriber_dn
```

to exist in the upgraded OID. If you are using wireless functionality (for example, Self Registration), with user-related model APIs against this OID instance, then this user should be granted CREATE, DELETE, and EDIT privileges for all the users in the default subscriber.

Before installing Oracle9iAS Wireless against an upgraded OID the above mentioned entity must be created with appropriate privileges. For details on creating such an entity with appropriate privileges refer to Chapter 12 - “Managing Oracle Internet Directory” in Oracle9i Application Server Administrator’s Guide, and Chapter 13 - “Directory Access Control” in *Oracle Internet Directory Administrator's Guide*.

## 4.5 Oracle9iAS Web Cache Issues

The following are known issues associated with Oracle9iAS Web Cache:

- [Variations in Host Names of Client Request URLs Should be Defined](#)
- [DAVOraWebCacheReadOnly Parameter Does Not Work](#)
- [Cannot Change Wallet Directory in Web Cache Manager](#)
- [Internet Explorer Limitation with Keep-Alive Setting](#)
- [Using newgrp Command on Linux Intel](#)

### 4.5.1 Variations in Host Names of Client Request URLs Should be Defined

Oracle9iAS Web Cache may crash if the host name of a request URL is ambiguous, for example, `http://myhost:7777/ojspdemos/fragment.jsp`.

To avoid potential problems, specify all possible variations of the site name with site aliases in the Site Definitions page (General Configuration > Site Definitions).

When Web Cache receives a request for a document, it looks at one of the following:

- the Host request-header field
- the host portion of the requested URL
- `<esi:include>` tag to determine the destination site

Web Cache then looks up the configured site settings and mappings (aliases) to determine if the site is supported. If the request does not include host information, then Web Cache sends the request to the default site.

### 4.5.2 DAVOraWebCacheReadOnly Parameter Does Not Work

The `DAVOraWebCacheReadOnly` parameter, if specified in the `httpd.conf` file, does not work with Web Cache version 9.0.2.0.0.

As a workaround, you can use the `<LimitExcept>` directive in the `httpd.conf` file, as described in the OraDAV module configuration chapter of the *Oracle HTTP Server Administration Guide*. Applying access restrictions to a location for all methods except GET, HEAD, and OPTIONS requests will essentially achieve the goal of using the `DAVOraWebCacheReadOnly` parameter. However, a caveat is that end users will always be restricted to GET, HEAD, and OPTIONS requests, even when Web Cache is not being used.

### 4.5.3 Cannot Change Wallet Directory in Web Cache Manager

In the Oracle9iAS Web Cache Manager, you cannot change the wallet directory from “System Default Location”. To change the wallet directory, you must make the following changes to `ORACLE_HOME/webcache/webcache.xml`:

1. Locate the `CACHE` element for your host.
2. If the `OSWALLET` element exists in `webcache.xml` (either as an element or an empty element), then change the text to the new wallet directory.

If there is no `OSWALLET` element, then you must create it between the `RESOURCELIMITS` and `CALYPSONETINFO` elements.

[Example 4-1](#) shows a sample `OSWALLET` element.

#### **Example 4-1 OSWALLET Element in webcache.xml (excerpt)**

```
<CACHE NAME="myhost.us.oracle.com-WebCache" ORACLEHOME="/u1/ora9ias" ...>
  ...
  <RESOURCELIMITS MAXINBOUNDCONNECTIONS="700" MAXCACHESIZE_MB="500"/>
  <OSWALLET>/u1/ora9ias/webcache/wallets/default</OSWALLET>
  <CALYPSONETINFO/>
  ...
</CACHE>
```

### 4.5.4 Internet Explorer Limitation with Keep-Alive Setting

For HTTPS requests, Internet Explorer 5.5 may send requests after Oracle9iAS Web Cache has already tried to close the connection. To resolve this issue, disable keep-alive by setting Keep-Alive to 0 on the Network Timeouts page (Cache-Specific Configuration > Network Timeouts) of the Oracle9iAS Web Cache Manager. This closes the connection between Oracle9iAS Web Cache and the client browser after the browser returns a response.

### 4.5.5 Using newgrp Command on Linux Intel

Avoid using the `newgrp` command on Linux Intel before installation to change the primary group. If you use `newgrp` before installation, the Web Cache Configuration Assistant might fail to start Web Cache after installation is complete. Using `newgrp` before installation creates a mismatch between the group identifier in the `webcache.xml` file (the primary group id) and the group identifier of the installed files (the changed group id).

If you must use `newgrp`, modify the `webcache.xml` file (line number 258) using the correct group id after installation is complete and run the following commands to start Web Cache:

```
$ cd $ORACLE_HOME/webcache/bin
$ webcachectl start
```

You can ignore the webcache configuration assistant failure warning at the end of installation.

## 4.6 Oracle9iAS Reports Services Issues

The following are known issues associated with Oracle9iAS Reports Services:

- [Graph not Generating Oracle6i Graphics](#)
- [Configuration of Reports Server with Oracle Enterprise Manager](#)
- [Shutting Down the Reports Server from Oracle Enterprise Manager](#)

### 4.6.1 Graph not Generating Oracle6i Graphics

Oracle9iAS Reports Services allows you to run Oracle6i Graphics for backward compatibility purposes. This is because Oracle9iAS Reports Services can open a Reports6i report. Therefore, the Oracle6i Graphics charts in the Reports6i report should continue to run correctly in the Oracle9iAS Reports Services environment.

However, in Oracle9iAS Reports Services environment, when you run a report that contains Oracle6i Graphics, you may get the following error message:

```
REP-1811: Error while generating graph. SSL fatal error: Cannot execute g90runm.
```

If this happens, you need to create a link from `g90runm` to `g90runm.sh` in your `ORACLE_HOME/bin` directory.

Note that you also need to specify the path of your Oracle6i home in the `ORACLE_GRAPHICS6I_HOME` variable in `g90runm.sh` and ensure that your Oracle6i home directory is in that path.

## 4.6.2 Configuration of Reports Server with Oracle Enterprise Manager

After installation, the Reports Server instance is not accessible from Oracle Enterprise Manager. This is because the password for the Reports target is not the Oracle9i Application Server administration password.

To fix this problem:

1. Open the file `ORACLE_HOME/sysman/emd/targets.xml`.
2. Search for the reports target. The target type for reports is `oracle_repserv`. The target definition contains a property for `Password`, for example:

```
<Property NAME="Password" VALUE="3f769cle7cfd7411" ENCRYPTED="TRUE" />
```

3. Change the `VALUE` to the Oracle9i Application Server admin password and set `ENCRYPTED` to `FALSE`. For example:

```
<Property NAME="Password" VALUE="adminpasswd" ENCRYPTED="FALSE" />
```

4. Restart Oracle Enterprise Manager:

```
# ORACLE_HOME/bin/emctl stop  
# ORACLE_HOME/bin/emctl start
```

Oracle Enterprise Manager automatically encrypts the password and set the `ENCRYPTED` flag to `TRUE`.

## 4.6.3 Shutting Down the Reports Server from Oracle Enterprise Manager

When running in secure mode, the Reports Server cannot be shut down from Oracle Enterprise Manager. In this case, you must shut down the Reports Server from the Reports Server dialog box or kill the process.

## 4.7 Oracle9iAS Clickstream Intelligence Issues

The following sections should be noted when installing, configuring, and using Oracle9iAS Clickstream Intelligence:

- [Configuring Clickstream After Installing Oracle9iAS Using Oracle Universal Installer](#)
- [Error Displaying Clickstream Runtime Administrator](#)

### 4.7.1 Configuring Clickstream After Installing Oracle9iAS Using Oracle Universal Installer

If the user choose not to configure Oracle9iAS Clickstream Intelligence via Oracle Universal Installer and decides to configure it at a later time, then they should do the following:

---

---

**Note:** Configuring Oracle9iAS Clickstream Intelligence at a later time is normally done through Oracle Enterprise Manager (OEM), but in Release 2 (9.0.2), configuring Oracle9iAS Clickstream Intelligence through OEM is unavailable

---

---

Verify that the environment variable `ORACLE_HOME` set to your Oracle9iAS installation directory before running the scripts provided below.

#### 1. Run Oracle9iAS Clickstream Intelligence Configuration tool.

```
LD_LIBRARY_PATH=ORACLE_HOME/lib:ORACLE_HOME/network/lib:ORACLE_HOME/jdk/jre/  
lib/sparc  
export LD_LIBRARY_PATH  
touch ORACLE_HOME/j2ee/deploy.ini  
ORACLE_HOME/jdk/bin/java -cp  
ORACLE_HOME/click/lib/click.jar:ORACLE_HOME/jlib/repository.jar  
oracle.click.common.ConfigureBI ORACLE_HOME/j2ee/deploy.ini  
ORACLE_HOME
```

## 2. Deploy Oracle9iAS Clickstream Intelligence to OC4J

```
ORACLE_HOME/jdk/bin/java -classpath
  ORACLE_HOME/dcm/lib/dcm.jar:
  ORACLE_HOME/jlib/emConfigInstall.jar:
  ORACLE_HOME/lib/classes12.zip:
  ORACLE_HOME/lib/dms.jar:
  ORACLE_HOME/j2ee/home/oc4j.jar:
  ORACLE_HOME/lib/xschema.jar:
  ORACLE_HOME/lib/xmlparserv2.jar:
  ORACLE_HOME/opmn/lib/ons.jar:
  ORACLE_HOME/j2ee/home/jaas.jar:
  ORACLE_HOME/j2ee/home/jazn.jar:
  ORACLE_HOME/j2ee/home/jaznplugin.jar:
  ORACLE_HOME/dcm/lib/oc4j_deploy_tools.jar
  oracle.j2ee.tools.deploy.Oc4jDeploy
  -oraclehome $ORACLE_HOME
  -verbose
  -inifile $ORACLE_HOME/j2ee/deploy.ini
```

Oracle9iAS Clickstream Intelligence uses Discoverer to display reports. The steps above will configure Discoverer automatically if the user has not done so.

## 3. Restart the iAS server and Discoverer server

```
ORACLE_HOME/dcm/bin/dcmctl stop
ORACLE_HOME/dcm/bin/dcmctl start
ORACLE_HOME/discoverer902/util/stopall.sh
ORACLE_HOME/discoverer902/util/startall.sh
```

Users will then be able to access Oracle9iAS Clickstream Intelligence at the following URL:

```
http://iashost:port/click'
```

## 4.7.2 Error Displaying Clickstream Runtime Administrator

An intermittent “Page Not Displayed” error may be experienced when using certain versions of Microsoft Internet Explorer to access Clickstream Runtime Administrator. This is due to issues between Oracle9iAS Web Cache and Internet Explorer when SSL is enabled.

This problem can be worked around using one of the following methods:

- By using the Reload button of the browser to reload the page.
- Disable SSL (recommended)

To do this, edit the file `$ORACLE_HOME/click/conf/click-apache.conf` to comment out the following lines (by adding a “#” character at the beginning of each line):

```
<Location /click>
  RewriteEngine on
  RewriteCond %{HTTPS} !=on
  RewriteRule ^(config/.*)$
      https://%{SERVER_NAME}:%{APACHEPORTSSL}/click/$1
  [R]
</Location>
```

Restart Oracle9iAS using Oracle Enterprise Manager or the following commands:

```
ORACLE_HOME/dcm/bin/dcmctl stop
ORACLE_HOME/dcm/bin/dcmctl start
```

- Disable Web Cache (not recommended as it will disable all web applications)

Perform the following steps:

1. Comment out the following two lines in

```
$ORACLE_HOME/Apache/Apache/conf/httpd.conf
```

```
Port 7777
Port 4443
```

The actual port numbers may vary if they have been modified from the default shown.

2. Edit `$ORACLE_HOME/click/conf/click-apache.conf` and change the line

```
RewriteRule ^(config/.*)$ https://%{SERVER_NAME}:4443/click/$1
```

to

```
RewriteRule ^(config/.*)$ https://%{SERVER_NAME}:4444/click/$1
```

Again, you may have set up your port numbers differently. 4444 is the SSL listener port defined in the SSL configuration section in `$ORACLE_HOME/Apache/Apache/conf/httpd.conf`.

3. Restart Oracle9iAS, and point the browser to the Oracle9iAS listen port defined in `httpd.conf` (by default it is 7778).

## 4.8 Oracle9iAS Single Sign-On Issues

The following are known issues associated with Oracle9iAS Single Sign-On:

- [Logging Out from Oracle9iAS Single Sign-On Enabled Applications Leaves Non-Oracle9iAS Single Sign-On Enabled Applications Open and Vice Versa](#)

### 4.8.1 Logging Out from Oracle9iAS Single Sign-On Enabled Applications Leaves Non-Oracle9iAS Single Sign-On Enabled Applications Open and Vice Versa

Not all applications are integrated with Oracle9iAS Single Sign-On. If an application is not integrated with Oracle9iAS Single Sign-On, then its logout function is also not integrated. That means that when users click the logout button, they are logged out of that application only; they are not logged out applications that are integrated with Oracle9iAS Single Sign-On. Users may mistakenly assume that they are logged out of all Oracle9i Application Server, which is not the case. Conversely, when users click the logout button from an Oracle9iAS Single Sign-On-enabled application, they are logged out of all Oracle9iAS Single Sign-On-enabled applications, but not out of applications that are not Oracle9iAS Single Sign-On-enabled.

## 4.9 Oracle9iAS Unified Messaging

On most UNIX systems, sendmail is configured by default and is started when the system comes up. To enable the SMTP server to listen to the default SMTP protocol port (port 25), sendmail must to be shutdown.

Run the following command as `root` to shut down sendmail:

For HP:

```
/sbin/init.d/sendmail stop
```

For Linux:

```
/etc/init.d/sendmail stop
```

For Compaq Tru64 UNIX:

```
/sbin/init.d/sendmail stop
```

For AIX:

```
/stopsrc -s sendmail
```

To prevent sendmail from restarting if the system is rebooted, remove the sendmail startup from the OS `init` files. If no other application running on that server uses it, rename the sendmail executable under `/usr/lib`.

## 4.10 Oracle9iAS Proxy Plug-in

The Oracle9iAS Proxy Plug-in is not supported on IBM AIX 5L-based systems for this release of Oracle9i Application Server.



---

---

## Documentation Errata

This section describes documentation issues in the following documentation:

- [Oracle9i Application Server Installation Guide](#)
- [Oracle9i Application Server Concepts](#)
- [Oracle9i Application Server Administrator's Guide](#)
- [Oracle9i Application Server Security Guide](#)
- [Oracle9i Application Server Globalization Support Guide](#)
- [Oracle9i Application Server: Migrating from Oracle Application Server](#)
- [Oracle Syndication Server User's and Administrator's Guide](#)
- [Oracle9i Application Developer's Guide - XML](#)
- [Online Help](#)

## 5.1 *Oracle9i Application Server Installation Guide*

The following are known issues with the *Oracle9i Application Server Installation Guide*:

- [InterConnect Software](#)

### 5.1.1 InterConnect Software

To clarify the information in *Oracle9i Application Server Installation Guide*, Appendix C, the Oracle9iAS Interconnect software is in the Oracle9iAS Integration CD-ROM in the CD Pack.

## 5.2 Oracle9i Application Server Concepts

Following are the known issues in the *Oracle9i Application Server Concepts*:

- [Characterization of New iPlanet Connector](#)

### 5.2.1 Characterization of New iPlanet Connector

The *Oracle9i Application Server Concepts* positioned Oracle Internet Directory incorrectly and mischaracterized the new iPlanet connector.

The sentence from the *Oracle9i Application Server Concepts*:

"With Oracle9iAS, Oracle Internet Directory includes an agent for out-of-the-box synchronization with Oracle Human Resources and an agent for synchronizing information with selected third party LDAP servers"

should read:

"With Oracle9iAS, Oracle Internet Directory includes connectors for out-of-the-box synchronization with Oracle Human Resources and iPlanet Directory Server 4.2 and 5.0."

## 5.3 *Oracle9i Application Server Administrator's Guide*

Following are the known issues in the *Oracle9i Application Server Administrator's Guide*:

- [Association Middle-Tier Installations with an Infrastructure](#)

### 5.3.1 Association Middle-Tier Installations with an Infrastructure

Chapter 2 of the *Oracle9i Application Server Administrator's Guide* states that once an infrastructure is installed on a host, all subsequent middle-tier installations on that host will automatically use the infrastructure. For Release 2 (9.0.2), if you install an infrastructure on a host, subsequent middle-tier installations will not automatically associate with that infrastructure. However, once a middle-tier installation has been associated with an infrastructure, all subsequent middle-tier installations on the same host will automatically associate with that infrastructure.

For the initial installation of the J2EE and Web Cache install type on a host, you can choose whether to associate an infrastructure with the install. If you do want to associate the install with an infrastructure, you can supply the information for whichever infrastructure you want.

For initial installations of all other install types on a host, the installation must be associated with an infrastructure of your choosing. You will be prompted to supply information about the infrastructure you want to use.

## 5.4 Oracle9i Application Server Security Guide

Following are the known issues in the Oracle9i Application Server Security Guide:

- [SSLPassPhraseDialog Not Valid in Virtual Host Context](#)
- [Remove PLsqlEnableConnectionPooling from Configured dads.conf File](#)
- [Updated Information Regarding Oracle9iAS Portal Default User Accounts](#)
- [Updated Information for Default User Password Policy](#)

### 5.4.1 SSLPassPhraseDialog Not Valid in Virtual Host Context

The *Oracle9i Application Server Security Guide* lists the “virtual host” as a context for `SSLPassPhraseDialog` directive. The valid context for `SSLPassPhraseDialog` directive is “server” only.

### 5.4.2 Remove PLsqlEnableConnectionPooling from Configured dads.conf File

The “Configuring Oracle9iAS Single Sign-On” chapter of the *Oracle9i Application Server Security Guide* contains information about a configured `dads.conf` file. The term `PLsqlEnableConnectionPooling` should be deleted from the file.

### 5.4.3 Updated Information Regarding Oracle9iAS Portal Default User Accounts

The “Oracle9iAS Portal Default User Accounts” bullet in the “Relationship between Oracle9iAS Portal and Oracle Internet Directory” section of the “Configuring Oracle9iAS Portal Security” chapter of the *Oracle9i Application Server Security Guide* states the following:

(`cn=PUBLIC, cn=PORTAL, cn=PORTAL_ADMIN`) are created in the subscriber’s user base (`cn=Users, o=MyCompany, dc=com`).

It should be changed to:

(`cn=PUBLIC, cn=PORTAL, cn=PORTAL_ADMIN`) are created in the subscriber’s user base (`cn=Users, dc=MyCompany, dc=com`).

#### 5.4.4 Updated Information for Default User Password Policy

The “Default User Password Policy in Oracle9iAS” table in the “Oracle9i Application Server Security Architecture and Features” chapter of the *Oracle9i Application Server Security Guide* should state this additional information:

“After ten failed attempts to log in with an incorrect password, user accounts are locked out for a period of 24 hours.”

## 5.5 Oracle9i Application Server Globalization Support Guide

Following are the known issues or errors in the Oracle9i Application Server Globalization Support Guide.

- [Multilingual Support for Oracle9iAS Single Sign-On](#)
- [Updated Instructions for Deploying World-of-Books Demo](#)

### 5.5.1 Multilingual Support for Oracle9iAS Single Sign-On

The following information was omitted from the Oracle9i Application Server Globalization Support Guide.

The Single Sign-On login page does not display language selection buttons if other languages were not installed. As a result, no product can run in non-English mode.

Oracle9iAS Single Sign-On supports 29 languages. English is the only language installed by default. You need to install other languages in order to support these languages during Single Sign-On login. To install additional languages, execute the following command:

```
ORACLE_HOME/jdk/bin/java -jar ORACLE_HOME/sso/lib/ossoca.jar langinst  
lang make_lang_avail ORACLE_HOME
```

*lang* specifies the code for the language to be installed.

*make\_lang\_avail* specifies whether or not to make the language available. Enter 1 to make the language available, 0 otherwise.

**See Also:** *Oracle9iAS Single Sign-On Administrator's Guide*

### 5.5.2 Updated Instructions for Deploying World-of-Books Demo

The section on “How to Deploy the World-of-Books Demo” in the “Multilingual Demo for Oracle9iAS” chapter of the *Oracle9i Application Server Globalization Support Guide* should be changed to remove the references on manual steps to deploy an OC4J applications.

The content should be replaced with the following:

How to Deploy the World-of-Books Demo on Oracle9iAS J2EE:

1. Add data sources through Oracle Enterprise Manager. The data source attributes can found in the following file:

```
ORACLE_HOME/j2ee/home/demo/globalization/j2ee_config/data-sources.xml
```

- Replace `<HOSTNAME>` with the database server's hostname.
- Replace `<PORT>` with the database server's port number.
- Replace `<ORACLE_SID>` with the database server's oracle SID.

After the data sources are added through Oracle Enterprise Manager, your `J2EE_HOME/config/data-sources.xml` should contain entries that correspond to those in `globalization/j2ee_config/data-sources.xml`.

2. Deploy the application `J2EE_HOME/demo/globalization/lib/g11n.ear` through Oracle Enterprise Manager, or the `dcmctl` command utility as demonstrated below:

```
dcmctl deployApplication -file J2EE_HOME/demo/globalization/lib/g11.ear
-application g11n -component home
```

where *home* is the default OC4J instance onto which the demo is deployed.

3. You can verify this by visiting the pages listed below on a Web browser. In order to view a particular language, your operating system should have that language installed.

```
Main site: http://<host>:<port>/g11n/imap.html
WOB site: http://<host>:<port>/g11n/wob/jsp/welcome.jsp
Supplier A: http://<host>:<port>/g11n/suppA/html/frame.html
Supplier B: http://<host>:<port>/g11n/suppB/html/frame.html
```

## 5.6 Oracle9i Application Server: Migrating from Oracle Application Server

Following are the known issues in *Oracle9i Application Server: Migrating from Oracle Application Server*:

- [Updated ossoconvert or ssl2oss1 Migration Tool Information](#)

### 5.6.1 Updated ossoconvert or ssl2oss1 Migration Tool Information

The *Oracle9i Application Server: Migrating from Oracle Application Server* guide lists the following parameters for the `ssl2oss1` or `ossoconvert` tool:

**Table 5–1 Summary of ssl2oss1 or ossoconvert Tool Parameters**

Parameter	Description	Requirement
<code>chain</code>	Oracle Application Server certificate chain file	optional
<code>capath</code>	Oracle Application Server certificate authority file	optional
<code>cafile</code>	Oracle Application Server certificate authority file	optional

To make sure a valid wallet generates, you must specify the trustpoints, that is, you need to specify the signers of the server certificates. This is the most common reason result for an invalid wallet.

There are two ways to specify the signers:

- Concatenate the signer (and all the intermediate signers, certificate chain) certificates into the server certificate file.
- Concatenate all the signers in one file and specify by `-chain`.

If you want to import other CA certificates, like `SSLCACertificateFile` in the `httpd.conf`, then use `-cafile` and `-capath` to do so.

## 5.7 Oracle Syndication Server User's and Administrator's Guide

Following are the known issues in the Oracle Syndication Server User's and Administrator's Guide:

- [Using Oracle9iAS Single Sign-On with Oracle9iAS Syndication Server](#)

### 5.7.1 Using Oracle9iAS Single Sign-On with Oracle9iAS Syndication Server

Appendix E in the *Oracle Syndication Server User's and Administrator's Guide* omitted the following information regarding how to use Oracle9iAS Single Sign-On with Oracle9iAS Syndication Server.

In the following instructions, *ORACLE\_HOME* is the home directory for the Portal & Wireless mid-tier installation type (which includes Oracle9iAS Syndication Server). Perform the following tasks to make Oracle9iAS Single Sign-On protect the Oracle9iAS Syndication Server URL.

1. Use Single Sign-On to protect the `/syndserver/OSS` URL.

In the *ORACLE\_HOME*/Apache/Apache/conf/mod\_osso.conf configuration file, insert the following lines between the `<IfModule>` and `</IfModule>` tags. Adding these lines protects the `/syndserver/OSS` directory from unauthenticated access.

```
<Location /syndserver/OSS>
    require valid-user
    AuthType Basic
</Location>
```

2. Configure the push URL, which is used internally to push content.

Configure the push URL in the file

*ORACLE\_HOME*/j2ee/OC4J\_Portal/applications/syndserver/syndserver/WEB-INF/web.xml by adding the following lines between the `<web-app>` and `</web-app>` tags.

```
<servlet-mapping>
    <servlet-name>OSS</servlet-name>
    <url-pattern>/OSSPUSH</url-pattern>
</servlet-mapping>
```

3. Protect the push URL to allow only receiving the HTTP GET request from the local scheduler sub-system.

In the `ORACLE_HOME/Apache/Apache/conf/mod_oc4j.conf` configuration file, add the following lines between the `<IfModule>` and `</IfModule>` tags.

```
<Location /syndserver/OSSPUSH>
  <Limit GET>
    Order deny,allow
    Deny from all
    Allow from localhost local-machine-name
  </Limit>
  <Limit POST>
    Deny from all
  </Limit>
</Location>
```

4. Restart Oracle HTTP Server to apply the changes.

You can use Oracle Enterprise Manager, the Distributed Configuration Management command-line tool (`dcmctl`), or `opmnctl` to restart Oracle HTTP Server.

5. Configure the `PUSH_HANDLER_URL` parameter using the Oracle9iAS Syndication Server Administration page.

In Oracle Enterprise Manager, go to the Syndication Server Administration Page. Choose the **Global Properties** tab, and change the value of the `PUSH_HANDLER_URL` parameter to the following URL:

```
http://<your-local-machine-name>:<your-port-number>/syndserver/OSSPUSH
```

## 5.8 Oracle9i Application Developer's Guide - XML

Updated versions of Chapters 5 and 6 of *Oracle9i Application Developer's Guide - XML* are available from OTN at

<http://otn.oracle.com/tech/xml/doc.html>

## 5.9 Online Help

The following are issues with online help for various components:

- [Broken Links to DAS Online Help](#)
- [Online Help May Not Display Correct Language](#)

## 5.9.1 Broken Links to DAS Online Help

A few Portal Help topics include links to the DAS (Delegated Administration Service) Help. If you find that these links are broken, it is probably because they are pointing to the wrong machine or port for your Oracle Internet Directory (OID) server. You can do one of the following:

- Correct the machine name or port in the URL in your browser's location field.
- (Preferred) Correct the Javascript that is used for these links. The Javascript is located in the following directory:

```
ORACLE_HOME/portal/doc/h_extlnk.js
```

In the function `show_das_help`, change the URL to point to the correct machine and port:

```
function show_das_help(dastopic) {  
    window.location="http://myoidmachine.com:3000/oiddas/oracle/ldap/das/onli  
nehelp/das/"+dastopic;  
}
```

## 5.9.2 Online Help May Not Display Correct Language

Translated versions of online help are installed into the Oracle home directory but are not always called correctly when using Oracle9iAS Discoverer Plus, Oracle9iAS Portal, or Oracle Ultra Search.

In order to view help information in the correct language, go to *ORACLE\_HOME/component/doc* to find the translated help files.

