

Oracle® Database

Client Quick Installation Guide

10g Release 2 (10.2) for Linux on POWER

B25150-01

November 2005

This guide describes how to quickly install Oracle Database Client on Linux on POWER systems. It includes information about the following:

1. [Reviewing Information About this Guide](#)
2. [Logging In to the System as root](#)
3. [Checking the Hardware Requirements](#)
4. [Checking the Software Requirements](#)
5. [Creating Required Operating System Group and User](#)
6. [Creating an Oracle Base Directory](#)
7. [Configuring the oracle User's Environment](#)
8. [Mounting the Product Disc](#)
9. [Installing Oracle Database Client](#)
10. [What to Do Next?](#)
11. [Documentation Accessibility](#)

1 Reviewing Information About this Guide

Note: This guide describes how to install Oracle Client on a system that does not have any Oracle software installed on it. If there is an existing Oracle software installation on this system, then refer to *Oracle Database Client Installation Guide for Linux on POWER* for more detailed installation instructions.

This guide describes how to complete a default installation of Oracle Database Client on a system that does not have any Oracle software installed on it. It describes how to install one of the following installation types:

- **Administrator:** Enables applications to connect to an Oracle Database instance on the local system or on a remote system. It also provides tools that enable you to administer Oracle Database.
- **Runtime:** Enables applications to connect to an Oracle Database instance on the local system or on a remote system.
- **Instant Client:** Enables you to install only the shared libraries required by Oracle Call Interface (OCI), Oracle C++ Call Interface (OCCI), Pro*C, or Java

database connectivity (JDBC) OCI applications. This installation type requires much less disk space as compared to the other Oracle Database Client installation types.

See Also: *Oracle Call Interface Programmer's Guide* for more information about the Instant Client feature

This guide does not describe how to install the Custom installation type.

Where to Get Additional Installation Information

For more detailed information about installing Oracle Database Client, refer to *Oracle Database Client Installation Guide for Linux x86-64*.

This guide is available on the product disc. To access it, use a Web browser to open the `welcome.htm` file located in the top-level directory of the installation media, and then select the **Documentation** tab.

2 Logging In to the System as root

Before you install Oracle Database Client, you must complete several tasks as the `root` user. To log in as the `root` user, complete one of the following procedures:

Note: You must install the software from an X Window System workstation, an X terminal, or a PC or other system with X server software installed.

- If you are installing the software from an X Window System workstation or X terminal, then:

1. Start a local terminal session, for example, an X terminal (`xterm`).
2. If you are not installing the software on the local system, then enter the following command to enable the remote host to display X applications on the local X server:

```
$ xhost fully_qualified_remote_host_name
```

For example:

```
$ xhost somehost.us.acme.com
```

3. If you are not installing the software on the local system, then use the `ssh`, `rlogin`, or `telnet` command to connect to the system where you want to install the software:

```
$ telnet fully_qualified_remote_host_name
```

4. If you are not logged in as the `root` user, then enter the following command to switch user to `root`:

```
$ su - root
password:
#
```

- If you are installing the software from a PC or other system with X server software installed, then:

Note: If necessary, refer to your X server documentation for more information about completing this procedure. Depending on the X server software that you are using, you may need to complete the tasks in a different order.

1. Start the X server software.
2. Configure the security settings of the X server software to permit remote hosts to display X applications on the local system.
3. Connect to the remote system where you want to install the software and start a terminal session on that system, for example, an X terminal (`xterm`).
4. If you are not logged in as the `root` user on the remote system, then enter the following command to switch user to `root`:

```
$ su - root
password:
#
```

3 Checking the Hardware Requirements

The system must meet the following minimum hardware requirements:

- 256 MB of physical RAM
- The following table describes the relationship between installed RAM and the configured swap space requirement.

RAM	Swap Space
Up to 256 MB	3 times the size of RAM
Between 257 MB and 512 MB	2 times the size of RAM
Between 513 MB and 726 MB	1.5 times the size of RAM
More than 726 MB	0.75 times the size of RAM

- The minimum client installation `TMP` space required is 115 MB. The minimum disk space requirement in the `/tmp` directory depends on the installation type you have selected. The following table lists the minimum disk space requirements for the `/tmp` directory in each type of installation.

Installation Type	Disk Space Required for the <code>/tmp</code> Directory (MB)
Admin	835
Runtime	470
Custom (all components selected)	765
Instant	120

- Between 34 MB and 820 MB of disk space for the Oracle software, depending on the installation type

To ensure that the system meets these requirements, follow these steps:

1. To determine the physical RAM size, enter the following command:

```
# grep MemTotal /proc/meminfo
```

If the size of the physical RAM installed in the system is less than the specified value, then you must install more memory before continuing.

2. To determine the size of the configured swap space, enter the following command:

```
# grep SwapTotal /proc/meminfo
```

If necessary, refer to your operating system documentation for information about how to configure additional swap space.

3. To determine the amount of free disk space available in the `/tmp` directory, enter the following command:

```
# df -k /tmp
```

If there is less than 400 MB of disk space available in the `/tmp` directory, then complete one of the following steps:

- Delete unnecessary files from the `/tmp` directory to meet the disk space requirement.
 - Set the `TEMP` and `TMPDIR` environment variables when setting the `oracle` user's environment (described later).
 - Extend the file system that contains the `/tmp` directory. If necessary, contact your system administrator for information about extending file systems.
4. To determine the amount of free disk space available on the system, enter the following command:

```
# df -k
```

The following table shows the approximate disk space requirements for software files for each installation type.

Installation Type	Requirement for Software Files (MB)
Instant Client	130
Administrator	850
Runtime	495
Custom (maximum)	790

Note: If you want to configure only the Instant Client Light component of Instant Client, then you need 34 MB of disk space to store the related files.

5. To determine whether the system architecture can run the software, enter the following command:

```
# grep "model name" /proc/cpuinfo
```

This command displays the processor type. Verify that the processor architecture matches the Oracle software release that you want to install. If you do not see the expected output, then you cannot install the software on this system.

4 Checking the Software Requirements

The system must meet the following minimum software requirements.

Item	Requirement
Operating system	One of the following operating system versions: <ul style="list-style-type: none">Red Hat Enterprise Linux AS/ES 4.0 (Update 1 or later)SUSE Linux Enterprise Server 9.0 with SP2 or later
Kernel version	The system must be running the following kernel version (or a later version): Red Hat Enterprise Linux 4.0: 2.6.9-11.EL SUSE Linux Enterprise Server 9.0: 2.6.5-7.191-pseries64

Item	Requirement
Packages	<p>The following packages (or later versions) must be installed:</p> <p>Red Hat Enterprise Linux 4.0:</p> <pre>Gmake-3.80-5 gcc-3.4.3-22.1 gcc-ppc32-3.4.3-22.1 gcc-c++-3.4.3-22.1 gcc-c++-ppc32-3.4.3-22.1 glibc-2.3.4-2.9 glibc-2.3.4-29 (64-Bit) libgcc-3.4.3-9.EL4 libgcc-3.4.3-9.EL4.ppc64.rp libstdc++-3.4.3-9.EL4 libstdc++-devel-3.4.3-9.EL4 libaio-0.3.103-3 libaio-0.3.103-3 (64-Bit) libaio-devel-0.3.103-3 (64-Bit) compat-libstdc++-33-3.2.3-47.3 binutils-2.15.92.0.2-13</pre> <p>Red Hat Enterprise Linux 4.0:</p> <pre>gcc-3.3.3-43.34 gcc-64bit-9-200505240008 gcc-c++-3.3.3-43.34 glibc-2.3.3-98.47 glibc-64bit-9-200506062240 libgcc-3.3.3-43.34 libgcc (64-bit) 9-200505240008 libstdc++-3.3.3-43.34 libstdc++-devel-3.3.3-43.34 libaio-0.3.102-1.2 libaio-64bit-9-200502241152 libaio-devel-0.3.102-1.2 libaio-devel-0.3.102-1.2 (64-bit) Gmake-3.80-184.1 binutils-2.15.90.0.1.1-32.10 binutils-64bit-9-200505240008</pre>
Oracle Messaging Gateway	<p>Oracle Messaging Gateway supports the integration of Oracle Streams Advanced Queuing (AQ) with the following software:</p> <p>IBM WebSphere MQ V5.3, client and server:</p> <pre>MQSeriesClient MQSeriesServer MQSeriesRuntime</pre>
C/C++ Runtime Environment	<p>Download the IBM XL C/C++ Advanced Edition V7.0.1 for Linux Runtime Environment Component for free without any license requirement from the following link:</p> <p>http://www-1.ibm.com/support/docview.wss?rs=2030&context=SSJT9L&context=SSENT9&context=SSEP5D&dc=D400&dc=D410&dc=D420&dc=D430&q1=Run-time+Environment+Component&uid=swg24007906&loc=en_US&cs=utf-8&lang=en</p> <p>You must also download and install the XL Optimization Libraries component from this link.</p>

Item	Requirement
PL/SQL native compilation, Pro*C/C++, Oracle Call Interface, Oracle C++ Call Interface, Oracle XML Developer's Kit (XDK)	<p>The version of GNU C and C++ compilers listed previously for the distribution are supported for use with these products.</p> <p>Note: IBM XL C/C++ compiler version 7.0 or later is also supported.</p> <p>If the IBM XL C/C++ Advanced Edition V7.0.1 for Linux on POWER compiler is to be used for Oracle user applications then the required version is V7.0.1 or higher. For download information and updates, refer to the following link:</p> <p>http://www-306.ibm.com/software/awdtools/xlcpp/features/linux/</p> <p>If the IBM XL C/C++ Advanced Edition V7.0.1 for Linux on POWER compiler is installed, the IBM XL C/C++ Advanced Edition V7.0.1 for Linux Runtime Environment Component will be automatically installed.</p>
Oracle JDBC/OCI Drivers	<p>You can use the following optional JDK version with the Oracle JDBC/OCI drivers; however, it is not required for the installation:</p> <ul style="list-style-type: none"> ■ IBM Java 1.4.2 64-bit (SR1a) or later ■ IBM Java 1.4.2 32-bit (SR1a) or later ■ IBM Java 1.3.1 32-bit (SR8) or later (for SLES 9 only) <p>Note: By default, IBM Java 1.4.2 32-bit is installed with this release.</p>

See Also: If you plan to use GNU Compiler Collection as the primary compiler, then refer to *Oracle Database Installation Guide for Linux on POWER* for instructions on configuring the primary compiler.

To ensure that the system meets these requirements:

1. To determine which version of the operating system is installed, enter the following command:

```
# cat /etc/issue
```

Note: Only the distributions and versions listed earlier in this section are supported. Do not install the software on other versions of Linux.

2. To determine whether the required kernel is installed, enter the following command:

```
# uname -r
```

The following is sample output obtained by running this command on a Red Hat Enterprise Linux 3.0 system:

```
2.6.9-11.EL
```

In this example, the output shows the kernel version (2.6.9) and errata level (11.EL) on the system.

If the kernel version does not meet the requirement specified earlier in this section, then contact your operating system vendor for information about obtaining and installing kernel updates.

3. To determine whether the required packages are installed, enter commands similar to the following:

```
# rpm -q package_name
```

If a package is not installed, or if the version is lower than the required version, then install it from your Linux distribution media or download the required package from your Linux vendor's Web site.

5 Creating Required Operating System Group and User

The following local operating system group and user must exist on the system:

- The Oracle Inventory group (`oinstall`)
- The Oracle software owner (`oracle`)

To determine if this group and user already exist, and if required, to create them, follow these steps:

1. To determine if the `oinstall` group exists, enter the following command:

```
# more /etc/oraInst.loc
```

If the output of this command shows the `oinstall` group name, then the group already exists.

If the `oraInst.loc` file exists, then the output from this command is similar to the following:

```
inventory_loc=/u01/app/oracle/oraInventory
inst_group=oinstall
```

The `inst_group` parameter shows the name of the Oracle Inventory group (`oinstall`).

2. If necessary, enter the following command to create the `oinstall` group:

```
# /usr/sbin/groupadd oinstall
```

3. To determine whether the `oracle` user exists and belongs to the correct groups, enter the following command:

```
# id oracle
```

If the `oracle` user exists, then this command displays information about the groups to which the user belongs. The output should be similar to the following, indicating that `oinstall` is the primary group:

```
uid=440(oracle) gid=200(oinstall) groups=201(dba),202(oper)
```

4. If necessary, complete one of the following actions:

- If the `oracle` user exists, but its primary group is not `oinstall`, then enter a command similar to the following, where the `-g` option specifies `oinstall` as the primary group and the `-G` option specifies any existing groups to which the `oracle` user belongs:

```
# /usr/sbin/usermod -g oinstall -G dba oracle
```

- If the `oracle` user does not exist, then enter the following command to create it:

```
# /usr/sbin/useradd -g oinstall [-G dba] oracle
```

This command creates the `oracle` user and specifies:

- `oinstall` as the primary group
- `dba` as an optional secondary group

5. Enter the following command to set the password of the `oracle` user:

```
# passwd oracle
```

6 Creating an Oracle Base Directory

Note: You need *not* perform this procedure if an Oracle base directory already exists on the system. If you determine that the `oinstall` group exists, then, typically, the Oracle base directory is the parent directory of the Oracle Inventory directory.

To create the Oracle base directory:

1. Enter the following command to display information about all mounted file systems:

```
# df -k
```

This command displays information about all the file systems mounted on the system, including:

- The physical device name
 - The total amount, used amount, and available amount of disk space
 - The mount point directory for that file system
2. From the display, identify either one or two file systems that meet the disk space requirements mentioned earlier in this section.
 3. Note the name of the mount point directory for each file system that you identified.
 4. Enter commands similar to the following to create the recommended subdirectories in the mount point directory that you identified and set the appropriate owner, group, and permissions on them:

```
# mkdir -p /mount_point/app/oracle_sw_owner  
# chown -R oracle:oinstall /mount_point/app/oracle_sw_owner  
# chmod -R 775 /mount_point/app/oracle_sw_owner
```

For example, if the mount point you identify is `/u01` and `oracle` is the user name of the Oracle software owner, then the recommended Oracle base directory path is as follows:

```
/u01/app/oracle
```

5. When you configure the `oracle` user's environment, set the `ORACLE_BASE` environment variable to specify the Oracle base directory that you have created.

7 Configuring the oracle User's Environment

You run Oracle Universal Installer from the `oracle` account. However, before you start Oracle Universal Installer, you must configure the environment of the `oracle` user. To configure the environment, you must:

- Set the default file mode creation mask (`umask`) to 022 in the shell startup file.
- Set the `DISPLAY` environment variable.

To set the `oracle` user's environment:

1. Start a new terminal session, for example, an X terminal (`xterm`).

2. Enter the following command to ensure that X Window applications can display on this system:

```
$ xhost fully_qualified_remote_host_name
```

3. Complete one of the following steps:

- If the terminal session is not connected to the system where you want to install the software, then log in to that system as the `oracle` user.
- If the terminal session is connected to the system where you want to install the software, then switch user to `oracle`:

```
$ su - oracle
```

4. To determine the default shell for the `oracle` user, enter the following command:

```
$ echo $SHELL
```

5. Open the `oracle` user's shell startup file in any text editor:

Note: On Red Hat Linux, `.bash_profile` is the user startup file for the Bash shell.

- Bourne shell (`sh`), Bash shell (`bash`), or Korn shell (`ksh`):

```
$ vi .bash_profile
```

- C shell (`csh` or `tcsh`):

```
% vi .login
```

6. Enter or edit the following line in the shell startup file, specifying a value of 022 for the default file mode creation mask:

```
umask 022
```

7. If the `ORACLE_SID`, `ORACLE_HOME`, or `ORACLE_BASE` environment variable is set in the file, then remove the corresponding lines from the file.

8. Save the file, and exit from the editor.
9. To run the shell startup script, enter the following command:
 - Bash shell:


```
$ . ~/.bash_profile
```
 - Bourne or Korn shell:


```
$ . ~/.profile
```
 - C shell:


```
% source ~/.login
```
10. If you are not installing the software on the local system, then enter a command similar to the following to direct X applications to display on the local system:

- Bourne, Bash, or Korn shell:


```
$ DISPLAY=local_host:0.0 ; export DISPLAY
```
- C shell:


```
% setenv DISPLAY local_host:0.0
```

In this example, *local_host* is the host name or IP address of the system that you want to use to display Oracle Universal Installer (your workstation or PC).

11. If you determined that the `/tmp` directory had insufficient free disk space when checking the hardware requirements, then identify a file system with the required amount of free space and set the `TEMP` and `TMPDIR` environment variables as follows:
 - a. Use the `df -k` command to identify a suitable file system with sufficient free space.
 - b. If necessary, enter commands similar to the following to create a temporary directory on the file system that you identified, and set the appropriate permissions on the directory:

```
$ su - root
# mkdir /mount_point/tmp
# chmod a+wr /mount_point/tmp
# exit
```

- c. Enter commands similar to the following to set the `TEMP` and `TMPDIR` environment variables:

Bourne, Bash, or Korn shell:

```
$ TMP=/mount_point/tmp
$ TMPDIR=/mount_point/tmp
$ export TEMP TMPDIR
```

C shell:

```
% setenv TMP /mount_point/tmp
% setenv TMPDIR /mount_point/tmp
```

12. Enter the following commands to ensure that the `ORACLE_HOME` and `TNS_ADMIN` environment variables are not set:

- Bourne, Bash, or Korn shell:

```
$ unset ORACLE_HOME
$ unset TNS_ADMIN
```

- C shell:

```
% unsetenv ORACLE_HOME
% unsetenv TNS_ADMIN
```

13. To verify that the environment has been set correctly, enter the following commands:

```
$ umask
$ env | more
```

Verify that the `umask` command displays a value of 22, 022, or 0022 and the environment variables that you set in this section have the correct values.

8 Mounting the Product Disc

On most Linux systems, the product disc mounts automatically when you insert it into the drive. If the disc does not mount automatically, follow these steps to mount it:

1. Switch user to root:

```
$ su - root
```

2. If necessary, enter a command similar to the following to eject the currently mounted disc, then remove it from the drive:

- Red Hat:

```
# eject /mnt/dvd
```

- SUSE:

```
# eject /media/dvd
```

In these examples, `/mnt/dvd` and `/media/dvd` are the mount point directories for the disc drive.

3. Insert the disc into the disc drive.
4. To verify that the disc mounted automatically, enter a command similar to the following:

- Red Hat:

```
$ ls /mnt/dvd
```

- SUSE:

```
$ ls /media/dvd
```

5. If this command fails to display the contents of the disc, then enter a command similar to the following:

- Red Hat:

```
# mount -t iso9660 /dev/dvd /mnt/dvd
```

- SUSE:

```
# mount -t iso9660 /dev/dvd /media/dvd
```

In these examples, `/mnt/dvd` and `/media/dvd` are the mount point directories for the disc drive.

9 Installing Oracle Database Client

After configuring the `oracle` user's environment, start Oracle Universal Installer and install the Oracle software as follows:

1. To start Oracle Universal Installer, enter the following command:

```
$ /mount_point/client/runInstaller
```

If Oracle Universal Installer does not start, then refer to *Oracle Database Client Installation Guide for Linux x86-64* for information about how to troubleshoot X display problems.

2. The following table describes the recommended action for each Oracle Universal Installer screen. Use the following guidelines to complete the installation:
 - If you need more assistance, or if you want to choose an option that is not a default, then click **Help** for additional information.
 - If you encounter errors while installing or linking the software, then refer to for information about troubleshooting.

Note: If you have completed the tasks listed previously, then you can complete the installation by choosing the default values on most screens.

Screen	Recommended Action
Welcome	Click Next .
Select Installation Type	Select InstantClient, Administrator, or Runtime . Then, click Next .
Specify Home Details	Specify the name and directory path of the Oracle home.
Product-Specific Prerequisite Checks	Verify that all of the prerequisite checks have succeeded, and then click Next . Oracle Universal Installer checks the system to verify that it is configured correctly to run Oracle software. If you have completed all of the preinstallation steps in this guide, then all of the checks should pass. If a check fails, then review the cause of the failure listed for that check on the screen. If possible, rectify the problem and rerun the check. Alternatively, if you are satisfied that your system meets the requirements, then you can select the check box for the failed check to manually verify the requirement.

Screen	Recommended Action
Summary	Review the information displayed on this screen, and then click Install .
Install	This screen displays status information while the product is being installed.
Configuration Assistants	This screen is displayed only if you select Administrator or Runtime on the Select Installation type screen. This screen displays status information for the Oracle Net Configuration Assistant that configures Oracle Net. When the message is displayed at the end of this process, click OK to continue.
Oracle Net Configuration Assistant: Welcome	This screen is displayed only if you select Administrator or Runtime on the Select Installation Type screen. Review the information on this screen, and then click Next . The Oracle Net Configuration Assistant configures the easy connect naming method. For more information about this naming method, click Help .
Oracle Net Configuration Assistant: Done	Click Finish to continue.
Execute Configuration Scripts	When prompted, read the instructions and then run the script mentioned on this screen. Click OK to continue.
End of Installation	To exit from Oracle Universal Installer, click Exit , and then click Yes .

10 What to Do Next?

After you have successfully installed Oracle Client, refer to *Oracle Database Client Installation Guide for Linux x86-64* for information about required and optional postinstallation steps.

11 Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible, with good usability, to the disabled community. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at

<http://www.oracle.com/accessibility/>

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

TTY Access to Oracle Support Services

Oracle provides dedicated Text Telephone (TTY) access to Oracle Support Services within the United States of America 24 hours a day, seven days a week. For TTY support, call 800.446.2398.

Oracle Database Client Quick Installation Guide, 10g Release 2 (10.2) for Linux on POWER
B25150-01

Copyright © 2005, Oracle. All rights reserved.

The Programs (which include both the software and documentation) contain proprietary information; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs, except to the extent required to obtain interoperability with other independently created software or as specified by law, is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. This document is not warranted to be error-free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose.

If the Programs are delivered to the United States Government or anyone licensing or using the Programs on behalf of the United States Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the Programs, including documentation and technical data, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement, and, to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software—Restricted Rights (June 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and we disclaim liability for any damages caused by such use of the Programs.

Oracle, JD Edwards, PeopleSoft, and Retek are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

The Programs may provide links to Web sites and access to content, products, and services from third parties. Oracle is not responsible for the availability of, or any content provided on, third-party Web sites. You bear all risks associated with the use of such content. If you choose to purchase any products or services from a third party, the relationship is directly between you and the third party. Oracle is not responsible for: (a) the quality of third-party products or services; or (b) fulfilling any of the terms of the agreement with the third party, including delivery of products or services and warranty obligations related to purchased products or services. Oracle is not responsible for any loss or damage of any sort that you may incur from dealing with any third party.

