

**Oracle® Retail Store Inventory Management**  
Installation Guide  
Release 15.0.1  
E76324-02

September 2017

Copyright © 2017, Oracle. All rights reserved.

Contributors: Nathan Young

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

## Value-Added Reseller (VAR) Language

### Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as **Access Via**™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as **Adobe Flex**™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.



---

---

# Contents

<b>Send Us Your Comments</b> .....	<b>ix</b>
<b>Preface</b> .....	<b>xi</b>
Audience .....	xi
Related Documents.....	xi
Customer Support.....	xi
Review Patch Documentation.....	xi
Improved Process for Oracle Retail Documentation Corrections .....	xii
Oracle Retail Documentation on the Oracle Technology Network.....	xii
Conventions.....	xii
<b>1 Preinstallation Tasks</b> .....	<b>1</b>
Implementation Capacity Planning.....	1
Check Supported Database Server Requirements.....	2
Check Supported Application Server Requirements .....	3
Check Single Sign-On Requirements .....	4
Check Directory Server Requirements.....	4
Check Third-Party Software Dependencies .....	4
Check Client PC and Web Browser Requirements.....	4
Supported Oracle Retail Products .....	5
UNIX User Account Privileges to Install the Software .....	5
SIM Installation Overview .....	5
<b>2 RAC and Clustering</b> .....	<b>7</b>
<b>3 Database Installation Tasks</b> .....	<b>9</b>
Expand the SIM Database Schema Installer Distribution.....	9
Required Database Character Set .....	9
Required Tablespaces .....	10
Create the SIM Database User.....	11
Run the SIM Database Schema Installer .....	12
Grant Privileges for the Roles.....	12
Resolving Errors Encountered During Database Schema Installation .....	12
Running Data Seeding.....	13
<b>4 Database Installation Tasks – Upgrade</b> .....	<b>15</b>
Upgrading SIM.....	15
<b>5 Application Installation Tasks</b> .....	<b>17</b>
Create the Domain with ADF Libraries and Enterprise Manager .....	17
Install RCU Database Schemas .....	23
Create a New ADF Domain (with managed server and EM) .....	30
Configuration of OID Provider in WebLogic Domain.....	41
Clustered Installations – Pre-Installation Steps .....	48
Expand the SIM Application Distribution.....	49

---

Loading SIM LDIFs into the OID.....	50
Set the LANG Environment Variable.....	50
Set the Environment Variables for the SIM Installer.....	50
Run the SIM Application Installer.....	51
Clustered Installations – Post-Installation Steps.....	52
SIM Database Authentication Provider set up (to be done after the application deploy).....	52
Review and/or Configure Oracle Single Sign-On.....	55
Create the SIM SSO provider in the SIMDomain.....	55
SIM Batch Scripts.....	58
Resolving Errors Encountered During Application Installation.....	58
Web Help Files.....	58
Starting and Stopping the Wavelink Server.....	58
<b>6 Test the SIM Application.....</b>	<b>61</b>
<b>A Appendix: SIM Database Schema Installer Screens.....</b>	<b>63</b>
<b>B Appendix: SIM Application WebLogic Server Installer Screens.....</b>	<b>71</b>
<b>C Appendix: Common Installation Errors.....</b>	<b>125</b>
EJB Deployment Errors during Installation to WebLogic.....	125
Output Freezes during Text Mode Installation to WebLogic.....	125
Database Installer Hangs on Startup.....	126
Warning: Could not create system preferences directory.....	126
Warning: Couldn't find X Input Context.....	126
ConcurrentModificationException in Installer GUI.....	127
A Second Login Screen Appears After Single Sign-On Login.....	127
Error Connecting to Database URL.....	128
GUI screens fail to open when running Installer.....	128
Log in fails with invalid username/password or user unauthorized errors.....	128
<b>D Appendix: Setting up SIM Reports/Tickets in BI Publisher.....</b>	<b>129</b>
BiPublisher 11g – BI Server Component Installation Tasks.....	129
BiPublisher 11g only - Installation Process Overview.....	129
BiPublisher 11g only – Install Oracle BI EE 11g.....	130
Post Install Steps.....	145
Installing the SIM BI Publisher Templates.....	149
Create the User and Role Required for the SIM Application to Run Reports.....	149
Configuring the BIP-SIM-DATASOURCE JDBC connection.....	156
Configuring SIM for CUPS printers using BiPublisher 11g.....	161
<b>E Appendix: Single Sign-On for WebLogic.....</b>	<b>163</b>
What Do I Need for Single Sign-On?.....	163
Can Oracle Access Manager Work with Other SSO Implementations?.....	163
Oracle Single Sign-on Terms and Definitions.....	164
What Single Sign-On is not.....	165
How Oracle Single Sign-On Works.....	165

---

Installation Overview .....	167
User Management.....	167
<b>F Appendix: Setting Up Password Stores with wallets/credential stores.....</b>	<b>169</b>
About Database Password Stores and Oracle Wallet .....	169
Setting Up Password Stores for Database User Accounts.....	170
Setting up Wallets for Database User Accounts .....	171
For RMS, RWMS, RPM Batch using sqlplus or sqlldr, RETL, RMS, RWMS, and ARI .....	171
Setting up RETL Wallets .....	173
For Java Applications (SIM, ReIM, RPM, RIB, AIP, Alloc, ReSA, RETL).....	174
How does the Wallet Relate to the Application? .....	177
How does the Wallet Relate to Java Batch Program use?.....	177
Database Credential Store Administration.....	177
Managing Credentials with WSLT/OPSS Scripts .....	179
listCred .....	180
updateCred .....	181
createCred .....	182
deleteCred.....	182
modifyBootStrapCredential .....	182
addBootStrapCredential .....	184
Quick Guide for Retail Password Stores (db wallet, java wallet, DB credential stores) .....	185
<b>G Appendix: Tablespace Creation .....</b>	<b>195</b>
Non-Encrypted Tablespace Creation .....	195
Encrypted Tablespace Creation .....	195
Configure a Wallet.....	195
Encryption at Tablespace Level .....	196
<b>H Appendix: Database Parameter File .....</b>	<b>199</b>
<b>I Appendix: Installation Order .....</b>	<b>201</b>
Enterprise Installation Order.....	201



---

---

# Send Us Your Comments

Oracle Retail Store Inventory Management, Installation Guide, Release 15.0.1

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

Are the implementation steps correct and complete?

Did you understand the context of the procedures?

Did you find any errors in the information?

Does the structure of the information help you with your tasks?

Do you need different information or graphics? If so, where, and in what format?

Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

---

**Note:** Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

---

Send your comments to us using the electronic mail address: [retail-doc\\_us@oracle.com](mailto:retail-doc_us@oracle.com)

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at [www.oracle.com](http://www.oracle.com).



---

---

# Preface

Oracle Retail Installation Guides contain the requirements and procedures that are necessary for the retailer to install Oracle Retail products.

## Audience

This Installation Guide is written for the following audiences:

- Database administrators (DBA)
- System analysts and designers
- Integrators and implementation staff

## Related Documents

For more information, see the following documents in the Oracle Retail Store Inventory Management Release 15.0.1 documentation set:

*Oracle Retail Store Inventory Management Release Notes*

*Oracle Retail Store Inventory Management User Guide*

*Oracle Retail Store Inventory Management Implementation Guides*

*Oracle Retail Store Inventory Management Operations Guide*

*Oracle Retail Store Inventory Management Security Guide*

*Oracle Retail Store Inventory Management Data Model*

## Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

Product version and program/module name

Functional and technical description of the problem (include business impact)

Detailed step-by-step instructions to re-create

Exact error message received

Screen shots of each step you take

## Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 15.0) or a later patch release (for example, 15.0.1). If you are installing the base release or additional patch releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch releases can contain critical information related to the base release, as well as information about code changes since the base release.

## Improved Process for Oracle Retail Documentation Corrections

To more quickly address critical corrections to Oracle Retail documentation content, Oracle Retail documentation may be republished whenever a critical correction is needed. For critical corrections, the republication of an Oracle Retail document may at times **not** be attached to a numbered software release; instead, the Oracle Retail document will simply be replaced on the Oracle Technology Network Web site, or, in the case of Data Models, to the applicable My Oracle Support Documentation container where they reside.

This process will prevent delays in making critical corrections available to customers. For the customer, it means that before you begin installation, you must verify that you have the most recent version of the Oracle Retail documentation set. Oracle Retail documentation is available on the Oracle Technology Network at the following URL:

<http://www.oracle.com/technetwork/documentation/oracle-retail-100266.html>

An updated version of the applicable Oracle Retail document is indicated by Oracle part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of a document with part number E123456-01.

If a more recent version of a document is available, that version supersedes all previous versions.

## Oracle Retail Documentation on the Oracle Technology Network

Oracle Retail product documentation is available on the following web site:

<http://www.oracle.com/technetwork/documentation/oracle-retail-100266.html>

(Data Model documents are not available through Oracle Technology Network. You can obtain them through My Oracle Support.)

## Conventions

**Navigate:** This is a navigate statement. It tells you how to get to the start of the procedure and ends with a screen shot of the starting point and the statement “the Window Name window opens.”

This is a code sample

It is used to display examples of code

---

---

# Preinstallation Tasks

This chapter discusses the tasks to complete before installation.

---

---

**Note:** Oracle Retail assumes that the retailer has applied all required fixes for supported compatible technologies.

---

---

## Implementation Capacity Planning

There is significant complexity involved in the deployment of Oracle Retail applications, and capacity planning is site specific. Oracle Retail strongly suggests that before installation or implementation you engage your integrator (such as the Oracle Retail Consulting team) and hardware vendor to request a disk sizing and capacity planning effort.

Sizing estimates are based on a number of factors, including the following:

- Workload and peak concurrent users and batch transactions
- Hardware configuration and parameters
- Data scarcity
- Application features utilized
- Length of time history is retained

Additional considerations during this process include your high availability needs as well as your backup and recovery methods.

## Check Supported Database Server Requirements

General Requirements for a database server running SIM include:

Supported On	Versions Supported
Database Server OS	<p>OS certified with Oracle Database 12cR1 Enterprise Edition. Options are:</p> <ul style="list-style-type: none"> <li>▪ Oracle Linux 6 and 7 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ Red Hat Enterprise Linux 6 and 7 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ AIX 7.1 (Actual hardware or LPARs)</li> <li>▪ Solaris 11 SPARC (Actual hardware or logical domains)</li> <li>▪ HP-UX 11.31 Integrity (Actual hardware, HPVM, or vPars)</li> </ul>
Database Server 12cR1	<p>Oracle Database Enterprise Edition 12cR1 (12.1.0.2) with the following specifications:</p> <p><b>Components:</b></p> <ul style="list-style-type: none"> <li>▪ Oracle Partitioning</li> <li>▪ Examples CD</li> </ul> <p><b>Oneoffs:</b></p> <ul style="list-style-type: none"> <li>▪ 20846438: ORA-600 [KKPAPXFORMFKK2KEY_1] WITH LIST PARTITION</li> <li>▪ 19623450: MISSING JAVA CLASSES AFTER UPGRADE TO JDK 7</li> <li>▪ 20406840: PROC 12.1.0.2 THROWS ORA-600 [17998] WHEN PRECOMPILING BY 'OTHER' USER</li> <li>▪ 20925154: ORA-39126: WORKER UNEXPECTED FATAL ERROR IN KUPW\$WORKER GATHER_PARSE_ITEMS JAVA</li> </ul> <p><b>RAC only:</b></p> <ul style="list-style-type: none"> <li>▪ 21260431: APPSST 12C : GETTING ORA-4031 AFTER 12C UPGRADE</li> <li>▪ 21373473: INSTANCE TERMINATED AS LMD0 AND LMD2 HUNG FOR MORE THAN 70 SECS</li> </ul> <p><b>Other components:</b></p> <ul style="list-style-type: none"> <li>▪ Perl interpreter 5.0 or later</li> <li>▪ X-Windows interface</li> <li>▪ JDK 1.7</li> </ul>

---

**Note:** By default, JDK is at 1.6. After installing the 12.1.0.2 binary, apply patch 19623450. Follow the instructions on Oracle Database Java Developer's Guide 12c Release 1 to upgrade JDK to 1.7. The Guide is available at: <http://docs.oracle.com/database/121/JJDEV/chone.htm#JJDEV01000>.

---

Follow-through to complete the post-patch operation.

---

## Check Supported Application Server Requirements

The SIM application must be deployed on Oracle WebLogic 12c (12.1.3) with ADF.

**Note:** SIM is certified to work with only Oracle Internet Directory LDAP server (OID), as specified in the Application Server Requirements section of the SIM Installation Guide. The sample, unsupported .ldif files that SIM includes are provided only as reference.

General requirements for an Oracle WebLogic Server capable of running the SIM application include the following.

Supported on:	Versions Supported:
Application Server OS	OS certified with Oracle Fusion Middleware 12.1.3 Options are: <ul style="list-style-type: none"> <li>▪ Oracle Linux 6 and 7 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ Red Hat Enterprise Linux 6 and 7 for x86-64 (Actual hardware or Oracle virtual machine).</li> <li>▪ AIX 7.1 (Actual hardware or LPARs)</li> <li>▪ Solaris 11.2 SPARC (Actual hardware or logical domains)</li> <li>▪ HP-UX 11.31 Integrity (Actual hardware, HPVM, or vPars)</li> </ul>
Application Server	Oracle Fusion Middleware 12.1.3 <b>Components:</b> <ul style="list-style-type: none"> <li>▪ FMW 12.1.3 Infrastructure (WLS and ADF included)</li> <li>▪ Oracle Identity Management 11g Release 1 (11.1.1.9)</li> <li>▪ Oracle Enterprise Manager 12.1.3</li> </ul> <b>Note:</b> Oracle Internet Directory (OID) is the supported LDAP directory for Oracle Retail products. For alternate LDAP directories, refer to Oracle WebLogic documentation set. <b>Java:</b> <ul style="list-style-type: none"> <li>▪ JDK 1.7+ 64 bit</li> </ul> <b>Optional (required for running reports)</b> <ul style="list-style-type: none"> <li>▪ BI Publisher 11.1.1.9</li> </ul> <b>Optional (required for SSO)</b> <ul style="list-style-type: none"> <li>• Oracle WebTier 11g (11.1.1.9)</li> <li>• Oracle Access Manager 11g Release 2 (11.1.2.3)</li> </ul> <b>Note:</b> A separate WebLogic 10.3.6 installation is required for Oracle Access Manager 11.1.2.3 <ul style="list-style-type: none"> <li>• Oracle Access Manager Agent (WebGate) 11g Release 2 (11.1.2.3)</li> </ul>

## Check Single Sign-On Requirements

If SIM is not being deployed in a Single Sign-On environment, skip this section.

If Single Sign-On is to be used, verify the Oracle Identity Management 11gR1 version 11.1.1.9 has been installed along with the components listed in the above Application Server requirements section. Verify the Oracle WebTier Server is registered with the Oracle Access Manager 11gR2 as a partner application.

## Check Directory Server Requirements

SIM uses directory server based user authentication and searching. For LDAP, SIM is supported with the following directory servers:

- Oracle Identity Management 11gR1 version 11.1.1.9

## Check Third-Party Software Dependencies

- Oracle Retail Wireless Foundation Server, provided by Wavelink 5.x.

## Check Client PC and Web Browser Requirements

Requirement	Versions
Operating system	Windows 7 or 8
Oracle (Sun) Java Runtime Environment (JRE)	Java 7+
Browser	Microsoft Internet Explorer 11 Mozilla Firefox ESR 38 Chrome 40+ The browser is used to launch the Java WebStart client.

---

**Note:** Oracle Retail does not recommend or support installations with less than 128 kb bandwidth available between the PC client and the data center. Limiting the client to less than 128 kb total available bandwidth causes unpredictable network utilization spikes, and performance of the client degrades below requirements established for the product. The 128 kb requirement provides reasonable, predictable performance and network utilization.

---

## Supported Oracle Retail Products

The following Oracle Retail products can be integrated with SIM. Next to each product is an indication of whether it is required or optional for SIM to function properly:

- Retail Integration Bus (RIB) 15.0.1 and all subsequent patches and hot fixes – Required

Although typically used to integrate SIM with RMS, RIB can also be used to integrate SIM with other merchandising systems.

---

**Note:** RIB requires custom modifications to use a merchandising system other than RMS.

---

- Retail Merchandising System (RMS) 15.0.1 – Optional
- Oracle Retail Price Management 15.0.1 – Optional
- Oracle Retail Xstore Suite 15.0.1 – Optional

---

**Note:** If integrating with Xstore Point of Service, SSL must be enabled for the SIM Webservices.

---

- Oracle Retail POS Suite 14.1.x – Optional

The above products can be installed before or after SIM. However, it is helpful to know the connection details for the other products ahead of time so that you can provide them to the SIM application installer, which will configure the connection points for you.

## UNIX User Account Privileges to Install the Software

A UNIX user account is needed to install the software. The UNIX user that is used to install the software should have write access to the WebLogic server installation files.

For example, “oretail.”

---

**Note:** Installation steps will fail when trying to modify files under the WebLogic installation unless the user has write access.

---

## SIM Installation Overview

The following basic steps are required to install and set up SIM for the first time.

1. Install the database (with or without RAC).
2. Install application server (WebLogic) if it has not been installed
3. Install the SIM database schema
4. Set role-based access control. See Chapter 3 of the *Oracle Retail Store Inventory Management Implementation Guide, Volume 1* for instructions.
5. Install the SIM application.
6. Run data-seeding from RMS (Applicable only if SIM integrate with RMS)



---

---

## RAC and Clustering

The Oracle Retail Store inventory Management System has been validated to run in two configurations on Linux:

- Standalone Oracle Application Server or Web Logic Server and Database installations
- Real Application Cluster Database and Oracle Application Server or Web Logic Server Clustering

The Oracle Retail products have been validated against a 12.1.0.2 RAC database. When using a RAC database, all JDBC connections should be configured to use THIN connections rather than OCI connections.

Clustering for Web Logic Server 12c is managed as an Active-Active cluster accessed through a Load Balancer. Validation has been completed utilizing a RAC 12.1.0.2 Oracle Internet Directory database with the Web Logic 12c cluster. It is suggested that a Web Tier 11.1.1.9 installation be configured to reflect all application server installations if SSO will be utilized.

### References for Configuration:

- Oracle® Fusion Middleware High Availability Guide 11g Release 1 (11.1.1) Part Number E10106-09
- Oracle Real Application Clusters Administration and Deployment Guide 12c Release 1 (12.1) E48838-10



---

---

## Database Installation Tasks

This chapter describes the tasks required for a full database installation.

---

---

**Note:** If the SIM 15.0 software is already installed, please see “**Database Installation Tasks – Upgrade**” for information on Upgrading to SIM 15.0.1.

---

---

### Expand the SIM Database Schema Installer Distribution

1. Log in to the UNIX server as a user which has sufficient access to run sqlplus from the Oracle Database installation.
2. Create a new staging directory for the SIM database schema installer distribution (sim15-dbschema.zip). There should be a minimum of 50 MB disk space available for the database schema installation files. This location is referred to as `INSTALL_DIR` for the remainder of this chapter.
3. Copy `sim15-dbschema.zip` to `<INSTALL_DIR>` and extract its contents.

### Required Database Character Set

SIM 15.0.1 databases should be created with the AL32UTF8 database character set. This will ensure support for characters of all languages supported by SIM and ensure proper integration with other Oracle Retail applications.

## Required Tablespaces

Before you run the SIM database schema installer, make sure that the required tablespaces have been created in the database. As of Release 15, SIM has its own dedicated tablespaces. They are: SIM\_DATA, SIM\_INDEX, SIM\_LOB\_DATA, SIM\_LOB\_INDEX, SIM\_ENCRYPTED\_DATA, and SIM\_ENCRYPTED\_INDEX. The SIM\_ENCRYPTED\_DATA and SIM\_ENCRYPTED\_INDEX tablespaces hold data which may include Personally Identifiable Information data (PII Data). If you hold the Advanced Security Option license, you can choose to create these two tablespaces with TDE tablespace encryption to protect the PII data. If you do not hold an Advanced Security Option license, you can create the tablespaces as normal tablespaces, but with no encryption. The tablespace names must always be SIM\_ENCRYPTED\_DATA and SIM\_ENCRYPTED\_INDEX regardless of whether TDE encryption is used, because the table and index creation scripts look for these specific names.

1. Modify the paths of the script `<INSTALL_DIR>/sim/dbschema/dbutils/create_tablespaces.sql`. The table below shows the default initial sizes:

TABLESPACE_NAME	Size
SIM_ENCRYPTED_INDEX	12G
SIM_ENCRYPTED_DATA	10G
SIM_INDEX	10G
SIM_DATA	8G
SIM_LOB_DATA	2G
SIM_LOB_INDEX	2G
USERS	2G

2. Once the script has been modified, execute it in SQL\*Plus as sys.
  - For Example: `SQL> @ create_tablespaces.sql`
3. Review `create_tablespaces.log` for errors and correct as needed.
4. If you do not wish to use TDE tablespace encryption, follow below steps; else for TDE encryption skip to step 5.
  - a. Modify the paths of the script `<INSTALL_DIR>/sim/dbschema/dbutils/create_encrypted_tablespaces_no_TDE.sql` as per your environment.
  - b. Run the script using SQL\*Plus as sys.
  - c. Review `Create_encrypted_tablespaces_no_TDE.log` for errors and correct as needed.
5. If you hold an Advanced Security Option license and wish to use TDE tablespace encryption
  - a. Modify the paths of the script `<INSTALL_DIR>/sim/dbschema/dbutils/create_encrypted_tablespaces_TDE.sql` as per your environment.
  - b. Run the script using SQL\*Plus as sys.
  - c. Review `Create_encrypted_tablespaces_TDE.log` for errors and correct as needed.
  - d. Refer to [Appendix: Tablespace Creation](#) for details about how to create tablespaces in an encrypted format.

## Create the SIM Database User

The user in the database which will own the SIM tables must be created prior to running the SIM database schema installer and also create additional db users.

---

**Note:** The below user creation scripts take three arguments on the command line in sqlplus: username, password, and temporary tablespace.

---

1. Change the directory to <INSTALL\_DIR>/sim/dbschema/dbutils/
2. Create a directory "log" for user creation spool files  
`mkdir log`
3. Create roles required for additional users.  
`SQL> @create_roles.sql`
4. A `create_user_sim_owner.sql` script has been provided that can be used for creating SIM database schema owner:  
`@create_user_sim_owner.sql`  
Example username : sim01
5. Create additional db users : In addition to SIM database Schema owner, SIM will also have six required database users as application data source users to connect to SIM databases:  
`SQL>@create_user_sim_admin.sql`  
Example username: sim01\_admin  
  
`SQL> @create_user_sim_rib.sql`  
Example username: sim01\_rib  
  
`SQL>@create_user_sim_business.sql`  
Example username: sim01\_business  
  
`SQL> @create_user_sim_business_viewer.sql`  
Example username: sim01\_business\_viewer  
  
`SQL> @create_user_sim_mps.sql`  
Example username: sim01\_mps  
  
`SQL> @create_user_sim_security.sql`  
Example username: sim01\_security

## Run the SIM Database Schema Installer

This installer installs the SIM database schema, compile SIM objects, insert SIM data, and produce the `dba_create_directory.sql` script.

1. Set the following environment variables:
  - Set the `ORACLE_HOME` to point to an installation that contains `sqlplus`. It is recommended that this be the `ORACLE_HOME` of the SIM database.
  - Set the `PATH` to: `$ORACLE_HOME/bin:$PATH`
  - Set the `ORACLE_SID` to the name of your database
  - Set the `NLS_LANG` for proper locale and character encoding

**Example:** `NLS_LANG=AMERICAN_AMERICA.AL32UTF8`

2. If you are using an X server such as Xceed, set the `DISPLAY` environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset `DISPLAY` for text mode.
3. Run the `install.sh` script. This launches the installer. After installation is completed, a detailed installation log file is created: `<INSTALL_DIR>/sim/dbschema/logs/sim-install-db.<timestamp>.log`.

**Note:** Appendix A contains details on every screen and field in the database schema installer.

4. When the installer finishes it prints the values of the database SID and database schema user. Note these values as they are needed later when you run the SIM application installer.
5. The SIM database schema installer will produce a `dba_create_directory.sql` script which must be reviewed by a DBA and then run on the database server in order to complete the installation.

## Grant Privileges for the Roles

Change the directory to `<INSTALL_DIR>/sim/dbschema/dbscripts/util`

```
sqlplus sim01/<password>@<          sim_db_name >  
SQL> @grant_sim_role_privs.sql <schema owner>
```

For example:

```
SQL> @grant_sim_role_privs.sql sim01
```

## Resolving Errors Encountered During Database Schema Installation

If the database schema installer encounters any errors, it halts execution immediately and prints to the screen which SQL script it was running when the error occurred. It also writes the path to this script to the `.dberrors` file. When this happens, you must run that particular script using `sqlplus`. After you are able to complete execution of the script, delete the `.dberrors` file and run the installer again. You can run the installer in silent mode so that you do not have to retype the settings for your environment. See Appendix D of this document for instructions on silent mode.

See Appendix F of this document for a list of common installation errors.

Subsequent executions of the installer will skip the SQL scripts which have already been executed in previous installer runs. This is possible because the installer maintains a

**.dbhistory** file with a listing of the SQL scripts that have been run. If you have dropped the SIM schema and want to start with a clean install, you can delete the **.dbhistory** file so that the installer runs through all of the scripts again. It is recommended that you allow the installer to skip the files that it has already run.

## Running Data Seeding

After full fresh install SIM database schema and SIM application installation tasks completed, store foundation data must be seeded into SIM before user can login to SIM application.

(For migrating SIM from previous release, see “*Oracle Retail Store Inventory Management Implementation Guide*” for details).

The data seeding process seeds store foundation data from RMS into SIM.

See the “Data Seeding” section of the “*Oracle Retail Store Inventory Management Implementation Guide, Volume 1*” for additional data seeding details.

The SIM database installer extracts the data seeding scripts from the *sim-database-data-seeding.zip* to the following location:

STAGING\_DIR/sim/dbschema/data\_seeding

This folder is referred to as DATA\_SEEDING\_DIR for the remainder of this chapter.

### Third-Party Software Dependencies

SIM data seeding requires groovy jar file to be installed and Groovy 2.4.5 from <http://groovy.codehaus.org> is already included under the DATA\_SEEDING\_DIR/lib folder.

Set the following environment variables:

- Set ORACLE\_SID to the name of SIM database.

Example:

```
export ORACLE_SID=<SIM_DB_NAME>
```

- Set the ORACLE\_HOME. It is recommended that this be the ORACLE\_HOME of the SIM database.

Example:

```
export ORACLE_HOME=/u00/oracle/product/12.1.0.2
```

- Set JAVA\_HOME

Example:

```
export JAVA_HOME= /path/java1.7+_64bit
```

Set NLS\_LANG

Example:

```
export NLS_LANG=AMERICAN_AMERICA.AL32UTF8
```

- Set the PATH to: \$ORACLE\_HOME/bin:

Example:

```
export PATH=$ORACLE_HOME/bin:$JAVA_HOME/bin:$PATH
```

1. Verify the directory and the file permissions:

The recommended permissions for data seeding directories are 775 (rwxrwxr-x).

2. View Data Seeding Options:

Change to <DATA\_SEEDING\_DIR>/bin directory:

```
startDataSeedCli.sh -h
```

3. Start Data Seeding Process:

The data seeding provides the following execution options. Please run the script with 1-6 consecutively as shown below.

**Note:** It is highly recommended to back up the SIM database before executing the data seeding scripts.

It is recommended to verify export log files before starting importing process.

- Set Up  
startDataSeedCli.sh -a 1 -s <simDBServer> -p <port> -d <simDB>
- Export Foundation Data  
startDataSeedCli.sh -a 2 -s <rmsDBServer> -p <port> -d <rmsDB>
- Export Store Data  
startDataSeedCli.sh -a 3 -s <rmsDBServer > -p <port> -d <rmsDB>
- Import Foundation Data  
startDataSeedCli.sh -a 4 -s <simDBServer> -p <port> -d <simDB>
- Import Store Data  
startDataSeedCli.sh -a 5 -s <simDBServer> -p <port> -d <simDB>
- Cleanup  
startDataSeedCli.sh -a 6 -s <simDBServer> -p <port> -d <simDB>

#### 4. Check data seeding logs:

The data seeding process writes master log files into <DATA\_SEEDING\_DIR>/log directory.

Please check following the master log files:

- export\_foundation.log
- export\_store.log
- import\_foundation.log
- import\_store.log
- data\_seed\_common.log

The master log files may have references to sub-process log files:

- <DATA\_SEEDING\_DIR>/export/foundation/log
- <DATA\_SEEDING\_DIR>/export/store/log
- <DATA\_SEEDING\_DIR>/import/foundation/log
- <DATA\_SEEDING\_DIR>/import/store/log

#### 5. Verify the seeding results files.

The verification files are located at directory <DATA\_SEEDING\_DIR>/verify/out :

- verify\_foundation\_data.out
- verify\_store\_data.out
- disabled\_constraints.out

#### 6. After inspecting the result files, resolve the problematic data. A database administrator will need to manually enable the disabled constraints which are reported.

#### 7. After data seeding is finished and you are convinced that your data was correctly seeded, you can remove all data seeding files from <DATA\_SEEDING\_DIR>

---

---

## Database Installation Tasks – Upgrade

### Upgrading SIM

SIM 15.0.1 is a patch installation from 15.0. If SIM 15.0 is already installed, it is possible to do a patch install from 15.0 to 15.0.1.

Follow the below steps for Patch Installation Steps:

1. Change the directory to <INSTALL\_DIR>/sim/dbschema
2. Create a directory sim-database-delta, and copy sim-database-delta.zip to sim-database-delta
3. Change the directory to <INSTALL\_DIR>/sim/dbschema/sim-database-delta and unzip sim-database-delta.zip
4. Refer readme.txt for Patch Installation Steps



---

---

## Application Installation Tasks

Before proceeding, you must install Oracle WebLogic Server 12c with ADF and any patches listed in the Chapter 1 of this document. The Oracle Retail Store Inventory Management application is deployed to a WebLogic Managed server within the WebLogic installation. It is assumed Oracle Database has already been configured and loaded with the appropriate Store Inventory Management schemas for your installation. Installing a separate domain is mandated. It can be called "SIMDomain" (or something similar) and will be used to install the managed servers. The ADF libraries should be extended to this domain and the Enterprise Manager application should be deployed.

---

---

**Note:** If this domain is to be setup in a secure mode. Please set up weblogic as SSL and refer to ORACLE Retail Merchandising Security Guide for details on all items to change to be in secure mode. This would best be done before domain and application install. The domain example below is for unsecured setup.

---

---

### Create the Domain with ADF Libraries and Enterprise Manager

Create a directory to install the WebLogic (this will be the MW\_HOME):

Example: `mkdir -p /u00/webadmin/products/wls_retail`

1. Set the MW\_HOME, JAVA\_HOME, and DOMAIN\_HOME environment variables:
  - MW\_HOME should point to your WebLogic installation.
  - JAVA\_HOME should point to the Java JDK 1.7+. This is typically the same JDK which is being used by the WebLogic domain where application is getting installed.
  - DOMAIN\_HOME should point to the full path of the domain into which application will be installed.

Example:

```
$ export MW_HOME=/u00/webadmin/products/wls_retail
$ export DOMAIN_HOME=/u00/webadmin/config/domains/wls_retail/APPNAMEDomain
$ export JAVA_HOME=/u00/webadmin/products/jdk_java
(This should point to the Java which is installed on your server)
$ export PATH=$JAVA_HOME/bin:$PATH
```

Going forward we will use the above references for further installations.

2. Set the system environment variable MW\_HOME to the new directory then cd to location where the jar is downloaded and run the installer using the following command:

```
java -jar ./fmw_12.1.3.0.0_infrastructure.jar
```


3. Welcome screen appears. Click **Next**.




4. Enter the following and click **Next**.  
Oracle home: <Path to the middleware home>

Example:


/u00/webadmin/products/wls\_retail




5. Select install type 'Fusion Middleware Infrastructure'. Click **Next**.




This screen will verify that the system meets the minimum necessary requirements.




6. Click Next.



7. If you already have an Oracle Support account, use this screen to indicate how you would like to receive security updates.
8. If you do not have one or if you want to skip this step, clear the check box and verify your selection in the follow-up dialog box.
9. Click Next.





10. Click Next.




11. Click Next.

12. Click Yes, if you wish to remain uninformed of security issues in your configuration.






10. Click Next.



11. Click Finish.



12. Continue with RCU installation.

## Install RCU Database Schemas

The RCU database schemas are required for the installation of retail application and configuration of domain.

---

**Note:** You need 'SYS' user privileges to install the RCU database schemas.


---

The following steps are provided for the creation of the database schemas:

1. Navigate to the directory into which RCU is installed. For example:

```
<MW_HOME>/oracle_common/bin/  
Run ". /rcu"
```

2. Click **Next**.




3. Select Create Repository and System Load and Product Load. Click Next.




4. Enter database connection details:

- Database Type: Oracle Database
- Host Name: dbhostname.us.oracle.com
- Port: 1521
- Service Name: dbservicename
- Username: sys
- Password: <syspassword>
- Role: SYSDBA



5. Click **Next**. The Installer checks prerequisites.
6. When the prerequisite checks are complete, click **OK**. Click **Next**.





7. Click the **Create a new prefix** option, the prefix name for your schemas should be unique to your application environment.  
Example: ReIM, ALLOC, ReSA, etc
8. Select the components to create:
  - Meta Data Services Oracle Platform Security Services

**Note:** Once OPSS schema is selected, the following dependent schemas will get selected automatically.

- Audit Services
- Audit Services Append
- Audit Services Viewer

**Note:** STB schema will be already selected as part of the Common Infrastructure component.



9. Select Use same passwords for all schemas.
10. Enter your password.


**Note:** This password is needed at the time of ADF domain creation.

Component	Schema Owner	Default Tablespace	Temp Tablespace
Metadata Services	APPNAME_MDS	*APPNAME_MDS	*APPNAME_IAS_TEMP
Audit Services	APPNAME_IAU	*APPNAME_IAS_IAU	*APPNAME_IAS_TEMP
Audit Services Append	APPNAME_IAU_APP...	*APPNAME_IAS_IAU	*APPNAME_IAS_TEMP
Audit Services Viewer	APPNAME_IAU_VIE...	*APPNAME_IAS_IAU	*APPNAME_IAS_TEMP
Oracle Platform Secu...	APPNAME_OPSS	*APPNAME_IAS_OPSS	*APPNAME_IAS_TEMP
Common Infrastructu...	APPNAME_STB	*APPNAME_STB	*APPNAME_IAS_TEMP

11. Click Next. A Repository Creation notification will appear. Click OK.



12. Tablespaces are created, and the progress will be displayed in a pop-up notification. When the operation is completed, click **OK**.



13. Click **Create**. The schema is created.





## Create a New ADF Domain (with managed server and EM)

To create a new domain and managed server with ADF libraries and EM, follow the below steps:

1. Set the environment variables:

```
export JAVA_HOME=<JDK_HOME>
(Example: /u00/webadmin/products/jdk_java) [JDK_HOME is the location where
jdk has been installed)
export PATH=$JAVA_HOME/bin:$PATH
export ORACLE_HOME=<MW_HOME>/oracle_common
(Example: /u00/webadmin/products/wls_retail/oracle_common)

cd $MW_HOME/oracle_common/common/bin
(MW_HOME is the location where Weblogic has been installed.)
```

2. Run the following command:

```
./config.sh
```

3. Select **Create a new domain**.

Domain location: Specify the path to the <DOMAIN\_HOME>  
Example: /u00/webadmin/config/domains/wls\_retail/APPNAMEDomain

4. Click **Next**.



5. Select **Create Domain Using Product Templates**.

6. Check the following components:

Oracle Enterprise Manager

---


**Note:** When Oracle Enterprise Manager component is selected, the following dependent components are selected automatically:

Oracle JRF

Weblogic Coherence Cluster Extension

---

7. Click Next.




Application location: Application directory location. Example:  
/u00/webadmin/config/applications/wls\_retail/APPNAMEDomain

8. Click Next.




9. Provide the WebLogic administrator credentials and click Next:

- Username: weblogic
- Password: <Password>




10. Select Domain Mode as Production and the JDK to use (as applicable) and click Next.




#### 11. Select RCU Data.


- Vendor: Oracle
- Drive: Use default selection (Oracle driver thin for service connections)
- DBMS/Service: dbservicename
- Host Name: dbhostname.us.oracle.com
- Port: 1521
- Schema Owner: APPNAME\_STB (Example: ALLOC\_STB, ReSA\_STB, etc)
- Password: <Password>. This password which was used for RCU schema creation.




12. Click the **Get RCU Configuration** button.



13. Click **Next**.



14. Click **Next** and it will test to make sure it can connect to your datasources.



15. Click **Next** to continue

16. Select advanced configuration for:


- Administration Server
- Node manager
- Managed Servers, Clusters and Coherence



17. Configure the Administration Server:


- Server Name: <APP name>\_AdminServer

- Listen address: Appserver Hostname or IPAddress of the Appserver Host.
- Listen port: <Port for Admin Server> Note: The port used here must be a free port.
- Server Groups: Unspecified



### 18. Configure Node Manager:


- Node manager type: Per domain default location
- Username: weblogic
- Password: <Password for weblogic>




19. Configure Managed Servers with the ADF template.

20. Click the **Add** button.


- Server Name: <appname-server>
- Listen address: Appserver Hostname or IPAddress of the Appserver Host
- Listen port: <Port for Managed Server> Note: The port used here must be a free port.
- Server Groups: JRF-MAN-SVR



21. Skip Configure Clusters and click **Next**.




22. No change needed. Click **Next**.




23. Click the Unix Machine tab.

24. Click the **Add** button, configure the machine, and click **Next**.


- Name: apphostname\_MACHINE
- Listen address: apphostname or IPAddress
- Listen port: <Port for node manager> Note: The port used here must be a free port.




25. Assign the configured Admin server and managed servers to the new machine and click **Next**.



26. Click Create.






27. Click Next.



28. When the process completes, click Finish.



29. Start the nodemanager from <DOMAIN\_HOME>/bin using the following:
 

```
./startNodeManager.sh
```
30. Start the WebLogic Domain (Admin Server) from <DOMAIN\_HOME>/bin using the following:
 

```
./startWebLogic.sh
```
31. You may configure boot.properties for starting the Weblogic domain without prompting to username and password:
 

Create the security folder at:

```
<DOMAIN_HOME>/servers/<AdminServer>/
```

Create the boot.properties file under:

```
<DOMAIN_HOME>/servers/<AdminServer>/security
```

The file 'boot.properties' should have the following:

```
-----
username=weblogic
password=<password>
-----
```

In the above, the password value is the password of WebLogic domain which is given at the time of domain creation.
32. Save the boot.properties file and restart the WebLogic server.
33. Start the Managed server from the Admin Console.

## Configuration of OID Provider in WebLogic Domain


---

**Note:** In this section, the base DN "dn=us,dn=oracle,dn=com" is used as an example. Modify this value as per the organisation's ldap settings.


---

Perform the following procedure to create providers in the domains created in the previous steps.


1. Log in to the Administration Console.  
<http://<host>:<port>/console/>
1. In the Domain Structure frame, click **Security Realms**.
2. In the Realms table, click myrealm. The Settings for myrealm page is displayed.
3. Click the **Providers** tab.




4. Click **Lock & Edit** and then click **New**. The 'Create a New Authentication Provider' page is displayed.




5. Enter **OIDAuthenticator** in the Name field and select **OracleInternetDirectoryAuthenticator** as the type. Click **OK**.



6. All the providers are displayed. Click **OIDAuthenticator**. Settings of OIDAuthenticator are displayed.



7. Set the Control Flag field to SUFFICIENT and click **Save**.
8. From the Providers tab, click on DefaultAuthenticator -> Configuration tab -> Common tab. Update the Control Flag to SUFFICIENT.
9. Click **Save**.



10. From the Providers tab, click the “OIDAuthenticator” (you just created), in the configuration -> Provider Specific tab enter your LDAP connection details:  
The values shown below are examples only. You should match the entries to your OID.
  - Host: <oidhost>
  - Port: <oidport>
  - Principal: cn=orcladmin
  - Credential: <password>
  - Confirm Credential: <password>
  - User Base DN: cn=users,dc=us,dc=oracle,dc=com
  - Check ‘Use Retrieved User Name as Principal.’
  - Check ‘SSL Enabled’ if the OID is SSL enabled. Port mentioned above must be an SSL port if OID is enabled.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Settings for OIDAuthenticator" and is divided into "Configuration" and "Performance" tabs. The "Configuration" tab is active, and the "Provider Specific" sub-tab is selected. The configuration includes fields for Host (idmhost.us.oracle.com), Port (3060), Principal (cn=orcladmin), Credential (masked), and Confirm Credential (masked). There is also a checkbox for "SSLEnabled". Below these are sections for "Users" and "Groups" with LDAP search filters. The "Users" section includes "User Base DN" (cn=Users,dc=us,dc=oracle,d) and "All Users Filter" (&(cn=\*)objectclass=person). The "Groups" section includes "Group Base DN" (cn=groups,dc=us,dc=oracle,d), "All Groups Filter" (&(cn=\*)(objectclass=group), "Group From Name Filter" (&(cn=%g)(objectclass=group), "Group Search Scope" (subtree), "Group Membership Searching" (unlimited), and "Max Group Membership Search Level" (0). There is also an "Ignore Duplicate Membership" checkbox.

11. Modify the following:

- Group Base DN: cn=Groups,dc=us,dc=oracle,dc=com

This screenshot shows the "Groups" configuration page. It contains several fields for configuring group search and membership:
 

- Group Base DN:** cn=groups,dc=us,dc=oracle,dc=com
- All Groups Filter:** (&(cn=\*)(objectclass=group)
- Group From Name Filter:** (&(cn=%g)(objectclass=group)
- Group Search Scope:** subtree
- Group Membership Searching:** unlimited
- Max Group Membership Search Level:** 0
- Ignore Duplicate Membership:** (checkbox)

12. Check Propagate Cause For Login Exception

Propagate Cause For Login Exception

Cache Enabled

Cache Size:

Cache TTL:

GUID Attribute:

13. Click **Save**.


14. Click the **Providers** tab in the 'myrealm' security realm.

The screenshot shows the Oracle WebLogic Administration Console interface. On the left, the 'Change Center' and 'Domain Structure' are visible. The main area displays the 'Settings for myrealm' configuration page, with the 'Providers' tab selected. Below the navigation tabs, there is a table of 'Authentication Providers'.

Name	Description	Version
Trust Service Identity Asserter	Trust Service Identity Assertion Provider	1.0
DefaultAuthenticator	WebLogic Authentication Provider	1.0
DefaultIdentityAsserter	WebLogic Identity Assertion provider	1.0
OIDAuthenticator	Provider that performs LDAP authentication	1.0

15. Click **Reorder**.

16. Move **OIDAuthenticator** to the top of the providers list



17. Click OK.

18. Once your changes are saved, click **Activate Changes**.

The screenshot shows the Oracle WebLogic Server Administration Console 12c interface. The main content area is titled "Settings for myrealm" and is under the "Providers" tab. A message box states: "All changes have been activated. However 2 items must be restarted for the changes to take effect." Below this, there is a table of "Authentication Providers".

Name	Description	Version
OIDAuthenticator	Provider that performs LDAP authentication	1.0
Trust Service Identity Asserter	Trust Service Identity Assertion Provider	1.0
DefaultAuthenticator	WebLogic Authentication Provider	1.0
DefaultIdentityAsserter	WebLogic Identity Assertion provider	1.0

19. Restart the WebLogic Adminserver and Managed server

## Clustered Installations – Pre-Installation Steps

Skip this section if you are not clustering the application server.

If SIM is being installed into a clustered environment, the "Cluster Address" field must be set prior to installation. This is set in:

Clusters -> sim-cluster (or name of your cluster) -> configuration (tab) -> general (tab)

Set the address to your cluster in the "Cluster Address" field, e.g.:

orapphost1:7143,orapphost2:7143

Home Log Out Preferences Record Help Welcome, weblogic Connected to: SIMDoma

Home > Summary of Clusters > sim-cluster

Settings for sim-cluster

Configuration Monitoring Control Deployments Services Notes

General JTA Messaging Servers Replication Migration Singleton Services Scheduling Overload Health Monitoring

HTTP Coherence

Save

This page allows you to define the general settings for this cluster.

**Name:** sim-cluster The name of this configuration. WebLogic Server uses an MBean to implement and persist the configuration. [More Info...](#)

**Default Load Algorithm:** round-robin Defines the algorithm to be used for load-balancing between replicated services if none is specified for a particular service. The round-robin algorithm cycles through a list of WebLogic Server instances in order. Weight-based load balancing improves on the round-robin algorithm by taking into account a pre-assigned weight for each server. In random load balancing, requests are routed to servers at random. [More Info...](#)

**Cluster Address:** orapphost7143.orapp! The address that forms a portion of the URL a client uses to connect to this cluster, and that is used for generating EJB handles and entity EJB failover addresses. (This address may be either a DNS host name that maps to multiple IP addresses or a comma-separated list of single address host names or IP addresses.) [More Info...](#)

## Expand the SIM Application Distribution

To expand the SIM application distribution, do the following.

1. Log in to the UNIX server as the user who owns the Web Logic installation. Create a new staging directory for the SIM application distribution (sim15-application.zip). There should be a approximately 1 GB disk space available for the application media and installation files.

This location is referred to as `INSTALL_DIR` for the remainder of this chapter.

2. Copy sim15-application.zip to `<INSTALL_DIR>` and extract its contents.

## Loading SIM LDIFs into the OID

The SIM installation media contains a zip file with a group of template LDIF files. They are in the SIM distribution you previously expanded:

```
<INSTALL_DIR>/sim/application/sim15/ldap/sim-ldap.zip
```

The LDIF files included are just templates and must be modified to fit the structure and conventions of the OID setup for your environment. Once the LDIFs are updated for your configuration they can be loaded into LDAP using the ldapadd tool that is included in the OID installation.

For example, to load the SIM Object classes (this is done on the OID host):

```
# export ORACLE_HOME=/u00/webadmin/products/wls_idm/Oracle_IDM
# export PATH=$ORACLE_HOME/bin:$PATH
# ldapadd -v -c -h <OID_HOST> -p 3060 -w <ORCLADMIN PASSWORD> -D cn=orcladmin
-f sim_objectclasses.ldif
```

The order of the LDIF install should be:

1. sim\_objectclasses.ldif
2. sim\_add\_company.ldif
3. sim\_add\_containers.ldif
4. sim\_data\_groups.ldif
5. sim\_data\_roles.ldif
6. sim\_data\_stores.ldif
7. sim\_data\_user\_groups.ldif
8. sim\_data\_users.ldif
9. sim\_data\_users\_roles.ldif

---

**Note:** Users that are needed for integration with SIM (e.g. for XStore or RIB) need to be a member of these groups :

- SIM\_SECURE\_USERS
  - SIM\_INTEGRATION\_USERS
- 

## Set the LANG Environment Variable

The LANG environment variable must be set in the profile of the UNIX user who owns the application server ORACLE\_HOME files. If you change the value of LANG or set the value for the first time, you must restart the Application Server in order for the change to take effect.

---

**Example:**

```
export LANG=en_US.utf8
```

---

## Set the Environment Variables for the SIM Installer

1. Set the following environment variables for the SIM installer (the following are just examples, use values for appropriate for your environment):

```
ORACLE_HOME=/u00/webadmin/products/wls_retail
WEBLOGIC_DOMAIN_HOME=/u00/webadmin/config/domains/wls_retail/SIMDomain
JAVA_HOME=/u00/webadmin/product/jdk_java
PATH=$JAVA_HOME/bin:$PATH
export ORACLE_HOME WEBLOGIC_DOMAIN_HOME JAVA_HOME PATH
```

2. If a secured datasource is going to be configured you also need to set “ANT\_OPTS” so the installer can access the key and trust store that is used for the datasource security:

```
export ANT_OPTS="-Djavax.net.ssl.keyStore=<PATH TO KEY STORE> -
Djavax.net.ssl.keyStoreType=jks -Djavax.net.ssl.keyStorePassword=<KEYSTORE
PASSWORD> -Djavax.net.ssl.trustStore=<PATH TO TRUST STORE> -
Djavax.net.ssl.trustStoreType=jks -
Djavax.net.ssl.trustStorePassword=<TRUSTSTORE PASSWORD>"
```

An example of this would be:

```
export ANT_OPTS="-Djavax.net.ssl.keyStore=/u00/webadmin/product/wls_retail
/wlserver/server/lib/orapphost.keystore -Djavax.net.ssl.keyStoreType=jks -
Djavax.net.ssl.keyStorePassword=retail123 -Djavax.net.ssl.trustStore=/
u00/webadmin/product/wls_retail /wlserver/server/lib/orapphost.keystore -
Djavax.net.ssl.trustStoreType=jks -
Djavax.net.ssl.trustStorePassword=retail123"
```

## Run the SIM Application Installer

This installer configures and deploys the SIM application and Java WebStart client files.

1. If you are using an X server such as Exceed, set the DISPLAY environment variable so that you can run the installer in GUI mode (recommended). If you are not using an X server, or the GUI is too slow over your network, unset DISPLAY for text mode.
2. Verify that the managed server to which SIM will be installed is currently running.
3. Run the install.sh script. This launches the installer. After installation is completed, a detailed installation log file is created:  
 <INSTALL\_DIR>/sim/application/logs/sim-install-app.<timestamp>.log.

---

**Note:** The manual install option in the installer is not functional for this release.

---



---

**Note:** See [Appendix: SIM Application WebLogic Server Installer Screens](#) for details on every screen and field in the WebLogic application installer.

---



---

**Note:** See [Appendix: Common Installation Errors](#) for details on common installation errors.

---

## Clustered Installations – Post-Installation Steps

Skip this section if you are not clustering the application server.

If you are installing the SIM application into a clustered WebLogic server environment the installer will automatically set the cluster to use a consensus migration basis. It is recommended to use database migration basis for clusters with only 2 nodes or if this is to be used in a production system.

The database cluster migration configuration setup is described in:

### Using Clusters for Oracle WebLogic Server 12c

DocID E24425-06

Please refer to that document on how to perform this procedure. In addition, note that since the installer sets this to consensus, this will need to be done every time the installer SIM is installed.

## SIM Database Authentication Provider set up (to be done after the application deploy)

**Note:** This procedure is only needed if you plan on using database authentication for the SIM application. This can be skipped if LDAP is going to be used for authentication.

1. Shut down all the servers of the WebLogic Domain created.
2. Once you extract the SIM installer to <INSTALL\_DIR> copy the sim-security.zip present in <INSTALL\_DIR>/sim/application/sim15 to the <WEBLOGIC\_DOMAIN\_HOME>/lib and extract it contents in the folder.
3. Start the domain admin server.
4. Log into the WebLogic console.
5. Navigate to: security realms -> myrealm (default realm) -> providers.

The screenshot shows the WebLogic console interface. On the left, there is a 'Change Center' with 'View changes and restarts' and 'Lock & Edit' buttons. Below it is the 'Domain Structure' tree showing 'SIMDomain' with sub-items like 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. At the bottom left, there is a 'How do I...' section with links to 'Configure Authentication and Identity Assertion providers' and 'Configure the Password Validation provider'.


The main content area is titled 'Settings for myrealm' and has several tabs: 'Configuration', 'Users and Groups', 'Roles and Policies', 'Credential Mappings', 'Providers', and 'Migration'. The 'Providers' tab is active, showing sub-tabs for 'Authentication', 'Password Validation', 'Authorization', 'Adjudication', 'Role Mapping', 'Auditing', and 'Credential Mapping'. Below these are 'Certification Path' and 'Keystores'.

A text block explains: 'An Authentication provider allows WebLogic Server to establish trust by validating a user. You must have one Authentication provider in a security realm, and you can configure multiple Authentication providers in a security realm. Different types of Authentication providers are designed to access different data stores, such as LDAP servers or DBMS. You can also configure a Realm Adapter Authentication provider that allows you to work with users and groups from previous releases of WebLogic Server.'


Below this is a 'Customize this table' section for 'Authentication Providers'. It includes a 'Lock & Edit' button and a table with columns 'Name', 'Description', and 'Version'. The table shows three providers:

Name	Description	Version
<input type="checkbox"/> Trust Service Identity Asserter	Trust Service Identity Assertion Provider	1.0
<input type="checkbox"/> DefaultAuthenticator	WebLogic Authentication Provider	1.0
<input type="checkbox"/> DefaultIdentityAsserter	WebLogic Identity Assertion provider	1.0

6. Click **Lock & Edit** in the change center.
7. Click New provider.
8. Select the provider type from the list: SimWlsDbAuthenticator.
9. Set the provider name (Default: SimWlsDbAuthenticator).



10. Click **Ok**.
11. Open the new provider configuration.
12. Under **Common**, set the Control Flag to SUFFICIENT.
13. Click **Save**.



14. Click the Provider Specific tab.
15. The SIM Data Source Name defaults to SimDataSource which is what the SIM installer creates. It should be left to the default value. The Group Name defaults to 'sim\_secure\_user'. If this was changed during the SIM installation then it also needs to be changed here.

16. Click **Save**.
17. Back on the provider tab, click **Reorder**.
18. Move the SimDbAuthenticator to the top of the list, or above the DefaultAuthenticator.

19. Click **Ok**.
20. Click **Activate Changes**.
21. Shutdown the SIMDomain (The adminserver and the managed servers).
22. Start the admin and managed servers for the domain.

## Review and/or Configure Oracle Single Sign-On

---

**Note:** This procedure is only needed if you plan on setting up the SIM application using Single Sign On (SSO) authentication. This can be skipped if SSO is not going to be configured for this environment. The Oracle Access Manager must be configured and the Oracle http server (Webtier and webgate) must be registered into the Oracle Access Manager.

---

### Create the SIM SSO provider in the SIMDomain

1. Shut down all the servers of the WebLogic Domain created.
2. Once you copy the contents to <INSTALL\_DIR> copy the sim-security.zip present in <INSTALL\_DIR>/sim/application/sim15 to the <WEBLOGIC\_DOMAIN\_HOME>/lib and extract its contents in the folder.
3. Start the domain admin server.
4. Log into the WebLogic console
5. Navigate to: security realms -> myrealm (default realm) -> providers.
6. Click 'Lock & Edit' in the change center.
7. Click **New**.
8. Select the provider type from the list: **SimWlsSsoAuthenticator**.
9. Set the provider name (Default: SimSsoAuthenticator).
10. Click **OK**.
11. Click on the newly created 'SimSsoAuthenticator'.
12. Under Common tab, set the Control Flag to SUFFICIENT and click **Save**.
13. Click **Provider Specific** tab.
14. Check that the GroupName is set to the name of the group used for SIM secure users (sim\_secure\_users by default).
15. All other values under the Provider Specific tab can be left as the default value.
16. Click **Save**.
17. On the provider list, click **Reorder**.
18. Move the SimWlsSsoAuthenticator to the top of the list.
19. Click **Ok**.
20. Click **Activate Changes** in the control center.
21. Shutdown the domain.
22. Start the admin and managed servers for the domain.

After the SSO provider is created in the SIMDomain, you will also have to set the protection of the SIM application resources correctly in the Application Domain that has been registered in the Oracle Access Manager.

In the Webtier/Webgate http server you need to set the mod\_wl\_ohs.conf file to redirect the http call to the where the SIM application has been deployed.

For example, in mod\_wl\_ohs.conf set:

```
<Location /sim-client >  
  WebLogicCluster orapphost1:orapphost2  
  SetHandler weblogic-handler  
</Location>
```

Then in Oracle Access Manager, set the protection of the resources in the Application Domain that has been registered for the SIM application. You must protect the /sim-client/launch resource and exclude the rest:

Resource URL: /sim-client/launch

Protection Level: Protected

Authentication Policy: Protected Resource Policy

Authorization Policy: Protected Resource Policy

Resource URL: /sim-client/.../\*

Protection Level: Excluded

In the OAM you need to add a response to the Protected Resource Policy:

1. Under Access Manager click **Application Domains**.
2. Search and click on the domain used for your SIM deployment.
3. Click **Authorization Policies**.
4. Click **Protected Resource Policy**.
5. Click **Responses**.
6. Click Add and enter the following values:
  - Type: Header
  - Name: OAM\_REMOTE\_USER\_GROUPS
  - Value: \$user.groups

It will look similar to the following:

The screenshot shows the Oracle Access Management console interface. At the top, there is a navigation bar with the Oracle logo and the text 'Access Management'. Below this are several tabs: 'Application Security' (selected), 'Federation', 'Mobile Security', and 'Configuration'. The main content area shows a breadcrumb trail: 'Launch Pad > Application Domain x > APP x > APP : Protected Resource ... x'. Below the breadcrumb, there is a link 'Access Manager >'. The main heading is 'Protected Resource Policy' with the sub-heading 'Authorization Policy'. To the right of the heading are 'Duplicate' and 'Apply' buttons. Below the heading is a descriptive text: 'Authorization policy contains a set of conditions that define whether a user should be permitted or denied access to the resources protected by the policy. Authorization rules and conditions apply to all resources within a specific Authorization policy.' Below this text are tabs for 'Summary', 'Resources', 'Conditions', 'Rules', and 'Responses' (selected). Under the 'Responses' tab, there is a checkbox for 'Identity Assertion' and a note: 'This will cause an assertion to be generated for the user, optionally containing any Asserted Attribute set below.' Below this is a table with the following data:

Name	Type	Value
OAM_REMOTE_USER_GROUPS	Header	\$user.groups

## SIM Batch Scripts

The SIM batch programs are installed into the `WEBLOGIC_DOMAIN_HOME` location that was specified during application installation.

The batch programs can be run from a different location if you cannot run them from under the application server `<WEBLOGIC_DOMAIN_HOME>`. To install the batch files in a different location just copy the entire batch folder to the appropriate destination.

The batch directory is assumed to be located on the same server as the application server. If you copy the SIM batch directory to a location on a different server, then you need to configure the file path to the `sim-batch.log` file, which is defined in `batch/resources/log4j.xml`.

See the “Batch Detail” section of the *Oracle Retail Store Inventory Management Operations Guide* for information about how to run batches.

## Resolving Errors Encountered During Application Installation

If the application installer encounters any errors, it halts execution immediately. You can run the installer in silent mode so that you do not have to retype the settings for your environment. See Appendix D of this document for instructions on silent mode.

See “[Appendix: Common Installation Errors](#)” for a list of common installation errors.

Since the application installation is a full reinstall every time, any previous partial installs are overwritten by the successful installation.

## Web Help Files

The application installer automatically copies the web help files to the proper location. They are accessible from the help links within the application.

## Starting and Stopping the Wavelink Server

In order to use handheld wireless devices with SIM, the Wavelink server must be running. The SIM application installer installs, configures, and starts the Wavelink server for you, so once the SIM application install is complete, the Wavelink server is ready to be used.

---

---

**Note:** Even if you use the AdminServer to restart SIM, you will still need to restart the Wavelink server manually.

---

---

The Wavelink server scripts are installed into the `<sim-wireless-directory>/bin`.

The following is an example for stopping and starting the Wavelink server:

```
# cd /u00/webadmin/config/domains/wls_retail/SIMDomain/retail/sim15/wireless/bin
# ./wavelink-shutdown.sh
# ./wavelink-startup.sh
```

---

---

**Note:** The wireless functionality in SIM is dependent on Wavelink and includes a client and server component. Wavelink software ensures that the wireless user interface of SIM can work with various handheld devices.

For the handheld to interact correctly with SIM, it is required to install the appropriate Wavelink studio client. The Wavelink studio client and its installation instructions can be found at

<http://www.wavelink.com/download/downloads.aspx>.

The Oracle Retail Wireless Foundation Server is bundled with the SIM server. It has a single session free license. For multiple sessions additional licenses need to be obtained.

Contact your Oracle sales representative or client partner for Wavelink Studio Client and Oracle Retail Wireless Foundation Server license information.

---

---

---

---

**Note:** For configurations of physical handheld devices or wireless network setup, check your hardware manufacturer's manual or Wavelink's studio client information. This information is not covered in this guide.

---

---



---

---

## Test the SIM Application

Once SIM database and application are installed, foundation data is imported into SIM, you should have a working SIM application installation. To launch the application client, open a web browser and go to the client URL. You can find the URL in the next steps section of the log file that was produced by the installer.

---

---

**Example:**

**WLS:** <http://orapphost:7143/sim-client/launch>

---

---



---

## Appendix: SIM Database Schema Installer Screens

You need the following details about your environment for the installer to successfully install the SIM database schema. Depending on the options you select, you may not see some screens.

### Screen: Data Source Details

**SIM Schema Installer - Oracle Retail**

**ORACLE**

**Data Source Details**

Please provide information on a pre-existing database user for this SIM installation. The installer will authenticate as this user and create the SIM database objects.

SIM Schema Owner: sim01

SIM Schema Password: .....

SIM Oracle SID: dolsp33app

Temporary tablespace name: TEMP

Buttons: Cancel, Back, Next, Install

---

<b>Field Title</b>	SIM Schema Owner
<b>Field Description</b>	The pre-existing database user for this installation.
<b>Example</b>	sim01

---

<b>Field Title</b>	Sim Schema Password
<b>Field Description</b>	The SIM Schema Owner's password.
<b>Field Title</b>	SIM Oracle SID
<b>Field Description</b>	The name of the database or pluggable db service name where the SIM schema will be installed.
<b>Example</b>	dolsp33app
<b>Field Title</b>	Temporary tablespace name
<b>Field Description</b>	Temporary tablespace provided to the create_user_sim_owner.sql script at the time that the SIM database user was created.
<b>Example</b>	TEMP

**Screen: Data Source Users Details**



<b>Field Title</b>	SIM Database Admin User Name
<b>Field Description</b>	The pre-existing database admin user for this installation.
<b>Example</b>	Sim_adm
<b>Field Title</b>	SIM Database Admin User Password
<b>Field Description</b>	The SIM database admin user's password.
<b>Field Title</b>	SIM Database Business User Name
<b>Field Description</b>	The pre-existing database business user for this installation.
<b>Example</b>	Sim_bsi

<b>Field Title</b>	SIM Database Business User Password
<b>Field Description</b>	The SIM database business user's password.
<b>Field Title</b>	SIM Database Business Viewer User Name
<b>Field Description</b>	The pre-existing database business viewer user for this installation.
<b>Example</b>	Sim_bsv
<b>Field Title</b>	SIM Database Business Viewer User Password
<b>Field Description</b>	The SIM database business viewer user's password.
<b>Field Title</b>	SIM Database MPS User Name
<b>Field Description</b>	The pre-existing database MPS user for this installation.
<b>Example</b>	Sim_mps
<b>Field Title</b>	SIM Database MPS User Password
<b>Field Description</b>	The SIM database MPS user's password.
<b>Field Title</b>	SIM Database RIB User Name
<b>Field Description</b>	The pre-existing database RIB user for this installation.
<b>Example</b>	Sim_rib
<b>Field Title</b>	SIM Database RIB User Password
<b>Field Description</b>	The SIM database RIB user's password.

<b>Field Title</b>	SIM Database Security User Name
<b>Field Description</b>	The pre-existing database security user for this installation.
<b>Example</b>	Sim_sec
<b>Field Title</b>	SIM Database Security User Password
<b>Field Description</b>	The SIM database security user's password.

Screen: PL/SQL Batch Setup – Base Directory



<b>Field Title</b>	PL/SQL batch data file location
<b>Field Description</b>	A directory which will be the parent directory for all other PL/SQL batch processing directories.
<b>Destination</b>	dba_create_directory.sql
<b>Example</b>	/usr/oracle/retail/sim/batch

## Screen: PL/SQL Batch Setup (3 screens)



<b>Field Title</b>	StockCount upload directory
<b>Field Description</b>	A filesystem directory and database directory object used for processing StockCount data.
<b>Destination</b>	dba_create_directory.sql
<b>Example</b>	/usr/oracle/retail/sim/batch/stockcountUpload
<b>Notes</b>	The installer will not create these directories or directory objects. It will produce the dba_create_directory.sql script, which can be used to create them.

### Screen: Installation Summary

**SIM Schema Installer - Oracle Retail**

**ORACLE**

**Installation Summary**

Summary of Installation.

SIM Schema Owner	sim01
Oracle SID	dolsp33app
Temporary Tablespace	TEMP
StockCount upload directory	racle/retail/sim/batch/stockcountUpload

Cancel Back Next Install

## Appendix: SIM Application WebLogic Server Installer Screens


You need the following details about your environment for the installer to successfully deploy the SIM application. Depending on the options you select, you may not see some screens.

### Screen: Installation Type

<b>Field Title</b>	Which Installation Method will you use?
<b>Field Description</b>	Choosing "Standalone server" will deploy SIM to a non-clustered environment, if "Cluster Servers" is chosen then it will deploy SIM to a cluster of servers defined in WebLogic.

**Screen: Cluster load-balancer Address**

This screen will be displayed, if Cluster Servers option is selected in “Installation Type” screen.



<b>Field Title</b>	Load-Balancer/Cluster DNS Address
<b>Field Description</b>	This contains Virtual Host name of the load balancer that will be used if SIM is to be deployed to a clustered environment. Please note this screen will not appear in case you select Standalone server in previous screen.

**Screen: Security Details**

**Store Inventory Management Installer - Oracle Retail**

**ORACLE**

**Security Details**

Provide security details for the SIM application

Note: enabling SSL requires that security certificates have been configured and installed for this WebLogic domain. The AdminServer and all managed servers must then be configured to use SSL.


Enable SSL for SIM?

Yes  
 No

Cancel Back Next Install

<b>Field Title</b>	Enable SSL for SIM?
<b>Field Description</b>	Choosing yes will deploy SIM using SSL, and will configure SIM to use SSL. In this case, SSL must be configured and enabled for the admin server and SIM managed server or cluster. Choosing no will deploy and configure SIM without SSL.

**Screen: Turn off the application server's non-SSL port**



<b>Field Title</b>	Disable non SSL port?
<b>Field Description</b>	Selecting Yes will make that the application server's non – SSL port inactive and a Selecting No will keep application server's non-SSL port active.

## Screen: Application Server Details

**Application Server Details**

Note: if SSL is enabled, this value MUST match the DNS name used in the SSL certificate.

Weblogic Server Hostname

Note: if SSL is enabled, this value MUST match SSL Port.

Weblogic Server Port

Weblogic Admin User Name

Weblogic Admin User Password

Cancel Back Next Install

<b>Field Title</b>	WebLogic Server Hostname
<b>Field Description</b>	The hostname of the server where the WebLogic server is installed.
<b>Example</b>	Dev0234
<b>Notes</b>	Used by installer scripts to install the application and to create default inputs for client codebase and JNDI provider URL.

<b>Field Title</b>	WebLogic Server Port
<b>Field Description</b>	Listen port for the WebLogic Admin server.
<b>Example</b>	7001

<b>Field Title</b>	WebLogic Admin User Name
<b>Field Description</b>	The WebLogic user which will be used to install the SIM application.
<b>Example</b>	Weblogic
<b>Notes</b>	Used by installer scripts to install the application

<b>Field Title</b>	WebLogic Admin User Password
<b>Field Description</b>	The password of the WebLogic Admin User used above.
<b>Notes</b>	Used by installer scripts to install the application

## Screen: Application Deployment Details

**Application Deployment Details**

Provide the following details for the SIM application being installed. The default values shown below are examples.

Client Context Root

Mobile Server Context Root

You can deploy to a single managed server or a cluster of servers. You can deploy to the AdminServer for testing purposes, but this is not recommended for production deployments.

Weblogic server/cluster

Cancel Back Next Install

<b>Field Title</b>	Client Context Root
<b>Field Description</b>	Context root for sim client.
<b>Example</b>	sim-client

<b>Field Title</b>	Mobile Server Context Root
<b>Field Description</b>	This is the managed server name for mobile deployment.
<b>Example</b>	sim-mobile

<b>Field Title</b>	WebLogic server/cluster
<b>Field Description</b>	This is the managed server name for standalone deployment and cluster name for deployment to clustered managed servers.
<b>Example</b>	sim-server

**Screen: Choose Apps to Integrate with SIM**



<b>Field Title</b>	Configure RIB for SIM?
<b>Field Description</b>	Select this option if you will be using RIB with SIM. Please note if you select this option then RIB Integration Details screen will be enabled and appropriate details have to be entered in RIB Integration Details screen.

<b>Field Title</b>	Configure RPM for SIM?
<b>Field Description</b>	Select this option if you will be using RPM with SIM. Please note if you select this option then RPM Integration Details screen will be enabled and appropriate details have to be entered in RPM Integration Details screen.

<b>Field Title</b>	Configure RMS for SIM?
<b>Field Description</b>	Select this option if you will be using RMS with SIM. Please note if you select this option then RMS Integration Details screen will be enabled and appropriate details have to be entered in RMS Integration Details screen.

<b>Field Title</b>	Configure Manifest for SIM? <b>Note:</b> Refer to the <i>Oracle Retail Store Inventory Management Operations Guide</i> for more information.
<b>Field Description</b>	Manifest integration is configured if an external Shipment Management System is to be used in conjunction with SIM. (Optional). Please note if you select this option then the Manifest Integration Details screen will be enabled and appropriate details will be entered in the subsequent Manifest Integration Details screen.

<b>Field Title</b>	Configure OMS for SIM? <b>Note:</b> Refer to the <i>Oracle Retail Store Inventory Management Operations Guide</i> for more information.
<b>Field Description</b>	OMS integration is configured if an external Shipment Management System is to be used in conjunction with SIM. (Optional). Please note if you select this option then OMS Integration Details screen will be enabled and appropriate details will be entered in the subsequent OMS Integration Details screen.

### Screen: RIB Integration Details

This screen will be displayed if the Configure RIB for SIM option is checked on the Choose Apps to Integrate with SIM screen.

<b>Field Title</b>	RIB SIM Provider URL
<b>Field Description</b>	This is the provider URL of the rib-sim application. If RIB SIM uses SSL, use t3s as the protocol, otherwise use t3.
<b>Example</b>	t3s://Dev01234.example.com:19106/rib-sim

<b>Field Title</b>	RIB Publish User Name
<b>Field Description</b>	This is the user name for the JNDI connection to the RIB Admin Server.
<b>Example</b>	ribuser


<b>Field Title</b>	RIB Publish User Password
<b>Field Description</b>	Password for the RIB publish user.

<b>Field Title</b>	SIM Inject User Name
<b>Field Description</b>	This is the user name for the JNDI connection from the RIB Admin Server.
<b>Example</b>	simribuser

<b>Field Title</b>	SIM Inject User Password
<b>Field Description</b>	Password for the SIM inject user.

**Screen: RPM Web service Policy**

This screen will be displayed if the Configure RPM for SIM option is checked on the Choose Apps to Integrate with SIM screen.



<b>Field Title</b>	Select the web service security policy for integration with RPM.
<b>Field Description</b>	Select the web service security policy for integration with RPM. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.

**Screen: RPM Integration Details**

This screen will be displayed if the Configure RPM for SIM option is checked on the Choose Apps to Integrate with SIM screen.

---

**Note:** If the user chooses to integrate SIM with RPM then RPM installation is a pre-requisite to installing SIM.


---

<b>Field Title</b>	RPM Price Change WSDL URL
<b>Field Description</b>	This is the provider URL for RPM Price change WSDL.  <b>Note:</b> User just need to know the WSDL URL of RPM if it will have. SIM will install without RPM being there
<b>Example</b>	http://dev1234.us.oracle.com:18007/rpm-PriceChange-AppServiceDecorator/ProxyService/PriceChangeAppServiceProxy?wsdl

<b>Field Title</b>	RPM Price Inquiry WSDL URL
<b>Field Description</b>	This is the provider URL for RPM Price Inquiry WSDL.
<b>Example</b>	http://dev1234.us.oracle.com:18007/rpm-PriceInquiry-AppServiceDecorator/ProxyService/PriceInquiryAppServiceProxy?wsdl

### Screen: RMS Web service Policy

This screen will be displayed if the Configure RMS for SIM option is checked on the Choose Apps to Integrate with SIM screen.



<b>Field Title</b>	Select the web service security policy for Integration with RMS.
<b>Field Description</b>	Select the type of web service security policy for integration with RMS. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.
<b>Example</b>	None, PolicyA, PolicyB.

**Screen: RMS Integration Details**


This screen will be displayed if the Configure RMS for SIM option is checked on the Choose Apps to Integrate with SIM screen.

**Note:** If the user chooses to integrate SIM with RMS then RMS installation is pre-requisite to install SIM.

<b>Field Title</b>	RMS Store Order WSDL URL
<b>Field Description</b>	This is the provider URL for RMS Store Order WSDL.
<b>Example</b>	http://dev1234.us.oracle.com:18007/rms-StoreOrder-AppServiceDecorator/ProxyService/StoreOrderAppServiceProxy?wsdl

### Screen: Manifest Web service Policy

This screen will be displayed if the Configure Manifest for SIM option is checked on the Choose Apps to Integrate with SIM screen.



<b>Field Title</b>	Select the web service security policy for Manifest Integration
<b>Field Description</b>	Select the type of web service security policy for Manifest Integration. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.
<b>Example</b>	None, PolicyA, PolicyB

**Screen: Manifest Integration Details**


This screen will be displayed if the Configure Manifest for SIM option is checked on the Choose Apps to Integrate with SIM screen.

The screenshot shows a window titled "Store Inventory Management Installer - Oracle Retail". The window contains the Oracle logo and a section titled "Manifest Integration Details". Below this title is a text input field labeled "Manifest WSDL URL" with the value "http://[Host]:[Port]/StoreShipmentManife:". At the bottom of the window are four buttons: "Cancel", "Back", "Next", and "Install".

<b>Field Title</b>	Manifest WSDL URL
<b>Field Description</b>	This is the provider URL for Manifest WSDL. <b>Note:</b> Refer to the <i>Oracle Retail Store Inventory Management Operations Guide</i> for more information.
<b>Example</b>	http://orapphost:17015/ StoreShipmentManifestBean/StoreShipmentManifestService?WSDL

**Screen: OMS Web service Policy**

This screen will be displayed, if Configure OMS for SIM option is checked on the Choose Apps to Integrate with SIM screen.




---

**Note:** This screen will appear when user chooses to integrate SIM with OMS

---


<b>Field Title</b>	Select the web service security policy for integration with OMS
<b>Field Description</b>	Selects the type of web service security policy for integration with OMS. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.
<b>Destination</b>	None, PolicyA, PolicyB

**Screen: OMS Integration Details**

This screen will be displayed if the Configure OMS for SIM option is checked on the Choose Apps to Integrate with SIM screen.


<b>Field Title</b>	OMS WSDL URL
<b>Field Description</b>	This is the provider URL for the OMS WSDL. <b>Note:</b> Refer to the <i>Oracle Retail Store Inventory Management Operations Guide</i> for more information.
<b>Example</b>	http://orribhost:18007/oms-CustomerOrder-AppServiceDecorator/ProxyService/CustomerOrderAppServiceProxy?wsdl

**Screen: JDBC Security Details**



<b>Field Title</b>	Enable Secure JDBC connection
<b>Field Description</b>	Select Yes if you have a secured database already set up, otherwise select No.

Screen: Data Source Details



<b>Field Title</b>	SIM JDBC URL
<b>Field Description</b>	URL used by the SIM application to access the SIM database schema.
<b>Destination</b>	WebLogic admin server
<b>Example</b>	<p>Standard Thin Connection:                      jdbc:oracle:thin:@myhost:1521:mysimsid</p> <p>If it is a pluggable db then use the URL as shown below                      jdbc:oracle:thin:@myhost:1521/&lt;service name&gt;</p> <p>RAC connection:                      jdbc:oracle:thin:@(DESCRIPTION =(ADDRESS_LIST =(ADDRESS = (PROTOCOL = TCP)(HOST = myhost1)(PORT = 1521))(ADDRESS = (PROTOCOL = TCP)(HOST = myhost2)(PORT = 1521))(LOAD_BALANCE = yes))(CONNECT_DATA =(SERVICE_NAME = mysimsid)))</p>

<b>Field Title</b>	SIM Database Schema Owner User Name
<b>Field Description</b>	The schema owner name.
<b>Destination</b>	WebLogic admin server
<b>Notes</b>	The schema owner name should match the name you provided when you ran the SIM database schema installer.

<b>Field Title</b>	SIM Database Schema Owner User Password
<b>Field Description</b>	The password for the SIM schema owner.

<b>Field Title</b>	SIM Database Admin User Name
<b>Field Description</b>	The database admin user name.

<b>Field Title</b>	SIM Database Admin User Password
<b>Field Description</b>	The password for the database admin user.

<b>Field Title</b>	SIM Database Business User Name
<b>Field Description</b>	The database business user name.

<b>Field Title</b>	SIM Database Business User Password
<b>Field Description</b>	The password for the database business user.

<b>Field Title</b>	SIM Database MPS User Name
<b>Field Description</b>	The database MPS user name.


<b>Field Title</b>	SIM Database MPS User Password
<b>Field Description</b>	The password for the database MPS user.

<b>Field Title</b>	SIM Database Security User Name
<b>Field Description</b>	The database security user name.

<b>Field Title</b>	SIM Database Security User Password
<b>Field Description</b>	The password for the database Security user.

### Screen: Secure Data Source Details

This screen is displayed if Secure JDBC connection is enabled.



<b>Field Title</b>	Identity Keystore
<b>Field Description</b>	Path to the identity keystore, i.e. /u00/webadmin/product/identity.keystore

<b>Field Title</b>	Identity Keystore Type
<b>Field Description</b>	Keystore type i.e: JKS

<b>Field Title</b>	Identity Keystore Password
<b>Field Description</b>	Password used to access the identity keystore defined above.

<b>Field Title</b>	Identity TrustStore
<b>Field Description</b>	Path to the identity truststore, i.e.: /u00/webadmin/product/identity.truststore

<b>Field Title</b>	Identity TrustStore Type
<b>Field Description</b>	Keystore type i.e. JKS

<b>Field Title</b>	Identity TrustStore Password
<b>Field Description</b>	Password used to access the identity truststore defined above.

**Screen: LDAP Server Details**

**LDAP Server Details**

SIM requires the use of an LDAP directory for storage of its user, role, and store entries. Please provide the details for your LDAP directory.

Note: If the ldap server is configured to use SSL, use ldaps as the protocol. Otherwise use ldap.

LDAP Server URL

Enter the search base DN. This is a directory entry under which SIM will search for user and store entries

LDAP Search Base DN

Enter the search user DN. SIM will authenticate to the LDAP directory as this entry.

LDAP User DN

LDAP User Password

Buttons: Cancel, Back, Next, Install

<b>Field Title</b>	LDAP server URL
<b>Field Description</b>	URL for your LDAP directory server.
<b>Example</b>	Non-secured ldap: ldap://myhost:3060/ Secured ldap: ldaps://myhost:2484/

<b>Field Title</b>	LDAP Search Base DN
<b>Field Description</b>	The directory entry under which SIM will search for user and store entries.
<b>Example</b>	dc=us,dc=oracle,dc=com

<b>Field Title</b>	LDAP User DN
<b>Field Description</b>	Distinguished name of the user that RPM uses to authenticate to the LDAP directory.
<b>Example</b>	cn=sim.admin,cn=Users,dc=us,dc=oracle,dc=com

<b>Field Title</b>	LDAP User Password
<b>Field Description</b>	Password for the search user DN.

**Screen: Mail Session Details**

<b>Field Title</b>	SIM Mail SMTP Host
<b>Field Description</b>	The SMTP server that will be used to send notification emails from SIM.
<b>Example</b>	mail.oracle.com

<b>Field Title</b>	Enable SSL for Mail session connection
<b>Field Description</b>	Select Yes for secure connection. Select No for plain connection.

<b>Field Title</b>	SIM Mail SMTP Port
<b>Field Description</b>	Port that the mail client is configured to use.

<b>Field Title</b>	SIM Mail User Name
<b>Field Description</b>	Username used to access the mail client.

<b>Field Title</b>	SIM Mail User Password
<b>Field Description</b>	Password for the above user.

<b>Field Title</b>	Enable authentication for mail session connection
<b>Field Description</b>	Yes or no depending on mail client configuration.

<b>Field Title</b>	Enable STARTTLS
<b>Field Description</b>	Yes or No depending on mail client configuration.

**Screen: Wireless Server Details**

<b>Field Title</b>	Wireless Server User Name
<b>Field Description</b>	User name for wireless server
<b>Destination</b>	Retail config wallet and installer creates WebLogic user with the given name above.

<b>Field Title</b>	Wireless Server User Password
<b>Field Description</b>	Password for wireless server user, the password must follow WebLogic password requirements (at least 8 characters in length and one non-alphabetic character).
<b>Destination</b>	Retail config wallet.

<b>Field Title</b>	SIM Wireless Server Port
<b>Field Description</b>	Choose an available port that the Wavelink server will use to listen for incoming messages from wireless devices.
<b>Destination</b>	wireless.cfg, wavelink-startup.sh
<b>Example</b>	40002

<b>Field Title</b>	Enable SSL for Wireless Server
<b>Field Description</b>	Yes or No depending on SSL configuration.

**Screen: Wireless Server SSL Details**

The screenshot shows a window titled "Store Inventory Management Installer - Oracle Retail" with the Oracle logo at the top. Below the logo is a section titled "Wireless Server SSL Details". This section contains five input fields:

- Wireless Server KeyStore Type: JKS
- Wireless Server KeyStore Name: /home/hostname.keystore
- Wireless Server KeyStore Password: [Masked with 8 dots]
- Wireless Server Key Name: wirelesskey
- Wireless Server Key Password: [Masked with 8 dots]

At the bottom of the window, there are four buttons: "Cancel" (with a red X icon), "Back" (with a left arrow icon), "Next" (with a right arrow icon), and "Install" (with a right arrow icon).

<b>Field Title</b>	Wireless Server Keystore Type
<b>Field Description</b>	Keystore type i.e: JKS

<b>Field Title</b>	Wireless Server Keystore Name
<b>Field Description</b>	Path to the wireless server keystore, i.e. /u00/webadmin/product/identity.keystore

<b>Field Title</b>	Wireless Server Keystore Password
<b>Field Description</b>	Password used to access the wireless server keystore defined above.

<b>Field Title</b>	Wireless Server Key Name
<b>Field Description</b>	The wireless server key alias name

<b>Field Title</b>	Wireless Server Key Password
<b>Field Description</b>	Password used to access the wireless server key alias name defined above.

**Screen: Batch Server Details**

<b>Field Title</b>	Batch User Name
<b>Field Description</b>	User name for Batch.
<b>Destination</b>	Retail config wallet and installer creates WebLogic user with the given name above.

<b>Field Title</b>	Batch User Password
<b>Field Description</b>	Password for batch user, the password must follow weblogic password requirements (at least 8 characters in length and one non-alphabetic character).
<b>Destination</b>	Retail config wallet.

## Screen: Server User Details

**Store Inventory Management Installer - Oracle Retail**

**ORACLE**

**Server User Details**

Note: this must be a valid user.

SIM Server User Name: sim.server

SIM Server User Password: .....

Buttons: Cancel, Back, Next, Install

<b>Field Title</b>	SIM Server User Name
<b>Field Description</b>	User name for SIM Server
<b>Destination</b>	Domain wallet and installer creates WebLogic user with the given name above.

<b>Field Title</b>	SIM Server User Password
<b>Field Description</b>	Password for SIM Server User, the password must follow WebLogic password requirements (at least 8 characters in length and one non-alphabetic character).
<b>Destination</b>	Weblogic Domain wallet/ weblogic default

**Screen: Internal Security Installation User Details**

The screenshot shows a window titled "Store Inventory Management Installer - Oracle Retail". Below the title bar is the Oracle logo. The main content area is titled "Internal Security Installation User Details". It contains two input fields: "SIM Internal Security Installation User Name" with the text "simsecuser" and "SIM Internal Security Installation User Password" with masked characters. At the bottom of the window, there are four buttons: "Cancel", "Back", "Next", and "Install".

<b>Field Title</b>	SIM Internal Security Installation User Name
<b>Field Description</b>	User name for SIM Internal Security Installation.
<b>Destination</b>	SIM database user for the SIM application and WebLogic user in database provider authentication. SIM stores are tied to this user. Example: simsecuser

<b>Field Title</b>	SIM Internal Security Installation User Password
<b>Field Description</b>	Password for SIM Internal Security Installation User, the password must follow WebLogic password requirements (at least 8 characters in length and one non-alphabetic character).
<b>Destination</b>	SIM database user for the SIM application and WebLogic user in database provider authentication.

## Screen: SIM Webservice Provider Policy

Store Inventory Management Installer - Oracle Retail

ORACLE

**SIM Webservice Provider Policy**

Select the Policy for securing SIM integration web services

None (disables access)

Cancel Back Next Install

<b>Field Title</b>	Select the policy for securing SIM web service providers
<b>Field Description</b>	Select the type of web service policy for SIM. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.
<b>Example</b>	None, PolicyA, PolicyB

**Screen: Printing Details**



<b>Field Title</b>	Configure SIM reporting for BI publisher
<b>Field Description</b>	Select this option if you will be using BI Publisher for SIM reporting. Please note if you select this option then the "Report BIP Details" screen will be enabled and appropriate details will have to be entered in the subsequent "Report BIP Details" Details screen.

<b>Field Title</b>	Configure SIM ticket Printing
<b>Field Description</b>	Choose the ticket printing option.

<b>Field Title</b>	Configure SIM ticket Printing "None"
<b>Field Description</b>	Select this option if you will not be using ticket printing feature.

<b>Field Title</b>	Configure SIM ticket Printing “BI Publisher”
<b>Field Description</b>	Select this option if you will be using an out of box BI Publisher ticketing implementation. Please note if you select this option then the “Ticket Printing BIP Details” screen will be enabled and appropriate details will have to be entered in the subsequent “Ticket Printing BIP Details” Details screen.

<b>Field Title</b>	Configure SIM ticket Printing “External Web Service”
<b>Field Description</b>	Select this option if you will provide web service provider. See <i>sim-1501-impl4</i> “Item Ticket Printing” Section in SIM Implementation Guide for details. Please note if you select this option then the “External Ticket Printing Service Details” screen will be enabled and appropriate details will have to be entered in the subsequent “External Ticket Printing Service Details” screen.

### Screen: Reporting BIP Details 1

This screen will be displayed if you select the Configure SIM reporting for BI Publisher option on the Printing Details screen.

<b>Field Title</b>	BI Publisher Host
<b>Field Description</b>	Host name where BI Publisher is installed.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	redevlv0074.us.example.com

<b>Field Title</b>	BI Publisher Port
<b>Field Description</b>	Port where BI Publisher is configured.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	7003

<b>Field Title</b>	BI Publisher Context Root
<b>Field Description</b>	Context root where BI Publisher is installed.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	Xmlpserver

<b>Field Title</b>	Enable SSL for reporting
<b>Field Description</b>	The Protocol to be used for configuring reporting.

### Screen: Reporting BIP Details 2

This screen will be displayed if you select the Configure SIM reporting for BI Publisher option on the Printing Details screen.

<b>Field Title</b>	Reporting URL
<b>Field Description</b>	Confirmation field of address configured from values provided on previous screen.
<b>Destination</b>	Updates the reporting tool related default values in SIM database.
<b>Example</b>	http://dev01234.us.oracle.com:18005/xmlpserver/

<b>Field Title</b>	Report Template Base Path
<b>Field Description</b>	The root directory in which your SIM report templates are located.
<b>Example</b>	/Base/SIM /u00/webadmin/product/10.3.X/WLS/user_projects/domains/bifoundation_domain/config/bipublisher/repository/Reports/Guest/SIM

<b>Field Title</b>	Reporting Username
<b>Field Description</b>	From the <i>Oracle Retail Store Inventory Management Implementation Guide</i> : <BIP_REPORTS_USER> or <SSO_USER>
<b>Destination</b>	This user MUST exist as a BI Publisher user.
<b>Example</b>	retail.user

<b>Field Title</b>	Reporting user Password
<b>Field Description</b>	From the <i>Oracle Retail Store Inventory Management Implementation Guide</i> : <BIP_REPORTS_USER_PASSWORD> or <SSO_PASSWORD>
<b>Destination</b>	Updates security wallet info

### Screen: Ticket Printing BIP Details 1

This screen will be displayed if you select the Configure SIM ticket printing option on the Printing Details screen.

<b>Field Title</b>	BI Publisher Host
<b>Field Description</b>	Host name where BI Publisher is installed.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	redevlv0074.us.example.com

<b>Field Title</b>	BI Publisher Port
<b>Field Description</b>	Port where BI Publisher is configured.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	7003

<b>Field Title</b>	BI Publisher Context Root
<b>Field Description</b>	Context root where BI Publisher is installed.
<b>Destination</b>	Updates the BI Publisher related default values in SIM database.
<b>Example</b>	Xmlpserver

<b>Field Title</b>	Enable SSL for ticket printing
<b>Field Description</b>	The Protocol to be used for ticket printing.

**Screen: Ticket Printing BIP Details 2**

This screen will be displayed if you select the Configure SIM ticket printing option on the Printing Details screen.

<b>Field Title</b>	Ticket Printing URL
<b>Field Description</b>	Confirmation field of address configured from values provided on previous screen.
<b>Destination</b>	Updates the ticket printing BIP related default values in SIM database.
<b>Example</b>	http://dev01234.us.oracle.com:18006/xmlpserver


<b>Field Title</b>	Ticket Template Base Path
<b>Field Description</b>	The root directory in which your SIM ticket templates are located. <b>Note:</b> See <a href="#">Appendix: Setting up SIM Reports/Tickets in BI Publisher</a> for instructions for migrating SIM reports/tickets to BI Publisher
<b>Example</b>	/Base/SIM An example from this install guide is: /u00/webadmin/product/10.3.X/WLS/user_projects/domains/bifoundation_domain/config/bipublisher/repository/Reports/Guest/SIM

<b>Field Title</b>	Ticket Printing Username
<b>Field Description</b>	From the <i>Oracle Retail Store Inventory Management Implementation Guide</i> : <BIP_TICKETPRINTING_USER> or <SSO_USER>
<b>Destination</b>	This user MUST exist as a BI Publisher user.
<b>Example</b>	retail.user

<b>Field Title</b>	Ticket Printing user Password
<b>Field Description</b>	From the <i>Oracle Retail Store Inventory Management Implementation Guide</i> : <BIP_TICKETPRINTING_USER_PASSWORD> or <SSO_PASSWORD>
<b>Destination</b>	Updates security wallet info

### Screen: External Ticket Printing WebService Policy

This screen will be displayed if you select the External Webservice option on the Printing Details screen.



<b>Field Title</b>	Select the web service security policy for external ticket printing <b>Note:</b> The user should refer the <i>Oracle Retail Store Inventory Management Operations Guide</i> to know what OMS to choose.
<b>Field Description</b>	Selects the type of web service security policy for external ticket printing. Please refer to the <i>Oracle Retail Store Inventory Management Security Guide</i> to learn more about Policy A and Policy B.
<b>Destination</b>	None, PolicyA, PolicyB <b>Note:</b> If web services are to be secured using either Policy A or Policy B, then user should have some basic knowledge about the same. A user can refer to security guide to know more about Policy A and Policy B

**Screen: External Ticket Printing Service Details**

This screen will be displayed if you select the External Webservice option on the Printing Details screen.

<b>Field Title</b>	External Ticket Printing WSDL URL
<b>Field Description</b>	This is the External Ticket Printing WSDL URL.
<b>Example</b>	http://hostname:18007/ticket-printing-AppServiceDecorator/ProxyService/ticketprintingAppServiceProxy?wsdl

**Screen: Enable SSO in SIM**



<b>Field Title</b>	Use Single Sign-On for user identification and authentication?
<b>Field Description</b>	This version of SIM has the option to use Single Sign-On (SSO) technology to authenticate users. If SSO is being used in your environment then click the check box. Leaving the box unchecked will configure SIM to use its own LDAP directory settings for authentication.

## Screen: Single Sign-On Details

**Store Inventory Management Installer - Oracle Retail**

**ORACLE**

**Single Sign On Details**

Please enter the Oracle Single Sign-On web tier server details.

SSO Server Host


SSO Server Port

Cancel Back Next Install

<b>Field Title</b>	SSO Server Host
<b>Field Description</b>	This is the host used to access the Single Sign-On web tier.
<b>Example</b>	WEBTIERSERVER.us.com

<b>Field Title</b>	SSO Server Port
<b>Field Description</b>	This is the HTTP port used to access the Single Sign-On web tier.
<b>Example</b>	18888

**Screen: Manual Deployment Option**



<b>Field Title</b>	Install files to app server ?
<b>Field Description</b>	The installer will configure the application and application server files. Then, it can proceed with installing the application into the server. If a user does not have filesystem access to application server, or wishes to deploy using a different method, he can choose to have the installer skip the final installation phase.
<b>Example</b>	Select Yes, I have write access to the application server.

## Screen: Installation Summary

Summary of Installation	
Enable SSL for SIM	true
Weblogic Server Hostname	mshp28206
Weblogic Admin Port	7142
Weblogic Admin User Name	weblogic
Client Context Root	sim-client
Mobile Server Context Root	sim-mobile
Weblogic server/cluster	sim-server
Configure RIB for SIM	true
Configure RPM for SIM	true

Buttons: Cancel, Back, Next, Install

<b>Field Title</b>	Summary of Installation
<b>Field Description</b>	Lists the values entered in the previous install screens.
<b>Example</b>	Verify each value and if they are correct click next, else use back button to go back and change the value. Selecting Cancel will Cancel the installation.



---

---

## Appendix: Common Installation Errors

This section provides some common errors encountered during installation.

### EJB Deployment Errors during Installation to WebLogic

#### Symptom

On servers that are encountering high memory usage, deployment of sim-server.ear will occasionally fail due to WebLogic's inability to start the EJB polling timer service.

```
[java] .....Failed to deploy the application with status failed
[java] Current Status of your Deployment:
[java] Deployment command type: deploy
[java] Deployment State      : failed
[java] Deployment Message    : weblogic.application.ModuleException:
Exception activating module: EJBModule(
sim-ejb3.jar)
[java]
[java]
[java] weblogic.management.scripting.ScriptException: Error occured while
performing deploy : Deployment Fail
ed.
[java] Unable to deploy EJB: PollingCoordinatorThreadBean from sim-ejb3.jar:
[java]
[java] Error starting Timer service
```

#### Solution

Delete the WebLogic managed server/cluster where sim was targeted in the Admin Console, and activate the changes. Manually delete the managed server directory <DOMAIN HOME>/servers/<SIM SERVER NAME>. Bounce the WebLogic admin server. Re-create the managed server in the Admin Console, Finally, re-run the installer. If the error persists after re-installation, consider reducing the cpu, disk, and memory load on the server.

### Output Freezes during Text Mode Installation to WebLogic

#### Symptom

The standard output of the installer in text mode will sometimes freeze partway through the installation.

#### Solution

Open a new terminal to the server and tail the log file located in sim/application/logs.

## Database Installer Hangs on Startup

### Symptom

When the database schema installer is run, the following is written to the console and the installer hangs indefinitely:

```
Running pre-install checks  
Running tnsping to get listener port
```

### Solution

The installer startup script is waiting for control to return from the **tnsping** command, but **tnsping** is hanging. Type Control+C to cancel the installer, and investigate and solve the problem that is causing the **tnsping <sid>** command to hang. This can be caused by duplicate database listeners running.

## Warning: Could not create system preferences directory

### Symptom

The following text appears in the installer Errors tab:

```
May 22, 2006 11:16:39 AM java.util.prefs.FileSystemPreferences$3 run  
WARNING: Could not create system preferences directory. System preferences are unusable.  
May 22, 2006 11:17:09 AM java.util.prefs.FileSystemPreferences  
checkLockFile0ErrorCode  
WARNING: Could not lock System prefs. Unix error code -264946424.
```

### Solution

This is related to Java bug 4838770. The `/etc/.java/.systemPrefs` directory may not have been created on your system. See <http://bugs.sun.com> for details.

This is an issue with your installation of Java and does not affect the Oracle Retail product installation.

## Warning: Couldn't find X Input Context

### Symptom

The following text appears in the console window during execution of the installer in GUI mode:

```
Couldn't find X Input Context
```

### Solution

This message is harmless and can be ignored.

## ConcurrentModificationException in Installer GUI

### Symptom

In GUI mode, the errors tab shows the following error:

```
java.util.ConcurrentModificationException
    at
java.util.AbstractList$Itr.checkForComodification(AbstractList.java:448)
    at java.util.AbstractList$Itr.next(AbstractList.java:419)
... etc
```

### Solution

You can ignore this error. It is related to third-party Java Swing code for rendering of the installer GUI and does not affect the retail product installation.

## A Second Login Screen Appears After Single Sign-On Login

If you are using Single Sign-On, you should not need to enter a SIM user name and password once SIM is launched. If the SIM login screen pops up, it means something went wrong with the SSO login. This could be caused by any of the following problems:

- There is no SIM user in LDAP for the SSO user name you are using.
- Permissions are not set up correctly for the SSO user in SIM.
- SSO is configured incorrectly on the server.
- SSO timed out. (This can happen especially the first time you launch SIM. Try launching SIM again.)

### Symptom

A second login screen appears after you have already logged in to Single Sign-On.

### Solution

See the *Oracle Retail Store Inventory Management Implementation Guide* for more information on setting up SIM users and using LDAP and SSO with SIM.

## Error Connecting to Database URL

### Symptom

After entering database credentials in the installer screens and hitting next, a message pops up with an error like this:

```
Error connecting to database URL <url> as user <user> details...
```

The message prevents you from moving on to the next screen to continue the installation.

### Solution

This error occurs when the installer fails to validate the user credentials you have entered on the screen. Make sure that you have entered the credentials properly. If you receive a message similar to this:

```
Error connecting to database URL <url> as user <user> java.lang.Exception:  
UnsatisfiedLinkError encountered when using the Oracle driver.  
Please check that the library path is set up properly or switch to the JDBC thin  
client.
```

It may mean that the installer is using the incorrect library path variables for the platform you are installing on. Open the file `<STAGING_DIR>/rms/dbschema/common/preinstall.sh` and toggle the variable, `use32bit`, to `True` if it is set to `False` or vice versa. This setting is dependent on the JRE that is being used.

## GUI screens fail to open when running Installer

### Symptom

When running the installer in GUI mode, the screens fail to open and the installer ends, returning to the console without an error message. The `ant.install.log` file contains this error:

```
Fatal exception: Width (0) and height (0) cannot be <= 0  
java.lang.IllegalArgumentException: Width (0) and height (0) cannot be <= 0
```

### Solution

This error is encountered when Antinstaller is used in GUI mode with certain X Servers. To work around this issue, copy `ant.install.properties.sample` to `ant.install.properties` and rerun the installer.

## Log in fails with invalid username/password or user unauthorized errors

### Symptom

The SIM application log in fails with the following messages: "Invalid username/password" or "User unauthorized or Not authenticated."

### Solution

In SIM Database, in the `CONFIG_SYSTEM` table, the value for `SECURITY_AUTHENTICATION_METHOD` should be set to 1 for LDAP authentication. Check in LDAP to be sure the password is set to the correct value.

---

---

# Appendix: Setting up SIM Reports/Tickets in BI Publisher

SIM 15.0.1 reports and ticket printing supports BiPublisher 11g.

## BiPublisher 11g – BI Server Component Installation Tasks

Oracle BI Publisher is used as the main RMS, RWMS, REIM, and SIM reporting engine and can be used in conjunction with external printing solutions like label printing. This section describes the installation of Oracle BI Publisher as a server application within WebLogic 10.3.6. One deployment of BI Publisher can be used for any of the RMS, RWMS, REIM, and SIM reports.

If you are installing BI Publisher as a part the Oracle OBIEE suite(which you will if installing BiPublisher 11g), refer to the appropriate Fusion Middleware guides for the installation of the product in a WebLogic server environment.

### BiPublisher 11g only - Installation Process Overview

Installing the BI Publisher server as a standalone web application in a WebLogic server involves the following tasks:

2. Run RCU to create BiPublisher related database schemas and other db objects.
3. Install Oracle BI EE under an existing Weblogic Server (WLS) 10.3.6 and choose “software only install”.
1. Configure Oracle BI EE, create default bifoundation\_domain and configure component “Business Intelligence Publisher” only.
2. Select the BIPlatform schema for update of the ORACLE 12.1.0.2 DB
3. Configure ports and document and test the URL’s that are created.

The following post-installation tasks are involved once BI Publisher has been installed:


4. Configure the BI Publisher repository. Set security model, add users, assign roles, add reports, add printers, set repository path, set data source, etc.
4. Set up the SIM reports in BiPublisher report repository.
5. Set up for the SIM application specific configuration files to integrate BI Publisher.

## BiPublisher 11g only – Install Oracle BI EE 11g

1. Run Repository Creation Utility (11.1.1.9.0) to create the BiPublisher-related database schemas and other database objects. Create the BIPlatform schema into an existing ORACLE 12c database.

**Note:** Download Repository Creation Utility software from <http://www.oracle.com/technetwork/middleware/bi-enterprise-edition/downloads/bi-downloads-2537285.html>. Install it on your desktop

2. Export your DISPLAY.  
Example: export DISPLAY=10.141.10.110:0.0
3. Launch Oracle BI EE RCU Repository Creation Utility to create the Oracle BI EE schemas need for the Oracle BiPublisher installation.
  - Go to \$RCU\_HOME/bin.  
Example: /linux/x86\_64/ofm\_11g/RCU\_11.1.1.9/rcuHome/bin>  
Start RCU: ./rcu
4. Click Next.




5. On this screen select Create Repository and Click Next




6. On the Database Connection Details screen, enter your Oracle Database information.




7. Click OK.




8. On the Select Components screen, select Oracle Business Intelligence check box and click Next.




9. Click OK.




10. Select Use same passwords for all schemas, enter in the password and click Next.




11. In the Map Tablespaces screen – accept the defaults by selecting Next.




12. Click OK.



13. Click OK.



14. The Summary of the Components created by the RCU tool is displayed. Click **Create**.



15. Click Close.




16. Install Oracle BI EE and select “Enterprise Install”. To initiate the Oracle BI EE installer – via command line navigate to:  
<OBIEE\_INSTALL>/obiee11.1.1.9/bishiphome/Disk1 and enter:  
./runInstaller

17. Click Next:




18. Select Skip Software Updates and click Next.




19. Select Enterprise Install and click Next.



20. Click Next.




21. Enter in credentials for Weblogic Admin and Domain Name:



22. Enter in the Oracle Middleware Home where you want to install Oracle BI EE and click **Next**.
  - Example: /u00/webadmin/product/wls\_obiee


**Note:** The remainder of the text entries will auto fill.



23. Select Business Intelligence Publisher only and click Next.



24. Enter the data base credentials of the BIPLATFORM schema.



## 25. Enter the Data base credentials for the MDS Schema.

1. Configure your BI ports. This screen allows you to assign Oracle BI EE ports from the staticports.ini file. Edit this file to make sure you will have the ports you want for your BiPublisher components. Otherwise the installer will assign default port numbers.

- This file is located in the Oracle BI EE software at:  
<OBIEE\_INSTALL>/obiee11.1.1.9/bishiphome/Disk1/stage/Response/staticports.ini.
- Only need to update the top section – See below for example for non-ssl setup:  
[WEBLOGIC]

#The Domain port no. This is the listen port of Weblogic Adminserver for the domain.

Domain Port No = 27001

#The "content" port for the BIEE apps. This is the Weblogic Managed Server port on which BIEE applications are deployed.

Oracle WLS BIEE Managed Server Port No = 29704

#The SSL port for the Weblogic Managed Server


#Oracle WLS BIEE Managed Server SSL Port No = 9804

#The Weblogic node manager port


Node Manager Port No = 9556




2. Uncheck software updates and Click Next.



3. Click Yes.



4. Click Install.




- The following screen will appear automatically and continue to the next screen.



- The following screen will appear automatically. Click Next when the button becomes enabled.




- The final Completion screen gives important details regarding file locations and Important URLs for managing the Weblogic server as well as URLs for xmlp server. Make sure to copy these details by using the Save button. Click **Finish**.



## Post Install Steps


- Test your BiPublisher installation, Get the xmlpserver url from your Installation Screen and launch xmlpserver. Login with the credentials you entered in your Oracle BI EE configuration (weblogic / password). Example URL: `http://[obiee_host]:[obiee_server_port]/xmlpserver`.




2. After sign on, select "Administration".




3. On the System Maintenance Section, click **Server Configuration**.




4. On this screen - In the Server Configuration Folder section, enter the path to your repository. On the Catalog section enter Catalog Type: Oracle BI Publisher – File System from the drop down menu.
  - This is the path you entered in the Configuration Section and Catalog Section:  
Example: `$<OBIEE_DOMAIN_HOME>/config/bipublisher/repository`
5. Click **Apply**.
6. Click **Administration** link at top of screen.



- Click on the Security Configuration link under the Security Center to setup a super user and apply the BI Publisher security model.



- Enable a Superuser by checking the “Enable Local Superuser” box and by entering name and password on the corresponding fields on this screen.
- Mark “Allow Guest Access” check box. Enter “Guest” as Guest Folder Name.
- Click **Apply**.
- Scroll down the screen and locate the Authorization section:



- Select BI Publisher Security from the Security Model list.
- The default user name for the BI Publisher Security Model is Administrator.
- On the password text field, enter a value that you can remember. It is going to be the password for Login to xmlpsrver.

15. Click **Apply**.
16. Restart WebLogic Server.

## Installing the SIM BI Publisher Templates

Manually copy SIM Reports to Reports repository using the instructions below:

The SIM reports will be copied to the 'Guest' location. Create a directory named 'SIM' under 'Guest' and copy the reports into 'SIM' directory:

```
example,  
/u00/webadmin/product/fmw/wls_obiee/user_projects/domains/bifoundation_domain/  
config/bipublisher/repository/Reports/Guest/SIM
```

The reports are included in the SIM application distribution in a zip file. Copy that file from where you installed the SIM application into the new report directory and unzip it:  
#

The following are the steps to extract the bip11g reports and copy them to the BIP11g repository:

```
cp <SIM15_MEDIA>/sim/application/sim15/reports/sim-reports.zip <TEMP_DIR> Where  
<TEMP_DIR> is a temporary directory where extract sim-reports.zip is extracted.  
cd <TEMP_DIR>  
unzip sim-reports.zip  
cd <TEMP_DIR>/bip11g  
cp *  
/u00/webadmin/product/fmw/wls_obiee/user_projects/domains/bifoundation_domain/conf  
ig/bipublisher/repository/Reports/Guest/SIM
```

## Create the User and Role Required for the SIM Application to Run Reports

In order for reports to be printed to a printer from the SIM application – a BI Publisher user will need to be created with a role that has the correct permissions to schedule and execute BI Publisher reports. The following are instructions on how to create the user/role: .

1. Log into BiPublisher as the Superuser that was created in prior security setup steps.


---

---

**Note:** You will not be able to login to xmlpserver as weblogic any more because we have already changed the Security Model.

---


---




2. Click the **Administration** link at top of screen.




3. Click on **Roles and Permissions** link.




4. Click **Create Role**.



5. Enter in a Name (example: Bipub\_default\_role) and click **Apply**.




6. Click the icon under the **Add Roles** column.




7. Move the following roles to the Included Roles and click **Apply**:


- BI Publisher Administrator
- BI Publisher Online Analyzer
- BI Publisher Scheduler




8. Click on the icon under the **Add Data Sources** column.




9. Add the BIP-SIM-DATASOURCE to the Allowed Data Source column and click **Apply**.



10. Click the **Users** tab to add a user.




11. Click Create User.




12. Add in a username and password and click **Apply**.

- Very Important: The username and password entered here has to be very specifically created to match the username and password that is entered in to the Sim Application Installer during installation time for the Ticket Printing User Name and Reports User Name. If different users are created during installation – each user will need to be created.



13. Click Assign Roles.



14. Move the newly created Bipub\_default\_role to the Assigned Roles column and click Apply.

### Configuring the BIP-SIM-DATASOURCE JDBC connection


Follow the below steps to configure a JDBC connection for the SIM Data Source, which is required for SIM reports.

1. Login as the super user that was created in prior security setup steps.

---

**Note:** You will not be able to login to xmlpserver as weblogic any more because we have already changed the Security Model.


---




2. Click the **Administration** link at top of screen.



3. Select the JDBC Connection hyperlink in the Data Sources lists.



4. Click the Add Data Source button.



5. Enter the appropriate details for the SIM data source. Click Test Connection to test the connection on the screen once the data is entered.

Data Source Name: BIP-SIM-DATASOURCE

- Must be BIP-SIM-DATASOURCE due to code dependencies.

Driver type is ORACLE 11g

Database driver class should be oracle.jdbc.OracleDriver.

Connection string is similar to this example:


- Pluggable: jdbc:oracle:thin:@dbhostname:1521/servicename
- Non- Pluggable dbc:oracle:thin:@dbhostname:1521:SID

Enter the username and password for the SIM application user's data source.


Click Test Connection to test the connection on the screen once the data is entered.

6. Scroll to the bottom of the screen:


- Check the Allow Guest Access check box
- Add the Bipub\_default\_role to the Allowed Roles column
- Click **Apply**.



7. Click Catalog link at the top of the screen – and then click the Guest folder on the left so that it is highlighted.



8. Click the Permissions link on the lower left of the screen.




9. Click OK.

10. Restart WebLogic Server.


## Configuring SIM for CUPS printers using BiPublisher 11g

Prerequisite: CUPS printer has to be set up on the host that the BiPublisher application is installed on.


1. Login to BI Publisher using the Super user that was created earlier and Click the Administration link at the top of the screen.



2. Click on the CUPS Server under the Delivery section.




3. Click Add Servers.



4. Enter in values and click **Apply**:

- Server Name: SIMCUP
  - Can be any name
- Host: localhost
- Port: 631
  - 631 is default port that is used as an example – This may be different on the host.

5. After adding, refresh the servers and printers.



---

---

## Appendix: Single Sign-On for WebLogic

Single Sign-On (SSO) is a term for the ability to sign onto multiple Web applications via a single user ID/Password. There are many implementations of SSO. Oracle provides an implementation with Oracle Access Manager.

Most, if not all, SSO technologies use a session cookie to hold encrypted data passed to each application. The SSO infrastructure has the responsibility to validate these cookies and, possibly, update this information. The user is directed to log on only if the cookie is not present or has become invalid. These session cookies are restricted to a single browser session and are never written to a file.

Another facet of SSO is how these technologies redirect a user's Web browser to various servlets. The SSO implementation determines when and where these redirects occur and what the final screen shown to the user is.

Most SSO implementations are performed in an application's infrastructure and not in the application logic itself. Applications that leverage infrastructure managed authentication (such as deployment specifying Basic or Form authentication) typically have little or no code changes when adapted to work in an SSO environment.

### What Do I Need for Single Sign-On?

A Single Sign-On system involves the integration of several components, including Oracle Identity Management and Oracle Access Management. This includes the following components:

- An Oracle Internet Directory (OID) LDAP server, used to store user, role, security, and other information. OID uses an Oracle database as the back-end storage of this information.
- An Oracle Access Manager (OAM) 11g Release 2 server and administrative console for implementing and configuring policies for single sign-on.
- A Policy Enforcement Agent such as Oracle Access Manager 11g Agent (WebGate), used to authenticate the user and create the Single Sign-On cookies.
- Oracle Directory Services Manager (ODSM) application in OIM11g, used to administer users and group information. This information may also be loaded or modified via standard LDAP Data Interchange Format (LDIF) scripts.
- Additional administrative scripts for configuring the OAM system and registering HTTP servers.

Additional WebLogic managed servers will be needed to deploy the business applications leveraging the Single Sign-On technology.

### Can Oracle Access Manager Work with Other SSO Implementations?

Yes, Oracle Access Manager has the ability to interoperate with many other SSO implementations, but some restrictions exist.

## Oracle Single Sign-on Terms and Definitions

The following terms apply to single sign-on.

### **Authentication**

Authentication is the process of establishing a user's identity. There are many types of authentication. The most common authentication process involves a user ID and password.

### **Dynamically Protected URLs**

A Dynamically Protected URL is a URL whose implementing application is aware of the Oracle Access Manager environment. The application may allow a user limited access when the user has not been authenticated. Applications that implement dynamic protection typically display a Login link to provide user authentication and gain greater access to the application's resources.

### **Oracle Identity Management (OIM) and Oracle Access Manager (OAM) for 11g**

Oracle Identity Management (OIM) 11g includes Oracle Internet Directory and ODSM. Oracle Access Manager (OAM) 11g R2 should be used for SSO using WebGate. Oracle Forms 11g contains Oracle HTTP server and other Retail Applications will use Oracle WebTier11g for HTTP Server.

### **MOD\_WEBLOGIC**

mod\_WebLogic operates as a module within the HTTP server that allows requests to be proxied from the OracleHTTP server to the Oracle WebLogic server.

### **Oracle Access Manager 11g Agent (WebGate)**

Oracle WebGates are policy enforcement agents which reside with relying parties and delegate authentication and authorization tasks to OAM servers.

### **Oracle Internet Directory**

Oracle Internet Directory (OID) is an LDAP-compliant directory service. It contains user ids, passwords, group membership, privileges, and other attributes for users who are authenticated using Oracle Access Manager.

### **Partner Application**

A partner application is an application that delegates authentication to the Oracle Identity Management Infrastructure. One such partner application is the Oracle HTTP Server (OHS) supplied with Oracle Forms Server or WebTier11g Server if using other Retail Applications other than Oracle Forms Applications.

All partner applications must be registered with Oracle Access Manager (OAM) 11g. An output product of this registration is a configuration file the partner application uses to verify a user has been previously authenticated.

### **Statically Protected URLs**

A URL is considered to be Statically Protected when an Oracle HTTP server is configured to limit access to this URL to only SSO authenticated users. Any unauthenticated attempt to access a Statically Protected URL results in the display of a login page or an error page to the user.

Servlets, static HTML pages, and JSP pages may be statically protected.

## What Single Sign-On is not

Single Sign-On is NOT a user ID/password mapping technology.

However, some applications can store and retrieve user IDs and passwords for non-SSO applications within an OID LDAP server. An example of this is the Oracle Forms Web Application framework, which maps Single Sign-On user IDs to a database logins on a per-application basis.

## How Oracle Single Sign-On Works

Oracle Access Manager involves several different components. These are:

- The Oracle Access Manager (OAM) server, which is responsible for the back-end authentication of the user.
- The Oracle Internet Directory LDAP server, which stores user IDs, passwords, and group (role) membership.
- The Oracle Access Manager Agent associated with the Web application, which verifies and controls browser redirection to the Oracle Access Manager server.
- If the Web application implements dynamic protection, then the Web application itself is involved with the OAM system.


### About SSO Login Processing with OAM Agents

1. The user requests a resource.
2. Webgate forwards the request to OAM for policy evaluation
3. OAM:
  - a. Checks for the existence of an SSO cookie.
  - b. Checks policies to determine if the resource is protected and if so, how?
4. OAM Server logs and returns the decision
5. Webgate responds as follows:
  - **Unprotected Resource:** Resource is served to the user
  - **Protected Resource:**  
Resource is redirected to the credential collector.  
The login form is served based on the authentication policy.  
Authentication processing begins
6. User sends credentials
7. OAM verifies credentials
8. OAM starts the session and creates the following host-based cookies:
  - **One per partner:** OAMAuthnCookie set by 11g WebGates using authentication token received from the OAM Server after successful authentication.  
**Note:** A valid cookie is required for a session.
  - **One for OAM Server:** OAM\_ID
9. OAM logs Success or Failure.
10. Credential collector redirects to WebGate and authorization processing begins.
11. WebGate prompts OAM to look up policies, compare them to the user's identity, and determine the user's level of authorization.
12. OAM logs policy decision and checks the session cookie.
13. OAM Server evaluates authorization policies and cache the result.
14. OAM Server logs and returns decisions

15. WebGate responds as follows:

- If the authorization policy allows access, the desired content or applications are served to the user.
- If the authorization policy denies access, the user is redirected to another URL determined by the administrator.

### SSO Login Processing with OAM Agents



## Installation Overview

Installing an Oracle Retail supported Single Sign-On installation using OAM11g requires installation of the following:

1. Oracle Internet Directory (OID) LDAP server and the Oracle Directory Services Manager. They are typically installed using the Installer of Oracle Identity Management . The ODSM application can be used for user and realm management within OID.
2. Oracle Access Manager 11gR2 has to be installed and configured.
3. Additional midtier instances (such as Oracle Forms 11gr2) for Oracle Retail applications based on Oracle Forms technologies (such as RMS). These instances must be registered with the OAM installed in step 2.
4. Additional application servers to deploy other Oracle Retail applications and performing application specific initialization and deployment activities must be registered with OAM installed in step 2.

### Infrastructure Installation and Configuration

The Infrastructure installation for Oracle Access Manager (OAM) is dependent on the environment and requirements for its use. Deploying Oracle Access Manager (OAM) to be used in a test environment does not have the same availability requirements as for a production environment. Similarly, the Oracle Internet Directory (OID) LDAP server can be deployed in a variety of different configurations. See the *Oracle Identity Management Installation Guide*11g.

### OID User Data

Oracle Internet Directory is an [LDAP v3](#) compliant directory server. It provides standards-based user definitions out of the box.

Customers with existing corporate LDAP implementations may need to synchronize user information between their existing LDAP directory servers and OID. OID supports standard LDIF file formats and provides a JNDI compliant set of Java classes as well. Moreover, OID provides additional synchronization and replication facilities to integrate with other corporate LDAP implementations.

Each user ID stored in OID has a specific record containing user specific information. For role-based access, groups of users can be defined and managed within OID. Applications can thus grant access based on group (role) membership saving administration time and providing a more secure implementation.

## User Management

User Management consists of displaying, creating, updating or removing user information. There are many methods of managing an LDAP directory including LDIF scripts or Oracle Directory Services Manager (ODSM) available for OID11g.

### ODSM

Oracle Directory Services Manager (ODSM) is a Web-based application used in OID11g is designed for both administrators and users which enables you to configure the structure of the directory, define objects in the directory, add and configure users, groups, and other entries. ODSM is the interface you use to manage entries, schema, security, adapters, extensions, and other directory features.

### **LDIF Scripts**

Script based user management can be used to synchronize data between multiple LDAP servers. The standard format for these scripts is the LDAP Data Interchange Format (LDIF). OID supports LDIF script for importing and exporting user information. LDIF scripts may also be used for bulk user load operations.

### **User Data Synchronization**

The user store for Oracle Access Manager resides within the Oracle Internet Directory (OID) LDAP server. Oracle Retail applications may require additional information attached to a user name for application-specific purposes and may be stored in an application-specific database. Currently, there are no Oracle Retail tools for synchronizing changes in OID stored information with application-specific user stores. Implementers should plan appropriate time and resources for this process. Oracle Retail strongly suggests that you configure any Oracle Retail application using an LDAP for its user store to point to the same OID server used with Oracle Access Manager.

---

---

## Appendix: Setting Up Password Stores with wallets/credential stores

As part of an application installation, administrators must set up password stores for user accounts using wallets/credential stores. Some password stores must be installed on the application database side. While the installer handles much of this process, the administrators must perform some additional steps.

Password stores for the application and application server user accounts must also be installed; however, the installer takes care of this entire process.

ORACLE Retail Merchandising applications now have 3 different types of password stores. They are database wallets, java wallets, and database credential stores. Background and how to administer them below are explained in this appendix

### About Database Password Stores and Oracle Wallet

Oracle databases have allowed other users on the server to see passwords in case database connect strings (username/password@db) were passed to programs. In the past, users could navigate to `ps -ef |grep <username>` to see the password if the password was supplied in the command line when calling a program.

To make passwords more secure, Oracle Retail has implemented the Oracle Software Security Assurance (OSSA) program. Sensitive information such as user credentials now must be encrypted and stored in a secure location. This location is called password stores or wallets. These password stores are secure software containers that store the encrypted user credentials.

Users can retrieve the credentials using aliases that were set up when encrypting and storing the user credentials in the password store. For example, if `username/password@db` is entered in the command line argument and the alias is called `db_username`, the argument to a program is as follows:

```
sqlplus /@db_username
```

This would connect to the database as it did previously, but it would hide the password from any system user.

After this is configured, as in the example above, the application installation and the other relevant scripts are no longer needed to use embedded usernames and passwords. This reduces any security risks that may exist because usernames and passwords are no longer exposed.

When the installation starts, all the necessary user credentials are retrieved from the Oracle Wallet based on the alias name associated with the user credentials.

There are three different types of password stores. One type explain in the next section is for database connect strings used in program arguments (such as `sqlplus /@db_username`). The others are for Java application installation and application use.

## Setting Up Password Stores for Database User Accounts

After the database is installed and the default database user accounts are set up, administrators must set up a password store using the Oracle wallet. This involves assigning an alias for the username and associated password for each database user account. The alias is used later during the application installation. This password store must be created on the system where the application server and database client are installed.

This section describes the steps you must take to set up a wallet and the aliases for the database user accounts. For more information on configuring authentication and password stores, see the *Oracle Database Security Guide*.

---

---

**Note:** In this section, <wallet\_location> is a placeholder text for illustration purposes. Before running the command, ensure that you specify the path to the location where you want to create and store the wallet.

---

---

To set up a password store for the database user accounts, perform the following steps:

1. Create a wallet using the following command:

```
mkstore -wrl <wallet_location> -create
```

After you run the command, a prompt appears. Enter a password for the Oracle Wallet in the prompt.

---

---

**Note:** The `mkstore` utility is included in the Oracle Database Client installation.

---

---

The wallet is created with the auto-login feature enabled. This feature enables the database client to access the wallet contents without using the password. For more information, refer to the *Oracle Database Advanced Security Administrator's Guide*.

2. Create the database connection credentials in the wallet using the following command:

```
mkstore -wrl <wallet_location> -createCredential <alias-name> <database-user-name>
```

After you run the command, a prompt appears. Enter the password associated with the database user account in the prompt.

3. Repeat Step 2 for all the database user accounts.
4. Update the `sqlnet.ora` file to include the following statements:

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA = (DIRECTORY =  
<wallet_location>)))  
SQLNET.WALLET_OVERRIDE = TRUE  
SSL_CLIENT_AUTHENTICATION = FALSE
```

5. Update the `tnsnames.ora` file to include the following entry for each alias name to be set up.

```
<alias-name> =  
  (DESCRIPTION =  
    (ADDRESS_LIST =  
      (ADDRESS = (PROTOCOL = TCP) (HOST = <host>) (PORT = <port>))  
    )  
    (CONNECT_DATA =  
      (SERVICE_NAME = <service>)  
    )  
  )
```

In the previous example, <alias-name>, <host>, <port>, and <service> are placeholder text for illustration purposes. Ensure that you replace these with the relevant values.

## Setting up Wallets for Database User Accounts

The following examples show how to set up wallets for database user accounts for the following applications:

- For RMS, RWMS, RPM Batch using sqlplus or sqlldr, RETL, RMS, RWMS, and ARI

### For RMS, RWMS, RPM Batch using sqlplus or sqlldr, RETL, RMS, RWMS, and ARI

To set up wallets for database user accounts, do the following.

1. Create a new directory called wallet under your folder structure.

```
cd /projects/rms15/dev/
mkdir .wallet
```

---

**Note:** The default permissions of the wallet allow only the owner to use it, ensuring the connection information is protected. If you want other users to be able to use the connection, you must adjust permissions appropriately to ensure only authorized users have access to the wallet.

---

2. Create a sqlnet.ora in the wallet directory with the following content.

```
WALLET_LOCATION = (SOURCE = (METHOD = FILE) (METHOD_DATA =
(DIRECTORY = /projects/rms15/dev/.wallet)) )
SQLNET.WALLET_OVERRIDE=TRUE
SSL_CLIENT_AUTHENTICATION=FALSE
```

---

**Note:** WALLET\_LOCATION must be on line 1 in the file.

---

3. Setup a tnsnames.ora in the wallet directory. This tnsnames.ora includes the standard tnsnames.ora file. Then, add two custom tns\_alias entries that are only for use with the wallet. For example, sqlplus /@dvols29\_rms01user.

```
ifile = /u00/oracle/product/12.1.0.2/network/admin/tnsnames.ora
```

Examples for a NON pluggable db:

```
dvols29_rms01user =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = xxxxxx.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SID = <sid_name> (GLOBAL_NAME = <sid_name>))))
```

```
dvols29_rms01user.world =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = xxxxxx.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SID = <sid_name> (GLOBAL_NAME = <sid_name>))))
```

Examples for a pluggable db:

```
dvols29_rms01user =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = xxxxxx.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SERVICE_NAME = <pluggable db name>)))
```

```
dvols29_rms01user.world =
  (DESCRIPTION = (ADDRESS_LIST = (ADDRESS = (PROTOCOL = tcp)
    (host = xxxxxx.us.oracle.com) (Port = 1521)))
    (CONNECT_DATA = (SERVICE_NAME = <pluggable db name>)))
```

---

**Note:** It is important to not just copy the tnsnames.ora file because it can quickly become out of date. The ifile clause (shown above) is key.

---

4. Create the wallet files. These are empty initially.
  - a. Ensure you are in the intended location.

```
$ pwd
/projects/rms15/dev/.wallet
```
  - b. Create the wallet files.

```
$ mkstore -wrl . -create
```
  - c. Enter the wallet password you want to use. It is recommended that you use the same password as the UNIX user you are creating the wallet on.
  - d. Enter the password again.

Two wallet files are created from the above command:

    - ewallet.p12
    - cwallet.sso
5. Create the wallet entry that associates the user name and password to the custom tns alias that was setup in the wallet's tnsnames.ora file.

```
mkstore -wrl . -createCredential <tns_alias> <username> <password>
```

---

**Example:** `mkstore -wrl . -createCredential dvols29_rms01user rms01user passwd`

---

6. Test the connectivity. The ORACLE\_HOME used with the wallet must be the same version or higher than what the wallet was created with.

```
$ export TNS_ADMIN=/projects/rms15/dev/.wallet /* This is very import to use
wallet to point at the alternate tnsnames.ora created in this example */
```

```
$ sqlplus /@dvols29_rms01user
```

```
SQL*Plus: Release 12
```

```
Connected to:
Oracle Database 12g
```

```
SQL> show user
USER is "rms01user"
```

Running batch programs or shell scripts would be similar:

```
Ex: dtesys /@dvols29_rms01user
script.sh /@dvols29_rms01user
```

Set the UP unix variable to help with some compiles :

```
export UP=/@dvols29_rms01user
for use in RMS batch compiles, and RMS, RWMS, and ARI forms compiles.
```

As shown in the example above, users can ensure that passwords remain invisible.

### Additional Database Wallet Commands

The following is a list of additional database wallet commands.

- Delete a credential on wallet

```
mkstore -wrl . -deleteCredential dvols29_rms01user
```

- Change the password for a credential on wallet

```
mkstore -wrl . -modifyCredential dvols29_rms01user rms01user passwd
```

- List the wallet credential entries

```
mkstore -wrl . -list
```

This command returns values such as the following.

```
oracle.security.client.connect_string1
oracle.security.client.user1
oracle.security.client.password1
```

- View the details of a wallet entry

```
mkstore -wrl . -viewEntry oracle.security.client.connect_string1
```

Returns the value of the entry:

```
dvols29_rms01user
```

```
mkstore -wrl . -viewEntry oracle.security.client.user1
```

Returns the value of the entry:

```
rms01user
```

```
mkstore -wrl . -viewEntry oracle.security.client.password1
```

Returns the value of the entry:

```
Passwd
```

## Setting up RETL Wallets

RETL creates a wallet under \$RFX\_HOME/etc/security, with the following files:

- cwallet.sso
- jazn-data.xml
- jps-config.xml
- README.txt

To set up RETL wallets, perform the following steps:

1. Set the following environment variables:
  - ORACLE\_SID=<retaildb>
  - RFX\_HOME=/u00/rfx/rfx-13
  - RFX\_TMP=/u00/rfx/rfx-13/tmp
  - JAVA\_HOME=/usr/jdk1.6.0\_12.64bit
  - LD\_LIBRARY\_PATH=\$ORACLE\_HOME
  - PATH=\$RFX\_HOME/bin:\$JAVA\_HOME/bin:\$PATH
2. Change directory to \$RFX\_HOME/bin.
3. Run setup-security-credential.sh.
  - Enter 1 to add a new database credential.
  - Enter the dbuseralias. For example, ret1\_java\_rms01user.
  - Enter the database user name. For example, rms01user.
  - Enter the database password.
  - Re-enter the database password.
  - Enter D to exit the setup script.

4. Update your RETL environment variable script to reflect the names of both the Oracle Networking wallet and the Java wallet.

For example, to configure RETLforRPAS, modify the following entries in `$RETAIL_HOME/RETLforRPAS/rfx/etc/rmse_rpas_config.env`.

- The RETL\_WALLET\_ALIAS should point to the Java wallet entry:
    - `export RETL_WALLET_ALIAS="retl_java_rms01user"`
  - The ORACLE\_WALLET\_ALIAS should point to the Oracle network wallet entry:
    - `export ORACLE_WALLET_ALIAS="dvols29_rms01user"`
  - The SQLPLUS\_LOGON should use the ORACLE\_WALLET\_ALIAS:
    - `export SQLPLUS_LOGON="/@${ORACLE_WALLET_ALIAS}"`
5. To change a password later, run `setup-security-credential.sh`.
    - Enter 2 to update a database credential.
    - Select the credential to update.
    - Enter the database user to update or change.
    - Enter the password of the database user.
    - Re-enter the password.

## For Java Applications (SIM, ReIM, RPM, RIB, AIP, Alloc, ReSA, RETL)

For Java applications, consider the following:

- For database user accounts, ensure that you set up the same alias names between the password stores (database wallet and Java wallet). You can provide the alias name during the installer process.
- Document all aliases that you have set up. During the application installation, you must enter the alias names for the application installer to connect to the database and application server.
- Passwords are not used to update entries in Java wallets. Entries in Java wallets are stored in partitions, or application-level keys. In each retail application that has been installed, the wallet is located in `<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/config` Example:  
`/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15/config`
- Application installers should create the Java wallets for you, but it is good to know how this works for future use and understanding.
- Scripts are located in `<WEBLOGIC_DOMAIN_HOME>/retail/<appname>/retail-public-security-api/bin` for administering wallet entries.
- Example:
  - `/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/retail-public-security-api/bin`
  - In this directory is a script to help you update each alias entry without having to remember the wallet details. For example, if you set the RPM database alias to `rms01user`, you will find a script called `update-RMS01USER.sh`.

---

**Note:** These scripts are available only with applications installed by way of an installer.

---

- Two main scripts are related to this script in the folder for more generic wallet operations: `dump_credentials.sh` and `save_credential.sh`.

- If you have not installed the application yet, you can unzip the application zip file and view these scripts in <app>/application/retail-public-security-api/bin.
- Example:
- /u00/webadmin/reim15/application/retail-public-security-api/bin

### update-<ALIAS>.sh

update-<ALIAS>.sh updates the wallet entry for this alias. You can use this script to change the user name and password for this alias. Because the application refers only to the alias, no changes are needed in application properties files.

Usage:

```
update-<username>.sh <myuser>
```

Example:

```
/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15/retail-public-security-api/bin> ./update-RMS01USER.sh
```

```
usage: update-RMS01USER.sh <username>
```

```
<username>: the username to update into this alias.
```

```
Example: update-RMS01USER.sh myuser
```

Note: this script will ask you for the password for the username that you pass in.

```
/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15/retail-public-security-api/bin>
```

### dump\_credentials.sh

dump\_credentials.sh is used to retrieve information from wallet. For each entry found in the wallet, the wallet partition, the alias, and the user name are displayed.

Note that the password is not displayed. If the value of an entry is uncertain, run save\_credential.sh to resave the entry with a known password.

```
dump_credentials.sh <wallet location>
```

Example:

```
dump_credentials.sh location:
```

```
/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15/config
```

```
Retail Public Security API Utility
```

```
=====
```

```
Below are the credentials found in the wallet at the
location/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15c
onfig
```

```
=====
```

```
Application level key partition name:reim15
User Name Alias:WLS-ALIAS User Name:weblogic
User Name Alias:RETAIL-ALIAS User Name:retail.user
User Name Alias:LDAP-ALIAS User Name:RETAIL.USER
User Name Alias:RMS-ALIAS User Name:rms15mock
User Name Alias:REIMBAT-ALIAS User Name:reimbat
```

**save\_credential.sh**

save\_credential.sh is used to update the information in wallet. If you are unsure about the information that is currently in the wallet, use dump\_credentials.sh as indicated above.

```
save_credential.sh -a <alias> -u <user> -p <partition name> -l <path of the
wallet file location where credentials are stored>
```

Example:

```
/u00/webadmin/mock15_testing/reim15/application/retail-public-security-api/bin>
save_credential.sh -l wallet_test -a myalias -p mypartition -u myuser
```

```
=====
Retail Public Security API Utility
=====
```

```
Enter password:
Verify password:
```

---

**Note:** -p in the above command is for partition name. You must specify the proper partition name used in application code for each Java application.

save\_credential.sh and dump\_credentials.sh scripts are the same for all applications. If using save\_credential.sh to add a wallet entry or to update a wallet entry, bounce the application/managed server so that your changes are visible to the application. Also, save a backup copy of your cwallet.sso file in a location outside of the deployment path, because redeployment or reinstallation of the application will wipe the wallet entries you made after installation of the application. To restore your wallet entries after a redeployment/reinstallation, copy the backed up cwallet.sso file over the cwallet.sso file. Then bounce the application/managed server.

---

**Usage**

```
=====
Retail Public Security API Utility
=====
usage: save_credential.sh -au[plh]
E.g. save_credential.sh -a rms-alias -u rms_user -p rib-rms -l ./
-a,--userNameAlias <arg>          alias for which the credentials
needs to be stored
-h,--help                          usage information
-l,--locationofWalletDir <arg>     location where the wallet file is
created.If not specified, it creates the wallet under secure-credential-wallet
directory which is already present under the retail-public-security-api/
directory.
-p,--appLevelKeyPartitionName <arg> application level key partition name
-u,--userName <arg>                username to be stored in secure
credential wallet for specified alias*
```

## How does the Wallet Relate to the Application?

The ORACLE Retail Java applications have the wallet alias information you create in an <app-name>.properties file. Below is the reim.properties file. Note the database information and the user are presented as well. The property called `datasource.credential.alias=RMS-ALIAS` uses the ORACLE wallet with the argument of RMS-ALIAS at the `csm.wallet.path` and `csm.wallet.partition.name = reim14` to retrieve the password for application use.

Reim.properties code sample:

```
datasource.url=jdbc:oracle:thin:@xxxxxxx.us.oracle.com:1521:pkols07
datasource.schema.owner=rms15mock
datasource.credential.alias=RMS-ALIAS
# =====
# ossa related Configuration
#
# These settings are for ossa configuration to store credentials.
# =====

csm.wallet.path=/u00/webadmin/config/domains/wls_retail/REIMDomain/retail/reim15co
nfig
csm.wallet.partition.name=reim15
```

## How does the Wallet Relate to Java Batch Program use?


Some of the ORACLE Retail Java batch applications have an alias to use when running Java batch programs. For example, alias REIMBAT-ALIAS maps through the wallet to dbuser RMS01APP, already on the database. To run a ReIM batch program the format would be: `reimbatchpgmname REIMBAT-ALIAS <other arguments as needed by the program in question>`

## Database Credential Store Administration


The following section describes a domain level database credential store. This is used in RPM login processing, SIM login processing, RWMS login processing, RESA login processing and Allocation login processing and policy information for application permission. Setting up the database credential store is addressed in the RPM, SIM, RESA, RWMS, and Alloc 15.0.1 install guides.

The following sections show an example of how to administer the password stores thru ORACLE Enterprise Manger Fusion Middleware Control, a later section will show how to do this thru WLST scripts.

1. The first step is to use your link to Oracle Enterprise Manager Fusion Middleware Control for the domain in question. Locate your domain on the left side of the screen and do a right mouse click on the domain and select **Security > Credentials**




2. Click on Credentials and you will get a screen similar to the following. The following screen is expanded to make it make more sense. From here you can administer credentials.



The Create Map add above is to create a new map with keys under it. A map would usually be an application such as rpm15. The keys will usually represent alias to various users (database user, WebLogic user, LDAP user, etc). The application installer should add the maps so you should not often have to add a map.

Creation of the main keys for an application will also be built by the application installer. You will not be adding keys often as the installer puts the keys out and the keys talk to the application. You may be using EDIT on a key to see what user the key/alias points to and possibly change/reset its password. To edit a key/alias, highlight the key/alias in question and push the edit icon nearer the top of the page. You will then get a screen as follows:



The screen above shows the map (rpm) that came from the application installer, the key (DB-ALIAS) that came from the application installer (some of the keys/alias are selected by the person who did the application install, some are hard coded by the application installer in question), the type (in this case password), and the user name and password. This is where you would check to see that the user name is correct and reset the password if needed. REMEMBER, a change to an item like a database password WILL make you come into this and also change the password. Otherwise your application will NOT work correctly.

## Managing Credentials with WSLT/OPSS Scripts

This procedure is optional as you can administer the credential store through the Oracle enterprise manager associated with the domain of your application install for ReIM , RPM, SIM, RESA, or Allocation.

An Oracle Platform Security Scripts (OPSS) script is a WLST script, in the context of the Oracle WebLogic Server. An online script is a script that requires a connection to a running server. Unless otherwise stated, scripts listed in this section are online scripts and operate on a database credential store. There are a few scripts that are offline, that is, they do not require a server to be running to operate.

Read-only scripts can be performed only by users in the following WebLogic groups: Monitor, Operator, Configurator, or Admin. Read-write scripts can be performed only by users in the following WebLogic groups: Admin or Configurator. All WLST scripts are available out-of-the-box with the installation of the Oracle WebLogic Server.

WLST scripts can be run in interactive mode or in script mode. In interactive mode, you enter the script at a command-line prompt and view the response immediately after. In

script mode, you write scripts in a text file (with a py file name extension) and run it without requiring input, much like the directives in a shell script.

The weakness with the WSLT/OPSS scripts is that you have to already know your map name and key name. In many cases, you do not know or remember that. The database credential store way through enterprise manager is a better way to find your map and key names easily when you do not already know them. A way in a command line mode to find the map name and alias is to run orapki. An example of orapki is as follows:

```
/u00/webadmin/product/wls_apps/oracle_common/bin> ./orapki wallet display -
wallet
/u00/webadmin/product/wls_apps/user_projects/domains/APPDomain/config/fmw
config
```

(where the path above is the domain location of the wallet)

Output of orapki is below. This shows map name of rpm and each alias in the wallet:

Requested Certificates:

User Certificates:

Oracle Secret Store entries:

```
rpm@#3#@DB-ALIAS
rpm@#3#@LDAP-ALIAS
rpm@#3#@RETAIL.USER
rpm@#3#@user.signature.salt
rpm@#3#@user.signature.secretkey
rpm@#3#@WEBLOGIC-ALIAS
rpm@#3#@WLS-ALIAS
```

Trusted Certificates:

Subject: OU=Class 1 Public Primary Certification Authority,O=VeriSign\, Inc.,C=US

OPSS provides the following scripts on all supported platforms to administer credentials (all scripts are online, unless otherwise stated). You need the map name and the key name to run the scripts below

- listCred
- updateCred
- createCred
- deleteCred
- modifyBootStrapCredential
- addBootStrapCredential

## listCred

The script `listCred` returns the list of attribute values of a credential in the credential store with given map name and key name. This script lists the data encapsulated in credentials of type password only.

### Script Mode Syntax

```
listCred.py -map mapName -key keyName
```

### Interactive Mode Syntax

```
listCred(map="mapName", key="keyName")
```

The meanings of the arguments (all required) are as follows:

- map specifies a map name (folder).
- key specifies a key name.

Examples of Use:

The following invocation returns all the information (such as user name, password, and description) in the credential with map name myMap and key name myKey:

```
listCred.py -map myMap -key myKey
```

The following example shows how to run this command and similar credential commands with WLST:

```
/u00/webadmin/product/wls_apps/oracle_common/common/bin>
sh wlst.sh
```

```
Initializing WebLogic Scripting Tool (WLST)...
```

```
Welcome to WebLogic Server Administration Scripting Shell
```

```
wls:/offline> connect('weblogic','password123','xxxxxx.us.oracle.com:17001')
Connecting to t3://xxxxxx.us.oracle.com:17001 with userid weblogic ...
Successfully connected to Admin Server 'AdminServer' that belongs to domain
'APPDomain'.
```

```
wls:/APPDomain/serverConfig> listCred(map="rpm",key="DB-ALIAS")
Already in Domain Runtime Tree
```

```
[Name : rms01app, Description : null, expiry Date : null]
PASSWORD:retail
```

```
*The above means for map rpm15 in APPDomain, alias DB-ALIAS points to database
user rms01app with a password of retail
```

## updateCred

The script updateCred modifies the type, user name, and password of a credential in the credential store with given map name and key name. This script updates the data encapsulated in credentials of type password only. Only the interactive mode is supported.

### Interactive Mode Syntax

```
updateCred(map="mapName", key="keyName", user="userName", password="passW",
[desc="description"])
```

The meanings of the arguments (optional arguments are enclosed by square brackets) are as follows:

- map specifies a map name (folder) in the credential store.
- key specifies a key name.
- user specifies the credential user name.
- password specifies the credential password.
- desc specifies a string describing the credential.

Example of Use:

The following invocation updates the user name, password, and description of the password credential with map name `myMap` and key name `myKey`:

```
updateCred(map="myMap", key="myKey", user="myUsr", password="myPassw")
```

## createCred

The script `createCred` creates a credential in the credential store with a given map name, key name, user name and password. This script can create a credential of type password only. Only the interactive mode is supported.

### Interactive Mode Syntax

```
createCred(map="mapName", key="keyName", user="userName", password="passW",  
[desc="description"])
```

The meanings of the arguments (optional arguments are enclosed by square brackets) are as follows:

- `map` specifies the map name (folder) of the credential.
- `key` specifies the key name of the credential.
- `user` specifies the credential user name.
- `password` specifies the credential password.
- `desc` specifies a string describing the credential.

Example of Use:

The following invocation creates a password credential with the specified data:

```
createCred(map="myMap", key="myKey", user="myUsr", password="myPassw")
```

## deleteCred

The script `deleteCred` removes a credential with given map name and key name from the credential store.

### Script Mode Syntax

```
deleteCred.py -map mapName -key keyName
```

### Interactive Mode Syntax

```
deleteCred(map="mapName", key="keyName")
```

The meanings of the arguments (all required) are as follows:

- `map` specifies a map name (folder).
- `key` specifies a key name.

Example of Use:

The following invocation removes the credential with map name `myMap` and key name `myKey`:

```
deleteCred.py -map myMap -key myKey
```

## modifyBootstrapCredential

The offline script `modifyBootstrapCredential` modifies the bootstrap credentials configured in the default `jps` context, and it is typically used in the following scenario: suppose that the policy and credential stores are LDAP-based, and the credentials to access the LDAP store (stored in the LDAP server) are changed. Then this script can be used to seed those changes into the bootstrap credential store.

This script is available in interactive mode only.

## Interactive Mode Syntax

```
modifyBootStrapCredential(jpsConfigFile="pathName", username="usrName",  
password="usrPass")
```

The meanings of the arguments (all required) are as follows:

- `jpsConfigFile` specifies the location of the file `jps-config.xml` relative to the location where the script is run. Example location:  
`/u00/webadmin/product/wls_apps/user_projects/domains/APPDomain/config/fmwconfig`. Example location of the bootstrap wallet is  
`/u00/webadmin/product/wls_apps/user_projects/domains/APPDomain/config/fmwconfig/bootstrap`
- `username` specifies the distinguished name of the user in the LDAP store.
- `password` specifies the password of the user.

Example of Use:

Suppose that in the LDAP store, the password of the user with distinguished name `cn=orcladmin` has been changed to `welcome1`, and that the configuration file `jps-config.xml` is located in the current directory. Then the following invocation changes the password in the bootstrap credential store to `welcome1`:

```
modifyBootStrapCredential(jpsConfigFile='./jps-config.xml',  
username='cn=orcladmin', password='welcome1')
```

Any output regarding the audit service can be disregarded.

## addBootStrapCredential

The offline script `addBootStrapCredential` adds a password credential with given map, key, user name, and user password to the bootstrap credentials configured in the default `jps` context of a `jps` configuration file.

Classloaders contain a hierarchy with parent classloaders and child classloaders. The relationship between parent and child classloaders is analogous to the object relationship of super classes and subclasses. The bootstrap classloader is the root of the Java classloader hierarchy. The Java virtual machine (JVM) creates the bootstrap classloader, which loads the Java development kit (JDK) internal classes and `java.*` packages included in the JVM. (For example, the bootstrap classloader loads `java.lang.String`.)

This script is available in interactive mode only.

### Interactive Mode Syntax

```
addBootStrapCredential(jpsConfigFile="pathName", map="mapName", key="keyName",  
username="usrName", password="usrPass")
```

The meanings of the arguments (all required) are as follows:

- `jpsConfigFile` specifies the location of the file `jps-config.xml` relative to the location where the script is run. Example location:  
`/u00/webadmin/product/wls_apps/user_projects/domains/APPDomain/config/fmwconfig`
- `map` specifies the map of the credential to add.
- `key` specifies the key of the credential to add.
- `username` specifies the name of the user in the credential to add.
- `password` specifies the password of the user in the credential to add.

Example of Use:

The following invocation adds a credential to the bootstrap credential store:

```
addBootStrapCredential(jpsConfigFile='./jps-config.xml', map='myMapName',  
key='myKeyName', username='myUser', password='myPass')
```

## Quick Guide for Retail Password Stores (db wallet, java wallet, DB credential stores)

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
<b>RMS batch</b>	DB	<RMS batch install dir (RETAIL_HOME)>/.wallet	n/a	<Database SID>_<Database schema owner>	<rms schema owner>	Compile, execution	Installer	n/a	Alias hard-coded by installer
<b>RMS forms</b>	DB	<forms install dir>/base/.wallet	n/a	<Database SID>_<Database schema owner>	<rms schema owner>	Compile	Installer	n/a	Alias hard-coded by installer
<b>ARI forms</b>	DB	<forms install dir>/base/.wallet	n/a	<Db_Ari01>	<ari schema owner>	Compile	Manual	ari-alias	
<b>RMWS forms</b>	DB	<forms install dir>/base/.wallet	n/a	<Database SID>_<Database schema owner>	<rwms schema owner>	Compile forms, execute batch	Installer	n/a	Alias hard-coded by installer
<b>RPM batch plsql and sqlldr</b>	DB	<RPM batch install dir>/.wallet	n/a	<rms schema owner alias>	<rms schema owner>	Execute batch	Manual	rms-alias	RPM plsql and sqlldr batches
<b>RWMS auto-login</b>	JAVA	<forms install dir>/base/.javawallet							
			<RWMS Installation name>	<RWMS database user alias>	<RWMS schema owner>	RWMS forms app to avoid dblogin screen	Installer	rwms15inst	
			<RWMS Installation name>	BI_ALIAS	<BI Publisher administrative user>	RWMS forms app to connect to BI Publisher	Installer	n/a	Alias hard-coded by installer

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
<b>AIP app</b>	JAVA	<weblogic domain home>/retail/<deployed aip app name>/config							Each alias must be unique
			aip	<AIP weblogic user alias>	<AIP weblogic user name>	App use	Installer	aip-weblogic-alias	
			aip	<AIP database schema user alias>	<AIP database schema user name>	App use	Installer	aip01user-alias	
			aip	<rib-aip weblogic user alias>	<rib-aip weblogic user name>	App use	Installer	rib-aip-weblogic-alias	
<b>RPM app</b>	DB credential store		Map=rpm or what you called the app at install time.	Many for app use					<weblogic domain home>/config/fmwc onfig/jps-config.xml has info on the credential store. This directory also has the domain cwallet.sso file.
<b>RPM app</b>	JAVA	<weblogic domain home>/retail/<deployed rpm app name>/config							Each alias must be unique
			rpm	<rpm weblogic user alias>	<rpm weblogic user name>	App use	Installer	rpm-weblogic-alias	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
			rpm	<rpm batch user name> is the alias. Yes, here alias name = user name	<rpm batch user name>	App, batch use	Installer	RETAIL.USER	
	JAVA	<retail_home>/orpatch/config/javaapp_rpm							Each alias must be unique
			retail_installer	<rpm weblogic user alias>	<rpm weblogic user name>	App use	Installer	weblogic-alias	
			retail_installer	<rms shema user alias>	<rms shema user name>	App, batch use	Installer	rms01user-alias	
			retail_installer	<reim batch user alias>	<reim batch user name>	App, batch use	Installer	reimbat-alias	
			retail_installer	<LDAP-ALIAS>	cn=rpm.admin,cn=Users,dc=us,dc=oracle,dc=com	LDAP user use	Installer	LDAP_ALIAS	
<b>ReIM app</b>	JAVA	<weblogic domain home>/retail/<deployed reim app name>/config							Each alias must be unique
			<installed app name, ex: reim>	<reim weblogic user alias>	<reim weblogic user name>	App use	Installer	weblogic-alias	
			<installed app name, ex: reim>	<rms shema user alias>	<rms shema user name>	App, batch use	Installer	rms01user-alias	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
			<installed app name, ex: reim>	<reim webservice validation user alias>	<reim webservice validation user name>	App use	Installer	reimwebser vice-alias	
			<installed app name, ex: reim>	<reim batch user alias>	<reim batch user name>	App, batch use	Installer	reimbat-alias	
			<installed app name, ex: reim>	<LDAP-ALIAS>	cn=REIM.A DMIN,cn=Users,dc=users,dc=oracle,dc=com	LDAP user use	Installer	LDAP_ALI AS	
	JAVA	<retail_home>/orpatch/conf/javaapp_reim							Each alias must be unique
			retail_installer	<reim weblogic user alias>	<reim weblogic user name>	App use	Installer	weblogic-alias	
			retail_installer	<rms shema user alias>	<rms shema user name>	App, batch use	Installer	rms01user-alias	
			retail_installer	<reim webservice validation user alias>	<reim webservice validation user name>	App use	Installer	reimwebser vice-alias	
			retail_installer	<reim batch user alias>	<reim batch user name>	App, batch use	Installer	reimbat-alias	
			retail_installer	<LDAP-ALIAS>	cn=REIM.A DMIN,cn=Users,dc=users,dc=oracle,dc=com	LDAP user use	Installer	LDAP_ALI AS	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
RESA app	DB credential store		Map=resaor what you called the app at install time	Many for login and policies					<weblogic domain home>/config/fmwconfig/jps-config.xml has info on the credential store. This directory also has the domain cwallet.sso file. The bootstrap directory under this directory has bootstrap cwallet.sso file.
RESA app	JAVA	<weblogic domain home>/retail/<deployed resa app name>/config							Each alias must be unique
			<installed app name>	<resa weblogic user alias>	<resa weblogic user name>	App use	Installer	wlsalias	
			<installed app name>	<resa schema db user alias>	<rmsdb shema user name>	App use	Installer	Resadb-alias	
			<installed app name>	<resa schema user alias>	<rmsdb shema user name>>	App use	Installer	resa-alias	
	JAVA	<retail_home>/orpatch/config/javaapp_resa							Each alias must be unique

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
			retail_installer	<resa weblogic user alias>	<resa weblogic user name>	App use	Installer	wlsalias	
			retail_installer	<resa schema db user alias>	<rmsdb shema user name>	App use	Installer	Resadb-alias	
	JAVA	<retail_home>/orpatch/config/javaapp_rasm							Each alias must be unique
			retail_installer	<alloc weblogic user alias>	<alloc weblogic user name>	App use	Installer	weblogic-alias	
<b>Alloc app</b>	DB credential store		Map=alloc or what you called the app at install time	Many for login and policies					<weblogic domain home>/config/fmwc onfig/jps-config.xml has info on the credential store. This directory also has the domain cwallet.sso file. The bootstrap directory under this directory has bootstrap cwallet.sso file.
<b>Alloc app</b>	JAVA	<weblogic domain home>/retail/config							Each alias must be unique

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
			<installed app name>	<alloc weblogic user alias>	<alloc weblogic user name>	App use	Installer	weblogic-alias	
			<installed app name>	<rms schema user alias>	<rms schema user name>	App use	Installer	dsallocAlias	
			<installed app name>	<alloc batch user alias>	<SYSTEM_ADMINISTRATOR>	Batch use	Installer	alloc14	
	JAVA	<retail_home>/orpatch/config/javaapp_alloc							Each alias must be unique
			retail_installer	<alloc weblogic user alias>	<alloc weblogic user name>	App use	Installer	weblogic-alias	
			retail_installer	<rms schema user alias>	<rms schema user name>	App use	Installer	dsallocAlias	
			retail_installer	<alloc batch user alias>	<SYSTEM_ADMINISTRATOR>	Batch use	Installer	alloc14	
	JAVA	<retail_home>/orpatch/config/javaapp_rasm							Each alias must be unique
			retail_installer	<alloc weblogic user alias>	<alloc weblogic user name>	App use	Installer	weblogic-alias	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
<b>SIM app</b>	DB credential store		Map=oracle.retail.sim	Aliases required for SIM app use					<weblogic domain home>/config/fmwc onfig/jps-config.xml has info on the credential store. This directory also has the domain cwallet.sso file.
	JAVA	<weblogic domain home>/retail/<deployed sim app name>/batch/resources/conf	oracle.retail.sim	<sim batch user alias>	<sim batch user name>	App use	Installer	BATCH-ALIAS	
	JAVA	<weblogic domain home>/retail/<deployed sim app name>/wireless/resources/conf	oracle.retail.sim	<sim wireless user alias>	<sim wireless user name>	App use	Installer	WIRELESS-ALIAS	
<b>RETL</b>	JAVA	<RETL home>/etc/security	n/a	<target application user alias>	<target application db userid>	App use	Manual	retl_java_rms01user	User may vary depending on RETL flow's target application
<b>RETL</b>	DB	<RETL home>/wallet	n/a	<target application user alias>	<target application db userid>	App use	Manual	<db>_<user>	User may vary depending on RETL flow's target application
<b>RIB</b>	JAVA	<RIBHOME DIR>/deployment-home/conf/security							<app> is one of aip, rfm, rms, rpm, sim, rwms, tafr
<b>JMS</b>			jms<1-5>	<jms user alias> for jms<1-5>	<jms user name> for jms<1-5>	Integration use	Installer	jms-alias	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
WebLogic			rib-<app>-app-server-instance	<rib-app weblogic user alias>	<rib-app weblogic user name>	Integration use	Installer	weblogic-alias	
Admin GUI			rib-<app>#web-app-user-alias	<rib-app admin gui user alias>	<rib-app admin gui user name>	Integration use	Installer	admin-gui-alias	
Application			rib-<app>#user-alias	<app weblogic user alias>	<app weblogic user name>	Integration use	Installer	app-user-alias	Valid only for aip, rpm, sim
DB			rib-<app>#app-db-user-alias	<rib-app database schema user alias>	<rib-app database schema user name>	Integration use	Installer	db-user-alias	Valid only for rfm, rms, rwms, tafr
Error Hospital			rib-<app>#hosp-user-alias	<rib-app error hospital database schema user alias>	<rib-app error hospital database schema user name>	Integration use	Installer	hosp-user-alias	
RFI	Java	<RFI-HOME>/retail-financial-integration-solution/service-based-integration/conf/security							
			<installed app name>	rfiAppServerAdminServerUserAlias	<rfi weblogic user name>	App use	Installer	rfiAppServerAdminServerUserAlias	
			<installed app name>	rfiAdminUiUserAlias	<ORFI admin user>	App use	Installer	rfiAdminUiUserAlias	
			<installed app name>	rfiDataSourceUserAlias	<ORFI schema user name>	App use	Installer	rfiDataSourceUserAlias	

Retail app	Wallet type	Wallet loc	Wallet partition	Alias name	User name	Use	Create by	Alias Example	Notes
			<installed app name>	ebsDataSourceUserAlias	<EBS schema user name>	App use	Installer	ebsDataSourceUserAlias	
			<installed app name>	smtpMailFromAddressAlias	<From email address>	App use	Installer	smtpMailFromAddressAlias	

## Appendix: Tablespace Creation

### Non-Encrypted Tablespace Creation

Standard SIM tablespaces are created using the create\_tablespaces.sql script located in <INSTALL\_DIR>/sim/dbschema/dbutils /.

1. Update the paths of the script in <INSTALL\_DIR>/sim/dbschema/dbutils /create\_tablespaces.sql as pertain to your environment.
2. The table below shows the default initial sizes.

TABLESPACE_NAME	Size
SIM_ENCRYPTED_INDEX	12G
SIM_ENCRYPTED_DATA	10G
SIM_INDEX	10G
SIM_DATA	8G
SIM_LOB_DATA	2G
SIM_LOB_INDEX	2G
USERS	2G

3. Once the paths of script has been modified, execute it in SQL\*Plus as sys.
4. Review create\_tablespaces.log for errors and correct as needed.

### Encrypted Tablespace Creation

If you do not have an Advanced Security Option license, create the sim\_encrypted\_data and sim\_encrypted\_index tablespaces as normal tablespaces but without the encryption.

1. Modify the paths of the script <INSTALL\_DIR>/sim/dbschema/dbutils /create\_encrypted\_tablespaces\_no\_TDE.sql
2. Run the script using SQL\*Plus as sys
3. Review create\_encrypted\_tablespaces\_no\_TDE.log for errors and correct as needed

With an Advanced Security license, tablespaces can be created in an encrypted format. The steps are:

### Configure a Wallet

1. Create a sqlnet.ora in \$TNS\_ADMIN directory of the database server similar to the below entry:

```
ENCRYPTION_WALLET_LOCATION =
  (SOURCE = (METHOD = FILE)
   (METHOD_DATA =
    (DIRECTORY = /u00/oracle/admin/ORACLE_SID/wallet)))
```

2. Create the wallet directory:

```
mkdir -p /u00/oracle/admin/<ORACLE_SID>/wallet
```

3. As a user with the 'alter system' privilege, create the wallet as follows:

Non-container databases:

- a. ADMINISTER KEY MANAGEMENT CREATE KEYSTORE  
'/u00/oracle/admin/dbName/wallet' IDENTIFIED BY "pwd#";
- b. KEY MANAGEMENT SET KEYSTORE OPEN IDENTIFIED BY "pwd#";
- c. KEY MANAGEMENT SET KEY IDENTIFIED BY "pwd#" WITH BACKUP;
- d. ADMINISTER KEY MANAGEMENT CREATE AUTO\_LOGIN KEYSTORE  
FROM KEYSTORE '/u00/oracle/admin/dbName/wallet' identified by pwd#;
- a. Container databases:
- b. ADMINISTER KEY MANAGEMENT CREATE KEYSTORE  
'/u00/oracle/admin/dbName/wallet' IDENTIFIED BY "pwd#";
- c. ADMINISTER KEY MANAGEMENT CREATE AUTO\_LOGIN KEYSTORE  
FROM KEYSTORE '/u00/oracle/admin/dbName/wallet' identified by "pwd#";
- d. ADMINISTER KEY MANAGEMENT SET KEYSTORE OPEN IDENTIFIED BY  
"pwd#" Container=ALL;
- e. ADMINISTER KEY MANAGEMENT SET KEY IDENTIFIED BY "pwd#" WITH  
BACKUP USING 'TDE\_ENCRYPTION' Container=all;

4. Confirm if the wallet is created and open (the TDE master encryption key has been created and inserted automatically):

```
SQL>
select substr(wrl_type, 1, 10) wrl_type, substr(wrl_parameter, 1, 45) param,
substr(status, 1, 10) status, substr(wallet_type, 1, 15) w_type
from v$encryption_wallet;
```

WRL_TYPE	PARAM	STATUS	W_TYPE
FILE	/u00/oracle/admin/ORACLE_SID/wallet	OPEN	AUTOLOGIN

An auto-open wallet is created. You are ready to create the encrypted tablespaces as shown in the following section.

## Encryption at Tablespace Level

Once the wallet is configured, determine an encryption algorithm to be used for the encrypted tablespace and then create them. The sample scripts use the default algorithm AES128:

1. Modify the paths of the script <INSTALL\_DIR>/sim/dbschema/dbutils  
/create\_encrypted\_  
tablespaces\_TDE.sql.
2. Run the script using SQL\*Plus as sys.
3. Review Create\_encrypted\_tablespaces\_TDE.log for errors and correct as needed.  
Once the tablespaces have been created, the SIM schema installation can be run.

---

**Note:** After encryption at the tablespace level, it is absolutely crucial to backup the contents in the wallet directory; otherwise, if they are lost you will not be able to access the tablespaces.

---



---



---

## Appendix: Database Parameter File

```
#####
# Copyright (c) 2014 by Oracle Corporation
# Oracle 12.1.0.x Parameter file
# NOTES: Before using this script:
#       1. Change <datafile_path>, <admin_path>, <utl_file_path>, <diag_path>
and <hostname>
#           values as appropriate.
#       2. Replace the word SID with the database name.
#       3. Size parameters as necessary for development, test, and production
environments.
# -----
*.audit_file_dest=full_path_of_audit_dir
*.audit_trail='db'
*.compatible='12.1.0.2'
*.control_files='full_path_of_controlfile_1','full_path_of_controlfile_2'
#####
# Memory Settings:
# xxxM = Some reasonable starting value for your environment.
#####
*.db_block_size=xxxM
*.db_cache_size=xxxM
*.java_pool_size=xxxM
*.memory_target=xxxM
*.pga_aggregate_target=xxxM
*.shared_pool_size=xxxM
*.streams_pool_size=xxxM

#####

*.db_block_size=8192
*.db_domain=''
*.db_name='dbName'
*.diagnostic_dest='full_path_of_diag_dir'
*.enable_pluggable_database=true|false
*.fast_start_mttr_target=900
*.nls_calendar='GREGORIAN'
*.nls_date_format='DD-MON-RR'
*.nls_language='AMERICAN'
*.nls_numeric_characters='.,'
*.nls_sort=BINARY
*.open_cursors=900
*.os_authent_prefix=''
*.plsql_optimize_level=2
*.processes=2000
*.query_rewrite_enabled='true'
*.remote_dependencies_mode='SIGNATURE'
*.remote_login_passwordfile='EXCLUSIVE'
*.remote_os_authent=true
*.sec_case_sensitive_logon=false
*.undo_tablespace='UNDOTBS1'
```



---

---

# Appendix: Installation Order

This section provides a guideline as to the order in which the Oracle Retail applications should be installed. If a retailer has chosen to use some, but not all, of the applications the order is still valid less the applications not being installed.

---

---

**Note:** The installation order is not meant to imply integration between products.

---

---

## Enterprise Installation Order

1. Oracle Retail Merchandising System (RMS), Oracle Retail Trade Management (RTM)
2. Oracle Retail Sales Audit (ReSA)
3. Oracle Retail Extract, Transform, Load (RETL)
4. Oracle Retail Active Retail Intelligence (ARI)
5. Oracle Retail Warehouse Management System (RWMS)
6. Oracle Retail Invoice Matching (ReIM)
7. Oracle Retail Price Management (RPM)
8. Oracle Retail Allocation
9. Oracle Retail Mobile Merchandising (ORMM)
10. Oracle Retail Xstore Office
11. Oracle Retail Xstore Point-of-Service, including Xstore Point-of-Service for Grocery, and including Xstore Mobile
12. Oracle Retail Xstore Environment
13. Oracle Retail EFTLink
14. Oracle Retail Store Inventory Management (SIM), including Mobile SIM
15. Oracle Retail Predictive Application Server (RPAS)
16. Oracle Retail Batch Script Architecture (BSA)
17. Oracle Retail Demand Forecasting (RDF)
18. Oracle Retail Category Management Planning and Optimization/Macro Space Optimization (CMPO/MSO)
19. Oracle Retail Replenishment Optimization (RO)
20. Oracle Retail Analytic Parameter Calculator Replenishment Optimization (APC RO)
21. Oracle Retail Regular Price Optimization (RPO)
22. Oracle Retail Merchandise Financial Planning (MFP)
23. Oracle Retail Size Profile Optimization (SPO)
24. Oracle Retail Assortment Planning (AP)
25. Oracle Retail Item Planning (IP)
26. Oracle Retail Item Planning Configured for COE (IP COE)
27. Oracle Retail Advanced Inventory Planning (AIP)
28. Oracle Retail Integration Bus (RIB)
29. Oracle Retail Services Backbone (RSB)

- 30.** Oracle Retail Financial Integration (ORFI)
- 31.** Oracle Retail Data Extractor for Merchandising
- 32.** Oracle Retail Clearance Optimization Engine (COE)
- 33.** Oracle Retail Analytic Parameter Calculator for Regular Price Optimization (APC-RPO)
- 34.** Oracle Retail Insights, including Retail Merchandising Insights (previously Retail Merchandising Analytics) and Retail Customer Insights (previously Retail Customer Analytics)