



# BEA AquaLogic Service Bus™

**Interoperability  
Solutions for  
Web Services Remote  
Portlets (WSRP)**



# Contents

## Introduction

- WSRP Producers and Consumers . . . . . 1-1
- WSRP Architecture . . . . . 1-2
  - Basic Architecture. . . . . 1-2
  - Enhanced Architecture with AquaLogic Service Bus . . . . . 1-2
- WSRP Design Concepts. . . . . 1-4
  - WSRP WSDLs . . . . . 1-4
  - WSRP Messages . . . . . 1-5

## Configuring AquaLogic Service Bus for WSRP

- Getting the Producer WSDL . . . . . 1-1
- Routing Messages Between the Consumer and Producer . . . . . 1-2
- Monitoring WSRP Applications . . . . . 1-3
- Load Balancing and Failover . . . . . 1-4

## WSRP Interoperability Example

- Example Prerequisites . . . . . 2-1
- Example Projects and Folders . . . . . 2-2
- Monitoring Example . . . . . 2-2
  - Step 1: Define WSDL Resources . . . . . 2-2
  - Step 2: Create Business Services . . . . . 2-3
  - Step 3: Create the Proxy Services . . . . . 2-5
  - Step 4: Retrieve the WSDL from the Producer . . . . . 2-8

Step 4.1: Create the Business Service to Retrieve the WSDL . . . . .	2-9
Step 4.2: Create an XQuery Expression to Construct URLs . . . . .	2-9
Step 4.3: Create a No-Op Proxy Service . . . . .	2-10
Step 4.4: Create a Common Proxy Service. . . . .	2-10
Step 5: Test the Configuration . . . . .	2-13



# Copyright

Copyright © 1995-2006 BEA Systems, Inc. All Rights Reserved.

## Restricted Rights Legend

This software is protected by copyright, and may be protected by patent laws. No copying or other use of this software is permitted unless you have entered into a license agreement with BEA authorizing such use. This document is protected by copyright and may not be copied photocopied, reproduced, translated, or reduced to any electronic medium or machine readable form, in whole or in part, without prior consent, in writing, from BEA Systems, Inc.

Information in this document is subject to change without notice and does not represent a commitment on the part of BEA Systems. THE DOCUMENTATION IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND INCLUDING WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. FURTHER, BEA SYSTEMS DOES NOT WARRANT, GUARANTEE, OR MAKE ANY REPRESENTATIONS REGARDING THE USE, OR THE RESULTS OF THE USE, OF THE DOCUMENT IN TERMS OF CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE.

## Trademarks and Service Marks

Copyright © 1995-2006 BEA Systems, Inc. All Rights Reserved. BEA, BEA JRocket, BEA WebLogic Portal, BEA WebLogic Server, BEA WebLogic Workshop, Built on BEA, Jolt, JoltBeans, SteelThread, Top End, Tuxedo, and WebLogic are registered trademarks of BEA Systems, Inc. BEA AquaLogic, BEA AquaLogic Data Services Platform, BEA AquaLogic Enterprise Security, BEA AquaLogic Interaction, BEA AquaLogic Interaction Analytics, BEA AquaLogic Interaction Collaboration, BEA AquaLogic Interaction Content Services, BEA AquaLogic Interaction Data Services, BEA AquaLogic Interaction Integration Services, BEA AquaLogic Interaction Process, BEA AquaLogic Interaction Publisher, BEA AquaLogic Interaction Studio, BEA AquaLogic Service Bus, BEA AquaLogic Service Registry, BEA Builder, BEA Campaign Manager for WebLogic, BEA eLink, BEA Kodo, BEA Liquid Data for WebLogic, BEA Manager, BEA MessageQ, BEA SALT, BEA Service Architecture Leveraging Tuxedo, BEA WebLogic Commerce Server, BEA WebLogic Communications Platform, BEA WebLogic Enterprise, BEA WebLogic Enterprise Platform, BEA WebLogic Enterprise Security, BEA WebLogic Express, BEA WebLogic Integration, BEA WebLogic Java Adapter for Mainframe, BEA WebLogic JDriver, BEA WebLogic Log Central, BEA WebLogic Mobility Server, BEA WebLogic Network Gatekeeper, BEA WebLogic Personalization Server, BEA WebLogic Personal Messaging API, BEA WebLogic Platform, BEA WebLogic Portlets for Groupware Integration, BEA WebLogic Real Time, BEA WebLogic RFID Compliance Express, BEA WebLogic RFID Edge Server, BEA WebLogic RFID Enterprise Server, BEA WebLogic Server Process Edition, BEA WebLogic SIP Server, BEA WebLogic WorkGroup Edition, BEA Workshop for WebLogic Platform, BEA Workshop JSP, BEA Workshop JSP Editor, BEA Workshop Struts, BEA Workshop Studio, Dev2Dev, Liquid Computing, and Think Liquid are trademarks of BEA Systems, Inc. Accelerated Knowledge Transfer, AKT, BEA Mission Critical Support, BEA Mission Critical Support Continuum, and BEA SOA Self Assessment are service marks of BEA Systems, Inc.

All other names and marks are property of their respective owners.

# Introduction

Web Services for Remote Portlets (WSRP) is an increasingly popular mechanism used to generate markup fragments on a remote system for display in a local portal application. This section describes how AquaLogic Service Bus can be used to provide Service Level Agreement (SLA) monitoring in applications that use WSRP.

This section discusses the following topics:

- [WSRP Producers and Consumers](#)
- [WSRP Architecture](#)
- [WSRP Design Concepts](#)

## WSRP Producers and Consumers

WSRP involves two integral components:

- The remote application, called a *WSRP producer* (referred to as a *producer* in this section) implements standards-based Web Services using the SOAP specification over HTTP. Producers are created using WebLogic Portal or third-party implementations of WSRP.
- A *WSRP consumer* (referred to as a *consumer* in this section) is a Portal application. Typically, the consumer application references the producer's WSDL when the portal is designed, and the consumer directly accesses the producer.


# WSRP Architecture

This section describes basic WSRP architecture and then shows how this architecture can be enhanced by adding AquaLogic Service Bus.

## Basic Architecture

The following figure shows the basic WSRP SOAP request and response flow between a producer application and a consumer application.


**Figure 1-1 Basic Request/Response Flow Between Producer and Consumer Applications**



## Enhanced Architecture with AquaLogic Service Bus

Because a WSRP producer implements SOAP Web Services, an enterprise service bus (such as AquaLogic Service Bus) can be used as an intermediary between the producer and consumer to provide Service Level Agreement (SLA) monitoring, as shown in the following figure.

**Figure 1-2 Enhanced WSRP Request / Response Flow Via AquaLogic Service Bus**



In this architecture, the WSRP SOAP request/response flow occurs in the following sequence:

1. **Inbound Request:** The consumer calls the proxy service in the AquaLogic Service Bus.
2. **Outbound Request:** The proxy service routes the request (a message containing the SOAP body and transport headers) to the producer.
3. **Outbound Response:** The producer returns a reply to AquaLogic Service Bus.
4. **Inbound Response:** The proxy service returns the reply (a message containing the SOAP body and transport headers) to the consumer.

The remainder of this section provides instructions for configuring the AquaLogic Service Bus to proxy service requests for WSRP services. It describes services that a producer provides, along with other attributes of WSRP that must be used to properly configure AquaLogic Service Bus.

This section also discusses different possible strategies that can be used to monitor producers with increasing degrees of detail. Finally, it discusses load balancing and failover with WSRP.

## WSRP Design Concepts

This topic describes the following WSRP design concepts:

- [WSRP WSDLs](#)
- [WSRP Messages](#)

## WSRP WSDLs

The following table describes the kinds of services offered by producers.

**Table 1-1 Producer Services**

Service	Description
Service Description	<i>Required service.</i> Used to describe the producer and the portlets that it makes available to consumers.
Markup	<i>Required service.</i> Manages user interaction with a remote portlet and returns the HTML markup used to render the portlet.
Registration	<i>Optional service.</i> Allows consumers to register themselves with the producer. Registration is required for complex producers.
Management	<i>Optional service.</i> Provided by complex producers for managing portlet customization and portlet preferences.
Markup Extension	Service provided by BEA Portal producers that replaces the Markup service. The Markup Extension allows more efficient message handling by using multipart MIME messages for transmitting HTML markup content.

Each producer implements a minimum of two services (Service Description and Markup). A *simple producer* offers just these two services. A *complex producer*, however, provides two additional services (Registration and Management). WebLogic Portal producers also implement an extension service (Markup Extension) that replaces the standard Markup service.

These services are described using a standard WSDL format. The producer supplies a single URL for retrieving its WSDL, which describes all of the services that are available from that producer.

The end points for each service indicate whether the consumer should use transport-level security (HTTPS) or not to communicate with the producer.

## WSRP Messages

WSRP uses SOAP over HTTP for all messages sent between producers and consumers. In addition to using standard message formats in the SOAP Body, WSRP requires that certain transport headers be set in the request message—at a minimum, consumers must set the `SOAPAction` header, cookie headers, and the usual HTTP headers (such as `Content-Type`). Producers will return a session cookie, plus any application-specific cookies, in the HTTP transport header of the response message. The consumer must return the session cookie in subsequent request messages.

## Introduction

# Configuring AquaLogic Service Bus for WSRP

The AquaLogic Service Bus Console, which is described in the [AquaLogic Service Bus Console Online Help](#), is used to configure AquaLogic Service Bus. For more information about creating WSRP-enabled portals using WebLogic Portal, see [Federated Portals Guide](#).

Configuring AquaLogic Service Bus for WSRP involves the following tasks:

- Implementing a service that consumers can invoke to obtain an appropriate WSDL for a particular producer
- Implementing the nuts and bolts of conveying a consumer's request to the producer and returning the response to the consumer

This topic describes the following tasks:

- [Getting the Producer WSDL](#)
- [Routing Messages Between the Consumer and Producer](#)
- [Monitoring WSRP Applications](#)
- [Load Balancing and Failover](#)

## Getting the Producer WSDL

As a common practice, consumers contact a producer directly to obtain its WSDL. However, if AquaLogic Service Bus is used to proxy the service, then all access to the producer occurs via AquaLogic Service Bus. Therefore, a proxy service must be implemented for consumers that calls the producer's real URL to obtain its WSDL, and then transforms the results by:

- Rewriting the endpoint address for the producer to refer to the Service Bus IP address and port
- Changing the endpoint URI to refer to the AquaLogic Service Bus proxy service that reflects the required monitoring granularity (as described in [“Monitoring WSRP Applications” on page 2-3](#))
- Changing the endpoint protocol and port to reflect whether transport security is used between the consumer and the AquaLogic Service Bus proxy service

The developer who creates a producer can specify whether the producer requires SSL or not (`secure=true`). In addition, the AquaLogic Service Bus administrator can change the security requirement to the consumer via AquaLogic Service Bus configuration. For example, suppose a producer does not require SSL. The AquaLogic Service Bus administrator can require consumers to use SSL by:

- Changing the WSDL to specify HTTPS
- Configuring the proxy services for WSRP to use the HTTPS transport

When configured in this way, AquaLogic Service Bus automatically bridges the secure messages from the consumer to the non-secure messages used by the producer.

## Routing Messages Between the Consumer and Producer

After the consumer has retrieved a copy of the WSDL, it uses the definitions in the WSDL to formulate service requests that it then sends to the producer via AquaLogic Service Bus.

The WSRP request / response process involves the following steps:

1. The consumer sends a message to the AquaLogic Service Bus proxy service corresponding to the producer service.
2. The proxy service executes a simple message flow that routes the message (unchanged) to the actual producer service.
3. The producer formulates a response that it then sends to the consumer via AquaLogic Service Bus.
4. The consumer receives the response (unchanged) from the producer.

WSRP Web services expose portlets and those can rely on HTTP cookies and sessions. Therefore, WLSB must be configured to propagate HTTP transport headers (such as `SOAPAction` and cookies). However, by default, AquaLogic Service Bus does not pass transport headers from the proxy service to the business service, because it cannot assume that the proxy

service uses the same transport as the business service. Therefore, the message flow must be configured to copy the request headers from the inbound request to the outbound request. Similarly, the response headers from the business service must be copied back to the proxy service's response to the consumer.

Although it is possible to copy *all* transport headers between the proxy service and the business service, it is necessary to be more selective to avoid errors. The Set-Cookie and Cookie headers must be copied. Because AquaLogic Service Bus is the entity that assembles the final message to send, it must own some of the headers information (such as `Content-Length`). For example, if the message flow were to copy the `Content-Length` header from the proxy service to the business service, it might result in an error because the length of the message could change during processing.

## Monitoring WSRP Applications

Monitoring tracks the usage of a producer's individual services and operations. Monitoring proxy services is very easy to set up. Fortunately, the message flow for WSRP services introduces very little overhead, and the mapping between proxy services and producers, and between business services and producers, is simple to configure. Therefore, to satisfy SLA requirements, it is sufficient to monitor only the proxy services.

### Monitoring for Proxy Services

To configure monitoring for WSRP proxy services, create a proxy service for each of the services implemented by the producer.

- Simple producers require only two proxies—one for the Markup service and one for the Description service.
- Complex producers require these two proxies plus two additional proxy services for Registration and Management.

These proxy services should be based on the standard WSRP WSDLs using SOAP bindings. Only a single business service for the producer should be created, and it should be configured to use "Any SOAP Service" instead of being based on a WSDL. The message flow between the proxies and the business service should not modify the SOAP body in any way. However, just as for all WSRP message flows, it must pass the request headers via HTTP from the client request to the actual producer. Similarly, the response HTTP headers returned by the producer must be copied back to the client in the message flow.

## Monitoring for Business Services

Monitoring is required for producer business services. Individual business services must be created for each of the Web services described in the producer's WSDL, and the business services must be defined using the WSDL. There is a one-to-one mapping between the proxy services and the business services—a simple, unconditional routing node is sufficient in the message flow.

For the operations to be counted correctly, AquaLogic Service Bus must be told which operation to use. Normally, the administrator would do this by selecting one of the operations from a drop-down menu when the business service is selected for the Route action. However, the operation specified by the client message is not the same for all messages, so a single, hard-coded value will not work here.

The administrator must ensure that the business service uses the same operation as the proxy service. While this could be achieved by specifying a Routing Table action that selects the case using the `$operation` variable, it is a very tedious approach because the WSRP standard defines 14 operations across all WSRP services, and each would require a Route action with transformations to propagate the transport headers.

Fortunately, there is a more effective alternative. When routing to the business service, rather than selecting the operation from the drop-down menu, an administrator should use another transformation in the request actions to insert the value of `$inbound/ctx:service/ctx:operation` into `$outbound/ctx:service`. With this transformation, the operation for the business service is dynamically set to the same value as was specified for the proxy service, and AquaLogic Service Bus will correctly count and monitor all operations of the service.

## Load Balancing and Failover

AquaLogic Service Bus allows business services to define multiple endpoints that all provide the same Web service. When multiple endpoints are defined, AquaLogic Service Bus can automatically load balance requests across endpoints, and it can automatically fail over requests when an endpoint is inaccessible. However, WSRP imposes some limitations on the use of these features.

Portlets are a means of surfacing a user interface to some application. Therefore, portlets typically have session data associated with them. To preserve session data, requests to the portlet must be directed to the same server (or cluster) that serviced the original request. This requirement makes load balancing via AquaLogic Service Bus inappropriate. Multiple endpoints in a business service will usually target different servers or cluster. Because there is no communication among servers that are in separate clusters, there is no way to preserve the session. Therefore, if multiple

endpoints are defined for a WSRP business service, then the load balancing algorithm must be set to "none".

Multiple endpoints can be used to provide redundancy in certain circumstances in the event that one of the endpoints is unavailable. The WSRP service is still available via a secondary endpoint. However, any session data that existed at the time the first endpoint failed will not be available on other endpoints.

This failover configuration is an option only for simple producers (see [“WSRP WSDLs” on page 1-4](#)), not for complex produces. Complex producers require that their consumers first register with the producer before sending service requests. The producer returns a registration handle that the consumer must include with each request to that producer. In the case where a business service defines multiple endpoints, each endpoint requires its own registration handle.

AquaLogic Service Bus is, however, stateless across requests—it does not maintain a mapping of the correct handle to send to a particular endpoint. In fact, it would only send the registration request to a single endpoint, so the consumer would be registered with only that one producer. If that one producer crashed, then AquaLogic Service Bus would route a service request to another endpoint defined for that business service, but the consumer would never have registered with that new producer, and the request would fail with an "InvalidRegistration" fault.

The management of registration handles therefore requires an application outside of AquaLogic Service Bus to maintain this state data. Error handling could be challenging to implement. Therefore, the registration requirement precludes defining multiple endpoints for complex producers. Because simple producers do not require or support the Registration service, a failover configuration that defines multiple endpoints in the business service is possible, although session data is lost on failover.

## Configuring AquaLogic Service Bus for WSRP

# WSRP Interoperability Example

This section describes a WSRP interoperability example. It contains the following topics:

- [Example Prerequisites](#)
- [Example Projects and Folders](#)
- [Monitoring Example](#)

## Example Prerequisites

The WSRP interoperability example assumes the following components and configuration:

- WebLogic Platform 9.2
- AquaLogic Service Bus 2.0/2.1/2.5
- Sample Platform domain configured at `platform:7001`
- AquaLogic Service Bus domain configured at `alsb:7001`
- Sample Portal application consumer
- Sample producer

For an AquaLogic Service Bus configuration that supports the configuration defined in this example, see the AquaLogic Service Bus/WSRP code sample, available from the AquaLogic Service Bus code samples page on BEA dev2dev for:

- AquaLogic Service Bus 2.5:  
<https://codesamples.projects.dev2dev.bea.com/servlets/Scarab/remcurreport/true/template/ViewIssue.vm/id/S267/nbrresults/13>
- AquaLogic Service Bus 2.0 and 2.1:  
<https://codesamples.projects.dev2dev.bea.com/servlets/Scarab/remcurreport/true/template/ViewIssue.vm/id/S175/nbrresults/13>

## Example Projects and Folders

This example describes the configurations corresponding to the ALSB 2.5 dev2dev code sample. The structure of the sample is divided into two projects—one containing common resources, and the other containing resources for the sample producer.

**Table 3-1 Projects in the WSRP Interoperability Examples**

Folder	Description
<code>wsrp</code>	Contains common resources that are not specific to any producer.
<code>operationExample</code>	Full example supports the most fine-grained monitoring. The folder contains producer-specified resources. See “ <a href="#">Monitoring Example</a> ” on page 3-2.

## Monitoring Example

The monitoring configuration example (in the `operationExample` folder) involves configuring AquaLogic Service Bus to monitor all services and operations of a producer.

The monitoring configuration uses both business services and proxy services that are based on the WSDLs defined by the WSRP standard. The example also defines the additional resources to describe the WSRP services and extend the message flows to support monitoring at the operation level. The rest of this section describes the tasks required to implement the monitoring configuration.

### Step 1: Define WSDL Resources

Import all of the WSRP WSDL definition files, along with the XML schema files on which the definitions depend. All of the files are available as part of the sample code associated with this example, but the standard resource locations are described in the following table.

**Table 3-2 WSDL Resource Definitions**

Resource Name	Location
wsrp_v1_bindings	<a href="http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_bindings.wsdl">http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_bindings.wsdl</a>
wsrp_v1_interfaces	<a href="http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_interfaces.wsdl">http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_interfaces.wsdl</a>
wsrp_v1_types	<a href="http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_types.xsd">http://www.oasis-open.org/committees/wsrp/specifications/version1/wsrp_v1_types.xsd</a>
wlp_wsrp_v1_bindings	\$BEA_HOME/weblogic81/portal/lib/wsrp/wsrp-common.jar
wlp_wsrp_v1_types	\$BEA_HOME/weblogic81/portal/lib/wsrp/wsrp-common.jar
xml	<a href="http://www.w3.org/2001/xml.xsd">http://www.w3.org/2001/xml.xsd</a>
wsrpWSDL	<a href="http://platform:7001/producer/producer_WSDL">http://platform:7001/producer/producer_WSDL</a>

Producers generated by BEA Portal extend the standard WSDLs by defining an additional port that allows messages to be sent using MIME attachments. Describing this extension is beyond the scope of this example, but it is still necessary to define these extension resources if the producer WSDL references them. In this example, an optional task is to create a resource for the WSDL used by the producer. After creating these WSDL and XML Schema resources, edit the references in each resource to resolve the dependencies on other resources.

## Step 2: Create Business Services

This monitoring example uses the WSDL bindings for each port type implemented by the producer. Because a business service can be associated with only one WSDL port or binding, a separate business service resource must be created for each. A simple producer implements only the required Markup and Service Description interfaces, while a complex producer also implements the Management and Registration interfaces. The services are created identically (except for the service name and types), as shown in the following table.

**Table 3-3 Business Service Configuration**

Service Name	Service Type
base	WSDL port: operationExample/wsrpWSDL, port="WSRPBaseService"
desc	WSDL port: operationExample/wsrpWSDL, port="WSRPServiceDescriptionService"
mgmt	WSDL port: operationExample/wsrpWSDL, port="WSRPPortletManagementService"
reg	WSDL port: operationExample/wsrpWSDL, port="WSRPRegistrationService"
ext	WSDL port: operationExample/wsrpWSDL, port="WLP_WSRP_Ext_Service"

For each service, minimally set the attributes listed in the following table.

**Table 3-4 Service Attributes for Business Services**

Name	Value	Comments
Protocol	HTTP	Or HTTPS if the producer was created with <code>secure="true"</code> .
Load Balancing Algorithm	none	Must be none, or session data will be lost across requests if multiple end points are defined.
Endpoint URI	For WebLogic Platform 8.1: <code>http://platform:7001/producer/producer/</code>	The URL is the same for Markup, Service Description, Registration Service and Portlet Management.

**Table 3-4 Service Attributes for Business Services (Continued)**

Name	Value	Comments
Endpoint URI (continued)	<p>For WebLogic Platform 9.2 the URLs are as follows:</p> <ul style="list-style-type: none"> <li>• Service Description: <code>http://bangpltw3k1:8003/wsrpProducer/pr oducer/wsrp_1.0/serviceDescription</code></li> <li>• Markup: <code>http://bangpltw3k1:8003/wsrpProducer/pr oducer/wsrp_1.0/markup</code></li> <li>• Registration: <code>http://bangpltw3k1:8003/wsrpProducer/pr oducer/wsrp_1.0/registration</code></li> <li>• Portlet Management: <code>http://bangpltw3k1:8003/wsrpProducer/pr oducer/wsrp_1.0/portletManagement</code></li> <li>• Markup Extension: <code>http://bangpltw3k1:8003/wsrpProducer/pr oducer/wsrp-wlp-ext-1.0/markup</code></li> </ul>	Multiple endpoints must be defined for WSRP producers.

## Step 3: Create the Proxy Services

Proxy services in this monitoring example are configured as follows:

- Just as the business services are based on a WSDL, the proxy services must be based on the same WSDL.
- One proxy service is created for each business service, but each proxy service must have a different URI.
- The configuration must specify which operation is being invoked.

To create the proxy services:

1. Creating the proxy service for the base WSRP service.

As in the earlier example, create the proxy service using the existing `operationExample/base` business service as the model. This will automatically base the proxy service on the same WSDL binding as the business service, and it will create a

message flow with an unconditional route action to the business service. For the Endpoint URI, anything may be used, such as the producer name with the port type abbreviation appended to it (for example, `/operationExampleBase`).

2. Edit the message flow to add the same transformations required to copy the request transport headers and response transport headers between the consumer and producer. WSRP relies on data conveyed in the transport headers to function properly. In particular, producers will return to consumers any session cookies in the response headers that they expect consumers to supply in subsequent requests. Similarly, producers expect consumers to provide the requested operation in the `SOAPAction` request header.

By default, AquaLogic Service Bus does not copy transport headers from the inbound request to the outbound request, or from the outbound response to the inbound response. The message flow must therefore propagate the required headers both in and out of the business service. Because these transformations are required for every WSRP service, it is convenient to define two common XQuery resources—one for request headers and one for response headers—that extract the correct headers.

For request headers, use the following query.

**Table 3-5 Request Header Query**

Name	Value
Resource Name	<code>wsrp/rqstHeaders</code>
Xquery	<pre> declare namespace ctx="http://www.bea.com/wli/sb/context"; declare namespace tp="http://www.bea.com/wli/sb/transforms"; declare variable \$in external; \$in/ctx:transport/ctx:request/tp:headers/child::*[1 ocal-name()!="Content-Length"]                     </pre>

The `rqstHeaders` query extracts all transport headers (except `Content-Length`) from the `$in` variable. AquaLogic Service Bus can sometimes reformat the message body so that its length no longer exactly matches the request message. Copying the length from the original request can result in transport errors if the body was modified (such as reformatted).

To copy the inbound request headers to the outbound business service, add the following Replace request action to the message flow:

Replace `./ctx:transport/ctx:request/tp:headers` in variable `outbound` with `xqTransform()`

Replace node contents

Variable Mapping (`wsrp/rqstHeaders`):

`in: $inbound`

Similar to the request side, the response side defines a common XQuery resource to extract all but the Content-Length header from the response returned from the producer.

For response headers, use the following query.

**Table 3-6 Response Header Query**

Name	Value
Resource Name	<code>wsrp/rspncHeaders</code>
Xquery	<pre> declare namespace ctx="http://www.bea.com/wli/sb/context"; declare namespace tp="http://www.bea.com/wli/sb/transport"; declare variable \$out external; \$out/ctx:transport/ctx:response/tp:headers/child::* [local-name()!="Content-Length"] </pre>

The following Replace response action in the route node propagates the required headers:

Replace `./ctx:transport/ctx:response/tp:headers` in variable `inbound` with `xqTransform()`

Replace node contents

Variable Mapping (`wsrp/rspncHeaders`):

`out: $outbound`

### 3. Specify which operation to invoke.

Normally, in a Route Action that routes to a WSDL-based service, an operation to invoke (by selecting the correct operation from the drop-down menu) is specified. However, each WSRP port implements several operations, and so the configuration requires a routing table with a case for each operation. Each case requires the same transformations to propagate the transport headers.

Creating all of the transformations in this way might prove to be quite tedious. Fortunately, there is a more convenient approach. Instead of using the drop-down menu, use another

transformation to copy the operation from the proxy service to the business service. Configure this transformation by adding an Insert Action to the Request Actions of the message flow:

```
Insert $inbound/ctx:service/ctx:operation as last child of ./ctx:service
in variable outbound
```

The proxy services for the other business services can be created by repeating these steps, although a shortcut can be used to avoid recreating all of the transformations manually. For example, to create the proxy service for the Service Description service:

1. Create a new proxy service using the existing `operationExample/base` proxy service just created as the model. Following this example, use `/operationExampleDesc` for the Endpoint URI.
2. On the Summary Page, click the edit link for General Configuration. The WSDL binding was created using the Base port, so correct that here to refer to the `WSRPServiceDescriptionService` port.
3. Edit the message flow. The route action refers to the base business service. Correct this to route to the `desc` service.

## Step 4: Retrieve the WSDL from the Producer

Create a service that will retrieve the WSDL from the producer and transform it to hide the actual producer endpoints. In this example the proxies for each producer have a different URI. The rest of this section describes how to create the resources to retrieve the producer WSDL.

### Step 4.1: Create the Business Service to Retrieve the WSDL

Create a business service to obtain the WSDL from the producer. This resource is specific to the producer, so it must be created in the `operationExample` project. The following table describes the properties of the business service.

**Table 3-7 Business Service Configuration Properties**

Name	Value	Comments
Service Name	<code>wsdlsvc</code>	Any name is allowed.
Service Type	Any XML Service	Consumers usually retrieve the WSDL from the producer using an HTTP GET request. Only XML services support GET.

**Table 3-7 Business Service Configuration Properties**

<b>Name</b>	<b>Value</b>	<b>Comments</b>
Protocol	HTTP	Or HTTPS
Load Balancing Algorithm	None	None is preferable
Endpoint URI	http://platform:7001/producer/producer?WSDL	Although multiple endpoints may be specified for retrieving the WSDL, doing so is of limited benefit.
HTTP Request Method	GET	

## Step 4.2: Create an XQuery Expression to Construct URLs

All endpoint addresses in the producer's WSDL must be transformed to reflect the AquaLogic Service Bus server address and the proxy service URI values. Because each producer WSDL can have four or more ports defined, it is convenient to create an XQuery expression to simplify the construction of the endpoint locations. The XQuery expression accepts the following three string variables as input and concatenates them together to form a SOAP address element:

- **base URL** for the AquaLogic Service Bus server
- **name** to identify the producer
- **extension** used to differentiate ports for a producer

The following table shows the query definition in the `wsrp` project.

**Table 3-8 XQuery Definition in the `wsrp` Project**

Name	Value
Resource Name	<code>wsrp/addr</code>
XQuery	<pre> declare variable \$baseURL external; declare variable \$name external; declare variable \$svc external; declare namespace soap="http://schemas.xmlsoap.org/wsdl/soap/"; &lt;soap:address location="{concat(\$baseURL, \$name, \$svc) }"/&gt; </pre>

### Step 4.3: Create a No-Op Proxy Service

A subsequent configuration task requires a service that does nothing. To create this service, define a new proxy service in the `wsrp` project folder with the resource name `nullSvc`. Accept all of the defaults for this service. Configuring this proxy service creates a message flow for the service of an echo node only, which is all that is required for this example.

### Step 4.4: Create a Common Proxy Service to Retrieve the WSDL

Create a proxy service used by consumers to get WSDLs from producers. This proxy service is appropriate for any producer configuration modeled on this basic sample. The example described in this section is only a suggestion—a different approach might better suit the specific requirements of a given implementation. Because this proxy service is not specific to a single producer, it should be created in the `wsrp` project folder.

The approach used in this step requires the administrator to assign each producer a name that is included in part of the URL to retrieve the WSDL. The message flow for the proxy service will extract the name from the URL, use it to locate the business service specific to that producer, obtain the WSDL, and then transform the WSDL to rewrite the endpoints to AquaLogic Service Bus. The proxy service endpoint URI is configured as `/getWSDL`, and the URL that consumers use to obtain a WSDL is:

```
http://alsb:7001/getWSDL/producerName
```

where `producerName` is the name assigned to the producer by the administrator. In this example, the producer name is `operationExample`.

The following table describes how the proxy service is configured:

**Table 3-9 Proxy Service Configuration Properties**

Property Name	Value	Comments
Service Name	producerWSDL	Any name is allowed.
Service Type	Any XML Service	
Protocol	HTTP	
Endpoint URI	/getWSDL	

The message flow for this proxy service consists of a pipeline pair and a route node. The request side of the pipeline pair consists of a single stage whose job is to extract the producer name from the URL and assign it to a context variable. The action is:

```
Assign $inbound/ctx:transport/ctx:request/http:relative-URI to variable producerName
```

The response side of the message flow is a stage where all of the transformations are performed. Before executing the Replace Actions to transform the WSDL, assign the base URL of the AquaLogic Service Bus server to a context variable to avoid specifying it on every transformation:

```
Assign "http://alsb:7001/" to variable nonSecureBaseURL
```

Edit the stage of the Response Pipeline to modify each Replace Action to make the transformation match the Endpoint URI given to the proxies created earlier. In this example, the proxies were created using the producer name with an abbreviated service type appended to it. The `addr XQuery` resource created earlier accepts an extension argument to construct the URI location. Simply change that argument to the proper value, as shown in the following table.

**Table 3-10 Extension Settings to Construct the URI Location**

If @binding is	svc arg of addr is
WSRP_v1_Markup_Binding_SOAP	"Base"
WSRP_v1_ServiceDescription_Binding_SOAP	"Desc"
WSRP_v1_PortletManagement_Binding_SOAP	"Mgmt"

**Table 3-10 Extension Settings to Construct the URI Location (Continued)**

If @binding is	svc arg of addr is
WSRP_v1_Registration_Binding_SOAP	"Reg"
WLP_WSRP_v1_Markup_Ext_Binding_SOAP	"Ext"

You must map "name:" to "\$producerName" and "BaseURL" to "\$nonSecureBaseURL" similar to the "svg arg" mapping in the table, [“Extension Settings to Construct the URI Location” on page 3-11](#).

The five Replace Actions are defined as shown in the following code listing. The value of name is replaced with the binding names from the table.

```

Replace
./*[local-name()="definitions"]/*[local-name()="service"]/*[local-name()="port"][ends-with(attribute::binding,"name")]/*[local-name()="address"
Replace entire node
name
WSRP_v1_Markup_Binding_SOAP
WSRP_v1_ServiceDescription_Binding_SOAP
WSRP_v1_PortletManagement_Binding_SOAP
WSRP_v1_Registration_Binding_SOAP
    
```

For the first Replace Action, the following User Namespace definitions must be added:

**Table 3-11 User Namespace Definitions on Replace Action**

Prefix	Namespace
wsdl	http://schemas.xmlsoap.org/wsdl/
soap	http://schemas.xmlsoap.org/wsdl/soap/

The route node of this message flow consists of a routing table that selects the case based on \$producerName. For each known producer, add cases so that each case routes to the correct business service to retrieve the WSDL if the name matches. This example uses the following directive:

```
= "operationExample" Route to wsdlSvc
```

To handle cases in which an unknown producer name is given, add a Default Case that routes to the no-op service:

```
Default Route to nullSvc
```

In this example, return an HTTP 404 status code by adding these response actions to the default case:

```
Insert <http:http-response-code>404</http:http-response-code> as last child
of ./ctx:transport/ctx:response in variable inbound
```

```
Reply With Failure
```

Finally, edit the Routing Table in the route node to make the cases correspond to the producers known to the system.

## Step 5: Test the Configuration

After completing the configuration, test it to verify that it works correctly. The testing steps for testing the configuration are as follows:

1. Retrieve the WSDL from a regular browser window by entering the following URL:  
`http://alsb:7001/getWSDL/operationExample`
2. Verify that all of the end point WSRP end point URLs (except for the BEA extension service) have been changed to correctly refer to the proxy service values on the AquaLogic Service Bus server.
3. Create a remote portlet in a Portal consumer application, specifying this URL as the address of the WSDL for the producer.

Use either the WebLogic Workshop or Portal Administration Tool to create the remote portlet. Except for entering a different URL to retrieve the WSDL, the steps to create this portlet are no different from those used to create the portlet not proxied by AquaLogic Service Bus.

4. After the consumer portal is complete, run the application.
5. Enable monitoring on the AquaLogic Service Bus components of interest.
6. Use the AquaLogic Service Bus Console to drill down to see message counts and performance statistics on all WSRP services and operations handled by the producer.

## WSRP Interoperability Example