PeopleTools 8.52 PeopleBooks Updates, June 2013

PeopleBook	Chapter	Description
Application Designer Developer's Guide	Appendix: Configuring Rich Text- Enabled Fields to Store Accented Western European Characters	Added an appendix describing how to support the display of accented Western European characters (umlauts for example) in rich text enabled fields.
Application Designer Developer's Guide	Constructing File Layouts and Performing Data Interchanges	Added a note to the section "Constructing File Layouts and Performing Data Interchanges" informing customers that file layouts should be reviewed regularly, especially after upgrades, to ensure they file layouts still reflect the structure of the underlying database (records, fields, and so on).
Application Designer Developer's Guide	Creating Page Definitions, Setting Page Field Properties for Controls, Setting Options Properties	Added section entitled "Data Conversion Considerations," which describes the current behavior of the rich text editor converting input to HTML.
Application Designer Developer's Guide	Controls, Setting Label Properties, Display Options	Removed "and check boxes" from the list of items for which the "no colon" label option applies.
Application	Using Scroll	Added a note reminding users that using the Find

PeopleBook	Chapter	Description
Designer Developer's Guide	Areas, Scroll Bars, and Grids > Header Area Properties	option does not search fields within HTML areas.
Application Designer Developer's Guide	Using Command Line Parameters, Building Projects	Updated the example command line arguments to match the described scenario. Previously, the project name in the example was different than the name stated in the scenario.
Application Designer Developer's Guide		Clarified note about using rich text-enabled long edit boxes within grids. It now reads: Note. The rich text editor is not supported within grids. If you insert a long edit box and make it rich text-enabled, the system automatically sets the long edit box Use properties to Display Only. (Use tab > Field Use Options > Display Only.)
Application Designer Developer's Guide	Using Scroll Areas, Scroll Bars, and Grids > Inserting and Manipulating Grid Columns	Added note to clarify long edit box behavior within grids. Note. Long edit boxes inserted into grids and set to display only always display the field content in expanded mode, regardless of how the Expand Field When Display Only option is set. (Use tab > Field Use Options > Expand Field When Display Only.)
Application Designer Developer's Guide	Designing Pages for Optimal Performance	Added a section entitled "Working with Autocomplete Fields" that describes behavior related to fields enabled for autocomplete (type ahead) and deferred processing.
BI Publisher for PeopleSoft	Defining Report Definitions	For setting output options, corrected the file name from Userfilename to the ReportFileName property.
Database Administrati on	Appendix: Administerin g PeopleSoft	Updated the documentation for implementing Oracle Golden Gate and Oracle Active Data Guard to reflect functionality enhancements that

PeopleBook	Chapter	Description
	Databases on Oracle	will be backported from PTools 853, to be delivered with next bundle.
Database Administrati on	Ensuring Data Integrity	Modified "Running SYSAUDIT" section: updated SYSAUDIT report information for SEC-17, SEC-24, SEC-25 and SEC-26, and SEC-27 for Oracle. Added a space in the SELECT procedures in the predicate.
Database Administrati on	Ensuring Data Integrity	Modified "Running DDDAUDIT" section. Removed INDEX-2 and INDEX-3. They were deprecated and moved into INDEX-1.
Integration Broker	Sending and Receiving Messages, Generating and Sending Messages, Setting and Overriding Target Connector Properties at Runtime	This section in PeopleBooks contained a subsection entitled, "Setting and Overriding Target Connector Properties at Runtime Using the OnRequestSend Event." OnRequestSend is a method. The title of the section has been changed to, "Setting and Overriding Target Connector Properties at Runtime Using the OnRequestSend Method."
Integration Broker	Sending and Receiving Messages, Generating and Sending Messages, Setting and Overriding Target Connector Properties at Runtime, Example: Setting Target Connector Properties Using the OnRequestSe nd Method	This section in PeopleBooks shows a PeopleCode example for loading all connectors that exist for a node and adding one additional property. The additional property being added was incorrectly referenced as FILENAME. The property name is mixed-case and is referenced as FileName. The example in PeopleBooks has been corrected.

PeopleBook	Chapter	Description
Integration Broker	Managing Services, Activating and Deactivating Services in Bulk	Previous versions of this PeopleBook incorrectly stated that when you deactivate a service the handler definitions, routing definitions, and queue definition associated with the service become deactivated. However, when you deactivate a service the handler definitions and routing definitions associated with the service do get deactivated. The queue definition does not become deactivated as it can be shared with other service operations. PeopleBooks has been corrected.
Integration Broker	Managing Service Operation Routing Definitions, Configuring Routing Definitions, Defining General Routing Information	The documentation for when the OnReceive Handler field appears on the Routings Routing Definitions page has been corrected as follows: This field displays when an OnReceive handler is defined for the service operation and one of the following conditions exists: The sending node is the local node, or; The service operation type is asynchronous request/response where the sender is not local and the receiver is local, or; The system is serving as a hub, and neither the sender (initiator) nor final receiver are local. Previous versions of PeopleBooks stated that all three conditions had to exist for the field to appear on the Routings - Routing Definitions page.
Integration Broker Administrati on	Configuring the System for Handling Services, Understandin g Configuring the System for Handling Services	Enhanced the section on namespaces to clarify that default values for the service and schema namespace are set on the Service Configuration page and that these values can be redefined on the service definition and in the message schema (in the case of nonrowset-based messages).
Integration	Managing	Added information to this section that states that

PeopleBook	Chapter	Description
Broker Administrati on	Integration Gateways, Understandin g Integration Gateway Configuration , Integration Gateway Versions and Application Server Versions	any remote gateway configured must be at the same version as the local-defined gateway.
Integration Broker Administrati on	Using the Integration Network, Prerequisites for Using the Integration Network	Added a section to the Using the Integration Network chapter that describes the prerequisites for using the integration network, including having PeopleTools installed, having PeopleTools running (the application server and web server), and the security requirement of users having the Integration Administration role assigned to their user profile.
Integration Broker Administrati on	Using the Integration Network, Deleting Nodes from the Integration Network	Added a section on the proper steps to delete a node from the integration network.
Integration Broker Administrati on	Setting Up Secure Integration Environments , Implementing Web Services Security, Understandin g WS- Security Processing Using SAML	The graphic in the section contained an error. It showed that the SAML credentials can be the default user ID or the PeopleSoft/single signon user ID. The SAML credentials is the logon user ID. The graphic in the section has been corrected.

PeopleBook	Chapter	Description
	Tokens, Outbound WS-Security Processing Using SAML Tokens	
PeopleCode API Reference	BI Publisher Classes	Corrected the description and returns for the ReportManager class, GetReportList method to indicate that it returns an array of Report objects (not ReportDefn objects as previously documented).
PeopleCode API Reference	BI Publisher Classes	Added missing documentation for the ReportFileName property to the ReportDefn class.
PeopleCode API Reference	Charting Classes	For the Gantt class, IsDrillable property, deleted the table row that indicated this property applied when a user clicked on an expand/collapse icon.
PeopleCode API Reference	Charting Classes	Corrected the code example for a scatter chart.
PeopleCode API Reference	Charting Classes	Corrected the input parameter for the following methods to indicate that an array of string is required (not an array of any): Chart class, SetXAxisLabels method Chart class, SetYAxisLabels method RatingBoxChart class, SetXAxisLabels method RatingBoxChart class, SetYAxisLabels method
PeopleCode API Reference	Charting Classes	Added documentation for the Chart class, SetGlyphArray method, which was overlooked and mistakenly not documented previously.
PeopleCode API Reference	File Class	For the Open method, added information on error conditions that prevent a Unicode file (UCS-2 or UTF-8) from being opened.
PeopleCode API	Internet Script Classes	For the RedirectURL method of the Response class, added the following note:

PeopleBook	Chapter	Description
Reference	(iScript)	Note. This function does not issue any kind of warning to the user about losing data. Your application should verify that all data is saved before launching a new page.
PeopleCode API Reference	XmlDoc Classes	Corrected the information on use of SOAPDoc objects to make it consistent with similar information in the SOAPDoc Class chapter.
PeopleCode Developer's Guide	Working With File Attachments	In "FTP Site Considerations," indicated that for many FTP servers, the FTP server's home directory is specifiable on a per-FTP-user basis.
PeopleCode Developer's Guide	Working With File Attachments	On the WebSphere web server, indicated that there are two deployed copies of web.xml and both must be edited to change the allowed MIME types. The second copy is located in: • PS_HOME/webserv/profile_name/config/cells/app_nameNodeCell/applications/app_name.ear/deployments/app_name/POR TAL.war/WEB-INF/web.xml
PeopleCode Language Reference	PeopleCode Built-in Functions	 Updated the documentation for CleanAttachments to provide additional information: When large numbers of orphaned file attachments might exist, Oracle recommends using the delivered Application Engine program, CLEANATT84, rather than the Delete Orphan Attachments button to remove the orphaned files. This avoids potential timeout issues. Because CleanAttachments is designed to work with multiple files, to track errors when using CleanAttachments, set your PeopleCode trace to 2112 and your SQL trace to 15 so that errors will be written to the appropriate trace files.
PeopleCode	PeopleCode	For the DoModalX and DoModalXComponent

PeopleBook	Chapter	Description
Language Reference	Built-in Functions	functions, updated information on the showInModal parameter to clarify that it completely overwrites the primary window when set to False. Added a note to avoid calling DoModalX or DoModalXComponent with the showInModal parameter set to False after having called DoModal or DoModalComponent, or after having called DoModalX or DoModalXComponent when the showInModal parameter is set to True.
PeopleCode Language Reference	PeopleCode Built-in Functions	For the EndModal and EndModalComponent functions, added a note that multiple, simultaneous EndModal or EndModalComponent invocations will close all open modal secondary windows.
PeopleCode Language Reference	PeopleCode Built-in Functions	For the DetachAttachment and ViewAttachment functions, clarified the following: If file type restrictions are changed so that access to a previously uploaded file is now blocked, a call to the function will return % Attachment_Success, even though the file and its contents are not downloaded.
PeopleCode Language Reference	PeopleCode Built-in Functions	For the GetFile function, added information on error conditions that prevent a Unicode file (UCS-2 or UTF-8) from being opened.
PeopleCode Language Reference	PeopleCode Built-in Functions	The SendMail function has been deprecated. Use the MCFOutboundEmail class instead.
PeopleCode Language Reference	PeopleCode Built-in Functions	For the SetTracePC function, corrected the system constant from %TracePC_EachStmt to %TracePC_Statements.
PeopleSoft Applications Users Guide	Working With Grids and Scroll Areas: Navigating Through Data, "Finding Data"	Clarified that the Find feature does not search HTML areas that are on grids or scroll areas
Pivot Grid	Understandin	Added the Copying a Pivot Grid Between

PeopleBook	Chapter	Description
	g PeopleSoft Pivot Grid	Databases section, including the names of the dms scripts used to import and export the specific pivot grid models.
Portal Technologies	Administerin g Portals Administerin g Homepages, Dashboard Pages and Pagelets Creating and Configuring WorkCenter Pages	Corrected and clarified information regarding deferred pagelet loading (formerly referred to as parallel loading or lazy loading in a few places) and moved discussion of the PTPGLTDEFERLOAD content reference attribute to a troubleshooting section.
Portal Technologies	Configuring the Portal Environment	When single signon has been set up, the portal web server and any content provider web servers should have the same values for the following fields: Inactivity Warning, Inactivity Logout, and HTTP Session Inactivity.
Portal Technologies	Configuring the Portal Environment	Updated the information on the attachmentExtraWindow custom property to explain that it applies to a secondary window displayed by Internet Explorer only.
Portal Technologies	Configuring Interwindow Communicati on	Revised the IWC chapter to include new examples, a revised process flow and diagram, clearer descriptions of IWC terms and features, and revised instructions and screen shots for publishing and subscribing to IWC messages.
Portal Technologies	Developing and Configuring Related Content Services	Added the following limitation: A component must be registered in order to select it to assign related content.
Portal Technologies	Developing and	Please note the following limitations on the display and use of related content:

PeopleBook	Chapter	Description
	Configuring Related Content Services	 The related content menu and the Related Content frame will not be displayed on pages that have the pagebar option set to disabled. The related content menu and the Related Content frame will not be displayed for modal or secondary pages. If the modal or secondary page has a related actions menu or glyph on a field that has a service targeted to open in <i>Target Content</i>, the frame will be opened in a new window instead. The related content menus, the Related Content frame, and related actions menus and links will not be displayed for content that has been produced for WSRP consumption. For example, the Related Actions menu will not be displayed on a pivot grid that has been produced as WSRP content. In accessibility mode, keyboard-only navigation is not available for the related content or related actions menus. Alternatively, you can use standard menu navigation.
Portal Technologies	Developing and Configuring Related Content Services	Added this note regarding configuration of the Actions folder and SmartNavigation: The Actions folder displays depending on the configuration of related actions for SmartNavigation. If the related actions are attached at the chart component level, the Actions folder will not appear in the drop down menu. If the related actions are attached to the data source's detail component, the Actions folder will appear in the drop down menu.
Portal Technologies	Developing and Configuring	In the section titled "Related Content Frame Options," described the Default Service option and the Sequence number column.

PeopleBook	Chapter	Description
	Related Content Services	
Portal Technologies	Using WSRP to Consume and Produce Remote Portlets	Please note the following limitations of producing PeopleSoft content to be consumed as a remote WSRP portlet: • Related content and related actions cannot be consumed as WSRP content. • WorkCenters cannot be consumed as WSRP content. • Gantt class, OrgChart class, and RatingBoxChart class objects cannot be consumed as WSRP content.
Security Administrati on	Setting General User Profile Attributes	Modified description for the Symbolic ID field, to indicate that the Symbolic ID is required when users submit jobs using Process Scheduler.
Service Operations Monitor	Running Batch Service Operation Archiving Processes	This chapter has been rewritten to clarify the differences in archiving asynchronous service operations versus synchronous service operations.
Service Operations Monitor	Running Batch Error Notification Processes	The incorrect path to the Error Notification page used for running batch error notification processes appeared in the Running Batch Error Notification Processes chapter in PeopleBooks. The incorrect path appeared in the Understanding Batch Error Notification Processes section and the Running Batch Error Notification Processes section. The correct path to the Error Notification page is PeopleTools, Integration Broker, Service Operations Monitor, Monitoring, Error Notification. The error has been corrected in PeopleBooks.
System and Server Administrati on	Using PeopleTools Utilities, Administratio	Added clarification to the note regarding the message sets reserved by Oracle.

PeopleBook	Chapter	Description
	n Utilities, Message Catalog	
System and Server Administrati on	Using PSADMIN Menus, Using the Web (PIA) Server Menu	Added a note stating that to view or edit the PIA configuration files when launched through PSADMIN on non-Windows systems (such as UNIX or Linux), an X Window System must be configured and running.
System and Server Administrati on	Using PeopleTools Utilities, Using Administratio n Utilities, Copy File Attachments	Added a note describing Oracle's recommendation to use the delivered CLEANATT84 Application Engine program rather than the Delete Orphan Attachments button.
System and Server Administrati on	Using PeopleTools Utilities, Using Administratio n Utilities, Load Application Server Cache	Updated procedure to point out differences between Windows and UNIX\Linux directory structure, as well as case requirements when creating the \SHARE directory for setting up shared cache.
System and Server Administrati on	Setting Application Server Domain Parameters, PSTOOLS Options	Added notes related to the proxy settings and the Java VM Options settings clarifying that if any Java code requires connection to the proxy, the proxy settings need to be set using the Java VM Options for the Java programs.
System and Server Administrati on	Working with IBM WebSphere	Clarified that Oracle no longer provides IBM WebSphere software. Customers must contact IBM for supported software versions.

PeopleBook	Chapter	Description
System and Server Administrati on	Setting Application Server Domain Parameters	Updated the documentation for MaxCacheMemory. Previously, it listed the default value for this parameter as 10, but the default (delivered) value for this parameter has been 0 (disabled) for numerous releases.
System and Server Administrati on	Securing PS_HOME and PS_CFG_HO ME, Resolving Initialization Timeout Issues	Updated the instructions for modifying timeout settings to include the use of the PeopleSoft Domain Environment Settings menu, accessed from the Quick-configure menu's Edit environment settings option.