

Oracle® Tuxedo JCA Adapter

Product Overview

11g Release 1 (11.1.1.2)

November 2010

ORACLE®

Copyright © 2010, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Oracle Tuxedo JCA Adapter Overview

Understanding the Oracle Tuxedo JCA Adapter	-1
A Brief History of the Oracle JCA Adapter.	-2
Release 11g Release 1 (11.1.1.1.0)	-2
Bi-Directional Service Request Invocation	-3
Transaction Context and Identity Propagation	-3
Session Authentication	-3
Data Privacy.	-4
Secure Socket Layer Support.	-4
Common Client Interface for Application Development	-4
Java Application-To-Monitor Interface.	-5
Limitations	-5
Release 11g Release 1 (11.1.1.2)	-5
Oracle Tuxedo JCA Adapter Supported Standards	-5
What's Next	-6

Oracle Tuxedo JCA Adapter Overview

This chapter contains the following sections:

- [Understanding the Oracle Tuxedo JCA Adapter](#)
- [A Brief History of the Oracle JCA Adapter](#)
- [Oracle Tuxedo JCA Adapter Supported Standards](#)
- [What's Next](#)

Understanding the Oracle Tuxedo JCA Adapter

The Oracle Tuxedo JCA Adapter is a JCA-based resource adapter that provides bi-directional service invocation between a JCA 1.5 compliant application servers and the Oracle Tuxedo system. Oracle Tuxedo JCA Adapter supports global and local transactions conforming to JCA transaction standards. It supports connection management, transaction infestation, identity propagation, and link-level security. Link-level security uses industry standard SSL/TLS or a proprietary high performance algorithm.


Oracle Tuxedo JCA Adapter supports synchronous and asynchronous request invocations. It supports JCA standard Common Client Interface (CCI) as well as Oracle Tuxedo standard JATMI (Java Application-To-Monitor Interface) API for use in JEE applications (EJBs, POJOs, Servlets/ JSPs, etc.), which need to access Oracle Tuxedo services. In order to access JEE application services from Oracle Tuxedo applications, standard ATMI is used. To an Oracle Tuxedo JEE, services appear as Oracle Tuxedo services.

Oracle Tuxedo JCA Adapter also creates a contract between the application server and the resource adapter using JCA standard Service Provider Interface (SPI). It allows Oracle Tuxedo JCA Adapter to be managed by (and compatible with), any JCA compliant application server.

Oracle Tuxedo JCA Adapter can be configured using a combination of the JCA standard resource adapter configuration file (`ra.xml`) and the Oracle Tuxedo specific configuration file (`dmconfig.xml`). Also, Oracle Tuxedo JCA Adapter can be deployed using native application server methods.

Figure 1 shows a graphical representation of the Oracle Tuxedo JCA Adapter architecture.

Figure 1 Oracle Tuxedo JCA Adapter Architecture



A Brief History of the Oracle JCA Adapter

Release 11g Release 1 (11.1.1.1.0)

Oracle Tuxedo JCA Adapter 11g Release 1 (11.1.1.1.0) introduced the following features:

- [Bi-Directional Service Request Invocation](#)
- [Transaction Context and Identity Propagation](#)
- [Session Authentication](#)
- [Data Privacy](#)
- [Secure Socket Layer Support](#)
- [Common Client Interface for Application Development](#)
- [Java Application-To-Monitor Interface](#)

Bi-Directional Service Request Invocation

The Oracle Tuxedo JCA Adapter allows a JEE application to access Oracle Tuxedo services using the JCA Common Client Interface (CCI) or the Java Application-To-Monitor Interface (JATMI). It also allows Oracle Tuxedo clients to access a POJO or EJB java object in an application server.

Transaction Context and Identity Propagation

Outbound transactions (application server-to-Oracle Tuxedo) are supported for transaction types defined by the Oracle Tuxedo JCA Adapter. The following transactions are supported:

- Container managed XA Transactions
- Container managed Local Transactions
- Adapter managed Local Transactions

Oracle Tuxedo JCA Adapter allows user identity to be sent to Oracle Tuxedo along with the service request. This allows proper access control of Oracle Tuxedo services from a remote user.

Session Authentication

Session authentication allows the Oracle Tuxedo JCA Adapter and the Oracle Tuxedo system to authenticate each other and create a trust relationship. Session authentication supports both domain password authentication and application password authentication.

Data Privacy

Link-level encryption is supported up to 128-bit encryption strength to protect data privacy between the java application server and Oracle Tuxedo. The following encryption strength levels are supported:

- 40-bit
- 56-bit
- 128-bit

Secure Socket Layer Support

Industrial standard Secure Socket Layer is supported for added security between Oracle Tuxedo JCA Adapter and Oracle Tuxedo. The following encryption strength levels are supported:

- 56-bit
- 112-bit
- 128-bit
- 256-bit

Common Client Interface for Application Development

The JEE Connector Architecture Common Client Interface (CCI) is supported for Oracle Tuxedo client access. The following Oracle Tuxedo typed buffers are supported for use with CCI records:

- STRING
- CARRAY
- FML/FML32
- MBSTRING
- VIEW/VIEW32
- X_C_TYPE
- X_COMMON
- X_OCTET
- XML

For more information see, [Oracle Tuxedo 11gR1, Managing Typed Buffers in *Programming An Oracle Tuxedo ATMI Application Using C*](#).

Java Application-To-Monitor Interface

The Java Application-To-Monitor Interface (JATMI) is a Java language-based, X/open XATMI interface that provides high performance global transaction synchronization functionality supported by Oracle Tuxedo. The following Oracle Tuxedo ATMIs are supported:

- tpcall
- tpacall
- tpacall (with asynchronous reply)
- tpcancel
- tpgetrply
- tpenqueue
- tpdequeue

For more information, see the [Oracle Tuxedo 11gR1 Command Reference Guide](#).

Limitations

The Oracle Tuxedo JCA Adapter *does not* support the following functionality:

- Inbound from Oracle Tuxedo request impersonation for authentication and ACL
- Inbound transactions from Oracle Tuxedo

Release 11g Release 1 (11.1.1.2)

Oracle Tuxedo JCA Adapter 11g Release 1 (11.1.1.2) introduces the following enhancements:

- Enhancements
 - Simplified Configuration and Deployment

Oracle Tuxedo JCA Adapter Supported Standards

Oracle Tuxedo JCA Adapter 11gR1 supports the following standard(s):

- [J2EE Connector Architecture \(Specification 1.5\)](#)

What's Next

After becoming familiar with the Oracle Tuxedo JCA Adapter Product Overview, refer to the following topics:

- Release Information
- For information regarding the current product release, refer to the [Oracle Tuxedo JCA Release Notes](#).
- Installing, Configuring, and Deploying the Oracle Tuxedo JCA Adapter.

For an explanation of how to install the product, refer to the [Oracle Tuxedo JCA Adapter Users Guide](#).

- Programming the Oracle Tuxedo JCA Adapter and Examples

For an explanation of how to program with the product, refer to the [Oracle Tuxedo JCA Adapter Programming Guide](#) and [Oracle Tuxedo JCA Adapter Reference Guide](#).