



IA-32 Assembly Language Reference Manual

Sun Microsystems, Inc.
901 San Antonio Road
Palo Alto, CA 94303-4900
U.S.A.

Part No: 816-1323-06
December 2001

Copyright 2001 Sun Microsystems, Inc. 901 San Antonio Road Palo Alto, CA 94303-4900 U.S.A. All rights reserved.

This product or document is protected by copyright and distributed under licenses restricting its use, copying, distribution, and decompilation. No part of this product or document may be reproduced in any form by any means without prior written authorization of Sun and its licensors, if any. Third-party software, including font technology, is copyrighted and licensed from Sun suppliers.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California. UNIX is a registered trademark in the U.S. and other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, docs.sun.com, AnswerBook, AnswerBook2, and Solaris are trademarks, registered trademarks, or service marks of Sun Microsystems, Inc. in the U.S. and other countries. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon an architecture developed by Sun Microsystems, Inc.

The OPEN LOOK and Sun™ Graphical User Interface was developed by Sun Microsystems, Inc. for its users and licensees. Sun acknowledges the pioneering efforts of Xerox in researching and developing the concept of visual or graphical user interfaces for the computer industry. Sun holds a non-exclusive license from Xerox to the Xerox Graphical User Interface, which license also covers Sun's licensees who implement OPEN LOOK GUIs and otherwise comply with Sun's written license agreements.

Federal Acquisitions: Commercial Software—Government Users Subject to Standard License Terms and Conditions.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright 2001 Sun Microsystems, Inc. 901 San Antonio Road Palo Alto, CA 94303-4900 U.S.A. Tous droits réservés

Ce produit ou document est protégé par un copyright et distribué avec des licences qui en restreignent l'utilisation, la copie, la distribution, et la décompilation. Aucune partie de ce produit ou document ne peut être reproduite sous aucune forme, par quelque moyen que ce soit, sans l'autorisation préalable et écrite de Sun et de ses bailleurs de licence, s'il y en a. Le logiciel détenu par des tiers, et qui comprend la technologie relative aux polices de caractères, est protégé par un copyright et licencié par des fournisseurs de Sun.

Des parties de ce produit pourront être dérivées du système Berkeley BSD licenciés par l'Université de Californie. UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, docs.sun.com, AnswerBook, AnswerBook2, et Solaris sont des marques de fabrique ou des marques déposées, ou marques de service, de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays. Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

L'interface d'utilisation graphique OPEN LOOK et Sun™ a été développée par Sun Microsystems, Inc. pour ses utilisateurs et licenciés. Sun reconnaît les efforts de pionniers de Xerox pour la recherche et le développement du concept des interfaces d'utilisation visuelle ou graphique pour l'industrie de l'informatique. Sun détient une licence non exclusive de Xerox sur l'interface d'utilisation graphique Xerox, cette licence couvrant également les licenciés de Sun qui mettent en place l'interface d'utilisation graphique OPEN LOOK et qui en outre se conforment aux licences écrites de Sun.

CETTE PUBLICATION EST FOURNIE "EN L'ETAT" ET AUCUNE GARANTIE, EXPRESSE OU IMPLICITE, N'EST ACCORDEE, Y COMPRIS DES GARANTIES CONCERNANT LA VALEUR MARCHANDE, L'APTITUDE DE LA PUBLICATION A REpondre A UNE UTILISATION PARTICULIERE, OU LE FAIT QU'ELLE NE SOIT PAS CONTREFAISANTE DE PRODUIT DE TIERS. CE DENI DE GARANTIE NE S'APPLIQUERAIT PAS, DANS LA MESURE OU IL SERAIT TENU JURIDIQUEMENT NUL ET NON AVENU.



011025@2471



Contents

Preface	11
1 Assembler Input	15
Introduction	15
Source Files in Assembly Language Format	16
File Organization	16
Statements	17
Values and Symbol Types	17
Expressions	20
Expression Syntax	20
Expression Semantics (Absolute vs. Relocatable)	21
Machine Instruction Syntax	22
Instruction Description	25
Pseudo Operations	26
General Pseudo Operations	26
Symbol Definition Pseudo Operations	30
2 Instruction-Set Mapping	33
Introduction	34
Notational Conventions	34
References	37
Segment Register Instructions	37
Load Full Pointer (lds,les, lfs, lgs, and lss)	37
Pop Stack into Word (pop)	38
Push Word/Long onto Stack (push)	39

I/O Instructions	40
Input from Port (in, ins)	40
Output from Port (out, outs)	41
Flag Instructions	42
Load Flags into AH Register (lahf)	42
Store AH into Flags (sahf)	43
Pop Stack into Flag (popf)	43
Push Flag Register Onto Stack (pushf)	44
Complement Carry Flag (cmc)	44
Clear Carry Flag (clc)	45
Set Carry Flag (stc)	45
Clear Interrupt Flag (cli)	45
Set Interrupt Flag (sti)	46
Clear Direction Flag (cld)	46
Set Direction Flag (std)	47
Arithmetic Logical Instructions	48
Integer Addition (add)	48
Integer Add With Carry (adc)	49
Integer Subtraction (sub)	49
Integer Subtraction With Borrow (sbb)	50
Compare Two Operands (cmp)	51
Increment by 1 (inc)	52
Decrease by 1 (dec)	53
Logical Comparison or Test (test)	53
Shift (sal, shl, sar, shr)	54
Double Precision Shift Left (shld)	55
Double Precision Shift Right (shrd)	56
One's Complement Negation (not)	57
Two's Complement Negation (neg)	58
Check Array Index Against Bounds (bound)	59
Logical And (and)	59
Logical Inclusive OR (or)	60
Logical Exclusive OR (xor)	61
Multiply and Divide Instructions	62
Signed Multiply (imul)	62
Unsigned Multiplication of AL, AX or EAX(mul)	64
Unsigned Divide (div)	65

Signed Divide (idiv)	66
Conversion Instructions	67
Convert Byte to Word (cbtw)	67
Convert Word to Long (cwtl)	67
Convert Signed Word to Signed Double Word (cwtd)	68
Convert Signed Long to Signed Double Long (cltd)	68
Decimal Arithmetic Instructions	69
Decimal Adjust AL after Addition (daa)	69
Decimal Adjust AL after Subtraction (das)	69
ASCII Adjust after Addition (aaa)	70
ASCII Adjust after Subtraction (aas)	71
ASCII Adjust AX after Multiply (aam)	71
ASCII Adjust AX before Division (aad)	72
Coprocessor Instructions	73
Wait (wait, fwait)	73
String Instructions	73
Move Data from String to String (movs)	74
Compare String Operands (cmps)	74
Store String Data (stos)	75
The Load String Operand (lods)	76
Compare String Data (scas)	77
Look-Up Translation Table (xlat)	78
Repeat String Operation (rep, repnz, repz)	79
Procedure Call and Return Instructions	79
Far Call — Procedure Call (lcall)	79
Near Call — Procedure Call (call)	80
Return from Procedure (ret)	81
Long Return (lret)	82
Enter/Make Stack Frame for Procedure Parameters (enter)	83
High Level Procedure Exit (leave)	84
Jump Instructions	84
Jump if ECX is Zero (jcxz)	84
Loop Control with CX Counter (loop, loopnz, loopz)	85
Jump (jmp, ljmp)	86
Interrupt Instructions	87
Call to Interrupt Procedure (int, into)	87
Interrupt Return (iret)	88

Protection Model Instructions	89
Store Local Descriptor Table Register (sldt)	89
Store Task Register (str)	90
Load Local Descriptor Table Register (lldt)	90
Load Task Register (ltr)	91
Verify a Segment for Reading or Writing (verr, verw)	91
Store Global/Interrupt Descriptor Table Register (sgdt, sidt)	92
Load Global/Interrupt Descriptor Table (lgdt, lidt)	93
Store Machine Status Word (smsw)	94
Load Machine Status Word (lmsw)	95
Load Access Rights (lar)	95
Load Segment Limit (lsl)	96
Clear Task-Switched (clts)	97
Adjust RPL Field of Selector (arpl)	97
Bit Instructions	98
Bit Scan Forward (bsf)	98
Bit Scan Reverse (bsr)	99
Bit Test (bt)	99
Bit Test And Complement (btc)	100
Bit Test And Reset (btr)	100
Bit Test And Set (bts)	101
Exchange Instructions	102
Compare and Exchange (cmpxchg)[486]	102
Floating-Point Transcendental Instructions	102
Floating-Point Sine (fsin)	102
Floating-Point Cosine (fcos)	102
Floating-Point Sine and Cosine (fsincos)	103
Floating-Point Constant Instructions	103
Floating-Point Load One (fld)	103
Processor Control Floating-Point Instructions	104
Floating-Point Load Control Word (fldcw)	104
Floating-Point Load Environment (fldenv)	104
Miscellaneous Floating-Point Instructions	104
Floating-Point Different Remainder (fprem)	104
Floating-Point Comparison Instructions	105
Floating-Point Unsigned Compare (fucom)	105
Floating-Point Unsigned Compare And Pop (fucomp)	105

Floating-Point Unsigned Compare And Pop Two (fucompp)	106
Load and Move Instructions	106
Load Effective Address (lea)	106
Move (mov)	107
Move Segment Registers (movw)	108
Move Control Registers (mov)	108
Move Debug Registers (mov)	109
Move Test Registers (mov)	109
Move With Sign Extend (movsx)	110
Move With Zero Extend (movzb)	110
Pop Instructions	111
Pop All General Registers (popa)	111
Push Instructions	112
Push All General Registers (pusha)	112
Rotate Instructions	112
Rotate With Carry Left (rcl)	112
Rotate With Carry Right (rcr)	113
Rotate Left (rol)	114
Rotate Right (ror)	115
Byte Instructions	116
Byte Set On Condition (setcc)	116
Byte Swap (bswap) [486]	117
Exchange Instructions	117
Exchange And Add (xadd) [486]	117
Exchange Register / Memory With Register (xchg)	118
Miscellaneous Instructions	119
Write Back and Invalidate Cache (wbinvd) [486 only]	119
Invalidate (invd) [486 only]	119
Invalidate Page (invlpg) [486 only]	119
LOCK Prefix (lock)	120
No Operation (nop)	121
Halt (hlt)	121
Real Transfer Instructions	122
Load Real (fld)	122
Store Real (fst)	122
Store Real and Pop (fstp)	123
Exchange Registers (fxch)	123

Integer Transfer Instructions	124
Integer Load (fild)	124
Integer Store (fist)	124
Integer Store and Pop (fistp)	124
Packed Decimal Transfer Instructions	125
Packed Decimal (BCD) Load (fbld)	125
Packed Decimal (BCD) Store and Pop (fbstp)	125
Addition Instructions	125
Real Add (fadd)	125
Real Add and Pop (faddp)	126
Integer Add (fiadd)	126
Subtraction Instructions	126
Subtract Real and Pop (fsub)	126
Subtract Real (fsubp)	127
Subtract Real Reversed (fsubr)	127
Subtract Real Reversed and Pop (fsubrp)	127
Integer Subtract (fisubrp)	128
Integer Subtract Reverse (fisubr)	128
Multiplication Instructions	128
Multiply Real (fmul)	128
Multiply Real and Pop (fmulp)	129
Integer Multiply (fimul)	129
Division Instructions	129
Divide Real (fdiv)	129
Divide Real and Pop (fdivp)	130
Divide Real Reversed (fdivr)	130
Divide Real Reversed and Pop (fdivrp)	130
Integer Divide (fidiv)	130
Integer Divide Reversed (fidivr)	131
Floating-Point Opcode Errors	131
Miscellaneous Arithmetic Operations	132
Square Root (fsqrt)	132
Scale (fscale)	132
Partial Remainder (fprem)	133
Round to Integer (frndint)	133
Extract Exponent and Significand (fextract)	133
Absolute Value (fabs)	133

Change Sign (fchs)	134
Comparison Instructions	134
Compare Real (fcom)	134
Compare Real and Pop (fcomp)	134
Compare Real and Pop Twice (fcompp)	135
Integer Compare (ficom)	135
Integer Compare and Pop (ficompp)	135
Test (ftst)	136
Examine (fxam)	136
Transcendental Instructions	137
Partial Tangent (fptan)	137
Partial Arctangent (fpatan)	137
$2^x - 1$ (f2xm1)	137
$Y * \log_2 X$ (fyl2x)	137
$Y * \log_2 (X+1)$ (fyl2xp1)	138
Constant Instructions	138
Load $\log_2 E$ (fldl2e)	138
Load $\log_2 10$ (fldl2t)	138
Load $\log_{10} 2$ (fldlg2)	139
Load $\log_e 2$ (fldln2)	139
Load pi (fldpi)	139
Load + 0 (fldz)	139
Processor Control Instructions	140
Initialize Processor (finit, fnint)	140
No Operation (fnop)	140
Save State (fsave, fnsave)	140
Store Control Word (fstcw, fnstcw)	141
Store Environment (fstenv, fnstenv)	141
Store Status Word (fstsw, fnstsw)	141
Restore State (frstor)	141
CPU Wait (fwait, wait)	142
Clear Exceptions (fclex, fnclex)	142
Decrement Stack Pointer (fdecstp)	142
Free Registers (ffree)	142
Increment Stack Pointer (fincstp)	142

3	Assembler Output	145
	Introduction	145
	Object Files in Executable and Linking Format (ELF)	146
	ELF Header	147
	Section Header	148
	Sections	152
	Symbol Tables	154
	String Tables	155
	Attribute Expression	156
A	Using the Assembler Command Line	157
	Assembler Command Line	157
	Assembler Command Line Options	158
	Disassembling Object Code	159
	Index	161

Preface

This preface is a brief description of the SunOS™ assembler that generates code for the Intel 32-bit processor architecture (IA-32). This preface also includes a list of documents that can be used for reference.

The SunOS assembler for IA-32, referred to as the “IA-32 Assembler” in this manual, translates source files that are in assembly language format into object files in linking format.

In the program development process, the assembler is a tool to use in producing program modules intended to exploit features of the IA-32 architecture in ways that cannot be easily done using high level languages and their compilers.

Whether assembly language is chosen for the development of program modules depends on the extent to which and the ease with which the language allows the programmer to control the architectural features of the processor.

The assembly language described in this manual offers full direct access to the IA-32 instruction set. The assembler may also be used in connection with SunOS 5.1 macro preprocessors to achieve full macro-assembler capability. Furthermore, the assembler responds to directives that allow the programmer direct control over the contents of the relocatable object file.

This document describes the language in which the source files must be written. The nature of the machine mnemonics governs the way in which the program’s executable portion is written. This document includes descriptions of the pseudo operations that allow control over the object file. This facilitates the development of programs that are easy to understand and maintain.

Before You Read This Book

Use the following documents as references:

- Intel 80386 Programmer's Reference Manual
- i486™ Microprocessor Programmer Reference Manual (1990)
- Intel 80387 Programmer's Reference Manual (1987)
- System V Application Binary Interface Intel 386 Processor Supplement
- System V Application Binary Interface
- SVID System V Interface Definition

You should also become familiar with the following:

- Man pages: `as(1)`, `ld(1)`, `cpp(1)`, `mn(4)`, `cof2elf(1)` (*elf - Executable and Linking Format*), `elf(3E)`, `dis(1)`, `a.out(5)`.
- ELF-related sections of the Programming Utilities manual.

How This Book Is Organized

This document is organized into the following chapters:

Chapter 1 describes the overall structure required by the assembler for input source files.

Chapter 2 describes the instruction set mappings for the IA-32 Assembler.

Chapter 3 provides an overview of ELF (*Executable and Linking Format*) for the relocatable object files produced by the assembler.

Appendix A describes the assembler command line options.

Ordering Sun Documents

Fatbrain.com, an Internet professional bookstore, stocks select product documentation from Sun Microsystems, Inc.

For a list of documents and how to order them, visit the Sun Documentation Center on Fatbrain.com at <http://www1.fatbrain.com/documentation/sun>.

Accessing Sun Documentation Online

The docs.sun.comSM Web site enables you to access Sun technical documentation online. You can browse the docs.sun.com archive or search for a specific book title or subject. The URL is <http://docs.sun.com>.

Typographic Conventions

The following table describes the typographic changes used in this book.

TABLE P-1 Typographic Conventions

Typeface or Symbol	Meaning	Example
AaBbCc123	The names of commands, files, and directories; on-screen computer output	Edit your <code>.login</code> file. Use <code>ls -a</code> to list all files. <code>machine_name% you have mail.</code>
AaBbCc123	What you type, contrasted with on-screen computer output	<code>machine_name% su</code> Password:
<i>AaBbCc123</i>	Command-line placeholder: replace with a real name or value	To delete a file, type rm <i>filename</i> .
<i>AaBbCc123</i>	Book titles, new words, or terms, or words to be emphasized.	Read Chapter 6 in <i>User's Guide</i> . These are called <i>class</i> options. You must be <i>root</i> to do this.

Shell Prompts in Command Examples

The following table shows the default system prompt and superuser prompt for the C shell, Bourne shell, and Korn shell.

TABLE P-2 Shell Prompts

Shell	Prompt
C shell prompt	machine_name%
C shell superuser prompt	machine_name#
Bourne shell and Korn shell prompt	\$
Bourne shell and Korn shell superuser prompt	#

Assembler Input

The IA-32 Assembler translates source files in the assembly language format specified in this document into relocatable object files for processing by the link editor. This translation process is called assembly. The main input required to assemble a source file in assembly language format is that source file itself.

This chapter has the following organization:

- “Introduction” on page 15
- “Source Files in Assembly Language Format” on page 16
- “Pseudo Operations” on page 26

Introduction

In whatever manner it is produced, the source input file must have a certain structure and content. The specification of this structure and content constitutes the syntax of the assembly language. A source file may be produced by one of the following:

- A programmer using a text editor
- A compiler as an intermediate step in the process of translating from a high-level language to executable code
- An automatic program generator
- Some other mechanism.

The assembler may also allow ancillary input incidental to the translation process. For example, there are several invocation options available. Each such option exercised constitutes information input to the assembler. However, this ancillary input has little

direct connection to the translation process, so it is not properly a subject for this manual. Information about invoking the assembler and the available options appears in the `as(1)` man pages.

This chapter describes the overall structure required by the assembler for input source files. This structure is relatively simple: the input source file must be a sequence of assembly language statements. This chapter also begins the specification of the contents of the input source file by describing assembly language statements as textual objects of a certain form.

This document completes the specification by presenting detailed assembly language statements that correspond to the IA-32 instruction set. For more information on assembly language instruction sets, please refer to the product documentation from Intel Corporation.

Source Files in Assembly Language Format

This section details the following:

- file organization
- statements
- values and symbols
- expressions
- machine instruction syntax

File Organization

Input to the assembler is a text file consisting of a sequence of statements. Each statement ends with the first occurrence of a newline character (ASCII LF), or of a semicolon (;) that is not within a string operand or between a slash and a newline character. Thus, it is possible to have several statements on one line.

To make programs easy to read, understand and maintain, however, it is good programming practice not to have more than one statement per line. As indicated above, a line may contain one or more statements. If several statements appear on a line, they must be separated by semicolons (;).

Statements

This section outlines the types of statements that apply to assembly language. Each statement must be one of the following types:

- An empty statement is one that contains nothing other than spaces, tabs, or formfeed characters.

Empty statements have no meaning to the assembler. They can be inserted freely to improve the appearance of a source file or of a listing generated from it.

- An assignment statement is one that gives a value to a symbol. It consists of a symbol, followed by an equal sign (=), followed by an expression.

The expression is evaluated and the result is assigned to the symbol. Assignment statements do not generate any code. They are used only to assign assembly time values to symbols.

- A pseudo operation statement is a directive to the assembler that does not necessarily generate any code. It consists of a pseudo operation code, optionally followed by operands. Every pseudo operation code begins with a period (.).
- A machine operation statement is a mnemonic representation of an executable machine language instruction to which it is translated by the assembler. It consists of an operation code, optionally followed by operands.

Furthermore, any statement remains a statement even if it is modified in either or both of the following ways:

- Prefixing a label at the beginning of the statement.

A label consists of a symbol followed by a colon (:). When the assembler encounters a label, it assigns the value of the location counter to the label.

- Appending a comment at the end of the statement by preceding the comment with a slash (/).

The assembler ignores all characters following a slash up to the next occurrence of newline. This facility allows insertion of internal program documentation into the source file for a program.

Values and Symbol Types

This section presents the values and symbol types that the assembler uses.

Values

Values are represented in the assembler by numerals which can be faithfully represented in standard two's complement binary positional notation using 32 bits. All

integer arithmetic is performed using 32 bits of precision. Note, however, that the values used in an IA-32 instruction may require 8, 16, or 32 bits.

Symbols

A symbol has a value and a symbol type, each of which is either specified explicitly by an assignment statement or implicitly from context. Refer to the next section for the regular definition of the expressions of a symbol.

The following symbols are reserved by the assembler:

`.Commonly referred to as dot. This is the location counter while assembling a program. It takes on the current location in the text, data, or bss section.`

`.text`

This symbol is of type text. It is used to label the beginning of a .text section in the program being assembled.

`.data`

This symbol is of type data. It is used to label the beginning of a data section in the program being assembled.

`.bss`

This symbol is of type bss. It is used to label the beginning of a .bss section in the program being assembled.

`.init`

This is used with C++ programs which require constructors.

`.fini`

This is used with C++ programs which require destructors.

Symbol Types

Symbol type is one of the following:

`undefined`

A value is of undefined symbol type if it has not yet been defined. Example instances of undefined symbol types are forward references and externals.

`absolute`

A value is of absolute symbol type it does not change with relocation. Example instances of absolute symbol types are numeric constants and expressions whose proper sub-expressions are themselves all absolute.

`text`

A value is of text symbol type if it is relative to the `.text` section.

`data`

A value is of data symbol type if it is relative to the `.data` section.

`bss`

A value is of bss symbol type if it is relative to the `.bss` section.

You can give any of these symbol types the attribute `EXTERNAL`.

Sections

Five of the symbol types are defined with respect to certain sections of the object file into which the assembler translates the source file. This section describes symbol types.

If the assembler translates a particular assembly language statement into a machine language instruction or into a data allocation, the translation is associated with one of the following five sections of the object file into which the assembler is translating the source file:

TABLE 1-1 Translations and their Associations

Section	Purpose
<code>text</code>	This is an initialized section. Normally, it is read-only and contains code from a program. It may also contain read-only tables.
<code>data</code>	This is an initialized section. Normally, it is readable and writable. It contains initialized data. These can be scalars or tables.
<code>bss</code>	This is an uninitialized section. Space is not allocated for this segment in the object file.
<code>init</code>	This is used with C++ programs that require constructors.
<code>fini</code>	This is used by C++ programs that require destructors.

An optional section, `.comment`, may also be produced.

The section associated with the translated statement is `.text` unless the original statement occurs after a section control pseudo operation has directed the assembler to associate the statement with another section.

Expressions

The expressions accepted by the assembler are defined by their syntax and semantics. The following are the operators supported by the assembler:

TABLE 1-2 Operators Supported by the Assembler

Operator	Action
+	Addition
-	Subtraction
*	Multiplication
\/	Division
&	Bitwise logical and
	Bitwise logical or
>>	Right shift
<<	Left shift
\%	Remainder operator
!	Bitwise logical and not
^	Bitwise logical XOR

Expression Syntax

Table 1-3 shows syntactic rules, the non terminals are represented by lowercase letters, the terminal symbols are represented by uppercase letters, and the symbols enclosed in double quotes are terminal symbols. There is no precedence assigned to the operators. You must use square brackets to establish precedence.

TABLE 1-3 Syntactical Rules of Expressions

expr	:	term
		expr "+" term
		expr "-" term
		expr "*" term
		expr "/" term
		expr "&" term
		expr " " term
		expr ">>" term
		expr "<<" term
		expr "\%" term
		expr "!" term
		expr "^" term
term	:	id
		number "-" term
		"[" expr "]"
		"<o>" term
		"<s>" term
		;
id	:	LABEL
		;
number	:	DEC_VAL
		HEX_VAL
		OCT_VAL
		BIN_VAL
		;

The terminal nodes are given by the following regular expressions:

```
LABEL = [a-zA-Z_] [a-zA-Z0-9_]*;  
DEC_VAL = [1-9] [0-9]*  
HEX_VAL = 0 [Xx] [0-9a-fA-F] [0-9a-fA-F]*  
OCT_VAL = 0 [0-7]*  
BIN_VAL = 0 [Bb] [0-1] [0-1]*
```

In the above regular expressions, choices are enclosed in square brackets; a range of choices is indicated by letters or numbers separated by a dash (-); and the asterisk (*) indicates zero or more instances of the previous character.

Expression Semantics (Absolute vs. Relocatable)

Semantically, the expressions fall into two groups, absolute and relocatable. The equations later in this section show the legal combinations of absolute and relocatable

operands for the addition and subtraction operators. All other operations are only legal on absolute-valued expressions.

All numbers have the absolute attribute. Symbols used to reference storage, text, or data are relocatable. In an assignment statement, symbols on the left side inherit their relocation attributes from the right side.

In the equations below, *a* is an absolute-valued expression and *r* is a relocatable-valued expression. The resulting type of the operation is shown to the right of the equal sign.

```
a + a = a
r + a = r
a - a = a
r - a = r
r - r = a
```

In the last example, you must declare the relocatable expressions before taking their difference.

Following are some examples of valid expressions:

```
label
$label
[label + 0x100]
[label1 - label2]
$[label1 - label2]
```

Following are some examples of invalid expressions:

```
[$label - $label]
[label1 * 5]
(label + 0x20)
```

Machine Instruction Syntax

This section describes the instructions that the assembler accepts. The detailed specification of how the particular instructions operate is not included; for this, see Intel's 80386 Programmer's Reference Manual.

The following list describes the three main aspects of the IA-32 Assembler assembler:

- All register names use the percent sign (%) as a prefix to distinguish them from symbol names.

- Instructions with two operands use the left one as the source and the right one as the destination. This is reversed from Intel's notation.
- Most instructions that can operate on a byte, word, or long may have b, w, or l appended to them. When an opcode is specified with no type suffix, it usually defaults to long. In general, the IA-32 Assembler derives its type information from the opcode, where the Intel assembler can derive its type information from the operand types. Where the type information is derived motivates the b, w, and l suffixes used in the IA-32 Assembler. For example, in the instruction `movw $1,%eax` the w suffix indicates the operand is a word.

Operands

Three kinds of operands are generally available to the instructions: *register*, *memory*, and *immediate*. Indirect operands are available *only* to jump and call instructions.

The assembler always assumes it is generating code for a 32-bit segment. When 16-bit data is called for (e.g., `movw %ax, %bx`), the assembler automatically generates the 16-bit data prefix byte.

Byte, word, and long registers are available on the IA-32 processor. The instruction pointer (`%eip`) and flag register (`%efl`) are not available as explicit operands to the instructions. The code segment (`%cs`) may be used as a source operand but not as a destination operand.

The names of the byte, word, and long registers available as operands and a brief description of each follow. The segment registers are also listed.

TABLE 1-4 8-bit (byte) General Registers

<code>%al</code>	Low byte of <code>%ax</code> register
<code>%ah</code>	High byte of <code>%ax</code> register
<code>%cl</code>	Low byte of <code>%cx</code> register
<code>%ch</code>	High byte of <code>%cx</code> register
<code>%dl</code>	Low byte of <code>%dx</code> register
<code>%dh</code>	High byte of <code>%dx</code> register
<code>%bl</code>	Low byte of <code>%bx</code> register
<code>%bh</code>	High byte of <code>%bx</code> register

TABLE 1-5 16-bit (word) General Registers

<code>%ax</code>	Low 16-bits of <code>%eax</code> register
------------------	---

TABLE 1-5 16-bit (word) General Registers (Continued)

%cx	Low 16-bits of %ecx register
%dx	Low 16-bits of %edx register
%bx	Low 16-bits of %ebx register
%sp	Low 16-bits of the stack pointer
%bp	Low 16-bits of the frame pointer
%si	Low 16-bits of the source index register
%di	Low 16-bits of the destination index register

TABLE 1-6 32-bit (long) General Registers

%eax	32-bit general register
%ecx	32-bit general register
%edx	32-bit general register
%ebx	32-bit general register
%esp	32-bit stack pointer
%ebp	32-bit frame pointer
%esi	32-bit source index register
%edi	32-bit destination index register

TABLE 1-7 Description of Segment Registers

%cs	Code segment register; all references to the instruction space use this register
%ds	Data segment register, the default segment register for most references to memory operands
%ss	Stack segment register, the default segment register for memory operands in the stack (i.e., default segment register for %bp, %sp, %esp, and %ebp)
%es	General-purpose segment register; some string instructions use this extra segment as their default segment
%fs	General-purpose segment register
%gs	General-purpose segment register

Instruction Description

This section describes the IA-32 instruction syntax.

The assembler assumes it is generating code for a 32-bit segment, therefore, it also assumes a 32-bit address and automatically precedes word operations with a 16-bit data prefix byte.

Addressing Modes

Addressing modes are represented by the following:

```
[sreg:] [offset] [( [base] [, index] [, scale] )]
```

- All the items in the square brackets are optional, but at least one is necessary. If you use any of the items inside the parentheses, the parentheses are mandatory.
- `sreg` is a segment register override prefix. It may be any segment register. If a segment override prefix is present, you must follow it by a colon before the offset component of the address. `sreg` does not represent an address by itself. An address must contain an offset component.
- `offset` is a displacement from a segment base. It may be absolute or relocatable. A label is an example of a relocatable offset. A number is an example of an absolute offset.
- `base` and `index` can be any 32-bit register. `Scale` is a multiplication factor for the index register field. Its value may be 1, 2, 4, 8 to indicate the number to multiply by. The multiplication then occurs by 1, 2, 4, and 8.

Refer to *Intel's 80386 Programmer's Reference Manual* for more details on IA-32 addressing modes.

Following are some examples of addresses:

```
movl var, %eax
```

Move the contents of memory location `var` into `%eax`.

```
movl %cs:var, %eax
```

Move the contents of the memory location `var` in the code segment into `%eax`.

```
movl $var, %eax
```

Move the address of `var` into `%eax`.

```
movl array_base(%esi), %eax
```

Add the address of memory location `array_base` to the contents of `%esi` to get an address in memory. Move the contents of this address into `%eax`.

```
movl (%ebx, %esi, 4), %eax
```

Multiply the contents of %esi by 4 and add this to the contents of %ebx to produce a memory reference. Move the contents of this memory location into %eax.

```
movl struct_base(%ebx, %esi, 4), %eax
```

Multiply the contents of %esi by 4, add this to the contents of %ebx, and add this to the address of struct_base to produce an address. Move the contents of this address into %eax.

Expressions and Immediate Values

An immediate value is an expression preceded by a dollar sign:

```
immediate: "$" expr
```

Immediate values carry the absolute or relocatable attributes of their expression component. Immediate values cannot be used in an expression, and should be considered as another form of address, i.e., the immediate form of address.

```
immediate: "$" expr ", " "$" expr
```

The first expr is 16 bits of segment. The second expr is 32 bits of offset.

Pseudo Operations

The pseudo-operations listed in this section are supported by the IA-32 Assembler.

General Pseudo Operations

Below is a list of the pseudo operations supported by the assembler. This is followed by a separate listing of pseudo operations included for the benefit of the debuggers (dbx(1)).

```
.align val
```

The align pseudo op causes the next data generated to be aligned modulo val. val should be a positive integer value.

```
.bcd val
```

The .bcd pseudo op generates a packed decimal (80-bit) value into the current section. This is not valid for the .bss section. val is a nonfloating-point constant.

- `.bss`
The `.bss` pseudo op changes the current section to `.bss`.
- `.bss tag, bytes`
Define symbol `tag` in the `.bss` section and add `bytes` to the value of `dot` for `.bss`. This does not change the current section to `.bss`. `bytes` must be a positive integer value.
- `.byte val [, val]`
The `.byte` pseudo op generates initialized bytes into the current section. This is not valid for `.bss`. Each `val` must be an 8-bit value.
- `.comm name, expr [, alignment]`
The `.comm` pseudo op allocates storage in the `.data` section. The storage is referenced by the symbol name, and has a size in bytes of `expr`. `expr` must be a positive integer. `name` cannot be predefined. If the alignment is given, the address of the name is aligned to a multiple of alignments.
- `.data`
The `.data` pseudo op changes the current section to `.data`.
- `.double val`
The `.double` pseudo op generates an 80387 64 bit floating-point constant (IEEE 754) into the current section. Not valid in the `.bss` section. `val` is a floating-point constant. `val` is a string acceptable to `atof(3)`; that is, an optional sign followed by a non-empty string of digits with optional decimal point and optional exponent.
- `.even`
The `.even` pseudo op aligns the current program counter (`.`) to an even boundary.
- `.file "string"`
The `.file` op creates a symbol table entry where `string` is the symbol name and `STT_FILE` is the symbol table type. `string` specifies the name of the source file associated with the object file.
- `.float val`
The `.float` pseudo op generates an 80387 32 bit floating-point constant (IEEE 754) into the current section. This is not valid in the `.bss` section. `val` is a floating-point constant. `val` is a string acceptable to `atof(3)`; that is, an optional sign followed by a non-empty string of digits with optional decimal point and optional exponent.
- `.globl symbol [, symbol] *`
The `globl` op declares each `symbol` in the list to be global; that is, each symbol is either defined externally or defined in the input file and accessible in other files; default bindings for the symbol are overridden.
- A global symbol definition in one file satisfies an undefined reference to the same global symbol in another file.

- Multiple definitions of a defined global symbol is not allowed. If a defined global symbol has more than one definition, an error occurs.

Note – This pseudo-op by itself does not define the symbol.

`.ident "string"`

The `.ident` pseudo op creates an entry in the comment section containing `string`. `string` is any sequence of characters, not including the double quote (").

`.lcomm name, expr`

The `.lcomm` pseudo op allocates storage in the `.bss` section. The storage is referenced by the symbol name, and has a size of `expr`. `name` cannot be predefined, and `expr` must be a positive integer type. If the alignment is given, the address of `name` is aligned to a multiple of alignment.

`.local symbol [, symbol] *`

Declares each `symbol` in the list to be local; that is, each symbol is defined in the input file and not accessible in other files; default bindings for the symbol are overridden. These symbols take precedence over *weak* and *global* symbols.

Because local symbols are not accessible to other files, local symbols of the same name may exist in multiple files.

Note – This pseudo-op by itself does not define the symbol.

`.long val`

The `.long` pseudo op generates a long integer (32-bit, two's complement value) into the current section. This pseudo op is not valid for the `.bss` section. `val` is a nonfloating-point constant.

`.nonvolatile`

Defines the end of a block of instruction. The instructions in the block may not be permuted. This pseudo-op has no effect if:

- The block of instruction has been previously terminated by a Control Transfer Instruction (CTI) or a label
- There is no preceding `.volatile` pseudo-op

`.section section_name [, attributes]`

Makes the specified section the current section.

The assembler maintains a section stack which is manipulated by the section control directives. The current section is the section that is currently on top of the stack. This pseudo-op changes the top of the section stack.

- If *section_name* does not exist, a new section with the specified name and attributes is created.
- If *section_name* is a non-reserved section, *attributes* must be included the first time it is specified by the `.section` directive.

`.set name, expr`

The `.set` pseudo op sets the value of symbol *name* to *expr*. This is equivalent to an assignment.

`.string "str"`

This pseudo op places the characters in *str* into the object module at the current location and terminates the string with a null. The string must be enclosed in double quotes (""). This pseudo op is not valid for the `.bss` section.

`.text`

The `.text` pseudo op defines the current section as `.text`.

`.value expr [, expr]`

The `.value` pseudo op is used to generate an initialized word (16-bit, two's complement value) into the current section. This pseudo op is not valid in the `.bss` section. Each *expr* must be a 16-bit value.

`.version string`

The `.version` pseudo op puts the C compiler version number into the `.comment` section.

`.volatile`

Defines the beginning of a block of instruction. The instructions in the section may not be changed. The block of instruction should end at a `.nonvolatile` pseudo-op and should not contain any Control Transfer Instructions (CTI) or labels. The volatile block of instructions is terminated after the last instruction preceding a CTI or label.

`.weak symbol [, symbol]`

Declares each *symbol* in the list to be defined either externally, or in the input file and accessible to other files; default bindings of the symbol are overridden by this directive.

- A *weak* symbol definition in one file satisfies an undefined reference to a global symbol of the same name in another file.
- Unresolved *weak* symbols have a default value of zero; the link editor does not resolve these symbols.
- If a *weak* symbol has the same name as a defined *global* symbol, the weak symbol is ignored and no error results.

Note – This pseudo-op does not itself define the symbol.

`symbol =expr`
Assigns the value of *expr* to *symbol*.

Symbol Definition Pseudo Operations

- `.def name`
The `.def` pseudo op starts a symbolic description for symbol name. See `endef`. name is a symbol name.
- `.dim expr [,expr]`
The `.dim` pseudo op is used with the `.def` pseudo op. If the name of a `.def` is an array, the expressions give the dimensions; up to four dimensions are accepted. The type of each expression should be positive.
- `.endef`
The `.endef` pseudo op is the ending bracket for a `.def`.
- `.file name`
The `.file` pseudo op is the source file name. Only one is allowed per source file. This must be the first line in an assembly file.
- `.line expr`
The `.line` pseudo op is used with the `.def` pseudo op. It defines the source line number of the definition of symbol name in the `.def`. `expr` should yield a positive value.
- `.ln line [,addr]`
This pseudo op provides the relative source line number to the beginning of a function. It is used to pass information through to `sdb`.
- `.scl expr`
The `.scl` pseudo op is used with the `.def` pseudo op. Within the `.def` it gives name the storage class of `expr`. The type of `expr` should be positive.
- `.size expr`
The `.size` pseudo op is used with the `.def` pseudo op. If the name of a `.def` is an object such as a structure or an array, this gives it a total size of `expr`. `expr` must be a positive integer.

`.stabs name type 0 desc value`

`.stabn type 0 desc value`

The `.stabs` and `.stabn` pseudo ops are debugger directives generated by the C compiler when the `-g` option is used. `name` provides the symbol table name and type structure. `type` identifies the type of symbolic information (that is, source file, global symbol, or source line). `desc` specifies the number of bytes occupied by a variable or type, or the nesting level for a scope symbol. `value` specifies an address or an offset.

`.tag str`

The `.tag` pseudo op is used in conjunction with a previously defined `.def` pseudo op. If the name of a `.def` is a structure or a union, `str` should be the name of that structure or union tag defined in a previous `.def-endif` pair.

`.type expr`

The `.type` pseudo op is used within a `.def-endif` pair. It gives name the C compiler type representation `expr`.

`.val expr`

The `.val` pseudo op is used with a `.def-endif` pair. It gives name (in the `.def`) the value of `expr`. The type of `expr` determines the section for name.

Instruction-Set Mapping

This chapter describes the instruction set mappings for the IA-32 Assembler processor. For more details of the operation and a summary of the exceptions, refer to the *Intel 486 Microprocessor Family Programmer's Reference Manual* from Intel Corporation.

This chapter is organized as follows:

- "Introduction" on page 34
- "Segment Register Instructions" on page 37
- "I/O Instructions" on page 40
- "Flag Instructions" on page 42
- "Arithmetic Logical Instructions" on page 48
- "Multiply and Divide Instructions" on page 62
- "Conversion Instructions" on page 67
- "Decimal Arithmetic Instructions" on page 69
- "Coprocesor Instructions" on page 73
- "String Instructions" on page 73
- "Procedure Call and Return Instructions" on page 79
- "Jump Instructions" on page 84
- "Interrupt Instructions" on page 87
- "Protection Model Instructions" on page 89
- "Bit Instructions" on page 98
- "Exchange Instructions" on page 102
- "Floating-Point Transcendental Instructions" on page 102
- "Floating-Point Constant Instructions" on page 103
- "Processor Control Floating-Point Instructions" on page 104
- "Miscellaneous Floating-Point Instructions" on page 104
- "Floating-Point Comparison Instructions" on page 105
- "Load and Move Instructions" on page 106
- "Pop Instructions" on page 111
- "Push Instructions" on page 112
- "Rotate Instructions" on page 112
- "Byte Instructions" on page 116
- "Exchange Instructions" on page 117

- “Miscellaneous Instructions” on page 119
- “Real Transfer Instructions” on page 122
- “Integer Transfer Instructions” on page 124
- “Packed Decimal Transfer Instructions” on page 125
- “Addition Instructions” on page 125
- “Subtraction Instructions” on page 126
- “Multiplication Instructions” on page 128
- “Division Instructions” on page 129
- “Miscellaneous Arithmetic Operations” on page 132
- “Comparison Instructions” on page 134
- “Transcendental Instructions” on page 137
- “Constant Instructions” on page 138
- “Processor Control Instructions” on page 140

Introduction

Although the IA-32 architecture supports address-size attributes of either 16 or 32 bits, the IA-32 assembler only supports address-size attributes of 32 bits. The operand-size is either 16 or 32 bits. An instruction that accesses 16-bit words or 32-bit longs has an operand-size attribute of either 16 or 32 bits.

Notational Conventions

The notational conventions used in the instructions included in this chapter are described below:

- The mnemonics are expressed in a regular expression-type syntax.
- When a group of letters is separated from other letters by a bar (|) within square brackets or curly braces, then the group of letters between the bars or between a bar and a closing bracket or brace is considered an atomic unit.
For example, `fld[1st]` means `fldl`, `flds`, or `fldt`; `fst{1s}` means `fst`, `fstl`, or `fstq`; and `fld{1|1l}` means `fld`, `fldl`, or `fldll`.
- Square brackets ([]) denote choices, but at least one is required.
- Alternatives enclosed within curly braces ({}) denote that you can use one or none of them
- The vertical bar separates different suffixes for operators or operands. For example, the following indicates that an 8-, 16-, or 32-bit immediate value is permitted in an instruction:

```
imm[8|16|32]
```

- The assembler's operators are built from the Intel operators by adding suffixes to them. The 80387, 80486 deals with three data types: integer, packed decimal, and real.

The assembler is not typed; the operator has to carry with it the type of data item it is operating on. If the operation is on an integer, the following suffixes apply: none for Intel's short (16 bits), l for Intel's long (32 bits), and ll for Intel's longlong (64 bits). If the operator applies to reals, then: s is short (32 bits), l is long (64 bits), and t is temporary real(80 bits).

- `reg [8 | 16 | 32]` defines a general-purpose register, where each number indicates one of the following:

```
32: %eax, %ecx, %edx, %ebx, %esi, %edi, %ebp, %esp
16: %ax, %cx, %dx, %bx, %si, %di, %bp, %sp
8: %al, %ah, %cl, %ch, %dl, %dh, %bl, %bh
```

- `imm [8 | 16 | 32 | 48]` — an immediate value. You define immediate values using the regular expression syntax previously described (see also Expressions and Immediate Values on page 210). If there is a choice between operand sizes, the assembler will choose the smallest representation.
- `mem [8 | 16 | 32 | 48 | 64 | 80]` — a memory operand; the 8, 16, 32, 48, 64, and 80 suffixes represent byte, word, long (or float), inter-segment, double, and long double memory address quantities, respectively.
- `creg` — a control register; the control registers are: `%cr0`, `%cr2`, `%cr3`, or `%cr4`.
- `r/m [8 | 16 | 32]` is a general-purpose register or memory operand; the operand type is determined from the suffix. They are: 8 = byte, 16 = word, and 32 = long. The registers for each operand size are the same as `reg [8 | 16 | 32]` above.
- `dreg` is a debug register; the debug registers are: `%db0`, `%db1`, `%db2`, `%db3`, `%db6`, `%db7`.
- `sreg` is a segment register. The 16-bit segment registers are: `%cs`, `%ds`, `%ss`, `%es`, `%fs`, and `%gs`.
- `treg` is a test register. The test registers are: `%tr6` and `%tr7`.
- `freg*` is floating-point registers `%st (%st(0))`, `%st(1) - %st(7)`.
- An instruction can act on zero or more operands. An operand can be any of the following:
 - an immediate operand (in the instruction itself)
 - a register (32-bit general, segment, or status/instruction register), (16-bit word register), and (8-bit byte register).
 - a pointer to a memory location.
 - an I/O port
- Instruction syntax is:
operand1 → operand2

where operand1 and operand2 are operated on and the result stored in operand2. The → arrow shows the direction. The direction is opposite of that described in the *IA 486 Microprocessor Family Programmer's Reference Manual*.

- `disp [8 | 32]` — the number of bits used to define the distance of a relative jump; because the assembler only supports a 32-bit address space, only 8-bit sign extended and 32-bit addresses are supported.
- `immPtr` — an immediate pointer; when the immediate form of a long call or a long jump is used, the selector and offset are encoded as an immediate pointer. An immediate pointer consists of `$imm16`, `$imm32` where the first immediate value represents the segment and the second represents the offset.
- `cc` — condition codes; the 30 condition codes are:

TABLE 2-1 Condition Codes

a	above
ae	above or equal
b	below
be	below or equal
c	carry
e	equal
g	greater
ge	greater than or equal to
l	less than
le	less than or equal to
na	not above
nae	not above or equal to
nb	not below
nbe	not below or equal to
nc	not carry
ne	not equal
ng	not greater than
nge	not greater than or equal to
nl	not less than
nle	not less than or equal to
no	not overflow

TABLE 2-1 Condition Codes *(Continued)*

np	not parity
ns	not sign
nz	not zero
o	overflow
p	parity
pe	parity even
po	parity odd
s	sign
z	zero

References

This document presumes that you are familiar with the manner in which the Intel instruction sets function. For more information on specific instruction descriptions, please refer to the *Intel 486 Microprocessor Family Programmer's Reference Manual* from Intel Corporation.

Segment Register Instructions

The following are the segment register instructions supported by the IA-32 processor.

Load Full Pointer (lds, les, lfs, lgs, and lss)

```
lds{w1}    mem[32|48], reg[16|32]
les{w1}    mem[32|48], reg[16|32]
lfs{w1}    mem[32|48], reg[16|32]
lgs{w1}    mem[32|48], reg[16|32]
lss{w1}    mem[32|48], reg[16|32]
```

Operation

mem[32|48] → reg[16|32]

Description

Reads a full pointer from memory and stores it in the specified segment register (DS, ES, FS, GS or SS) with a 16- or 32-bit offset value.

Example

Load a 16-bit pointer from memory location 0x44444444 into the DX register:

```
ldsw 0x44444444, %dx
```

Load a 32-bit pointer from memory location 0x33333333 into the EDX register:

```
lds1 0x33333333, %edx
```

Pop Stack into Word (pop)

```
pop{w|l}          r/m[16|32]  
pop{1}           [%ds|%ss|%es|%fs|%gs]
```

Operation

stack → r/m[16|32]

stack → segment register

Description

Replaces the previous contents of the register or memory operand with a word or long from the top of the stack.

Replaces the previous contents of the segment register operand with a long.

For a word, SP + 2; for a long, SP + 4.

Example

Replace the contents of the memory location pointed to by the EDI register, plus an offset of 4, with the word from the top of the stack:

```
popw 4(edi)
```

Replace the contents of the memory location pointed to by the EAX register with the long from the top of the stack:

```
popl %eax
```

Push Word/Long onto Stack (push)

```
push{wl}      r/m[16|32]
push{wl}      imm[8|16|32]
push{l}       [%cs|%ds|%ss|%es|%fs|%gs]
```

Operation

$r/m[16|32] \rightarrow \text{stack segment register} \rightarrow \text{stack}$

Description

For a word, $SP - 2$; for a long, $SP - 4$. Replaces the new top of stack, pointed to by SP , with the register, memory, immediate, or segment register operand.

Example

Replaces the new top of stack with the 16-bit immediate value, -126:

```
pushw $-126
```

Replaces the new top of stack with the 32-bit immediate value, 23456789:

```
pushl $23456789
```

Replaces the new top of stack with the content of the AX register:

```
pushw %ax
```

Replaces the new top of stack with the content of the EBX register:

```
pushl %ebx
```

I/O Instructions

Input from Port (in, ins)

```
in{bwl}      imm8
in{bwl}      (%dx)
ins{bwl}
```

Operation

imm[8|16|32] → [AL|AX|EAX]

DX → [AL|AX|EAX] DX → ES:(E)DI

Description

`in` transfers a byte, word, or long from the immediate port into the byte, word, or long memory address pointed to by the AL, AX, or EAX register, respectively.

The second form of the `in` instruction transfers a byte, word, or long from a port (0 to 65535), specified in the DX register, into the byte, word, or long memory address pointed to by the AL, AX, or EAX register, respectively.

When an 8-bit port is specified, the upper-eight bits of the port address will be 0.

The `ins` instruction transfers a string from a port specified in the DX register to the memory byte or word pointed to by the ES:destination index. Load the desired port number into the DX register and the desired destination address into the DI or EDI index register before executing the `ins` instruction. After a transfer occurs, the destination-index register is automatically incremented or decremented as determined by the value of the direction flag (DF). The index register is incremented if DF = 0 (DF cleared by a `cld` instruction); it is decremented if DF = 1 (DF set by a `std` instruction). The increment or decrement count is 1 for a byte transfer, 2 for a word, and 4 for a long. Use the `rep` prefix with the `ins` instruction for a block transfer of CX bytes or words.

Example

Transfer an immediate 8-bit port address into the AL register:

```
inb $0xff
```

Transfer a 16-bit port address, specified in the DX register, into the AX register:

```
inw (%dx)
```

Transfer a string from the port address, specified in the DX register, into the ES:destination index register:

```
insl
```

Output from Port (out, outs)

```
out{bwl}      imm8  
out{bwl}      (%dx)  
outs{bwl}
```

Operation

[AL|AX|EAX] → imm[8|16|32]

[AL|AX|EAX] → DX

ES:(E)DI → DX

Description

Transfers a byte, word, or long from the memory address pointed to by the content of the AL, AX, or EAX register to the immediate 8-, 16-, or 32-bit port address.

The second form of the `out` instruction transfers a byte, word, or long from the AL, AX, or EAX registers respectively to a port (0 to 65535), specified by the DX register.

The `outs` instruction transfers a string from the memory byte or word pointed to by the ES:source index to the port addressed in the DX register. Load the desired port number into the DX register and the desired source address into the SI or ESI index register before executing the `outs` instruction. After a transfer occurs, the destination-index register is automatically incremented or decremented as determined by the value of the direction flag (DF). The index register is incremented if DF = 0 (DF cleared by a `cld` instruction); it is decremented if DF = 1 (DF set by a `std` instruction). The increment or decrement count is 1 for a byte transfer, 2 for a word, and 4 for a long. Use the `rep` prefix with the `outs` instruction for a block transfer of CX bytes or words.

Example

Transfer a word from the AX register into the 16-bit port address, 0xff:

```
outw $0xff
```

Transfer a long from the EAX register into the 32-bit port address specified by the DX register:

```
outl (%dx)
```

Transfer a string from the memory byte or word pointed to by the ES:source index to the port addressed in the DX register:

```
outs1
```

Flag Instructions

Load Flags into AH Register (lahf)

```
lahf
```

Operation

SF:ZF:xx:AF:xx:PF:xx:CF → AH

Description

Transfers the low byte of the flags word to the AH register. The bits (lsb to msb) are: sign, zero, indeterminate, auxiliary carry, indeterminate, parity, indeterminate, and carry.

Example

Transfer the flags word into the AH register:

```
lahf
```

Store AH into Flags (sahf)

sahf

Operation

AH → SF:ZF:xx:AF:xx:PF:xx:CF

Description

Loads flags (sign, zero, indeterminate, auxiliary carry, indeterminate, parity, indeterminate, and carry) with values from the AH register.

Example

Load values from the AH register into the flags word:

sahf

Pop Stack into Flag (popf)

popf{wl}

Operation

stack → flags register

Description

Pops the word or long from the top of the stack and stores the value in the flags register. Stores a word in FLAGS; stores a long in EFLAGS.

Example

Pops the word from the top of the stack and stores it in the flags register:

popfw

Pops the long from the top of the stack and stores it in the eflags register:

popfl

Push Flag Register Onto Stack (pushf)

`pushf {wl}`

Operation

flags register → stack

Description

For a word, SP - 2 and copies FLAGS to the new top of stack pointed to by SP. For a long, SP - 4 and copies EFLAGS to the new top of stack pointed to by SS:eSP.

Example

Pushes the flags register onto the top of the stack:

`pushfw`

Pushes the eflags register onto the top of the stack:

`pushfl`

Complement Carry Flag (cmc)

`cmc`

Operation

not CF → CF

Description

Reverses the setting of the carry flag; affects no other flags.

Example

Reverse the setting of the carry flag:

`cmc`

Clear Carry Flag (clc)

`clc`

Operation

$0 \rightarrow \text{CF}$

Description

Sets the carry flag to zero; affects no other flags.

Example

Clear the carry flag:

`clc`

Set Carry Flag (stc)

`stc`

Operation

$1 \rightarrow \text{CF}$

Description

Sets the carry flag to 1.

Example

Set the carry flag:

`stc`

Clear Interrupt Flag (cli)

`cli`

Operation

0 → IF

Description

Clears the interrupt flag if the current privilege level is at least as privileged as IOPL; affects no other flags. External interrupts disabled at the end of the `cli` instruction or from that point on until the interrupt flag is set.

Example

Clear the interrupt flag:

```
cli
```

Set Interrupt Flag (`sti`)

```
sti
```

Operation

1 → IF

Description

Sets the interrupt flag to 1.

Example

Set the interrupt flag:

```
sti
```

Clear Direction Flag (`cld`)

```
cld
```

Operation

0 → DF

Description

Clears the direction flag; affects no other flags or registers. Causes all subsequent string operations to increment the index registers, (E)SI and/or (E)DI, used during the operation.

Example

Clear the direction flag:

```
cld
```

Set Direction Flag (std)

```
std
```

Operation

1 → DF

Description

Sets the direction flag to 1, causing all subsequent string operations to decrement the index registers, (E)SI and/or (E)DI, used during the operation.

Example

Set the direction flag:

```
std
```

Arithmetic Logical Instructions

Integer Addition (add)

```
add{bwl}    reg[8|16|32], r/m[8|16|32]
add{bwl}    r/m[8|16|32], reg[8|16|32]
add{bwl}    imm[8|16|32], r/m[8|16|32]
```

Operation

$\text{reg}[8|16|32] + \text{r/m}[8|16|32] \rightarrow \text{r/m}[8|16|32]$

$\text{r/m}[8|16|32] + \text{reg}[8|16|32] \rightarrow \text{reg}[8|16|32]$

$\text{imm}[8|16|32] + \text{r/m}[8|16|32] \rightarrow \text{r/m}[8|16|32]$

Description

Integer adds operand1 to operand2 and stores the result in operand2.

When an immediate byte is added to a word or long, the immediate value is sign-extended to the size of the word or long operand.

If you wish to decimal adjust (daa) or ASCII adjust (aaa) the add result, use the form of add that stores the result in AL.

Example

Integer adds the 8-bit constant, -126, to the content of the AL register:

```
addb $-126,%al
```

Integer adds the word contained in the effective address (addressed by the EDI register plus an offset of 4) to the content of the DX register:

```
addw 4(%edi),%dx
```

Integer adds the content of the EDX register to the effective address (addressed by the EDI register plus an offset of 4):

```
addl %edx, 4(%edi)
```

Integer Add With Carry (adc)

```
adc{bwl}    reg[8|16|32], r/m[8|16|32]
adc{bwl}    r/m[8|16|32], reg[8|16|32]
adc{bwl}    imm[8|16|32], r/m[8|16|32]
```

Operation

$(\text{reg}[8|16|32] + \text{CF}) + \text{r/m}[8|16|32] \rightarrow \text{r/m}[8|16|32]$

$(\text{r/m}[8|16|32] + \text{CF}) + \text{reg}[8|16|32] \rightarrow \text{reg}[8|16|32]$

$(\text{imm}[8|16|32] + \text{CF}) + \text{r/m}[8|16|32] \rightarrow \text{r/m}[8|16|32]$

Description

Integer adds operand1 and the carry flag to operand2 and stores the result in operand2. `adc` is typically executed as part of a multi-byte or multi-word add operation. When an immediate byte is added to a word or long, the immediate value is sign-extended to the size of the word or long operand.

Example

Integer add the 8-bit content of the effective memory address (ESI register plus an offset of 1) and the carry flag to the content of the address in the CL register:

```
adcb 1(%esi), %cl
```

Integer add the 16-bit content of the effective memory address (EDI register plus an offset of 4) and the carry flag to the content of the address in the DX register:

```
adcw 4(%edi), %dx
```

Integer add the 32-bit content of the address in the EDX register and the carry flag to the effective memory address (EDI register plus an offset of 4):

```
adcl %edx, 4(%edi)
```

Integer Subtraction (sub)

```
sub{bwl}    reg[8|16|32], r/m[8|16|32]
sub{bwl}    r/m[8|16|32], reg[8|16|32]
sub{bwl}    imm[8|16|32], r/m[8|16|32]
```

Operation

$r/m[8|16|32] - \text{reg}[8|16|32] \rightarrow r/m[8|16|32]$

$\text{reg}[8|16|32] - r/m[8|16|32] \rightarrow \text{reg}[8|16|32]$

$r/m[8|16|32] - \text{imm}[8|16|32] \rightarrow r/m[8|16|32]$

Description

Subtracts operand1 from operand2 and stores the result in operand2. When an immediate byte value is subtracted from a word, the immediate value is sign-extended to the size of the word operand before the subtract operation is executed.

If you wish to decimal adjust (`das`) or ASCII adjust (`aas`) the `sub` result, use the form of `sub` that stores the result in AL.

Example

Integer subtract the 8-bit constant, -126, from the content of the effective address (addressed by the ESI register plus an offset of 1):

```
subb $-126, 1(%esi)
```

Integer subtract the 16-bit constant, 1234, from the content of the effective address (addressed by the EDI register plus an offset of 4):

```
subw $1234, 4(%edi)
```

Integer subtract the 32-bit content of the EDX register from the effective address (addressed by the EDI register plus an offset of 4):

```
subl %edx, 4(%edi)
```

Integer Subtraction With Borrow (`sbb`)

```
sbb{bwl}    reg[8|16|32], r/m[8|16|32]
sbb{bwl}    r/m[8|16|32], reg[8|16|32]
sbb{bwl}    imm[8|16|32], r/m[8|16|32]
```

Operation

$r/m[8|16|32] - (\text{reg}[8|16|32] + \text{CF}) \rightarrow r/m[8|16|32]$

$\text{reg}[8|16|32] - (r/m[8|16|32] + \text{CF}) \rightarrow \text{reg}[8|16|32]$

$r/m[8|16|32] - (imm[8|16|32] + CF) \rightarrow r/m[8|16|32]$

Description

Subtracts (operand1 and the carry flag) from operand2 and stores the result in operand2. When an immediate byte value is subtracted from a word, the immediate value is sign-extended to the size of the word operand before the subtract operation is executed.

Example

Integer subtract the 8-bit content of the CL register plus the carry flag from the effective address (addressed by the ESI register plus an offset of 1):

```
sbbb %cl, 1(%esi)
```

Integer subtract the 16-bit constant, -126, plus the carry flag from the AL register:

```
sbbw $-126, %al
```

Integer subtract the 32-bit constant, 12345678, plus the carry flag from the effective address (addressed by the EDI register plus an offset of 4):

```
sbb1 $12345678, 4(%edi)
```

Compare Two Operands (cmp)

```
cmp{bwl}          reg[8|16|32], r/m[8|16|32]  
cmp{bwl}          r/m[8|16|32], reg[8|16|32]  
cmp{bwl}          imm[8|16|32], r/m[8|16|32]
```

Operation

$r/m[8|16|32] - reg[8|16|32]$

$reg[8|16|32] - r/m[8|16|32]$

$r/m[8|16|32] - imm[8|16|32]$

Description

Subtracts operand1 from operand2, but does not store the result; only changes the flags. `cmp` is typically executed in conjunction with conditional jumps and the `setcc`

instruction. If an operand greater than one byte is compared to an immediate byte, the immediate byte value is first sign-extended.

Example

Compare the 8-bit constant, 0xff, with the content of the AL register:

```
cmpb $0xff, %al
```

Compare the 16-bit content of the DX register with the effective address (addressed by the EDI register plus an offset of 4):

```
cmpw %dx, 4(%edi)
```

Compare the 32-bit content of the effective address (addressed by the EDI register plus an offset of 4) to the EDX register:

```
cmpl 4(%edi), %edx
```

Increment by 1 (inc)

```
inc{bwl}          r/m[8|16|32]
```

Operation

$r/m[8|16|32] + 1 \rightarrow r/m[8|16|32]$

Description

Adds 1 to the operand and does not change the carry flag. Use the add instruction with an immediate value of 1 to change the carry flag.

Example

Add 1 to the contents of the byte at the effective address (addressed by the ESI register plus an offset of 1):

```
incb 1(%esi)
```

Add 1 to the 16-bit contents of the AX register:

```
incw %ax
```

Add 1 to the 32-bit contents at the effective address (addressed by the EDI register):

```
incl 4(%edi)
```

Decrease by 1 (dec)

```
dec{bwl}          r/m[8|16|32]
```

Operation

$r/m[8|16|32] - 1 \rightarrow r/m[8|16|32]$

Description

Subtracts 1 from the operand. Does not change the carry flag. To change the carry flag, use the `sub` instruction with an immediate value of 1.

Example

Subtract 1 from the 8-bit contents of the effective address (addressed by the ESI register plus an offset of 1):

```
decb 1(%esi)
```

Subtract 1 from the 16-bit contents of the BX register:

```
decw %bx
```

Subtract 1 from the 32-bit contents of the effective address (addressed by the EDI register plus an offset of 4):

```
decl 4(%edi)
```

Logical Comparison or Test (test)

```
test{bwl}          reg[8|16|32], r/m[8|16|32]  
test{bwl}          r/m[8|16|32], reg[8|16|32]  
test{bwl}          imm[8|16|32], r/m[8|16|32]
```

Operation

$reg[8|16|32]$ and $r/m[8|16|32] \rightarrow r/m[8|16|32]$

$r/m[8|16|32]$ and $reg[8|16|32] \rightarrow reg[8|16|32]$

$\text{imm}[8|16|32]$ and $r/m[8|16|32] \rightarrow r/m[8|16|32]$

Description

Performs a bit-wise logical AND of the two operands. The result of a bit-wise logical AND is 1 if the value of that bit in both operands is 1; otherwise, the result is 0. `test` discards the results and modifies the flags. The OF and CF flags are cleared; SF, ZF and PF flags are set according to the result.

Example

Perform a logical AND of the constant, 0xff, and the 8-bit contents of the effective address (addressed by the ESI register plus an offset of 1):

```
testb $0xff, 1(%esi)
```

Perform a logical AND of the 16-bit contents of the DX register and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
testw %dx, 4(%edi)
```

Perform a logical AND of the constant, 0xffeeddcc, and the 32-bit contents of the effective address (addressed by the EDI register plus an offset of 4):

```
testl $0xffeeddcc, 4(%edi)
```

Shift (`sal`, `shl`, `sar`, `shr`)

`shl{bwl} %cl, r/m[8|16|32]` `sar{bwl} imm8, r/m[8|16|32]` `sar{bwl} %cl, r/m[8|16|32]`
`shr{bwl} imm8, r/m[8|16|32]`

```
sal{bwl}      %cl, r/m[8|16|32]
shl{bwl}      imm8, r/m[8|16|32]
sal{bwl}      imm8, r/m[8|16|32]
shr{bwl}      %cl, r/m[8|16|32]
```

Operation

shift-left $r/m[8|16|32]$ by `imm8` $\rightarrow r/m[8|16|32]$

shift-left $r/m[8|16|32]$ by `%cl` $\rightarrow r/m[8|16|32]$

shift-right $r/m[8|16|32]$ by `imm8` $\rightarrow r/m[8|16|32]$

shift-right $r/m[8|16|32]$ by `%cl` $\rightarrow r/m[8|16|32]$

Description

`sal` (or its synonym `shl`) left shifts (multiplies) a byte, word, or long value for a count specified by an immediate value and stores the product in that byte, word, or long respectively. The second variation left shifts by a count value specified in the CL register. The high-order bit is shifted into the carry flag; the low-order bit is set to 0.

`sar` right shifts (signed divides) a byte, word, or long value for a count specified by an immediate value and stores the quotient in that byte, word, or long respectively. The second variation right shifts by a count value specified in the CL register. `sar` rounds toward negative infinity; the high-order bit remains unchanged.

`shr` right shifts (unsigned divides) a byte, word, or long value for a count specified by an immediate value and stores the quotient in that byte, word, or long respectively. The second variation divides by a count value specified in the CL register. `shr` sets the high-order bit to 0.

Example

Right shift, count specified by the constant (253), the 8-bit contents of the effective address (addressed by the ESI register plus an offset of 1):

```
sarb $253, 1(%esi)
```

Right shift, count specified by the contents of the CL register, the 16-bit contents of the effective address (addressed by the EDI register plus an offset of 4):

```
shrw %cl, 4(%edi)
```

Left shift, count specified by the constant (253), the 32-bit contents of the effective address (addressed by the EDI register plus an offset of 4):

```
shll $253, 4(%edi)
```

Double Precision Shift Left (`shld`)

```
shld{wl}      imm8, reg[16|32], r/m[16|32]
```

```
shld{wl}      %cl, reg[16|32], r/m[16|32]
```

Operation

by `imm8` shift-left `r/m[16|32]` bits `reg[16|32]` → `r/m[16|32]`

by `reg[16|32]` shift-left `r/m[16|32]` bits `r/m[16|32]` → `r/m[16|32]`

Description

`shld` double-precision left shifts a 16- or 32-bit register value into a word or long for the count specified by an immediate value, MODULO 32 (0 to 31). The result is stored in that particular word or long.

The second variation of `shld` double-precision left shifts a 16- or 32-bit register or memory value into a word or long for the count specified by register CL MODULO 32 (0 to 31). The result is stored in that particular word or long.

`shld` sets the SF, ZF, and PF flags according to the value of the result; CS is set to the value of the last bit shifted out; OF and AF are undefined.

Example

Use the count specified by the constant, 253, to double-precision left shift a 16-bit register value from the DX register to the effective address (addressed by the EDI register plus an offset of 4):

```
shldw $253, %dx, 4(%edi)
```

Use the count specified (%CL MOD 32) by the 32-bit EDX register to double-precision left shift a 32-bit memory value at the effective address (addressed by the EDI register plus an offset of 4):

```
shldl %cl,%edx, 4(%edi)
```

Double Precision Shift Right (`shrd`)

```
shrd{wl}          imm8, reg[16|32], r/m[16|32]  
shrd{wl}          %cl, reg[16|32], r/m[16|32]
```

Operation

by `imm8` shift-right `r/m[16|32]` bits `reg[16|32]` → `r/m[16|32]`

by `reg[16|32]` shift-right `r/m[16|32]` bits `r/m[16|32]` → `r/m[16|32]`

Description

`shrd` double-precision right shifts a 16- or 32-bit register value into a word or long for the count specified by an immediate value MODULO 32 (0 to 31). The result is stored in that particular word or long.

The second variation of `shrd` double-precision right shifts a 16- or 32-bit register or memory value into a word or long for the count specified by register CL MODULO 32 (0 to 31). The result is stored in that particular word or long.

`shrd` sets the SF, ZF, and PF flags according to the value of the result; CS is set to the value of the last bit shifted out; OF and AF are undefined.

Example

Use the count specified by the constant, 253, to double-precision right shift a 16-bit register value from the DX register to the effective address (addressed by the EDI register plus an offset of 4):

```
shrdw $253, %dx, 4(%edi)
```

Use the count specified (%CL MOD 32) by the 32-bit EDX register to double-precision right shift a 32-bit memory value at the effective address (addressed by the EDI register plus an offset of 4)

```
shrdl %cl,%edx, 4(%edi)
```

One's Complement Negation (`not`)

```
not{bwl}          r/m[8|16|32]
```

Operation

```
not r/m[8|16|32] → r/m[8|16|32]
```

Description

Inverts each bit value of the byte, word, or long; that is, every 1 becomes a 0 and every 0 becomes a 1.

Example

Invert each of the 8-bit values at the effective address (addressed by the ESI register plus an offset of 1):

```
notb 1(%esi)
```

Invert each of the 16-bit values at the effective address (addressed by the EDI register plus an offset of 4):

```
notw 4(%edi)
```

Invert each of the 32-bit values at the effective address (addressed by the EDI register plus an offset of 4):

```
notl 4(%edi)
```

Two's Complement Negation (`neg`)

```
neg{bwl}    r/m[8|16|32]
```

Operation

two's-complement $r/m[8|16|32] \rightarrow r/m[8|16|32]$

Description

Replace the value of the byte, word, or long with its two's complement; that is, `neg` subtracts the byte, word, or long value from 0, and puts the result in the byte, word, or long respectively.

`neg` sets the carry flag to 1, unless initial value of the byte, word, or long is 0. In this case `neg` clears the carry flag to 0.

Example

Replace the 8-bit contents of the effective address (addressed by the ESI register plus an offset of 1) with its two's complement:

```
negb 1(%esi)
```

Replace the 16-bit contents of the effective address (addressed by the EDI register plus an offset of 4) with its two's complement:

```
negw 4(%edi)
```

Replace the 32-bit contents of the effective address (addressed by the EDI register plus an offset of 4) with its two's complement:

```
negl 4(%edi)
```

Check Array Index Against Bounds (bound)

`bound{wl} reg[16|32], r/m[16|32]`

Operation

`r/m[16|32] bound reg[16|32] → CC is unchanged`

Description

Ensures that a signed array index (16- or 32-bit register) value falls within the upper and lower bounds of a block of memory. The upper and lower bounds are specified by a 16- or 32-bit register or memory value. If the signed array index value is not within the bounds, an Interrupt 5 occurs; the return EIP points to the `bound` instruction.

Example

Check the 16-bit signed array index value in the AX register against the doubleword with the upper and lower bounds specified by DX:

```
boundw %ax, %dx
```

Check the 32-bit signed array index value in the EAX register against the doubleword with the upper and lower bounds specified by EDX:

```
boundl %eax, %edx
```

Logical And (and)

```
and{bwl} reg[8|16|32], r/m[8|16|32]
and{bwl} r/m[8|16|32], reg[8|16|32]
and{bwl} imm[8|16|32], r/m[8|16|32]
```

Operation

`reg[8|16|32] and r/m[8|16|32] → r/m[8|16|32]`

`r/m[8|16|32] and reg[8|16|32] → reg[8|16|32]`

`imm[8|16|32] and r/m[8|16|32] → r/m[8|16|32]`

Description

Performs a logical AND of each bit in the values specified by the two operands and stores the result in the second operand.

TABLE 2-2 Logical AND

Values	Result
0 LAND 0	0
0 LAND 1	0
1 LAND 0	0
1 LAND 1	1

Example

Perform an 8-bit logical AND of the CL register and the contents of the effective address (addressed by the ESI register plus an offset of 1):

```
andb %cl, 1(%esi)
```

Perform a 16-bit logical AND of the constant, 0xffee, and the contents of the effective address (addressed by the AX register):

```
andw $0xffee, %ax
```

Perform a 32-bit logical AND of the contents of the effective address (addressed by the EDI register plus an offset of 4) and the EDX register:

```
andl 4(%edi), %edx
```

Logical Inclusive OR (or)

```
or{bwl}      reg[8|16|32], r/m[8|16|32]
or{bwl}      r/m[8|16|32], reg[8|16|32]
or{bwl}      imm[8|16|32], r/m[8|16|32]
```

Operation

reg[8|16|32] LOR r/m[8|16|32] → r/m[8|16|32]

r/m[8|16|32] LOR reg[8|16|32] → reg[8|16|32]

imm[8|16|32] LOR r/m[8|16|32] → r/m[8|16|32]

Description

Performs a logical OR of each bit in the values specified by the two operands and stores the result in the second operand.

TABLE 2-3 Inclusive OR

Values	Result
0 LOR 0	0
0 LOR 1	1
1 LOR 0	1
1 LOR 1	1

Example

Perform an 8-bit logical OR of the constant, 0xff, and the AL register:

```
orb $0xff, %al
```

Perform a 16-bit logical OR of the constant, 0xff83, and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
orw $0xff83, 4(%edi)
```

Perform a 32-bit logical OR of the EDX register and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
orl %edx, 4(%edi)
```

Logical Exclusive OR (xor)

```
xor{bwl}    reg[8|16|32], r/m[8|16|32]  
xor{bwl}    r/m[8|16|32], reg[8|16|32]  
xor{bwl}    imm[8|16|32], r/m[8|16|32]
```

Operation

reg[8|16|32] XOR r/m[8|16|32] → r/m[8|16|32]

r/m[8|16|32] XOR reg[8|16|32] → reg[8|16|32]

imm[8|16|32] XOR r/m[8|16|32] → r/m[8|16|32]

Description

Performs an exclusive OR of each bit in the values specified by the two operands and stores the result in the second operand.

TABLE 2-4 Exclusive XOR

Values	Result
0 XOR 0	0
0 XOR 1	1
1 XOR 0	1
1 XOR 1	0

Example

Perform a 8-bit exclusive OR of the constant, 0xff, and the AL register:

```
xorb $0xff, %al
```

Perform a 16-bit exclusive OR of the constant, 0xff83, and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
xorw $0xff83, 4(%edi)
```

Perform a 32-bit exclusive OR of the EDX register and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
xorl %edx, 4(%edi)
```

Multiply and Divide Instructions

When the type suffix is not included in a multiply or divide instruction, it defaults to a long.

Signed Multiply (imul)

```
imulb      r/m8
imulw      r/m16
imul{1}    r/m32
imul{wl}   r/m[16|32], reg[16|32]
```

`imul{bwl} imm[16|32], r/m[16|32], reg[16|32]`

Operation

`r/m8 × AL → AX` `r/m16 × AX → DX:AX`

`r/m32 × EAX → EDX:EAX` `r/m[16|32] × reg[16|32] → reg[16|32]`

`imm[16|32] × r/m[16|32] → reg[16|32]`

Description

The single-operand form of `imul` executes a signed multiply of a byte, word, or long by the contents of the AL, AX, or EAX register and stores the product in the AX, DX:AX or EDX:EAX register respectively.

The two-operand form of `imul` executes a signed multiply of a register or memory word or long by a register word or long and stores the product in that register word or long.

The three-operand form of `imul` executes a signed multiply of a 16- or 32-bit immediate by a register or memory word or long and stores the product in a specified register word or long.

`imul` clears the overflow and carry flags under the following conditions:

TABLE 2-5 Clearing OF and CF Flags — `imul`

Instruction Form	Condition for Clearing OF and CF
<code>r/m8 × AL → AX</code>	AL = sign-extend of AL to 16 bits
<code>r/m16 × AX → DX:AX</code>	AX = sign-extend of AX to 32 bits
<code>r/m32 × EAX → EDX:EAX</code>	EDX:EAX = sign-extend of EAX to 32 bits
<code>r/m[16 32] × reg[16 32] → reg[16 32]</code>	Product fits exactly within reg[16 32]
<code>imm[16 32] × r/m[16 32] → reg[16 32]</code>	Product fits exactly within reg[16 32]

Example

Perform an 8-bit signed multiply of the AL register and the contents of the effective address (addressed by the ESI register plus an offset of 1):

```
imulb 1(%esi)
```

Perform a 16-bit signed multiply of the constant, -126, and the contents of the effective address (addressed by the EDI register plus an offset of 4). Store the result in the DX register:

```
imulw $-126, 4(%edi), %dx
```

Perform a 32-bit signed multiply of the constant, 12345678, and the contents of the effective address (addressed by the EDI register plus an offset of 4). Store the result in the EDX register:

```
imull $12345678, 4(%edi), %edx
```

Unsigned Multiplication of AL, AX or EAX(mul)

```
mul{bwl}    r/m[8|16|32]
```

Operation

$r/m8 \times AL \rightarrow AX$

$r/m16 \times AX \rightarrow DX:AX$

$r/m32 \times EAX \rightarrow EDX:EAX$

Description

`mul` executes a unsigned multiply of a byte, word, or long by the contents of the AL, AX, or EAX register and stores the product in the AX, DX:AX or EDX:EAX register respectively.

`mul` clears the overflow and carry flags under the following conditions:

TABLE 2-6 Clearing OF and CF Flags — `mul`

Instruction Form	Condition for Clearing OF and CF
$r/m8 \times AL \rightarrow AX$	clear to 0 if AH is 0; otherwise, set to 1
$r/m16 \times AX \rightarrow DX:AX$	clear to 0 if DX is 0; otherwise, set to 1
$r/m32 \times EAX \rightarrow EDX:EAX$	clear to 0 if EDX is 0; otherwise, set to 1

Example

Perform an 8-bit unsigned multiply of the AL register and the contents of the effective address (addressed by the ESI register plus an offset of 1):

```
mulb 1(%esi)
```

Perform a 16-bit unsigned multiply of the AL register and the contents of the effective address (addressed by the EDI register plus an offset of 4):

```
mulw 4(%edi)
```

Perform a 32-bit unsigned multiply of the AL register and the contents of the effective address (addressed by the EDI register plus an offset of 1):

```
mull 1(%edi)
```

Unsigned Divide (div)

```
div{bwl}          r/m[8|16|32]
```

Operation

AX r/m8 → AL DX:AX

r/m16 → AX EDX:EAX

r/m32 → EAX

Description

`div` executes unsigned division. `div` divides a 16-, 32-, or 64-bit register value (dividend) by a register or memory byte, word, or long (divisor). The quotient is stored in the AL, AX, or EAX register respectively.

The remainder is stored in AH, Dx, or EDX. The size of the divisor (8-, 16- or 32-bit operand) determines the particular register used as the dividend.

The OF, SF, ZF, AR, PF and CF flags are undefined.

Example

Perform an 8-bit unsigned divide of the AX register by the contents of the effective address (addressed by the ESI register plus an offset of 1) and store the quotient in the AL register, and the remainder in AH:

```
divb 1(%esi)
```

Perform a 16-bit unsigned divide of the DX:AX register by the contents of the effective address (addressed by the EDI register plus an offset of 4) and store the quotient in the AX register, and the remainder in DX:

```
divw 4(%edi)
```

Perform a 32-bit unsigned divide of the EDX:EAX register by the contents of the effective address (addressed by the EDI register plus an offset of 4) and store the quotient in the EAX register, and the remainder in EDX:

```
divl 4(%edi)
```

Signed Divide (*idiv*)

```
idiv{bwl}      r/m[8|16|32]
```

Operation

AX r/m8 → AL

DX:AX r/m16 → AX

EDX:EAX r/m32 → EAX

Description

idiv executes signed division. *idiv* divides a 16-, 32-, or 64-bit register value (dividend) by a register or memory byte, word, or long (divisor). The size of the divisor (8-, 16- or 32-bit operand) determines the particular register used as the dividend, quotient, and remainder.

TABLE 2-7 *idiv* Register Assignment

Divisor Operand Size	Dividend	Quotient	Remainder
byte	AX	AL	AH
word	DX:AX	AX	DX
long	EDX:EAX	EAX	EDX

If the resulting quotient is too large to fit in the destination, or if the divisor is 0, an Interrupt 0 is generated. Non-integral quotients are truncated toward 0. The remainder has the same sign as the dividend; the absolute value of the remainder is always less than the absolute value of the divisor.

Example

Perform a 16-bit signed divide of the DX:AX register by the contents of the effective address (addressed by the EDI register plus an offset of 4) and store the quotient in the AX register

```
divw 4(%edi)
```

Conversion Instructions

Convert Byte to Word (cbtw)

```
cbtw
```

Operation

sign-extend AL → AX

Description

cbtw converts the signed byte in AL to a signed word in AX by extending the most-significant bit (sign bit) of AL into all bits of AH.

Example

```
cbtw
```

Convert Word to Long (cwtl)

```
cwtl
```

Operation

sign-extend AX → EAX

Description

`cwtl` converts the signed word in `AX` to a signed long in `EAX` by extending the most-significant bit (sign bit) of `AX` into two most-significant bytes of `EAX`.

Example

```
cwtl
```

Convert Signed Word to Signed Double Word (`cwtd`)

```
cwtd
```

Operation

sign-extend `AX` → `DX:AX`

Description

`cwtd` converts the signed word in `AX` to a signed double word in `DX:AX` by extending the most-significant bit (sign bit) of `AX` into all bits of `DX`.

Example

```
cwtd
```

Convert Signed Long to Signed Double Long (`cltd`)

```
cltd
```

Operation

sign-extend `EAX` → `EDX:EAX`

Description

`cld` converts the signed long in EAX to a signed double long in EDX:EAX by extending the most-significant bit (sign bit) of EAX into all bits of EDX.

Example

```
cld
```

Decimal Arithmetic Instructions

Decimal Adjust AL after Addition (`daa`)

```
daa
```

Operation

decimal-adjust AL → AL

Description

Use `daa` only after executing the form of an `add` instruction that stores a two-BCD-digit byte result in the AL register. `daa` then adjusts AL to a two-digit packed decimal result.

Example

Decimal adjust the two-BCD-digit in the AL register:

```
daa
```

Decimal Adjust AL after Subtraction (`das`)

```
das
```

Operation

decimal-adjust AL → AL

Description

Use `das` only after executing the form of a `sub` instruction that stores a two-BCD-digit byte result in the AL register. `das` then adjusts AL to a two-digit packed decimal result.

Example

Decimal adjust the two-BCD-digit in the AL register:

```
das
```

ASCII Adjust after Addition (`aaa`)

```
aaa
```

Operation

ASCII-adjust AL → AL

Description

You use `aaa` only after executing the form of an `add` instruction that stores a two-BCD-digit byte result in the AL register. `aaa` then adjusts AL to contain the correct decimal result. The top nibble of AL is set to 0. To convert AL to an ASCII result, follow the `aaa` instruction with:

```
or %al, 0x30
```

Table 2–8 shows how `aaa` handles a carry.

TABLE 2–8 `aaa` Handling a Carry

Carry	Action
decimal carry	AH + 1; CF and AF set to 1
no decimal carry	AH unchanged; CF and AF cleared to 0

Example

Adjust the AL register to contain the correct decimal result after an add instruction that stores a two-BCD-digit byte.

```
aaa
```

ASCII Adjust after Subtraction (aas)

```
aas
```

Operation

ASCII-adjust AL → AL

Description

Use `aas` only after executing the form of an add instruction that stores a two-BCD-digit byte result in the AL register. `aas` then adjusts AL to contain the correct decimal result. The top nibble of AL is set to 0. To convert AL to an ASCII result, follow the `aas` instruction with:

```
or %al, 0x30
```

Table 2–9 shows how `aas` handles a carry.

TABLE 2–9 How `aas` Handles a Carry

Carry	Action
decimal carry	AH - 1; CF and AF set to 1
no decimal carry	AH unchanged; CF and AF cleared to 0

Example

Adjust the AL register to contain the correct decimal result after a `sub` instruction that stores a two-BCD-digit byte

```
aas
```

ASCII Adjust AX after Multiply (aam)

```
aam
```

Operation

$AL \div 10 \rightarrow AH \text{ mod } 10 \quad AL \rightarrow AL$

Description

You use `aam` only after executing a `mul` instruction between two BCD digits (unpacked). `mul` stores the result in the AX register. The result is less than 100 so it can be contained in the AL register (the low byte of the AX register). `aam` unpacks the AL result by dividing AL by 10, stores the quotient (most-significant digit) in AH, and stores the remainder (least-significant digit) in AL.

Example

Adjust the AL register to contain the correct decimal result after a `mul` instruction between two BCD digits:

```
aam
```

ASCII Adjust AX before Division (`aad`)

```
aad
```

Operation

$AL + (AH \times 10) \rightarrow AL \quad 0 \rightarrow AH$

Description

`aad` prepares two unpacked BCD digits for a division operation that yields an unpacked result. The least-significant digit is in AL; the most-significant in AH.

`aad` prepares the AL and AH registers:

```
AL + (AH × 10) → AL  
0 → AH
```

AX is then equal to the binary equivalent of the original unpacked two-digit BCD number.

Example

Adjust the AL and AH registers for a division operation by setting the AX register equal to the original unpacked two-digit number:

```
aad
```

Coprocessor Instructions

`fwait`

Wait (wait, fwait)

`wait`

Description

`wait` — processor suspends instruction execution until the BUSY # pin is inactive (high).

`fwait` — processor checks for pending unmasked numeric exceptions before proceeding.

Example

Suspend instruction execution until not BUSY and check for exceptions:

```
wait
```

String Instructions

All string op mnemonics default to long.

Move Data from String to String (movs)

```
movs {bwl}
movs {bwl} m[8|16|32], reg[16|32]
```

Operation

move {bwl} [(E)SI] → ES: (E)DI

move {bwl} DS: [(E)SI] → ES: [(E)DI]

Description

Copies the byte, word, or long in [(E)SI] to the byte, word, or long in ES:[(E)DI]. Before executing the move instruction, load the index values into the SI source- and DI destination-index registers.

The destination operand must be addressable from the ES register; it cannot span segments. A source operand, however, can span segments; the default is DS.

After the data is moved, both the source- and destination-index registers are automatically incremented or decremented as determined by the value of the direction flag (DF). The index registers are incremented if DF = 0 (DF cleared by a `cld` instruction); they are decremented if DF = 1 (DF set by a `std` instruction). The increment/decrement count is 1 for a byte move, 2 for a word, and 4 for a long.

For a block move of CX bytes or words, precede a `movs` instruction with a `rep` prefix.

Example

Copy the 8-bit byte from the DS:[(E)SI] to the ES:[(E)DI] register.

```
movsb
```

Compare String Operands (cmps)

```
cmps {bwl}
```

Operation

compare DS:[(E)SI] with ES:[(E)DI]

Description

Compares the byte, word, or long in DS:[(E)SI] with the byte, word, or long in ES:[(E)DI]. Before executing the `cmps` instruction, load the index values into the SI source- and DI destination-index registers.

`cmps` subtracts the operand indexed by the destination-index from the operand indexed by the source-index register.

After the data is compared, both the source- and destination-index registers are automatically incremented or decremented as determined by the value of the direction flag (DF). The index registers are incremented if DF = 0 (DF cleared by a `cld` instruction); they are decremented if DF = 1 (DF set by a `std` instruction). The increment/decrement count is 1 for a byte move, 2 for a word, and 4 for a long.

For a block compare of CX or ECX bytes, words or longs, precede a `cmps` instruction with a `repz` or `repnz` prefix.

Example

Compare the 8-bit byte in the DS:[(E)SI] register to the ES:[(E)DI] register.

```
cmpsb
```

Compare the 16-bit word in the DS:[(E)SI] register to the ES:[(E)DI] register.

```
cmpsw
```

Compare the 32-bit word in the DS:[(E)SI] register to the ES:[(E)DI] register.

```
cmpsl
```

Store String Data (`stos`)

```
stos{bwl}
```

Operation

store [AL | AX | EAX] → ES:[(E)DI]

Description

Transfers the contents of the AL, AX, or EAX register to the memory byte or word addressed in the destination register relative to the ES segment. Before executing the move instruction, load the index values into the DI destination-index register.

The destination operand must be addressable from the ES register; it cannot span segments.

After the data is transferred, the destination-index register is automatically incremented or decremented as determined by the value of the direction flag (DF). The index registers are incremented if DF = 0 (DF cleared by a `cld` instruction); they are decremented if DF = 1 (DF set by a `std` instruction). The increment/decrement count is 1 for a byte move, 2 for a word, and 4 for a long.

For a block transfer of CX bytes, words or longs, precede a `stos` instruction with a `rep` prefix.

Example

Transfer the contents of the AL register to the memory byte addressed in the destination register, relative to the ES segment.

```
stosb
```

Transfer the contents of the AX register to the memory word addressed in the destination register, relative to the ES segment

```
stosw
```

Transfer the contents of the EAX register to the memory double-word addressed in the destination register, relative to the ES segment

```
stosl
```

The Load String Operand (`lods`)

```
lods{bwl}
```

Operation

load ES:[(E)DI] → [AL | AX | EAX]

Description

Loads the memory byte or word addressed in the destination register into the AL, AX, or EAX register. Before executing the `lods` instruction, load the index values into the SI source-index register.

After the data is loaded, the source-index register is automatically incremented or decremented as determined by the value of the direction flag (DF). The index register

is incremented if DF = 0 (DF cleared by a `cld` instruction); it is decremented if DF = 1 (DF set by a `std` instruction). The increment/decrement count is 1 for a byte move, 2 for a word, and 4 for a long.

For a block transfer of CX bytes, words or longs, precede a `lods` instruction with a `rep` prefix; however, `lods` is used more typically within a loop construct where further processing of the data moved into AL, AX, or EAX is usually required.

Example

Load the memory byte addressed in the destination register, relative to the ES segment register, into the AL register.

```
lodsb
```

Load the memory word addressed in the destination register, relative to the ES segment register, into the AX register.

```
lodsw
```

Load the memory double-word addressed in the destination register, relative to the ES segment register, into the EAX register.

```
lodsl
```

Compare String Data (`scas`)

```
scas{bwl}
```

Operation

compare ES:[(E)DI] with [AL | AX | EAX]

Description

Compares the memory byte or word addressed in the destination register relative to the ES segment with the contents of the AL, AX, or EAX register. The result is discarded; only the flags are set.

Before executing the `scas` instruction, load the index values into the DI destination-index register. The destination operand must be addressable from the ES register; it cannot span segments.

After the data is transferred, the destination-index register is automatically incremented or decremented as determined by the value of the direction flag (DF). The

index registers are incremented if DF = 0 (DF cleared by a `cld` instruction); they are decremented if DF = 1 (DF set by a `std` instruction). The increment/decrement count is 1 for a byte move, 2 for a word, and 4 for a long.

For a block search of CX or ECX bytes, words or longs, precede a `scas` instruction with a `repz` or `repnz` prefix.

Example

Compare the memory byte addressed in the destination register, relative to the ES segment, with the contents of the AL register.

```
scasb
```

Compare the memory word addressed in the destination register, relative to the ES segment, with the contents of the AX register

```
scasw
```

Compare the memory double-word addressed in the destination register, relative to the ES segment, with the contents of the EAX register

```
scasl
```

Look-Up Translation Table (`xlat`)

```
xlat
```

Operation

set AL to DS:[(E)BX + unsigned AL]

Description

Changes the AL register from the table index to the table entry. AL should be the unsigned index into a table addressed by DS:BX (16-bit address) or DS:EBX (32-bit address).

Example

Change the AL register from the table index to the table entry.

```
xlat
```

Repeat String Operation (*rep*, *repnz*, *repz*)

```
rep;  
repnz;  
repz;
```

Operation

repeat string-operation until tested-condition

Description

Use the *rep* (repeat while equal), *repnz* (repeat while nonzero) or *repz* (repeat while zero) prefixes in conjunction with string operations. Each prefix causes the associated string instruction to repeat until the count register (CX) or the zero flag (ZF) matches a tested condition.

Example

Repeat while equal: Copy the 8-bit byte from the DS:[(E)SI] to the ES:[(E)DI] register.

```
rep; movsb
```

Repeat while not zero: Compare the memory byte double-word addressed in the destination register EDI, relative to the ES segment, with the contents of the EAX register.

```
repnz; scasd
```

Repeat while zero: Transfer the contents of the EAX register to the memory double-word addressed in the destination register EDI, relative to the ES segment.

```
repz; stosd
```

Procedure Call and Return Instructions

Far Call — Procedure Call (*lcall*)

```
lcall    immptr  
lcall    *mem48
```

Operation

far call ptr16:{16|32} far call m16:{16|32}

Description

The `lcall` instruction calls intersegment (far) procedures using a full pointer. `lcall` causes the procedure named in the operand to be executed. When the called procedure completes, execution flow resumes at the instruction following the `lcall` instruction (see the `return` instruction).

`lcall ptr16:{16|32}` uses a four-byte or six-byte operand as a long pointer to the called procedure.

`lcall m16:{16|32}` fetches the long pointer from the specified memory location.

In Real Address Mode or Virtual 8086 Mode, the long pointer provides 16 bits for the CS register and 16 or 32 bits for the EIP register. Both forms of the `lcall` instruction push the CS and IP or EIP registers as a return address.

Example

Use a four-byte operand as a long pointer to the called procedure.

```
lcall $0xfebc, $0x12345678
```

Fetch a long pointer from the memory location addressed by the `edx` register, offset by 3.

```
lcall *3(%edx)
```

Near Call — Procedure Call (`call`)

```
call      disp32
call     *r/m32
```

Operation

near call rel{16|32}

near call r/m{16|32}

Description

The `call` instruction calls near procedures using a full pointer. `call` causes the procedure named in the operand to be executed. When the called procedure completes, execution flow resumes at the instruction following the `call` instruction (see the `return` instruction).

`call rel{16|32}` adds a signed offset to address of the instruction following the `call` instruction to determine the destination; that is, the displacement is relative to the next instruction. The displacement value is stored in the EIP register. For `rel16`, the upper 16 bits of EIP are cleared to zero resulting in an offset value that does not exceed 16 bits.

`call r/m{16|32}` specifies a register or memory location from which the absolute segment offset is fetched. The offset of the instruction following the `call` instruction is pushed onto the stack. After the procedure completes, the offset is popped by a near `ret` instruction within the procedure.

Both forms of the `call` instruction have no affect on the CS register.

Example

Program counter minus 0x11111111.

```
call .-0x11111111
```

Add a signed offset value to the address of the next instruction.

```
call *4(%edi)
```

Return from Procedure (`ret`)

```
ret
ret     imm16
```

Operation

return to caller

Description

The `ret` instruction transfers control to the return address located on the stack. This address is usually placed on the stack by a `call` instruction. Issue the `ret` instruction within the called procedure to resume execution flow at the instruction following the `call`.

The optional numeric (16- or 32-bit) parameter to `ret` specifies the number of stack bytes or words to be released after the return address is popped from the stack. Typically, these bytes or words are used as input parameters to the called procedure.

For an intersegment (near) return, the address on the stack is a segment offset that is popped onto the instruction pointer. The CS register remains unchanged.

Example

Transfer control to the return address located on the stack.

```
ret
```

Transfer control to the return address located on the stack. Release the next 16-bytes of parameters.

```
ret 16
```

Long Return (`lret`)

```
lret  
lret    imm16
```

Operation

return to caller

Description

The `lret` instruction transfers control to a return address located on the stack. This address is usually placed on the stack by an `lcall` instruction. Issue the `lret` instruction within the called procedure to resume execution flow at the instruction following the `call`.

The optional numeric (16- or 32-bit) parameter to `lret` specifies the number of stack bytes or words to be released after the return address is popped from the stack. Typically, these bytes or words are used as input parameters to the called procedure.

For an intersegment (far) return, the address on the stack is a long pointer. The offset is popped first, followed by the selector.

In Real Mode, CS and IP are loaded directly. In Protected mode, an intersegment return causes the processor to check the descriptor addressed by the return selector. The AR byte of the descriptor must indicate a code segment of equal or lesser privilege

(or greater or equal numeric value) than the current privilege level. Returns to a lesser privilege level cause the stack to be reloaded from the value saved beyond the parameter block.

Example

Transfer control to the return address located on the stack.

```
lret
```

Transfer control to the return address located on the stack. Release the next 16-bytes of parameters.

```
lret $-32767
```

Enter/Make Stack Frame for Procedure Parameters (enter)

```
enter      imm16, imm8
```

Operation

make stack frame for procedure parameters

Description

Create the stack frame required by most block-structured high-level languages. The `imm16` operand specifies the number of bytes of dynamic storage allocated on the stack for the routine being entered. The `imm8` operand specifies the lexical nesting level (0 to 31) of the routine within the high-level language source code. The nesting level determines the number of stack frame pointers copied into the new stack frame from the preceding frame.

Example

Create a stack frame with 0xfecd bytes of dynamic storage on the stack and a nesting level of 0xff.

```
enter $0xfecd, $0xff
```

High Level Procedure Exit (leave)

leave

Operation

set (E)SP to (E)BP, then pop (E)BP

Description

The `leave` instruction reverses the actions of an `enter` instruction. `leave` copies the frame pointer to the stack point and releases the stack space formerly used by a procedure for its local variables. `leave` pops the old frame pointer into (E)BP, thus restoring the caller's frame. A subsequent `ret nn` instruction removes any arguments pushed onto the stack of the exiting procedure.

Example

Copy the frame pointer to the stack pointer and release the stack space.

leave

Jump Instructions

Jump if ECX is Zero (jcxz)

jcxz disp8

Operation

jump to disp8 if (E)CX is 0

Description

The `jcxz` instruction tests the contents of the CX or ECX register for 0. `jcxz` differs from other conditional jumps that it tests the flags, rather than (E)CX.

`jcxz` is useful at the beginning of a loop that terminates with a conditional loop instruction; such as:

```
loopne .-126
```

In this case, `jcxz` tests `CX` or `ECX` for 0 prior to entering the loop, thus executing 0 times:

Example

```
jcxz .-126  
...  
loopne .-126
```

Loop Control with CX Counter (`loop`, `loopnz`, `loopz`)

<code>loop</code>	<code>disp8</code>
<code>loopnz</code>	<code>disp8</code>
<code>loopne</code>	<code>disp8</code>
<code>loopz</code>	<code>disp8</code>
<code>loope</code>	<code>disp8</code>

Operation

decrement count; jump to `disp8` if count not equal 0

decrement count; jump to `disp8` if count not equal 0 and `ZF` = 0

decrement count; jump to `disp8` if count not equal 0 and `ZF` = 1

Description

`loop` decrements the count register; the flags register remains unchanged. Conditions are checked for by the particular form of `loop` you used. If the conditions match, a short jump is made to the address specified by the `disp8` operand. The range of the `disp8` operand, relative to the current instruction, is +127 decimal bytes to -128 decimal bytes.

`loop` instructions provide iteration control and combine loop index management with conditional branching. Prior to using the `loop` instruction, load the count register with an unsigned iteration count. Then, add the `loop` instruction at the end of a series of instructions to be iterated. The `disp8` operand points to the beginning of the iterative loop.

Example

Decrement the count register and when the count is not equal to zero, jump short to the disp8 location.

```
loopne .-126
```

Jump (jmp, ljmp)

```
jmp    disp{8|16|32}
jmp    *r/m{16|32}
ljmp   immPtr
ljmp   *mem48
jcc    disp{8|32}
```

Operation

jump short or near; displacement relative to next instruction

jump far (intersegment; 4- or 6-byte immediate address)

jump if condition is met; displacement relative to next instruction

Description

The jmp instruction transfers execution control to a different point in the instruction stream; records no return information.

Jumps with destinations of disp[8|16|32] or r/m[16|32] are near jumps and do not require changes to the segment register value.

jmp rel{16|32} adds a signed offset to the address of the instruction following the jmp instruction to determine the destination; that is, the displacement is relative to the next instruction. The displacement value is stored in the EIP register. For rel16, the upper 16 bits of EIP are cleared to zero resulting in an offset value not to exceed 16 bits.

ljmp ImmPtr or *mem48 use a four- or six-byte operand as a long pointer to the destination. In Real Address Mode or Virtual 8086 mode, the long pointer provides 16 bits for the CS register and 16 or 32 bits for the EIP register. In Protected mode, both long pointer forms consult the AR (Access Rights) byte of the descriptor indexed by the selector part of the long pointer. The jmp performs one of the following control transfers depending on the value of the AR byte:

- A jump to a code segment at the same privilege level
- A task switch

Example

Jump to the relative effective address (addressed by the EDI register plus an offset of 4):

```
jmp *4(%edi)
```

Long jump, use 0xfebc for the CS register and 0x12345678 for the EIP register:

```
ljmp $0xfebc, $0x12345678
```

Jump if not equal:

```
jne .+10
```

Interrupt Instructions

Call to Interrupt Procedure (*int*, *into*)

```
int 3  
int imm8  
into
```

Operation

interrupt 3 — trap to debugger

interrupt numbered by immediate byte

interrupt 4 — if overflow flag is 1

Description

The *int* instruction generates a software call to an interrupt handler. The *imm8* (0 to 255) operand specifies an index number into the IDT (Interrupt Descriptor Table) of the interrupt routine to be called. In Protect Mode, the IDT consists of an array of 8-byte descriptors; the descriptor for the interrupt invoked must indicate an interrupt, trap, or task gate. In Real Address Mode, the IDT is an array of four byte-long pointers. In Protected and Real Address Modes, the base linear address of the IDT is defined by the contents of the IDTR.

The `into` form of the `int` instruction implies interrupt 4. The interrupt occurs only if the overflow flag is set.

The first 32 interrupts are reserved for system use. Some of these interrupts are used for internally generated exceptions.

The `int imm8` form of the interrupt instruction behaves like a far call except that the flags register is pushed onto the stack before the return address. Interrupt procedures return via the `iret` instruction, which pops the flags and return address from the stack.

In Real Address Mode, the `int imm8` pushes the flags, CS, and the return IP onto the stack, in that order, then jumps to the long pointer indexed by the interrupt number.

Example

Trap to debugger:

```
int $3
```

Trap to interrupt 0xff:

```
int $0xff
```

Trap to interrupt 4:

```
into
```

Interrupt Return (`iret`)

```
iret
```

Operation

return → routine

Description

In Real Address Mode, `iret` pops CS, the flags register, and the instruction pointer from the stack and resumes the routine that was interrupted. In Protected Mode, the setting of the nested task flag (NT) determines the action of `iret`. The IOPL flag register bits are changed when CPL equals 0 and the new flag image is popped from the stack.

`iret` returns from an interrupt procedure without a task switch if `NT` equals 0. Returned code must be equally or less privileged than the interrupt routine as indicated CS selector RPL bits popped from the stack. If the returned code is less privileged, `iret` pops `SS` and the stack pointer from the stack.

`iret` reverses the operation of an `INT` or `CALL` that caused the task switch if `NT` equals 1. The task executing `iret` is updated and saved in its task segment. The code that follows `iret` is executed if the task is re-entered.

Example

Resume the interrupted routine:

```
iret
```

Protection Model Instructions

Store Local Descriptor Table Register (`sldt`)

```
sldt    r/m16
```

Operation

LDTR → r/m[16]

Description

The Local Descriptor Table Register (LDTR) is stored by `sldt` as indicated by the effective address operand. LDTR is stored into the two-byte register or the memory location.

`sldt` is not used in application programs. It is used only in operating systems.

Example

Store the LDTR in the effective address (addressed by the `EBX` register plus and offset of 5):

```
sldt 5(%ebx)
```

Store Task Register (str)

```
str    r/m16
```

Operation

STR → r/m(16)

Description

The contents of the task register is stored by `sldt` as indicated by the effective address operand. STR is stored into the two-byte register or the memory location.

Example

Store `str` in the effective address (addressed by the EBX register plus an offset of 5):

```
str 5(%ebx)
```

Load Local Descriptor Table Register (lldt)

```
lldt    r/m16
```

Operation

SELECTOR → LDTR

Description

LDTR is loaded by LLDT. The operand (word) contains a selector to a local GDT (Global Descriptor Table). The descriptor registers are not affected. The task state segment LDT field does not change.

The LDTR is marked invalid if the selector operand is 0. A #GP fault is caused by all descriptor references (except LSL VERR, VERW, or LAR instructions).

LLDT is not used in application programs. It is used in operating systems.

Example

Load the LLDT register from the effective address (addressed by the EBX register plus and offset of 5):

```
lldt 5(%ebx)
```

Load Task Register (ltr)

```
ltr    r/m16
```

Operation

r/m16 → Task Register

Description

The task register is loaded by LTR from the source register or memory location specified by the operand. The loaded task state segment is tagged busy. A task switch does not occur.

Example

Load the TASK register from the effective address (addressed by the EBX register plus and offset of 5):

```
ltr 5(%ebx)
```

Verify a Segment for Reading or Writing (verr, verw)

```
verr    r/m16  
verw    r/m16
```

Operation

1 → ZF (if segment can be read or written)

Description

VERR and VERW contains the value of a selector in the two-byte register or memory operand. VERR and VERW determine if the indicated segment can be reached in the current privilege level and whether it is readable (VERR) or writable (VERW). If the segment can be accessed, the zero flag (ZF) is set to 1, otherwise the zero flag is set to 0. For the zero flag to be set these conditions must be met:

- The selector denotes a descriptor; the selector is “defined”.
- The selector is a code or data segment; not a task segment, LDT or a gate.
- For VERR, the segment must be readable, for VERW, writable.
- The descriptor privilege level (DPL) can be any value for VERR. otherwise the DPL must have the same or less privilege as the current level and the DPL of the selector.

Validation is performed as if the segment were loaded into DS, ES, FS, or GS and the indicated write or read performed. The validation results are indicated by the zero flag. The value of the selector cannot result in an exception.

Example

Determine if the segment indicated by the effective address (addressed by the EBX register plus an offset of 5) can be reached in the current privilege level and whether it is readable (VERR):

```
verr 5(%ebx)
```

Store Global/Interrupt Descriptor Table Register (sgdt, sidt)

```
sgdt      mem48  
sidt      mem48
```

Operation

DTR → mem48

Description

The contents of the descriptor table register is copied by `sgdt/sidt` to the six bytes of memory specified by the operand. The first word at the effective address is assigned the LIMIT field of the register. If the operand-size attribute is 32-bits:

- The base field of the register is assigned to the next three bytes.
- The fourth byte is written as zero.
- The last byte is undefined.

If the operand-size attribute is 16-bits, the 32-bit BASEfield of the register is assigned to the next four bytes.

`sgdt/sldt` are not used in application programs, they are used in operating systems.

Example

Copy the contents of the Global Descriptor Table Register to the specified memory location:

```
sgdt 0x55555555
```

Copy the contents of the Interrupt Descriptor Table Register to the effective address (addressed by the EBX register plus an offset of 5):

```
sidt 5 (%ebx)
```

Load Global/Interrupt Descriptor Table (`lgdt`, `lidt`)

```
lgdt      mem48
lidt      mem48
```

Operation

MEM48 → GDTR MEM48 → IDTR

Description

The GDTR and IDTR are loaded with a linear base address and limit value from a six-byte operand in memory by the `lgdt/lidt` instructions. For a 16-bit operand:

- Load the register with a 16-bit limit and a 24-bit base.
- The six-byte data operand high-order eight bits are not used.

For a 32-bit operand:

- Load the register with a 16-bit limit and a 32-bit base.
- The six-byte data operand high-order eight bits are used as the high-order base address bits.

All 48-bits of the six-byte data operand are always stored into by the `sgdt/sidt` instructions. For a 16-bit and a 32-bit operand, the upper eight-bits are written with the high-order eight address bits. `lgdt` or `lidt`, when used with a 16-bit operand to load the register stored by `sgdt` or `sidt`, stores the upper eight-bits as zeros.

`lgdt` and `lidt` are not used in application programs; they are used in operation system. `lgdt` and `lidt` are the only instructions that load a linear address directly in 80386 Protected Mode.

Example

Load the Global/Interrupt Descriptor Table Register from memory address 0x55555555:

```
lgdt 0x55555555
lidt 0x55555555
```

Store Machine Status Word (`smsw`)

`smsw` `r/m16`

Operation

MSW → `r/m16`

Description

The machine status word is stored by `smsw` in the two-byte register of memory location pointed to by the effective address operand.

80386 machines should use `MOV ..., CR0`.

Example

Store the machine status word in the effective address (addressed by the EBX register plus an offset of 5):

```
smsw 5(%ebx)
```

Load Machine Status Word (lmsw)

`lmsw` `r/m16`

Operation

`r/m16` → MSW

Description

The machine status word (part of CR0) is loaded by `lmsw` from the source operand. `lmsw` can be used to switch to Protected Mode if followed by an intersegment jump to clear the instruction queue. `lmsw` cannot switch back to Real Address Mode.

`lmsw` is not used in application programs. It is used in operating systems.

Example

Load the machine status word from the contents of the effective address (addressed by the EBX register plus an offset of 5):

```
lmsw 5(%ebx)
```

Load Access Rights (lar)

`lar` `r/m32, reg32`

Operation

`r/m16` (masked by FF00) → r16

`r/m32` (masked by 00FxFF00) → r32

Description

If the selector is visible at the CPL (modified by the RPL) and is a valid descriptor type, `lar` stores a form of the second doubleword of the descriptor for the source selector. The designated register is loaded with the double-word (high-order) of the descriptor masked by 00FxFF00, and the zero flag is set to 1. The x in 00Fx ... indicates that these four bits loaded by `lar` are undefined. The zero flag is cleared if the selector is invisible or of the wrong type.

The 32-bit value is stored in the 32-bit destination register if the 32-bit operand size is specified. If the 16-bit operand size is specified, the lower 16-bits of this value are stored in the 16-bit destination register.

For `lar`, all data segment descriptors and code are valid.

Example

Load access rights from the contents of the effective address (addressed by the EBX register plus an offset of 5) into the EDX register:

```
lar 5(%ebx), %edx
```

Load Segment Limit (`lsl`)

```
lsl r/m32, reg32
```

Operation

Selector `rm16` (byte) → `r16`

Selector `rm32` (byte) → `r32`

Selector `rm16` (page) → `r16`

Selector `rm32` (page) → `r32`

Description

`lsl` loads a register with a segment limit (unscrambled). The descriptor type must be accepted by `lsl`, and the source selector must be visible at the CPL weakened by RPL. ZF is then set to 1. Otherwise, ZF is set to 0 and the destination register is unchanged.

The segment limit is loaded as a byte value. A page value limit in the descriptor is translated by `lsl` to a byte limit before `lsl` loads it in the destination register (the 20-bit limit from the descriptor is shifted left 12 and OR'd with 0000FFFH).

`lsl` stores the 32-bit granular limit in the 16-bit destination register.

For `lsl`, code and data segment descriptors are valid.

Example

Load a segment limit from the contents of the effective address (addressed by the EBX register plus an offset of 5) into the EDX register.

```
lsl 5(%ebx), %edx
```

Clear Task-Switched (clts)

```
clts
```

Operation

0 → TS Flag in CR0

Description

The task-switched flag in register CR0 is cleared by `clts`. The TS Flag is set by the 80386 for each task switch. The TS Flag is used as follows:

- If the TS Flag is set, each execution of the ESC instruction is trapped.
- If the TS Flag and the MP Flag are both set, execution of a Wait instruction is trapped.

If a task switch is made after an ESC instruction is started, save the processor extension context before a new ESC instruction can be run. The fault handler resets the TS Flag and saves the context.

`clts` is not used in application program, it is used in operating systems.

`clts` can only be executed at privilege level 0.

Example

Clear the TS flag:

```
clts
```

Adjust RPL Field of Selector (arpl)

```
arpl r16, r/m16
```

Operation

If RPL 1 < RPL 2, 1 → ZF

Description

`arpl` has two operands. The first operand is a 16-bit word register or memory variable that contains the value of a selector. The second operand is a word register. If the RPL field of the second operand is greater than the RPL field of the first operand, ZF is set to 1 and the RPL field of the first operand is increased to match the RPL field of the second operand. Otherwise, no change is made to the first operand and the ZF is set to 0.

`arpl` is not used in application programs, it is used in operating systems.

`arpl` guarantees that a selector to a subroutine does not request a privilege greater than allowed. Normally, the second operand of `arpl` is a register that contains the CS selector value of the caller.

Example

```
arpl %sp, 5(%ebx)
```

Bit Instructions

Bit Scan Forward (bsf)

```
bsf{wl}          r/m[16|32], reg[16|32]
```

Operation

(r/m = 0) 0 → ZF (r/m ≠ 0) 0 → ZF

Description

bsf scans the bits, starting at bit 0, in the doubleword operand or the second word. If the bits are all zero, ZF is cleared. Otherwise, ZF is set and the bit index of the first set bit, found while scanning in the forward direction, is loaded into the destination register.

Example

```
bsf 4(%edi), %edx
```

Bit Scan Reverse (bsr)

```
bsr{wl}          r/m[16|32], reg[16|32]
```

Operation

(r/m = 0) 0 → ZF (r/m ≠ 0) 0 → ZF

Description

bsr scans the bits, starting at the most significant bit, in the doubleword operand or the second word. If the bits are all zero, ZF is cleared. Otherwise, ZF is set and the bit index of the first set bit found, while scanning in the reverse direction, is loaded into the destination register

Example

```
bsr 4(%edi), %edx
```

Bit Test (bt)

```
bt{wl}          imm8, r/m[16|32]  
bt{wl}          reg[16|32], r/m[16|32]
```

Operation

BIT [LeftSRC, RightSRC] → CF

Description

The bit indicated by the first operand (base) and the second operand (offset) are saved by *bt* into CF (carry flag).

Example

```
bt1 $253, 4(%edi)
bt1 %edx, 4(%edi)
```

Bit Test And Complement (btc)

```
btc{wl}          imm8, r/m[16|32]  btc{wl}          reg[16|32], r/m[16|32]
```

Operation

BIT [LeftSRC, RightSRC] → CF

NOT BIT [LeftSRC, RightSRC] → BIT[LeftSRC, RightSRC]

Description

The bit indicated by the first operand (base) and the second operand (offset) are saved by *btc* into CF (carry flag) and complements the bit.

Example

```
bt1 $253, 4(%edi)
bt1 %edx, 4(%edi)
```

Bit Test And Reset (btr)

```
btr{wl}          imm8, r/m[16|32]
btr{wl}          reg[16|32], r/m[16|32]
```

Operation

BIT[LeftSRC, RightSRC] → CF

0 → BIT[LeftSRC, RightSRC]

Description

The value of the first operand (base) and the second operand (bit offset) are saved by `btr` into the carry flag and then it stores 0 in the bit.

Example

```
btrl $253, 4(%edi)
    btrl $edx, 4(%edi)
```

Bit Test And Set (bts)

```
bts{wl}    imm8, r/m[16|32]
bts{wl}    reg[16|32], r/m[16|32]
```

Operation

BIT[LeftSRC, RightSRC] → CF

0 → BIT[LeftSRC, RightSRC]

Description

The value of the first operand (base) and the second operand (bit offset) are saved by `bts` into the carry flag and then it stores 1 in the bit.

Example

```
btsl $253, 4(%edi)
    btsl $edx, 4(%edi)
```

Exchange Instructions

Compare and Exchange (cmpxchg)[486]

`cmpxchg{bwl}` `reg[8|16|32], r/m[8|16|32]`

Example

```
cmpxchgb %cl, 1(%esi)
cmpxchgl %edx, 4(%edi)
```

Floating-Point Transcendental Instructions

Floating-Point Sine (fsin)

`fsin`

Example

Replace the contents of the top of the stack with its sine.

`fsin`

Floating-Point Cosine (fcos)

`fcos`

Example

Replace the contents of the top of the stack with its cos.

```
fcos
```

Floating-Point Sine and Cosine (fsincos)

```
fsincos
```

Example

Replace the contents of the top of the stack with its sine and then push the cosine onto the FPU stack.

```
fsincos
```

Floating-Point Constant Instructions

Floating-Point Load One (fld)

```
fldl  
fldl2+  
fldl2e  
fldpi  
fldlg2  
fldln2  
fldz
```

Example

Use these constant instructions to push often-used values onto the FPU stack.

```
fldl 2(%ecx)
```

Processor Control Floating-Point Instructions

Floating-Point Load Control Word (fldcw)

fldcw r/m16

Example

Load the FPU control word with the value in the specified memory address.

```
fldcw 2(%ecx)
```

Floating-Point Load Environment (fldenv)

fldenv mem

Example

Reload the FPU environment from the source-operand specified memory space.

```
fldenv 2(%ecx)
```

Miscellaneous Floating-Point Instructions

Floating-Point Different Remainder (fprem)

fprem1

Example

Divide stack element 0 by stack element 1 and leave the remainder in stack element 0.

```
fprem
```

Floating-Point Comparison Instructions

Floating-Point Unsigned Compare (fucom)

```
fucom    freg
```

Description:

Compare stack element 0 with stack element (i). Use condition codes:

No compare: 111

(i) < stack 0: 000

(i) > stack 0: 001

(i) = stack 0: 100

Example

Compare stack element 0 with stack element 7.

```
fucom %st(7)
```

Floating-Point Unsigned Compare And Pop (fucomp)

```
fucomp    freg
```

Description

Compare stack element 0 with stack element (i). Use condition codes shown for fucom. Then pop the stack.

Example

```
fucomp %st(7)
```

Floating-Point Unsigned Compare And Pop Two (fucompp)

```
fucompp
```

Description

Compare stack element 0 with stack element (i). Use condition codes shown for fucom. Then pop the stack twice.

Example

```
fucompp %st(7)
```

Load and Move Instructions

Load Effective Address (lea)

```
lea{wl}          r/m[16|32], reg[16|32]
```

Operation

Addr(m) → r16 Addr(m) → r32

Truncate to 16 bits(Addr(m)) → r16

Truncate to 16 bits(Addr(m)) → r32

Description

The offset part of the effective address is calculated by `leal` and stored in the specified register. The specified register determines the operand-size attribute if the instruction. The USE attribute of the segment containing the second operand determines the address-size attribute.

Example

```
leal 0x33333333, %edx
```

Move (mov)

```
mov{bwl}      imm[8|16|32], r/m[8|16|32]
mov{bwl}      reg[8|16|32], r/m[8|16|32]
mov{bwl}      r/m[8|16|32], reg[8|16|32]
```

Operation

SRC → DEST

Description

`mov` stores or loads the following special registers in or from a general purpose register.

- Control registers CR0, CR2, and CR3
- Debug registers DR0, DR1, DR2, DR3, DR6, and DR7
- Test registers TR6 and TR7

These instructions always use 32-bit operands.

Example

```
movl %cr3, %ebp
movl %db7, %ebp
movl %ebp, %cr3
movl %ebp, %db7
movl %tr7, %ebp
movl %ebp, %tr7
```

Move Segment Registers (movw)

```
movw    sreg, r/m16
movw    r/m16, sreg
```

Operation

r/m16 → Sreg

Sreg → r/m16

Description

movw copies the first operand to the second operand, including data from a descriptor. The descriptor table entry for the selector contains the data for the register. The DS and ES registers can be loaded with a null selector without causing an exception. Use of DS or ES however, causes a #GP(0), and no memory reference occurs.

All interrupts are inhibited until after the execution of the next instruction, after a movw into SS. Special actions and checks result from loading a segment register under Protected Mode.

Example

```
movw %CS, 5(%ebx)
movw %(%ebx), %CS
```

Move Control Registers (mov)

```
mov{1}  creg, reg32
mov{1}  reg32, creg
```

Operation

SRC → DEST

Description

This form of mov stores or loads the Control Register CR0, CR2, or CR4 to or from a general purpose register.

These instructions are always used with 32-bit operands.

Example

```
movl %cr3, %ebp
movl %ebp, %cr3
```

Move Debug Registers (mov)

```
mov{1}    dreg, reg32
mov{1}    reg32, dreg
```

Operation

SRC → DEST

Description

This form of `mov` stores or loads the Debug Register DR1, DR2, or DR3, DR6, and DR7 to or from a general purpose register.

These instructions are always used with 32-bit operands.

Example

```
movl %db7, %ebp
movl %ebp, %db7
```

Move Test Registers (mov)

```
mov{1}    treg, reg32
mov{1}    reg32, treg
```

Operation

SRC → DEST

Description

This form of `mov` stores or loads the Test Register TR6 or TR7 to or from a general purpose register.

These instructions are always used with 32-bit operands.

Example

```
movl %tr7, %ebp
movl %ebp, %tr7
```

Move With Sign Extend (movsx)

```
movsx{wl}      r/m8, reg[16|32]
movsxl        r/m16, reg32
```

Operation

SignExtend(SRC) → DEST

Description

`movsx` reads the contents of the register or effective address as a word or byte. `movsx` then sign-extends the 16- or 32-bit value to the operand-size attribute of the instruction. The result is stored in the destination register by `movsx`.

Example

```
movsxb1 1(%esi), %edx
movsxl 5(%ebx), %edx
```

Move With Zero Extend (movzb)

```
movzb{wl}      r/m8, reg[16|32]
movzwl        r/m16, reg32
```

Operation

SignExtend(SRC) → DEST

Description

`movzx` reads the contents of the register or effective address as a word or byte. `movzx` then sign-extends the 16- or 32-bit value to the operand-size attribute of the instruction. The result is stored in the destination register by `movzx`.

Pop Instructions

Pop All General Registers (`popa`)

`popa{w1}`

Operation

POP → r16 POP → r32

Description

The eight 16-bit general registers are popped by `popa`. However, the SP value is not loaded into SP, it is discarded. `popa` restores the general registers to their values before a previous `pusha` was executed. DI is the first register popped.

The eight 32-bit registers are popped by `popad`. However, the ESP value is not loaded into ESP, it is discarded. `popad` restores the general registers to their values before a previous `pushad` was executed. EDI is the first register popped.

Example

`popa1`

Push Instructions

Push All General Registers (pusha)

`pusha{wl}`

Operation

SP → r16

SP → r32

Description

The 16-bit or 32-bit general registers are saved by `pusha` and `pushad`, respectively. The stack pointer is decremented by 16 by `pusha` to hold the eight word values. The stack pointer is decremented by 32 by `pushad` to hold the eight doubleword values. The registers are pushed onto the stack in the order received; the stack bytes appear in reverse order. DI or EDI is the last stack pushed.

Example

`pushal`

Rotate Instructions

Rotate With Carry Left (rcl)

`rcl{bwl}` `imm8, r/m[8|16|32]`
`rcl{bwl}` `%c1, r/m[8|16|32]`

Operation

r/m high-order bit → CF

CF → r/m low-order bit

r/m → ShiftLeft

Description

The left rotate instruction shifts all bits in the register or memory operand specified. The carry flag (CF) is included in the rotation. The most significant bit is rotated to the carry flag, the carry flag is rotated to the least significant bit position, all other bits are shifted to the left. The result includes the original value of the carry flag.

The first operand value indicates how many times the rotate takes place. The value is either the contents of the CL register or an immediate number. For a single rotate, where the first operand is one, the overflow flag (OF) is defined. For all other cases, OF is undefined. After the shift, the carry flag bit is XORed with the most significant result bit.

Example

```
rclb $1, 1(%esi)
rclb $253, 1(%esi)
rclb %c1, 1(%esi)
rcll $1, 4(%edi)
rcll $253, 4(%edi)
rcll %c1, 4(%edi)
```

Rotate With Carry Right (rcr)

```
rcr{bwl}          imm8, r/m[8|16|32]
rcr{bwl}          %c1, r/m[8|16|32]
```

Operation

r/m high-order bit → CF

CF → r/m low-order bit

r/m → ShiftRight

Description

The right rotate instruction shifts all bits in the register or memory operand specified. The carry flag (CF) is included in the rotation. The least significant bit is rotated to the carry flag, the carry flag is rotated to the most significant bit position, all other bits are shifted to the right. The result includes the original value of the carry flag.

The first operand value indicates how many times the rotate takes place. The value is either the contents of the CL register or an immediate number. For a single rotate, where the first operand is one, the overflow flag (OF) is defined. For all other cases, OF is undefined. After the shift, the carry flag bit is XORed with the two most significant result bits.

Example

```
rcrb $1, 1(%esi)
rcrb $253, 1(%esi)
rcrb %cl, 1(%esi)
rcrl $1, 4(%edi)
rcrl $253, 4(%edi)
rcrl %cl, 4(%edi)
```

Rotate Left (rol)

```
rol{bwl}      imm8, r/m[8|16|32]
rol{bwl}      %cl, r/m[8|16|32]
```

Operation

r/m high-order bit → CF

CF → r/m low-order bit

r/m → ShiftLeft

Description

The left rotate instruction shifts all bits in the register or memory operand specified. The most significant bit is rotated to the carry flag, the carry flag is rotated to the least significant bit position, all other bits are shifted to the left. The result *does not* include the original value of the carry flag.

The first operand value indicates how many times the rotate takes place. The value is either the contents of the CL register or an immediate number. For a single rotate,

where the first operand is one, the overflow flag (OF) is defined. For all other cases, OF is undefined. After the shift, the carry flag bit is XORed with the most significant result bit.

Example

```
rclb $1, 1(%esi)
rclb $253, 1(%esi)
rclb %cl, 1(%esi)
rcll $1, 4(%edi)
rcll $253, 4(%edi)
rcll %cl, 4(%edi)
```

Rotate Right (ror)

```
ror{bwl}      imm8, r/m[8|16|32]
ror{bwl}      %cl, r/m[8|16|32]
```

Operation

r/m high-order bit → CF

CF → r/m low-order bit

r/m → ShiftRight

Description

The right rotate instruction shifts all bits in the register or memory operand specified. The least significant bit is rotated to the carry flag, the carry flag is rotated to the most significant bit position, all other bits are shifted to the right. The result *does not* include the original value of the carry flag. The first operand value indicates how many times the rotate takes place. The value is either the contents of the CL register or an immediate number. For a single rotate, where the first operand is one, the overflow flag (OF) is defined. For all other cases, OF is undefined. After the shift, the carry flag bit is XORed with the two most significant result bits.

Example

```
rcrib $1, 1(%esi)
rcrib $253, 1(%esi)
rcrib %cl, 1(%esi)
rcrl $1, 4(%edi)
```

```
rcr1 $253, 4(%edi)
rcr1 %c1, 4(%edi)
```

Byte Instructions

Byte Set On Condition (setcc)

```
setcc    r/m8
```

Operation

ConditionTrue: 1 → r/m8

ConditionFalse: 0 → rm/8

Description

If the condition is met, *setcc* stores a one byte at the destination specified by the effective address. If the condition is not met, *setcc* stores a zero byte. The following table lists the *setcc* condition options. Similar condition options are separated by commas, followed by the flag condition.

TABLE 2-10 *setcc* Condition List

Instruction (<i>set+cc</i>)	Set Byte If:
<i>seta, setnbe</i>	greater, not equal or less than, CF=0 & ZF=0
<i>setae, setnc, setnb</i>	equal or greater, not carry, not less than, CF=0
<i>setb, setc, setnae</i>	less than carry, carry = 1, not equal or greater than, CF=1
<i>setbe, setna</i>	equal or less than, not greater than carry, CF=1 or ZF=1
<i>sete, setz</i>	equal, zero, ZF=1
<i>setg, setnle</i>	greater, ZF=0 or SF=OF. not equal or less, ZF=1 or SF ≠ OF
<i>setge, setnl</i>	equal or greater, not less, SF = OF
<i>setl, setnge</i>	less, not equal or greater, SF ≠ OF

TABLE 2-10 *setcc* Condition List (Continued)

Instruction (<i>set+cc</i>)	Set Byte If:
<i>setle, setng</i>	equal or less, not greater, ZF = 1 and SF ≠ OF
<i>setne, setnz</i>	not equal, not zero, ZF = 0
<i>setno</i>	not overflow, OF = 0
<i>setns</i>	not sign, SF=0
<i>seto</i>	overflow, OF = 1
<i>setpe, setp</i>	parity even, parity, PF = 1
<i>setpo, setnp</i>	parity odd, not parity, PF = 0
<i>sets</i>	sign, SF = 1

Example

```
set(cc) 1(%esi)
```

Byte Swap (*bswap*) [486]

```
bswap reg[16|32]
```

Example

Convert little/big endian to big/little endian by swapping bytes.

```
bswap %ebx
```

Exchange Instructions

Exchange And Add (*xadd*) [486]

```
xadd{bwl} reg[8|16|32], r/m[8|16|32]
```

Example

Exchange the byte contents of the ESI register with the byte register and load the sum into the ESI register.

```
xaddb %cl, 1(%esi)
```

Exchange Register / Memory With Register (`xchg`)

```
xchg{bwl}          reg[8|16|32], r/m[8|16|32]
```

Operation

DEST → temp

SRC → DEST

temp → SRC

Description

Two operands, in either order, are exchanged by `xchg`. During the exchange, BUS LOCK is asserted (regardless of the value of IOPL or the LOCK prefix) if a memory operand is part of the exchange.

Example

```
xchgb %cl, 1(%esi) /*exchange byte register with EA byte */
xchgl %ebp, %eax
xchgl %ebx, %eax
xchgl %ecx, %eax
xchgl %edi, %eax
xchgl %edx, %eax
xchgl %edx, 4(%edi) /*exchange word register with EA word */
xchgl %esi, %eax
xchgl %esp, %eax
```

Miscellaneous Instructions

Write Back and Invalidate Cache (wbinvd) [486 only]

wbinvd

Example

Write back and invalidate the cache.

wbinvd

Invalidate (invd) [486 only]

invd

Example

Invalidate the entire cache.

invd

Invalidate Page (invlpg) [486 only]

invlpg mem32

Example

Invalidate a single entry in the translation lookaside buffer.

invlpg 5(%ebx)

LOCK Prefix (lock)

lock

Operation

LOCK# → NEXT Instruction

Description

The LOCK # signal is asserted during execution of the instruction following the lock prefix. This signal can be used in a multiprocessor system to ensure exclusive use of shared memory while LOCK # is asserted. The bts instruction is the read-modify-write sequence used to implement test-and-run.

The lock prefix works only with the instructions listed here. If a lock prefix is used with any other instructions, an undefined opcode trap is generated.

bt, bts, btr, btc	m, r/imm
xchg	r, m
xchg	m, r
add, or, adc, sbb, and, sub, xor	m, r/imm
not, neg, inc, dec	m

Memory field alignment does not affect the integrity of lock.

If a different 80386 processor is concurrently executing an instruction that has a characteristic listed here, locked access is not guaranteed. The previous instruction:

- Does not follow a lock prefix
- Is not on the previous list of acceptable instructions
- A memory operand specified has a partial overlap with the destination operand.

Example

lock

No Operation (nop)

`nop`

Operation

NO OPERATION

Description

No operations are performed by `nop`. The `xchgl %eax, %eax` instruction is an alias for the `nop` instruction.

Example

`nop`

Halt (hlt)

`hlt`
Address Prefix
`addr16`
Data Prefix
`data16`

Operation

HLT → ENTER HALT STATE

Description

`halt` puts the 80386 in a HALT state by stopping instruction execution. Execution is resumed by an `nmi` or an enabled interrupt. After a `halt`, if an interrupt is used to continue execution, the saved CS:EIP or CS:IP value points to the next instruction (after the `halt`).

The `halt` instruction is privileged.

Example

```
hlt
```

Real Transfer Instructions

Load Real (fld)

```
fld{1st}
```

Operation

SRC → STACK ELEMENT 0

Description

The source operand is pushed onto the stack by `fld`. The register used before the stack top-pointer is decremented, is the register number used if the source is a register.

Example

Load stack element 7 onto stack element 0.

```
fld %st (7)
```

Store Real (fst)

```
fst{1st}
```

Operation

STACK ELEMENT 0 → DESTINATION

Description

The current value of stack element 0 is copied to the destination. The destination can be a single- or double-real memory operand or another register.

Example

Store the contents of stack element 7 onto stack element 0.

```
%fst (7)
```

Store Real and Pop (fstp)

```
fstp{1st}
```

Operation

STACK ELEMENT 0 → DESTINATION THEN POP

Description

The current value of stack element 0 is copied to the destination. The destination can be a single-, double-, or extended-real memory operand, or another register. Then pop the stack register.

Example

Copy the contents of stack element 0 onto stack element 7 and pop stack element 0.

```
%fstp (7)
```

Exchange Registers (fych)

```
fych
```

Example

Exchange the contents of stack element 0 and stack element 7.

```
fych %st (7)
```

Integer Transfer Instructions

Integer Load (fild)

```
fild{1|11}
```

Example

Convert the integer operand (signed) into extended-real and load it onto the floating-point stack.

```
fild 2(%eax)
```

Integer Store (fist)

```
fist{1}
```

Example

Convert the value in stack element 0 into a signed integer and transfer the result to register ECX with an offset of 2.

```
fist 2(%ecx)
```

Integer Store and Pop (fistp)

```
fistp{1|11}
```

Example

Convert the value in stack element 0 into a signed integer and transfer the result to register ECX with an offset of 2, then pop the stack.

```
fistp 2(%ecx)
```

Packed Decimal Transfer Instructions

Packed Decimal (BCD) Load (fbld)

`fbld`

Example

Convert the source operand (BCD) into extended-real and push it onto the floating-point stack.

```
fbld 2(%ecx)
```

Packed Decimal (BCD) Store and Pop (fbstp)

`fbstp`

Example

Convert the value in stack element 0 to a packed decimal integer and store the result in register ECX with an offset of 2, and pop the stack.

```
fbstp 2(%ecx)
```

Addition Instructions

Real Add (fadd)

`fadd{ls}`

Example

Add stack element 7 to stack element 0 and return the sum to stack element 0.

```
fadd %st(7), %st
```

Real Add and Pop (faddp)

```
faddp
```

Example

Add stack element 0 to stack element 7 and return the sum to stack element 7, then pop the stack.

```
faddp %st, %st(7)
```

Integer Add (fiadd)

```
fiadd{1}
```

Example

Add the integer contents of register ECX to stack element 0.

```
fiadd 2(%ecx)
```

Subtraction Instructions

Subtract Real and Pop (fsub)

```
fsub{1s}
```

Example

Subtract stack element 7 from stack element 0 and return the difference to stack element 0.

```
fsub %st(7), %st
```

Subtract Real (fsubp)

```
fsubp
```

Example

Subtract stack element 7 from stack element 0 and return the difference to stack element 7, then pop the stack.

```
fsubp %st, %st(7)
```

Subtract Real Reversed (fsubr)

```
fsubr{1s}
```

Example

Subtract stack element 0 from stack element 7 and return the difference to stack element 0.

```
fsubr %st(7), %st
```

Subtract Real Reversed and Pop (fsubrp)

```
fsubrp
```

Example

Subtract stack element 0 from stack element 7 and return the difference to stack element 7, then pop the stack.

```
fsubrp %st, %st(7)
```

Integer Subtract (fisubrp)

```
fisubrp
```

Example

Subtract stack element 0 from the integer contents of register ECX (with an offset of 2) and return the difference to register ECX, then pop the stack.

```
fisubrp 2(%ecx)
```

Integer Subtract Reverse (fisubr)

```
fisubr{1}
```

Example

Subtract stack element 0 from the integer contents of register ECX (with an offset of 2) and return the difference to stack element 0.

```
fisubr 2(%ecx)
```

Multiplication Instructions

Multiply Real (fmul)

```
fmul{1s}
```

Example

Multiply stack element 7 by stack element 0 and return the product to stack element 0.

```
fmul %st(7), %st
```

Multiply Real and Pop (fmulp)

```
fmulp
```

Example

Multiply stack element 0 by stack element 7 and return the product to stack element 7, then pop the stack.

```
fmulp %st, %st(7)
```

Integer Multiply (fimul)

```
fimul{1}
```

Example

Multiply the integer contents of register ECX by stack element 0, return the product to register ECX.

```
fimul 2(%ecx)
```

Division Instructions

Divide Real (fdiv)

```
fdiv{1s}
```

Example

Divide stack element 0 by stack element 7 and return the result to stack element 0.

```
fdiv %st(7), %st
```

Divide Real and Pop (fdivp)

fdivp

Example

Divide stack element 7 by stack element 0 and return the result to stack element 7, then pop the stack.

```
fdivp %st, %st(7)
```

Divide Real Reversed (fdivr)

fdivr{1s}

Example

Divide stack element 0 by stack element 7 and return the result to stack element 7.

```
fdivr %st, %st(7)
```

Divide Real Reversed and Pop (fdivrp)

fdivrp

Example

Divide stack element 0 by stack element 7 and return the result to stack element 7, then pop the stack.

```
fdivrp %st, %st(7)
```

Integer Divide (fidiv)

fidiv{1}

Example

Divide stack element 0 by the integer contents of register ECX, with an offset of 2, and return the result to register ECX.

```
fidiv 2(%ecx)
```

Integer Divide Reversed (fidivr)

```
fidivr{1}
```

Example

Divide the integer contents of register ECX, with an offset of 2, by stack element 0 and return the result to stack element 0.

```
fidivr 2(%ecx)
```

Floating-Point Opcode Errors



Caution – The IA-32 Assembler generates the wrong object code for some of the floating-point opcodes `fsub`, `fsubr`, `fdiv`, and `fdivr` when there are two floating register operands, and the second op destination is not the zeroth floating-point register. This error has been made in many IA-32 assemblers and would probably cause problems if it were fixed.

Replace the following instructions, in column 1, with their substitutions, in column 2, for IA-32 platforms:

TABLE 2-11 Floating-point Opcodes

<code>fsub %st,%st(n)</code>	<code>fsubr %st, %st(n)</code>
<code>fsubp %st,%st(n)</code>	<code>fsubrp %st, %st(n)</code>
<code>fsub</code>	<code>fsubr</code>
<code>fsubr %st,%st(n)</code>	<code>fsub %st, %st(n)</code>
<code>fsubrp %st,%st(n)</code>	<code>fsubp %st, %st(n)</code>
<code>fsubr</code>	<code>fsub</code>
<code>fdiv %st,%st(n)</code>	<code>fdivr %st,%st(n)</code>

TABLE 2-11 Floating-point Opcodes (Continued)

fsub %st,%st(n)	fsubr %st, %st(n)
fdivp %st,%st(n)	fdivrp %st,%st(n)
fdiv	fdivr
fdivr %st, %st(n)	fdivir %st, %st(n)
fdivrp %st, %st(n)	fdivp %st, %st(n)
fdivr	fdiv

Miscellaneous Arithmetic Operations

Square Root (fsqrt)

fsqrt

Example

Replace stack element 0 with the square root of its value.

fsqrt

Scale (fscale)

fscale

Example

Add the integer value in stack element 1 to the exponent of stack element 0 (multiplication and division by powers of 2).

fscale

Partial Remainder (fprem)

fprem

Example

Divide stack element 0 by stack element 1 and return the (partial) remainder to stack element 0.

fprem

Round to Integer (frndint)

frndint

Example

Round the value in stack element 0 to an integer according to the FPU control word RC field.

frndint

Extract Exponent and Significand (fextract)

fextract

Example

Separate stack element 0 into its exponent and significand and return the exponent to stack element 0, then push the significand onto the FPU stack.

fextract

Absolute Value (fabs)

fabs

Example

Replace stack element 0 with its absolute value.

```
fabs
```

Change Sign (fchs)

```
fchs
```

Example

Replace the sign of stack element 0 with the opposite sign.

```
fchs
```

Comparison Instructions

Compare Real (fcom)

```
fcom{1s}
```

Example

Compare stack element 0 with stack element 7. Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100.

```
fcom %st(7)
```

Compare Real and Pop (fcomp)

```
fcomp{1s}
```

Example

Compare stack element 0 with stack element 7. Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100, then pop the stack.

```
fcomp %st(7)
```

Compare Real and Pop Twice (fcompp)

```
fcompp
```

Example

Compare stack element 0 with stack element 1. Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100, then pop the stack twice.

```
fcompp
```

Integer Compare (ficom)

```
ficom{1}
```

Example

Integer compare stack element 0 with the contents of register ECX (with an offset of 2). Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100,

```
ficom 2(%ecx)
```

Integer Compare and Pop (ficompl)

```
ficompl{1}
```

Example

Integer compare stack element 0 with the contents of register ECX (with an offset of 2). Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100, then pop the stack.

```
ficomp 2(%ecx)
```

Test (ftst)

```
ftst
```

Example

Compare stack element 0 with the value 0.0. Condition codes contain the result: No compare=111, st 0 greater than st 7=000, st 0 less than st 7=001, equal compare=100,

```
ftst
```

Examine (fxam)

```
fxam
```

Example

Report the type of object in stack element 0. FPU flags C3, C2, and C0 return the type:

Unsupported	000
NaN	001
Normal	010
Infinity	011
Zero	100
Empty	101
Denormal	110

```
fxam
```

Transcendental Instructions

Partial Tangent (fptan)

fptan

Example

Replace stack element 0 with its tangent and push a value of 1 onto the FPU stack.

fptan

Partial Arctangent (fpatan)

fpatan

Example

Divide stack element 1 by stack element 0, compute the arctangent and return the result in radians to stack element 1, then pop the stack.

fpatan

$2^x - 1$ (f2xm1)

f2xm1

Example

Replace the contents of stack element 0 (st) with the value of $(2^{\text{st}}-1)$.

f2xm1

$Y * \log_2 X$ (fyl2x)

fyl2x

Example

Compute the logarithm (base-2) of stack element 0 and multiply the result by stack element 1 and return the result to stack element 1, then pop the stack.

`fy12x`

$Y * \log_2 (X+1)$ (`fy12xp1`)

`fy12xp1`

Example

Compute the logarithm (base-2) of stack element 0 plus 1.0 and multiply the result by stack element 1 and return the result to stack element 1, then pop the stack.

`fy12xp1`

Constant Instructions

Load $\log_2 E$ (`f1d12e`)

`f1d12e`

Example

Push $\log_2 e$ onto the FPU stack

`f1d12e`

Load $\log_2 10$ (`f1d12t`)

`f1d12t`

Example

Push $\log_2 10$ onto the FPU stack.

`fldl2t`

Load $\log_{10} 2$ (`fldlg2`)

`fldlg2`

Example

Push $\log_{10} 2$ onto the FPU stack.

`fldlg2`

Load $\log_e 2$ (`fldln2`)

`fldln2`

Example

Push $\log_2 e$ onto the FPU stack.

`fldln2`

Load pi (`fldpi`)

`fldpi`

Example

Push π onto the FPU stack.

`fldpi`

Load + 0 (`fldz`)

`fldz`

Example

Push +0.0 onto the FPU stack.

```
fldz
```

Processor Control Instructions

Initialize Processor (finit, fninit)

```
finitfninit
```

Example

```
finit
```

No Operation (fnop)

```
fnop
```

Example

```
fnop
```

Save State (fsave, fnsave)

```
fsave  
fnsave
```

Example

```
fsave 2(%ecx)
```

Store Control Word (fstcw, fnstcw)

```
fstcw  
fnstcw
```

Example

```
fstcw 2(%ecx)
```

Store Environment (fstenv, fnstenv)

```
fstenv  
fnstenv
```

Example

```
fstenv 2(%ecx)
```

Store Status Word (fstsw, fnstsw)

```
fstsw  
fnstsw
```

Example

```
fstsw %ax
```

Restore State (frstor)

```
frstor
```

Example

```
frstor 2(%ecx)
```

CPU Wait (fwait, wait)

fwait
wait

Example

fwait

Clear Exceptions (fclex, fnclex)

fclex
fnclex

Example

fclex

Decrement Stack Pointer (fdecstp)

fdecstp

Example

fdecstp

Free Registers (ffree)

ffree

Example

ffree %st(7)

Increment Stack Pointer (fincstp)

fincstp

Example

fincstp

Assembler Output

This chapter is an overview of ELF (*Executable and Linking Format*) for the relocatable object files produced by the assembler. The fully detailed definition of ELF appears in the System V Application Binary Interface and the Intel 386 Processor Supplement.

This chapter is organized as follows:

- “Introduction” on page 145
- “Object Files in Executable and Linking Format (ELF)” on page 146

Introduction

The main output produced by assembling an input assembly language source file is the translation of that file into an object file in (ELF). ELF files produced by the assembler are relocatable files that hold code and/or data. They are input files for the linker. The linker combines these relocatable files with other ELF object files to create an executable file or a shared object file in the next stage of program building, after translation from source files into object files.

The three main kinds of ELF files are relocatable, executable and shared object files.

The assembler can also produce ancillary output incidental to the translation process. For example, if the assembler is invoked with the `-V` option, it can write information to standard output and to standard error.

The assembler also creates a default output file when standard input or multiple input files are used. Ancillary output has little direct connection to the translation process, so it is not properly a subject for this manual. Information about such output appears in `as(1)` manual page.

Certain assembly language statements are directives to the assembler regarding the organization or content of the object file to be generated. Therefore, they have a direct effect on the translation performed by the assembler. To understand these directives, described in Chapter 2 it is helpful to have some working knowledge of ELF, at least for relocatable files.

Object Files in Executable and Linking Format (ELF)

Relocatable ELF files produced by the assembler consist of:

- An ELF header
- A section header table
- Sections

The ELF header is always the first part of an ELF file. It is a structure of fixed size and format. The fields, or members, of the structure describe the nature, organization and contents of the rest of the file. The ELF header has a field that specifies the location within the file where the section header table begins.

The section header table is an array of section headers that are structures of fixed size and format. The section headers are the elements of the array, or the entries in the table. The section header table has one entry for each section in the ELF file. However, the table can also have entries (section headers) that do not correspond to any section in the file. Such entries and their array indices are reserved. The members of each section header constitute information useful to the linker about the contents of the corresponding section, if any.

All of a relocatable file's information that does not lie within its ELF header or its section header table lies within its sections. Sections contain most of the information needed to combine relocatable files with other ELF files to produce shared object files or executable files. Sections also contain the material to be combined. For example, sections can hold:

- Relocation tables
- Symbol tables
- String tables

Each section in an ELF file fills a contiguous (possibly empty) sequence of that file's bytes. Sections never overlap. However, the (set theoretic) union of a relocatable ELF header, the section header table, and all the sections can omit some of the bytes. Bytes

of a relocatable file that are not in the ELF header, or in the section header table, or in any of the sections constitute the inactive space. The contents of a file's inactive space, if any, are unspecified.

ELF Header

The ELF *header* is always located at the beginning of the ELF file. It describes the ELF file organization and contains the actual sizes of the object file control structures.

The ELF header consists of the following fields, or members, some have the value 0 for relocatable files:

<code>e_ident</code>	This is a byte array consisting of the <code>EI_NIDENT</code> initial bytes of the ELF header, where <code>EI_NIDENT</code> is a name for 16. The elements of this array mark the file as an ELF object file and provide machine-independent data that can be used to decode and interpret the file's contents.
<code>e_type</code>	Identifies the object file type. A value of 1, that has the name <code>ET_REL</code> , specifies a relocatable file. Table 3-1 describes all the object file types.
<code>e_machine</code>	Specifies the required architecture for an individual file. A value of 3, that has the name <code>EM_386</code> , specifies Intel 80386. <code>EM_486</code> , specifies Intel 80486.
<code>e_version</code>	Identifies the version of this object file's format. This field should have the current version number, named <code>EV_CURRENT</code> .
<code>e_entry</code>	Virtual address where the process is to start. A value of 0 indicates no associated entry point.
<code>e_phoff</code>	Program header table's file offset, in bytes. The value of 0 indicates no program header. (Relocatable files do not need a program header table.)
<code>e_shoff</code>	Section header table's file offset, in bytes. The value of 0 indicates no section header table. (Relocatable files must have a section header table.)
<code>e_flag</code>	Processor-specific flags associated with the file. For the Intel 80386, this field has value 0.
<code>e_ehsize</code>	ELF header's size, in bytes.
<code>e_phentsize</code>	Size, in bytes, of entries in the program header table. All entries are the same size. (Relocatable files do not need a program header table.)

e_phnum	Number of entries in program header table. A value of 0 indicates the file has no program header table. (Relocatable files do not need a program header table.)
e_shentsize	Size, in bytes, of the section header structure. A section header is one entry in the section header table; all entries are the same size.
e_shnum	Number of entries in section header table. A value of 0 indicates the file has no section header table. (Relocatable files must have a section header table.)
e_shstrndx	Section header table index of the entry associated with the section name string table. A value of SHN_UNDEF indicates the file does not have a section name string table.

TABLE 3-1 Object File Types

Type	Value	Description
none	0	No file type
rel	1	Relocatable file
exec	2	Executable file
dyn	3	Shared object file
core	4	Core file
loproc	0xff00	Processor-specific
hiproc	0xffff	Processor-specific

Section Header

The section header table has all of the information necessary to locate and isolate each of the file's sections. A section header entry in a section header table contains information characterizing the contents of the corresponding section, if the file has such a section.

Each entry in the section header table is a section header. A section header is a structure of fixed size and format, consisting of the following fields, or members:

sh_name	Specifies the section name. The value of this field is an index into the section header string table section, wherein it indicates the beginning of a null-terminated string that names the section.
sh_type	Categorizes the section's contents and semantics. Table 3-3 describes the section types.

<code>sh_flags</code>	One-bit descriptions of section attributes. Table 3-2 describes the section attribute flags.
<code>sh_addr</code>	Address where the first byte resides if the section appears in the memory image of a process; a value of 0 indicates the section does not appear in the memory image of a process.
<code>sh_offset</code>	Specifies the byte offset from the beginning of the file to the first byte in the section.
	<hr/> Note – If the section type is <code>SHT_NOBITS</code> , the corresponding section occupies no space in the file. In this case, <code>sh_offset</code> specifies the location at which the section would have begun if it did occupy space within the file. <hr/>
<code>sh_size</code>	Specifies the size, in byte units, of the section.
	<hr/> Note – Even if the section type is <code>SHT_NOBITS</code> , <code>sh_size</code> can be nonzero; however, the corresponding section still occupies no space in the file. <hr/>
<code>sh_link</code>	Section header table index link. The interpretation of this information depends on the section type, as described in Table 3-3.
<code>sh_info</code>	Extra information. The interpretation of this information depends on the section type, as described in Table 3-3.
<code>sh_addralign</code>	If a section has an address alignment constraint, the value in this field is the modulus, in byte units, by which the value of <code>sh_addr</code> must be congruent to 0; i.e., $sh_addr = 0 \pmod{sh_addralign}$. For example, if a section contains a long (32 bits), the entire section must be ensured long alignment, so <code>sh_addralign</code> has the value 4. Only 0 and positive integral powers of 2 are currently allowed as values for this field. A value of 0 or 1 indicates no address alignment constraints.
<code>sh_entsize</code>	Size, in byte units, for entries in a section that is a table of fixed-size entries, such as a symbol table. Has the value 0 if the section is not a table of fixed-size entries

TABLE 3-2 Section Attribute Flags

Flag	Default Value	Description
<code>SHF_WRITE</code>	0x1	Contains data that is writable during process execution.

TABLE 3-2 Section Attribute Flags (Continued)

Flag	Default Value	Description
SHF_ALLOC	0x2	Occupies memory during process execution. This attribute is <i>off</i> if a control section does not reside in the memory image of the object file.
SHF_EXECINSTR	0x4	Contains executable machine instructions.
SHF_MASKPROC	0xf0000000	Reserved for processor-specific semantics.

TABLE 3-3 Section Types

Name	Value	Description	Interpretation by	
			sh_info	sh_link
SHT_NULL	0	Marks section header as inactive; file has no corresponding section.	0	SHN_UNDEF
SHT_PROGBITS	1	Contains information defined by the program, and in a format and with a meaning determined solely by the program.	0	SHN_UNDEF
SHT_SYMTAB	2	Is a complete symbol table, usually for link editing. This table can also be used for dynamic linking; however, it can contain many unnecessary symbols. Note: Only one section of this type is allowed in a file	One greater than the symbol table index of the last local symbol.	The section header index of the associated string table.
SHT_STRTAB	3	Is a string table. A file can have multiple string table sections.	0	SHN_UNDEF
SHT_RELA	4	Contains relocation entries with explicit addends. A file can have multiple relocation sections.	The section header index of the section to where the relocation applies.	The section header index of the associated symbol table.
SHT_HASH	5	Is a symbol rehash table. Note: Only one section of this type is allowed in a file	0	The section header index of the symbol table to which the hash table applies.

TABLE 3-3 Section Types (Continued)

Name	Value	Description	Interpretation by	
			sh_info	sh_link
SHT_DYNAMIC	6	Contains dynamic linking information. Note: Only one section of this type is allowed in a file	0	The section header index of the string table used by entries in the section.
SHT_NOTE	7	Contains information that marks the file.	0	SHN_UNDEF
SHT_NOBITS	8	Contains information defined by the program, and in a format and with a meaning determined by the program. However, a section of this type occupies no space in the file, but the section header's <i>offset</i> field specifies the location at which the section would have begun if it did occupy space within the file.	0	SHN_UNDEF
SHT_REL	9	Contains relocation entries without explicit addends. A file can have multiple relocation sections.	The section header index of the section to where the relocation applies.	The section header index of the associated symbol table.
SHT_SHLIB	10	Reserved.	0	SHN_UNDEF
SHT_DYNSYM	11	Is a symbol table with a minimal set of symbols for dynamic linking. Note: Only one section of this type is allowed in a file	One greater than the symbol table index of the last local symbol.	The section header index of the associated string table.
SHT_LOPROC	0x70000000	Lower and upper bounds of range of section types reserved for processor-specific semantics.	0	SHN_UNDEF
SHT_HIPROC	0x7fffffff			
SHT_LOUSER	0x80000000	Lower and upper bounds of range of section types reserved for application programs. Note: Section types in this range can be used by an application without conflicting with system-defined section types.	0	SHN_UNDEF
SHT_HIUSER	0xffffffff			

Note – Some section header table indices are reserved, and the object file does not contain sections for these special indices.

Sections

A section is the smallest unit of an object file that can be relocated. Sections containing the following material usually appear in relocatable ELF files:

- Executable text
- Read-only data
- Read-write data
- Read-write uninitialized data (only *section header* appears)

Sections do not need to occur in any particular order within the object file. The sections of a relocatable ELF file contain all of the file information that is not contained in the ELF header or in the section header table. The sections in any ELF file must satisfy several conditions:

1. Every section in the file must have one section header entry in the section header table to describe the section. However, the section header table can have section header entries that correspond to no section in the file.
2. Each section occupies one contiguous sequence of bytes within a file. The section can be empty (even so, its section header entry in the section header table can have a nonzero value for the field `sh_size`).
3. A byte in a file can reside in at most one section. Sections in a file cannot overlap.
4. An object file can have inactive space. Inactive space is the set of all bytes in the file that are not part of the ELF header, the section header table, the program header table (for executable files), or of any section in the file. The contents of the inactive space are unspecified.

Sections can be added for multiple text or data segments, shared data, user-defined sections, or information in the object file for debugging.

Note – Not all of the sections where there are entries in the file section header table need to be present.

Predefined Sections

Sections having certain names beginning with "." (dot) are predefined, with their types and attributes already assigned. These special sections are of two kinds: predefined user sections and predefined nonuser sections.

Predefined User Sections

Sections that an assembly language programmer can manipulate by issuing section control directives in the source file are *user sections*. The predefined user sections are those predefined sections that are also user sections.

Table 3–4 lists the names of the predefined user sections and briefly describes each.

TABLE 3–4 Predefined User Sections

Section Name	Description
".bss"	Uninitialized read-write data.
".comment"	Version control information.
".data" & ".data1"	Initialized read-write data.
".debug"	Debugging information.
".fini"	Runtime finalization instructions.
".init"	Runtime initialization instructions.
".rodata" & ".rodata1"	Read-only data.
".text"	Executable instructions.
".line"	Line # info for symbolic debugging.
".note"	Special information from vendors or system builders.

Predefined Non-User Sections

Table 3–5 shows the predefined sections that are not user sections, because assembly language programmers cannot manipulate them by issuing section control directives in the source file.

TABLE 3–5 Predefined Non-user Sections

Section Name	Description
".dynamic"	Dynamic linking information.
".dynstr"	Strings needed for dynamic linking.
".dysym"	Dynamic linking symbol table.
".got"	Global offset table.
".hash"	A symbol hash table.
".interp"	The path name of a program interpreter.

TABLE 3-5 Predefined Non-user Sections (Continued)

Section Name	Description
".plt"	The procedure linking table.
".relname" & ".relaname"	Relocation information. name is the section to which the relocations apply. e.g., ".rel.text", ".rela.text".
".shstrtab"	String table for the section header table names.
".strtab"	The string table.
".symtab"	The symbol table.

Relocation Tables

Locations represent *addresses in memory* if a section is allocatable; that is, its contents are to be placed in memory at program runtime. Symbolic references to these locations must be changed to addresses by the link editor.

The assembler produces a companion *relocation table* for each relocatable section. The table contains a list of relocations (that is, adjustments to locations in the section) to be performed by the link editor.

Symbol Tables

The *symbol table* contains information to locate and relocate symbolic definitions and references. The assembler creates the symbol table section for the object file. It makes an entry in the symbol table for each symbol that is defined or referenced in the input file and is needed during linking.

The symbol table is then used by the link editor during relocation. The symbol table's section header contains the symbol table index for the first non-local symbol.

The symbol table contains the following information:

st_name	Index into the object file symbol string table. A value of zero indicates the corresponding entry in the symbol table has no name; otherwise, the value represents the string table index that gives the symbol name.
st_value	Value of the associated symbol. This value is dependent on the context; for example, it can be an address, or it can be an absolute value.
st_size	Size of symbol. A value of 0 indicates that the symbol has either no size or an unknown size.
st_info	Specifies the symbol type and binding attributes. Table 3-6 and Table 3-7 describe the symbol types and binding attributes.

st_other	Undefined meaning. Current value is 0.
st_shndx	Contains the section header table index to another relevant section, if specified. As a section moves during relocation, references to the symbol continue to point to the same location because the value of the symbol changes as well.

TABLE 3-6 Symbol Types

Value	Type	Description
0	notype	Type not specified.
1	object	<i>Symbol</i> is associated with a data object; for example, a variable or an array.
2	func	<i>Symbol</i> is associated with a function or other executable code. When another object file references a function from a shared object, the link editor automatically creates a procedure linkage table entry for the referenced symbol.
3	section	<i>Symbol</i> is associated with a section. These types of symbols are primarily used for relocation.
4	file	Gives the name of the source file associated with the object file.
13	loproc	Values reserved for processor-specific semantics.
15	hiproc	

TABLE 3-7 Binding Attributes

Value	Binding	Description
0	local	<i>Symbol</i> is defined in the object file and not accessible in other files. Local symbols of the same name can exist in multiple files.
1	global	<i>Symbol</i> is either defined externally or defined in the object file and accessible in other files.
2	weak	<i>Symbol</i> is either defined externally or defined in the object file and accessible in other files; however, these definitions have a lower precedence than globally defined symbols.
13	loproc	Values reserved for processor-specific semantics.
15	hiproc	

String Tables

A *string table* is a section which contains null-terminated variable-length character sequences, or strings. The object file uses these strings to represent symbol names and file names. The strings are referenced by indices into the string table section. The first and last bytes of a string table must be the null character.

- A string table index can refer to any byte in the section.

- Empty string table sections are permitted if zero is the value of `sh_size` in the section header entry for the string table in the section header table.

A string can appear multiple times and can also be referenced multiple times. References to substrings can exist, and unreferenced strings are allowed.

Attribute Expression

Attribute expressions are used to generate entries of relocation table. The form of the attribute expression is:

```
symbol-name@attribute
```

Attributes begin with the @ sign followed by a reserved identifier. Table 3-8 describes the identifier attributes used in the IA-32 assembler.

TABLE 3-8 Identifier Attributes

Attribute	Description	Relocation Table Entry Generated
@GOT	Address of the Global Offset Table (GOT) entry for the identifier	R_386_GOT32
@GOTOFF	The difference between a symbol's value and the Global Offset Table (GOT).	R_386_GOTOFF
@PLT	Address of a function's Procedure Linkage Table (PLT) entry	R_386_PLT32

Note – To obtain correct position-independent code, conform to the IA-32 architecture and the System V ABI.

The special symbol `_GLOBAL_OFFSET_TABLE_` can be used in the IA-32 assembler for building of position-independent code.

Using the Assembler Command Line

This chapter describes how to invoke the assembler and use the command-line options.

This chapter is organized as follows:

- “Assembler Command Line” on page 157
- “Assembler Command Line Options” on page 158
- “Disassembling Object Code” on page 159

Assembler Command Line

Invoke the assembler command line as follows:

```
as [options] [inputfile] ...
```

Note – The language drivers (such as *cc* and *f77*) invoke the assembler command line with the *fbe* command. You can use either the *as* or *fbe* command to invoke the assembler command line.

The *as* command translates the assembly language source files, *inputfile*, into an executable object file, *objfile*. The assembler recognizes the file name argument *hyphen* (-) as the standard input. It accepts more than one file name on the command line. The input file is the concatenation of all the specified files. If an invalid option is given or the command line contains a syntax error, the assembler prints the error (including a synopsis of the command line syntax and options) to standard error output, and then terminates.

The assembler supports `#define` macros, `#include` files, and symbolic substitution through use of the C preprocessor `cpp`. The assembler invokes the preprocessor before assembly begins if it has been specified from the command line as an option. (See the `-P` option.)

Assembler Command Line Options

<code>-b</code>	Enable Sun SourceBrowser.
<code>-Dname</code> <code>-Dname=def</code>	When the <code>-P</code> option is in effect, these options are passed to the <code>cpp</code> preprocessor without interpretation by the <code>as</code> command; otherwise, they are ignored.
<code>-Ipath</code>	When the <code>-P</code> option is in effect, this option is passed to the <code>cpp</code> preprocessor without interpretation by the <code>as</code> command; otherwise, it is ignored.
<code>-K {pic.PIC}</code>	Generate position-independent code.
<code>-L</code>	Save all symbols, including temporary labels that are normally discarded to save space, in the ELF symbol table.
<code>-m</code>	This new option runs <code>m4</code> macro preprocessing on input. The <code>m4</code> preprocessor is more powerful than the C preprocessor (invoked by the <code>-P</code> option), so it is more useful for complex preprocessing. See the <code>m4(1)</code> for a detailed description of the <code>m4</code> macro-processor.
<code>-o outfile</code>	Takes the next argument as the name of the output file to be produced. By default, the <code>.s</code> suffix, if present, is removed from the input file and the <code>.o</code> suffix is appended to form the output file name.
<code>-P</code>	Run <code>cpp</code> , the C preprocessor, on the files being assembled. The preprocessor is run separately on each input file, not on their concatenation. The preprocessor output is passed to the assembler.
<code>-Q[y n]</code>	This new option produces the “assembler version” information in the comment section of the output object file if the <code>y</code> option is specified; if the <code>n</code> option is specified, the information is suppressed.
<code>-s</code>	This new option places all stabs in the <code>.stabs</code> section. By default, stabs are placed in <code>.stabs.excl</code> sections, that are stripped out by the static linker <code>ld</code> during final execution. When the <code>-s</code> option is used, stabs remain in the final executable because <code>.stab</code> sections are not stripped out by the static linker <code>ld</code> .

- S Produce a disassembly of the emitted code to the standard output.
[[aAbBcClL]] Adding the character to the S option:
- a - disassembling with address
 - b - disassembling with '.bof'
 - c - disassembling with comments (default)
 - l - disassembling with line numbers
- Capital letters turn switch off for corresponding option
- T This is a migration option for 4.1 assembly files to be assembled on 5.0 systems. With this option, the symbol names in 4.1 assembly files will be interpreted as 5.0 symbol names.
- U*name* When the -P option is in effect, this option is passed to the *cpp* preprocessor without interpretation by the *as* command; otherwise, it is ignored.
- V This option writes the version information on the standard error output.
- xF Generates additional information for performance analysis of the executable using WorkShop (SPARCworks) analyzer. If the input file does not contain any stabs (debugging directives), then the assembler will generate some default stabs which are needed by the SPARCworks analyzer.

Disassembling Object Code

The `dis` program is the object code disassembler for ELF. It produces an assembly language listing of the object file. For detailed information about this function, see the `dis(1)` manual page.

Index

A

- addresses, 154
- addressing mode
 - base and index, 25
 - offset, 25
 - scale, 25
 - segment register, 25
- as command, 157
- assembler (as)
 - addition instructions, 125, 126
 - arithmetic logical instructions, 48, 61
 - bit instructions, 98, 101
 - byte instructions, 116, 117
 - comparison instructions, 134, 136
 - constant instructions, 138, 139
 - conversion instructions, 67, 68
 - coprocessor instructions, 73
 - decimal arithmetic instructions, 69, 72
 - division instructions, 129, 131
 - exchange instructions, 102, 117, 118
 - expressions, 20, 26
 - flag instructions, 42, 47
 - floating point comparison instructions, 105, 106
 - floating point constant instructions, 103
 - floating point opcode errors, 131
 - floating point transcendental instructions, 102, 103
 - immediate values, 26
 - input format, 16, 17
 - instruction descriptions, 25, 36
 - addressing modes, 25, 26
- assembler (as) (*continued*)
 - instructions
 - addition, 125, 126
 - arithmetic logical, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61
 - arithmetic/logical, 48
 - bit, 98, 99, 100, 101
 - byte, 116, 117
 - comparison, 134, 135, 136
 - constant, 138, 139
 - conversion, 67, 68
 - coprocessor, 73
 - decimal arithmetic, 69, 70, 71, 72
 - division, 129, 130, 131
 - exchange, 102, 117, 118
 - flag, 42, 43, 44, 45, 46, 47
 - floating point comparison, 105, 106
 - floating point constant, 103
 - floating point transcendental, 102, 103
 - integer transfer, 124
 - interrupt, 87, 88
 - I/O, 40, 41
 - jump, 84, 85, 86
 - load and move, 106, 107, 108, 109, 110
 - load full pointer, 37
 - miscellaneous, 119, 120, 121
 - miscellaneous arithmetic operations, 132, 133, 134
 - miscellaneous floating point, 104
 - multiply, 128, 129
 - multiply and divide, 62, 64, 65, 66
 - packed decimal transfer, 125

assembler (as), instructions (*continued*)

- pop, 111
- pop stack into word, 38
- procedure call, 79
- procedure call and return, 79, 80, 81, 82, 83, 84
- processor control, 140, 141, 142
- processor control floating point, 104
- protection model, 89, 90, 91, 92, 93, 94, 95, 96, 97
- push, 112
- push stack into word, 39
- real transfer, 122, 123
- return, 79
- rotate, 112, 113, 114, 115
- string, 73, 74, 75, 76, 77, 78, 79
- subtraction, 126, 127, 128
- transcendental, 137, 138

integer transfer instructions, 124

interrupt instructions, 87, 88

I/O instructions, 40

jump instructions, 84, 86

load and move instructions, 106, 110

miscellaneous arithmetic operations, 132, 134

miscellaneous instructions, 119, 121

mnemonics

- addition, 125
- arithmetic, 132

multiplication instructions, 128, 129

multiply and divide instructions, 62, 66

object file

- .comment section, 19

operands

- immediate, 23
- memory, 23
- overview, 23
- register, 23

operations, dbx pseudo, 31

operations, general pseudo, 26, 29

operators, 20

other floating point instructions, 104

packed decimal transfer instructions, 125

pop instructions, 111

procedure call and return instructions, 79, 84

assembler (as), operands (*continued*)

- process control floating point instructions, 104
- processor control instructions, 140, 142
- protection model instructions, 89, 97
- push instructions, 112
- real transfer instructions, 122, 123
- rotate instructions, 112, 115
- segment register instructions, 37, 39

statements

- assignment, 17
- empty, 17
- machine operation, 17
- modifying, 17
- pseudo operation, 17

string instructions, 73, 79

subtraction instructions, 126, 128

SunOS vs. Intel, mnemonics, 34, 142

- notational conventions, 34

symbols, 18

syntax rules, 20, 22

transcendental instructions, 137, 138

types, 18, 19

values, 18, 19

assembler command line, 157

assembler command line options, 158

assembly language, 15

C

cc language driver, 157

command line options

- , 158
- D, 158
- I, 158
- o, 158
- P, 158
- Q, 158
- s, 158
- U, 159
- V, 159

D

default output file, 145

dis program, 159
disassembling object code, 159

E

ELF header

e_ehsize, 147
e_entry, 147
e_flag, 147
e_ident, 147
e_machine, 147
e_phentsize, 147
e_phnum, 148
e_phoff, 147
e_shentsize, 148
e_shnum, 148
e_shoff, 147
e_shstrndx, 148
e_type, 147
e_version, 147

ELF section, 152

predefined non-user section, 153
predefined user section, 153

ELF section header

sh_addr, 149
sh_addralign, 149
sh_entsize, 149
sh_flags, 149
sh_info, 149
sh_link, 149
sh_name, 148
sh_offset, 149
sh_size, 149
sh_type, 148

ELF string table, 155

ELF symbol table, 154

st_info, 154
st_name, 154
st_other, 155
st_shndx, 155
st_size, 154
st_value, 154

expression

absolute, 22
relocatable, 22

F

f77 language driver, 157
fbe command, 157
.file, 27

G

.globl, 27

H

hyphen (-), 157

I

-I option, 158

instructions

addition

fadd(), 125
faddp(), 126
fiadd(), 126

arithmetic logical

adc(), 49
add(), 48
and(), 59
bound(), 59
cmp(), 51
dec(), 53
inc(), 52
neg(), 58
not(), 57
or(), 60
sal(), 54
sar(), 54
sbb(), 50
shl(), 54
shld(), 55
shr(), 54
shrd(), 56
sub(), 49
test(), 53
xor(), 61

bit

bsf(), 98

instructions, bit (*continued*)

- bsr(), 99
- bt(), 99
- btc(), 100
- btr(), 100
- bts(), 101
- byte
 - bswap(), 117
 - setcc(), 116
- comparison
 - fcom(), 134
 - fcomp(), 134
 - fcompp(), 135
 - ficom(), 135
 - ficompp(), 135
 - ftst(), 136
 - fxam(), 136
- constant
 - fldl2e(), 138
 - fldl2t(), 138
 - fldlg2(), 139
 - fldln2(), 139
 - fldpi(), 139
 - fldz(), 139
- conversion
 - cbtw(), 67
 - cltd(), 68
 - cwtd(), 68
 - cwtl(), 67
- coprocessor
 - fwait(), 73
 - wait(), 73
- decimal arithmetic
 - aaa(), 70
 - aad(), 72
 - aam(), 71
 - aas(), 71
 - daa(), 69
 - das(), 69
- division
 - fdiv(), 129
 - fdivr(), 130
 - fdivrp(), 130
 - fidiv(), 130
 - fidivr(), 131
- exchange
 - cmpxchg(), 102

instructions, exchange (*continued*)

- xadd(), 117
- xchg(), 118
- flag
 - clc(), 45
 - cld(), 46
 - cli(), 45
 - cmc(), 44
 - lahf(), 42
 - popf(), 43
 - pushf(), 44
 - sahf(), 43
 - stc(), 45
 - std(), 47
 - sti(), 46
- floating point comparison
 - fucom(), 105
 - fucomp(), 105
 - fucompp()', 106
- floating point constant
 - fld1(), 103
 - fld12+(), 103
 - fld12e(), 103
 - fldlg2(), 103
 - fldln2(), 103
 - fldpi(), 103
 - fldz(), 103
- floating point transcendental
 - fcos(), 102
 - fs(), 103
 - fsin(), 102
- integer transfer
 - fild(), 124
 - fist(), 124
 - fistp(), 124
- interrupt
 - int(), 87
 - into(), 87
 - iret(), 88
- I/O
 - in(), 40
 - ins(), 40
 - out(), 41
 - outs(), 41
- jump
 - jcc(), 86
 - jcxz(), 84

instructions, jump (*continued*)

- jmp(), 86
- ljmp(), 86
- loop(), 85
- loope(), 85
- loopne(), 85
- loopnz(), 85
- loopz(), 85
- load and move
 - lea(), 106
 - mov(), 107, 108, 109
 - movsb(), 110
 - movsbl(), 110
 - movw(), 108
 - movzwl(), 110
- load full pointer
 - lds(), 37
 - les(), 37
 - lfs(), 37
 - lgs(), 37
 - lss(), 37
- miscellaneous
 - hlt(), 121
 - invd(), 119
 - invlp(), 119
 - lock(), 120
 - nop(), 121
 - wbinvd(), 119
- miscellaneous arithmetic o, 133
- miscellaneous arithmetic ope, 133
- miscellaneous arithmetic oper, 133, 134
- miscellaneous arithmetic operations, 132
- miscellaneous floating point
 - fprem, 104
- multiply
 - fimul(), 129
 - fmul(), 128
 - fmulp(), 129
- multiply and divide
 - div(), 65
 - idiv(), 66
 - imul(), 62
 - imulb(), 62
 - mul(), 64
- packed decimal transfer
 - fbld(), 125
 - fbst(), 125

instructions, packed decimal transfer (*continued*)

- pop
 - popa(), 111
 - pop stack into word
 - pop(), 38
- procedure call and return
 - call(), 80
 - enter(), 83
 - lcall(), 79
 - leave(), 84
 - lret(), 82
 - ret(), 81
- processor control
 - fclex(), 142
 - fdecstp(), 142
 - ffree(), 142
 - fincstp(), 142
 - finit(), 140
 - fnclx(), 142
 - fninit(), 140
 - fnop(), 140
 - fnsave(), 140
 - fnstcw(), 141
 - fnstenv(), 141
 - fnstsw(), 141
 - frstor(), 141
 - fsave(), 140
 - fstcw(), 141
 - fstenv(), 141
 - fstsw(), 141
 - wait(), 142
- processor control floating point, 104
- protection model
 - arpl(), 97
 - lar(), 95
 - lgdt(), 93
 - lidt(), 93
 - lldt(), 90
 - lmsw(), 95
 - lsl(), 96
 - ltr(), 91
 - sgdt(), 92
 - sidt(), 92
 - sldt(), 89
 - smsw(), 94
 - str(), 90
 - verr(), 91

instructions, protection model (*continued*)

- verw(), 91
- push
 - pusha(), 112
- push stack into word
 - push(), 39
- real transfer
 - fld(), 122
 - fst(), 122
 - fstp(), 123
 - fxch(), 123
- rotate
 - rcl(), 112
 - rcr(), 113
 - rol(), 114
 - ror(), 115
- string
 - cmps(), 74
 - lods(), 76
 - movs(), 74
 - rep(), 79
 - repnz(), 79
 - repz(), 79
 - scas(), 77
 - stos(), 75
 - xlat(), 78
- subtraction
 - fisubr(), 128
 - fisubrp(), 128
 - fsub(), 126
 - fsubr(), 127
 - fsubrp(), 127
 - subp(), 127
- transcendental
 - f2xm1(), 137
 - fptan(), 137
 - fyl2x(), 137
 - fyl2xp1(), 138

invoking, as command, 157

L

language drivers, 157
.local, 28

M

-m option, 158
machine instruction syntax, 22, 23

- derived type information, 23
- destination operand, 23
- register name, 22
- source operand, 23

multiple files, on as command line, 157
multiple sections, 152
multiple strings, in string table, 156

N

.nonvolatile, 28
notational conventions

- condition codes, 36
- control register, 35
- distance of relative jump, 36
- immediate pointer, 36
- immediate value, 35
- memory operand, 35

O

operands

- byte register, 23

operations, general pseudo, 26

- .align val, 26
- .bcd val, 26
- .bss, 27
- .bss tag, bytes, 27
- .byte val, 27
- .comm name, expr, 27
- .data, 27
- .double val, 27
- .even, 27

options

- command line, 158

P

-P option, 158
predefined non-user sections, 153
predefined user sections, 153

Programming Utilities - SunOS 5.0, 12
pseudo-operations, 26

Q

-Q option, 158

R

relocatable files, 145
relocation tables, 154

S

-s option, 158
.section, 28
section header, 148
sections, 152
statements
 append comment, 17
 assignment, 17
 empty, 17
 label prefix, 17
 machine operation, 17
 pseudo operation, 17
string tables, 155
strings
 multiple references in string table, 156
 unreferenced in string table, 156
strings, multiple in string table, 156
sub-strings in string table
 references to, 156
symbol, 30
symbol, reserved
 .bss, 18
 .data, 18
 .fini, 18
 .init, 18
 .text, 18
symbol tables, 154
symbol types
 absolute, 18
 attribute, 19
 bss, 19

symbol types (*continued*)
 data, 19
 object file sections, 19
 text, 19
 undefined, 18

U

-U option, 159

V

-V option, 159
.volatile, 29

W

.weak, 29

