

TradingXpert Installation Guide

Sun™ ONE Integration Server, B2B

Version 3.6.2

816-6721-10
March 2003

Sun Microsystems, Inc.
4150 Network Circle
Santa Clara, CA 95054 U.S.A.

Copyright © 2003 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, U.S.A. All rights reserved.U.S.

Government Rights - Commercial software. Government users are subject to the Sun Microsystems, Inc. standard license agreement and applicable provisions of the FAR and its supplements.

Parts of the product may be derived from Berkeley BSD systems, licensed from the University of California.

UNIX is a registered trademark in the U.S. and in other countries, exclusively licensed through X/Open Company, Ltd.

Sun, Sun Microsystems, the Sun logo, Java, Solaris, Sun[tm] ONE and the Sun[tm] ONE logo are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.

All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. in the U.S. and other countries. Products bearing SPARC trademarks are based upon architecture developed by Sun Microsystems, Inc.

Products covered by and information contained in this service manual are controlled by U.S. Export Control laws and may be subject to the export or import laws in other countries. Nuclear, missile, chemical biological weapons or nuclear maritime end uses or end users, whether direct or indirect, are strictly prohibited. Export or reexport to countries subject to U.S. embargo or to entities identified on U.S. export exclusion lists, including, but not limited to, the denied persons and specially designated nationals lists is strictly prohibited.

DOCUMENTATION IS PROVIDED "AS IS" AND ALL EXPRESS OR IMPLIED CONDITIONS, REPRESENTATIONS AND WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT, ARE DISCLAIMED, EXCEPT TO THE EXTENT THAT SUCH DISCLAIMERS ARE HELD TO BE LEGALLY INVALID.

Copyright © 2003 Sun Microsystems, Inc., 4150 Network Circle, Santa Clara, California 95054, Etats-Unis. Tous droits réservés.

Droits du gouvernement américain, utilisateurs gouvernementaux - logiciel commercial. Les utilisateurs gouvernementaux sont soumis au contrat de licence standard de Sun Microsystems, Inc., ainsi qu'aux dispositions en vigueur de la FAR (Federal Acquisition Regulations) et des suppléments à celles-ci.

Des parties de ce produit pourront être dérivées des systèmes Berkeley BSD licenciés par l'Université de Californie.

UNIX est une marque déposée aux Etats-Unis et dans d'autres pays et licenciée exclusivement par X/Open Company, Ltd.

Sun, Sun Microsystems, le logo Sun, Java, Solaris, Sun[tm] ONE et le logo Sun[tm] ONE sont des marques de fabrique ou des marques déposées de Sun Microsystems, Inc. aux Etats-Unis et dans d'autres pays.

Toutes les marques SPARC sont utilisées sous licence et sont des marques de fabrique ou des marques déposées de SPARC International, Inc. aux Etats-Unis et dans d'autres pays. Les produits portant les marques SPARC sont basés sur une architecture développée par Sun Microsystems, Inc.

Les produits qui font l'objet de ce manuel d'entretien et les informations qu'il contient sont régis par la législation américaine en matière de contrôle des exportations et peuvent être soumis au droit d'autres pays dans le domaine des exportations et importations. Les utilisations finales, ou utilisateurs finaux, pour des armes nucléaires, des missiles, des armes biologiques et chimiques ou du nucléaire maritime, directement ou indirectement, sont strictement interdites. Les exportations ou réexportations vers des pays sous embargo des États-Unis, ou vers des entités figurant sur les listes d'exclusion d'exportation américaines, y compris, mais de manière non exclusive, la liste de personnes qui font objet d'un ordre de ne pas participer, d'une façon directe ou indirecte, aux exportations des produits ou des services qui sont régi par la législation américaine en matière de contrôle des exportations et la liste de ressortissants spécifiquement désignés, sont rigoureusement interdites.

LA DOCUMENTATION EST FOURNIE "EN L'ÉTAT" ET TOUTES AUTRES CONDITIONS, DECLARATIONS ET GARANTIES EXPRESSES OU TACITES SONT FORMELLEMENT EXCLUES, DANS LA MESURE AUTORISÉE PAR LA LOI APPLICABLE, Y COMPRIS NOTAMMENT TOUTE GARANTIE IMPLICITE RELATIVE A LA QUALITE MARCHANDE, A L'APTITUDE A UNE UTILISATION PARTICULIERE OU A L'ABSENCE DE CONTREFAÇON.

Contents

| | |
|--|-----------|
| List of Figures | 7 |
| List of Tables | 9 |
| List of Procedures | 11 |
| Preface | 13 |
| Audience for This Guide | 13 |
| Organization of This Guide | 14 |
| Conventions | 14 |
| Text Conventions | 14 |
| Directory Variable Conventions | 15 |
| Other Documentation Resources | 17 |
| The TradingXpert Documentation Set | 17 |
| | |
| Chapter 1 Introduction | 19 |
| TradingXpert Software Dependencies | 19 |
| TradingXpert/ECXpert Configurations | 22 |
| About the TradingXpert Installer | 23 |
| Installer Dependencies | 23 |
| What the TradingXpert Installer Does | 23 |
| Application Server 6.5 Environment | 23 |
| Application Server 7.0 Environment | 24 |
| Installed TradingXpert Software | 25 |
| TradingXpert Software Modules | 25 |
| Installed Directory Structure | 25 |
| TradingXpert Directory Structure: Application Server 6.5 | 26 |
| TradingXpert Directory Structure: Application Server 7.0 | 28 |
| Upgrading to Version 3.6.2 | 30 |

| | |
|--|-----------|
| Chapter 2 Solaris Installation | 31 |
| Hardware and Software Requirements | 31 |
| Installing TradingXpert in a Sun ONE Application Server 6.5 Environment | 32 |
| Pre-Installation Tasks (Application Server 6.5) | 32 |
| Checking the BDGHOME Environment Variable | 33 |
| Creating a Web Server Instance for TradingXpert | 33 |
| Installation Procedures (Application Server 6.5) | 34 |
| Configuration Tasks (Application Server 6.5) | 35 |
| Editing the TradingXpert Configuration File | 35 |
| Copying TradingXpert Map Files to ECXpert | 37 |
| Configuring TradingXpert to Run on a Different Machine from ECXpert | 37 |
| Installing TradingXpert in a Sun ONE Application Server 7.0 Environment | 40 |
| Pre-Installation Tasks (Application Server 7.0) | 41 |
| Creating an Application Server Instance for TradingXpert | 41 |
| Modifying the server.policy File | 42 |
| Installation Procedures (Application Server 7.0) | 43 |
| Configuration Tasks (Application Server 7.0) | 44 |
| | |
| Chapter 3 Windows Installation | 45 |
| Hardware and Software Requirements | 45 |
| Installing TradingXpert in a Sun ONE Application Server 6.5 Environment | 46 |
| Pre-Installation Tasks (Application Server 6.5) | 46 |
| Checking the BDGHOME Environment Variable | 47 |
| Creating a Web Server Instance for TradingXpert | 48 |
| Installation Procedures (Application Server 6.5) | 48 |
| Configuration Tasks (Application Server 6.5) | 49 |
| Editing the TradingXpert Configuration File | 50 |
| Modifying the Application Server Classpath Variable | 52 |
| Setting the URL Prefix for TradingXpert | 52 |
| Copying TradingXpert Map Files to ECXpert | 53 |
| Configuring TradingXpert to Run on a Different Machine from ECXpert | 54 |
| Installing TradingXpert in a Sun ONE Application Server 7.0 Environment | 58 |
| Pre-Installation Tasks (Application Server 7.0) | 59 |
| Creating an Application Server Instance for TradingXpert | 59 |
| Modifying the server.policy File | 60 |
| Installation Procedures (Application Server 7.0) | 61 |
| Deploying the TradingXpert Archive (TX.war) | 62 |
| Configuration Tasks (Application Server 7.0) | 63 |

| | |
|--|-----------|
| Chapter 4 Testing Your TradingXpert Installation | 65 |
| Setting Up ECXpert for the Test Scenario | 66 |
| Setting up ECXpert Manually | 67 |
| Exchange A: <i>TXhost</i> Sends Purchase Orders to <i>webuser1</i> | 67 |
| Exchange B: <i>webuser1</i> Sends Invoices to <i>TXhost</i> | 72 |
| Exchange C: <i>webuser1</i> Sends File Attachment to <i>TXhost</i> | 78 |
| Importing/Deleting Setup Data | 82 |
| Importing Setup Data | 82 |
| Deleting Setup Data | 85 |
| Testing TradingXpert with the Test Scenario | 85 |
| | |
| Index | 93 |

List of Figures

| | | |
|-------------|---|----|
| Figure 1-1 | TradingXpert Software Dependencies | 20 |
| Figure 1-2 | TradingXpert/ECXpert Configurations | 22 |
| Figure 2-1 | TradingXpert and ECXpert on Different Machines | 38 |
| Figure 3-1 | TradingXpert and ECXpert on Different Machines | 54 |
| Figure 4-1 | Service List Screen for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 68 |
| Figure 4-2 | Partnership Info for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 69 |
| Figure 4-3 | Input EDI for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 70 |
| Figure 4-4 | Protocols for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 71 |
| Figure 4-5 | Service List for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 72 |
| Figure 4-6 | Partnership Info for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 73 |
| Figure 4-7 | Input HREC for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 74 |
| Figure 4-8 | Output EDI for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 75 |
| Figure 4-9 | Protocols for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 76 |
| Figure 4-10 | Service List for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 78 |
| Figure 4-11 | Partnership Info for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 79 |
| Figure 4-12 | Protocols for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 80 |
| Figure 4-13 | ECXpert Home Page | 86 |
| Figure 4-14 | ECXpert Utilities Menu | 86 |
| Figure 4-15 | Document Submission Form | 87 |
| Figure 4-16 | TradingXpert Login Screen | 88 |
| Figure 4-17 | Trade Center Screen | 89 |
| Figure 4-18 | Inbound Documents Screen | 89 |
| Figure 4-19 | Purchase Order Document | 90 |
| Figure 4-20 | Attachment Options at Bottom of an Invoice | 91 |

List of Tables

| | | |
|------------|---|----|
| Table 1 | Book Contents | 14 |
| Table 2 | Document Conventions | 14 |
| Table 3 | TradingXpert Directory Variables | 15 |
| Table 4 | TradingXpert Documentation Set | 17 |
| Table 1-1 | TradingXpert 3.6.2 Product Support Matrix | 20 |
| Table 1-2 | TradingXpert Software Modules | 25 |
| Table 1-3 | TradingXpert Installed Directory Structure | 26 |
| Table 1-4 | Installed J2EE Module Directory Structure | 28 |
| Table 1-5 | Installed Application Directory Structure | 29 |
| Table 2-1 | Hardware and Software Requirements for Solaris | 31 |
| Table 2-2 | TradingXpert Configuration Properties | 36 |
| Table 3-1 | Hardware and Software Requirements for Windows | 45 |
| Table 3-2 | TradingXpert Configuration Properties | 51 |
| Table 4-1 | Service List details for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 68 |
| Table 4-2 | Partnership Information for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 69 |
| Table 4-3 | Input EDI Information for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 71 |
| Table 4-4 | Protocols for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 71 |
| Table 4-5 | Service List details for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 72 |
| Table 4-6 | Partnership Information for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 74 |
| Table 4-7 | Input HREC for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 75 |
| Table 4-8 | Output EDI for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 76 |
| Table 4-9 | Protocols for <i>webuser1</i> Sending Invoices to <i>TXhost</i> | 77 |
| Table 4-10 | Service List details for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 78 |
| Table 4-11 | Partnership Information for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 79 |
| Table 4-12 | Protocols for <i>webuser1</i> Sending Attachments to <i>TXhost</i> | 81 |
| Table 4-13 | Parameters for <i>TXhost</i> Sending Purchase Order to <i>webuser1</i> | 87 |

List of Procedures

- To run the TradingXpert installation script 34
- To configure TradingXpert to run on a machine different from ECXpert 38
- To set up TX Host as if ECXpert were installed locally 39
- To set up TX Host to access Oracle 40
- To modify the server.policy file 42
- To run the TradingXpert setup script 43
- To run the TradingXpert installer 49
- To modify the Application Server classpath 52
- To set up a URL prefix for TradingXpert 52
- To configure TradingXpert to run on a machine different from ECXpert 54
- To set up TX Host as if ECXpert were installed locally 55
- To set up TX Host to access Oracle 57
- To modify the server.policy file 60
- To run the TradingXpert setup script 61
- To deploy the TX.war file 62
- To set up ECXpert manually 67
- To import Test Scenario Setup Data 82
- To delete Test Scenario Setup Data 85
- To conduct the TradingXpert test scenario 85

Preface

This book explains how to install Sun™ Open Net Environment (Sun ONE) Integration Server, B2B Edition software (TradingXpert 3.6.2), and this preface contains the following sections:

- [Audience for This Guide](#)
- [Organization of This Guide](#)
- [Conventions](#)
- [Other Documentation Resources](#)

Audience for This Guide

The audience for this guide is ECXpert administrators who wish to install a TradingXpert front end to ECXpert. TradingXpert enables browser-based users to interact with business partners through an ECXpert system.

This guide assumes the reader has a general understanding of ECXpert functions and is familiar with ECXpert administration tasks.

Organization of This Guide

All users should read the introduction and then the appropriate platform-specific chapter. The following table briefly describes the contents of each chapter:

Table 1 Book Contents

| Chapter | Description |
|---|--|
| Chapter 1, "Introduction" | Explains the TradingXpert software dependencies, what the installer does, and where TradingXpert software modules are installed. |
| Chapter 2, "Solaris Installation" | Describes installation of TradingXpert software on the Solaris platform, including any pre-installation and post-installation configuration tasks that have to be performed. |
| Chapter 3, "Windows Installation" | Describes installation of TradingXpert software on the Windows platform, including any pre-installation and post-installation configuration tasks that have to be performed. |
| Chapter 4, "Testing Your TradingXpert Installation" | Explains how to test your TradingXpert installation using an example test scenario. |

Conventions

This section provides information about the conventions used in this document.

Text Conventions

Table 2 Document Conventions

| Format | Description |
|----------------|--|
| <i>italics</i> | Italicized text represents a placeholder. Substitute an appropriate clause or value where you see italic text. Italicized text is also used to designate a document title, for emphasis, or for a word or phrase being introduced. |

Table 2 Document Conventions (*Continued*)

| Format | Description |
|---------------|---|
| monospace | Monospace text represents example code, commands that you enter on the command line, directory, file, or path names, error message text, class names, method names (including all elements in the signature), package names, reserved words, and URL's. |
| [] | Square brackets to indicate optional values in a command line syntax statement. |
| ALL CAPS | Text in all capitals represents file system types (GIF, TXT, HTML and so forth), environment variables (IMQ_HOME), or acronyms (TradingXpert, JSP). |
| Key+Key | Simultaneous keystrokes are joined with a plus sign: Ctrl+A means press both keys simultaneously. |
| Key-Key | Consecutive keystrokes are joined with a hyphen: Esc-S means press the Esc key, release it, then press the S key. |

Directory Variable Conventions

TradingXpert documentation makes use of two directory variables whose values depend on platform and on the version of application server in which TradingXpert is deployed. **Table 3** describes these variables and summarizes how they are used.

Table 3 TradingXpert Directory Variables

| Variable | Description |
|-----------------|--|
| BDGHOME | <p>This is an ECXpert environment variable that points to the location of the ECXpert installed software.</p> <p>$BDGHOME = \textit{Root_ECX_Install}/NS\text{-apps}/ECXpert$</p> <p>where $\textit{Root_ECX_Install}$ is the root installation directory of ECXpert software.</p> |

Table 3 TradingXpert Directory Variables (*Continued*)

| Variable | Description |
|----------------|---|
| TX_HOME | <p>This is used in TradingXpert documentation to refer to the root TradingXpert installation directory. The directory depends upon the version of Sun ONE Application Server in which TradingXpert is being deployed.</p> <p>Sun ONE Application Server 6.5:</p> <p><code>TX_HOME = Root_AS_Install/APPS/FX</code></p> <p>where <i>Root_AS_Install</i> is the root installation directory of the Application Server 6.5 software. For details of the installed TradingXpert software, see “TradingXpert Directory Structure: Application Server 6.5” on page 26.</p> <p>Sun ONE Application Server 7.0:</p> <p><code>TX_HOME = arbitrary installation directory</code></p> <p>You can select any directory in which to install TradingXpert files. For details of the installed TradingXpert software, see “TradingXpert Directory Structure: Application Server 7.0” on page 28.</p> |

In this guide, `TX_HOME` and `BDGHOME` are shown *without* platform-specific environment variable notation or syntax (for example, `$BDGHOME` on UNIX). All path names use UNIX file separator notation (`/`).

Other Documentation Resources

In addition to this guide, TradingXpert provides additional documentation resources.

The TradingXpert Documentation Set

The documents that comprise the TradingXpert documentation set are listed in [Table 4](#) in the order in which you would normally use them.

Table 4 TradingXpert Documentation Set

| Document | Audience | Description |
|---|---------------------------------------|---|
| <i>TradingXpert Installation Guide</i> | Administrators | Explains how to install TradingXpert software on Solaris and Windows platforms. |
| <i>TradingXpert Release Notes</i> | Administrators and developers | Includes descriptions of new features, limitations, and known bugs, as well as technical notes. |
| <i>TradingXpert Administrator's and Developer's Guide</i> | Users, administrators, and developers | Provides a quick-start tutorial for users, customizing instructions for administrators, and programming information for developers. |

Other Documentation Resources

Introduction

This chapter provides an overall introduction to installing the TradingXpert product. The topics covered are:

- “TradingXpert Software Dependencies”
- “TradingXpert/ECXpert Configurations” on page 22
- “Installed TradingXpert Software” on page 25
- “Upgrading to Version 3.6.2” on page 30


TradingXpert Software Dependencies

TradingXpert provides a browser-based front end for ECXpert. It is used to support ECXpert trading partners that do not have Electronic Data Interchange (EDI) processing capability. TradingXpert makes it possible for these partners to use ECXpert to submit HTML formatted documents to their partners and retrieve similarly formatted documents from them.

To perform these document exchange functions, TradingXpert has critical dependencies on a number of external software systems, as illustrated in [Figure 1-1](#):

ECXpert TradingXpert is a front end for ECXpert, submitting documents to ECXpert for processing and retrieving documents processed by ECXpert. TradingXpert relies upon the dispatching, data transformation, and partner management support provided by ECXpert.

Oracle DBMS In addition to interacting with ECXpert to submit documents, TradingXpert accesses the ECXpert Oracle database (in which ECXpert partnership and tracking information is stored) to retrieve documents processed by ECXpert.

Figure 1-1 TradingXpert Software Dependencies

Application server TradingXpert runs in an application server environment. (Note in the “[TradingXpert 3.6.2 Product Support Matrix](#),” [Table 1-1 on page 20](#), that both versions 6.5 and 7.0 of the Sun ONE Application Server are supported, resulting in some differences in the installed TradingXpert files.)

Web server A web server is required to support the interaction of browser-based ECXpert partners with TradingXpert—for receiving and sending of HTML formatted documents. The web server can be integrated with the application server (as in Sun ONE Application Server 7.0) or be a stand-alone product (as in Sun ONE Web Server 6.0).

[Table 1-1](#) shows the supported versions for TradingXpert software dependencies, including those illustrated in [Figure 1-1](#).

Table 1-1 TradingXpert 3.6.2 Product Support Matrix

| Platform/Product | Used For | Supported Platform/Product Version ¹ |
|------------------|---|---|
| ECXpert | Dispatching and transforming documents and managing trading partners. | ECXpert 3.6.2 |

Table 1-1 TradingXpert 3.6.2 Product Support Matrix (*Continued*)

| Platform/Product | Used For | Supported Platform/Product Version ¹ |
|--|--|---|
| Oracle database | ECXpert dependency: Storing partnership and process tracking data. | Oracle 8i, version 8.1.7 |
| Application server | TradingXpert runtime environment | Sun ONE Application Server <ul style="list-style-type: none"> • Enterprise Edition, 6.5 • Standard Edition (SE), 7.0 |
| Web browser | Accessing TradingXpert from a browser-based ECXpert partner | Netscape 4.79, 6.2, or higher |
| Sun ONE Application Server, Enterprise Edition, 6.5 Environment | | |
| Web server | Accessing TradingXpert from a browser-based ECXpert partner | Sun ONE Web Server, Enterprise Edition 6.0 SP5 |
| Java Runtime Environment (JRE) | Application server support | JDK/JRE 1.3.1_02 ² : <ul style="list-style-type: none"> • Solaris 2.6, 7, and 8 • Windows NT 4.0 SP 6a and Windows 2000 Professional and Server SP 3 |
| Java Software Development Kit (JDK), Standard Edition | Compiling TradingXpert Java programs | Version 1.3.1_02: <ul style="list-style-type: none"> • Solaris 2.6, 7, and 8 • Windows NT 4.0 SP 6a and Windows 2000 Professional and Server SP 3 |
| Sun ONE Application Server, Standard Edition, 7.0 Environment | | |
| Java Runtime Environment (JRE) | application server support | JDK/JRE 1.4.0_02 ³ : <ul style="list-style-type: none"> • Solaris 2.6, 7, and 8 • Windows NT 4.0 SP 6a and Windows 2000 Professional and Server SP 3 |
| Java Software Development Kit (JDK), Standard Edition | Compiling TradingXpert Java programs | Version 1.4.0_02: <ul style="list-style-type: none"> • Solaris 2.6, 7, and 8 • Windows NT 4.0 SP 6a and Windows 2000 Professional and Server SP 3 |

1. Check the *ECXpert Release Notes* for any updates to supported versions

2. Download this JDK from: <http://java.sun.com/j2se/1.3/index.html>


3. Download this JDK from: <http://java.sun.com/j2se/1.4/index.html>

TradingXpert 3.6.2 is supported on Solaris and Windows operating systems and platforms. The hardware and software requirements for these platforms are specified in their respective platform-specific chapters of this book.

TradingXpert/ECXpert Configurations

When installing TradingXpert, there are two basic configurations (see [Figure 1-2](#)): TradingXpert and ECXpert installed on the same host machine or on different machines. If TradingXpert and ECXpert are running on different machines, then both must be running the same operating system platform: Solaris or Windows.

Figure 1-2 TradingXpert/ECXpert Configurations



Running TradingXpert on a machine different from ECXpert requires a few additional configuration tasks compared to running both on the same machine (see [“Configuring TradingXpert to Run on a Different Machine from ECXpert”](#) on page 37 for the Solaris platform and [“Configuring TradingXpert to Run on a Different Machine from ECXpert”](#) on page 54 for the Windows platform). Both machines need to run the same operating system.

About the TradingXpert Installer

You install the TradingXpert 3.6.2 product using the software distribution provided on the Sun ONE Integration Server, B2B Edition CD-ROM set. For detailed instructions, see the platform-specific procedures in subsequent chapters.

Installer Dependencies

The software systems on which TradingXpert depends should be installed prior to running the TradingXpert installer. This allows you to configure these systems to support TradingXpert. The following software should be installed before installing TradingXpert:

- ECXpert

Make sure you have a functioning ECXpert installation (including its associated Oracle database). See the *ECXpert Installation Guide* for more information.

- Application server

TradingXpert is deployed into an application server environment, making the application server a prerequisite to installing TradingXpert.

- Web server (should be independently installed if it is not already integrated with the application server—for example, Sun ONE Application Server 7.0 has a built in web server.)

What the TradingXpert Installer Does

There are two TradingXpert installers: one for Application Server 6.5 environments and one for Application Server 7.0 environments. Each of these installers performs different operations.

Application Server 6.5 Environment

The TradingXpert installer sets up a directory structure and copies TradingXpert files into those directories (see [“TradingXpert Directory Structure: Application Server 6.5” on page 26](#)). The installer also registers TradingXpert with the Application Server, and (on Solaris platforms) modifies the Application Server classpath.

However, the installer does not perform any configuration of TradingXpert to inter-operate with ECXpert or the web server. Once TradingXpert software is installed, therefore, you have to manually perform the following configurations (see [“Configuration Tasks \(Application Server 6.5\)” on page 35](#) for Solaris and [“Configuration Tasks \(Application Server 6.5\)” on page 49](#) for Windows):

- modify the TradingXpert configuration file (`FXproperties`) to point to the root TradingXpert installation directory and to the ECXpert configuration file
- configure the web server instance used by TradingXpert to use the “TX” URL prefix required by TradingXpert
- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory
- optionally, configure TradingXpert to run on a different host machine from ECXpert (as shown in [“TradingXpert/ECXpert Configurations” on page 22](#)).

Application Server 7.0 Environment

TradingXpert installation places TradingXpert files into two directory trees (see [“TradingXpert Directory Structure: Application Server 7.0” on page 28](#)). It also modifies the TradingXpert configuration file (`FXproperties`) to point to the root TradingXpert installation directory and to the ECXpert configuration file.

Once the TradingXpert installer completes its work, you have to manually perform the following configurations (see [“Configuration Tasks \(Application Server 7.0\)” on page 44](#) for Solaris and [“Configuration Tasks \(Application Server 7.0\)” on page 63](#) for Windows):

- Windows only: deploy the TradingXpert Web Archive File (`TX.war`) using Sun ONE Application Server 7.0 tools
- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory
- optionally, configure TradingXpert to run on a different host machine from ECXpert (as shown in [“TradingXpert/ECXpert Configurations” on page 22](#)).

Installed TradingXpert Software

The software installed by the TradingXpert installer consists of a number of different modules, as described in “[TradingXpert Software Modules](#),” below. These modules are placed in a directory structure outlined in “[Installed Directory Structure](#)” on page 25.

TradingXpert Software Modules

[Table 1-2](#) identifies the software modules included with the TradingXpert product.

Table 1-2 TradingXpert Software Modules

| Module | Contents |
|--------------------------------|--|
| Forms | HTML forms used to view standard EDI document types. These use tags to insert data. |
| Graphical User Interface (GUI) | HTML templates and code used to implement browser screens in TradingXpert’s Trade Center user interface. |
| Java programs | Programs (and corresponding source code) that enable TradingXpert operations. Many of these use the ECXpert API to submit documents to ECXpert and to access and update data in the ECXpert Oracle database. |
| ECXpert API | An implementation of the ECXpert API that is used by TradingXpert’s Java programs. |
| Maps | Software used to transform EDI-formatted documents to TradingXpert format (name-value pairs) and <i>visa versa</i> . |
| Logger | Software that tracks, logs, and reports TradingXpert activity. |

Installed Directory Structure

The placement of files by the TradingXpert installer depends upon the version of application server in which TradingXpert is deployed:

- Sun ONE Application Server 6.5
- Sun ONE Application Server 7.0

The following sections show the installed directory structure for each.

TradingXpert Directory Structure: Application Server 6.5

Table 1-3 shows the installed directory structure for a TradingXpert installation. All subdirectories are under the `TX_HOME` directory (see “[Directory Variable Conventions](#)” on page 15 for the definition of `TX_HOME`).

Table 1-3 TradingXpert Installed Directory Structure

| Subdirectory | Contents |
|----------------------------|--|
| <code>./common</code> | Common Java programs (and source) used to support all TradingXpert operations, including access to ECXpert and the ECXpert Oracle database. Also includes the TradingXpert configuration file (<code>FXproperties</code>). |
| <code>./document</code> | Java programs (and source) used to retrieve, manage, and process documents in response to Trade Center button clicks. Also includes a working directory for processing document files. |
| <code>./events</code> | Java programs (and source) used to support e-mail notification of inbound and outbound documents that have reached their expiration dates. |
| <code>./forms/en_us</code> | HTML forms and data for displaying documents: <code>/default</code> Location for default forms (.html) representing EDI document types, as well as rules files (.rules) used for document turnarounds and order files (.order) used to assist ECXpert mapping. Subdirectories can contain files customized to various partners. <code>/from_scratch_data</code> Data files (.dat) used to provide default values for from-scratch documents. |
| <code>./login</code> | Java programs (and source) used to log in to ECXpert and return the opening Trade Center screen. |

Table 1-3 TradingXpert Installed Directory Structure (*Continued*)

| Subdirectory | Contents |
|-------------------|---|
| ./maps_etc | <p>Map files and other assorted files used to support TradingXpert operations:</p> <p><i>/customization</i> Sample customization files demonstrating creation of a new “cinfo” document type for processing by TradingXpert.</p> <p><i>/import</i> Data files containing ECXpert setup information (memberships, partnerships, and service lists) used in testing TradingXpert installation.</p> <p><i>/map_sources</i> Source code (in .zip format) that can be used to customize TradingXpert maps.</p> <p><i>/maps/platform</i> Maps for all document types supported (by default) by TradingXpert, where <i>platform</i> is <i>nt</i> and <i>/or solaris</i>.</p> <p><i>/newmember</i> Java programs (and source) used to support new member self-registration.</p> <p><i>/reports</i> Java programs (and source) used to support tracking and reporting of document status.</p> <p><i>/sampledata</i> Example data files to demonstrate various TradingXpert customizations.</p> |
| ./profile | Java programs (and source) used to access and update ECXpert membership information. |
| ./templates/en_us | Dynamic HTML templates used to implement screens in the Trade Center user interface. |
| ./tradeCenter | Java programs (and source) used to implement operations in the main Trade Center screen. |
| ./users | Location for user-specific information. User-specific subdirectories contain files such as document templates created by users in the Trade Center user interface. |
| ./web/en_us | Static HTML templates used to implement screens in the Trade Center user interface. |

TradingXpert Directory Structure: Application Server 7.0

TradingXpert files are installed in two separate locations: a J2EE module directory and a TradingXpert application directory. In this structure, the TradingXpert Java programs that enable TradingXpert operations are placed in a different location than their corresponding source code, and customizable files are separated from static user interface components.

J2EE Module Directory

The J2EE module directory is created automatically when the TradingXpert Web Archive file (TX.war) is deployed to the application server. It contains the subdirectories shown in [Table 1-4](#) within the following application server directory path:

```
Root_AS_Install/domains/domain1/appServer_instance/applications/  
J2EE-modules/TX_1
```

where *Root_AS_Install* is the root installation directory for the application server and *appServer_instance* is the name of an application server instance you create to support TradingXpert.

Table 1-4 Installed J2EE Module Directory Structure

| Subdirectory | Contents |
|--------------|--|
| ./web/en_us | Static HTML templates used to implement screens in the Trade Center user interface. |
| ./WEB-INF | Contains a web.xml file that references files installed in the TradingXpert application directory (Table 1-5 on page 29) plus the following subdirectories: /classes Java program files that enable TradingXpert operations /lib ECXpert API libraries (ecxsdkjni.jar) used by Java program files. |

TradingXpert Application Directory

The TradingXpert application directory structure is created when you install TradingXpert into a `TX_HOME` directory of your choice. Table 1-5 shows the installed subdirectory structure under `TX_HOME`:

Table 1-5 Installed Application Directory Structure

| Subdirectory | Contents |
|----------------------------|---|
| <code>./config</code> | Contains the TradingXpert configuration file (<code>FXproperties</code>). |
| <code>./document</code> | Working directory for processing document files. |
| <code>./forms/en_us</code> | HTML forms and data for displaying documents: <ul style="list-style-type: none"> <code>/default</code> Location for default forms (XSL stylesheets) representing EDI document types, as well as rules files (<code>.rules</code>) used for document turnarounds and order files (<code>.order</code>) used to assist ECXpert mapping. Subdirectories can contain files customized to various partners. <code>/from_scratch_data</code> Data files (<code>.dat</code>) used to provide default values for from-scratch documents. |
| <code>./lib</code> | ECXpert API native libraries. |
| <code>./maps_etc</code> | Map files and other assorted files used to support TradingXpert operations: <ul style="list-style-type: none"> <code>/customization</code> Sample customization files demonstrating creation of a new “cinfo” document type for processing by TradingXpert. <code>/import</code> Data files containing ECXpert setup information (memberships, partnerships, and service lists) used in testing TradingXpert installation. <code>/map_sources</code> Source code (in <code>.zip</code> format) that can be used to customize TradingXpert maps. <code>/maps/platform</code> Maps for all document types supported (by default) by TradingXpert, where <i>platform</i> is <code>nt</code> and/or <code>solaris</code>. <code>/newmember</code> Java programs (and source) used to support new member self-registration. <code>/reports</code> Java programs (and source) used to support tracking and reporting of document status. <code>/sampledata</code> Example data files to demonstrate various TradingXpert customizations. |

Table 1-5 Installed Application Directory Structure (*Continued*)

| Subdirectory | Contents |
|--------------------------------|---|
| <code>./src</code> | <p>Source code corresponding to Java programs that enable TradingXpert operations:</p> <p><code>/document</code> Source code for Java programs used to retrieve, manage, and process documents in response to Trade Center button clicks.</p> <p><code>/events</code> Source code for Java programs used to support email notification of inbound and outbound documents that have reached their expiration dates.</p> <p><code>/login</code> Source code for Java programs used to log in to ECXpert and return the opening Trade Center screen.</p> <p><code>/profile</code> Source code for Java programs used to access and update ECXpert membership information.</p> <p><code>/tradeCenter</code> Source code for Java programs used to implement operations in the main Trade Center screen.</p> |
| <code>./templates/en_us</code> | Dynamic XSL style sheets used to implement screens in the Trade Center user interface. |
| <code>./users</code> | Location for user-specific information. User-specific subdirectories contain files such as document templates created by users in the Trade Center user interface. |

Upgrading to Version 3.6.2

TradingXpert 3.6.2 is fully compatible with TradingXpert 3.6.1 and earlier versions, unless it is installed in a Sun ONE Application Server 7.0 environment. In that case, the software is installed in a different location, and any previously customized forms will not only need to be copied to the new location, but will also need to be modified as described in the *TradingXpert Release Notes*.

TradingXpert 3.6.2 is also compatible with ECXpert 3.6.1 and earlier versions, and with their respective versions of Oracle database.

When upgrading an earlier version of TradingXpert to Version 3.6.2, you should first back up all customized files, install Version 3.6.2, and then place the customized files in their correct respective locations in the TradingXpert or ECXpert directory structure.

Solaris Installation

This chapter provides the information required to install and configure TradingXpert software on the Solaris platform. Aside from having common hardware and software requirements, installation and configuration of TradingXpert depends upon whether the product is being deployed in a Sun ONE Application Server 6.5 or a Sun ONE Application Server 7.0 environment. Hence, this chapter is broken down into the following sections:

- “Hardware and Software Requirements”
- “Installing TradingXpert in a Sun ONE Application Server 6.5 Environment” on page 32
- “Installing TradingXpert in a Sun ONE Application Server 7.0 Environment” on page 40

Hardware and Software Requirements

The minimum requirements for installing TradingXpert on a Solaris platform are indicated in [Table 2-1](#).

Table 2-1 Hardware and Software Requirements for Solaris

| Component | Requirements |
|------------------|---|
| Operating system | Solaris 2.6, 7, and 8 |
| CPU | Sun Ultra™ 1 (or compatible) workstation that is TCP/IP networked |
| RAM | 512 Mbytes |
| Hard drive space | The installed product requires approximately 200 Mbytes Document storage might require up to 6 Gbytes. |

Table 2-1 Hardware and Software Requirements for Solaris (*Continued*)

| Component | Requirements |
|--------------------------|--|
| Other dependent software | See Table 1-1 on page 20 for the supported versions of the Java Runtime Environment (JRE), Java Software Development Kit (JDK), Oracle, and supported versions of other software products on which TradingXpert depends. |

Installing TradingXpert in a Sun ONE Application Server 6.5 Environment

This section, specific to the Sun ONE Application Server 6.5, covers the following topics:

- Pre-Installation Tasks
- Installation Steps
- Configuring a TradingXpert Installation

Pre-Installation Tasks (Application Server 6.5)

You should perform the following tasks before installing TradingXpert in a Sun ONE Application Server 6.5 environment. These tasks should be performed under the same non-root user account: the ECXpert administrator account (for example, `ecxadmin`).

1. Check that all hardware and software requirements ([Table 2-1 on page 31](#)) are met by your Solaris system.
2. Install ECXpert 3.6.2 and check that it is running properly. In particular, make sure that Oracle is up and running and that the `BDGHOME` environment variable is set on the ECXpert host machine (see [“Checking the BDGHOME Environment Variable” on page 33](#)).

If ECXpert is running on a host machine different from the one on which TradingXpert is to be installed, then you will have to perform additional setup operations for TradingXpert to run in this configuration (see [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 37](#)).

3. Check that Sun ONE Web Server 6.0 is installed and configured properly.

If Sun ONE Web Server 6.0 has not previously been installed, install it and create an instance that will receive requests from TradingXpert's browser-based user interface (see ["Creating a Web Server Instance for TradingXpert"](#)).

4. Check that Sun ONE Application Server 6.5 is installed and configured properly.

If Sun ONE Application Server 6.5 has not previously been installed, install it, and configure it to communicate with the Sun ONE Web Server instance to be used by TradingXpert (see your application server documentation for procedures).

Checking the BDGHOME Environment Variable

The value of the `BDGHOME` environment variable (see [Table 3 on page 15](#)) must be properly set on the ECXpert host computer.

1. Check for `BDGHOME`.

The value of `BDGHOME` should be the full path to your ECXpert installed directory structure (see [Table 3 on page 15](#)).

2. If `BDGHOME` has not been properly set:

```
setenv BDGHOME Root_ECX_Install/NS-apps/ECXpert
```

where `Root_ECX_Install` is the root installation directory of ECXpert software.

Creating a Web Server Instance for TradingXpert

1. Launch the Sun ONE Web Server's Administration Server.
2. Enter the Administration Console URL:

```
http://web_server_host:port
```

where `web_server_host` is the name of your web server's host computer, and `port` is the number of the port used for web server administration.

3. Log in under the web server administrator account.

The Administration Console window opens up.

4. Click Add Server.

5. Enter the Server Name.

This is the web server's host computer (`web_server_host`)

6. Enter the Server Port.

This is the number of the port on which the web server instance will be listening for requests from the TradingXpert browser-based user interface.

7. Enter the Server Identifier.

Use an instance identifier such as `tradingx`

8. Click OK.

9. Click Configure Your New Server.

10. Turn on the new server instance.

A success window confirmation appears.

11. Click OK.

Installation Procedures (Application Server 6.5)

Installation of TradingXpert requires you to locate the software distribution files in the Sun ONE Integration Server, B2B Edition CD-ROM set and run the TradingXpert install script.

► To run the TradingXpert installation script

1. Log in under the same user account (for example, `ecxadmin`) that was used to install ECXpert, Sun ONE Web Server 6.0, and Sun ONE Application Server 6.5.

2. Insert the Sun ONE Integration Server B2B Edition 3.6.2 Solaris CD-ROM into your CD-ROM drive.

3. Change directories to the directory on the CD-ROM which contains the `install_all` file:

```
/TradingXpert3.6.2/install_bits/TX_for_AppServer6.5/
```

4. Type the following command at the command prompt:

```
install_all
```

The installer script requests that you enter the following values:

- the directory (*Root_AS_Install*) where Application Server 6.5 is installed. Enter the full path. There is no default value.
- the ECXpert version supporting TradingXpert. Enter the value `3.6.2`

Configuration Tasks (Application Server 6.5)

The TradingXpert installer script performs the following operations:

- sets up a directory structure and copies TradingXpert files into it (see [“TradingXpert Directory Structure: Application Server 6.5” on page 26](#))
- registers TradingXpert with the application server
- makes required modifications to the application server classpath.

The installer script does not, however, configure TradingXpert to inter-operate with ECXpert. Therefore, once TradingXpert software is installed, you have to perform the following configuration tasks:

- edit the TradingXpert configuration file (`FXproperties`) to specify the TradingXpert installation directory, the location of the ECXpert configuration file (`ecx.ini`), and the TradingXpert URL prefix (`TX`)
- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory
- optionally, configure TradingXpert to run on a different host machine from ECXpert

These tasks are described in the sections that follow.

Editing the TradingXpert Configuration File

You are required to edit the TradingXpert configuration file (`FXproperties`) to specify the TradingXpert installation directory (`FX.rootdir`), the location of the ECXpert configuration file (`FX.ecxini.file`), and the TradingXpert URL prefix (`FX.basedir`).

The configuration file is located in:

`TX_HOME/common/` (Application Server 6.5)

`TX_HOME/config/` (Application Server 7.0)

The properties you are required to set, and a number of additional TradingXpert properties that you might optionally set, are described in [Table 2-2](#).

Table 2-2 TradingXpert Configuration Properties

| Property | Default Value | Description |
|------------------------|-------------------|---|
| FX.rootdir | no default | Points to the TradingXpert installation directory (TX_HOME). Note that the path should end with a trailing slash. For example: /disk1/ias6.5/ias/APPS/FX/ |
| FX.ecxini.file | no default | TradingXpert needs to access the ECXpert properties file (ecx.ini), normally located in BDGHOME/config. |
| FX.basedir | TX | The URL prefix you use to access the TradingXpert login screen and other TradingXpert functions. |
| FX.session.timeout | 8 (in minutes) | Sets the time (in minutes) from the last user action to when TradingXpert times out. On timeout, the user is requested to log in again. For production environments, it is recommended that you set the timeout value to 30 minutes. |
| FX.remoteSubmission | FALSE | Specifies remote submission of documents by TradingXpert to ECXpert. A value of FALSE means TradingXpert and ECXpert run on the same host machine. A value of TRUE means TradingXpert and ECXpert run on different hosts. (See “Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 37.) |
| FX.remoteECXPathPrefix | no default | Only applies if TradingXpert and ECXpert run on different hosts (FX.remoteSubmission=TRUE). If needed (Solaris environments), this property specifies an ECXpert mount point to be pre-pended to directory paths used in the retrieval of ECXpert documents. (See “Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 37.) |

Table 2-2 TradingXpert Configuration Properties (*Continued*)

| Property | Default Value | Description |
|----------|---------------|--|
| FX.debug | FALSE | Sets the debugging flag. When TRUE, TradingXpert prints a large volume of messages to <code>kjs</code> logs to facilitate debugging. In production environments, the value should be set to FALSE. |

Copying TradingXpert Map Files to ECXpert

The TradingXpert installer places default map files in the following directory:

```
TX_HOME/maps_etc/maps/solaris
```

These default map files can be used as is, as source for customizing your TradingXpert installation, or as examples for creating your own map files. Whatever the case, the map files used for TradingXpert processing need to be placed in the following ECXpert directory, where they can be accessed to perform data transformations:

```
BDGHOME/maps
```


If you want to test your TradingXpert installation using the test scenario provided with the product (see [Chapter 4, “Testing Your TradingXpert Installation”](#)), then copy the `850html.sun` and `html810.sun` default maps to the `BDGHOME/maps` directory.

Configuring TradingXpert to Run on a Different Machine from ECXpert

This section provides additional configuration tasks required if TradingXpert is installed on a machine different from ECXpert, as shown in [Figure 2-1](#). The tasks described assume the following scenario:

- “TX Host” is the host for TradingXpert. This includes, also, the Sun ONE Application Server and an Oracle client.
- “ECX Host” is the host for ECXpert and can also host an Oracle client (if Oracle is running on a remote host).
- “Oracle Host” is the host for the Oracle database server. (Oracle might also be running locally on ECX Host.)

Figure 2-1 TradingXpert and ECXpert on Different Machines



The general procedures required to set up this configuration are detailed below.

➤ **To configure TradingXpert to run on a machine different from ECXpert**

1. Set up TX Host as if ECXpert were installed locally. This involves providing access to the ECXpert directory structure and configuration file (`ecx.ini`), and setting a `BDGHOME` environment variable. See [“Setting up TX Host as if ECXpert Were Installed Locally”](#) on page 39.
2. Set up TX Host to access the Oracle database used by ECXpert (it is assumed that ECX Host is already set up to access the database). See [“Setting up TX Host to Access the Oracle Database Used by ECXpert”](#) on page 40.

These procedures apply to an initial installation of TradingXpert on a separate machine, *or* to a migration of TradingXpert away from the machine hosting ECXpert. They allow TradingXpert to submit document files to ECXpert, retrieve documents from ECXpert, and access the partnership and process tracking information stored in the Oracle database.

Setting up TX Host as if ECXpert Were Installed Locally

► To set up TX Host as if ECXpert were installed locally

1. Mount the ECX Host's ECXpert installed directory structure (the directory referenced by `BDGHOME`) on TX Host.

2. Set the `BDGHOME` environment variable on TX Host.

The `BDGHOME` environment variable on TX Host should point to the same directory as the `BDGHOME` environment variable on ECX Host.

3. Give the TradingXpert user privileges to access (read) ECXpert's `BDGHOME/data` directory.

4. Restart TX Host.

This is necessary for the changes in environment variable settings to take effect.

5. Edit the `ecx.ini` file on ECX Host to specify a static TCP/IP port for communication with ECXpert (this is used to submit documents to ECXpert):

- a. Open the `ecx.ini` file.

The file is located in the `BDGHOME/config` directory

- b. Modify the `[tcpip-connector]` section as follows:

```
port_location = static
admin_port_type = manual
admin_port = any unused port
listener_port_type = manual
listener_port = any unused port
```

- c. Restart ECXpert for these changes to take effect.

6. Modify TradingXpert's `FXproperties` file on TX Host.

- a. Turn on the `FXremoteSubmission` property:

```
FX.remoteSubmission: TRUE
```

- b. Set the `FXremoteECXPathPrefix` property to specify the ECXpert mount point in [Step 1](#). This path is to be pre-pended to directory paths specified in the `ecx.ini` file for the retrieval of ECXpert documents. For example, if the mountpoint is `/h/EXC_Host`, then TradingXpert will retrieve files from ECXpert at `/h/EXC_Host/BDGHOME/data...`

- c. Restart TradingXpert on TX Host for property edits to take effect.

Setting up TX Host to Access the Oracle Database Used by ECXpert

► **To set up TX Host to access Oracle**

1. Install the Oracle client on TX Host, if not already installed.
2. Give the TradingXpert user privileges to access Oracle client software.
3. Edit the `tnsnames.ora` file to reference the Oracle Server
4. Check that the `ORACLE_HOME` and `ORACLE_SID` variables are properly set on ECX Host.

These entries are found in the `[ORACLE_ENV]` section of the `ecx.ini` file, locate the `DB_SERVER` parameter.

5. Check the `DB_SERVER` parameter of the `ecx.ini` file.

In the `[DB_SECTION]` section of the `ecx.ini` file, locate the `DB_SERVER` parameter. If not already included, enter the following lines in the `[DB_SECTION]` section:

```
[DB_SECTION]
DB_SERVER=Oracle DB alias
DB_USER=Oracle username
DB_SERVER=Oracle password
```

where *Oracle DB alias* is the Oracle database alias from the `tnsnames.ora` file in [Step 3](#).

Installing TradingXpert in a Sun ONE Application Server 7.0 Environment

This section, specific to the Sun ONE Application Server 7.0, covers the following topics:

- Pre-Installation Tasks
- Installation Steps
- Configuring a TradingXpert Installation

Pre-Installation Tasks (Application Server 7.0)

You should perform the following tasks before installing TradingXpert in a Sun ONE Application Server 7.0 environment. These tasks (except where noted) should be performed under the same non-root user account: the ECXpert administrator account (for example, `ecxadmin`).

1. Check that all hardware and software requirements ([Table 2-1 on page 31](#)) are met by your Solaris system.
2. Install ECXpert 3.6.2 and check that it is running properly. In particular, make sure that Oracle is up and running and that the `BDGHOME` environment variable is set on the ECXpert host machine (see [“Checking the BDGHOME Environment Variable” on page 33](#)).

If ECXpert is running on a host machine different from the one on which TradingXpert is to be installed, then you will have to perform additional setup operations for TradingXpert to run in this configuration (see [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 37](#)).

3. Check that Sun ONE Application Server 7.0—which includes a built-in web server—is installed and properly configured. (If Sun ONE Application Server 7.0 has not previously been installed, you must log in as root to install it.) With the application server running, perform the following steps:
 - a. Log in under your TradingXpert user account (for example, `ecxadmin`).
 - b. Create an application server instance that will host TradingXpert (see [“Creating an Application Server Instance for TradingXpert,”](#) below).
 - c. Modify the `server.policy` file for the application server instance so that the TradingXpert setup script can delete temporary files (see [“Modifying the server.policy File” on page 42](#)).

Creating an Application Server Instance for TradingXpert

1. Launch the Sun ONE Application Server’s Administration Server.
2. Enter the Administration Console URL:

```
http://AS_admin_host:port
```

where `AS_admin_host` is the server hosting the Application Server’s administration server and `port` is the port number of the listener.

3. Log in under the application server administrator account.
The Administration Console window opens, displaying existing application server instances.
4. Click New.
The new application server instance dialogue is displayed.
5. Enter the Instance Name.
This is the name of the application server instance that will host TradingXpert (for example, `tradingx`).
6. Enter the HTTP Port.
This is the port on which the application server instance (web server instance) will be listening for requests from the TradingXpert browser-based user interface.
7. Enter a user account in the Run As User field.
Use the account under which TradingXpert will be running (for example, `ecxadmin`).
8. Click OK.
The Administration Console window will display the new application server instance.
9. Click the link for the newly created application server instance.
A multi-tabbed dialog is displayed.
10. Click Start to turn on the new server instance.

Modifying the server.policy File

► To modify the server.policy file

1. Open the server.policy file found in the following directory:

Root_AS_Install/domains/domain1/appServer_instance/config/

where *Root_AS_Install* is the root installation directory for the application server and *appServer_instance* is the name of the application server instance to be used by TradingXpert (for example, `tradingx`)—see [“Creating an Application Server Instance for TradingXpert” on page 41](#).

2. Find the following entry:

```
permission java.io.FilePermission "<<ALL FILES>>", "read,write";
```

3. Add permission to delete.

```
"read,write,delete"
```

4. Save the file.
5. Restart the application server instance for the change to take effect.

Installation Procedures (Application Server 7.0)

Installation of TradingXpert requires you to locate the software distribution files in the Sun ONE Integration Server, B2B Edition CD-ROM set and run the TradingXpert setup script.

► To run the TradingXpert setup script

1. Log in under the same user account (for example, `ecxadmin`) that was used to install ECXpert and to create the application server instance for TradingXpert (see ["Creating an Application Server Instance for TradingXpert" on page 41](#)).
2. Insert the Sun ONE Integration Server B2B Edition 3.6.2 Solaris CD-ROM into your CD-ROM drive.
3. Change directories to the directory on the CD-ROM which contains the `setup` file:

```
/TradingXpert3.6.2/install_bits/TX_for_AppServer7.0/
```

4. Type the following command at the command prompt:

```
setup
```

The installer script requests that you enter the following values:

- the TradingXpert application directory, `TX_HOME` (see ["TradingXpert Application Directory" on page 29](#) and [Table 3 on page 15](#))
Be sure to enter the full path. There is no default value.
- the value of the ECXpert `BDGHOME` environment variable (see [Table 3 on page 15](#)).
Be sure to enter the full path. There is no default value.

- the domain of the application server instance that will support TradingXpert (see [“Creating an Application Server Instance for TradingXpert” on page 41](#)).
Be sure to type in the domain name (for example, `domain1`). There is no default value.
- the application server administrator account and password
- the name of the application server instance in which TradingXpert is to run (for example, `tradingx`)
- the application server administrator access port number

The installer uses these values to modify the `FXproperties` and `TX.war` files, deploy the `TX.war` file, update the TradingXpert native library directory path, and, finally, stop and restart the application server instance.

Configuration Tasks (Application Server 7.0)

The TradingXpert installer script performs the following operations:

- places a number of TradingXpert files into a predefined directory structure (see [“TradingXpert Application Directory” on page 29](#)).
- deploys the TradingXpert web archive file (`TX.war`):
 - configures the application server (and included web server) to run TradingXpert
 - places a number of files in the application server directory structure (see [“J2EE Module Directory” on page 28](#)).
- modifies the TradingXpert configuration file (`FXproperties`) to point to the root TradingXpert installation directory and to the ECXpert configuration file

Once TradingXpert software is installed, however, you still have to perform two optional configuration tasks, depending on your use of TradingXpert, for TradingXpert to inter-operate with ECXpert:

- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory (see instructions in [“Copying TradingXpert Map Files to ECXpert” on page 37](#))
- configure TradingXpert to run on a different host machine from ECXpert (see instructions in [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 37](#)).

Windows Installation

This chapter provides the information required to install and configure TradingXpert software on the Windows platform. Aside from having common hardware and software requirements, installation and configuration of TradingXpert depends upon whether the product is being deployed in a Sun ONE Application Server 6.5 or a Sun ONE Application Server 7.0 environment. Hence, this chapter is broken down into the following sections:

- “Hardware and Software Requirements”
- “Installing TradingXpert in a Sun ONE Application Server 6.5 Environment” on page 46
- “Installing TradingXpert in a Sun ONE Application Server 7.0 Environment” on page 58

Hardware and Software Requirements

The minimum requirements for installing TradingXpert on a Windows platform are indicated in [Table 3-1](#).

Table 3-1 Hardware and Software Requirements for Windows

| Component | Requirements |
|------------------|---|
| Operating system | Windows NT 4.0 SP6a (Sun ONE Application Server 6.5 only) Windows 2000 (Professional, Server, Advanced Server) SP2 |
| CPU | Intel Pentium 600 MHz (or compatible) workstation |
| RAM | 512 Mbytes |
| Hard drive space | The installed product requires approximately 200 Mbytes Document storage might require up to 6 Gbytes. |

Table 3-1 Hardware and Software Requirements for Windows (*Continued*)

| Component | Requirements |
|--------------------------|--|
| Other dependent software | See Table 1-1 on page 20 for the supported versions of the Java Runtime Environment (JRE), Java Software Development Kit (JDK), Oracle, and supported versions of other software products on which TradingXpert depends. |

Installing TradingXpert in a Sun ONE Application Server 6.5 Environment

This section, specific to the Sun ONE Application Server 6.5, covers the following topics:

- Pre-Installation Tasks
- Installation Steps
- Configuring a TradingXpert Installation

Pre-Installation Tasks (Application Server 6.5)

You should perform the following tasks before installing TradingXpert in a Sun ONE Application Server 6.5 environment:

1. Check that all hardware and software requirements ([Table 3-1 on page 45](#)) are met by your Windows system.
2. Install ECXpert 3.6.2 and check that it is running properly. In particular, make sure that Oracle is up and running and that the `BDGHOME` environment variable is set on the ECXpert host machine (see [“Checking the BDGHOME Environment Variable” on page 47](#)).

If ECXpert is running on a host machine different from the one on which TradingXpert is to be installed, then you will have to perform additional setup operations for TradingXpert to run in this configuration. In particular, ECXpert should be installed in a directory tree on an otherwise unused drive (see [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 54](#)).

3. Check that Sun ONE Web Server 6.0 is installed and configured properly.

If Sun ONE Web Server 6.0 has not previously been installed, install it and create an instance that will receive requests from TradingXpert's browser-based user interface (see ["Creating a Web Server Instance for TradingXpert" on page 48](#)).

4. Check that Sun ONE Application Server 6.5 is installed and configured properly.

If Sun ONE Application Server 6.5 has not previously been installed, install it, and configure it to communicate with the Sun ONE Web Server instance to be used by TradingXpert (see your application server documentation for procedures).

Checking the BDGHOME Environment Variable

The value of the `BDGHOME` environment variable (see [Table 3 on page 15](#)) must be properly set on the ECXpert host computer.

1. From the Windows toolbar, open Settings > Control Panel > System.

The System Properties window opens.

2. Choose the Environment tab.
3. Check for `BDGHOME` in the System Variables field.

`BDGHOME` is a *system* variable, not a *user* variable. If set as a user variable Sun ONE Application Server won't be able to read it. The value of `BDGHOME` should be the full path to your ECXpert installed directory structure (see [Table 3 on page 15](#)).

4. If `BDGHOME` has not been properly set:
 - a. Set the value of `BDGHOME`.
 - b. Click OK.
 - c. Restart your computer.

Creating a Web Server Instance for TradingXpert

1. Launch the Sun ONE Web Server's Administration Server.

2. Enter the Administration Console URL:

`http://web_server_host:port`

where *web_server_host* is the name of your web server's host computer, and *port* is the number of the port used for web server administration.

3. Log in under the web server administrator account.

The Administration Console window opens up.

4. Click Add Server.

5. Enter the Server Name.

This is the web server's host computer (*web_server_host*)

6. Enter the Server Port.

This is the number of the port on which the web server instance will be listening for requests from the TradingXpert browser-based user interface.

7. Enter the Server Identifier.

Use an instance identifier such as `tradingx`

8. Click OK.

9. Click Configure Your New Server.

10. Turn on the new server instance.

A success window confirmation appears.

11. Click OK.

Installation Procedures (Application Server 6.5)

Installation of TradingXpert requires you to locate the software distribution files in the Sun ONE Integration Server, B2B Edition CD-ROM set and run the TradingXpert install script.

► **To run the TradingXpert installer**

1. Insert the Sun ONE Integration Server B2B Edition 3.6.2 Windows CD-ROM into your CD-ROM drive.
2. Launch a DOS shell:
 - a. From the Windows toolbar choose Start > Run.
 - b. In the Open field, type `command`.
 - c. Click OK.

3. Change directories to the directory on the CD-ROM which contains the `install_all.bat` file:

```
\TradingXpert3.6.2\install_bits\TX_for_AppServer6.5\
```

4. Type the following command at the command prompt:

```
install_all.bat Root_AS_Install ECX_version
```

where *Root_AS_Install* is the root installation directory for Sun ONE Application Server, and *ECX_version* is the release version of ECXpert. For example:

```
E:\...AppServer6.5\> install_all.bat D:\ias65\ias 3.6.2
```

The TradingXpert installer will display a few cryptic lines of output as it performs the installation.

Configuration Tasks (Application Server 6.5)

The TradingXpert installer performs the following operations:

- sets up a directory structure and copies TradingXpert files into it (see [“TradingXpert Directory Structure: Application Server 6.5” on page 26](#))
- registers TradingXpert with the application server (but does not make required modifications to the application server classpath).

The installer does not configure TradingXpert to inter-operate with ECXpert or the web server. Therefore, once TradingXpert software is installed, you have to manually perform the following configuration tasks:

- edit the TradingXpert configuration file (`FXproperties`) to specify the TradingXpert installation directory, the location of the ECXpert configuration file (`ecx.ini`), and the TradingXpert URL prefix (`TX`)
- modify the application server classpath variable to reference the `ecxsdkjni.jar` file
- set the TradingXpert web server instance to use the “TX” URL prefix required by TradingXpert
- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory
- optionally, configure TradingXpert to run on a different host machine from ECXpert

These tasks are described in the sections that follow.

Editing the TradingXpert Configuration File

You are required to edit the TradingXpert configuration file (`FXproperties`) to specify the TradingXpert installation directory (`FX.rootdir`), the location of the ECXpert configuration file (`FX.ecxini.file`), and the TradingXpert URL prefix (`FX.basedir`).

The configuration file is located in:

`TX_HOME\common\` (Application Server 6.5)

`TX_HOME\config\` (Application Server 7.0)

The properties you are required to set, and a number of additional TradingXpert properties that you might optionally set, are described in [Table 3-2](#).

Table 3-2 TradingXpert Configuration Properties

| Property | Default Value | Description |
|------------------------|-------------------|--|
| FX.rootdir | no default | Points to the TradingXpert installation directory (<code>TX_HOME</code>). Note that the path should end with a trailing slash. For example: <code>/disk1/ias6.5/ias/APPS/FX/</code> |
| FX.ecxini.file | no default | TradingXpert needs to access the ECXpert properties file (<code>ecx.ini</code>), normally located in <code>BDGHOME/config</code> . |
| FX.basedir | TX | The URL prefix you use to access the TradingXpert login screen and other TradingXpert functions. |
| FX.session.timeout | 8 (in minutes) | Sets the time (in minutes) from the last user action to when TradingXpert times out. On timeout, the user is requested to log in again. For production environments, it is recommended that you set the timeout value to 30 minutes. |
| FX.remoteSubmission | FALSE | Specifies remote submission of documents by TradingXpert to ECXpert. A value of <code>FALSE</code> means TradingXpert and ECXpert run on the same host machine. A value of <code>TRUE</code> means TradingXpert and ECXpert run on different hosts. (See “Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 54.) |
| FX.remoteECXPathPrefix | no default | Only applies if TradingXpert and ECXpert run on different hosts (<code>FX.remoteSubmission=TRUE</code>). If needed (Solaris environments) this property specifies an ECXpert mountpoint to be pre-pended to directory paths in the retrieval of ECX documents. (See “Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 54.) |
| FX.debug | FALSE | Sets the debugging flag. When <code>TRUE</code> , TradingXpert prints a large volume of messages to <code>kjs</code> logs to facilitate debugging. In production environments, the value should be set to <code>FALSE</code> . |

Modifying the Application Server Classpath Variable

Perform the following steps to modify the Application Server classpath variable to reference the `ecxsdkjni.jar` file.

► To modify the Application Server classpath

1. Launch the `kregedit` program.

This program is a Sun ONE utility for modifying Application Server registry entries. To launch it:

- a. Select Start>Run.
 - b. Enter `kregedit`.
 - c. Click OK.
2. Navigate to SOFTWARE>Sun ONE>Application Server>6.5>Java>ClassPath.
 3. Double-click the Classpath entry to open the Modify Value dialog box.
 4. Add the following entry to the end of the classpath:

`Root_ASInstall\ias\classes\java\ecxsdkjni.jar`

(Be sure to add a semicolon before the entry.)

5. Click OK.

Setting the URL Prefix for TradingXpert

In the URL you use to invoke TradingXpert, “TX” is always the prefix. Use the following instructions to set your TradingXpert web server instance to use the TradingXpert “TX” URL prefix, and to point the web server instance to the static HTML templates used to implement screens in TradingXpert’s browser-based user interface.

► To set up a URL prefix for TradingXpert

1. Launch the Sun ONE Web Server’s Administration Server.
2. Enter the Administration Console URL in your browser.

`http://web_server_host:port/https-admserv/bin/index`

where *web_server_host* is the name of your web server’s host computer, and *port* is the number of the port on which your server listens.

3. Select the server instance you set up for TradingXpert.
See [“Creating a Web Server Instance for TradingXpert”](#), Step 7 on page 48.
4. Click the Manage button.
5. Choose the Virtual Server Class tab.
6. Select the class “default class.”
7. Click the Manage button.
8. Choose the Content Management tab
9. Click the Additional Documents Directory button.
10. Add the URL prefix “TX”.
11. In the Map to Directory field insert the path to the TradingXpert static HTML templates:

```
TX_HOME/web
```
12. Click OK.
13. Click Apply Changes.

An acknowledgement should appear.

Copying TradingXpert Map Files to ECXpert

The TradingXpert installer places default map files in the following directory:

```
TX_HOME/maps_etc/maps/nt
```

These default map files can be used as is, as source for customizing your TradingXpert installation, or as examples for creating your own map files. Whatever the case, the map files used for TradingXpert processing need to be placed in the following ECXpert directory, where they can be accessed to perform data transformations:

```
BDGHOME/maps
```


If you want to test your TradingXpert installation using the test scenario provided with the product (see [Chapter 4, “Testing Your TradingXpert Installation”](#)), then copy the `850html.mmc` and `html810.mmc` default maps to the `BDGHOME/maps` directory.

Configuring TradingXpert to Run on a Different Machine from ECXpert

This section provides additional configuration tasks required if TradingXpert is installed on a machine different from ECXpert, as shown in [Figure 3-1](#). The tasks described assume the following scenario:

- “TX Host” is the host for TradingXpert. This includes, also, the Sun ONE Application Server and an Oracle client.
- “ECX Host” is the host for ECXpert and can also host an Oracle client (if Oracle is running on a remote host).
- “Oracle Host” is the host for the Oracle database server. (Oracle might also be running locally on ECX Host.)

Figure 3-1 TradingXpert and ECXpert on Different Machines



The general procedures required to set up this configuration are detailed below.

► To configure TradingXpert to run on a machine different from ECXpert

1. Install ECXpert on ECX Host on a drive that is not used for any other purpose (for example, $Y:\backslash$) and share that drive.
2. Mount the ECX Host’s shared drive on TX Host by mapping it to an unused drive letter (for example, drive $Y:\backslash$).
3. Set up TX Host as if ECXpert were installed locally. This involves setting up a `BDGHOME` environment variable and providing a local ECXpert configuration file (`ecx.ini`). See [“Setting up TX Host as if ECXpert Were Installed Locally.”](#)

4. Set up TX Host to access the Oracle database used by ECXpert (it is assumed that ECX Host is already set up to access the database). See [“Setting up TX Host to Access the Oracle Database Used by ECXpert” on page 57](#).

These procedures apply to an initial installation of TradingXpert on a separate machine, *or* to a migration of TradingXpert away from the machine hosting ECXpert.

Setting up TX Host as if ECXpert Were Installed Locally

► To set up TX Host as if ECXpert were installed locally

1. Set the `BDGHOME` environment variable on TX Host.
 - a. From the Windows toolbar, open Settings > Control Panel > System. The System Properties window opens.
 - b. Choose the Environment tab.
 - c. In the Variable box near the bottom, enter `BDGHOME`.
 - d. In the Value box, enter the value that the `BDGHOME` environment variable has on ECX Host.
For example: `y:\my_bdghome_path`
 - e. Click the Set button.
 - f. Restart TX Host.

This is necessary for the changes in environment variable settings to take effect. (You can wait until you complete [Step 3 on page 57](#) to restart the computer.)

(If the Sun ONE Application Server is started using the System Account, you will have to add `BDGHOME` to the System Variables section rather than to the User Variables section.)

2. Create a `config` directory on TX Host.
 - a. Open a file system window or a Command Prompt window.
 - b. Create a `config` directory immediately below the directory specified for `BDGHOME` in [Step 1](#).

For example, if you set `BDGHOME` to `y:\my_bdghome_path`, you would now create `y:\my_bdghome_path\config`.
3. Edit the `ecx.ini` file on ECX Host to specify a static TCP/IP port for communication with ECXpert (this is used to submit documents to ECXpert):
 - a. Open the `ecx.ini` file.

The file is located in the `BDGHOME\config` directory.
 - b. Modify the `[tcpip-connector]` section as follows:


```
port_location = static
admin_port_type = manual
admin_port = any unused port
listener_port_type = manual
listener_port = any unused port
```
 - c. Restart ECXpert for these changes to take effect.
4. Copy the edited `ecx.ini` file from ECX Host to TX Host.

Place the file in the `config` directory created in [Step 2](#).
5. Modify the `ecx.ini` file on TX Host.

Replace the drive letter for all directory paths with the drive letter used to map `TX_Host` to the `ECX_Host` shared drive (for example, drive `y:\`), as shown in the following example:

```
[gateway]
...
repository = y:\NS-apps\ECXpert\data\bundle
...
[tcpip-connector]
...
port_location = static
...
admin_port = <any unused port>
admin_port_type = manual
listener_port = <any unused port>
listener_port_type = manual
...
repository = y:\NS-apps\ECXpert\data\work\trk
```

```

remote_dir = y:\NS-apps\ECXpert\data\work\remote
...
[translate]
...
workDir=y:\NS-apps\ECXpert\data\work
...
inputDir=y:\NS-apps\ECXpert\data\input
outputDir=y:\NS-apps\ECXpert\data\output
mapsDir=y:\NS-apps\ECXpert\maps
...
[FAGen]
...
outputDir=y:\NS-apps\ECXpert\data\output

```

6. Modify the `FXproperties` file on TX Host.
 - a. Turn on the remote submission property:

```
FX.remoteSubmission: TRUE
```
 - b. Make sure the ECX path prefix property value is empty

```
FX.remoteECXPathPrefix: (nothing following the colon).
```
 - c. Restart TradingXpert on TX Host for property edits to take effect.

Setting up TX Host to Access the Oracle Database Used by ECXpert

► To set up TX Host to access Oracle

1. Install the Oracle client on TX Host, if not already installed.
2. Edit the `tnsnames.ora` file to reference the Oracle Server
3. Set the `ORACLE_HOME` and `ORACLE_SID` variables on TX Host.
 - a. From the Control Panel, double-click the System icon
 - b. Choose the Environment tab.
 - c. Click anywhere in the User Variables list.

This is necessary to activate the User Variables list for the next several steps. It does not matter which variable your click selects.

- d. In the Variable box near the bottom, enter `ORACLE_HOME`.

- e. In the Value box, enter the same value that the `ORACLE_HOME` environment variable has on ECX Host.

For example: `d:\orant`

Avoid using spaces in directory and file names (for example, use "ProgramFiles" instead of "Program Files.")

- f. Click the Set button.
- g. Repeat **Step c** through **Step f** for the `ORACLE_SID` environment variable.
- h. Click OK to close the System Properties dialog.
- i. Restart TX Host.

This is necessary for the changes in environment variable settings to take effect.

4. Check the `DB_SERVER` parameter of the `ecx.ini` file on TX Host.

In the `[DB_SECTION]` section of the `ecx.ini` file you copied to TX Host, locate the `DB_SERVER` parameter. Enter a line in the `[DB_SECTION]` section as follows:

```
[DB_SECTION]
DB_SERVER=Oracle DB alias
```

where *Oracle DB alias* is the Oracle database alias from the `tnsnames.ora` file in **Step 2**.

Installing TradingXpert in a Sun ONE Application Server 7.0 Environment

This section, specific to the Sun ONE Application Server 7.0, covers the following topics:

- Pre-Installation Tasks
- Installation Steps
- Configuring a TradingXpert Installation

Pre-Installation Tasks (Application Server 7.0)

You should perform the following tasks before installing TradingXpert in a Sun ONE Application Server 7.0 environment:

1. Check that all hardware and software requirements ([Table 3-1 on page 45](#)) are met by your Windows system.
2. Install ECXpert 3.6.2 and check that it is running properly. In particular, make sure that Oracle is up and running and that the `BDGHOME` environment variable is set on the ECXpert host machine (see [“Checking the BDGHOME Environment Variable” on page 47](#)).

If ECXpert is running on a host machine different from the one on which TradingXpert is to be installed, then you will have to perform additional setup operations for TradingXpert to run in this configuration. In particular, ECXpert should be installed in a directory tree on an otherwise unused drive (see [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 54](#)).

3. Check that Sun ONE Application Server 7.0—which includes a built-in web server—is installed and running, and create an application server instance for TradingXpert (see [“Creating an Application Server Instance for TradingXpert,”](#) below).
4. Modify the `server.policy` file for the application instance so that TradingXpert setup script can delete temporary files (see [“Modifying the server.policy File” on page 60](#)).

Creating an Application Server Instance for TradingXpert

1. Launch the Sun ONE Application Server’s Administration Server.
2. Enter the Administration Console URL:

```
http://AS_admin_host:port
```

where `AS_admin_host` is the server hosting the Application Server’s administration server and `port` is the port number of the listener.

3. Log in under the application server administrator account.

The Administration Console window opens, displaying existing application server instances.

4. Click New.

The new application server instance dialogue is displayed.

5. Enter the Instance Name.

This is the name by which TradingXpert will be associated with the application server instance (for example, `tradingx`).

6. Enter the HTTP Port.

This is the port on which the application server instance (web server instance) will be listening for requests from the TradingXpert browser-based user interface.

7. Enter a user account in the Run as user field.

Use the account under which TradingXpert will be running (for example, `ecxadmin`).

8. Click OK.

The Administration Console window will display the new application server instance.

9. Click the link for the newly created application server instance.

A multi-tabbed dialog is displayed.

10. Click Start to turn on the new server instance.

Modifying the `server.policy` File

► **To modify the `server.policy` file**

1. Open the `server.policy` file found in the following directory:

```
Root_AS_Install\domains\domain1\appServer_instance\config\
```

where `Root_AS_Install` is the root installation directory for the application server and `appServer_instance` is the name of the application server instance to be used by TradingXpert (for example, `tradingx`)—see [“Creating an Application Server Instance for TradingXpert” on page 59](#).

2. Find the following entry:

```
permission java.io.FilePermission "<<ALL FILES>>", "read,write";
```

3. Add permission to delete.

```
"read,write,delete"
```

4. Save the file.

5. Restart the application server instance for the change to take effect.

Installation Procedures (Application Server 7.0)

Installation of TradingXpert requires you to locate the software distribution files in the Sun ONE Integration Server, B2B Edition CD-ROM set and then perform the following procedures:

- run the TradingXpert setup script
- deploy the TradingXpert Web Archive file (TX.war).

► To run the TradingXpert setup script

1. Insert the Sun ONE Integration Server B2B Edition 3.6.2 Windows CD-ROM into your CD-ROM drive.
2. Launch a DOS shell:
 - a. From the Windows toolbar choose Start > Run.
 - b. In the Open field, type `command`.
 - c. Click OK.

3. Change directories to the directory on the CD-ROM which contains the `setup.bat` file:

```
\TradingXpert3.6.2\install_bits\TX_for_AppServer7.0\
```

4. Create a `TX_HOME` directory.

This directory can be wherever you wish (see [Table 3 on page 15](#)).

5. Type the following command at the command prompt:

```
setup.bat Root_AS_Install TX_HOME BDGHOME
```

where `Root_AS_Install` is the root installation directory for Sun ONE Application Server, `TX_HOME` is the root TradingXpert installation directory, and `BDGHOME` is the location of the ECXpert installed software. For example:

```
E:\...AppServer7.0\> setup.bat D:\ias7 D:\myTX
D:\ECX_root\NS-apps\ECXpert
```

Deploying the TradingXpert Archive (TX.war)

► To deploy the `tx.war` file

1. Point your browser at the Sun ONE Application Server 7.0 administration interface:

`http://AS_admin_host:port`

where `AS_admin_host` is the server hosting the Application Server's administration server and `port` is the port number of the listener.

2. Use the deployment tool to deploy `TX.war`:
 - a. Open the tree view on the left side to App Server Instances> `appServer_instance`>Applications>Web Apps
where `appServer_instance` is the name of the application server instance hosting TradingXpert (for example, `tradingx`).
 - b. Click Web Apps
A deployment management dialogue is displayed
 - c. Click the Deploy button.
An Upload WAR file dialogue is displayed.
 - d. Browse to the location of the `TX.war` file (`TX_HOME`) and click OK.
A dialogue specifying deployment parameters is displayed.
 - e. Click OK.
the dialogue displayed in **Step b** is displayed showing the deployed `TX.war` web application.
3. Update the TradingXpert native library directory path:
 - a. Open the tree view on the left side to the application server instance hosting TradingXpert and select the application server instance hosting TradingXpert (for example, `tradingx`).
 - b. Choose the JVM Settings tab.
 - c. Click on the Path Settings link.
 - d. Enter the following value in the Native Library Path Prefix field:
`TX_HOME\lib`
where you enter the full path for `TX_HOME`.

- e. Click Save.
4. Stop and then re-start the application server instance.
 - a. Open the tree view on the left side to the application server instance hosting TradingXpert and select the application server instance hosting TradingXpert (for example, `tradingx`).
A warning is displayed indicating that you have to apply changes.
 - b. Click Apply Changes.
A warning is displayed indicating that you have to restart the application server instance.
 - c. Click Stop.
 - d. Click Start.

Configuration Tasks (Application Server 7.0)

The TradingXpert installer script performs the following operations:

- places a number of TradingXpert files into a predefined directory structure (see [“TradingXpert Application Directory” on page 29](#))
- modifies the TradingXpert configuration file (`FXproperties`) to point to the root TradingXpert installation directory and to the ECXpert configuration file

Deploying the `TX.war` file places a number of TradingXpert files in the application server directory structure (see [“J2EE Module Directory” on page 28](#)) and configures the application server to run TradingXpert.

Once these TradingXpert installation operations are completed, however, you still have to perform two optional configuration tasks, depending on your use of TradingXpert:

- copy TradingXpert map files, as needed, to the appropriate ECXpert map directory (see instructions in [“Copying TradingXpert Map Files to ECXpert” on page 53](#))
- configure TradingXpert to run on a different host machine from ECXpert (see instructions in [“Configuring TradingXpert to Run on a Different Machine from ECXpert” on page 54](#))

Testing Your TradingXpert Installation

This chapter explains how to test your TradingXpert installation using an example document exchange scenario. In this test scenario, a browser-based ECXpert trading partner (*webuser1*) receives a purchase order from an EDI-based trading partner (*TXhost*), and turns that purchase order around to submit an invoice, as well as a file attachment, back to *TXhost*.

To carry out the test scenario, you must first set up the required ECXpert service lists and partnerships between *webuser1* and *TXhost*. Once this is done, you can run through the test scenario: *TXhost* submits a purchase order (EDI doc type = 850) to ECXpert, and *webuser1* uses TradingXpert to retrieve that document and send back an invoice (EDI doc type = 810), as well as an attachment, to *TXhost*.

This chapter covers two topics:

- “Setting Up ECXpert for the Test Scenario”
- “Testing TradingXpert with the Test Scenario” on page 85

Setting Up ECXpert for the Test Scenario

In order to conduct the test scenario, ECXpert must first be set up with the memberships, partnerships, and service lists required to perform the example document exchange. You can do the set up in either of two ways:

- using the ECXpert user interface to manually perform the setup—this helps you understand how to set up ECXpert for browser-based trading partners
- importing setup data provided in the TradingXpert software distribution—this might save you time.

The sections that follow describe these two approaches.

Either way, the test scenario assumes that *TXhost* receives documents over FTP protocols, and you are therefore required to provide the TCP configuration information indicated in the following worksheet:

TCP Configuration Worksheet

| FTP Configuration Parameter | Default string in setup data | Your Value |
|-----------------------------|------------------------------|------------|
| Host_name:port | ftphost | |
| User name | ftpusername | |
| Password | ftpuserpwd | |
| Outbound directory | outputdir | |

NOTE Be sure to copy the required map files to `BDGHOME/maps`. See [“Copying TradingXpert Map Files to ECXpert” on page 37](#) for the Solaris platform and [“Copying TradingXpert Map Files to ECXpert” on page 53](#) for the Windows platform.

Setting up ECXpert Manually

To set up the necessary memberships, service lists, and partnerships for the test scenario manually, rather than import them (see “[Importing/Deleting Setup Data](#)” on page 82), you perform the following steps:

► **To set up ECXpert manually**

1. Set up memberships for *TXhost* and *webuser1*.
 - a. *TXhost* with EDI trading address of `ZZ:TXhost`.
 - b. *webuser1* with EDI trading address of `ZZ:webuser1`.
2. Set up a service list and partnership for the following exchanges:
 - Exchange A:** *TXhost* sends purchase order to *webuser1*
 - Exchange B:** *webuser1* sends an invoice back to *TXhost*
 - Exchange C:** *webuser1* sends a file attachment back to *TXhost*

The procedures for [Step 2](#) are covered in detail in the following sections.

Exchange A: *TXhost* Sends Purchase Orders to *webuser1*

This section explains how to set up the service list and partnership needed for *TXhost* to send purchase orders to *webuser1*.

Service List Setup A

This service list does not include the Gateway service: after a purchase order (ANSI X.12 850) is parsed and translated to TradingXpert format, it is stored by ECXpert until being retrieved by TradingXpert. If Gateway is in this service list, ECXpert attempts to send purchase orders directly to the trading partner.

[Figure 4-1](#) and the accompanying [Table 4-1](#) show how to set up a service list for this exchange.

Figure 4-1 Service List Screen for *TXhost* Sending Purchase Order to *webuser1*




Table 4-1 Service List details for *TXhost* Sending Purchase Order to *webuser1*

| Field | Value | Explanation |
|--------------------------------------|----------|---|
| Service List Details | | |
| Service List Data Type | EDI | Indicates the type of document being serviced |
| Sending Member ID | * | Applies to any sending member |
| Receiving Member ID | webuser1 | Applies to browser-based ECXpert partner |
| Select Service to add to List | | |

Table 4-1 Service List details for *TXhost* Sending Purchase Order to *webuser1* (Continued)

| Field | Value | Explanation |
|-------|-----------|---|
| | Parse | Breaks incoming EDI into its constituent parts. |
| | Translate | Converts documents from one format to another. |

Partnership Setup A

The partnership setup includes a number of screens corresponding to the different tabs required to configure the partnership.

Partnership Info Figure 4-2 and the accompanying Table 4-2 show how to set up the Partnership Info tab for this exchange.

Figure 4-2 Partnership Info for *TXhost* Sending Purchase Order to *webuser1*




Table 4-2 Partnership Information for *TXhost* Sending Purchase Order to *webuser1*

| Field | Value | Explanation |
|----------------------------|--------|--|
| Partnership Details | | |
| Sending Member | TXhost | EDI-enabled ECXpert partner sending the purchase order |

Table 4-2 Partnership Information for *TXhost* Sending Purchase Order to *webuser1*

| Field | Value | Explanation |
|----------------------|--|--|
| Receiving Member | webuser1 | Browser-based ECXpert partner receiving the purchase order by way of TradingXpert |
| Document Type | 850 | ANSI X.12 doc type for purchase order |
| Partnership Type | EDI to Application | The document will be picked up by the TradingXpert application |
| Map Name | 850html.sun (Solaris) or 850html.mmc (Windows) | The map file used to convert inbound 850 documents to TradingXpert format (EDI to Application) |
| Incoming SMTP | | |
| [Parameters] | Default | Not needed for this document exchange. |

Input EDI Figure 4-3 and the accompanying Table 4-3 show how to set up the Input EDI tab for this exchange.

Figure 4-3 Input EDI for *TXhost* Sending Purchase Order to *webuser1*





Table 4-3 Input EDI Information for *TXhost* Sending Purchase Order to *webuser1*

| Field | Value | Explanation |
|--------------------------------------|-------------|-------------------------------|
| Interchange Level Information | | |
| Sender Qualifier ID | ZZ:TXhost | EDI trading address |
| Receiver Qualifier ID | ZZ:webuser1 | EDI trading address |
| Standard | ANSI | Using ANSI X.12 doc type |
| Group Level Information | | |
| Functional ID Code | PO | Corresponds to purchase order |
| Group Version | 004010 | |
| Functional Acknowledgments | | |
| [Parameters] | Default | Not needed. |

Protocols Figure 4-4 and the accompanying Table 4-4 show how to set up the Protocols tab for this exchange.

Figure 4-4 Protocols for *TXhost* Sending Purchase Order to *webuser1***Table 4-4** Protocols for *TXhost* Sending Purchase Order to *webuser1*

| Field | Value | Explanation |
|--------------------------|-------|--|
| Outgoing Protocol | | |
| Drop-down protocol list | POLL | TradingXpert will retrieve the document, as opposed to its being sent to the Gateway |

Exchange B: *webuser1* Sends Invoices to *TXhost*

This section explains how to set up the service list and partnership needed for *webuser1* to send invoices to *TXhost*.

Service List Setup B

Figure 4-5 and the accompanying Table 4-5 show how to set up a service list for this exchange.

Figure 4-5 Service List for *webuser1* Sending Invoices to *TXhost*




Table 4-5 Service List details for *webuser1* Sending Invoices to *TXhost*

| Field | Value | Explanation |
|-----------------------------|----------|---|
| Service List Details | | |
| Service List Data Type | EDI | Indicates the type of document being serviced |
| Sending Member ID | webuser1 | Applies to browser-based ECXpert partner |

Table 4-5 Service List details for *webuser1* Sending Invoices to *TXhost* (Continued)

| Field | Value | Explanation |
|--------------------------------------|-----------|---|
| Receiving Member ID | * | Applies to any receiving member |
| Select Service to add to List | | |
| | Parse | Breaks incoming document into its constituent parts. |
| | Translate | Converts documents from one format to another |
| | Gateway | Uses Gateway to send document to receiving member (<i>TXhost</i>) |

Partnership Setup B

The partnership setup includes a number of screens corresponding to the different tabs required to configure the partnership.

Partnership Info Figure 4-6 and the accompanying Table 4-6 show how to set up the Partnership Info tab for this exchange.

Figure 4-6 Partnership Info for *webuser1* Sending Invoices to *TXhost*

The screenshot shows the 'Change Partnership' interface with the following details:

- Partnership Info Tab:** Selected.
- Partnership Details:**
 - Sending Member: webuser1
 - Receiving Member: TXhost
 - Partnership Type: Application to EDI
 - Map Name: html810.sun
 - Document Type: 810
 - Partnership Description: (empty field)
 - Do not purge for (days): 5
 - Billing Code: (empty field)
 - Trading: Enable Trading Disable Trading
- Incoming SMTP:**
 - Sender Certificate Type: None
 - Receiver Certificate Type: None

Table 4-6 Partnership Information for *webuser1* Sending Invoices to *TXhost*

| Field | Value | Explanation |
|----------------------------|--|---|
| Partnership Details | | |
| Sending Member | webuser1 | Browser-based ECXpert partner sending the invoice by way of TradingXpert |
| Receiving Member | TXhost | EDI-enabled ECXpert partner receiving the invoice |
| Document Type | 810 | ANSI X.12 doc type for invoice |
| Partnership Type | Application to EDI | The document will be sent by the TradingXpert application to ECXpert |
| Map Name | html810.sun (Solaris) or html810.mmc (Windows) | The map file used to convert TradingXpert format to outbound 810 documents (Application to EDI) |
| Incoming SMTP | | |
| [Parameters] | Default | Not needed for this document exchange. |

Input HREC Figure 4-7 and the accompanying Table 4-7 show how to set up the Input HEC tab for this exchange.

Figure 4-7 Input HREC for *webuser1* Sending Invoices to *TXhost*




Table 4-7 Input HREC for *webuser1* Sending Invoices to *TXhost*

| Field | Value | Explanation |
|--------------------------------------|-------------|--------------------------|
| Interchange Level Information | | |
| Sender Qualifier ID | ZZ:webuser1 | EDI trading address |
| Receiver Qualifier ID | ZZ:TXhost | EDI trading address |
| Standard | ANSI | Using ANSI X.12 doc type |
| Group Level Information | | |
| Application Sender | NONE | |
| Application Receiver | NONE | |
| Functional ID Code | IN | Corresponds to invoice |
| Group Version | 004010 | |

Output EDI Figure 4-8 and the accompanying Table 4-8 show how to set up the Output EDI tab for this exchange.

Figure 4-8 Output EDI for *webuser1* Sending Invoices to *TXhost*

The screenshot shows the 'Change Partnership' application window. The 'Output EDI' tab is selected. The interface includes a sidebar with navigation options: Membership, Partnership, Tracking, Job Tracking, Certificates, Services, and Logout. The main content area is divided into several sections:

- Enveloping Options:**
 - EDI Envelope: ECX generates (or overrides) entire envelope
 - Standard: ANSI
- Version Information:**
 - Interchange Version (ISA 12): [Empty text box]
- Generate Control Numbers Starting With:**

| Interchange | Group | Document |
|-------------|-------|----------|
| 1236 | 2334 | 3445 |
- FA Information:**
 - FA (997) Expected?
 - FA overdue in (minutes): 5259600
- Delimiters and Separators:**
 - Segment Terminator (hex value): 0D0A
 - Test or Production: PRODUCTION

Table 4-8 Output EDI for *webuser1* Sending Invoices to *TXhost*

| Field | Value | Explanation |
|---------------------------|--|--|
| Enveloping Options | | |
| EDI Envelope | ECXpert generates (or overrides) entire envelope | |
| Standard | ANSI | |
| [Remaining parameters] | Default | Not needed for this document exchange. |

Protocols Figure 4-9 and the accompanying Table 4-9 show how to set up the Protocols tab for this exchange.

Figure 4-9 Protocols for *webuser1* Sending Invoices to *TXhost*




Table 4-9 Protocols for *webuser1* Sending Invoices to *TXhost*

| Field | Value | Explanation |
|---------------------------|-------------------------------------|---|
| Outgoing Protocol | | |
| Pull-down protocol list | FTP | |
| Precommunications Service | <NONE> | |
| Delivery Timing | Immediate | |
| Host Name | <i>myserver</i> | The name of the machine on which the invoice will be deposited |
| Port | 21 | The ftp port of the machine on which the invoice will be deposited, typically 21 |
| Username | <i>ftpuser</i> | The username you will use to log on to the machine on which the invoice will be deposited |
| Password | ***** | The password for the user you entered in the Username field |
| Confirm Password | ***** | The password for the user you entered in the Username field, entered a second time for confirmation |
| Outbound Transfer Mode | Binary | |
| Outbound Dir | /tmp (Solaris) D:\temp (Windows) | The directory where the file will be deposited |
| Outbound Pattern | invoice_data | |
| [Remaining parameters] | Default | Not needed for this document exchange. |

NOTE You should also go to the ECXpert Server Administration interface to check that the ECXpert FTP server is on. For instructions, see your *ECXpert Administrator's Guide*, Chapter 3.

Exchange C: *webuser1* Sends File Attachment to *TXhost*

This section explains how to set up the service list and partnership needed for *webuser1* to send file attachments to *TXhost*.

Service List Setup C

Figure 4-10 and the accompanying Table 4-10 show how to set up a service list for this exchange.

Figure 4-10 Service List for *webuser1* Sending Attachments to *TXhost*




Table 4-10 Service List details for *webuser1* Sending Attachments to *TXhost*

| Field | Value | Explanation |
|-----------------------------|----------|---|
| Service List Details | | |
| Service List Data Type | ATTACH | Indicates the type of document being serviced |
| Sending Member ID | webuser1 | Applies to browser-based ECXpert partner |
| Receiving Member ID | * | Applies to any receiving partner |

Table 4-10 Service List details for *webuser1* Sending Attachments to *TXhost* (Continued)

| Field | Value | Explanation |
|--------------------------------------|---------|---|
| Select Service to add to List | | |
| | OutPrep | Marks files that do not need processing as ready for the Gateway service. |
| | Gateway | Uses Gateway to send document to receiving member (<i>TXhost</i>) |

Partnership Setup C

The partnership setup includes a number of screens corresponding to the different tabs required to configure the partnership.

Partnership Info Figure 4-11 and the accompanying Table 4-11 show how to set up the Partnership Info tab for this exchange.

Figure 4-11 Partnership Info for *webuser1* Sending Attachments to *TXhost*
Table 4-11 Partnership Information for *webuser1* Sending Attachments to *TXhost*

| Field | Value | Explanation |
|----------------------------|----------|---|
| Partnership Details | | |
| Sending Member | webuser1 | Browser-based ECXpert partner sending the attachment by way of TradingXpert |

Table 4-11 Partnership Information for *webuser1* Sending Attachments to *TXhost*

| Field | Value | Explanation |
|----------------------|----------------------------|--|
| Receiving Member | TXhost | EDI-enabled ECXpert partner receiving the attachment |
| Document Type | ATTACH | ANSI X.12 doc type for invoice |
| Partnership Type | Application to Application | Neither partner is EDI-enabled. |
| Map Name | | No map file is needed. |
| Incoming SMTP | | |
| [Parameters] | Default | Not needed for this document exchange. |

Protocols Figure 4-12 and the accompanying Table 4-12 show how to set up the Protocols tab for this exchange.

Figure 4-12 Protocols for *webuser1* Sending Attachments to *TXhost*




Table 4-12 Protocols for *webuser1* Sending Attachments to *TXhost*

| Field | Value | Explanation |
|---------------------------|-----------------|---|
| Outgoing Protocol | | |
| Pull-down protocol list | FTP | |
| Precommunications Service | <NONE> | |
| Delivery Timing | Immediate | |
| Host Name | <i>myserver</i> | The name of the machine on which the invoice will be deposited |
| Port | 21 | The ftp port of the machine on which the invoice will be deposited, typically 21 |
| Username | <i>ftpuser</i> | The username you will use to log on to the machine on which the invoice will be deposited |
| Password | ***** | The password for the user you entered in the Username field |
| Confirm Password | ***** | The password for the user you entered in the Username field, entered a second time for confirmation |
| Outbound Transfer Mode | Binary | |
| Outbound Dir | /tmp | The directory where the file will be deposited |
| Outbound Pattern | attachment | |
| [Remaining parameters] | Default | Not needed for this document exchange. |

NOTE You should also go to the ECXpert Server Administration interface to check that the ECXpert FTP server is on. For instructions, see your *ECXpert Administrator's Guide*, Chapter 3.

Importing/Deleting Setup Data

Rather than manually setting up ECXpert to support the TradingXpert test scenario, as detailed in [“Setting up ECXpert Manually” on page 67](#), you can import the memberships, service lists, and partnerships for the test scenario using the import files provided on your installation disk.

NOTE The import files provided on your installation disk are intended only to provide example data. The import files should not be modified except as instructed in the following procedure. Also, because of an error in the import file, you must correct the imported data, as described in the note appended to [Step 7 on page 84](#).

Importing Setup Data

You import data in the `tx-mem.imp` file into the ECXpert Oracle database using the ECXpert import utility.

► **To import Test Scenario Setup Data**

1. Log in to the TradingXpert machine as the same user under which you installed TradingXpert.
2. Change to the `maps_etc/import` directory in the TradingXpert installed directory structure (see [“Installed Directory Structure” on page 25](#)).

```
cd TX_HOME/maps_etc/import
```

3. Make backup copies of the `tx-mem.imp` and `del-tx-mem.imp` files.
4. Edit the `tx-mem.imp` and `del-tx-mem.imp` files.

Using a text editor, do a global search and replace of the strings `“ftphost,”` `“ftpusername,”` `“ftpuserpwd,”` and `“outputdir”` with the appropriate values from the table [“TCP Configuration Worksheet” on page 66](#).

5. Make sure `BDGHOME` is set to the location of the ECXpert installation (see [Table 3 on page 15](#)) so that the application server will use the same `ecx.ini` file that ECXpert uses.

On Solaris:

```
setenv BDGHOME /disk1/Root_ECX_Install/NS-apps/ECXpert
```

where *Root_ECX_Install* is the root installation directory of ECXpert software.

On Windows:

In the Control Panel of the machine on which ECXpert is installed, double-click the System icon, then click the Environment tab. Make sure the `BDGHOME` variable has the value:

```
Root_ECX_Install\NS-apps\ECXpert
```

where *Root_ECX_Install* is the root installation directory of ECXpert software.

6. Make sure the application server can reference the `BDGHOME/lib` directory.

On Solaris:

If it is not, use the following syntax to modify the `LD_LIBRARY_PATH` environment variable in the administrator user's `.profile` or `.login` file.

For the C shell:

```
setenv LD_LIBRARY_PATH BDGHOME/lib:$LD_LIBRARY_PATH
```

For the Bourne shell:

```
LD_LIBRARY_PATH=BDGHOME/lib:$LD_LIBRARY_PATH
```

```
export LD_LIBRARY_PATH
```

On Windows:

In the Control Panel of the machine on which ECXpert is installed, double-click the System icon, then click the Environment tab. Make sure the `PATH` environment variable includes the value:

```
BDGHOME/lib
```

7. Populate the database.

Use the ECXpert import utility, which is located at `BDGHOME/bin/import`. Type the following command in the Command Prompt window:

```
BDGHOME/bin/import ECX ECX  
TX_HOME/maps_etc/import/tx-mem.imp /tmp/good /tmp/bad
```

where

- `ECX` is both the username and the password of the ECXpert administrator
- `TX_HOME/maps_etc/import/tx-mem.imp` is the location of the import file that will populate TradingXpert members, partnership, and service lists
- `/tmp/good` is the log file that records successful data imports
- `/tmp/bad` is the log file that records rejected data.

NOTE You will see error messages after running the import command line. Note that one record is rejected: the `EDIFACT INVOIC` partnership does not import correctly. To remedy this, log in to the ECXpert Administration interface and perform the following tasks:

1. Select the partnership of Doc Type `INVOIC`.
 2. Select the Output EDI tab.
 3. Change the Standard from `ANSI` to `EDIFACT`.
 4. In the Version Number field, type "D"
 5. In the Release Number field, type "97A"
 6. Save the partnership.
-

Deleting Setup Data

To clean up the database and erase all the TradingXpert members, partnerships, and service lists that you just created, follow these steps:

► To delete Test Scenario Setup Data

1. Log in to the TradingXpert machine as the same user under which you installed TradingXpert.
2. Erase the TradingXpert Commerce Integration Suite test data in the database.

Use the ECXpert import utility, which is located at `BDGHOME/bin/import`. Type the following command in the Command Prompt window:

```
BDGHOME/bin/import ECX ECX
    TX_HOME/maps_etc/import/del-tx-mem.imp /tmp/good /tmp/bad
```

where

- `ECX` is both the username and the password of the ECXpert administrator
- `TX_HOME/maps_etc/import/del-tx-mem.imp` is the location of the import file that will delete the TradingXpert setup data.
- `/tmp/good` is the log file that records successful data deletions
- `/tmp/bad` is the log file that records rejected data deletions.

Testing TradingXpert with the Test Scenario

This section describes the procedure for conducting the TradingXpert test scenario: *TXhost* submits a purchase order (EDI doc type = 850) to ECXpert, and *webuser1* uses TradingXpert to retrieve that document and send back an invoice (EDI doc type = 810), as well as an attachment.

► To conduct the TradingXpert test scenario


1. Open the ECXpert administration interface by entering the following URL in your browser:

```
http://ECXhostname:port/
```

where *ECXhostname* is the name of the host machine where ECXpert is installed, and *port* is the port number ECXpert is using.

The [ECXpert Home Page](#) (Figure 4-13) appears.

Figure 4-13 ECXpert Home Page



2. Click the Utilities button.

The **ECXpert Utilities Menu** (Figure 4-14) appears.

Figure 4-14 ECXpert Utilities Menu



3. Click the Document Submission Form link.

The **Document Submission Form** (Figure 4-15) appears.

Figure 4-15 Document Submission Form

The screenshot shows a web browser window with the title "Sun-ONE Integration Server B2B Edition (ECXpert) Utilities". The main content area is titled "Submission Information" and contains the following form fields:

- Sending Member:** TXhost
- Password:** *****
- Receiving Member:** webuser1
- File Name:** /tmp/850edi.txt
- File Type:** EDI

A "Submit" button is located at the bottom center of the form.

4. Enter parameters for the `submit` command.

Refer to [Table 4-13](#) for detailed information about the parameters.

Table 4-13 Parameters for *TXhost* Sending Purchase Order to *webuser1*

| Parameter | Value | Explanation |
|------------------|------------|--|
| Sending Member | TXhost | The sending member's ID |
| Password | ***** | Password for the sending member |
| Receiving Member | webuser1 | The receiving member's ID |
| File Name | 850edi.txt | The name of the EDI purchase order file to be submitted to TradingXpert. The demo file, which is included in the <code>/maps_etc/sampledata</code> directory, is named <code>850edi.txt</code> . |
| File Type | EDI | The type of data file being submitted to ECXpert |

5. Click the Submit button.

A message appears providing feedback on the command. If any errors are encountered they are displayed first.

6. Optionally, view the tracking information for your submission.
 - a. Log in to the ECXpert Product Administrative Interface.
 - b. Click the Tracking button on the left.

The Enter Search Constraints tab appears.
 - c. Set Search Level to Document.
 - d. Enter today's date.
 - e. Click the **Search** button.
7. Open the TradingXpert user interface by entering the following URL in your browser:

`http://TradingXpert_hostname:port/TX`

where *hostname* is the name of the host machine where TradingXpert is installed, and *port* is the port number TradingXpert is using.

The **TradingXpert Login Screen (Figure 4-16)** appears.


Figure 4-16 TradingXpert Login Screen




8. Log in to TradingXpert as webuser1.

Use the User ID `webuser1` and the Password `webuser1` and click Login.

The **Trade Center Screen (Figure 4-17)** appears.

Figure 4-17 Trade Center Screen


9. View the incoming purchase order.
 - a. Click the Inbound icon to view incoming documents.
The **Inbound Documents Screen (Figure 4-18)** appears.

Figure 4-18 Inbound Documents Screen

- b. Search for all incoming documents from TXhost.

- c. Find the purchase order just sent from TXhost and click View.
The **Purchase Order Document (Figure 4-19)** is displayed.

Figure 4-19 Purchase Order Document



- 10. Create an invoice from the purchase order.

At the bottom of the purchase order, click the Create Invoice button.

An invoice form (Figure 4-20) will appear; the data fields will be pre-filled with data from the purchase order.

Figure 4-20 Attachment Options at Bottom of an Invoice

The screenshot displays the Sun ONE Integration Server B2B Edition (TradingXpert) interface. The top navigation bar includes 'Logout' and 'Help' links. The main header shows 'Sun ONE Integration Server B2B Edition (TradingXpert)' and 'Welcome webuser1'. A left sidebar contains navigation buttons: 'Get Documents', 'Inbound', 'Outbound', 'My Profile', 'New Document', and 'Template'. The main content area shows invoice details for Line Number 0002, including Description (white paint), Buyer's Part Number (DE-7667-3), Vendor's Part Number (no time), Amount/each (\$), Qty Ordered (10), Qty Shipped, Qty Difference, and Reason (Backordered). Below this is an 'Attach File' section with a text input field, a 'Browse...' button, and a 'Any Type' dropdown menu. At the bottom, there are buttons for 'Submit Document', 'Add Line Items', 'Delete Line Items', and 'Save As Template'.

11. Attach a file to the invoice.

At the bottom of the invoice screen is an Attach File section. Attach any file on your hard drive by first either entering the full path of the file or clicking Browse to select a file, and then selecting Any Type from the drop-down menu.

12. Submit the invoice with attachment to TXhost by clicking the Submit Document button.

A screen will appear confirming that the document was submitted successfully.

13. Verify receipt of the invoice and attachment in ECXpert.

a. Return to the ECXpert administration interface:

`http://ECXhostname:port`

where *ECXhostname* is the name of the host machine where ECXpert is installed, and *port* is the port number ECXpert is using.

- b.** On the ECXpert home page (Figure 4-13), click Support.
- c.** Enter the ECXpert administrator user name and password and click Enter.
- d.** Click the Tracking button, then enter search constraints to find the 810 invoice document sent by webuser1 to TXhost.
- e.** View tracking information for the inbound document and attached file.

Index

A

- application server
 - instance for TradingXpert 41, 59
 - relation to TradingXpert 20
 - supported versions 21
 - TradingXpert installer dependencies 23
- Application Server 6.5
 - TradingXpert configuration tasks
 - Solaris 35
 - Windows 49
 - TradingXpert installation procedures
 - Solaris 34
 - Windows 48
 - TradingXpert installer, and 23
 - TradingXpert pre-installation tasks
 - Solaris 32
 - Windows 46
- Application Server 7.0
 - TradingXpert configuration tasks
 - Solaris 44
 - Windows 63
 - TradingXpert installation procedures
 - Solaris 43
 - Windows 61
 - TradingXpert installer, and 24
 - TradingXpert pre-installation tasks
 - Solaris 41
 - Windows 59

B

- BDGHOME environment variable 15, 33, 47

C

- classpath variable (Windows) 52
- configuration
 - TCP 66
 - TradingXpert on different machine than ECXpert
 - Solaris 37
 - Windows 54
 - TradingXpert with ECXpert 22
- configuration file
 - editing 35, 50
 - location 35, 50
 - properties 36, 51
- configuration tasks
 - Solaris
 - Application Server 6.5 35
 - Application Server 7.0 44
 - Windows
 - Application Server 6.5 49
 - Application Server 7.0 63

D

dependencies

- about 19
- application server 20, 23
- ECXpert 19, 23
- for TradingXpert installer 23
- Oracle 19
- product support matrix 20
- web server 20, 23

directory structure

- on Application Server 6.5 26
- on Application Server 7.0 28

directory variable, TX_HOME 16

E

ECXpert

- configuration with TradingXpert 22
- relation to TradingXpert 19
- TradingXpert installer dependencies 23

environment variable, BDGHOME 15

F

files

- configuration 35, 50
- map 37, 53
- server.policy 42, 60
- TX.war 62

FXproperties file, *see* configuration file

H

hardware requirements

- Solaris 31
- Windows 45

I

installation procedures

Solaris

- Application Server 6.5 34
- Application Server 7.0 43

Windows

- Application Server 6.5 48
- Application Server 7.0 61

M

map files, copying

- Solaris 37
- Windows 53

O

Oracle

- relation to TradingXpert 19
- supported version 21

P

pre-installation tasks

Solaris

- Application Server 6.5 32
- Application Server 7.0 41

Windows

- Application Server 6.5 46
- Application Server 7.0 59

properties, configuration 36, 51

R

- requirements
 - hardware
 - Solaris 31
 - Windows 45
 - software
 - Solaris 31
 - Windows 45

S

- server.policy file 42, 60
- software dependencies, *see* dependencies
- software modules 25
- software requirements
 - Solaris 31
 - Windows 45
- supported products and platforms 20

T

- TCP configuration 66
- Testing TradingXpert
 - test scenario 65
- testing TradingXpert
 - running the test scenario 85
 - setting up ECXpert
 - importing data 82
 - manually 67
- TX.war file, deploying 28, 44, 62
- TX_HOME directory variable 16

U

- upgrading TradingXpert 30
- URL prefix, setting 52

W

- web browser, supported version 21
- web server
 - relation to TradingXpert 20
 - supported version 21
 - TradingXpert installer dependencies 23
- web server instance for TradingXpert 33, 48

