

Product Installation Manual
Oracle Financial Services Pricing Management
Version 6.1.0.0.0
March 2015



Document Control

Author: Niraj Ranjan Biswal	Group: OFSAA	
Created on : 08-Feb-12	Revision No : 1.10	
Updated by : Arpana Danayak		
Updated on : March-15		

Table of Contents

About this Manual	1
Audience	1
Scope	1
Organization of the Manual	1
Conventions Used in this Manual	1
Pre-Requisites	3
Environment.....	3
Front-End Access	3
Installing Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product	5
Pre-Installation Activities	5
Pre-Upgrade Activities	6
Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product Installation	7
Machine A – Product App Layer	8
Machine B – Product Database Layer.....	21
Machine C – Product Web Layer.....	27
Silent Installation.....	32
Post Installation Activities	36

About this Manual

Oracle Financial Services Pricing Management enables banks to assess the cost and risk added to their portfolio by each new loan, thereby price the loan appropriately. Traditionally, banks have adopted a uniform loan pricing policy which does not take into account the incremental risk that the bank was taking on its books on account of the new loan. This results in a less than optimum loan price which is not sufficient to cover the additional risk.

Oracle Financial Services Pricing Management addresses this need by estimating the transfer rates, capital charges and the corresponding price to be charged for the new exposure. It estimates the cash flows from each new loan and calculates the risk-adjusted performance measures, RAROC and SVA in order to measure the returns generated from a loan by considering the risk added by it. It enables banks to identify good credits and avoid bad credits.

Audience

This Manual is meant for use by the Oracle Financial Services Analytical Applications Infrastructure System Administrator. It provides step-by-step instructions necessary for installing the Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product.

Scope

This manual provides a step-wise instruction to install the Oracle Financial Services Pricing Management Product in an existing Oracle Financial Services Analytical Applications Infrastructure hosted in OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit - Oracle 11g R2 (11.2.0.2.0) environment. The supported web-servers are Tomcat 7.0.19, Websphere 7.0.0.17 and Web logic 10.3.5.0.

Note: Linux 6 is not supported for PRMGR v6.1 even though AAI supports it. PRMGR v6.1 is not qualified on Solaris 5.11.

Organization of the Manual

The Installation Manual is organized into the following chapters.

Pre Requisites section identifies the hardware and base software environment that is required for a successful installation & functioning of the Oracle Financial Services Analytical Applications Infrastructure Solution.

Installing Oracle Financial Services Analytical Applications Infrastructure Solution section details the pre-installation activities followed by a step-by-step instruction on the various installation options.

Post installation Activities section details the steps that are required to be performed after a successful installation of the Oracle Financial Services Analytical Applications Infrastructure Solution.

Conventions Used in this Manual

References to sections or chapters in the manual are displayed in *Italics*.

Screen names are displayed in the following manner:

Introduction screen

Options and buttons are displayed in **Bold**.

Notes are displayed as follows:

Note

- It is important that the password should be 6 characters long. If you do not adhere to this pre-requisite, you will see a system message that reads **Password must be at least 6 characters long**.

Pre-Requisites

The installation process requires certain environmental variables to be set prior to starting the installation. You must ensure that these requirements are met before starting the installation. You are requested to refer to the Release Notes for the latest updates on hardware or software requirements and the OFSAAI Installation Manual for the environment variables.

Environment

Installation of Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product requires the OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit - Oracle 11g R2 (RAC) (11.2.0.2.0) – OBIEE (11.1.1.6.1) of **Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 for OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit**, to be installed in either a single-tier or multi-tier environment. It is implicit that all base software versions and patch levels required by the OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit version of Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 is available and adhered to. The supported web-servers are Tomcat 7.0.19, Websphere 7.0.0.17 and Web logic 10.3.5.0.

Note

- Linux 6 is not supported for PRMGR v6.1 even though AAI supports it. PRMGR v6.1 is not qualified on Solaris 5.11.
- The Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) installer download contains only the ERwin XML file that is required for uploading the model. This file is sufficient to install the v6.1 (6.1.0.0.0) product. However, this XML file cannot be opened in the ERwin Data modeler tool and hence cannot be used for any data model customization. ERwin file is delivered as a patch and need to be downloaded separately. This ERwin file should be used for any customization of the data model. Reference bug / patch where ERwin file can be downloaded is Bug 16183020 - PM-TP 6.1.0.0.0 DATA MODEL.

The OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit - Oracle 11g R2 (RAC) (11.2.0.2.0) version of Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0, once installed must be configured.

- **Install FTP v6.1 before Pricing Management Installation.**

These one-offs are only required when installing v6.1 on Infrastructure 7.3.2.0.0 or 7.3.3.0.0; higher versions of Infrastructure will incorporate the fixes represented by these one-offs.

- Bug 14766836 - BREADCRUMB IS SHOWING 'LIMITS SUMMARY\$' INSTEAD OF 'LIMITS SUMMARY'.
One-Off Patch : - 14766836_GENERIC.zip
ML version - 7.3.2.0.10
- Bug 14359454 - NEW COLUMN UDP FOR IDENTIFYING ECONOMIC VALUE RELATED COLUMNS
One-Off Patch : - 14359454_GENERIC.zip
ML version - 7.3.2.0.11

- Bug 14676961 - ERROR WHILE OPENING MEMBER SCREEN UNDER DIMENSION MANAGEMENT
One-Off Patch : - 14676961_GENERIC.zip
ML version - 7.3.2.0.12
- Bug 16066102 - OBJECT MIGRATION EDIT: TP/ALM SHARED OBJECTS DISPLAYED IN DUPLICATE, CANNOT SAVE
One-Off Patch : - 16066102_GENERIC.zip
ML version - 7.3.2.0.20

Note: Above mentioned patches are not required if platform 7.3.2.1 has been already applied.

Front-End Access

- Internet Explorer 8.0/9.0
- Java Plug-in 1.6.0_21
- Acrobat Reader 8.0
- The screen resolutions supported are 1024*768 and 1280*1024

Note

- Ensure that Java Plug-in is enabled in the browser settings.

Installing Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product

Note: If you want to create ETL Application and source for this product, then the jdbc url should be in following format. Other formats are not supported in this version.

jdbc:oracle:thin:@<HOST_NAME>:<PORT_NO>:<ORACLE_SID>

Pre-Installation Activities

The following is the Pre Installation checklist to ensure the readiness to start installing Oracle Financial Services Pricing Management Product:

- Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 must be successfully installed on OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit - Oracle 11gR2 (RAC) (11.2.0.2.0).

- If Infrastructure installation is on multitier environment, Execute the following commands in the DB Layer terminal

```
chmod -R 777 < ftpshare folder >
```

- Navigate to ftpshare folder and set the *umask* shown as below, this will make sure all the new files created will have 666 file permission.

```
cd < ftpshare folder >
```

```
umask 0000
```

- Execute `.profile` .
- The Config and atomic schema should be two distinct oracle database users.
- Please execute “privileges_atomic_user.sql” from DBA user. This will provide required privileges for atomic schema.
- Please copy the entire PRMGR v6.1.0.0.0 installer download directory to the server location (Including the DataModel directory). Please give read, write and execute permission to all the files present in this directory.
- Please specify the log file path and name in the log4j.xml. Please update the “value” attribute marked in the following picture

```
<!DOCTYPE log4j:configuration SYSTEM "log4j.dtd">
<log4j:configuration xmlns:log4j="http://jakarta.apache.org/log4j/">
<appender name="ConfigReveleusFileAppender" class="org.apache.log4j.RollingFileAppender">
  <param name="file" value="/u02/setupkit/ALM60/log/FTP60.log"/>
  <param name="Append" value="true"/>
</appender>
</log4j:configuration>
```

Figure 1: Log4j.xml file configuration

- Please make sure the path given in the log4j.xml file has read/write/execute permission.
- Please execute the “config_table_privileges_for_atomic_user.sql” script in configuration schema. This file will be present inside \$FIC_HOME directory.
- Please make sure FICServer is up and running before proceeding for installation.

Pre-Upgrade Activities

This section is applicable only for customers upgrading from earlier version.

Back-up of Database schema and Files

Back-up existing config and atomic schema of the information domain that is being upgraded. This can be used to restore back the application, in case of any failures during upgrade.

Back-up FTPSHARE and \$FIC_HOME folders of your existing environment.

Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product Installation

The Oracle Financial Services Analytical Applications Infrastructure Product comprises of components that are installed in Web, Application & Database layer. Hence if you have installed Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 in a multi-tier architecture, the Oracle Financial Services Pricing Management Product installer must be invoked on each of the machines that host the Oracle Financial Services Analytical Applications Infrastructure tier.

For a Single-tier installation, the installer is required to be invoked only once on the machine that hosts all the Oracle Financial Services Analytical Applications Infrastructure tiers.

This section describes the installation process where the Three Product setup components are installed on separate machines in with the Product installation on separate machines. Machine A will be used to install Product Application Layer components, Machine B will be used to install Product Database Layer components and Machine C will be used to install Product Web Layer components.

Note

This section holds applicable if Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 is installed on OEL/RHEL 5.3 / 5.5, Solaris 5.10 and AIX 5.3 (ML12) / AIX 6.1 (ML07), 64 bit - Oracle 11g (RAC) on separate machines A, B and C respectively.

Refer to section on "Silent Installation", if a silent installation is required

Machine A – Product App Layer

Step 1

To begin Oracle Financial Services Pricing Manager product installation, execute Setup.sh.



Figure 2: Installation Splash Screen

Step 2




Figure 3: Introduction Screen

Upon invoking the installer, the **Introduction** screen will display the pre-requisites for installation. Ensure that the pre-requisites are satisfied before you proceed.

Step 3

Please choose the log mode for this installer. In case, if Debug is selected, the Passwords will be printed in the Log File.




Figure 4: Log Mode Option Screen

Step 4

Please provide the 9 digit Customer Identification number provided during the OFSAAI installation.




Figure 5: Customer ID Input Screen

Click **Next** to continue.

Step 5

The **Pre Setup Information** screen requests for setup information.

Select the appropriate Oracle Financial Services Analytical Applications Infrastructure layer that has been installed on the machine.

Example **AppLayer**




Figure 6: Pre Setup Information Screen – Choose Layer to Install

Note

- For a single-tier Oracle Financial Services Analytical Applications Infrastructure installation, you must select App Layer, DB Layer and Web layer. For a multi-tier Oracle Financial Services Analytical Applications Infrastructure installation, select the corresponding layer installed on the machine.

Step 6

This panel seeks information on whether a new infodomain has to be created or the existing infodomain to be used for apps installation. Please choose the desired option.




Figure 7: Pre Setup Information Screen – Infodomain type

Click **Next** to continue.

Step 7-i

If the option “New Infodomain” was chosen in the previous panel then the following panel will be next displayed which will seek information of the following details to create infodomain.

Please specify a DB name for the new infodomain. Please make a TNS entry with the DB name specified in the tnsname.ora file in the oracle server.

Please enter the newly created atomic schema user name, password, jdbc url in relevant fields.

Click **Next** to continue




Figure 8: Database details for the new Infodomain

Step 7-ii

If the option “New Infodom” was chosen in the previous panel then the following panel will be displayed following the panel 7-i which will seek further information of the following details to create infodom.

Please specify the name and description for the new infodom to be created.

Please specify a segment name to be created.

Note: Here, recommended Infodom Name limit is max 10 characters, and Segment name should not exceed 10 characters.

Also specify the Application server and database server log path for infodom maintenance (to be created)




Figure 9: Infodom details for creation of new Infodom

Click **Next** to continue.

Step 7-iii

If the option “New Infodom” was chosen in the previous panel then the following panel will be displayed following the panel 7-ii which will display the pre-infodom creation details. Please check and verify all the details before proceeding to the next step.




Figure 10: Pre Infodom Creation Summary

Click **Next** to continue creation of information domain. A new information domain will be created on clicking Next.

Step 7-iv

If the option “Existing Infodom” was chosen in the Step 6 then the following panel will be displayed which will prompt to select the infodom from list of infodoms present in the setup, enter segment code and enter the application schema’s TNS name.




Figure 11: Installation in Progress

Step 8

PRMGR v6.1 (6.1.0.0.0) data model is packaged as part of PRMGR v6.1 (6.1.0.0.0) product installer and will be installed as part of the upcoming steps, if required.

The following screen prompts the user to opt for model upload process through installer.




Figure 12: Pre-Setup Information

Clicking 'No' implies that PRMGR v6.1 (6.1.0.0.0) model has been uploaded into information domain prior to this installation.

Clicking 'Yes' will proceed with the PRMGR v6.1 (6.1.0.0.0) model upload process as part of the installation.

If the user selects "Yes", Step 9 and 10 will be performed. will appear.

Upon selecting "No..", Step 9 to 10 will be skipped.

Click **Next** to proceed.

Step 9

The following panel prompts the user to choose whether the released version of Datamodel or the customized datamodel to be uploaded.

On selecting 'Released Data Model' option, installer uploads the PRMGR v6.1 (6.1.0.0.0) data model that is packaged as part of the PRMGR v6.1 (6.1.0.0.0) product.

On selecting 'Customized Data Model' option, installer allows the user to select the data model. Please choose desired option.

Click **Next** to proceed.




Figure 13: Pre – Setup information

Step 10

If the option “Customized Data Model” was chosen then the following panel will be displayed prompting user to select the customized data model located in the machine.

Please choose the customized datamodel file from the server.

Note:

The data model xml file should be available in the server.

In case the installation is being performed on an existing information domain, the data model that is planned to be selected in this panel should be merged with the data model that was previously uploaded in the information domain.

In case the installation is being performed on a new information domain, data model that is either customized or merged with other data models can be selected in this panel.




Figure 14: Pre – Setup information

Step 11

The following panel displays pre-model upload details.

Please verify the details before proceeding to the next step.

Click **Next** to proceed for model upload.




Figure 15: Pre – Model Upload Summary

Clicking on 'Next' will start the model upload process. This process will take some time depending on the size of the data model and available physical memory in the environment. User will not be able to take any further action on the screen, until the model upload process is complete. Also, this step cannot be rolled back.

If the model upload fails, then a pop-up message with relevant error and the log file path will be displayed.

Review errors and take relevant action. Continue with this step until the model upload is successful and the installer takes the user to next step.

Note

Some of the common errors during model upload are

- Insufficient heap memory on the client machine
- Possible reason/resolution: The java memory settings in "reveusstartup.sh" located in \$FIC_APP_HOME/common/FICServer/bin directory should be increased.
- Error while getting the Erwin File path
- Possible reason/resolution: Restart the FICServer.
- Error in Upload Operation :
"FAILED WHILE SUPER CATEGORY - SUB CATEGORY RELATIONS HANDLINGDELETING"
- Possible reason/resolution: Incorrect Erwin.xsl file version in \$FIC_APP_HOME/common/FICServer/conf directory. Please copy appropriate version Erwin.xsl file from the path \$FIC_APP_HOME/common/FICServer/conf/Erwin<ERwin_version> directory to \$FIC_APP_HOME/common/FICServer/conf.

- Incremental/Sliced model upload might give errors in case there are NOT NULL columns that are being added to a table that already has rows or if the columns that are being dropped have values. Check the data model changes excel file for any such cases. In such a case, take a backup of the table and truncate the table. Insert records back into the table with a default value for the NOT NULL column.
- Navigate to the previous screen and proceed with the steps mentioned above.

Step – 12

The following panel seeks input from the user on whether to create new ETL application/source pair or use an existing one.

In case of upgrade, if customer selects an existing application/source pair, then existing ETL definitions under the source will be over-written with the packaged definitions. Customer can also choose to create a new application / source pair and then merge the changes between the packaged definition and their existing definitions offline.

Please choose a desired option.

Click **Next** to continue




Figure 16: Pre – Setup Information

Step 13-i

If the option "New application/source pair" was chosen then the following panel will be displayed seeking the application and source name for creation of the same.

Please specify all the details required for application and source creation.

Click **Next** to proceed.

Clicking 'Next' will create application and source within OFSAAI. Source model will also be generated. This process will take some time depending on the number of entities / attributes in the atomic schema. This step cannot be rolled back.




Figure 17: Pre – Setup Information

Note:

ETL Source will be created pointing to the information domain (atomic schema) that is specified during the installation.

Step 13-ii

If the option “Existing application/source pair” was chosen the following panel will be displayed prompting user to select app/source pair from the list of pairs already present.

Please choose the desired ETL application/source pair into which ETL definitions will be deployed.

Click **Next** to proceed




Figure 18: Pre – Setup Information

Step 14

This panel displays all the pre-installation summary. Please verify all details and proceed.
Click **Install** to proceed.




Figure 19: Pre – Install Summary

Step 15

This panel displays the installation process. Please wait until it completes.




Figure 20: Installation is in progress

Step 16

The following screen displays the completion of installation of the Oracle Financial Services Pricing Manager Product Setup.

Click **Done** to exit.




Figure 21: Installation Complete

Machine B – Product Database Layer

Step 1

To begin Oracle Financial Services Pricing Manager product installation, execute Setup.sh.



Figure 22: Installation Splash Screen

Step 2




Figure 23: Introduction Screen

Upon invoking the installer, the **Introduction** screen will display the pre-requisites for installation. Ensure that the pre-requisites are satisfied before you proceed.

Step 3

Please choose the log mode for this installer. In case, if Debug is selected, the Passwords will be printed in the Log File.

Click **Next** to proceed.




Figure 24: Log Mode Option Screen

Step 4

Please provide the 9 digit Customer Identification number provided during the OFSAAI installation.




Figure 25: Customer ID Input Screen

Click **Next** to continue.

Step 5

The **Pre Setup Information** screen requests for setup information.

Select the appropriate Oracle Financial Services Analytical Applications Infrastructure layer that has been installed on the machine.

Example **Database Layer**




Figure 26: Pre Setup Information Screen – Choose Layer to Install

Note

- For a single-tier Oracle Financial Services Analytical Applications Infrastructure installation, you must select App Layer, DB Layer and Web layer. For a multi-tier Oracle Financial Services Analytical Applications Infrastructure installation, select the corresponding layer installed on the machine.

Step 6

This panel seeks information on whether a new infodomain has to be created or the existing infodomain to be used for apps installation. Please choose the desired option.




Figure 7: Pre Setup Information Screen – Infodomain type

Click **Next** to continue.

Step 7

If the option “Existing Infodomain” was chosen in the Step 6 then the following panel will be displayed which will prompt to select the infodomain from list of infodomains present in the setup, enter segment code and enter the application schema’s TNS name.




Figure 27: Pre Setup Information Screen

Step 8

This panel displays all the pre-installation summary. Please verify all details and proceed.

Click **Install** to proceed.




Figure 28: Pre – Install Summary

Step 9

This panel displays the installation process. Please wait until it completes.




Figure 29: Installation is in progress

Step 10

The following screen displays the completion of installation of the Oracle Financial Services Pricing Manager Product Setup.

Click **Done** to exit.




Figure 30: Installation Complete

Machine C – Product Web Layer

Step 1

To begin Oracle Financial Services Pricing Manager product installation, execute Setup.sh.




Figure 31: Installation Splash Screen

Step 2




Figure 32: Introduction Screen

Upon invoking the installer, the **Introduction** screen will display the pre-requisites for installation. Ensure that the pre-requisites are satisfied before you proceed.

Step 3

Please choose the log mode for this installer. In case, if Debug is selected, the Passwords will be printed in the Log File.

Click **Next** to proceed.




Figure 33: Log Mode Option Screen

Step 4

Please provide the 9 digit Customer Identification number provided during the OFSAAI installation.




Figure 34: Customer ID Input Screen

Click **Next** to continue.

Step 5

The **Pre Setup Information** screen requests for setup information.

Select the appropriate Oracle Financial Services Analytical Applications Infrastructure layer that has been installed on the machine.

Example **Web Layer**




Figure 35: Pre Setup Information Screen – Choose Layer to Install

NOTE

- For a single-tier Oracle Financial Services Analytical Applications Infrastructure installation, you must select App Layer, DB Layer and Web layer. For a multi-tier Oracle Financial Services Analytical Applications Infrastructure installation, select the corresponding layer installed on the machine.

Step 6

This panel seeks information on whether a new infodomain has to be created or the existing infodomain to be used for apps installation. Please choose the desired option.

Step 7

If the option “Existing Infodomain” was chosen in the Step 6 then the following panel will be displayed which will prompt to select the infodomain from list of infodomains present in the setup, enter segment code and enter the application schema’s TNS name.




Figure 36: Pre Setup Information Screen

Step 8

This panel displays all the pre-installation summary. Please verify all details and proceed. Click **Install** to proceed.




Figure 38: Pre – Install Summary

Step 9

This panel displays the installation process. Please wait until it completes.




Figure 39: Installation is in progress

Step 10

The following screen displays the completion of installation of the Oracle Financial Services Pricing Manager Product Setup.

Click **Done** to exit.




Figure 40: Installation Complete

Silent Installation

Silent installation is achieved via a properties file [Silent.props] that must be updated with proper values, before attempting to install using the silent mode.

The following table lists all the properties that need to be specified

Property Name	Description of Property	Permissible values	Comments
LOG_MODE	Mode for logging	0 = Debug 1 = General	Optional; Default : 0
CUSTOMER_ID	Customer id specified while installing OFSAAI	Not Applicable	MANDATORY
INSTALL_WEB	Install web-tier components	0 = No 1 = Yes	Default : 0
INSTALL_DB	Install database-tier components	0 = No 1 = Yes	Default : 0
INSTALL_APP	Install Application-tier components be installed	0 = No 1 = Yes	Default : 0
INSTALL_ADMIN_BI	Install admin-BI components	0 = No 1 = Yes	Default : 0 Applicable only if INSTALL_WEB=1 OR INSTALL_DB=1
INFODOM_NAME=	Information Domain(infodom)	Not Applicable	MANDATORY
SEGMENT_CODE=	Segment Code	Not Applicable	MANDATORY
TABLESPACE	Tablespace name	Not Applicable	MANDATORY
INFODOM_TYPE	New Infodom or Existing Infodom	0 = New 1 = Existing	# Specify Infodom Type Mandatory if this an App Layer Installation i.e you have specified INSTALL_APP=1
APPL_TNS	TNS Name of the Infodom database	Not Applicable	MANDATORY

APPL_USER	User-id of the Database Schema for new Infodom	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
APPL_PWD	Password of the Database Schema for new Infodom	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
APPL_URL	JDBC Connection String of the the Database Schema for new Infodom	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
RAC_STATUS	whether the Database Schema for new Infodom is a RAC database	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
INFODOM_DESC	description for the Database Schema for new Infodom	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
APPFTP_LOG_PATH=	Infodom Maintenance log path(to be created) for the new Infodom for applayer	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and

			INFODOM_TYPE=0
DBFTP_LOG_PATH	Infodom Maintenance log path(to be created) for the new Infodom for DBLayer	Not Applicable	# Mandatory if this an App Layer Installation and if you want to create a new infodom # i.e you have specified INSTALL_APP=1 and INFODOM_TYPE=0
OBI_HOST	Host Name of the OBIEE Server	Not Applicable	Applicable if INSTALL_ADMIN_BI=1
OBI_PORT	Port Number of the OBIEE Server	Not Applicable	Applicable if INSTALL_ADMIN_BI=1
OBI_CONTEXT	Context Name of the OBIEE Server	Not Applicable	Applicable if INSTALL_ADMIN_BI=1
UPLOAD_MODEL	wheter you want to perform Model Upload	0 = No 1 = yes	Mandatory if INSTALL_APP=1
MODEL_TYPE	released datamodel or customized datamodel	0 = released 1 = customized	Mandatory if INSTALL_APP=1
DATAMODEL	the path for the cutomized datamodel	Not Applicable	# Mandatory only if you want to upload the customized datamodel # i.e you have specified MODEL_TYPE=1
DM_DIRECTORY	the file name for the cutomized datamodel	Not Applicable	# Mandatory only if you want to upload the customized datamodel # i.e you have specified MODEL_TYPE=1
ETL_APP_NAME	The ETL application name	Not Applicable	# Mandatory if this an App Layer installation # i.e you have specified INSTALL_APP=1
ETL_SRC_NAME	The ETL Source into which the Table-2-Table ETL definitions on staging tables will be deployed	Not Applicable	This Source must be mapped to the above ETL Application

ETL_APPSRC_TYPE	create new ETL App/Src pair or use an existing one	0 = New 1 = Existing	# Mandatory if this an App Layer installation # i.e you have specified INSTALL_APP=1 # 0 = If you want to create a new ETL app/src pair # 1 = If you want to use an existing pair
ETL_APP_DESC	Please give description for the ETL App	Not Applicable	# Mandatory if you want to create new ETL app/src pair #i.e you have specified ETL_APPSRC_TYPE=0
ETL_SRC_DESC	Please give description for the ETL Src	Not Applicable	# Mandatory if you want to create new ETL app/src pair #i.e you have specified ETL_APPSRC_TYPE=0

How to install in Silent Mode

- The installer folder contains a template file "Silent.template"
- Create a copy of this file and rename the copy as "Silent.props"
- Edit the file "Silent.props" and specify the parameters as per the requirements
- On the UNIX Command prompt, execute the following command
 - o "Setup.sh SILENT"
- Refer to the console log [or the file preinstall.log] for any error messages.

Post Installation Activities

Oracle Financial Services Analytical Applications Infrastructure Server Memory Configuration

The Oracle Financial Services Analytical Applications Infrastructure Application Server is started using `reveleusstartup.sh`. This file can be edited for setting customized memory settings, garbage collector settings depending on the available hardware configuration. Please raise an SR in support.oracle.com if you have any queries related to EPM applications.

Once the installation of Oracle Financial Services Pricing Management Product is completed, you must perform the following steps.

- Check the Log file (The path and file name specified in the `log4j.xml`).
- Ignore the following errors in the log file:
 - Error: ORA-02260: table can have only one primary key.
 - Error: ORA-00955: name is already used by an existing object.
 - Error: ORA-00001: unique constraint (<<UNIQUE KEY NAME>>) violated.
 - Error: ORA-02275: such a referential constraint already exists in the table.
 - Error: ORA-01430: column being added already exists in table.
 - Error: ORA-02303: cannot drop or replace a type with type or table dependents.
- Ignore following errors if the setup is upgraded from 6.0.1/6.0.2/6.0.3 or if Funds transfer Pricing v6.1.0.0.0 and Hedge Management solution v6.1.0.0.0 and Asset Liability Management v6.1.0.0.0 and Pricing Management v6.1.0.0.0 is/are installed in the same infodomain.
 - Error:ORA-01442: column to be modified to NOT NULL is already NOT NULL
 - Error:ORA-01451: column to be modified to NULL cannot be modified to NULL
 - Ignore these errors for FSI_M_PROD_CHARACTERISTICS
 - Error:ORA-00904: "RATE_PRICING_OPTION_P": invalid identifier
 - Error:ORA-00904: "BOUGHT_SOLD_FLG_P": invalid identifier
 - Error:ORA-00904: "RATE_FLOOR_LIFE_P": invalid identifier
 - Error:ORA-00904: "NET_MARGIN_P": invalid identifier
 - Error:ORA-00904: "GROSS_MARGIN_P": invalid identifier
 - Error:ORA-00904: "ACCR_BASIS_P": invalid identifier
 - Error:ORA-00904: "ADJ_TYPE_P": invalid identifier
 - Error:ORA-00904: "COMP_BASIS_P": invalid identifier
 - Error:ORA-00904: "MIN_RATE_CHANGE_P": invalid identifier

- Error:ORA-00904: "BINARY_RANGE_CAP_P": invalid identifier
 - Error:ORA-00904: "BINARY_RANGE_FLOOR_P": invalid identifier
 - Error:ORA-00904: "RATE_PRICING_OPTION_R": invalid identifier
 - Error:ORA-00904: "BOUGHT_SOLD_FLG_R": invalid identifier
 - Error:ORA-00904: "RATE_CAP_LIFE_R": invalid identifier
 - Error:ORA-00904: "NET_MARGIN_R": invalid identifier
 - Error:ORA-00904: "GROSS_MARGIN_R": invalid identifier
 - Error:ORA-00904: "ACCR_BASIS_R": invalid identifier
 - Error:ORA-00904: "ADJ_TYPE_R": invalid identifier
 - Error:ORA-00904: "COMP_BASIS_R": invalid identifier
 - Error:ORA-00904: "MIN_RATE_CHANGE_R": invalid identifier
 - Error:ORA-00904: "BINARY_RANGE_CAP_R": invalid identifier
 - Error:ORA-00904: "BINARY_RANGE_FLOOR_R": invalid identifier
- o Add the below mentioned entries in excludeURLList.cfg file located in the path \$FIC_WEB_HOME/webroot/conf/
 - /fsapps/common/batchCreate.action
 - /fsapps/common/batchEdit.action

Note: Copy the above information into notepad, and then copy it from notepad into cfg file. Take extra care to avoid copying formatting characters into the cfg file.

- o The web.xml under the path \$FIC_WB_HOME \webroot\WEB-INF\ should have Resource tag, if not present add the tag and replace ORDEMO with the INFODOM name.

```
<resource-ref>
    <description>DB Connection ORDEMO</description>
    <res-ref-name>jdbc/ORDEMO</res-ref-name>
    <res-type>javax.sql.DataSource</res-type>
    <res-auth>Container</res-auth>
</resource-ref>
```

Note: Copy the above information into notepad, and then copy it from notepad into xml file. Take extra care to avoid copying formatting characters into the xml file.

Configuration in Websphere Application Server

- Create JDBC Provider for the configuration of connection pool for the above created Infodom (Refer to: the chapter *Creating the JDBC Provider* of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual).
- Create a data source to access the data from the database. (Refer to: the chapter *Creating the Data Source* of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual)
- After creating a Data Source, Click the newly created Data Source (\$DATA_SOURCE\$) and navigate to the path

Data sources>\$DATA_SOURCE\$>Connection pools

And set the values for Connection timeout to 0 seconds, Maximum connections to 100 connections, Minimum connections to 10 connections as shown in the below figure.




Figure 41:

- Expand the **Server Types** under **Servers** option in the LHS menu. Click on **WebSphere application servers** option. This will display the **Application Servers** page.

Navigate to the **Web Container** option of the application server, under **Custom properties**, add a new property **com.ibm.ws.webcontainer.invokefilterscompatibility** and set the value to **true** Save the new property. Use below figure for reference




Figure 42:

Configuration in Tomcat Application Server

- Copy \$ORACLE_HOME/jdbc/lib/ojdbc6.jar to the path \$TOMCAT_DIRECTORY/common/lib/
- Edit the server.xml present under the path \$TOMCAT_DIRECTORY\conf\ with the below changes, which is required for connection pooling.

Note: Copy the following information into notepad, and then copy it from notepad into xml file. Take extra care to avoid copying formatting characters into the xml file.

```
<Context path="/" $CONTEXTNAME$ " docBase=" $APP_DEPLOYED_PATH$ "
debug="0" reloadable="true" crossContext="true">
```

```
  <Resource auth="Container"
    name="jdbc/ $INFODOM_NAME$"
    type="javax.sql.DataSource"
    driverClassName="oracle.jdbc.driver.OracleDriver"
    username=" $ATOMICSCHEMA_USERNAME$"
    password=" $ATOMICSCHEMA_PASSWORD$"
    url=" $JDBC_CONNECTION_URL "
    maxActive="100"
    maxIdle="30"
    maxWait="10000"
    removeAbandoned="true" removeAbandonedTimeout="60"
    logAbandoned="true"/>
```

```
</Context>
```

NOTE;

- \$TOMCAT_DIRECTORY\$ should be replaced by Tomcat application installed path
- \$CONTEXTNAME\$ should be replaced by Oracle Financial Services Analytical Applications Infrastructure context name
- \$APP_DEPLOYED_PATH\$ should be replaced by the Oracle Financial Services Analytical Applications Infrastructure application deployed path

- \$INFODOM_NAME\$ should be replaced by Infodom Name
- \$ATOMICSHEMA_USERNAME\$ should be replaced by Atomic schema database user name
- \$ATOMICSHEMA_PASSWORD\$ should be replaced by Atomic schema database password
- \$JDBC_CONNECTION_URL should be replaced by JDBC connection string

Ex: jdbc:Oracle:thin:<IP>:<PORT>:<SID>

jdbc:oracle:thin 10.80.50.53:1521:soluint

- Configuration in Weblogic Application Server
- Create JDBC Provider for the configuration of connection pool and a data source to access the data from the database for the above created Infodom (Refer to: the chapter Creating data Source – WebLogic of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual).
- After creating a Data Source, Click the newly created Data Source (\$DATA_SOURCE\$) and navigate to the path

Home >Summary of Services: JDBC >Summary of JDBC Data Sources >JDBC Data Source-<INFODDOM_NAME>

And set the values for Initial Capacity to 10, Maximum capacity to 100 ,Capacity Increment by 1, Statement Cache Type to LRU and Statement Cache size to 10 as shown in the below figure.

The screenshot shows a configuration page for a JDBC Data Source. It contains several input fields and a dropdown menu, each with a corresponding help text link:

- Initial Capacity:** Input field with value 10. Help text: "The number of physical connections to create when creating the connection pool. [More Info...](#)"
- Maximum Capacity:** Input field with value 100. Help text: "The maximum number of physical connections that this connection pool can contain. [More Info...](#)"
- Capacity Increment:** Input field with value 1. Help text: "The number of connections created when new connections are added to the connection pool. [More Info...](#)"
- Statement Cache Type:** Dropdown menu with value LRU. Help text: "The algorithm used for maintaining the prepared statements stored in the statement cache. [More Info...](#)"
- Statement Cache Size:** Input field with value 10. Help text: "The number of prepared and callable statements stored in the cache. (This may increase server performance.) [More Info...](#)"

At the bottom of the form, there is a "Save" button and a link to "Advanced" settings.

Figure : 43

- All Oracle Financial Services Analytical Applications Infrastructure Servers must be shut down.
- Oracle 11g service must be running.
- You must have the following information available and handy before you start the installation:
- The FTPshare path as configured in Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0.
- The name of the Information Domain in Oracle Financial Services Analytical Applications Infrastructure 7.3.2.0.0 or 7.3.3.0.0 into which the Oracle Financial Services Pricing Management data model has been uploaded.

- The Oracle Financial Services Analytical Applications Infrastructure User ID that has access to the above Information Domain.

Deploy the EAR or WAR file

- If the Web-Server is Tomcat then re-create and re-deploy the WAR file (OFSAAI war file). (Refer to: Tomcat WAR Files Creation and Tomcat WAR Files Deployment of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual). Ensure that the previously deployed applications in Tomcat are removed before starting the re-deployment. Start all OFSAAI servers. All servers should be directly started in the server.
- If the Web-Server is Websphere re-create and re-deploy the WAR file (OFSAAI war file). (Refer to: Websphere WAR Files Creation and Websphere WAR Files Deployment of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual). Ensure that the previously deployed applications in Websphere are removed before starting the re-deployment. Start all OFSAAI servers. All servers should be directly started in the server.
- If the Web-Server is Weblogic re-create and re-deploy the WAR file (OFSAAI war file). (Refer to: Weblogic WAR Files Creation and Weblogic WAR Files Deployment of the Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0 Installation Manual). Ensure that the previously deployed applications in Weblogic are removed before starting the re-deployment. Start all OFSAAI servers. All servers should be directly started in the server.
- Start all Oracle Financial Services Analytical Applications Infrastructure Servers.

Note

If you need assistance in starting the servers, then refer to *Starting Oracle Reveleus Servers* in the Installation Guide Oracle Financial Services Analytical Applications Infrastructure 7.3.3.0.0.

.profile should be executed before starting any activity from the console.



Installation Manual

March 2015

Oracle Financial Services Pricing Management v6.1 (6.1.0.0.0) Product

Oracle Corporation

World Headquarters

500 Oracle Parkway

Redwood Shores, CA 94065

U.S.A.

Worldwide Inquiries:

Phone: +1.650.506.7000

Fax: +1.650.506.7200

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.