

Oracle® Application Integration Architecture

Agile Product Lifecycle Management Integration Pack for SAP:
Design to Release Implementation Guide

Release 11.2

E36364-01

September 2012

The Agile Product Lifecycle Management Integration Pack for SAP: Design to Release implementation guide is a valuable resource for administrators and developers involved in the implementation, administration and deployment of Oracle's next-generation integrated enterprise PLM processes provided by Oracle Application Integration Architecture (AIA) Pre-Built Integrations Release 11.3.

The first part of this guide focuses on understanding the pre-built integration between Agile PLM and SAP. It also lists the various assumptions and constraints, process flows, interfaces and integration services used by Agile PLM Pre-Built integrations.

The second part of this guide discusses the prerequisites, post installation configuration steps, cross-references and National language support (NLS) required for integrating Agile PLM with SAP.

Oracle Application Integration Architecture Agile Product Lifecycle Management Integration Pack for SAP:
Design to Release Implementation Guide, Release 11.2

E36364-01

Copyright © 2001, 2012, Oracle and/or its affiliates. All rights reserved.

Primary Author: Oracle Corporation

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle America, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Contents

Preface	3
What's New in this Guide	3
Common Oracle AIA Pre-Built Integration Guides	3
Additional Resources.....	4
Chapter 1: Overview of Agile PLM Integration for SAP	5
Architecture of Agile PLM to SAP Integration.....	6
SAP to Agile Processes.....	7
Components of Agile PLM Integration for SAP	8
Chapter 2: Process Integration for Change Order Release	11
Change Order Release Process.....	11
CO Release Process Integration Solution Assumptions	17
CO Release Integration Sequence.....	18
CO Release Services Orchestration.....	19
AIA Services for CO Release	22
Integration Services for CO Release.....	25
CO Release Integration Customization Points	28
Properties and DVMs for CO Release.....	32
Chapter 3: Process Integration for New Part Request	33
NPR Services Orchestration.....	38
AIA Services for NPR	40
Properties and DVMs for NPR.....	44
Chapter 4: Process Integration for Item Attribute Update	45
IA Update Process Integration Solution Assumptions	47
IA Update Integration Sequence	48
IA Update Services Orchestration	49
AIA Services for IA Update.....	50
IA Update Integration Customization Points.....	53
Essential Properties and DVMs for IA Update.....	53
Chapter 5: Implementing the Process Integration Pack	54
Prerequisites.....	55
Setting up the Participating Applications	55
Agile PLM	55
Setting up SAP	62
SQL Script for Loading Cross-Reference Data	65
Identifying Cross-Reference Data	69

Populating Cross-References.....	75
Configuring the Integration	79
Domain Value Maps	97
Application Interfaces	102
Handling Errors.....	105
Chapter 6: Customizations	107
Customizing the Transformations.....	107
Customization in Agile	108
Customization in SAP	109
User Exits	110
Appendix A: National Language Support in Agile – SAP Integration.....	113
Requester Flows.....	113
Provider Flows.....	113
Appendix B: Functionalities Available	115
Appendix C: Agile to SAP Entity Maps.....	119
Bill of Materials Mappings.....	119
Item EBO Mappings	120
Item Attribute Update Mappings	125
Engineering Change Order EBO Mappings	125
Appendix D: Queue Management.....	127
Queue Management Solution.....	128
Queue Manager Services.....	130
Transformations.....	133
Queue User Interface Application.....	135
Appendix E: Troubleshooting	141
Engineering Change Order Issues	141
Installation Issues	141
Queue Issues	142
SAP Issues	144
Agile Issues	146

Preface

Welcome to the Agile Product Lifecycle Management Integration Pack for SAP: Design to Release Implementation guide.

What's New in this Guide

- The Oracle Application Integration Architecture Installation and Upgrade Guide for Pre-Built Integrations is restructured into a general installation chapter with an individual configuration and deployment chapter for each pre-built integration.
- The term process integration pack is replaced with the term pre-built integrations.
- The implementation guides are restructured into two parts: design and set up.
 - Part I - Design: This part provides functional overviews, activity diagrams, assumptions and constraints, and technical sequence diagrams and steps.
 - Part II - Set up: This part provides prerequisites, data requirements, and configuration steps.
- Starting with this release, these integrations are no longer available:
 - Oracle CRM On Demand Integration Pack for JD Edwards EnterpriseOne: Lead to Order
 - Oracle Workforce Administration Integration Pack for PeopleSoft Human Resources

Common Oracle AIA Pre-Built Integration Guides

- Oracle Application Integration Architecture Pre-Built Integrations 11.3 includes the following guides shared by all products delivered with this release:
- Oracle Application Integration Architecture Installation and Upgrade Guide for Pre-Built Integrations Release 11.3.

This guide provides an overview of the installation process, including how to install, configure, and deploy your pre-built integrations. The steps required to upgrade your pre-built integrations to the latest release are also provided.

- Oracle Application Integration Architecture Pre-Built Integrations 11.3:

Utilities Guide

- This guide describes:
 - How to work with and configure Session Pool Manager (SPM), which is a service in the Oracle SOA Suite web server whose primary function is to manage a pool of web server session tokens that can be reused by BPEL flows.
 - How to deploy and configure the AIACompositeScheduler. This is a utility component that is used by pre-built integrations to schedule a service-oriented architecture (SOA) composite to be invoked at the specified time interval.
- Oracle Application Integration Architecture Pre-Built Integrations 11.3: Product-to-Guide Index. The product-to-Guide index lists the guides that provide information for each product delivered in this release.

Additional Resources

The following resources are also available:

- **Oracle Application Integration Architecture Foundation Pack:**

Oracle AIA Pre-Built integrations require Foundation Pack 11.1.1.6, RUP patch 14253266 or later be installed. Refer to the Foundation Pack documentation library on OTN to download the Foundation Pack guides at http://docs.oracle.com/cd/E23943_01/aia.htm.

- **Oracle Application Integration Architecture: Product-to-Guide Index:**

Oracle Technology Network: <http://www.oracle.com/technetwork/index.html>

- **Known Issues and Workarounds:**

My Oracle Support: <https://support.oracle.com/>

- **Release Notes:**

Oracle Technology Network: <http://www.oracle.com/technetwork/index.html>

- **Documentation updates:**

Oracle Technology Network: <http://www.oracle.com/technetwork/index.html>

Chapter 1: Overview of Agile PLM Integration for SAP

This chapter discusses:

- Architecture of Agile PLM Integration
- Agile PLM to SAP process flows
- SAP to Agile PLM process flows
- Solution Design Assumptions and Constraints
- Components of Agile SAP Design To Release PIP

This integration between Agile PLM and SAP R/3 is designed to address the primary requirements for product information synchronization between Agile Product Collaboration and SAP.

The Agile PLM pre-built integration is aimed at enabling product development process between Agile PLM and SAP. This integration allows rapid implementation of Agile's next generation integrated enterprise PLM processes and helps customers reduce cost and mitigate risks associated with third party and custom integrations.

This integration aims to meet the following objectives:


- Follows a business process flow
- Maintains data accuracy and integrity at all times in both the systems
- Allows for easy configuration of business process flow, data field mappings, and transformations tools, such as Rules, Lookups, and User Exits
- Provides for robust exception handling including ease of understanding for end user, strong notification configurability, and easy troubleshooting

These are the functionalities of the Agile to SAP integration:

- Manufacturing release of new product definition and product launch
- Change Management of previously launched products
- Bi-directional synchronization of Engineering Change status and Item Cost information, from SAP to Agile PLM
- Tracking and monitoring of the change processing queue

Architecture of Agile PLM to SAP Integration

The Agile PLM to SAP Integration is requester-provider type integration as shown in this diagram:



Agile to SAP Processes

These are the Agile to SAP Processes:

- Change Order Release
- New Part Request

Change Order Release

During a product design phase, new products and parts are introduced and existing parts go through design changes. Change Orders (CO) are used to release information about the attributes and design information of a part to the manufacturing system.

The Change Order Release Process (CORP) constitutes of New Part/Product Release (PREL) and Product Design Modification flows of Agile PLM.

While Agile is the system of record for item description, design, specs and many other pieces of information above, the ERP system typically has many more attributes and placeholders for information than the PLM system. Hence, the change order release needs to be updated in ERP system.

The release of a change order in Agile PLM system acts as a trigger for the synchronization of product design information with ERP system. Agile system being a system of records for product design data, the synchronization process typically involves transfer of the released revision of product design from Agile PLM to the manufacturing system. The Agile system can be configured to trigger the synchronization process on any Change Order status as required.

Change Order Release Process as well as New Product Release processes use the same integration sequence. [Chapter 2 - Process Integration for Change Order Release](#) describes the integration details for both.

New Part Request

A New Part Request (NPR) process can be triggered On-demand by user. This is a synchronous process, which reserves and fetches the part number from the SAP system.

See [Chapter 3 - Process Integration for New Part Request](#) for complete information.

SAP to Agile Processes

Though Agile is considered as system of records, there might be several part attributes that can be maintained within ERP. The Product Data Management (PDM) group might require information on these attributes within PLM item data. To provide the PDM group with this information within Agile item object, SAP to Agile process enable synchronous or batch update of the configured field values from ERP in to designated item fields of PLM.

For example update in cost of an item in ERP would get updated in Agile PLM in batch mode, based on the back ground schedule of job in SAP.

Solution Design Assumptions and Constraints

These are the design assumptions and constraints:

Design Assumptions

- Agile Content Server will be the used for Events to trigger the payload from Agile to Integration.
- This design assumes that the following statements are true:
 - There will be pre-defined blank templates made available for Custom fields
 - Transformation logic for classification elements will be pre-coded in the Out-of-the-Box XSL, but you may need to modify it to suit your PLM implementation

- This design leverages AIA error handling framework.

Design Constraints

- In few cases configuration driven XSLT may not reflect the changes immediately and may require a restart as the main XSL sheet would get cached after a successful compilation
- ACS limits the Events to be triggered from workflow only for the Change Status which can be used for this Integration.
- Error handling capabilities of this integration are constrained by the capabilities of AIA framework.

Components of Agile PLM Integration for SAP

This integration has the following components:

- Agile PLM Content Service (ACS)
- Software Development Kit (SDK)
- Agile Process extensions (PX)
- Web Service Extensions (WSX)
- Oracle Application Integration Architecture (AIA) Foundation Pack
- SAP

Agile Content Service (ACS)

Agile Content Service is an event-driven XML-based publishing service that makes the product record available to a wide variety of business applications and users, both internally and across the global manufacturing network. In addition to allowing employees and supply chain partners to publish the product record on demand, Agile Content Service can be configured to automatically publish the Item Master and BOM changes during any phase of the product lifecycle to multiple destinations, ensuring that everyone is working with up-to-the-minute information.

The output generated by an ACS module is an aXML file or a PDX package.

Software Development Kit (SDK)

SDK contains a collection of tools; application programming interfaces (APIs), sample applications, and documentation. You use SDK to build custom applications that access Agile application server functionality. By using Agile SDK, you can create programs that perform tasks automatically in Agile PLM.

Agile SDK enables the following operations:

- Integrate Agile PLM with SAP or other custom applications.
- Develop applications to process product data.
- Perform batch operations against the Agile Application Server.

Agile SDK has the following modules:

Agile API: A Java API with interfaces that expose Agile PLM business objects. Use Agile API to create additional Agile PLM clients. You can also use it as part of an extension developed using web service extensions (WSX) or process extensions (PX).

Process Extension(PX): A framework that allows Agile PLM customers to extend the functionality of Agile PLM clients by adding external reports, user-driven and workflow-driven customized actions, customized tools, and customized automatic number sources. PX helps in binding the data in Agile PLM with other applications.

The new part request is the only process integrations that use PX to extract Agile PLM's data and send it to ABCS.

Web service Extension (WSX): A framework that allows Agile PLM customers to extend the functionality of the Agile PLM server and expose customer-specific solutions using a web service. WSX is a Web service engine enabling communication between Agile PLM and disparate systems both internal and external, including Enterprise Resource Planning (ERP) systems. WSX can be used to provide content to exchanges, reports, and custom applications and import product content data from ERP and other supply chain applications. WSX can simplify the process for aggregating raw product content and making critical product content available in realtime to other core systems.

For more information about Agile PLM components, see "*Agile Product Lifecycle Management Administrator Guide*" and "*SDK Developer Guide*."

Oracle Application Integration Architecture Foundation Pack

Oracle Application Integration Architecture (AIA) Foundation Pack enables customers to simplify cross-application business process integrations using a standards-based, pre-built integration solution. Designed to promote rapid deployment, re-usability, and configurability of business processes, AIA Foundation Pack saves significant time, effort and cost, compared to building integrations from the ground up and helps you realize the value of a Service Oriented Architecture (SOA) at an accelerated pace.

AIA pre-built integrations are specific to business processes and applications. Built using AIA Foundation Pack, these specific business process integrations provides an open, standards-based approach for organizations to integrate end-to-end business processes across a broad range of custom, Oracle or third-party applications.

For more information about the AIA Foundation Pack development methodology, see *Oracle Fusion Middleware Developer's Guide for Oracle Application Integration Architecture Foundation, Pack 11g Release 1*.

SAP

SAP is an acronym for System Application and Products which creates a common centralized database for all the applications running in an organization. SAP products are generally focused on Enterprise Resource Planning (ERP).

SAP applications are built to manage product operations, cost accounting, assets, materials and personnel. SAP ERP runs on majority of platforms including Microsoft Windows and it uses client/server model. SAP provides majority of new dimensional enterprise products namely SEM, SRM, CRM, APO, etc.

Chapter 2: Process Integration for Change Order Release

This chapter discusses:

- Change Order Release Process
- Posting CO Data to SAP
- CO Release Process Integration Solution Assumptions
- CO Release Integration Sequence
- AIA Services for CO Release
- CO Release Integration Customization Points

Integration of Change Order Release, namely the Engineering Change Order (ECO) and New Part/Product Release (PREL) from Agile to SAP is about introducing a new product, components & structure into SAP upon release of design from Agile or updating existing design metadata or structure.

This process is triggered from Agile.

Note: The integration flow is similar for both ECO and PREL use cases.

Change Order Release Process

The process of change order release, which comprises of new part introduction and manufacturing update, is the flow of Item and BOM information from Agile to SAP. This information is pushed from Agile, triggered by an event tied to the change in status of a Change Order object. The information is then parsed in an integration object format and sent to SAP for implementation. A confirmation of the implementation status is sent back to Agile.

This integration process supports the following flow:

1. Release of Change Order in Agile
2. aXML generation by Agile Content Server
3. Parsing and transformation of aXML Data
4. Posting Changer Order Data to SAP
5. Communicating Order Processing Status to Agile

Release of CO in Agile

When a change analyst approves the change order in Agile, it is marked as *Released*. This makes all the changes specified in CO take effect in Agile.

Before a CO is released, it is pre-validated at the approval stage. This involves validation of certain business rules to ascertain that the flow of CO from Agile to SAP would meet all the conditions set in the destination system.

aXML generation by Agile Content Server

The Agile content server generates an aXML (Agile XML) file from CO data. This file contains information of items, BOM, manufacturers and the CO itself.

For the purpose of Agile to SAP integration process, the ACS is configured to ensure the following:

- The aXML file is configured to carry the following elements from a CO:
 - **Change Order Data:** Cover Page, Page Two, Page Three, Affected Items tab attributes
 - **Revised Item Data:** Title Block, Page Two, Page Three
- BOM Data: BOM tab of Items (including reference designators) with delta BOMs only for the revision on CO.
- Upon release of a CO, the aXML file goes to a JMS Queue.

Parsing and Transformation of aXML Data

The data contained in aXML file generated by Agile is not in the format that is understood by enterprise business objects. Hence, this data has to be parsed and transformed.

The parsing and transformation of aXML data entails the following:

1. Segregation of Business Objects
2. Sequencing and Queuing of Change Orders
3. Translating Agile 'Site' specific objects into SAP's 'Plant' specific objects
4. Translating Agile CO Types into SAP's CO Type. All the change types from Agile are mapped to Engineering Change Master record in SAP.
5. Ascertaining business objects existence from SAP to prepare the data in create or update mode.
6. Mapping Agile CO Attributes to corresponding attributes in SAP
7. Defining User Exit Points for custom transformations

Segregation of Business Objects

The aXML file contains collective information about the business objects – CO, Item Attributes, Revised Item Lines, BOM Redlines, Reference designators, etc. This information is broken down into individual components and mapped, one to one, with corresponding EBOs, namely Item, Change and Structure.

In order to maintain referential integrity, the Change Number is associated with each individual business object.

Sequencing and Queuing of COs

The CO release process begins with queuing of CO Number in Process Queue Controller, which sequences the COs for transfer of parsed data to SAP. Once the data is processed by SAP, and its implementation status received, the CO is removed from the Process Queue.

For complete details on sequencing and queuing of change orders, refer Queue Manager Section in Appendix D.

Translating Site Objects

The data coming from Agile is split into individual SAP Organization specific business objects. This is because the data in Agile can be:

- Centralized – all design locations share the same product design information or
- De-centralized – the Item Attributes, change control, etc. are implemented to multiple sites.

The Data in SAP, however, is segregated by Plants.

Translating CO Types

In Agile, a CO is categorized into the following change types:

- Engineering Change Order (ECO)
- Manufacturing Change Order (MCO)
- Site Change Order (SCO)

These categories are called *Classes* in Agile. A class may have one or more sub-classes.

SAP does not have separate categories for each of these change types, and hence, cannot be differentiated. Hence, while parsing and processing of these change types in Agile, they are translated in SAP with the following characteristics:

Feature	ECO	MCO	SCO
Customer adoption	All installations	All installations	---
New Revisions for revised items	Mandatory	Not supported	Not supported
Tables redlined	BOMs; Global as well as site-specific	Global BOM as well as site-specific	Site-specific BOMs.
Effectivity Date	At line level; Global when multi-site is not enabled; Separate for each site when multi-site is enabled	Not specified on Change Order	At line level; site-specific only
Other line-level attributes	Global when multi-site is not enabled; Separate for each site when multi-site is enabled	Global when multi-site is not enabled; Separate for each site when multi-site is enabled	Site-specific only
New Item Release	Supported	Supported	Only item updates are supported

Mapping CO Attributes

The source system attributes are mapped to destination system attributes. This mapping also defines the direction of data flow.

This is accomplished as follows:

- Two different sets of mappings are defined.
 - One for information flowing from Agile to EBOs.
 - Another, for information flowing from EBOs to Agile.
- These are accessed in the UI as different 'mapping profiles'.
- A parameter is specified with each mapping done from the UI. This parameter determines whether the mapping applies to one or both of the directions of data flow.

See [Appendices](#) for complete list of Agile to SAP Mappings.

Ascertaining Item Existence in SAP

An Item is created in the SAP Plant in two ways:

1. Agile releases New Part Introduction information to SAP through a CO, as a First Time release.
2. The Item information is loaded in SAP by an external system, other than SAP and Agile.

If the Item already exists in the SAP Plant, and Agile releases CO to create the same Item, the system would update the item. Since, Agile does not explicitly pass information about first time or subsequent release of Item; a cross reference table is employed to ascertain the existence of the Item in SAP.

This cross reference table maintains unique identifiers for the Items received from Agile and corresponding Items created in SAP. It also maintains the unique identifiers for the Items created in SAP by an external application. These unique identifiers help in ascertaining the existence of an Item in SAP, thus eliminating any duplication errors.

Defining User Exit Points

User Exits have been provided in the integration to allow custom transformations or filtration routines that a customer may want to add in the process without affecting the main integration flow. The user exit points for each process are listed in their respective chapters.

Posting CO Data to SAP

PLM records the design specifications of a part. This information is updated either on an engineering change order (ECO) or a manufacturing change order (MCO). A new part is created in the ERP using reference material in SAP. Revisions to a part, effective date, bills of material, item, and reference designator information are controlled by ECO which transfers the information from Agile to ERP system.

The release of change order in the PLM system acts as a trigger for the synchronization of product design information with ERP system. Synchronization process is the transfer of the released revision of the product design from Agile PLM to the manufacturing system.

Process queue controller drives the integration of change order release process between agile PLM and SAP system. To maintain the integrity of data in the ERP system, it is important that change orders are transferred to that system in the same sequence they were released by the source system.

The Agile PLM to SAP process flow consists of two phases: *Pre-Process ECO* and *Post-Process ECO*:

Pre-Process ECO

ABM to EBM transformations

- Invoke Provider

- Receive Response
- Send Response to the Queue

Post-Process ECO

- Update transfer status in Agile

CO Processing in SAP

The processing of Change Order data into the ERP system is the backbone of this integration. As part of this step, the following activities need to be performed:

- **Item Master synchronization:** For all items pushed to the ERP system, verify whether or not the items already exist. If the item didn't exist in ERP then create it. If the Item already exists in ERP, then update the Item. It is assumed that the source and target systems are in synch before the integration come in to play and hence the integration doesn't check if both the systems are in synch before posting the data.
- **Create Change Order:** The actual Change Order is created as change master object in the ERP system. When the Change master record is posted in to SAP, the status would be set to 'Inactive'. Once all the line items on this Change are posted successfully in to SAP then the integration should change the Change master status in SAP to 'Active'. That means this Change Master is complete and all the changes effective on this Change will be in-force from scheduled effectivity/valid from date. This 'Active' Change Order status of SAP is transferred to the corresponding mapped Page Two field in Agile as "Transferred".
- **Item Plant assignment:** Items are assigned to plants based on criteria specified in the section on supporting distributed manufacturing above.
- **BOM Update** (including reference designator): The aXML data from Agile contains only the changes made to Bills of Material and not the complete Bill of Material. As a result, BOM data needs to be in sync between Agile and ERP for the older revision in order for the new revision of BOM data to be posted successfully.

Communicating CO Implementation status to Agile

When the process of posting Change Order data into the SAP system completes (successfully or with errors), the following steps are taken


If the parameter **Change.TransferStatusAttribute** is assigned to Page Two field in Agile, then upon successful creation of Change Order in SAP with status *Active* would be propagated back to Agile as 'Transferred' in the specified Page Two field, else *Errored* status is propagated.

CO Release Process Integration Solution Assumptions

- Change Orders should be transferred to the ERP in the order in which they were released by the source system.
- If a part does not exist in ERP system, then create the part.
- If a part exists in ERP system, just update the part.
- Design changes, Effectivity Date, Bill of Material, Item and Reference Designators are all controlled by ECO.
- Part information and design specifications are updated from Agile to ERP system using ECO.
- There is a business process that prioritizes and monitors the Change Order Process.
- At a given time, only one Change Order (i.e.) first one in the queue undergoes ERP Processing. The next process can start its execution only after the execution of the first process is completed.
- Integration administrator has the provision of error handling and reporting the same to the end user.

CO Release Integration Sequence

The integration flow is same for both ECO and PREL:



CO Release Integration Flow

An Engineering Change Order is created with items in Affected Items (AI) tab with new revisions and lifecycle phases specified. The ECO is routed for Approval (workflow step).

1. An ACS Workflow Event is generated on Approval of the ECO in Agile to trigger the ECO process flow.
2. The Queue framework captures the ACS payload (AXML) generated for the event and adds it to the integration Queue.
3. The Queue framework identifies the highest priority Queue Message, processes it to create an ECO ABM and triggers the Requestor ABCS.
4. The Requestor ABCS transforms the ECO ABM to ECO EBM and triggers an operation on the EBS which routes the EBM to the ECO business flow with ECO EBM as the input.
5. The ECO Business Flow:

This table list the activities involved in the Change Order Release Services orchestration:

#	Activity	Remarks
1	Agile ACS acts as a trigger for ECO Use case.	Agile ACS transmits Agile Engineering Change Order Data in payload in the form of predefined XML format known as aXML. This file will get queued up for the further processing.
2	QueueController processes the payload	The Queue Controller Framework reads the highest priority Queue Message and transforms the payload (aXML) to AgileCreateEngineeringChangeOrderListABM.
3	Invoke ProcessEngineeringChangeOrderAgileReqABCS	QueueController invokes the ProcessEngineeringChangeOrderAgileReqABCS with AgileCreateEngineeringChangeOrderListABM as input.
4	ProcessEngineeringChangeOrderAgileReqABCS makes call back to Agile Web services, if needed.	ProcessEngineeringChangeOrderAgileReqABCS calls the web services exposed in agile side to enrich AgileCreateEngineeringChangeOrderListABM. AgileCreateEngineeringChangeOrderListABM is transformed into CreateEngineeringChangeOrderEBM.
5	ProcessEngineeringChangeOrderAgileReqABCS invokes EngineeringChangeOrderEBS	ProcessEngineeringChangeOrderAgileReqABCS invokes CreateEngineeringChangeOrder operation on EngineeringChangeOrderEBS with CreateEngineeringChangeOrderEBM as input
6	EngineeringChangeOrderEBS routes CreateEngineeringChangeOrderListEBM to CreateEngineeringChangeOrderListEBF	CreateEngineeringChangeOrderListEBM is passed to CreateEngineeringChangeOrderListEBF as input.
7	CreateEngineeringChangeOrderEBF invokes ItemEBS	CreaterItemListEBM is passed to ItemEBS as input
8	ItemEBS routes the CreaterItemListEBM to SyncItemListSAPProvABCS	CreaterItemListEBM is passed to SyncItemListSAPProvABCS as input
9	SyncItemListSAPProvABCS transforms the input and calls the SAP service	SyncItemListSAPProvABCS transforms CreaterItemListEBM to the input of SAP service and calls that service.Creates items in ERP
10	SyncItemListSAPProvABCS calls ItemResponseEBS (Response Port) with CreaterItemListResponseEBM	SyncItemListSAPProvABCS invokes the CreaterItemListResponse operation on ItemResponseEBS with CreaterItemListResponseEBM as input
11	CreateEngineeringChangeOrderListEBF calls	CreateEngineeringChangeOrderListEBM will be passed to ProcessBillOfMaterialsListSAPProvABCS

#	Activity	Remarks
	ProcessBillOfMaterialsListSAPProvABCS	as the input
12	ProcessBillOfMaterialsListSAPProvABCS invokes BillOfMaterialsEBS	
13	Based on the existence of the BOM BillOfMaterialsEBS routes to CreateBillOfmaterialsListSAPProvABCSImpl (or) UpdateBillOfMaterialsListSAPProvABCSImpl	
a)	BillOfMaterialsEBS calls CreateBillOfMaterialsListSAPProvABCSImpl	CreateBillOfMaterialsListEBM is passed to CreateBillOfmaterialsListSAPProvABCSImpl
b)	ProcessBillOfMaterialsListSAPProvABCSImpl is invoked before BillOfMaterialsEBS calls UpdateBillOfMaterialsListSAPProvABCSImpl	CreateEngineeringChangeOrderListEBM is passed to ProcessBillOfMaterialsListSAPProvABCSImpl & after this UpdateBillOfMaterialsListEBM is passed to UpdateBillOfMaterialsListSAPProvABCSImpl
14 a)	CreateBillOfMaterialsListSAPProvABCSImpl transforms the input and calls the SAP service	CreateBillOfMaterialsListSAPProvABCSImpl will transform CreateBillOfMaterialsListEBM to the input of SAP service and calls that service. Creates the BillOfMaterialsList in ERP
b-i)	ProcessBillOfMaterialsListSAPProvABCSImpl transforms the input and calls the SAP service	ProcessBillOfMaterialsListSAPProvABCSImpl transforms CreateEngineeringChangeOrderListEBM to the input of SAP service and calls that service
b.ii)	UpdateBillOfMaterialsListSAPProvABCSImpl transforms the input and calls the SAP service	UpdateBillOfMaterialsListSAPProvABCSImpl transforms UpdateBillOfMaterialsListEBM to the input of SAP service and calls that service. Updates the <i>BillOfMaterialsList</i> in ERP
15 a)	CreateBillOfMaterialsListSAPProvABCSImpl calls BillOfMaterialsResponseEBS (Response Port) with CreateBillOfMaterialsListResponseEBM	CreateBillOfMaterialsListSAPProvABCSImpl invokes CreateBillOfMaterialsListResponse operation on BillOfMaterialsResponseEBS with CreateBillOfMaterialsrListResponseEBM as input
b)	UpdateBillOfMaterialsListSAPProvABCSImpl calls BillOfMaterialsResponseEBS (Response Port) with UpdateBillOfMaterialsListResponseEBM	UpdateBillOfMaterialsListSAPProvABCSImpl invokes UpdateBillOfMaterialsListResponse operation on BillOfMaterialsEBS with UpdateBillOfMaterialsListResponseEBM as input
16	CreateEngineeringChangeOrderEBF calls CreateEngineeringChangeOrderSAPProvABCS	CreateEngineeringChangeOrderListEBM is passed to CreateEngineeringChangeOrderListSAPProvABCS as input
17	CreateEngineeringChangeOrderListSAPP	CreateEngineeringChangeOrderListSAPProvABCS

#	Activity	Remarks
	rovABCS transforms the input and calls the SAP service	transforms CreateEngineeringChangeOrderListEBM into the input of SAP Service and calls that service. Creates items in ERP, creates an ECO, associates revised items to it and creates BOM
18	CreateEngineeringChangeOrderListEBF calls EngineeringChangeOrderResponseEBS (Response Port) with the CreateEngineeringChangeOrderResponseEBM	CreateEngineeringChangeOrderListEBF invokes CreateEngineeringChangeOrderListResponse operation on EngineeringChangeOrderResponseEBS with CreateEngineeringChangeOrderListResponseEBM as input.
19	EngineeringChangeOrderResponseEBS routes the response message to ProcessEngineeringChangeOrderAgileReqABCS .	EngineeringChangeOrderResponseEBS routes CreateEngineeringChangeOrderListResponseEBM to ProcessEngineeringChangeOrderAgileReqABCS.
20	ProcessEngineeringChangeOrderAgileReqABCS sends the status back to the QueueController to update the queue.	ProcessEngineeringChangeOrderAgileReqABCS replies back to the QueueController with the status of the ECO business process. This status is updated against the Queue message in the database by the QueueController
21	ProcessEngineeringChangeOrderAgileReqABCS invokes the Agile Web Services.	ProcessEngineeringChangeOrderAgileReqABCS transforms CreateEngineeringChangeOrderListResponseEBM into AgileUpdateEngineeringChangeOrderListABM. AgileUpdateEngineeringChangeOrderListABM is sent as an input to the Agile Web Service. The web services would update transfer status on the Change Order in Agile which will be predefined P2 or P3 attributes on ECO object in Agile. AgileUpdateEngineeringChangeOrderListResponseABM is sent back to <i>ProcessEngineeringChangeOrderAgileReqABCS</i> .

AIA Services for CO Release

The process integration for ECO/PREL uses the following industry components:

EBOs	<ol style="list-style-type: none"> 1. EngineeringChangeOrderEBO 2. BillOfMaterialsEBO 3. ItemEBO
------	---

EBOs	<ol style="list-style-type: none"> 4. CreateEngineeringChangeOrderListEBM 5. CreateEngineeringChangeOrderListResponseEBM 6. CreateBillOfMaterialsListEBM 7. CreateBillOfMaterialsListResponseEBM 8. UpdateBillOfMaterialsListEBM 9. UpdateBillOfMaterialsListResponseEBM 10. CreateItemEBM 11. CreateItemResponseEBM
EBSs	<ol style="list-style-type: none"> 12. EngineeringChangeOrderListEBS (CreateEngineeringChangeOrderListResponseEBM) 13. BillOfMaterialsEBS (CreateBillOfMaterialsListEBM/ CreateBillOfMaterialsListResponseEBM) 14. ItemEBS (CreateItemEBM/ CreateItemResponseEBM)

Core Components Locations

EBO & EBM XSD files	<p>\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseObjectLibrary/Core/EBO/EngineeringChangeOrder/</p> <p>\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseObjectLibrary/Core/EBO/BillOfMaterials/</p> <p>\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseObjectLibrary/Core/EBO/Item/</p>
WSDL files	\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseBusinessServiceLibrary/Core/EBO/

For detailed documentation of individual EBOs, click the **EBO Name link** on the *Integration Scenario Summary* page in the *Oracle AIA Console*. You can also use the *Integration Scenario Summary* page to search for and view integration scenarios that utilize a particular EBO or EBS.

EBOs can be extended, for instance, to add new data elements. These extensions are protected, and will remain intact after a patch or an upgrade.

For more information, see *Oracle Application Integration Architecture – Foundation Pack: Integration Developer’s Guide*, “Extensibility for AIA Artifacts.”

Agile & SAP Components for CO Release

Services	Agile (Requester)	SAP (Provider)
ABMs	AgileCreateEngineeringChangeOrderListABM AgileCreateEngineeringChangeOrderListResponseABM AgileUpdateEngineeringChangeOrderListABM AgileUpdateEngineeringChangeOrderListResponseABM	BAPI_MATERIAL_GET_ALL BAPI_MATERIAL_GET_ALLResponse BAPI_MATERIAL_GET_DETAIL BAPI_MATERIAL_GET_DETAILResponse BAPI_MATERIAL_SAVEDATA BAPI_MATERIAL_SAVEDATAResponse CSAP_MAT_BOM_READ CSAP_MAT_BOM_READResponse CCAP_REV_LEVEL_MAINTAIN CCAP_REV_LEVEL_MAINTAINResponse BAPI_MAT_BOM_EXISTENCE_CHECK BAPI_MAT_BOM_EXISTENCE_CHECKResponse CSAP_MAT_BOM_ALLOC_CREATE CSAP_MAT_BOM_ALLOC_CREATEResponse CSAP_MAT_BOM_CREATE CSAP_MAT_BOM_CREATEResponse CSAP_MAT_BOM_MAINTAIN CSAP_MAT_BOM_MAINTAINResponse CCAP_ECN_MAINTAIN CCAP_ECN_MAINTAINResponse
ABCS	ProcessEngineeringChangeOrderAgileReqABCS	CreateEngineeringChangeOrderListSAPPProvABCSImpl CreateEngineeringChangeOrderListEBF ProcessBillOfMaterialsListSAPPProvABCS ProcessBillOfMaterialsListSAPPProvABCSImpl CreateBillOfMaterialsListSAPPProvABCSImpl UpdateBillOfMaterialsListSAPPProvABCSImpl SyncltemListSAPPProvABCS
EBS	EngineeringChangeOrderEBS (CreateEngineeringChangeOrderList Operation)	EngineeringChangeOrderResponseEBS (CreateEngineeringChangeOrderListResponse Operation) BillOfMaterialsEBS

Services	Agile (Requester)	SAP (Provider)
		BillOfMaterialsResponseEBS ItemEBS ItemResponseEBS
BPEL	CreateQueueService QueueProcessorServiceImpl	---
Mediator Service	ACSAXMLJMConsumer ACSAXMLFileConsumer CreateQueueControlService QueueProcessorService EngineeringChangeOrderService	ItemService BOMServiceESB ReserveItemservice ECORouterService

Component Locations

ABO XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/Agile/V1/schemas
ABM XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/Agile/V1/schemas \$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/SAP/Release1/Core/ABM/EngineeringChangeOrder

Integration Services for CO Release

These are the integration services for Change Order release:

1. EngineeringChangeOrderEBS

EngineeringChangeOrderEBS is the Enterprise Business Service, which exposes the operations related to the Engineering Change Order Integration on the EngineeringChangeOrder EBO. The following are the routing rules:

EngineeringChangeOrderEBS Mediator service

- ProcessEngineeringChangeOrderAgileReqABCS
Route CreateEngineeringChangeOrderListEBM to
CreateEngineeringChangeOrderListSAPProvABCImpl

EngineeringChangeOrderResponseEBS Mediator Service

- CreateEngineeringChangeOrderListSAPProvABCSEBMSpl
Route CreateEngineeringChangeOrderListResponseEBM to
ProcessEngineeringChangeOrderAgileReqABCSEBMSpl

2. ItemEBS

ItemEBS Mediator Service

- CreateEngineeringChangeOrderListEBF
Route CreateItemEBM to SyncItemEBM to SAPProvABCSEBMSpl

ItemResponseEBS Mediator service

- SyncItemEBM to SAPProvABCSEBMSpl
Route CreateItemEBM to
CreateEngineeringChangeOrderListEBF

3. BillOfMaterialsEBS

BillOfMaterialsEBS Mediator service

- ProcessBillOfMaterialsListSAPProvABCSEBMSpl
 - Route CreateBillOfMaterialsListEBM to
CreateBillOfMaterialsListSAPProvABCSEBMSpl
 - Route UpdateBillOfMaterialsListEBM to
UpdateBillOfMaterialsListSAPProvABCSEBMSpl

BillOfMaterialsResponseEBS Mediator service

- CreateBillOfMaterialsListSAPProvABCSEBMSpl
Route CreateBillOfMaterialsListResponseEBM to
ProcessBillOfMaterialsListSAPProvABCSEBMSpl
- UpdateBillOfMaterialsListSAPProvABCSEBMSpl
Route UpdateBillOfMaterialsListResponseEBM to
ProcessBillOfMaterialsListSAPProvABCSEBMSpl

4. ProcessEngineeringChangeOrderAgileReqABCSEBMSpl

ProcessEngineeringChangeOrderAgileReqABCS is used for transforming AgileCreateEngineeringChangeOrderListABM into CreateEngineeringChangeOrderListEBM. This service invokes the CreateEngineeringChangeOrder operation on EngineeringChangeOrderEBS for creation of ECO in SAP.

Based on the status of ECO creation in SAP this service updates the queue status. Also the Transfer status attribute in Change Order is updated by this service. This service is implemented as *Asynchronous* BPEL composite.

The QueueController creates the AgileCreateEngineeringChangeOrderListABM and invokes the ProcessEngineeringChangeOrderAgileReqABCS.

1. Transforms the AgileCreateEngineeringChangeOrderListABM to CreateEngineeringChangeOrderListEBM and invokes the CreateEngineeringChangeOrder operation on EngineeringChangeOrderEBS with CreateEngineeringChangeOrderListEBM as input. This is routed for creation of ECO in SAP.
2. CreateEngineeringChangeOrderListResponseEBM is received from EngineeringChangeOrderEBS and based on the status of ECO creation in SAP, The QueueController is invoked to update the status of the Queue Message.
3. ProcessEngineeringChangeOrderAgileReqABCS transforms CreateEngineeringChangeOrderListResponseEBM into AgileUpdateEngineeringChangeOrderListABM and sent as an input to the Agile Web Service.
4. The web services update the transfer status of the Change Order in Agile which will be predefined P2 or P3 attributes on ECO object in Agile. AgileUpdateEngineeringChangeOrderListResponseABM is sent back to ProcessEngineeringChangeOrderAgileReqABCS.

Transformations

AgileCreateEngineeringChangeOrderListABM_to_CreateEngineeringChangeOrderEBM.xsl

1. Transforms AgileCreateEngineeringChangeOrderListABM to CreateEngineeringChangeOrderListEBM
 2. CreateEngineeringChangeOrderResponseEBM_to_AgileUpdateEngineeringChangeOrderListABM.xsl
 3. Transforms CreateEngineeringChangeOrderResponseEBM to AgileUpdateEngineeringChangeOrderListABM
- 5. CreateEngineeringChangeOrderListSAPProvABCImpl**
1. This is a single operation service. This accepts an Engineering Change Order containing Item and BOMs information message as a request and returns a response.

2. In Agile to SAP flow, CreateEngineeringChangeOrderListSAPProvABCImpl is used for transforming CreateEngineeringChangeOrderListEBM into CCAP_ECN_MAINTAINABM, which invokes the CreateEngineeringChangeOrder operation in SAP.
3. In return flow, CCAP_ECN_MAINTAIN BAPI sends CCAP_ECN_MAINTAINResponse which is transformed by CreateEngineeringChangeOrderListSAPProvABCImpl into CreateEngineeringChangeOrderListResponseEBM.
4. This service is implemented as Asynchronous BPEL Composite

CO Release Integration Customization Points

This table lists the Change Order integration customization information:

Agile

Name	Property	Description
ProcessEngineeringChangeOrderAgileReqABCS (Agile Process ECO requestor flow)	AgileCreateEngineeringChangeOrderListABM_to_CreateEngineeringChangeOrderListEBM_Impl.xml	ReqABM to ReqEBM (main)
	AgileCreateEngineeringChangeOrderListABM_to_CreateEngineeringChangeOrderListEBM_Custom.xml	ReqABM to ReqEBM (custom elements)
	CreateEngineeringChangeOrderListEBM_EBMHeader_Custom.xml	EBM to EBMHeader (custom elements)
	CreateEngineeringChangeOrderListEBM_EBMHeader_Impl.xml	EBM to EBMHeader (main)
	CreateEngineeringChangeOrderListResponseEBM_to_UpdateEngineeringChangeOrderListEBM_Impl.xml	RespEBM to ReqEBM (main)
	UpdateEngineeringChangeOrderListEBM_to_AgileUpdateEngineeringChangeOrderListABM_Impl.xml	ReqEBM to ReqABM (main)

SAP

Name	Property	Description
------	----------	-------------

CreateEngineeringChangeOrderListSAPProvABCImpl CreateEngineeringChangeOrderListEBF	CreateEngineeringChangeOrderListEBMtoABM_Custom.xml	Custom transformations for Engineering Change Order Request EBM to Request ABM
	XformReqEBMToResEBM_Custom.xml	Custom transformations for Engineering Change Order Request EBM to Engineering Change Order Response EBM
	CreateECOEBMtoItemListEBM_Custom.xml	Custom transformations for Engineering Change Order Request EBM to Item List EBM
	UpdateXformEngineeringChangeOrderListEBMtoEBM_Custom.xml	Custom transformations for update Engineering Change Order list EBM to Engineering Change Order list EBM
	XformEBMtoBillOfMaterialProcess_Custom.xml	Custom transformations for Engineering Change Order list EBM to Engineering Change Order list EBM for BOM
	XformECOListEBMtoECOListResponseEBM_Custom.xml	Custom transformations for Engineering Change Order list request EBM to Engineering Change Order list Response EBM
	XformEngineeringChangeOrderListEBMtoEBM_Custom.xml	Custom transformations for create Engineering Change Order list EBM to Engineering Change Order list EBM
	ECOEBMtoExistenceCheck_Custom.xml	Custom transformations for Engineering Change Order list EBM to BOM_Existence_Check ABM
ProcessBillOfMaterialsListSAPProvABCS	ECOEBMtoGlobalBOMExistenceCheck_Custom.xml	Custom transformations for Engineering Change Order list EBM to global BOM_Existence_Check ABM
	ECOEBMtoGlobalUpdateBOMEBM_Custom.xml	Custom transformations for Engineering Change Order list EBM to global Update BillOfMaterials List EBM
	ECOListEBMtoBOMListEBM_Custom.xml	Custom transformations for Engineering Change Order list EBM to Create BillOfmaterials List EBM

	ECOListEBMToUpdateBOMListEBM_Custom.xml	Custom transformations for Engineering Change Order list EBM to Update BillOfMaterials List EBM
	XformEBMHeadertoECOListResponseEBM_Custom.xml	Custom transformations for EBM Header to Create EngineeringChangeOrder List EBM
	XformECOListEBMtoEBMHeader_Custom.xml	Custom transformations for Create EngineeringChangeOrder List EBM to EBM Header
CreateBillOfMaterialsListSAPProvABCImpl	BOMEBMToCreateGlobalBOMABM_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to Create Global BOM ABM
	BOMEBMToExistenceCheck_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to global BOM Existence Check ABM
	BOMEBMToPlantExistenceCheck_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to BOM Existence Check ABM
	BOMEBMToPlantExtensionABM_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to BOM Plant Extension ABM
	BillOfMaterialsListEBMToCreateBOM_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to Create BOM ABM
	XformBOMReqEBMToResEBM_Custom.xml	Custom transformations for Create BillOfMaterials List EBM to Create BillOfMaterials List Response EBM
UpdateBillOfMaterialsListSAPProvABCImpl	BOMEBMToGlobalBOMABM_Custom.xml	Custom transformations for Update BillOfMaterials List EBM to Update global BOM ABM
	BOMEBMToPlantExistenceCheck_Custom.xml	Custom transformations for Update BillOfMaterials List EBM to BOM Existence Check ABM

	BOMEBMTtoPlantExtensionABM_Custom.xml	Custom transformations for Update BillOfMaterials List EBM to BOM Plant Extension ABM
	BOMEBMTtoUpdateBOMABM_Custom.xml	Custom transformations for Update BillOfMaterials List EBM to Update BOM ABM
	XformBOMReqEBMtoResEBM_Custom.xml	Custom transformations for Update BillOfMaterials List EBM to Update BillOfMaterials List Response EBM
ProcessBillOfMaterialsListSAPPProvABCImpl	XformECOEBMtoABM.xml	Custom transformations for CreateEngineeringChangeOrderListEBM to Read BOM ABM
	XformABMtoECOEBM.xml	Custom transformations for Read BOM ResponseABM to CreateEngineeringChangeOrderList EBM
SyncItemListSAPPProvABC	XFormItemEBMtoGetDetailRefMaterial_Custom.xml	Custom transformations for CreateItem List EBM to Get detail Reference Material ABM
	XFormItemEBMtoReferenceMaterial_Custom.xml	Custom transformations for CreateItem List EBM to Get Reference Material ABM
	XFormItemEBMtoRevisionABM_Custom.xml	Custom transformations for CreateItem List EBM to Create Revision ABM
	XFormItemListEBMtoSavedData_Custom.xml	Custom transformations for CreateItem List EBM to Create Item List ABM
	XFormItemListEBMtoUpdateItem_Custom.xml	Custom transformations for CreateItem List EBM to Update Item list ABM(for Get All ReferenceMaterial-4.6)
	XFormItemListEBMtoUpdate_Item_Custom.xml	Custom transformations for CreateItem List EBM to Update Item list ABM(for Get Detail ReferenceMaterial)
	XformItemListEBMtoItemListResponseEBM_Custom.xml	Custom transformations for CreateItem List EBM to Create ItemList Response EBM

Properties and DVMs for CO Release

The following mandatory DVMs and Properties (in AIAConfigProperties.xml) must be set for the CO Release process:

- AGILE_SITE_TARGET_MAPPING
- AGILE_TARGET_SITE_MAPPING
- LANGUAGE_CODE
- ECO_ENGINEERINGCHANGEORDERLINE_REVISEDBILOFMATERIALS_BILLOFMATERIALSCOMPONENTITEM_CHANGETYPECODE
- ITEM_PRIMARYCLASSIFICATIONCODE
- ITEM_STATUS_CODE
- ITEM_UOM_CODE
- ECO_STATUS_CODE
- REFERENCE MATERIALS

Chapter 3: Process Integration for New Part Request

This chapter discusses:

- NPR Process in Agile
- NPR Process in SAP
- NPR Process Integration Solution Assumptions
- NPR Integration Sequence
- AIA Services for NPR
- NPR Integration Customization Points

Agile PLM system record for product design and part information, new part numbers themselves may originate in a system outside of Agile. This is easily understood when looking at the interactions of various roles that can be involved in the process of generating new part numbers.

An engineer designing an electronic assembly, for example, a circuit board may need a part that cannot be found in the system, for instance, a new resistor. The engineer raises a new part request to doc control to route the request to materials managers for review. A buyer looks into catalogs offered by approved manufacturers and finds a couple of parts that meet the criteria. The buyer then contacts the manufacturers, confirms availability, procures specifications, and then approves the new part request with the new manufacturer part numbers attached to it. Doc control compiles all the information and assigns an internal part number corresponding to the manufacturer parts and informs the engineer.

A New Part Request (NPR) process can be triggered on demand by user. This is a synchronous process, which reserves and fetches the part number from the SAP system.

NPR Process in Agile

A New Part Request process in Agile is executed using an object of the Engineering Change Requests (ECR) class. Since the part number(s) being requested do not exist yet in Agile, there are no affected items on this ECR.

A number of variants of this process are possible:

- A single item number is reserved in SAP per ECR
- Multiple item numbers are reserved in SAP per ECR

On Demand New Part Request

The synchronous on-demand NPR process allows you to achieve the following:

User in Agile requires a new part number to be used on a design. In Agile, user clicks on New Object icon to create a new item for a given subclass such as Part or Document. The on-demand NPR process compliments or replaces the new item creation process in Agile by providing the user a Process Extension that a user can use to trigger the creation of a new item.

The overall process flow is as follows:

- User calls a process extension (PX) from Agile's auto number menu on the Create New Item popup. This option is available whenever the part number generation process is generic (mainly using a sequence).
- Since a SAP material type is required to get the next available sequence number from SAP, the item type (subclass) is still passed as a parameter as part of this process. In DVM (Domain Value Mapping) the Agile's subclass is mapped to corresponding SAP material type.
- The PX requests a new part number from SAP. This process reserves the next available part number in SAP.
- New reserved part number is sent back to Agile.
- The new part number is returned to the calling PX and the Agile New Part Creation process is executed as usual from there onwards. If an error is encountered during PX execution, then the error message is displayed as a popup window in Agile.

For detail error information, log on to BPEL console.

NPR Process in SAP

It is assumed that the internal number range assignments are configured in SAP for those material types which are mapped to corresponding Part or Document subclass of Agile that requires auto number generation.

When the synchronous auto number PX is executed from Agile, it calls a standard SAP API with input as material type.

1. SAP checks if there is a valid internal number range defined for the provided material type. If yes, the program returns the next available number to the calling program.
2. If no valid internal number range is defined, it returns an error to the calling program.

Since this complete process is synchronous, the user will not experience the SAP processes at all as they run in the background to return the SAP assigned number. For the user, the process will appear similar to the auto number assignment within Agile.


NPR Process Integration Solution Assumptions

Here are the assumptions for the NPR process:

- The Item type/Agile subclass type is mapped to material type (MARA-MTART) in SAP.
- For a given valid material type, internal number range assignment is already configured in SAP.


NPR Integration Sequence

This figure shows the process flow from Agile to SAP for process a new part number request:



NPR process flow


This figure shows the sequence of events that occur when creating a new part number request:



Sequence for creating a new part number

NPR Integration Flow

The New Part Request process is triggered from a PX. It is a synchronous process and therefore the process is designed based on the Requestor - Provider pattern as shown in this figure:



Process flow from Agile to SAP for new part number

The PX creates the Agile request ABM (*AgileCreateItemABM*) for the *CreateItemAgileReqABCS* and invokes it:

1. The request *AgileCreateItemABM* is transformed to the *CreateItemEBM* for NPR process.
2. Using the Asynchronous Message Pattern NPR Process is invoked on the *ItemEBS* by the *CreateItemAgileReqABCSImpl* with the *CreateItemEBM* as input.
3. The *CreateItemEBM* is routed to the *ReserveItemSAPProvABCS* with the *CreateItemEBM* as input.
4. The *ReserveItemSAPProvABCS* will implement the business logic for generating the New Part number in SAP.
5. A response *CreateItemResponseEBM* with New Part Number is returned to the *ItemResponseEBS* and routed back to the *CreateItemAgileReqABCSImpl*.
6. The *CreateItemAgileReqABCSImpl* transforms the response *CreateItemResponseEBM* to Agile response *AgileCreateItemResponseABM*.
7. *CreateItemAgileReqABCS* receives *AgileCreateItemResponseABM* and returns back to the PX.
8. The Part Number from the response ABM (*AgileCreateItemResponseABM*) is returned to the web client and displayed in the Number field in the Create Item screen.


NPR Services Orchestration

NPR Process itself is an asynchronous process, whereas PX expects the response synchronously. There could be a delayed response from the provider as the *CreateItemAgileReqABCImpl* is implemented as an *Asynchronous BPEL Composite*. To facilitate this, *Synchronous BPEL Composite CreateItemAgileReqABC* is used to invoke the *CreateItemAgileReqABCImpl* and receive the response back. *CreateItemAgileReqABC* is invoked by the PX synchronously.

The asynchronous message pattern Request-Delayed response pattern with one way calls in Enterprise Business Services (EBS) is used here with EBMID as the correlation ID.

Between the *CreateItemAgileReqABC* and *CreateItemAgileReqABCImpl* ABMHeader Id is used as the correlation ID.

This figure shows the sequence of events during NPR services orchestration:



AutoNumber PX

This table describes the activities involved when creating a new part number request:

#	Activity	Remarks
1	Agile NPRAutnumberPX is triggered	The Agile NPRAutnumberPX is triggered by an Agile user from the Agile Web client as part of New Part creation in Agile.
2	Invoke CreateItemAgileReqABCS with	NPRAutnumberPX process invokes the

#	Activity	Remarks
	AgileCreateItemABM as input	CreateItemAgileReqABCS with AgileCreateItemABM ABM as input.
3	Invoke CreateItemAgileReqABCImpl with AgileCreateItemABM as input	NPRAutnumberPX process invokes the CreateItemAgileReqABCImpl with AgileCreateItemABM ABM as input.
4	CreateItemAgileReqABCImpl invokes the ItemEBS with CreateItem operation	An invoke activity in CreateItemAgileReqABCImpl transforms the AgileCreateItemABM ABM to CreateItemReqMsg EBM and invokes the CreateItem operation on ItemEBS with CreateItemReqMsg as the input. CreateItemReqMsg will be routed to SAP ReserItemSAPProvABCS.
5	ReserItemSAPProvABCS on the SAP first transforms & then calls the SAP service	ReserItemSAPProvABCS will first transform CreateItemReqMsg into the input of SAP Service to reserve the item in SAP and then calls that service. This would create an Item in using a generic part number generation process (mainly using a sequence). ReserItemSAPProvABCS invokes ItemResponseEBS with CreateItemResponseMsg as input which is routed back to the CreateItemAgileReqABCImpl.
6	CreateItemAgileReqABCImpl first transforms & then returns the response to CreateItemAgileReqABCS	CreateItemAgileReqABCImpl will first transform CreateItemResponseMsg to AgileCreateItemResponseABM and returns the same to CreateItemAgileReqABCS.
7	CreateItemAgileReqABCS returns AgileCreateItemResponseABM to NPRAutnumberPX.	
8	NPRAutnumberPX returns the partNumber to New Part Creation UI in Agile	NPRAutnumberPX gets the partNumber from the <i>AgileCreateItemResponseABM</i> and returns it to the New Part Creation UI in Agile web client which gets displayed in the Number field.

AIA Services for NPR

The process integration for NPR uses the following industry components:

Core components for NPR

EBOs	ItemEBO
EBMs	CreateItemEBM CreateItemResponseEBM
EBSs	ItemEBS

Core Components Locations

EBO & EBM XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseObjectLibrary/Core/EBO/Item
WSDL files	\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseBusinessServiceLibrary/Core/EBO/Item

For detailed documentation of individual EBOs, click **EBO Name link** on the *Integration Scenario Summary* page in the *Oracle AIA Console*. You can also use the *Integration Scenario Summary* page to search for and view integration scenarios that utilize a particular EBO or EBS.

EBOs can be extended, for instance, to add new data elements. These extensions are protected, and will remain intact after a patch or an upgrade.

For more information, see *Oracle Application Integration Architecture – Foundation Pack: Integration Developer’s Guide*, “Extensibility for AIA Artifacts.”

Agile & SAP Components for NPR

This table contains the Agile and SAP components for NPR:

Services	Agile (Requester)	SAP (Provider)
ABMs	AgileCreateItemABM AgileCreateItemResponseABM	BAPI_STDMATERIAL_GETINTNUMBER BAPI_STDMATERIAL_GETINTNUMBERResponse
ABCS	CreateItemAgileReqABCS CreateItemAgileReqABCSImpl	ReserveItemSAPProvABCS
EBS	ItemEBS	ItemResponseEBS

Component Locations

ABO XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/Agile/V1/schemas
ABM XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/Agile/V1/schemas \$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/SAP/Release1/Core/ABM/Item

Integration Services for NPR

These are the integration services for NPR:

ItemEBS

ItemEBS is the Enterprise Business Service, which exposes the operations related to the Item Integration on the Item EBO. The following are the routing rules:

ItemEBS Mediator service

- `CreateItemAgileReqABCSImpl`
Route `CreateItemEBM` to `ReserveItemSAPProvABCS`

ItemResponseEBS Mediator service

- `ReserveItemSAPProvABCS`
Route `CreateItemResponseEBM` to `CreateItemAgileReqABCSImpl`

CreateItemAgileReqABCSImpl

`CreateItemAgileReqABCSImpl` will transform the Agile message (`AgileCreateItemABM`) into `CreateItemEBM` & call the routing service to Create Item and get the `CreateItemResponseEBM` response from the SAP system. It then transforms the `CreateItemResponseEBM` response from the routing EBS back to an Agile message (`AgileCreateItemResponseABM`) & send it to `CreateItemAgileReqABCS` which returns it to the calling Agile PX.

Flow

Receives `AgileCreateItemABM` from `CreateItemAgileReqABCS`, which gets the same from `NPRAutnumberPX` process extensions.

1. Transforms this message into the `CreateItemEBM` -

- Populates EBM header
- Determines Target System ID(s) and adds into the EBM header to control routing
- Validates Required fields
- Maps to EBM
- 2. Call Target 'ItemEBS' Service with operation CreateItem
- 3. Transform CreateItemResMsg Response EBM(CreateItemResponseEBM) to AgileCreateItemResponseABM Agile message.
- 4. Send 'AgileCreateItemResponseABM back to CreateItemAgileReqABCS, which in turn sends it back to the respective PX.
- 5. CreateItemAgileReqABCImpl has the following transformation:
 - a. AgileCreateItemABM_to_CreateItemEBM2.
CreateItemResponseEBM_to_AgileCreateItemResponseABM

ReserveItemSAPProvABCS

This is a single operation service. This accepts a Material Type of an Item information message as a request and returns a response.

In Agile to SAP flow, ReserveItemSAPProvABCS is used for transforming CreateItemEBM into BAPI_STDMATERIAL_GETINTNUMBER ABM, which invokes the Reserve Item operation in SAP.

In return flow, BAPI_STDMATERIAL_GETINTNUMBER sends BAPI_STDMATERIAL_GETINTNUMBERResponseABM which is transformed by ReserveItemSAPProvABCS into CreateItemResponseEBM.

This service is implemented as asynchronous BPEL Composite.

NPR Integration Customization Points

These are the NPR integration customization points:

Agile

Property	Name	Description
CreateItemAgileReqABCImpl (Agile Process Item requestor flow)	AgileCreateItemABM_to_CreateItemEBM_Custom.xsl	Request ABM to Request EBM
	CreateItemEBM_EBMHeader_Custom.xsl	Request EBM to EBM Header

SAP

Property	Name	Description
ReserveItemSAPProvABCS	GenerateItemEBMtoABM_Custom.xml	Request EBM to Request ABM
	GenerateItemABMtoEBM_Custom.xml	ResponseABM to ResponseEBM

Properties and DVMs for NPR

The ITEM_PRIMARYCLASSIFICATIONCODE property must be set for the New Part Request in the AIAConfigProperties.xml to work.

Chapter 4: Process Integration for Item Attribute Update

This chapter discusses:

- Item Attribute Update Process
- IA Update Process Integration Solution Assumptions
- IA Update Integration Sequence
- AIA Services for IA Update
- IA Update Integration Customization Points

Required as part of the Manufacturing Update process for product information synchronization, the Item Attributes information from ERP system is required to be updated in Agile. The term Item applies to both Parts and Documents in Agile considering the documents are integrated in to SAP as part object only and not as Document Info Record (DIR). DIR is not in scope for this version of integration.

Since item attribute information can exist in multiple plants in the ERP system, it is supported only for cases where the system can accurately determine which plant in ERP to pick up item attribute information from.

Item Attribute Update Process

The update of Item Attribute information from ERP to PLM is done event based and in near real time.

The following steps are executed:

The process kicks off when configured field/s are modified and saved on an item in SAP.

1. Retrieve the attributes that have changed on the item in SAP. This data is retrieved from one or more organizations (plants) as per site-org mappings or from the configured single organization.
2. Update the information into Agile.

The input consists of the item attribute values, which need to be updated in Agile. Unique identifiers for the item, along with values for all the attributes mapped for transfer from ERP to Agile are provided as input.

As of Agile 9.3.1, an item number is the only attribute that is required for uniquely identifying the item to be updated. A planned enhancement in the next major release of Agile PLM would require that the item revision be specified as part of the unique key as well, since all the item attributes could potentially be under revision control with that enhancement. Even in Agile 9.2.2.2, Item Description and Mass can have different values for different revisions of the item.

A unique item revision in Agile is composed of a Rev Number as well as a Change Order number (since it's possible for certain types of Change Orders in Agile to revise an item without changing its revision number). In the context of integration, however, updates to item attributes applies to the latest released revision in most cases.

The following guidelines are followed when querying an item from Agile for update:

- In the first release of integration, developed on Agile 9.2.2.5, only the item number is used to query the item to be updated. The item number will pull up the latest released revision of the item by default, and all updates are made to the latest released revision of the item.
- A future release of the integration should plan on enhancing this capability to accept a revision number (and optionally, a Change number) along with the item number to pull up a unique item revision for update (if a Change number is not specified, the latest released Change corresponding to that revision is assumed).

Processing

Item attribute update is done near real time, or batch. In order to achieve this implementation needs one time configuration of change pointers and *Application Link Enabling* (ALE) in SAP. For more details please refer to Chapter 5: Implementing the Process Integration Pack Section: Setup for SAP.

As part of this configuration, all the fields that need to be updated back in to Agile will be configured such that any changes saved to these fields on an item would trigger the update process immediately. For the batch process, it is required to schedule the **IDOC** as a background job.

The moment user saves the changes on item in SAP the change pointers configuration would trigger an event. The event will push the data to the configured partner (ALE configurations) and in this case it is Agile system. All the changes made on the item are captured and will be updated on the specified item in Agile. This process triggers once for each item change save event.

Exceptions

In all cases, the exception message displayed to the user must contain the item number that was being updated along with other supporting information as indicated.

Insufficient privilege to discover, read, or update the item.

- Invalid field value
 - Invalid list value

- Invalid data format for text, money or date fields
- Item does not exist

IA Update Process Integration Solution Assumptions

If item information needs to be retrieved from multiple plants in SAP (ERP) system, the following constraints must be met in order to support this process:

Agile multi-sites is configured

1. There is a one-to-one mapping between Agile sites and ERP plants
2. The attribute(s) to be updated with ERP data are on the Sites tab of the item

This release of the integration intends to solve a use case where any given Change is interfaced to only one destination system.

The following exception conditions are tested to make sure that they return user-friendly error messages. In all cases, the exception message displayed to the user must contain the Item number that was being updated and the step at which the error occurred, along with other supporting information as needed.

Insufficient privilege to discover, read, or update attributes on the Item object


Invalid field value (indicate the field for which the value is incorrect, and the value that is being passed on to the field)

- Item object does not exist

Note: New Item Creation is not part of the scope for this activity. It is assumed that the item exists in both Agile and SAP, by means of a prior New Part Introduction or independent offline load processes.

IA Update Integration Sequence


This figure shows the sequence of events that occur during IA update:



IA update sequence

IA Update Services Orchestration

This sequence diagram shows the process flow for IA update process flow:



Sequence diagram for IA update process flow

This table describes the activities involved in the IA update process:

#	Activity	Description
1	SAP Item Operational Attribute Update Action Trigger	SAP Item Operational Attribute Update Action trigger Invokes the UpdateItemListSAPReqABCS
2	UpdateItemListSAPReqABCS calls UpdateItemListSAPReqABCImpl	UpdateItemListABM will be passed to UpdateItemListSAPReqABCImpl as the input
3	UpdateItemListSAPReqABCImpl invokes ItemEBS	An invoke activity in UpdateItemListSAPReqABCImpl invokes the UpdateItemList operation on ItemEBS with UpdateItemListEBM as input
4	ItemEBS routes UpdateItemListEBM to	ItemEBS routes UpdateItemListEBM as input

#	Activity	Description
	UpdateItemListAgileProvABCImpl	to UpdateItemListAgileProvABCImpl
5	UpdateItemListAgileProvABCImpl invokes Agile's Item Operational Attribute Update Web Service	UpdateItemListAgileProvABCImpl transforms the UpdateItemListEBM to AgileUpdateItemListABM and invokes UpdateItem service operation on Agile Web Service to update Item cost related attribute information from SAP to Agile. The AgileUpdateItemListResponseABM is returned back to UpdateItemListAgileProvABCImpl

AIA Services for IA Update

The process integration for IA Update uses the following industry components:

Core Components for AIA Update

EBOs	ItemEBO
EBMs	UpdateItemListEBM UpdateItemListResponseEBM
EBSs	ItemEBS ItemResponseEBS

Core Components Locations

EBO & EBM XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseObjectLibrary/Core/EBO/Item
WSDL files	\$AIA_HOME/AIAMetaData/AIAComponents/EnterpriseBusinessServiceLibrary/Core/EBO/Item

For detailed documentation of individual EBOs, click **EBO Name link** on the *Integration Scenario Summary* page in the *Oracle AIA Console*. You can also use the *Integration Scenario Summary* page to search for and view integration scenarios that utilize a particular EBO or EBS.

EBOs can be extended, for instance, to add new data elements. These extensions are protected, and will remain intact after a patch or an upgrade.

For more information, see *Oracle Application Integration Architecture – Foundation Pack: Integration Developer’s Guide*, “Extensibility for AIA Artifacts.”

SAP & Agile Components for IA Update

This table lists the SAP & Agile components for IA updates:

Services	SAP (Requester)	Agile (Provider)
ABMs	UpdateItemListABM	AgileUpdateListABM AgileUpdateListResponseABM
ABCS	UpdateItemListSAPReqABCImpl UpdateItemListSAPReqABCS	UpdateItemListAgileProvABCImpl
EBS	ItemEBS	ItemResponseEBS

Component Locations

ABO XSD files	\$AIA_HOME/AIAMetaData/AIAComponents/ApplicationObjectLibrary/Agile/V1/sc hemas
---------------	--

Integration Services for IA Update

These are the integration services for IA Update:

1. ItemEBS

ItemEBS is the Enterprise Business Services which exposes the following operations related to the Item Attribute Update Integration on the ItemEBO.

The following are the routing rules:

ItemEBS Mediator service

- UpdateItemListSAPReqABCImpl
Route UpdateItemListEBM to UpdateItemListAgileProvABCImpl

2. UpdateItemListSAPReqABCImpl

This is called when there is a need to update multiple items in Agile with all the operational attributes as well as attributes such as unit cost from SAP. This is a push from SAP to the Agile.

The requester ABCS, defined as a "synchronous" process, receives a list of Item Ids from the SAP Change Pointer program. The lists of Ids are those which have last_update_date greater than the last run date of the Change Pointer.

- The requester BPEL Composite filters the list of Ids that are present in the xref tables in the FMW layer. This provides a list of Items that were actually from the Agile system alone. The original list of Item Ids may be those which are from non-Agile sources as well.
- The BPEL Composite then makes a Mediator call out for end point virtualization. This Mediator layer has an SAP Adapter which calls the BAPI that provides the Item details that is needed to be sent out. This is the Item ABM.
- A transformation converts the ABM to an EBM.
- An Asynchronous request-delayed response call is made to the ItemEBS with the ItemListEBM. This is routed to the appropriate provider.
- The BPEL instance gets invoked when the asynchronous call gets back from the provider and provides the status of the transaction back to the caller concurrent program (since that is a synchronous call).
- The concurrent program logs the status of this call.

3. UpdateItemListAgileProvABCImpl

UpdateItemListAgileProvABCImpl is used to facilitate the communication between ItemEBS and Agile web service used for updating the Items' operational attributes, item cost information in batch mode in Agile.

Receives UpdateItemListReqMsg that contains UpdateItemListEBM

- Transform operation is called to convert the UpdateItemListEBM into AgileUpdateItemListABM.
- AgileUpdateItemListABM is sent as input to the web service operation UpdateItems (Coarse Grained APIs on Agile side) to update Items in Agile.
- AgileUpdateItemListResponseABM is received on successful execution of Coarse Grained API.
- Transform operation is called to convert the AgileUpdateItemListABM to UpdateItemListResponseEBM, which is returned as output of this BPEL Composite.
- If the UpdateItems service operation fails on the Agile side, a new Fault is generated and is sent across with appropriate error message.

IA Update Integration Customization Points

These are the IA Update integration customization points:

SAP

Property	Name	Description
UpdateItemListSAPReqABCSImpl	XFormABMToEBM_Custom.xml	Custom transformations for Item Request ABM to Request EBM

Agile

Property	Name	Description
UpdateItemListAgileProvABCImpl (Agile update item attributes provider flow)	AgileUpdateItemResponseABM_to_UpdateItemResponseEBM_Custom.xml	RespABM to RespEBM (custom element)
	AgileUpdateItemResponseABM_to_UpdateItemResponseEBM_Impl.xml	RespABM to RespEBM (main)
	UpdateItemListEBM_to_AgileUpdateItemListABM_Impl.xml	ReqEBM to ReqABM (main)

Essential Properties and DVMs for IA Update

The following mandatory DVMs and Properties (in AIAConfigProperties.xml) should be set for the Item Attribute Update process to flow to work:

- AGILE_SITE_TARGET_MAPPING
- AGILE_TARGET_SITE_MAPPING
- ITEM_PRIMARYCLASSIFICATIONCODE

Chapter 5: Implementing the Process Integration Pack

This chapter discusses:

- Setting up the Participating Applications
- Loading Cross Reference Data
- Configuring the integration
- Domain Value Maps
- Application Interfaces
- Handling Errors

Prerequisites

The Agile PLM integration is deployed through the AIA Installer. For proper functioning, the integration requires certain settings and configurations in Partner Applications like Agile PLM and SAP ERP, and in AIA configuration property files.

SOA 11.1.1.6 should be installed and relevant patches are to be applied.

AIA Foundation Pack Foundation Pack 11.1.1.6, RUP patch 14253266 or later should be installed.

- Agile PLM must be installed and configured accordingly.
- Oracle Application adapter for SAP need to be installed.
- All the required webservices for the corresponding BAPI's and Idoc's of SAP need to be generated from Oracle Application adapter.
- SAP environment must be installed and configured accordingly.
- SAP Version should be 4.7 and above.

Setting up the Participating Applications

Before enable the Agile to SAP integration, you must set up the following participating applications:

- AgilePLM
- SAP
- Cross-reference data

Agile PLM

After installation of Agile pre-built integration, the Agile Administrator is required to setup Agile Content Services. The following are the settings/configurations:

This section discusses the following post-installation configurations using Java client for the Agile PLM SAP pre-built integration:

Create new JMS Destination.

1. Create new events for ECO, MCO and SCO.
2. Create new subscribers for ECO, MCO and SCO.
3. Creating Auto Numbers
4. Updating Change Order Page Two Fields
5. Configuring Sites

6. Configuring Site Attributes
7. Configuring and Deploying PX

Creating New JMS Destination

To create new JMS Destination:

1. Login to Agile Java Client using the login credentials provided.
2. Navigate to **Admin, System Settings, Agile Content Service, Destinations**.
3. Click  (New) button to create a new JMS Destination.

Parameters	Variables
Name	SOA Application Server
Description	SOA Application Server
Protocol	JMS
Username	SOA Application Server Username
Password	SOA Application Server Password
Provider Context Factory	weblogic.jndi.WLInitialContextFactory
Connection Factory	jms/aia/AIAAgilePLMECOCF
Default Provider URL	t3://<soa_hostname>:<port>
Destination Name	jms/aia/AIAAgilePLMECOJMSQueue

Note: If you are pointing Agile to a clustered FMW environment, the **Default Provider URL** needs to contain all possible URLs in the cluster separated by a comma. For example, *t3://<soa_hostname1>:<soa_port1>,<soa_hostname2>:<soa_port2>*.

4. Test the JMS Destination. The test needs to be successful.

Create New Events for ECO, MCO and SCO

To create new events for ECO, MCO and SCO

1. Navigate to **Admin, System Settings, Agile Content Service, Events**.
2. Click  button to create new Event(s).
 - a. Enter **Name** and **Description**.
 - b. Choose relevant workflows.
 - i. For SCO choose **Default Site Change Orders**.
 - ii. For ECO choose **Default Change Orders**.
 - iii. For MCO choose **Default Manufacturer Orders**.
 - c. Choose the workflow status as **Released**.

Creating New Subscribers for ECO, MCO and SCO

To create new subscribers for ECO, MCO and SCO:

1. Navigate to **Admin, System Settings, Agile Content Service, Subscribers**.
2. Click  button to create new Subscribers for ECO, MCO and SCO.
 - a. Enter a **Name** and a **Description** for subscribers.
 - b. Associate the workflow as Automated Transfer Orders(ATO).
 - c. Choose **All Change Orders**, **All Manufacturer Orders**, and **All Site Change Orders** as **Criteria** for ECO, MCO and SCO respectively.
 - d. Choose appropriate **Event** that you created for ECO, MCO and SCO.
 - e. Click **OK**.
3. Select the **Subscriber Details** tab to add the subscriber detail information.
4. Click  button to create a new row.

This opens Subscriber Detail window.

 - a. Click **Destinations** field and select JMS Destination that was created.
 - b. Click **Filters** field and choose the following filters for **Filters** field using **>** **button** in the pop up that appears.
 - i. ECO: **Default Change Order Filter**
 - ii. MCO: **Default Manufacture Order Filter**.

- iii. SCO: **Default Site Changes Order Filter.**

Note: Also add the **Default Item Filter** as filter for all the three; ECO, MCO and SCO.

- c. Click Role(s) field and select all the roles using **> button** in the pop up that appears.
 - d. Select **aXML** as **Format**.
 - e. Select **English** as **Language**.
 - f. Select **All** as **Site**.
5. Select each subscriber at a time and click  button to enable all the created subscriptions.
 6. Navigate to **Admin, System Settings, Agile Content Service, Filters**.
 7. Select **Default Item Filter** and double-click.
 8. Navigate to the **Filters** tab and append **Sites** to the **View Tabs** field value.
 - a. Choose **Tab and Items** in the **BOM Options** field.
 - b. Select **All Levels** checkbox in the **BOM Level** field.
 - c. Choose **Tab and Manufacturer Parts** in the **AML Options** field.
 9. Select **Default Change Order Filter** and double-click.
 10. Navigate to **Filters** tab and,
 - a. Choose **Redline Changes Only** option as **No**.
 - b. Choose **Affected Items Options** as **Tab and Items**.
 11. Select **Default Site Change Order Filter** and double-click.
 12. Navigate to **Filters** tab and,
 - a. Choose **Redline Changes Only** option as **No**.
 - b. Choose **Affected Items Options** as **Tab and Items**.
 13. Navigate to **Admin, User Settings, Privileges**.
 14. Click  button to create **Modify** privileges for **Changes, MCO and SCO**.
 - a. Enter **Name** and **Description**.
 - b. Select **Yes** for **Enabled**.
 - c. Select **Modify** for **Privilege**.
 - d. Click **Criteria** field and choose the relevant criteria for each of the **Changes, MCO and SCO**.
 - e. Click **Applied to** field and select all attributes, including the invisible/disabled attributes.
 - f. Click **OK**.

This opens the privilege screen of the entity for which you set privileges. You now need to assign roles to the privileges that you have created for Changes, MCO, and SCO.

15. Navigate to **Where Used** tab.
16. Click  button and select the roles in the **Select Roles** pop up.
17. Click **OK** to assign these roles to the privilege that you have created.
18. Navigate to **Admin, User Settings, Privileges** and double click **Read**.
19. Click  button in **Privileges to Read** screen to create **Read** privileges for MCO.
20. In the Create Privilege pop up that opens
 - a. Enter **Name** and **Description** for the privilege in respective fields
 - b. Choose **Yes** for **Enabled** field.
 - c. Choose **Read** for **Privilege** field.
 - d. Choose **All Manufacturer Orders** for **Criteria** field.
 - e. Choose both visible and invisible/disabled attributes in the **Applied to** field.
 - f. Click **OK**.

This opens privilege information screen for MCO.

21. Navigate to **Where Used** tab.
22. Click  button to select roles and assign to the created privilege.
23. Modify the **Read Changes** and **Read Items** to include **Admin** user.
24. Click **OK**.
25. Navigate to **Admin, Data Settings** and double click **Classes**
26. Double click **Parts** in Classes window.
27. Navigate to **User Interface Tabs** tab.
28. Double click **Page Two**.
29. Navigate to **Attributes Page Two** tab.
30. Check for the attribute **Numeric01** and double click it and change the **Name** to **ERP Manufacturer Cost**.

Note: If the user does not have Sites version on the Agile application then, perform the steps till the end of this section. Else move to the next section.

31. Navigate to **Admin, Data Settings** and double click **Classes**.

32. Double click **Parts** in Classes window.

Note: Repeat the process also for Document.

33. Navigate to **User Interface Tabs** tab.
34. Double click **Page Two**.
35. Navigate to **Attributes Page Two** tab.
36. Check for the **MultiList01** and double click it and change the **Name** to *OrganizationCodes*.

You also need to assign the values that are specific to sites or organization codes on the Agile side.

37. Click **New List** button to create the **List** of values.
38. Click **OK**.

This opens Create a new list value screen.

39. Enter the values for **Name** and **Description** specifying the list of Organizations used.
40. Click **Add**.
41. Navigate to **List** tab.
42. Click  button to add the batch list.
43. Add batch list values in the pop up window.
44. Click **OK**.
45. Ensure that **Page Two** on these classes in enabled.

Creating Auto Numbers

To create auto numbers:

1. Navigate to **Admin, Data Settings, AutoNumbers**.
2. Click  button to create auto numbers for NPR Document Number.
3. Enter the following fields in the Define the AutoNumber screen.
 - a. Enter name as NPR Document Number
 - b. Choose **Yes** for **Enabled**.
 - c. Choose **Custom** for **Type**.

- d. Choose **Document** for **Where Used**.
 - e. Choose **com.oracle.aia.npr.NPRAutoNumber** for **Custom AutoNumber**.
 - f. Click **OK**.
4. Click  button to create auto numbers for NPR Part Number.
 5. Enter the following fields in the Define the AutoNumber screen:
 - a. Enter name as NPR Part Number
 - b. Choose **Yes** for **Enabled**.
 - c. Choose **Custom** for **Type**.
 - d. Choose **Part** for **Where Used**.
 - e. Choose **com.oracle.aia.npr.NPRAutoNumber** for **Custom AutoNumber**.
 - f. Click **OK**.

Updating Change Order Page Two Fields

To update Change Order Page Two fields:

1. Navigate to **Admin, DataSettings, Classes**.
2. Double click **Classes** and navigate to **Changes, Change Orders**.
3. Double click **Change Orders** and navigate to **User Interface Tabs** in **Change Order** window.
4. Double click **Page Two** and Navigate to **Attribute Page Two** tab.
5. Select **Text02** and double click.
6. Set **Visible** to **Yes** in **Attributes Text02** window.
7. Click **Save**.
8. Navigate to **Admin, User Settings, Privileges** and double click **Read**.
9. Click  to create a new Read privilege to read all the ECO fields.
10. Select required fields in **Applied To** field in **Read Changes Page Two** window.
11. Click **OK**.
12. Navigate to **Where Used** tab.
13. Click  to select roles and select appropriate users in **Select Roles** window.

Use the same procedure that you used for setting Read privileges and set Modify privilege for ECO fields.

Configuring Sites

You need to configure sites only if the Agile application is enabled with Sites version.

To configure sites:

1. Login to web client using `http://<AGILE_HOSTNAME>/Agile/PLMServlet`.
2. Click  button.
3. Select **Sites** from the options.
4. Select *Site* for **Type** and enter **Site Name**.
5. Click **Finish**.

Configuring Sites Attributes

To configure Site attributes:

1. Navigate to **Admin, Data Settings, Classes**.
2. Double click **Classes** and navigate to **Items, Parts** in Classes window.
3. Double click **Parts** and navigate to **User Interface Tabs, Sites**.
4. Double click **Sites** and navigate to **Attributes: Sites** tab.
5. Select **Numeric01** and double click and in the window that opens
 - a. Change **Name** to **UnitCostAttribute**.
 - b. Set **Visibility** to **Yes**.

Setting up SAP

SAP ALE (Application Link Enabling) interface is a part of integration layer within SAP's Business Framework Architecture (BFA). It is a component based architecture that enables business process integration and asynchronous data communication either between two or more SAP systems or between SAP and external systems.

Application systems are loosely coupled in an ALE integrated system and the data is exchanged asynchronously. Consistency is maintained as data is exchanged between application systems in a controlled manner.

The following are the details that have to be maintained for ALE Configuration. Each step is dealt in detail with the help of a screen shots.

Defining Logical System

1. Assigning Logical Systems
2. Modeling Distribution Scenario
3. Defining RFC Destination
4. Defining Ports
5. Defining Partner Profiles
6. Activation of Change Pointers Globally

Defining Logical System

1. Enter transaction code SALE in the transaction space. Go to *Sending and Receiving Systems > Logical Systems*. Select Define Logical System option.
2. In *Change View "Logical System" Overview* screen, select **New Entries** option.
3. In *New Entries: Overview of Added Entries* screen, type in the **logical system names** which have to be assigned to the systems that are in communication and **save** the entries.

Assigning Logical Systems

1. Enter the transaction code SALE. Go to *Sending and Receiving Systems > Logical Systems*. Select **Assign Client to Logical Systems** option.
2. In *Change View "Clients": Overview* screen, select **New Entries** option.
3. As per the selection, user would be redirected to the *New Entries: Details of Added Entries* screen. Enter the Client & Logical System defined earlier. Also enter the other appropriate values and **save** the data.

Modeling the Distribution Scenario

1. Enter transaction code **BD64**, switch to **edit** mode and select **Create Model View**.
2. In *Create Model View* screen, enter **Short text**, **Technical name**, **Start date** and **End Date**.
3. Select the Model view and Add Message Type 'MATMAS. Save the entries. Select the Model view and then choose the EDIT option in the menu bar. Choose model view & then Distribute. The Model view is Distributed now.

Defining RFC Destination

1. Enter transaction **SM59**, choose **TCP/IP connections** and click on **Create** button in the menu..
2. In *RFC Destination* screen, enter data in **RFC destination**, **Connection type** as **T** and **Description**, respectively.

- a. Click **Enter** to enable TCP/IP connection related fields.
- b. Choose **Registration** and provide **Program ID** and **save** the entries.

Defining Ports

1. Enter transaction code **WE21** in the transaction space.
 - c. Select **Transactional RFC** and choose **Create** option.
2. In *Ports in IDoc processing* pop-up, select **Generate port name** option.
 - d. Provide **port name**, if **Own port name** option is selected.
3. In *creating a tRFC port* screen, enter **Description**, **RFC Destination** and select an appropriate **Version** and **save** the entries.

Defining Partner Profiles

1. Enter transaction code **WE20** in the transaction space.
2. From the drop down list, choose **Partner Type LS** and select **Create** option.
3. In *Partner profiles* screen, add message type **SYNCH** in **out bound parameters** and **MATMAS** in **inbound parameters**. Provide any other relevant information, like ports, idoc type and **save** the inputs.

Partner profiles: Outbound parameters screen displays the parameters and the setup of *ALE Configuration* is completed.

Activating Change Pointers Globally

This section explains about the configuration of **Change Pointers** for triggering **MATMAS Idoc** to send **Material Attributes** from SAP to Agile.

Enter transaction code **BD61** in the transaction area. In the *Activate Change Pointers Generally* screen, select **Change Pointers** checkbox and save the transaction.

Activation of Change Pointers for MATMAS Message Type

Enter transaction code **BD50**. In *Change View "Activate Change Pointers for Message Type": Overview* screen, select **MATMAS** message type checkbox and Save the transaction.

Activation of Change pointers for Individual fields in Material Master

Enter transaction code **BD52**. In the work area gives the Message Type as **MATMAS** and click continue. Delete those fields for which Change Pointer activation are not required. Save the transaction.

Reference Material Setup in SAP

To create an Item in SAP, reference material need to be configured based on the Material type. In case if the Item need to be created in more than one Plant then reference material need to be maintained in all the Plants .The purpose of this reference material is to default all the mandatory values which are needed for creation of material in SAP. This reference material varies from customer to customer based on their implementation setup.

SQL Script for Loading Cross-Reference Data

There is no utility in 11g to load cross-reference records similar to 10g. However, this can be accomplished with an SQL script.

The following is an example of a SQL script that loads cross-reference records for the XRef table, ITEM_ITEMID with columns AGILE_01 and SAP_01. This sample scripts allows you to build XREF records for a single item.You can modify this SQL script to suit your specific requirements.

```

DECLARE

XrefTableName_vc2 VARCHAR2 (2000);

XrefColumnName1_vc2 VARCHAR2 (2000);

XrefColumnName2_vc2 VARCHAR2 (2000);

XrefColumnName3_vc2 VARCHAR2 (2000);

Value_vc2 VARCHAR2 (2000);

RowNumber_vc2 VARCHAR2 (48);

IsDeleted_vc2 VARCHAR2 (1);

LastModified_ts TIMESTAMP (6);

BEGIN

/* The following values need to be set just once per load*/

XrefTableName_vc2 := 'oramds:/apps/AIAMetaData/xref/ITEM_ITEMID.xref';

IsDeleted_vc2 := 'N';

XrefColumnName1_vc2 := 'COMMON';

XrefColumnName2_vc2 := 'AGILE_01';

XrefColumnName3_vc2 := 'SAP_01';

```

```

/* You'll just need to change the Value_vc2 variable for your specific edge app values
*/

/* Row Number is unique to a group of three inserts and ties them together. It's a system
generated guid in all cases */

/* Copy this section as many times as needed for each set of three records you need inserted */

/***** Begin set of 3 inserts
*****/

RowNumber_vc2 := SYS_GUID;

/* Common row should have a guid for its value */

Value_vc2 := SYS_GUID;

LastModified_ts := SYSTIMESTAMP;

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values
(XrefTableName_vc2, XrefColumnName1_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/* Value specific to each application, for Agile value generation please check XREF_
Instructions.doc */

Value_vc2 := 'AgileValue1';

LastModified_ts := SYSTIMESTAMP;

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values
(XrefTableName_vc2, XrefColumnName2_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/* Value specific to each application, for SAP value generation please check XREF_
Instructions.doc */

Value_vc2 := 'SAPValue1';

```

```

LastModified_ts := SYSTIMESTAMP;

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values
(XrefTableName_vc2, XrefColumnName3_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/***** End of set of 3 inserts
*****/

END;

```

The following is an example of a SQL script that loads cross-reference records for the XRef table, CHANGE_CHANGEID with columns AGILE_01 and SAP_01. You can modify this SQL script to suit your specific requirements.

```

DECLARE

XrefTableName_vc2 VARCHAR2 (2000);

XrefColumnName1_vc2 VARCHAR2 (2000);

XrefColumnName2_vc2 VARCHAR2 (2000);

XrefColumnName3_vc2 VARCHAR2 (2000);

Value_vc2 VARCHAR2 (2000);

RowNumber_vc2 VARCHAR2 (48);

IsDeleted_vc2 VARCHAR2 (1);

LastModified_ts TIMESTAMP (6);

BEGIN

/* The following values need to be set just once per load*/

XrefTableName_vc2 := 'oramds:/apps/AIAMetaData/xref/CHANGE_
CHANGEID.xref';

```

```

IsDeleted_vc2 := 'N';

XrefColumnName1_vc2 := 'COMMON';

XrefColumnName2_vc2 := 'AGILE_01';

XrefColumnName3_vc2 := 'SAP_01';

/* You'll just need to change the Value_vc2 variable for your specific edge app values
*/

/* Row Number is unique to a group of three inserts and ties them together. Its a
system generated guid in all cases */

/* Copy this section as many times as needed for each set of three records you need
inserted */

/***** Begin set of 3 inserts
*****/

RowNumber_vc2 := SYS_GUID;

/* Common row should have a guid for its value */

Value_vc2 := SYS_GUID;

LastModified_ts := SYSTIMESTAMP;

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values
(XrefTableName_vc2, XrefColumnName1_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/* Value specific to each application, for Agile value generation please check XREF_
Instructions.doc */

Value_vc2 := 'AgileValue1';

LastModified_ts := SYSTIMESTAMP;

```

```

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values
(XrefTableName_vc2, XrefColumnName2_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/* Value specific to each application, for SAP value generation please check XREF_
Instructions.doc */

Value_vc2 := 'SAPValue1';

LastModified_ts := SYSTIMESTAMP;

Insert into XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_
NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) values

(XrefTableName_vc2, XrefColumnName3_vc2, RowNumber_vc2, Value_vc2,
IsDeleted_vc2, LastModified_ts);

/***** End of set of 3 inserts
*****/

END;
```

Identifying Cross-Reference Data

This pre-built integration uses the xref_data table present in Metadata database (MDS) to maintain a cross-reference between Agile and SAP. This cross-reference information helps map Agile Parts/Documents/Change Orders to SAP Items/Change Orders.

There are two main virtual tables in the AIA_XREF schemas XREF_DATA table that maintain this cross-reference information.

CHANGE_CHANGEID - maintains all the Change Order information

ITEM_ITEMID - maintains Item information.

Example:

- A Change Order ECO001 contains two revised items

- P0001 in site 'Detroit'
- P0002 in site 'Michigan'
- Both these revised items have component items.
 - P0001 has component items C0001 and C0002
 - P0002 has component items C0003 and C0004
- When this Change Order is released from Agile to the SAP, the following entries are made in the CHANGE_CHANGEID virtual table.

XREF_TABLE	XREF_COLUMN	ROW_NUMBER	VALUE
CHANGE_CHANGEID	AGILE_01	E45E015046AF11DD9 F2E436FB39961A8	ECO001::DETROIT
CHANGE_CHANGEID	COMMON	E45E015046AF11DD9 F2E436FB39961A8	2d3738333032373031 32383837353631
CHANGE_CHANGEID	SAP_01	E45E015046AF11DD9 F2E436FB39961A8	11075
CHANGE_CHANGEID	AGILE_01	E45E015046AF11DD9 F2E436FB39961A9	ECO001::MICHIGAN
CHANGE_CHANGEID	COMMON	E45E015046AF11DD9 F2E436FB39961A9	2d3738333032373031 32383837353632
CHANGE_CHANGEID	SAP_01	E45E015046AF11DD9 F2E436FB39961A9	11076

- The first row entry is made by the Agile BPEL flow for Change Order number ECO001 that is created on an item, which belongs to a site mapped to the 0001 Plant in SAP.
- The second entry (Common) is also created by the Agile BPEL flow. It indicates the common "business component id" for this particular in integration entity and is used for linking change orders to SAP Change Orders.
- The third row entry represents the SAP change id corresponding to the Agile change order ECO001. Another set of entries will be made for the change order ECO0001 for site PAV0.
- For each revised item and component items in the Change Order, entries will be made into the ITEM_ITEMID virtual table.

For example: For ECO001, the following entries are made in the ITEM_ITEMID table:

XREF_TABLE	XREF_COLUMN	ROW_NUMBER	VALUE
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDFB	P0001::DETROIT
ITEM_ITEMID	COMMON	0078BE703EC711DD	353138353737393537

XREF_TABLE	XREF_COLUMN	ROW_NUMBER	VALUE
		BF9CA7AA7FE3BDFB	32383638303435
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDFB	66247::204
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDF C	P0002::MICHIGAN
ITEM_ITEMID	COMMON	0078BE703EC711DD BF9CA7AA7FE3BDF C	353138353737393537 32383638303436
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDF C	66248::207
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDF D	C0001::DETROIT
ITEM_ITEMID	COMMON	0078BE703EC711DD BF9CA7AA7FE3BDF D	353138353737393537 32383638303437
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDF D	66249::204
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDFE	C0002::DETROIT
ITEM_ITEMID	COMMON	0078BE703EC711DD BF9CA7AA7FE3BDFE	353138353737393537 32383638303438
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDFE	66250::204
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDFE	C0003::MICHIGAN
ITEM_ITEMID	COMMON	0078BE703EC711DD BF9CA7AA7FE3BDFE	353138353737393537 32383638303439
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDFE	66251::207
ITEM_ITEMID	AGILE_01	0078BE703EC711DD BF9CA7AA7FE3BDF G	C0004::MICHIGAN
ITEM_ITEMID	COMMON	0078BE703EC711DD BF9CA7AA7FE3BDF G	353138353737393537 32383638303440

XREF_TABLE	XREF_COLUMN	ROW_NUMBER	VALUE
ITEM_ITEMID	SAP_01	0078BE703EC711DD BF9CA7AA7FE3BDF G	66252::207

- The first row entry is made by the Agile PLM BPEL flow for part P0001. This part belongs to an Agile site that is mapped to site DETROIT.
- The second entry (Common) is also created by the Agile BPEL flow. It indicates the common "business component id" for this particular in integration entity and is used to link Agile Parts/Documents/Change orders to SAP Items/Change Orders.
- The third row entry represents the SAP inventory item id corresponding to the item P1B and the organization id for the item. The rest of the entries represent the revised and component items for the ECO001.
- The ITEM_ITEMID virtual table contains the similar xref entries for each item/part created through the new part request process.

Creating Cross-Reference Data

If data needs to be ported from other existing integrations to the Agile PLM pre-built integration, first the relationship between the Agile entities and the SAP entities should be established and each Agile site should be mapped to corresponding SAP plant by inserting the relevant data in the **xref_data** table.

Load the required integration data manually in the xref_data table to establish the link between Agile PLM and SAP. This data will map the Agile PLM entities to the SAP entities as described in the previous section.

Even for existing Agile PLM pre-built integrations, if an item or change order needs to be created in SAP and then it is created in Agile, for the pre-built integration to process the item xref entry for that item needs to be made. All the update (reverse) flows for the pre-built integration will update the item attributes in Agile only if there is an entry in the **xref_data** table for that particular item.

Cross Reference file is stored in Metadata database repository in the below path

oramds:/apps/AIAMetaData/xref/<xref-name>.xref where xref-name is ITEM_ITEMID or CHANGE_CHANGE_ID

The data that has to be inserted in the xref_data table should be put in an XML file with the following format.

This is a sample change order data file:

```

<xref xmlns="http://xmlns.oracle.com/xref">
  <table name="CHANGE_CHANGEID">
    <columns>
      <column name="SAP_01"/>
      <column name="COMMON"/>
      <column name="AGILE_01"/>
    </columns>
    <rows>
      <row>
        <cell colName="SAP_01">11075</cell>
        <cell colName="COMMON">2d373833303237303132383837353631</cell>
        <cell colName="AGILE_01">ECO001::DETROIT</cell>
      </row>
      <row>
        <cell colName="SAP_01">11076</cell>
        <cell colName="COMMON">2d373833303237303132383837353632</cell>
        <cell colName="AGILE_01"> ECO001::MICHIGAN</cell>
      </row>
    </rows>
  </table>
</xref>

```

The change id number that is inserted in the SAP_01 column for a particular change order can be obtained using the following query:-

```
Select change_id from eng_engineering_changes
```

```
where
```

```
change_notice=<AgileChangeOrder>;
```

- The business component id that is inserted in the COMMON column can be any unique number.
- The Agile change order number and the SAP organization corresponding to the Agile site are inserted into the AGILE_01 column separated by ":".

This is a sample Item Data file:

```
<xref xmlns="http://xmlns.oracle.com/xref">
```

```

<table name="ITEM_ITEMID">
  <columns>
    <column name="SAP_01"/>
    <column name="COMMON"/>
    <column name="AGILE_01"/>
  </columns>
<rows>
  <row>
    <cell colName="SAP_01">66247::0001</cell>
    <cell colName="COMMON">35313835373739353732383638303435</cell>
    <cell colName="AGILE_01"> P0001::DETROIT</cell>
  </row>
  <row>
    <cell colName="SAP_01">66248::PAV0</cell>
    <cell colName="COMMON">35313835373739353732383638303436</cell>
    <cell colName="AGILE_01"> P0002::MICHIGAN</cell>
  </row>
  <row>
    <cell colName="SAP_01">66249::0001</cell>
    <cell colName="COMMON">35313835373739353732383638303437</cell>
    <cell colName="AGILE_01"> C0001::DETROIT</cell>
  </row>
  <row>
    <cell colName="SAP_01">66250::0001</cell>
    <cell colName="COMMON">35313835373739353732383638303438</cell>
    <cell colName="AGILE_01"> C0002::DETROIT</cell>
  </row>
  <row>
    <cell colName="SAP_01">66251::PAV0</cell>
    <cell colName="COMMON">35313835373739353732383638303439</cell>
    <cell colName="AGILE_01"> C0003::MICHIGAN</cell>
  </row>
  <row>
    <cell colName="SAP_01">66252::PAV0</cell>

```

```

    <cell colName="COMMON">35313835373739353732383638303440</cell>
    <cell colName="AGILE_01"> C0004::MICHIGAN</cell>
  </row>
</rows>
</table>
</xref>

```

The Item inventory number and the organization id is inserted in the SAP_01 column separated by ":".

The business component id that is inserted in the COMMON column can be any unique number.

- The Agile item number and the SAP plant corresponding to the Agile site are inserted into the AGILE_01 column separated by ":".

Populating Cross-References

If you want to perform an initial data load yourself, after the data load is performed in edge applications, then you must manually populate the ITEM_ITEMID and CHANGE_CHANGEID cross-reference (XRef) tables after installing and configuring the PIP. You must manually add the cross-reference data into the ITEM_ITEMID and CHANGE_CHANGEID XRef tables by using SQL insert statements.

For each SAP item processed through initial loads, the following rows need to be created in the XRef data table:

- One row for Agile: AGILE_01
- One row for SAP: SAP_01
- One row for Common: COMMON

The physical XREF table (XREF_DATA) can be located in the database configured for FMW/SOA and contains the following columns:

XRef Table Format

Column Name	Description
XREF_TABLE_NAME	This column stores the XREF data types. For example: oramds:/apps/AIAMetaData/xref/ITEM_ITEMID.xref oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref

Column Name	Description
XREF_COLUMN_NAME	This column stores the values indicating the edge applications and COMMON value: AGILE_01 SAP_01 COMMON
ROW_NUMBER	This column stores the GUID.
IS_DELETED	This column indicates whether the column is deleted or not. For example, 'N'.
LAST_MODIFIED	This column stores last modified time.

ITEM_ITEMID XRef Table Value Format

XRef_Column_Name	Value
COMMON	GUID
AGILE_01	Agile ItemID::Site For example, Part1::DETROIT
SAP_01	SAP ItemID::Plant ID For example, 60031::0001

Sample SQL Insert Statements for ITEM_ITEMID Table:

For SAP_01:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER,
VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/ITEM_ITEMID.xref ', 'SAP_01',
'BD618D40B30C11DEBFA5D9490F57512E ', '532922::0001', 'N', SYSTIMESTAMP)
```

For AGILE_01:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER,
VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/ITEM_ITEMID.xref ', 'AGILE_01',
'BD618D40B30C11DEBFA5D9490F57512E', 'TM0101P::DETROIT', 'N', SYSTIMESTAMP)
```

For COMMON:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER,
VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/ITEM_ITEMID.xref ', 'COMMON ',
'BD618D40B30C11DEBFA5D9490F57512E', '2d373037303636323539363632323735', 'N',
```

SYSTIMESTAMP)

Sample Data for XRef ITEM_ITEMID Table

XRef_Table	XRef_Column	Row_Number	Value	IS_Deleted	Last_Modified
oramds:/apps/AIA MetaData/xref/ITEM_ITEMID.xref	SAP_01	BD618D40B30C11DEBFA5D9490F57512E	532922::0001	N	2012-4-11.11.29. 54.210000000
oramds:/apps/AIA MetaData/xref/ITEM_ITEMID.xref	AGILE_01	BD618D40B30C11DEBFA5D9490F57512E	TM0101P::DETROIT	N	2012-4-11.11.29. 54.210000000
oramds:/apps/AIA MetaData/xref/ITEM_ITEMID.xref	COMMON	BD618D40B30C11DEBFA5D9490F57512E	2d373037303636323539363632323735	N	2012-4-11.11.29. 54.210000000

CHANGE_CHANGEID XRef Table Value Format

XRef_Column_Name	Value
COMMON	GUID
AGILE_01	Agile ItemID::Site For example, Part1::DETROIT
SAP_01	SAP ChangeID

XRef_Column_Name	Value
	For example, 60031

Sample SQL Insert Statements for CHANGE_CHANGEID Table

For SAP_01:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref ', ' SAP_01',
'C7D0C3D0740D11E1BFF50FA2D024BE6E', '92219', 'N', SYSTIMESTAMP)
```

For AGILE_01:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref ', ' AGILE_01',
'C7D0C3D0740D11E1BFF50FA2D024BE6E ', ' C00374::V1', 'N', SYSTIMESTAMP)
```

For COMMON:

```
INSERT INTO XREF_DATA (XREF_TABLE_NAME, XREF_COLUMN_NAME, ROW_NUMBER, VALUE, IS_DELETED, LAST_MODIFIED) VALUES ('
oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref ', ' COMMON', '
C7D0C3D0740D11E1BFF50FA2D024BE6E ', '2d383932333633343735363134363035', 'N',
SYSTIMESTAMP)
```

Sample Data for CHANGE_CHANGEID Table

XRef_Table	XRef_Column	Row_Number	Value	IS_Deleted	Last_Modified
oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref	SAP_01	BD618D40B30C11DEBFA5D9490F57512E	92219	N	2012-4-11.11.29. 54.210000000
oramds:/apps/AIAMetaData/xref/CHANGE_CHANGEID.xref	AGILE_01	C7D0C3D0740D11E1BFF50FA2D024BE6E	C00374::DETROIT	N	2012-4-11.11.29. 54.210000000

XRef_Table	XRef_Column	Row_Number	Value	IS_Deleted	Last_Modified
D.xref					
oramds:/apps/AIA MetaData/xref/CH ANGE_CH ANGEI D.xref	COMMON	C7D0C3D0740 D11E1BFF50F A2D024BE6E	2d3839323336 333437353631 34363035	N	2012-4-11.11.29. 54.210000000

Configuring the Integration

This pre-built integration uses various configuration parameters that control the behavior of the flow. Standard AIA XML configuration file, **AIAConfigurationProperties.xml**, is used for capturing configuration parameters. AIA configuration file supports system level configuration parameters, service level parameters and module configuration parameters. System level parameters apply to all pre-built integrations running on the SOA suite. Service level parameters can be configured at the individual service levels, such as ABCS.

The configuration properties from Agile Module and SAP Module are listed separately in this section, only for the purpose of identification. The actual **AIAConfigurationProperties.xml** file on AIA Server is a merger of both.

Configuration Parameters

This pre-built integration uses the following type of configuration parameters -

- **PIP Level** configuration parameters: PIP Configuration parameters are implemented using AIA module configuration entry. The module configuration entry has a name and can contain any number of configuration parameters. A naming convention of *PIPS.PIPName* is used for naming modules. The parameters inside the module are named using with cascaded naming convention where individual words are separated with dots. For example, *agile.replicate.item*.
- **Service Level** configuration parameters: While most configuration requirements are satisfied by

the PIP Level configuration parameters, sometimes the behavior of a flow needs to be controlled at the service level. These parameters can be captured using AIA service configuration parameters. Service configuration entry is identified by the service name such as *CreateItemAgileReqABCImpl*. The parameter names themselves are named using cascaded naming convention as explained above.

Steps to upload to MDS

- a) Update the required property in AIAConfigurationProperties.xml file.
- b) Go to <AIA_HOME>\aia_instances\AIA1115\config' path and open the UpdateMetaDataDP.xml file and add <include name="config/AIAConfigurationProperties.xml"/>.
- c) Go to <AIA_HOME>\Infrastructure\Install\config and run the below command.
ant -f UpdateMetaData.xml

Note: Whenever the AIAConfigurationProperties.xml file is updated, the file must be updated in the MDS

Agile Configurations

Properties	(default) Value/Setting	Description
Module Name	Agile	
MULTISITE_ENABLED	TRUE	When set to True, the sites specified in Sites Tab of Items are used to determine the Plants in SAP to which they are mapped. When set to False, Page2 Multilist01 attribute is used to determine the Plants in SAP to which the Item will be extended to.
Item.UnitCostAttribute	Site.Numeric01	Determines the attribute to which the unit cost from SAP would be updated in Agile.
Change.TransferStatusAttribute	PageTwo.Text02	Determines the attribute to which the transfer status of a Change should be written. When the Change flow is from Agile to SAP, the possible values are "Transferred" or

Properties	(default) Value/Setting	Description
		"Errored". When the Change flow is from SAP to Agile, the value would be the same as that of the Status of the Change in all the Plants of SAP.
Service Name	CreateQueueService	
TRACE.LOG.ENABLED	false	Use tracelog for the flow
Service Name	QueueProcessorServiceImpl	
TRACE.LOG.ENABLED	false	Use tracelog for the flow
Service Name	UpdateItemAgileProvABCSImpl	
ABCSExtension.PreProcessABM	FALSE	User exit for the pre-process ABM should be called or not
ABCSExtension.PreProcessEBM	FALSE	User exit for the pre-process EBM should be called or not
ABCSExtension.PostProcessEBM	FALSE	User exit for the post-process EBM should be called or not
ABCSExtension.PostProcessABM	FALSE	User exit for the post-process ABM should be called or not
TRACE.LOG.ENABLED	FALSE	Use tracelog for the flow
ROUTE_TO_CAVS	FALSE	Route to CAVS, if set as True
Routing.ItemABSService.AGILE_01.EndpointURI	http://\${agile.host}:\${agile.port}/Agile/integration/services/ItemABS	Route to ItemABS
ItemResponseEBS.UpdateItemResponse.RouteToCAVS	FALSE	Route to CAVS is set to TRUE
Routing.ItemResponseEBS.UpdateItemResponse.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/syncresponsesimulator	If Route to CAVS set as true this endpoint URI will trigger
Service Name	ProcessEngineeringChangeOrderAgileReqABCSImpl	
ABCSExtension.PreProcessABM	FALSE	User exit for the pre-process ABM should be called or not
ABCSExtension.PreProcessEBM	FALSE	User exit for the pre-process EBM should be called or not
ABCSExtension.PostProcessE	FALSE	User exit for the post-process

Properties	(default) Value/Setting	Description
BM		EBM should be called or not
ABCSExtension.PostProcessABM	FALSE	User exit for the post-process ABM should be called or not
TRACE.LOG.ENABLED	FALSE	Use tracelog for the flow
ROUTE_TO_CAVS	FALSE	Route to CAVS, if set as True
Default.SystemID	AGILE_01	
Routing.ChangeABSService.RouteToCAVS	false	
Routing.ChangeABSService.AGILE_01.EndpointURI	http:// \${agile.host}:\${agile.port}/Agile/ integration/services/ChangeABS	
Routing.EngineeringChangeOrderEBS.CreateEngineeringChangeOrderList.RouteToCAVS	false	CAVS property set to false
Routing.EngineeringChangeOrderEBS.CreateEngineeringChangeOrderList.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS end point URI

Note: Multisite_Enabled property is governed by Distributed Processing aspects covered in Chapter 2: Process Integration for ECO/PREL. When it is set to TRUE (default), the Item.UnitCostAttribute is set to Site Tab Flex Attributes. You can use Numeric, Text or Money flex fields in the Site tab for these settings and is denoted by the first element, Site. For example, if Site.Numeric01 is set to FALSE, all these attributes are set to Page2 or Page3 flex fields. Hence, the settings need to be changed to PageTwo.Numeric01 or PageThree.Numeric01 accordingly. The names of the attributes can be derived from the ItemABM Schema, which can be found in Agile Application Interfaces.

SAP Configurations

Properties	(Default) Value/Setting	Description
ModuleName	SAP	
LANG_LOCALE	en-US	Used to specify the language code and locale of the SAP system
GLOBAL_LEVEL_BOM	FALSE	When this property is set to FALSE, in SAP the BOM are created at plant level and not

Properties	(Default) Value/Setting	Description
		at the global level. If set to TRUE, the BOM will be created at the global level.
DEFAULT_SYSTEM_ID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
MATERIAL_TYPE	FERT	Used to specify the material type in SAP to be "Finished Product"
SAP46_N_ABOVE	TRUE	Specifies that the version of SAP used is greater than 4.6.
BOM_USAGE	1	BOM_USAGE denotes the usage of the BOM. 1 indicates production level BOM. This value is dependent on the business process implemented at the client site. Some other values are: 2 indicates engineering/design BOM 3 indicates universal BOM 4 indicates plant maintenance BOM
ITEM_CATEGORY	L	ITEM_CATEGORY denotes the category of the item that is added to the BOM. L indicates stock item. This value is dependent on the business process implemented at the client site. Some other values are: N indicates non-stock item T denotes text item D denotes document item
ServiceName	ReserveItemSAPProvABCS	
ABCSEXTENSION.PREPROC ESSEBM	false	User exit for the pre-process EBM should be called or not

Properties	(Default) Value/Setting	Description
ABCSEXTENSION.POSTPRO CESSEBM	false	User exit for the post-process EBM should be called or not
ABCSEXTENSION.POSTPRO CESSITEMEBM	false	User exit for the post-process Item EBM should be called or not
ABCSEXTENSION.PREPROC ESSITEMEBM	false	User exit for the pre-process Item EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.ItemResponseEBS.Ro uteToCAVS	false	Route to CAVS, if set as True
Routing.ItemResponseEBS.CA VS.EndpointURI	http://\${fp.server.soaserverhost name}:\${fp.server.soaserverpo rt}/ AIAValidationSystemServlet/ asyncreponserecipient	CAVS Endpoint URI
Routing.GenerateltemNumber Service_Reserve.RouteToCAV S	false	Route to CAVS, if set as True
Routing.GenerateltemNumber Service_Reserve.SAP_01.End pointURI	http://\${fp.server.soaserverhost name}:\${fp.server.soaserverpo rt}/soa- infra/services/default/Reservelt emService/Reservelt emService_e ep	Reservelt emSAP runtime target endpoint URI
Routing.GenerateltemNumber Service_Reserve.CAVS.Endpo intURI	http://\${fp.server.soaserverhost name}:\${fp.server.soaserverpo rt}/AIAValidationSystemServlet /syncreponsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use tracelog for the flow
Service Name	CreateEngineeringChangeOrderListEBF	
ABCSEXTENSION.PREPROC ESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPRO	false	User exit for the post-process

Properties	(Default) Value/Setting	Description
CESSEBM		EBM should be called or not
ABCSEXTENSION.POSTPROCESSITEMEBM	false	User exit for the post-process Item EBM should be called or not
ABCSEXTENSION.PREPROCESSITEMEBM	false	User exit for the pre-process Item EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.ItemEBSV2.RouteToCAVS	false	Route to CAVS, if set as True
Routing.ItemEBSV2.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/ItemEBSV2/ItemEBSV2_ep	ItemEBS runtime target endpoint URI
Routing.ItemEBSV2.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
Routing.EngineeringChangeOrderResponseEBS.RouteToCAVS	false	Route to CAVS, if set as True
Routing.EngineeringChangeOrderResponseEBS.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/EngineeringChangeOrderResponseEBS!1.0/EngineeringChangeOrderResponseEBS_ep	EngineeringChangeOrderEBS runtime target endpoint URI
Routing.EngineeringChangeOrderResponseEBS.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/asyncreponserecipient A	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use tracelog for the flow

Properties	(Default) Value/Setting	Description
Service Name	CreateEngineeringChangeOrderListSAPProvABCS	
ABCSEXTENSION.PREPROCESSESSABM	false	User exit for the pre-process ABM should be called or not
ABCSEXTENSION.POSTPROCESSESSABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.PREPROCESSESBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPROCESSESBM	false	User exit for the post-process EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.CreateEngineeringChangeOrderService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateEngineeringChangeOrderService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-Infra/services/default/ECOService/ECORouterService_ep	CreateEngineeringChangeOrderService runtime target endpoint URI
Routing.CreateEngineeringChangeOrderService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/syncresponsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use tracelog for the flow
Service Name	SyncItemListsAPProvABCS	
ABCSEXTENSION.PREPROCESSESSREVLEVELABM	false	User exit for the pre-process ABM should be called or not
ABCSEXTENSION.POSTPROCESSESSREVLEVELABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.PREPROCESSESSAVEDDATAABM	false	User exit for the pre-process SAVED DATA ABM should be called or not
ABCSEXTENSION.POSTPROCESSESSAVEDDATAABM	false	User exit for the post-process SAVED DATA ABM should be called or not

Properties	(Default) Value/Setting	Description
ABCSEXTENSION.PREPROC ESSREFMATERIALABM	false	User exit for the pre-process REF MATERIAL ABM should be called or not
ABCSEXTENSION.POSTPRO CESSREFMATERIALABM	false	User exit for the post-process REF MATERIAL ABM should be called or not
ABCSEXTENSION.PREPROC ESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPRO CESSEBM	false	User exit for the post-process EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.Call_ItemListRespon seEBS.RouteToCAVS	false	Route to CAVS, if set as True
Routing.Call_ItemListRespon seEBS.CAVS.EndpointURI	http://\${fp.server.soaserverhost name}:\${fp.server.soaserverpo rt}/AIValidationSystemServlet / asyncreponserecipient	CAVS Endpoint URI
Routing.CreateReferencemater ial.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateReferencemater ial.SAP_01.EndpointURI	http://\${fp.server.soaserverhost name}:\${fp.server.soaserverpo rt}/soa- infra/services/default/ItemServi ceESB/ItemServiceESB_ep	CreateReferenceMaterial runtime target endpoint URI
Routing.CreateReferencemater ial.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname }:\${fp.server.soaserverport}/AI ValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
Routing.CreateDetailReference material.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateDetailReference material.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname }:\${fp.server.soaserverport}/so a- infra/services/default/ItemServi	CreateDetailReferenceMaterial runtime target endpoint URI

Properties	(Default) Value/Setting	Description
	ceESB/ItemServiceESB_ep	
Routing.CreateDetailReference material.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} }:\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
Routing.CreateItemService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateItemService.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} }:\${fp.server.soaserverport}/so a- Infra/services/default/ItemServiceESB/ItemServiceESB_ep	CreateItemService runtime target endpoint URI
Routing.CreateItemService.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} }:\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
Routing.CreateItemRevisionService.RouteToCAVS	False	Route to CAVS, if set as True
Routing.CreateItemRevisionService.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} }:\${fp.server.soaserverport}/so a- Infra/services/default/ItemServiceESB/ItemServiceESB_ep	CreateItemRevisionService runtime target endpoint URI
Routing.CreateItemRevisionService.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} }:\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	False	Use tracelog for the flow
ServiceName	ProcessBillOfMaterialsListSAPProvABCS	
ABCSEXTENSION.PREPROCESSABM	false	User exit for the pre-process ABM should be called or not
ABCSEXTENSION.POSTPROCESSABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.PREPROCESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPRO	false	User exit for the post-process

Properties	(Default) Value/Setting	Description
CESSEBM		EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.GlobalBillOfMaterialExistenceCheckService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.GlobalBillOfMaterialExistenceCheckService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	Global BillOfMaterialExistenceCheckService runtime target endpoint URI
Routing.GlobalBillOfMaterialExistenceCheckService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulatorr	CAVS Endpoint URI
Routing.BillOfMaterialExistenceCheckService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.BillOfMaterialExistenceCheckService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	BillOfMaterialExistenceCheckService runtime target endpoint URI
Routing.BillOfMaterialExistenceCheckService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	False	Use tracelog for the flow
ServiceName	CreateBillOfMaterialsListSAPProvABCImpl	
ABCSEXTENSION.PREPROCESSESBOMEXISTENCECHECKABM	false	User exit for the pre-process BOM Existence Check ABM should be called or not
ABCSEXTENSION.POSTPROCESSESBOMEXISTENCECHECKABM	false	User exit for the post-process BOM Existence Check ABM should be called or not
ABCSEXTENSION.PREPROCESSESBOMPLANTEXTENSION	false	User exit for the pre-process BOM Plant Existence Check

Properties	(Default) Value/Setting	Description
ABM		ABM should be called or not
ABCSEXTENSION.POSTPROCESSBOMPLANTEXTENSIONABM	false	User exit for the post-process BOM Plant Existence Check ABM should be called or not
ABCSEXTENSION.PREPROCESSBOMCREATEABM	false	User exit for the pre-process BOM Create ABM should be called or not
ABCSEXTENSION.POSTPROCESSBOMCREATEABM	false	User exit for the post-process BOM Create ABM should be called or not
ABCSEXTENSION.PREPROCESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPROCESSEBM	false	User exit for the post-process EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.BillOfMaterialsResponseEBS.RouteToCAVS	False	Route to CAVS, if set as True
Routing.BillOfMaterialsResponseEBS.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/asyncresponserecipient	CAVS Endpoint URI
Routing.CreateGlobalBillOfMaterialService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateGlobalBillOfMaterialService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	CreateBillOfMaterialService runtime target endpoint URI
Routing.CreateGlobalBillOfMaterialService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
Routing.CreateBillOfMaterialService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.CreateBillOfMaterialService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}	CreateBillOfMaterialService runtime target endpoint URI

Properties	(Default) Value/Setting	Description
	rt}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	
Routing.CreateBillOfMaterialService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
Routing.BOMPlantExtensionService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.BOMPlantExtensionService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	BOMPlantExtensionService runtime target endpoint URI
Routing.BOMPlantExtensionService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
Routing.BillOfMaterialExistenceCheckService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.BillOfMaterialExistenceCheckService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	BillOfMaterialExistenceCheckService runtime target endpoint URI
Routing.BillOfMaterialExistenceCheckService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use tracelog for the flow
ServiceName	UpdateBillOfMaterialsListSAPProvABCImpl	
ABCSEXTENSION.PREPROCESSBOMEXISTENCECHECKABM	false	User exit for the pre-process BOM Existence Check ABM should be called or not
ABCSEXTENSION.POSTPROCESSBOMEXISTENCECHECKABM	false	User exit for the post-process BOM Existence Check ABM should be called or not
ABCSEXTENSION.PREPROCESSBOMPLANTEXTENSION	false	User exit for the pre-process BOM Plant Existence Check

Properties	(Default) Value/Setting	Description
ABM		ABM should be called or not
ABCSEXTENSION.POSTPROCESSBOMPLANTEXTENSIONABM	false	User exit for the post-process BOM Plant Existence Check ABM should be called or not
ABCSEXTENSION.PREPROCESSBOMUPDATEABM	false	User exit for the pre-process BOM Update ABM should be called or not
ABCSEXTENSION.POSTPROCESSBOMUPDATEABM	false	User exit for the post-process BOM Update ABM should be called or not
ABCSEXTENSION.PREPROCESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPROCESSEBM	false	User exit for the post-process EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.BillOfMaterialsResponseEBS.RouteToCAVS	false	Route to CAVS, if set as True
Routing.BillOfMaterialsResponseEBS.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIValidationSystemServlet/asyncresponserecipient	CAVS Endpoint URI
Routing.UpdateGlobalBillOfMaterialService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.UpdateGlobalBillOfMaterialService.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	UpdateBillOfMaterialService runtime target endpoint URI
Routing.UpdateGlobalBillOfMaterialService.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIValidationSystemServlet/syncresponsesimulator	CAVS Endpoint URI
Routing.BillOfMaterialExistenceCheckService.RouteToCAVS	false	Route to CAVS, if set as True

Properties	(Default) Value/Setting	Description
Routing.BillOfMaterialExistenceCheckService.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/soa- infra/services/default/BOMServiceESB/BOMServiceESB_ep	BillOfMaterialExistenceCheckService runtime target endpoint URI
Routing.BillOfMaterialExistenceCheckService.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
Routing.BOMPlantExtensionService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.BOMPlantExtensionService.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/soa- infra/services/default/BOMServiceESB/BOMServiceESB_ep	BOMPlantExtensionService runtime target endpoint URI
Routing.BOMPlantExtensionService.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
Routing.UpdateBillOfMaterialService.RouteToCAVS	false	Route to CAVS, if set as True
Routing.UpdateBillOfMaterialService.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/soa- infra/services/default/BOMServiceESB/BOMServiceESB_ep	UpdateBillOfMaterialService runtime target endpoint URI
Routing.UpdateBillOfMaterialService.CAVS.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/AI AValidationSystemServlet/sync responsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use trace log for the flow
ServiceName	UpdateItemListSAPReqABCImpl	
ABCEXTENSION.PREPROCESSESSABM	false	User exit for the pre-process ABM should be called or not

Properties	(Default) Value/Setting	Description
ABCSEXTENSION.PREPROC ESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPRO CESSABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.POSTPRO CESSEBM	false	User exit for the post-process EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.ItemEBSV2.RouteToCAVS	false	Route to CAVS, if set as True
Routing.ItemEBSV2.SAP_01.EndpointURI	http:// \${fp.server.soaserverhostname} :\${fp.server.soaserverport}/soa- infra/services/default/ItemEBS V2/ItemEBSV2_ep	ItemEBS runtime target endpoint URI
Routing.ItemEBSV2.CAVS.EndpointURI	http://\${fp.server.soaserverhostname};:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
ServiceName	UpdateItemListSAPReqABCS	
ABCSEXTENSION.POSTPRO CESSABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.PREPROC ESSABM	false	User exit for the pre-process ABM should be called or not
Default.SystemID	SAP_01	
TRACE.LOG.ENABLED	false	
ServiceName	ProcessBillOfMaterialsListSAPProvABCImpl	
ABCSEXTENSION.PREPROC ESSABM	false	User exit for the pre-process ABM should be called or not
ABCSEXTENSION.POSTPRO CESSABM	false	User exit for the post-process ABM should be called or not
ABCSEXTENSION.PREPROC ESSEBM	false	User exit for the pre-process EBM should be called or not
ABCSEXTENSION.POSTPRO	false	User exit for the post-process

Properties	(Default) Value/Setting	Description
CESSEBM		EBM should be called or not
Default.SystemID	SAP_01	Used to get the default XREF Target column name when TargetId is empty in incoming EBM. It should be kept SAP_01 as default for this release
Routing.Retrieve_BOMData.RouteToCAVS	false	Route to CAVS, if set as True
Routing.Retrieve_BOMData.SAP_01.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/soa-infra/services/default/BOMServiceESB/BOMServiceESB_ep	ProcessBillOfMaterialsListImpl runtime target endpoint URI
Routing.Retrieve_BOMData.CAVS.EndpointURI	http://\${fp.server.soaserverhostname}:\${fp.server.soaserverport}/AIAValidationSystemServlet/synresponsesimulator	CAVS Endpoint URI
TRACE.LOG.ENABLED	false	Use tracelog for the flow

Setting up National Language Support

Here are the steps to set up National Language Support (NSL):

- Setting up NLS in Agile
- Setting up NLS in FMW for Agile
- Editing AIAConfigurations
- Setting Up DVMs
- Setting up the DVMs for NLS

Setting up NLS in Agile

To set up NLS in Agile:

1. In Agile Java Client, for each subscriber of MCO, SCO, ECO, go to the subscriber details page and set the language.

Note: For ease of understanding, we are using "Japanese" as language.

2. Change the language preference of all the users creating CO and Items, including integration user, to Japanese.

Setting up NLS in FMW for Agile

To set up NLS in FMW for Agile:

1. Edit the following XSL file and replace the hard-coded string 'Preliminary' to Japanese equivalent coming from Agile List values

VAIA_HOME\services\core\Agile\UtilityServices\QueueProcessorServiceImpl\AgileData_to_AgileCreateEngineeringChangeOrderListABM_Impl.xml

2. Edit the following XSL file and replace the following values:

VAIA_HOME\services\core\Agile\RequesterABCS\ProcessEngineeringChangeOrderAgileReqABCSImpl\AgileCreateEngineeringChangeOrderListABM_to_CreateEngineeringChangeOrderListEBM_Impl.xml

Replace the hard-coded string 'Preliminary' to the Japanese equivalent coming from Agile list values.

Replace the hard-coded string 'SCO' to Japanese equivalent coming from Agile list values.

3. Edit the following XSL file and replace hard coded strings 'Errored' with Japanese equivalent

VAIA_HOME\services\core\Agile\RequesterABCS\ProcessEngineeringChangeOrderAgileReqABCSImpl\AgileCreateEngineeringChangeOrderListABM_to_AgileUpdateEngineeringChangeOrderListABM_Impl.xml

4. Edit the following XSL file and replace the following values:

VAIA_HOME\services\core\Agile\RequesterABCS\ProcessEngineeringChangeOrderAgileReqABCSImpl\UpdateEngineeringChangeOrderListEBM_to_AgileUpdateEngineeringChangeOrderListABM_Impl.xml

Replace the hard coded string 'Transferred' with its Japanese equivalent.

Replace the hard coded string 'Errored' with its Japanese equivalent..

Note: Use an UTF-8 based editor like JEdit to carry out these changes. Choose UTF-8 as the character set while loading the file to edit. Set FTP transfer mode to Binary while uploading these files to AIA components.

Editing AIAConfigurations

Edit the property 'LANG_LOCALE' under module 'Agile' to 'Japanese'. The language value is available under column COMMON in the DVM - 'LANGUAGE_CODE'.

Setting up DVMs

To set up DVMs, enter the Japanese language values under Agile column, AGILE_01 in the following DVMs:

- ITEM_PRIMARYCLASSIFICATIONCODE
- ITEM_STATUS_CODE
- ITEM_UOM_CODE
- ECO_STATUS_CODE

After all the xsls are modified, the corresponding process flows need to be redeployed for the xsl changes to take effect.

Setting up the DVMs for NLS

To set up DVMs for NLS, configure SAP_01 with the appropriate language code of SAP in the *LANGUAGE_CODE* DVM column.

Domain Value Maps

DVMs are a standard feature of the Oracle SOA Suite. They enable you to equate lookup codes and other static values across applications, for example, FOOT and FT or US and USA. DVMs are static in nature, though administrators can add additional maps as needed. Transactional business processes never update DVMs; they only read from them. DVMs are stored in XML files and cached in memory at run time.

DVM types are seeded for the Oracle Design to Release: Agile Product Lifecycle Management - SAP flows and administrators can extend the list of mapped values by adding more maps. The DVM data should be synchronized with what the participating applications use. This synchronization should occur before any initial loads are run or any incremental transactional flows are initiated.

During installation, the DVMs used for the pre-built integration are imported with default data mappings. The values mapped by these DVMs must be changed as needed. Many DVMs are seeded and do not need to be changed. Because most of the Agile PLM attributes being mapped are list values, the Agile PLM data is not seeded and should be changed accordingly.

Out-of-the-Box DVMs

During installation, the DVMs used for the pre-built integration are imported with default data mappings. The values mapped by these DVMs have to be changed as needed. There are many DVMs that are seeded and need not be touched. Since most of the Agile attributes being mapped are list values, the Agile data is not seeded. Hence, it should be changed accordingly and then updated in the MDS.

Some of the most used DVMs, with their Out-of-the-Box values, are listed below. You can modify their values as per your requirements. For complete list of available DVMs, including the most used ones, see the List of DVMs.

Note: You can only add more rows of value mappings but should not change the DVM name, the column names, or the number of columns.

Sample DVMs

These are the sample domain value mapping (DVM):

ECO_ENGINEERINGCHANGEORDERLINE_STATUS_CODE

Used for SAP attribute -

ECO_ATTR/ECO_REVISSED_ITEM_TYPE/ECO_REVISSED_ITEM_TYPE_ITEM/STATUS_NAME

SAP_01	COMMON
Release	RELEASE
Open1	OPEN_1
EBS_Release	EBS_RELEASE
EBS Open	EBS_OPEN
Implemented	IMPLEMENTED
Create	CREATE
In Progress	IN_PROGRESS
Scheduled1	SCHEDULED_1
Cancelled	CANCELLED
Approval	APPROVAL
Pending Response	PENDING_RESPONSE
EBS_Create	EBS_CREATE
EBS_Review	EBS_REVIEW

SAP_01	COMMON
EBS_Archive	EBS_ARCHIVE
Completed	COMPLETED
Hold	HOLD
Draft	DRAFT
Review	REVIEW
Released	RELEASED
Archive	ARCHIVE

ECO_STATUS_CODE

Used for SAP attribute - ECO_CHANGE_ORDER_TYPE/STATUS_NAME, ECO_REVISIED_ITEM_TYPE/STATUS_NAME. Use for Agile's Status attribute of a Change.

SAP_01	COMMON	AGILE_01
Release	RELEASE	
EBS_Approval	EBS_APPROVAL	
Open1	OPEN_1	
EBS_Release	EBS_RELEASE	
EBS Open	EBS_OPEN	
Implemented	IMPLEMENTED	Implemented
Create	CREATE	
In Progress	IN_PROGRESS	
Scheduled	SCHEDULED	Released
Cancelled	CANCELLED	
Approval	APPROVAL	
Pending Response	PENDING_RESPONSE	
EBS_Create	EBS_CREATE	
EBS_Review	EBS_REVIEW	
EBS_Archive	EBS_ARCHIVE	
Completed	COMPLETED	
Hold	HOLD	
Draft	DRAFT	

SAP_01	COMMON	AGILE_01
Review	REVIEW	
Released	RELEASED	
Archive	ARCHIVE	

ITEM_STATUS_CODE

This value is used for SAP Item attribute ITEM_OBJ/MAIN_OBJ_TYPE/INVENTORY_ITEM_STATUS_CODE. The Agile Item Lifecycle phase attribute is mapped.

SAP_01	COMMON	AGILE_01
A	A	
Concept	CONCEPT	
Design	DESIGN	Preliminary
Engineer	ENGINEER	Pilot
Inactive	INACTIVE	Inactive, 02
Lease	LEASE	
Non-Stock	NONSTOCK	
Nwe B	NWEB	
OPM	OPM	
Obsolete	OBSOLETE	Obsolete, 02
Pending	PENDING	
Phase-Out	PHASEOUT	
Production	PRODUCTION	Production, 03
Prototype	PROTOTYPE	Prototype
R&D	R&D	

AGILE_SITE_TARGET_MAPPING

DEFAULT_MASTER_ORG in SAP is specified here. This is used when the Multisite Enabled property is set to False and no Plant is specified for the Item where it extends to.

When the Multisite_Enabled property is true, the Sites in Agile are mapped to various Plants in SAP. A Site could be mapped to multiple Plants in the SAP column with "|" delimiter.

AGILE_TARGET_SITE_MAPPING

The SAP Plants to Agile Sites are mapped. This is used for SAP to Agile flows. There is one to one mapping between the SAP Plant to Agile Site.

List of DVMs

This table describes the domain value mappings and their description:

Note: Important DVMs are listed in bold typeface.

Domain Value Map	Description
ITEM_UOM_CODE:	This DVM is used to maintain the Unit of Measure values of Agile corresponding to SAP
REFERENCEMATERIALS:	We are maintaining this DVM to populate the mandatory parameters of SAP BasicData1, Basic data2, MRP1, MRP2, MRP3 views which are not being sent from Agile
LANGUAGE_CODE:	This DVM is used to populate the Multi languages, as of now we are dealing with only English language
ITEM_STATUS_CODE:	This DVM is used to maintain the Life Cycle Phase codes and Special Plant Material Status of SAP
ITEM_PRIMARYCLASSIFICATIONCODE:	This DVM is used to populate the Material type of SAP
ECO_STATUS_CODE:	The DVM is used to handle the Status Codes of Change Order in SAP.
AGILE_SITE_TARGET_MAPPING	This DVM is used to map SAP Plants to Agile Sites. This is used for Agile to SAP flows
AGILE_TARGET_SITE_MAPPING	This DVM is used to map SAP Plants to Agile Sites. This is used for SAP to Agile flows
ECO_ENGINEERINGCHANGEORDERLINE_RE VISED BILLOFMATERIALS_BILLOFMATERIA LSCOMPONENTITEM_CHANGETYPECODE:	We are using this DVM to recognize the Creation or updation of Bill of Materials in Agile

Application Interfaces

Application Interfaces are the web services and APIs that communicate and transact between Application and Integration Layers.

Agile PLM Interfaces

These are the Agile PLM interfaces used in this integration:

WSDLs

ItemABS.wsdl	Used to create an item in SAP
ItemABS.wsdl	Used to update an Item in SAP
ChangeABS.wsdl	Used to create an EngineeringChangeOrder in SAP

XSDs

ItemABM.xsd	Contains the Item Request and Response ABM
ItemABM.xsd	Contains the Update Item List Request and Response ABM
EngineeringChangeOrderABM.xsd	Contains CreateEngineeringChangeOrderListABM and CreateEngineeringChangeOrderListResponse ABM

SAP Interfaces

These are the SAP interfaces used in this integration:

WSDLs

Reserveltemservice.wsdl	The interface to the SAP Process Item API
GenerateItemNumberService_Reserve.wsdl	BAPI_STDMATERIAL_GETINTNUMBER
ItemServiceESB.wsdl	The interface to the SAP Process Item API -
CreateReferencematerial.wsdl	BAPI_MATERIAL_GET_ALL

CreateItemService.wsdl	BAPI_MATERIAL_SAVEDATA
CreateDetailReferencematerial.wsdl	BAPI_MATERIAL_GET_DETAIL
CreateItemRevisionService.wsdl	CCAP_REV_LEVEL_MAINTAIN
BOMServiceESB.wsdl	The interface to the SAP Process BOM API
BOMPlantExtensionService.wsdl	CSAP_MAT_BOM_ALLOC_CREATE
CreateBillOfMaterialService.wsdl	CSAP_MAT_BOM_CREATE
BillOfMaterialExistenceCheckService.wsdl	BAPI_MAT_BOM_EXISTENCE_CHECK
BOMServiceESB.wsdl	The interface to the SAP Process BOM API -
BOMPlantExtensionService.wsdl	CSAP_MAT_BOM_ALLOC_CREATE
UpdateBillOfMaterialService.wsdl	CSAP_MAT_BOM_MAINTAIN
BillOfMaterialExistenceCheckService.wsdl	BAPI_MAT_BOM_EXISTENCE_CHECK
BOMServiceESB.wsdl	The interface to the SAP Process BOM API -
BillOfMaterialExistenceCheckService.wsdl	BAPI_MAT_BOM_EXISTENCE_CHECK
ECORouterService.wsdl	The interface to the SAP Process ECO API -
CreateEngineeringChangeOrderService.wsdl	CCAP_ECN_MAINTAIN
MATMAS01_receive.wsdl	The interface to the SAP Process Item API - MATMAS01
ProcessBOMService.wsdl	The interface to the SAP Process BOM API
ProcessBillOfMaterialsListImpl.wsdl	CSAP_MAT_BOM_READ

XSDs

BAPI_MAT_BOM_EXISTENCE_CHECK_request.xsd	Contains the BillOfMaterialExistenceCheck Request ABM
BAPI_MAT_BOM_EXISTENCE_CHECK_response.xsd	Contains the BillOfMaterialExistenceCheck Response ABM
CCAP_ECN_MAINTAIN_request.xsd	Contains the CreateEngineeringChangeOrderList Request ABM
CCAP_ECN_MAINTAIN_response.xsd	Contains the CreateEngineeringChangeOrderList Response ABM
MATMAS01_event.xsd	Contains the UpdateItem ABM
BAPI_STDMATERIAL_GETINTNUMBER_request.xsd	Contains the ReserveItem Request ABM
BAPI_STDMATERIAL_GETINTNUMBER_response.xsd	Contains the ReserveItem Response ABM

onse.xsd	
BAPI_MATERIAL_GET_ALL_request.xsd	Contains the CreateReferencematerial Request ABM
BAPI_MATERIAL_GET_ALL_response.xsd	Contains the CreateReferencematerial Response ABM
BAPI_MATERIAL_GET_DETAIL_request.xsd	Contains the CreateDetailReferencematerial Request ABM
BAPI_MATERIAL_GET_DETAIL_response.xsd	Contains the CreateDetailReferencematerial Response ABM
BAPI_MATERIAL_SAVEDATA_request.xsd	Contains the CreateItem Request ABM
BAPI_MATERIAL_SAVEDATA_response.xsd	Contains the CreateItem Response ABM
CCAP_REV_LEVEL_MAINTAIN_request.xsd	Contains the CreateItemRevision Request ABM
CCAP_REV_LEVEL_MAINTAIN_response.xsd	Contains the CreateItemRevision Response ABM
BAPI_MAT_BOM_EXISTENCE_CHECK_request.xsd	Contains the BillOfMaterialExistenceCheck Request ABM
BAPI_MAT_BOM_EXISTENCE_CHECK_response.xsd	Contains the BillOfMaterialExistenceCheck Response ABM
CSAP_MAT_BOM_ALLOC_CREATE_request.xsd	Contains the BOMPlantExtension Request ABM
CSAP_MAT_BOM_ALLOC_CREATE_response.xsd	Contains the BOMPlantExtension Response ABM
CSAP_MAT_BOM_CREATE_request.xsd	Contains the CreateBillOfMaterial Request ABM
CSAP_MAT_BOM_CREATE_response.xsd	Contains the CreateBillOfMaterial Response ABM
BAPI_MAT_BOM_EXISTENCE_CHECK_request.xsd	Contains the BillOfMaterialExistenceCheck Request ABM
BAPI_MAT_BOM_EXISTENCE_CHECK_response.xsd	Contains the BillOfMaterialExistenceCheck Response ABM
CSAP_MAT_BOM_ALLOC_CREATE_request.xsd	Contains the BOMPlantExtension Request ABM
CSAP_MAT_BOM_ALLOC_CREATE_response.xsd	Contains the BOMPlantExtension Response ABM
CSAP_MAT_BOM_MAINTAIN_request.xsd	Contains the UpdateBillOfMaterial Request ABM
CSAP_MAT_BOM_MAINTAIN_response.xsd	Contains the UpdateBillOfMaterial Response ABM

CSAP_MAT_BOM_READ_request.xsd	Contains the Read BOM Request ABM
CSAP_MAT_BOM_READ_response.xsd	Contains the Read BOM Response ABM

Handling Errors

Based on the roles defined for the services, email notifications are sent if an error occurs. The roles below can be assigned at various levels in a hierarchy (service, process, domain) so that when a service errors out -- the Error Handling Framework will use the role value to derive the user(s) that need to be notified of the error. The Error Handling Framework then notifies the user(s) via their preferred notification method, puts the error in the user's Oracle Worklist, and puts the error in the error log.

Role: Actor role associated with the error notification. Actor roles receive notifications for and are assigned to error scenarios occurring in Oracle AIA integration flows. An example of an Actor role is a task editable in the Error Console and is meant to be worked on, and resolved by the actor assigned to the task.

FYI Role: FYI role associated with the error notification. This role receives for-your-information (FYI) notifications for error scenarios occurring in Oracle AIA integration flows. An example of an FYI role is a customer service representative. The task is displayed in read-only view in the Error Console.

For more information about AIA error handling, see *Oracle Fusion Middleware Infrastructure Components and Utilities User's Guide for Oracle Application Integration Architecture Foundation Pack 11g Release 1*, "Setting Up Error Handling."

Chapter 6: Customizations

This chapter discusses:

- Customizing the Transformations
- User Exits

The Integration provides two approaches of customizations:

1. **Customizing the Transformations:** This approach allows to modify the mappings between the attributes of the participating applications.
2. **User Exits:** These pre-defined extension points are provided in the OOTB BPEL flow. You can plug-in your own logic at these exit points to validate, enrich and transform data.

Customizing the Transformations

There may be a need for out-of-the-box and user defined attributes mapping between applications, which are not covered as part of standard transformations. Considering this, the transformation files (XSLs) have been externalized to facilitate the implementers to carry out the following:

- Modify the out-of-the-box transformations:

Add new mappings for the Agile attributes to EBM attributes. These Agile attributes could either be the ones that have not been mapped out-of-the-box including any of the flex-fields.

The transformations support the following requirements:

- In the integration flow, there are multiple transformations involving multiple ABO/Ms and EBO/Ms.ss

The transformations support the flex field mappings

In this mechanism of transformations, customer can provide XSLs for complex transformations that are not part of the standard transformations. It is required to support the transformations for user-defined EBO extensions (ex. Custom tags) and in places where customer want to override the standard transformation logic.

Transformation Rules

These are the transformation rules:

- For a transformation from ABM into EBM, all the flex-fields (interchangeably user defined

attribute / Flex attribute) go under Specification Group element under the main EBM element with a matching type like ValueText (for text values), ValueNumeric (for numeric values) etc carrying the values.

- For the transformations from EBM into ABM depending upon the identification element of Specification and Specification Group pull processing is done to populate the UDAs.
- For Classification elements, like Item Classification etc, the field values are translated using a configuration, into EBM and vice-versa. The configuration states are <<Name in Agile>> <<Name on EBO>> <<Name SAP ERP>>. For rest of the classification elements like part type, product family etc fields need to be packed/ unpacked on/from the XXCatalog element on the EBM.

Customization in Agile

The XSL transformations in Agile PLM Integration are externalized, i.e., these are hosted on implementation server under:

<AIA_Home>/AIAComponents/Transformations/Agile/

Refer Customization Points of each Process (in corresponding chapters).

The implementers modify the XSLs based on the customization points against each process to modify, include new mappings for the Agile attributes to the EBM elements. The entire behavior of the OOTB mappings can be enhanced using this approach.

Note: Server has to be restarted to bring the changes into effect.

Sample Customization

A few sample customizations have been provided at <AIA_HOME>\PIPS\Core\Agile\Samples. A sample customization of ECO attributes is given below:

User-Defined ECO - in Sites Tab Under Items

Mapping:

Agile	EBM	SAP
Item.Site:List0 1	corecomEBO:RevisedItem/corecomEBO:BaseUOMCode	Primary UOM Code

Template:

- createEngineeringChangeOrderLines_With_SiteData
- createEngineeringChangeOrderLines_With_OrgData
- createEngineeringChangeOrderLines_With_DefaultMasterOrgData

Customization in SAP

To customize a Mapping File:

1. Pickup the <flow>_Custom XSL file from either the Requester/Provider/EBS service where <flow> is the process name, such as ECO_CHANGE_ORDER_TYPE.
 - a. If only flex-field transformation has to be modified then the custom targets can be modified to include the new mappings.
For example, ECO_CHANGE_ORDER_TYPE_Custom in Create Eco flow for the change order flex attributes
 - b. The user need not set the custom transformations property in this case as the targets are already included in the base transformation file.
If the entire mapping has to be modified then the user can copy the base mappings into the custom target (e.g. Custom in Create ECO flow) in the custom file and modify the mappings as desired.
 - c. After modifying the file the user has to set the Custom Transformations property in the AIA Configurations file and update the configuration file from MDS respository
2. Restart the server after step 2 and 3. The server must be restarted for the new transformations to load into the JVM.

Templates in the Custom Files

1. **CreateEngineeringChangeOrderListEbmToAbm:** The following templates are used in the custom transformation files that are used to map the flex field attributes.
 - a. ECO_CHANGE_ORDER_TYPE_Custom
 - b. ECO_REVISIED_ITEM_TYPE_ITEM_Custom
 - c. REFERENCE_DESIGNATOR_TBL_Custom
 - d. COMPONENT_ITEM_TBL_Custom
 - e. SUBSTITUTE_COMPONENT_TBL_ITEM_Custom
 - f. STRUCTURE_HEADER_Custom

The **Custom** template is used for modifying the entire mapping.

3. **ItemEbmToAbm:** The template CUSTOM_OBJ_TYPE_Custom is used to map the flex field attributes. The template “Custom” is used to replace the entire mapping.
4. **UpdateItemListABMtoEBM:** The template ItemSpecificationGroup_Custom is used to map the flex field to the specification group in the EBM. The “UpdateItemListABMtoEBMCustom” template is used to replace the entire file.

Note: Since the templates are directly included inside the objects only the specific attributes being mapped should be put in the custom xsl and not the entire hierarchy.

Replacing the Entire Mapping

Use this template, **UpdateItemListABMtoEBMCustom** for complete ABM to EBM transformation.

Change the following property in AIA Configurations file:

1. File Path: \$AIA_HOME/config/AIAConfigurationProperties.xml.

This step is not required if the flex field mapping is done.

Note: The use custom transformation property is per integration flow and has to be set accordingly.

2. Reload the AIA Configurations file.
3. Restart the Server.

User Exits

The Agile to SAP integration provides user exits to allow custom transformations or filtration routines a customer may want to add in the process without affecting the main integration flow. The user exit points for each process are listed in their respective chapters.

These are the user exit points for requester and provider flows:

- Requester
- Provider

Requester Flows

User exits points for the Requester flow:

- Just prior to the execution of transformation of ABM to EBM
- Just prior to the invocation of Enterprise Business Service

- Just prior to the execution of transformation of EBM to ABM
- Just prior to the invocation of callback service or response return

Provider Flows

User exits points for the Provider flow:

- Just prior to the execution of transformation of EBM to ABM
- Just prior to the invocation of Application Service
- Just prior to the execution of transformation of ABM to EBM
- Just prior to the invocation of callback EBS or return of response message

Steps for User Exits

These are the steps for implementing user exits:

1. Identify which out-of-box flow is to be extended.
2. Identify the suitable exit point in the flow.
3. Develop the flow.
4. Configure the out-of-box flow to include the newly developed flow.
5. Test the developed flow.

Appendix A: National Language Support in Agile – SAP Integration

National Language Support (NLS) has been implemented in the Agile to SAP Integration.

Requester Flows

Before sending the EBM to Agile, the Language code is converted to the common value, which is configured from the DVM **LANGUAGE_CODE**.

Note: Have to make sure that the values are configured for the DVM's **LANGUAGE_CODE** before the flows are triggered.

In AIA Release 2.3 PIP, a change in ECO status returns the SID and the Change ID as an input to the Requester ABCS. However, from AIA Release 2.4 , 2.5 and 3.1 PIP onwards, another field called `Language_Code` has been added to input parameters in the transformations, which has a default value as en-US.

Provider Flows

In the AIA Release 3.1 PIP, the default language code in Agile is set to en-US. This code value is sent over to the provider ABCS in SAP without any conversion. However, from AIA Release 2.4 PIP onwards, this language code from Agile PLM is converted to a SAP system value using the **LANGUAGE_CODE** DVM.

Appendix B: Functionalities Available

The following functionalities are available across different versions of Agile PLM and SAP combination deployments:

Features/Agile and SAP Versions	Agile 9.2.2.6 and SAP 4.7	Agile 9.2.2.6 and SAP ECC 6.0	Agile 9.2.2.7 and SAP 4.7	Agile 9.2.2.7 and SAP ECC 6.0	Agile 9.3,9.3.x, 9.3.1.1,9.3.1.2 and SAP 4.7	Agile 9.3, 9.3.x, 9.3.1.1,9.3.1.2 and ECC 6.0
NPR (Action PX)	N	N	N	N	N	N
NPR (Auto Number PX)	Y	Y	Y	Y	Y	Y
PREL(ECO Forward Flow From Agile to SAP)	Y	Y	Y	Y	Y	Y
ECO Update Flow (From Agile to SAP)	Y	Y	Y	Y	Y	Y
Item Balance Update Flow (From SAP to Agile)	N	N	N	N	N	N
Item Operational Attribute Update Flow (Cost Attribute Updates only) (From SAP to	Y	Y	Y	Y	Y	Y

Agile)						
Queue Functionality (AQ (Database Persistent))	Y	Y	Y	Y	Y	Y
NPR (Action PX)	N	N	N	N	N	N
NPR (Auto Number PX)	Y	Y	Y	Y	Y	Y
PREL(ECO Forward Flow From Agile to SAP)	Y	Y	Y	Y	Y	Y
ECO Update Flow (From Agile to SAP)	Y	Y	Y	Y	Y	Y
Item Balance Update Flow (From SAP to Agile)	N	N	N	N	N	N
Item Operational Attribute Update Flow (Cost Attribute Updates only) (From SAP to Agile)	Y	Y	Y	Y	Y	Y

Queue Functionality (AQ (Database Persistent))	Y	Y	Y	Y	Y	Y
--	----------	----------	----------	----------	----------	----------

Appendix C: Agile to SAP Entity Maps

This appendix contains information on the following mappings:

- Bill of Materials
- Item EBO
- Item Attribute Update
- Engineering Change Order EBO

Bill of Materials Mappings

Agile Entity Attribute	Bill of Materials EBO	SAP Entity: Attribute Group: Attribute	Comments
Part/Document. Title Block. Number	\\BillOfMaterialsEBO\ItemReference\Identification\ID	MATNR:Material Number	
Changes.changeNumber	\\BillOfMaterialsEBO\Identification\ContextID	AENNR:Change Number	
BOM.ITEM_NUMBER	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\ItemReference\ID	IDNRK:BOM Component	
BOM.FIND_NUMBER	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\Identification\ContextID	POSNR:Position Number	
REFDESIG.LABEL	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\ProcessingInstruction\Identification\ID	EBORT:Installation point for sub-item	
BOM.QUANTITY	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\Quantity	Menge:Quantity	

Agile Entity Attribute	Bill of Materials EBO	SAP Entity: Attribute Group: Attribute	Comments
BOM.DESCRPTION	\\BillOfMaterialsEBO\identification\ItemReference\ Description	POTX1:BOM item text (line 1)	
	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\ StorageUnitCode	MEINS:Comp Unit Of Measure	
	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\ ItemReference\ClassificationCode	POSTP:Item Category	
	\\BillOfMaterialsEBO\BillOfMaterialsComponentItem\ItemReference\ TypeCode	STLAN:BOM Usage	
BOM. Sites. Site Name	\\BillOfMaterialsEBO\identification\ContextID	werks:Plant	

Item EBO Mappings

Agile Entity Attribute	Item EBO	BAPI_MATERIAL_SAVEDATA	Comments
Part/Document. Title Block. Number	\\ItemEBO\Name	BAPIMATHEAD: MATNR: Material number:	Associate type Field Description
Part/Document. Title Block. Description	\\ItemEBO\Description	BAPI_MAKT: MATL_DESC Material Description:	
	\\ItemEBO\TypeCode	BAPIMATHEAD: MATI_TYPE Material Type	
Mass	\\ItemEBO\BaseUOM Code	BAPI_MARA: BASE_UOM: Base Unit of Measure	

Agile Entity Attribute	Item EBO	BAPI_MATERIAL_SA VEDATA	Comments
	\\ItemEBO\PrimaryClassificationCode	BAPI_MARA: MATL_GROU:P Material group	
	\\ItemEBO\TemplateItemReference\ ClassificationCode	BAPI_MARA: MAT_GRP_SM: Material group	
	\\ItemEBO\ItemCatalog\Identification\ID	BAPI_MARA: ITEM_CAT: General Item Category Group:	
Part/Document. Title Block. Lifecycle Phase	\\ItemEBO\ItemLifecycleCharacteristics\Lifecycle Code	BAPI_MARA: MSTAE: X-Plant matl status	
Part/Document. Title Block. Description	\\ItemIdentification\BasicUOMCode\Revision\Label	BAPI_MLTX: TEXT_ID / TEXT_NAME: Basic Data text	
	\\ItemEBO\ItemPhysicalCharacteristics\ VolumeMeasure	BAPI_MARM: VOLUME:	
		VOLUMEUNIT: Volume Unit of Measure	
	\\ItemEBO\ItemPurchasingCharacteristics\ UnitListPrice\Amount	BAPI_MBEW: STD_PRICE: Standard Price	
	\\ItemPhysicalCharacteristics\heightmeasure \\ItemPhysicalCharacteristics\lengthmeasure \\ItemPhysicalCharacteristics\widthmeasure	BAPI_MARM: HEIGHT,LENGTH,WI DTH UNIT_DIM Unit of Dimension for height,length,width	
	\\ItemOrderManagementCharacteristics\custom/Delivery Plant	BAPI_MVKE: DELYG_PLNT: Delivery Plant	

Agile Entity Attribute	Item EBO	BAPI_MATERIAL_SA VEDATA	Comments
Part/Document. Sites. Site Name	\\ItemIdentification\Co ntextID	BAPI_MARC: PLANT: PLANT	
	\\ItemEBO\InventoryLo cation\SerialNumberS pecificationCode	BAPI_MARC: SERNO_PROF: Serial Number Profile	
	\\ItemEBO\relatedItem\ relationshipCode	BAPI_MARA: BASIC_MATL WRKST_NEW	
	\\ItemEBO\itemClassifi cation\classificationCo de	BAPI_MARA: DIVISION: DIVISION	
	\\itemEBO\itemManufa cturingCharacteristics\ custom\laborOffice	BAPI_MARA: DSN_OFFICE LABOR	
	\\ItemIdentification\Gti n	BAPI_MARM: EAN_UPC: International Article Number	
	\\ItemIdentification\EA NCode	BAPI_MARM: EAN_CAT: Category of International Article Number	
	\\ItemEBO\itemRevisio nHistory\identification\ id	BAPI_MARA: OLD_MAT_NO: Old material number	
	\\ItemEBO\itemPurcha singCharacteristics\ custom\purchasingGroup	BAPI_MARC: PUR_GROUP: Purchasing Group	
	\\ItemPurchasingChar acteristics/ AssetClassificationCo de/Codetype	BAPI_MARC: COMM_CODE: Harmonized code	
	\\ItemPlanningCharact eristics\inventoryPlann ing Code	BAPI_MARC: AVAILCHECK: Availability check	

Agile Entity Attribute	Item EBO	BAPI_MATERIAL_SA VEDATA	Comments
	\\ItemAttachment\attachment\note\status	BAPI_MARA: DOC_CHG_NO: Document change number	
Part/Document. Changes. Lifecycle Phase	\\ItemEBO\ItemLifecycleCharacteristics\LifecyclePhaseCode	BAPI_MARA: SAL_STATUS: Cross distribution chain status	
	\\Item Order Management Characteristics\Custom\Transportation Group	BAPI_MARA: TRANS_GRP: Transportation group	
	\\ItemEBO\InventoryLocation\Identification\ID	BAPI_MARD: STGE_LOC: Storage Location	
Part/Document. Sites. Make/Buy	\\ItemPlanningCharacteristics\MakeOrBuycode		
	\\ItemPlanningCharacteristics\MakeOrBuycode	BAPI_MARC: SPPROCTYPE: Special procurement type	
	\\ItemPlanningCharacteristics\ProcessingLeadTimeCharacteristics\ fixedDuration	BAPI_MARC: GR_PR_TIME: Goods receipt processing time in days	
	\\ItemPlanningCharacteristics\ProcessingLeadTimeCharacteristics\ postProcessingDuration	BAPI_MARC: PLND_DELRV: Planned Delivery Time	
	\\ItemEBO\Custom/Product Hierarchy	BAPI_MARA: PROD_HIER: Product Hierarchy	
	\\ItemPhysicalCharacteristics\custom/Netweight	BAPI_MARA: NET_WEIGHT: Net weight	

Agile Entity Attribute	Item EBO	BAPI_MATERIAL_SA VEDATA	Comments
		UNIT:OF_WT Unit Of weight: Weight	
	\\ItemEBO\ItemPhysicalCharacteristics\WeightMeasure	BAPI_MARAM: GROSS_WT: Gross Weight	
		UNIT_OF_WT UNIT OF WEIGHT: Unit of weight	
	\\ItemPlanningCharacteristics\Custom\MRPC Controller	BAPI_MARC: MRP_CTRLER: MRP Controller	
	\\ItemOrderManagementCharacteristics\Custom>LoadingGroup	BAPI_MARC: LOADINGGRP: Loading Group	
	\\ItemOrderManagementCharacteristics\custom\Sales Organization	BAPI_MVKE: SALES_ORG: Sales Organization	
	\\ItemEBO\Custom/Product Allocation	BAPI_MARA: PROD_ALLOC: Product Allocation Determination Procedure	
	\\ItemEBO\Custom\Authorization Group	BAPI_MARA: AUTHORITYGROUP Authorization Group	
	\\ItemManufacturingCharacteristics\Custom\CountryOfOrigin	BAPI_MARC: COUNTRYORI: Country of Origin	

Item Attribute Update Mappings

Agile Entity Attribute	Item EBO	MATMAS01	Comments
Part/Document. Title Block. Number	\\ItemEBO\Name	E1MARAM: MATNR Material number:	
Part/Document. Title Block. Unit Cost Attribute	\\ItemEBO\ItemPurchasingCharacteristics\UnitListPrice\Amount	E1MBEWM: STPRS Standard Price E1MBEWM: VERPR Moving Average Price	
Part/Document. Sites. Site Name	\\ItemIdentification\ContextID	E1MARCM: WERKS Plant	

Engineering Change Order EBO Mappings

Agile Entity Attribute	Engineering Change Order EBO	CCAP_ECN_MAINTA IN SAP Entity: Attribute:Description	Comments
CHANGE.CHANGE_NUMBER	\\Identification\ ID	AENR_API01:CHANGE_NO:Change Number	Change Notice
CHANGE.DESCRPTION	\\Identification\ Description	AENR_API01:DESCRIPT: Change number description	
CHANGE.RELEASE_DATE	InitiationDate	AENR_API01:VALID_FROM:Valid from date	
ECO/MCO/SCO. Affected Item. Effectivity Date	EngineeringChangeOrderLine/Effective Date	AEDT_API01:ALT_DATE:Alternative date external key	
CHANGE.REASON	\\Identification\Revision\Reason	AENR_API01:REASON_CHG:Reason for change	
	\\Identification\Status	AENR_API01:STATUSS:Status of change number	

Agile Entity Attribute	Engineering Change	CCAP_ECN_MAINTA	Comments
Changes .Affected Items. New Revision	\\EngineeringChangeOrderLine\EffectivityControlItem Reference\Revision\Number	REVLV:Revision level	
Agile Entity Attribute	Engineering Change Order EBO	CCAP_REL_LEVEL_MAINTAIN	
CHANGE.CHANGE_NUMBER	\\Identification\ ID	AENNR Change Number	
ECO/MCO/SCO. Affected Item. Item Number	\\EngineeringChangeOrderLine\RevisedItem	MATNR Material Number	
Change Orders Class.Affected Items. New Revision	\\EngineeringChangeOrderLine\EffectivityControlItemReference\Revision\Number	REVLV Revision level	

Appendix D: Queue Management

This appendix contains information on the following:

- Queue Schema
- Queue Controller
- Queue Monitor
- Queue User Interface (UI) Application

The Queue Management feature in this pre-built integration caters to the following requirements:

- Event to produce filtered payload to a file destination or JMS destination.
- Payload is defined using a standard XSD.
- Files or JMS Messages produced by events are sequenced in the order in which the objects are released.

Note: These requirements are leveraged using the Agile Content Service (ACS). ACS has the ability to produce payload to a File or JMS destination. The payload is based on filters configured for the ACS Event defined by Agile provided AXML schema definition. Also the ACS transmits the messages in the order in which the ATOs are released.

- Queue to manage messages.
- Queue Monitoring UI to enable reordering and resubmitting unprocessed messages.

The Queue manages the payloads based on the Business Process for which the message is produced by the Event.


- Queue controlling mechanism.
 - Triggers the Business Flow based on the business process of message.
 - Processes the messages sequentially depending upon the order specified in the message (the highest order message is picked first for processing).
 - A message is not picked for processing unless the processing of the previous message is complete.
 - The order of the messages, which have not been picked for processing, can be re-ordered.

For more information on Queue Manager, see *Agile PLM Integration Pack for SAP Release 3.1 - User Guide* at <http://www.oracle.com/technology/documentation/>

Queue Management Solution

The Queue Management Solution comprises of the following components:

- **Queue DB:** The database persist the data related to a Queue messages.
- **Queue Controller:** Polls for new Event payloads and add them to the Queue DB. The highest priority message for each Business Process is picked and processed sequentially to trigger its Business Flow.
- **Queue Monitoring:** UI which monitors the Queue message status supports Re ordering of priorities of the Queue Messages. Also provides the facility to re submit the un processed messages.



Queue Monitoring

Queue Schema

To support the queue monitoring solution flow, a polling strategy similar to “PollingControlTableStrategy” is used. Two tables are used to manage the sequential processing and reordering of messages.

The first table QUEUE_TABLE will have all the queue messages that are being provided by the Event trigger. The QUEUE_CONTROL_TABLE table will store the relevant information of the message from the QUEUE_TABLE which has not been processed yet.

The Queue Manager needs to ensure that there is only one message in the control table which is not yet processed. When the processing of a message is complete, a Pending message from the Queue table is inserted into this table. This would facilitate the sequential processing of messages. Also since all the pending messages are stored in the Queue table, they could be reordered.

Queue DB Details

The Queue Schema has the following tables:

ECO_QUEUE	This table holds the data of Process ECO. The PROCESS_TYPE column is used as identifier for Process ECO.
ECO_QUEUE_CONTROL	This table stores the details about the rows that are currently under processing state.
ECO_QUEUE_TABLE_CRITERIA	This table contains the data needed for a criteria. One set of criteria forms a filter.
ECO_QUEUE_TABLE_FILTER	This table contains the data needed to form a filter, i.e., the criterion to be used to form a specific filter.
ECO_QUEUE_STATUS	This table holds the data to control the simultaneous processing and suspending the Queue. By changing the values in the ECO_QUEUE_STATUS column, the number of simultaneously processed ECOs can be changed.

The structure of ECO_QUEUE_STATUS table is:

ECO_QUEUE_STATUS_ID	ECO_QUEUE_STATUS	Description
1	1 or 0	The status of the Queue - in suspended or resume mode.
2	1	The count of rows that can be processed simultaneously for Process ECO. A value of 1 means sequential processing.
3	5	The count of rows that can be processed simultaneously for Validate ECO.

Queue Controller

A polling strategy on the Queue DB is used for addressing the Queue Management business requirements. The Queue Controller provides an ECO system to ensure that this polling strategy works in tandem to ensure the following:

All Event transmitted File/JMS Messages are added to the Queue.

At any given point of time there is only one pending message in the control table

Once the processing of a message in control table is complete, insert the highest priority queue message from the queue table to the control table.

In case the Integration flow errors out, the queue manager will wait until the message is resubmitted or removed.

Queue Monitor

When a Change Order is released by Agile Content Service (ACS), it is picked up by the Queue Controller. The Queue Monitor displays a list of all the Change Orders awaiting processing and facilitates you to reorder their sequence of processing.

For the first time after deployment, the Queue is in Suspended state. You are required to resume it. For complete details on Queue Monitor, refer Agile to SAP Integration User Guide.

The screenshot displays the Oracle Application Integration Architecture Queue Monitor. The interface includes a search bar with options for 'Advanced', 'Saved Search', and 'All Change Orders'. Below the search bar, there are filters for 'Match' (All/Any), 'Process Type' (ProcessECO), and 'Delete Flag' (No). A toolbar contains buttons for 'Resubmit', 'Remove', 'Suspend', 'Resume', 'Refresh', and 'Change Priorities'. The main area is a table with the following data:

Reference	Change Number	Release Time	Processed Time	Process Status
AT000678	CTEST10	Jun 16, 2011 10:26:40 AM	Jun 16, 2011 4:57:07 AM	COMPLETED
AT000676	CTEST00	Jun 15, 2011 6:37:57 PM	Jun 15, 2011 1:08:19 PM	COMPLETED
AT000675	CTEST807	Jun 15, 2011 5:32:32 PM	Jun 15, 2011 12:02:47 PM	COMPLETED
AT000670	CTEST802	Jun 15, 2011 4:29:32 PM	Jun 15, 2011 10:59:51 AM	COMPLETED
AT000668	CTEST800	Jun 15, 2011 4:05:00 PM	Jun 15, 2011 10:35:27 AM	COMPLETED
AT000665	SA-0000797	Jun 15, 2011 11:00:13 AM	Jun 15, 2011 5:30:36 AM	COMPLETED
AT000664	CTEST796	Jun 15, 2011 10:38:10 AM	Jun 15, 2011 5:08:54 AM	COMPLETED
AT000663	CTEST795	Jun 14, 2011 6:45:30 PM	Jun 14, 2011 1:15:44 PM	COMPLETED
AT000662	CTEST794	Jun 14, 2011 6:36:19 PM	Jun 14, 2011 1:06:34 PM	COMPLETED

Copyright © 2009 - Oracle. All rights reserved.

Queue Manager Services

The following services are deployed as part of the Queue Manager:

CreateQueueService

1. CreateQueueControlService

2. QueueProcessorService
3. QueueProcessorServiceImpl

CreateQueueService

The CreateQueueService is implemented as an Mediator Routing Service. An Adapter Service (File/JMS Adapter) polls on the destinations for any Event payloads. The payload is in the form of aXML files. This service receives message as a binary element (aXML File). For each payload received the service inserts a new row into the QUEUE table. An Adapter Service (DB Adapter) is used for the same. The Toplink solution generates the required schema from the table for this DB Adapter.

The service uses transformation services to populate any NOT NULL columns in the table.

OBJECT_REFERENCE is inserted with the file name of the AXML file using the Mediator header transformation extension functions.

- PROCESS_STATUS is Pending for the newly inserted row.
- PROCESS_PRIORITY is captured from the file name. (ACS can be configured to append an default order for the file name)

CreateQueueControlService

The CreateQueueControlService is implemented as an Mediator Routing Service. A DB Adapter polls on the QUEUE_CONTROL_TABLE table. If there are no rows which are in Pending status, the CreateQueueControlService invokes a DB Adapter service which executes a custom SQL. This SQL identifies the highest priority pending Queue message from QUEUE_TABLE table and inserts the same in QUEUE_CONTROL_TABLE table.


This polling strategy ensures that at any point of time there is only one Pending message in the QUEUE_CONTROL_TABLE table. Once the Pending message is processed and status completed, a new Pending message is inserted from QUEUE_TABLE table to the QUEUE_CONTROL_TABLE table. When the status for a message is completed in the QUEUE_CONTROL_TABLE that row would be deleted from the table.

QueueProcessorService

The QueueProcessorService is implemented as an Mediator service which acts like an Interface and provides a façade in front of the QueueProcessorServiceImpl service. A DB Adapter polls on the QUEUE_CONTROL table for any Pending messages. A Pending message in the table is routed to the QueueProcessorServiceImpl service which processes the message. Based on the result from the implementation service the status of the message is updated in the control table.

QueueProcessorServiceImpl

The following figure illustrates how QueueProcessorServiceImpl invokes the RequestorABCS:



The primary task of this service is to invoke the RequestorABCS. The Response from RequestorABCS is processed and the Queue is updated with processing status.

Input: The QueueMessage generated by Toplink solution in the QueueProcessorService is used as the input for this Service.

Output: QueueStatusMessage which contains the status and result of processed Queue message.

The following table lists the steps required to invoke the RequestorABCS:

#	Name	Step Description
1.	QueueProcessorService Invokes QueueProcessorServiceImpl process	The QueueProcessorService invokes QueueProcessorServiceImpl with QueueMessage (generated by Toplink solution for QUEUE table) as input.
2	Invoke UpdateQueueStatus DB Adapter service	The input QueueMessage in this process is assigned with following values to update the Queue message in the Queue DB PROCESS_STATUS = Processing PROCESS_ID = BPEL Process Id PROCESS_LOCK = 1
3.	Transform Agile Data(AXML) to ABM	The QueueMessage will have the Agile Data payload which is transformed to ABM

#	Name	Step Description
4.	Invoke RequestorABCS	QueueProcessorServiceImpl invokes the RequestorABCS with ABM as input.
5.	Invoke Coarse Grained Web Service	RequestorABCS optionally invokes the coarse grained web services to get the ABM populated with any missing information required for the Integration flow.
6.	RequestorABCS Transforms ABM to EBM	The response ABM from coarse grained WS is transformed to EBM and an operation on EBS is invoked with EBM as the input.
7.	RequestorABCS orchestrates the business flow	The RequestorABCS routes the EBM to the EBS.
8.	EBS routes the response to RequestorABCS	The response EBM from EBS is routed to the RequestorABCS which is transformed to ABM and returned to the QueueProcessorServiceImpl
9.	QueueProcessorServiceImpl invokes UpdateQueueResult DB Adapter service	The result from the RequestorABCS is used to update the status of Queue in the Queue DB. Also the Process lock is released.

Transformations

The AXML payload is transformed to the ABM which is input for the **RequestorABCS**. Since the ABM schema is defined on the lines of AXML schema this transformation will be simpler to do in the Jdeveloper XSL mapper.

Implementation Details

The **QueueProcessorServiceImpl** is implemented as an *Asynchronous BPEL Composite*. There are calls to the **RequestorABCS**, DB Adapters for updating Queue status and invoking the **RequestorABCS**. These involve some logic (parsing the AXML payload) which cannot be achieved using the Mediator.

Note: Queuelid is used for correlation set between the **QueueProcessorServiceImpl** and the **RequestorABCS**.

Error Management

All errors in the Integration flow are handled in the RequestorABCS and EBF. Any such errors leading to failure of the Queue processing will be handled in this process. As a result of such error the Queue Status and Result with failure status is updated in the Queue DB.

Queue User Interface Application

The Queue User Interface (UI) application provides the following features:

- Easy access Enterprise Manager (EM) console link to SOA composite instances for Change Orders
- User role-based access
- Add new users into user roles

Easy Access EM Console Link to SOA Composite Instances for Change Orders

This feature enables you to easily access the flow trace of the SOA composite instances in EM console for a given change order. The new column **Instance ID** added in the Queue UI application shows the instance id value of the first SOA composite in the flow with a hyperlink to view the full flow trace.

The hyperlinked **Instance ID** takes you to login screen of the EM console. After successful authentication, you can access the flow trace of execution for a given change order.

The following screenshots shows how to access the EM console for successful and errored instances of SOA composites through hyperlinked **Instance ID** field in the Queue UI application.

ORACLE Application Integration Architecture

Logged In As weblogic Logout

Change Order Queue

Search Advanced Saved Search All Change Orders

Match All Any

Process Type ProcessECO

Delete Flag No

Search Reset

Resubmit Remove Suspend Resume Refresh Change Priorities

Reference	Change Number	Release Time	Processed Time	Process Status	Instance ID
✓ ATO00055	C00035	Apr 19, 2012 8:42:58 PM	Apr 19, 2012 8:43:19 PM	COMPLETED	210045

Copyright © 2009 - Oracle. All rights reserved.

Figure 1

ORACLE
Enterprise Manager 11g
Fusion Middleware Control

11g

Login to Oracle Fusion Middleware Control
Form: fam_soa_domain
* User Name:
* Password:

Enhanced User Experience

- Menu Based Navigation
Finding a feature in Enterprise Manager is now easy with menus. Well-designed menu navigation makes the product easy to learn and remember.
- Interactive Correlation Charts
- Dynamic Context Menu
- Context Sensitive Help

New Features

- SOA Management
You can manage, monitor and diagnose the SOA infrastructure, as well as the composite applications you deploy. You can configure service engines such as BPEL, Mediator, Human Work Flow and can deploy and manage SCA composite applications.
- Identity Management
- WebCenter Management
- Complete Security and Audit Management
- Configure Logging and Search Log Files

Did you know...

Manage and Secure Web Services and SOA Applications
You can manage and secure Web services and SOA applications. You can define service policies. You can enforce service policies of service endpoints. You can monitor Web service endpoints and monitor their performance and faults.

Copyright © 1998, 2010, Oracle. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates.
Other names may be trademarks of their respective owners.

Figure 2




Figure 3

User Role-Based Access in Queue UI Application

From AIA release 11.2 onwards, the Queue UI application ships with role-based controlled access to the application. Following are the two roles:

Role	Description
<p>For Change UI administrators:</p> <p>Role Name: ChangeOrderUIAdminRole</p>	<p>Have full access to the Queue UI application.</p> <p>Have exclusive access to,</p> <ol style="list-style-type: none"> Suspend or resume of the queue. Resubmit an errored message. Reorder the priorities of messages. Remove a message from the queue. Access the EM console for successful and errored

	instances of SOA composites through hyperlinked Instance ID field in the Queue UI application.
For business users: Role Name: ChangeOrderUIBusinessRole	Have view only access to the Queue UI application. The user does not have the exclusive privileges mentioned for the administrators.

Note: As part of the Queue UI installation, the Queue UI application ships with the following two default users:

1. **ChangeOrderUIAdmin: This role belong to ChangeOrderUIAdminRole**
2. **ChangeOrderUIBusiness: This role belongs to ChangeOrderUIBusinessRole**

The default password for these users is same as that of the application server password provided at the time of the PIP installation. The Weblogic administrator is by default granted ChangeOrderUIAdmin role.

The following are the screenshots for different user role scenarios:

1. Figure 1: Administrator role view of the Queue UI application.




Figure 4

2. Business user role view of the Queue UI application.




Figure 5

3. The view of the Queue UI application when a user is not assigned any of the Change Order UI roles.




Figure 6

Add New Users into User Roles in Queue UI Application

To add new users to user roles in the Queue UI application, perform the following steps:

1. Log on to the Weblogic Server by using the appropriate port, <http://<hostname>:<portnumber>/console>.
2. Click **Security Realms** on the left pane of the Weblogic Administration Console.
3. Click **myrealm** (or the realm with true in the Default Realm column) in the Realms table.
4. Click **Users and Groups** tab.
5. Add a new user and provide all the details.
6. Click the newly added user and go to the **Groups** tab.
7. Select ChangeOrderUIAdminRole or ChangeOrderUIBusinessRole from the list of available groups and move them to the list of chosen groups for the user. Click **Save** to save the changes.

Appendix E: Troubleshooting

This appendix covers common troubleshooting issues:

- Engineering Changer Order
- Installation
- Queue
- SAP
- Agile

Engineering Change Order Issues

These are the common ECO issue and solutions:

1. **Issue:** In ECO forward flow, after the ECO is processed successfully but the transfer status attribute (flex) in the ECO in Agile is not getting updated.
Solution: Check which flexfield attribute has been enabled corresponding to the change. Then, ensure that the same attribute has been configured in the AIAConfigurationProperties.xml for that property.
2. **Issue:** For the Item Cost update update flows, the attributes in Agile are not getting updated.
Solution: First check whether Multisite Enabled property is set to True or False. Based on this given value, it should be ensured that the Cost attributes in AIAConfigurationProperties.xml are correctly set.

See, [Chapter 4 in Agile PLM-SAP Design to Release - Implementation Guide](#).

Installation Issues

These are the common installation issue and solutions:

1. **Issue:** While installing the AIA FP in the Linux box, deployment of configurations/deploying the PIP did not succeeded due to SOA server was being unable to restart itself automatically using the deployment script given in the AIA FP.
Solution: To resolve this installation issue:
 1. Stop SOA server.
 2. Restart the SOA server from this location:
`$Middleware_Home\user_projects\domains\soa_domain\bin>.\startManagedWeblogic.sh soa_server1`

- Click on the retry button on the configuration wizard.

Queue Issues

These are the common queue issue and solutions:

- Issue:** Once an ECO/MCO/SCO has been released in Agile, the Queue does not display any corresponding entry for the change order.

Solution: To resolve this queue issue:

- Check Agile for ATO which was created on the release of the particular change order. Check the status on the Where Sent tab of the ATO.
- If it shows a *Failure* message, this implies that an error occurred while ACS was processing the publishing of the data to JMS destination. The error message is specified in the Transmission Notes column.

Destination	Filters	Data Format	Language	Site	Date Sent	Transmission St...	Transmission Notes	Response	Roles
JMS Destination - AIA04	Default Change Order Filter, Default Item Filter	sXML	English	All		Failure	jms.QueueConnectionFactory not found		Exec (Rest), Rest (Rest), Mana, Read

- After you make any necessary changes to the transfer order or the destination to correct the problem, reset the destination to attempt delivery again. Once a destination has failed, no other transfer orders can be sent to that destination until it has been reset.
- To reset the destination, in Agile Java client, go to **Admin > System Settings > Agile Content Service > Destinations**.
- Select the particular destination and click the Reset icon. The Reset icon is next to the **Delete** icon.

Name	Description	URL or Target Path	Status
Example Destination	Application Server Directory	.	
JMS Destination - AIA04		opmn:ormi://adtc60070fems.us.oracle.com:6083:oc...	Success


After resetting the Destination, test the Destination to ensure the Test is Successful for the Destination. In case it fails, this has to be resolved, mainly by ensuring all the ECO Queue settings are correct and SOA Port specified in the URL is correct.

If the status of the ATO transfer is **Success**, it implies that the ACS is publishing the data to JMS queue was successful. Then we need to troubleshoot in the BPEL console.

- a. Navigate to the Weblogic EM Console: `http://<host name>:<port number>/em`
- b. Click the **Instances** tab. Check for the instance of the *UpdateBillOfMaterialsListSAPProvABCImpl* for which the error occurred.

Instance	Typ	State	Time	Composite Instance
Retrive_BOMData	W	Completed	Jun 22, 2011 6:36:27 AM	ProcessBillOfMate
BOMServiceESB_ep	W	Completed	Jun 22, 2011 6:36:27 AM	BOMServiceESB o
BOMServiceESB	M	Completed	Jun 22, 2011 6:36:28 AM	BOMServiceESB o
ProcessBillOfMaterialsListImpl	W	Completed	Jun 22, 2011 6:36:27 AM	BOMServiceESB o
ProcessBillOfMaterialsListSAPProvABC	W	Completed		ProcessBillOfMate
BillOfMaterialsEBS	W	Completed	Jun 22, 2011 6:36:29 AM	ProcessBillOfMate
BillOfMaterialsEBS_ep	W	Completed	Jun 22, 2011 6:36:29 AM	BillOfMaterialsEBS
BillOfMaterialsEBS	M	Recovery Needs	Jun 22, 2011 6:36:34 AM	BillOfMaterialsEBS
UpdateBillOfMaterialsListSAPProvABC	W	Completed	Jun 22, 2011 6:36:33 AM	BillOfMaterialsEBS
UpdateBillOfMaterialsListSAPProvAI	W	Failed	Jun 22, 2011 6:36:33 AM	UpdateBillOfMateri
UpdateBillOfMaterialsListSAPProvAI	W	Failed	Jun 22, 2011 6:36:34 AM	UpdateBillOfMateri
BillOfMaterialsRouterService	W	Completed	Jun 22, 2011 6:36:33 AM	UpdateBillOfMateri
BOMServiceESB_ep	W	Failed	Jun 22, 2011 6:36:33 AM	BOMServiceESB o
BOMServiceESB	M	Failed	Jun 22, 2011 6:36:34 AM	BOMServiceESB o
UpdateBillOfMaterialServ	W	Failed	Jun 22, 2011 6:36:33 AM	BOMServiceESB o
BillOfMaterialsErrorResponseEBS	W	Completed	Jun 22, 2011 6:36:34 AM	UpdateBillOfMateri
BillOfMaterialsResponseEBS	W	Completed	Jun 22, 2011 6:36:34 AM	BillOfMaterialsRes
BillOfMaterialsResponseEBS	M	Completed	Jun 22, 2011 6:36:34 AM	BillOfMaterialsRes
ProcessBillOfMaterialsList	W	Completed	Jun 22, 2011 6:36:34 AM	BillOfMaterialsRes
ProcessBillOfMaterials	W	Completed	Jun 22, 2011 6:36:34 AM	ProcessBillOfMate

- c. Click on the Instance Name and go to the *Flow* link. In the BPEL flow shown, find the element at which the error has occurred and then click on the element to view the Activity Audit trail for more details.



SAP Issues

When implementing the Agile to SAP pre-built integration, you might encounter the following issues.

Issue: When updating SAP Item attributes to Agile, if Agile application is down or an error occurs in processing the data, then the data cannot be resubmitted to Agile.

Solution: If there is any error in the SAP item attributes update to Agile, an email is sent to the customer/administrator specifying the failure.

To resolve the issue, identify the failed IDOC and resubmit from SAP:

- a. Open the error mail that was sent to the customer/user/admin.
- b. Click on the hyperlink provided on the error mail.
- c. Open the BPELConsole and navigate to the instance that was given in the link.
- d. Scroll down to the Assign Fault and check the IDOC number that has failed.
- e. Navigate to SAP application and re-submit the IDOC with the item attribute details provided in the email.

Note: Please check whether the Agile application server is up and running before initiating the process.

Issue: If there is an error in **CreateBillOfMaterialsListSAPProvABCSImpl** with the error description as *"javax.xml.rpc.soap.SOAPFaultException: com.sap.mw.jco.JCO\$AbapException: (126) ERROR: Terminate processing"*.

Solution: Perform these steps:

- a. Check whether the components in the Bill Of Materials created in SAP. If the components are not created, add the components to the affected item and then release the ECO.
- b. Check whether the components have a valid Item Category, BOM Usage and Effectivity date.

Issue: If there is an error in **UpdateBillOfMaterialsListSAPProvABCSImpl** with the error description as *"javax.xml.rpc.soap.SOAPFaultException: com.sap.mw.jco.JCO\$AbapException: (126) ERROR: Terminate processing"*

Solution: Perform these steps:

- a. Check whether the components in the Bill Of Materials created in SAP or not. If the components are not created, add the components to the affected item and then release the ECO.
- b. Check whether the components have a valid Item Category, BOM Usage and Effectivity date.
- e. Check whether the components defined while creating the Bill Of Material have unique Find Number on Agile side.

Issue: If there is an error in **SyncltemListSAPProvABCS** with the error description as *"Exception during SOAP invoke: com.sap.mw.jco.JCO\$AbapException: (126) REVISION_LEVEL_EXISTS: REVISION_LEVEL_EXISTS"* even though the process is showing as success.

Solution: This error can be ignored as it is only a check for revision existence for the particular item/material.

Issue: If there is an error in **SyncltemListSAPProvABCS** or **ReserveltemSAPProvABCS** with the error description as *"Exception during SOAP invoke: java.lang.Exception: BapiError: Enter a material type; nested exception is: javax.xml.rpc.soap.SOAPFaultException: java.lang.Exception: BapiError: Enter a material type"*

Solution: Check whether the ITEM_PRIMARYCLASSIFICATIONCODE DVM is mapped correctly. If not modify the same and re-submit from the queue management console.

Check whether the REFERENCEMATERIALS is mapped with the corresponding material on the SAP system.

Issue: If there is an error in **SyncltemListSAPProvABCS** with the error description as *"Exception during SOAP invoke: com.ibi.sap.SapAdapterException: Field: REV_LEVEL_NEW exceeds defined in structure INPUT allowed length 2: ABC; nested exception is: javax.xml.rpc.soap.SOAPFaultException: com.ibi.sap.SapAdapterException: Field: REV_LEVEL_NEW exceeds defined in structure INPUT allowed length 2: ABC"*

Solution: Check whether the revision level defined for the affected item is 2 characters.

Issue: MediatorMessageProcessingFailed due to Timed out exception

Solution: Remove the ECO from the queue with processing state and re-release the ECO from Agile.

Agile Issues

Issue: Issue in fetching the Part number from SAP using NPR.

Solution: Encrypt the SOA_LOGIN_PASSWORD by using the following command in Agile:

<AgileHome>/agileDomain/bin/encryptpwd.sh and place the encrypted password in the config.properties in NPRpx.jar of Agile.