

Oracle® Server CLI Tools User's Guide

ORACLE®

Part No: E52099-11
August 2016

Part No: E52099-11

Copyright © 2014, 2016, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS. Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Référence: E52099-11

Copyright © 2014, 2016, Oracle et/ou ses affiliés. Tous droits réservés.

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf stipulation expresse de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, accorder de licence, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Si ce logiciel, ou la documentation qui l'accompagne, est livré sous licence au Gouvernement des Etats-Unis, ou à quiconque qui aurait souscrit la licence de ce logiciel pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique:

U.S. GOVERNMENT END USERS. Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer des dommages corporels. Si vous utilisez ce logiciel ou matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour ce type d'applications.

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

Intel et Intel Xeon sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. AMD, Opteron, le logo AMD et le logo AMD Opteron sont des marques ou des marques déposées d'Advanced Micro Devices. UNIX est une marque déposée d'The Open Group.

Ce logiciel ou matériel et la documentation qui l'accompagne peuvent fournir des informations ou des liens donnant accès à des contenus, des produits et des services émanant de tiers. Oracle Corporation et ses affiliés déclinent toute responsabilité ou garantie expresse quant aux contenus, produits ou services émanant de tiers, sauf mention contraire stipulée dans un contrat entre vous et Oracle. En aucun cas, Oracle Corporation et ses affiliés ne sauraient être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'accès à des contenus, produits ou services tiers, ou à leur utilisation, sauf mention contraire stipulée dans un contrat entre vous et Oracle.

Accessibilité de la documentation

Pour plus d'informations sur l'engagement d'Oracle pour l'accessibilité à la documentation, visitez le site Web Oracle Accessibility Program, à l'adresse <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Accès aux services de support Oracle

Les clients Oracle qui ont souscrit un contrat de support ont accès au support électronique via My Oracle Support. Pour plus d'informations, visitez le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> ou le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> si vous êtes malentendant.

Contents

Using This Documentation	11
Oracle Server CLI Tools Overview	15
Host-to-ILOM Interconnect	17
CLI Tools Command Syntax and Conventions	19
CLI Tools Command Syntax	19
CLI Tools Device-Naming Convention	20
Using biosconfig to Update the BIOS	23
biosconfig Command Overview	23
biosconfig Requirements	24
biosconfig Device Terminology	24
Editing XML Files	25
biosconfig Command Syntax	26
biosconfig for Oracle Solaris OS	27
biosconfig for Windows	27
▼ Install the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit	28
▼ Uninstall the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit	35
Viewing biosconfig Command Options and Version Information	38
▼ View biosconfig Command Options	38
▼ View biosconfig Version Information	39
Configuring the Device Boot Order	40
Methods for Changing the Boot List	40

▼ Set the First Boot Device for the Next Boot	41
▼ Make a Persistent Change to Boot Order	42
▼ Change Boot Order Based on the PCI Bus, Device, or Function	43
Configuring the BIOS CMOS	44
▼ Capture the BIOS CMOS Golden Image	45
▼ Apply the BIOS CMOS Golden Image	46
Configuring Individual CMOS Settings	47
Commands That Produce Unrelated, Innocuous, Extra Output	50
Using <code>firmware-check</code> to Confirm Minimum Required Firmware	53
<code>firmware-check</code> Command Overview	53
<code>firmware-check</code> Features	54
<code>firmware-check</code> Command Prerequisites	54
<code>firmware-check</code> Command Syntax	54
Checking System Firmware Information	55
▼ Manually Check System Firmware	55
▼ List Current System Firmware	56
▼ Perform a Silent Check and Log the Results	56
Using <code>fwupdate</code> to Update Firmware	57
<code>fwupdate</code> Command Overview	57
<code>fwupdate</code> Features	58
<code>fwupdate</code> Command Prerequisites	58
Downloading Firmware Patches	59
<code>fwupdate</code> and Service Processor Access	59
<code>fwupdate</code> Command Syntax	60
Listing Component Firmware Information	61
<code>list</code> Subcommand Overview	61
▼ List All Component Firmware Information	64
▼ List Specific Component Firmware Information	68
Checking System Firmware	70
<code>check</code> Subcommand Overview	70
▼ Check System Firmware Information	71
Updating Component Firmware	71
<code>update</code> Subcommand Overview	72
Updating Component Firmware With a Metadata File (Automatic Mode)	72

Updating Component Firmware Without a Metadata File (Manual Mode)	80
▼ Reset a Device After a Firmware Update	86
Execution Summary	88
Using hwmgmtcli to Display Hardware Information	89
hwmgmtcli Command Syntax	89
▼ List Subsystem Information	91
▼ View Open Problems	91
▼ Export Subsystem Information	92
Using ilomconfig to Configure Oracle ILOM	93
ilomconfig Command Overview	94
ilomconfig Features	94
Restoring and Modifying Oracle ILOM XML Configuration Files	94
ilomconfig Command Syntax	95
Importing and Exporting XML Configurations	97
▼ Export an XML Configuration	98
▼ Import an XML Configuration	99
Listing System and SP Information	101
▼ List System Summary Information	101
▼ List Users	102
▼ List an SNMP Community	102
▼ List IPv4 Network Settings	102
▼ List IPv6 Network Settings	103
▼ List Service Processor Identification Information	103
▼ List DNS Information	103
▼ List Clock Information	104
Modifying Oracle ILOM Configurations	104
▼ Restore Oracle ILOM to Defaults	104
▼ Create a User	105
▼ Delete a User	105
▼ Modify a User Password or Role	105
▼ Create an SNMP Community	106
▼ Modify IPv4 Network Settings	106
▼ Modify IPv6 Network Settings	107
▼ Modify Identification Information	108

▼ Modify DNS Information	108
▼ Modify Clock Information	109
Configuring the Host-to-ILOM Interconnect	109
Providing Host Credentials to the Service Processor	110
▼ Enable the Host-to-ILOM Interconnect	110
▼ Disable the Host-to-ILOM Interconnect	111
▼ Modify the Host-to-ILOM Interconnect	111
▼ List the Host-to-ILOM Interconnect Settings	112
▼ Verify the Host-to-ILOM Interconnect Settings	112
▼ Set Up a Credential Cache on the Host	112
▼ Delete a Credential Cache on the Host	113
Managing ILOM and Host Watchdog	113
HMP Watchdog Overview	113
ILOM Watchdog ilomconfig Commands	117
Host Watchdog ilomconfig Commands	119
Troubleshooting ILOM Watchdog and Host Watchdog States	121
Using ipmitool for Windows	125
ipmitool Overview	125
Sun IPMI System Management Driver 2.1	126
Configuring Boot Order Using ipmitool	126
Using nvmeadm to Configure an NVM Express Device	129
nvmeadm Command Overview	129
▼ List NVMe Controllers	131
▼ List NVMe Namespaces	132
▼ List the Supported LBA Format	133
▼ List NVMe Controller Log Pages	134
▼ List NVMe Features of the Controller	135
▼ Format All Namespaces on the Controller	135
▼ Erase All Namespaces	136
▼ Export an SSD Disk Configuration	136
▼ Import an SSD Disk Configuration	137
Using raidconfig to Configure RAID	139
raidconfig Command Overview	139

raidconfig Features	140
raidconfig Requirements	140
raidconfig Command Syntax	141
Listing Controller, RAID and Disk Information	142
list Subcommand Overview	142
▼ Display a Brief Listing of All Devices	145
▼ Display a Brief Listing of a Device	146
▼ Display a Detailed Listing of a Device	147
Creating and Deleting RAID Volumes	148
▼ Create a RAID Volume	149
▼ Delete a RAID Volume	150
Adding and Removing Disks and RAID Volumes	150
▼ Add a Disk to a RAID Configuration	151
▼ Remove a Disk from a RAID Volume	151
▼ Add Spare Disks	152
▼ Remove a Spare Disk or a RAID Volume	153
Modifying a RAID Volume or Controller	153
▼ Modify a RAID Volume	154
▼ Modify a Controller	155
▼ Modify the BIOS Boot Target	155
▼ Disable Auto Rebuild	156
▼ Modify a RAID Volume Name	156
▼ Enable or Disable JBOD Mode	156
Starting or Stopping a Task on a Disk or RAID	158
Executing Tasks on a Disk or RAID Volume	158
▼ Start or Stop a Task on a Disk or RAID Volume	159
Restoring or Clearing a RAID Controller Configuration	160
▼ Check to See If a Controller Configuration Exists	160
▼ Restore a RAID Controller Configuration	161
▼ Clear a RAID Controller Configuration	161
Exporting or Importing a RAID Volume Configuration	162
▼ Export a RAID Volume Configuration	162
▼ Import a RAID Volume Configuration	163
Creating RAID Volumes With Partial Disks	163
Guidelines for Using the RAID Volume Size Option	164
Disk Display	164
Partial Disk Properties in XML File	165

▼ Create a RAID Volume with Partial Disks	165
Adding or Removing a Partial Disk	166
Using ubiosconfig to Update the UEFI BIOS	169
ubiosconfig Command Syntax	169
▼ Export UEFI Settings to an XML File	171
▼ Import UEFI BIOS Settings to a Server	172
▼ Display Information on Changes to UEFI BIOS Settings	172
▼ Cancel Pending Changes to UEFI BIOS Settings	173
▼ Reset the UEFI BIOS Settings to Factory Default	173
Using zoningcli to Configure Zoning for the SPARC T3-1 Server	175
zoningcli Command Overview	176
▼ List Zoning Information	176
▼ Enable and Disable Zoning	177
▼ Configure Zoning	177
CLI Tools Error Codes	179
Common Error Codes	179
biosconfig Error Codes	180
firmware-check Error Codes	181
fwupdate Error Codes	181
hwmgmtcli Error Codes	182
ilomconfig Error Codes	183
nvmeadm Error Codes	184
raidconfig Error Codes	184
ubiosconfig Error Codes	186
zoningcli Error Codes	187
Index	189

Using This Documentation

This section describes how to get the latest documentation and support for Oracle Hardware Management Pack (HMP). It also provides feedback links and a document change history.

- “Documentation and Feedback” on page 11
- “Support and Training” on page 11
- “Contributing Authors” on page 12
- “Change History” on page 12

Documentation and Feedback

The following documentation is available related to the Oracle Hardware Management Pack.

Documentation	Link
All Oracle products	https://docs.oracle.com
Oracle Hardware Management Pack	http://www.oracle.com/goto/ohmp/docs
Oracle ILOM	http://www.oracle.com/goto/ilom/docs

Provide feedback on this documentation at:

<http://www.oracle.com/goto/docfeedback>.

Support and Training

These web sites provide additional resources:

- Support: <https://support.oracle.com>

- Training: <http://education.oracle.com>

Contributing Authors

The following authors contributed to this documentation: Cynthia Chin-Lee, Lisa Kuder, David Moss, Ralph Woodley, Michael Bechler.

Change History

The following changes have been made to the documentation set.

- May 2014. Initial publication.
- June 2014. Updated *Release Notes* to add issue 18866436. Updated the Hardware Management Agent overview description in the *Installation Guide* and *Management Agents User's Guide*. Updated the *CLI Tools User's Guide* to add a procedure on checking the Host-to-ILOM Interconnect connection.
- August 2014. Added a note regarding Oracle Solaris 11.2 integration. Updated the *CLI Tools User's Guide* to make editorial improvements. Updated the *Installation Guide* to document an installation issue and updated the *Management Agents User's Guide* to make minor technical updates.
- September/October 2014. Updated the *Installation Guide* and *Release Notes* to add support for Oracle Linux Fault Management Architecture (FMA) software.
- November 2014. Updated the *CLI Tools User's Guide* and *Release Notes* to include NVMe controller support and additional Oracle Hardware Management Pack 2.3.1 updates.
- January 2015. Updated the *Release Notes* to include Oracle Hardware Management Pack 2.3.1.1 updates (issue fixes only, no new features).
- June 2015. Updated the *Release Notes* to include Oracle Hardware Management Pack 2.3.2.2 updates. Updated the *CLI Tools User's Guide* to add error codes for the `ubiosconfig` command and added information on updating firmware on QLogic and Emulex fiber channel controllers. Updated the *Installation Guide*, *Management Agents User's Guide* and *CLI Tools User's Guide* to make editorial improvements and other minor technical updates.
- July 2015. Updated *Release Notes* for minor editorial change. Updated the *Management Agents User's Guide* add additional information on Sun Storage 6 Gb SAS PCIe HBA disk events. Other minor editorial updates made to library.
- September 2015. Updated *Release Notes* to include Oracle Hardware Management Pack 2.3.3 updates. Updated the *Installation Guide* and *Linux FMA User's Guide* to add information on disabling EDAC. Updated *CLI Tools User's Guide* to describe manual power cycle requirement for remote service processor firmware updates. Updated *Management*

Agents User's Guide snmpwalk and set examples. Other minor editorial updates made to library.

- December 2015. Updated the *Release Notes* to add information about feature releases and bug fixes per release. Updated the *CLI Tools User's Guide* to add nvmeadm error codes. Updated the *Command Quick Reference* to add note about Oracle ILOM local host credential cache support.
- July 2016. Updated the *Release Notes* to include Oracle Hardware Management Pack 2.3.6 updates. Updated the *CLI Tools User's Guide* and *Command Quick Reference* to add firmware-check command and check subcommand for fwupdate. Updated the *Installation Guide* for Oracle Hardware Management Pack OS dependencies.
- July 2016. Updated the *CLI Tools User's Guide* and *Command Quick Reference* to make minor technical updates.
- July 2016. Updated the *CLI Tools User's Guide* to correct information on the service processor device identifier used with Oracle Hardware Management Pack 2.3.6.
- August 2016. Updated the *Release Notes* to include Oracle Hardware Management Pack 2.3.7 updates. Updated the *CLI Tools User's Guide* to add additional information on updating firmware with the fwupdate command.

Oracle Server CLI Tools Overview

Oracle Server Command Line Interface (CLI) Tools are part of Oracle Hardware Management Pack and include a rich set of tools and agents that you run from your operating system to configure and monitor server hardware. For information on which servers support each of the CLI tools, refer to <http://www.oracle.com/goto/ohmp>.

The Oracle Oracle Hardware Management Pack download package includes a cross-platform installer for all components. For more information on installing Oracle Oracle Hardware Management Pack components, refer to the [Oracle Hardware Management Pack Installation Guide](#).

Beginning with Oracle Solaris 11.2, Oracle Hardware Management Pack for Oracle Solaris has become an integrated component of the operating system. Do **not** download and use other versions of Oracle Hardware Management Pack that are not specifically qualified for the Oracle Solaris 11.2 (and later). For details, see <http://www.oracle.com/goto/ohmp/solarisdocs>.

Note - This documentation applies to servers running Oracle Solaris 11.1 and earlier or other supported operating systems. If you have Oracle Solaris 11.1 or earlier or other operating systems, continue to use Oracle Hardware Management Pack, available as a separate download from <https://support.oracle.com>.

The following table lists the available Oracle Server CLI Tools.

Tool	Description	Link
biosconfig	Configure your server's BIOS CMOS settings and host boot order. This tool is only available for systems that <i>do not</i> have UEFI-enabled BIOS.	“Using biosconfig to Update the BIOS” on page 23
firmware-check	Check to ensure that the server firmware is at the minimum required version.	“Using firmware-check to Confirm Minimum Required Firmware” on page 53
fwupdate	Update, query, and validate the firmware for Oracle server devices.	“Using fwupdate to Update Firmware” on page 57
hwmgmtcli	Get system information from the Oracle ILOM service processor.	“Using hwmgmtcli to Display Hardware Information” on page 89

Tool	Description	Link
<code>ilomconfig</code>	Manage Oracle ILOM configurations.	“Using <code>ilomconfig</code> to Configure Oracle ILOM” on page 93
<code>ipmitool</code>	Using <code>ipmitool</code> for Windows.	“Using <code>ilomconfig</code> to Configure Oracle ILOM” on page 93
<code>nvmeadm</code>	Modify the controller and device configuration on an NVM Express (NVMe) subsystem.	“Using <code>nvmeadm</code> to Configure an NVM Express Device” on page 129
<code>raidconfig</code>	Configure RAID volumes.	“Using <code>raidconfig</code> to Configure RAID” on page 139
<code>ubiosconfig</code>	Import and export your server's UEFI BIOS settings to an XML file. This tool is only available for systems that <i>have</i> UEFI-enabled BIOS.	“Using <code>ubiosconfig</code> to Update the UEFI BIOS” on page 169
<code>zoningcli</code>	Tool for Oracle SPARC T3-1 servers running Oracle Solaris OS. Enables you to configure systems that have the 16 disk backplane (SAS-2 expander) into two separated zones.	“Using <code>zoningcli</code> to Configure Zoning for the SPARC T3-1 Server” on page 175

For more information on other Oracle Hardware Management Pack features, see [Oracle Hardware Management Pack Installation Guide](#) and [Oracle Server Management Agents User's Guide](#).

For late-breaking issues and information about the CLI Tools, refer to the [Oracle Hardware Management Pack 2.3.x Release Notes](#).

Host-to-ILOM Interconnect

With Oracle ILOM 3.0.12 and later, a Host-to-ILOM Interconnect communication channel is available to enable you to communicate locally with Oracle ILOM from the host operating system (OS) without the use of a network management connection (NET MGT) to the server.

Note - The Oracle Hardware Management Pack refers to this feature as Host-to-ILOM Interconnect. The Oracle ILOM interface refers to this feature as Local Host Interconnect or LAN-over-USB.

The Host-to-ILOM Interconnect is available on the latest Oracle servers and can provide a more reliable and potentially faster data transfer rate for Oracle Hardware Management Pack CLI tools than traditional KCS interfaces.

Accessing the service processor using the Host-to-ILOM Interconnect requires that you either provide credentials manually or set up a host credentials cache using `ilomconfig`. For more information, see [“Providing Host Credentials to the Service Processor”](#) on page 110.

For more information on enabling the Host-to-ILOM Interconnect, refer to [“Enabling the Host-to-ILOM Interconnect”](#) in *Oracle Hardware Management Pack Installation Guide*.

CLI Tools Command Syntax and Conventions

The following table shows the information covered in this section.

Description	Links
Shows the syntax to use for CLI commands.	“CLI Tools Command Syntax” on page 19
Describes the CLI tools naming convention for devices.	“CLI Tools Device-Naming Convention” on page 20

CLI Tools Command Syntax

Most CLI tools commands conform to one of the following two command syntax formats:

- *command [option]*
- *command subcommand target [option]*

Note - The `biosconfig` tool does not conform to the above syntax. See [“Using biosconfig to Update the BIOS” on page 23](#) for more information.

The following table describes the command fields.

Command Field	Description	Examples
<i>command</i>	The action that you want to perform. Identifies that CLI tool that you are using. Consists of lower-case letters only.	<code>biosconfig</code> , <code>fwupdate</code> , <code>raidconfig</code> , <code>ilomconfig</code>
<i>subcommand</i>	Further defines the task to be performed by the <i>command</i> . Generally used as verbs. Consists of lower-case letters, hyphens, or the underscore character.	<code>list</code> , <code>update</code> , <code>reset</code> , <code>expander-boot-record</code>

Command Field	Description	Examples
	The subcommand is not required when the <code>--version</code> or <code>--help</code> options is used immediately following the command.	
<i>target</i>	Describes the object or target that is being acted upon by the subcommand. Application specific.	<code>all, disk, expander, bridge, controller, user, snmp-community</code>
<i>option</i>	Modifies the command or subcommand and can be optional or mandatory depending on the command or subcommand.	<code>-n</code> or <code>--device_name</code> <code>-f</code> or <code>--filename</code>
	There are long and short options that have identical functionality and are provided for ease of use:	<code>-r</code> or <code>--reset</code>
	Short-option is a hyphen followed by a single letter.	
	Long-option is two hyphens followed by a string.	

The following options apply to all CLI Tools commands.

Short Option	Long Option	Description
<code>-?</code>	<code>--help</code>	Displays help information.
<code>-V</code>	<code>--version</code>	Displays the tool version.
<code>-q</code>	<code>--quiet</code>	Suppresses informational message output and returns only error codes.
<code>-y</code>	<code>--yes</code>	Confirms operation. Does not prompt user for confirmation on the operation when running.

When using a command option and its corresponding value or device name, you can use an equal sign (=) or a space as shown in the following examples:

- Using a command with spaces:
`raidconfig create raid -c c2 --raid-level 1 --number-disks 2`
- Using a command with equal signs (=):
`raidconfig create raid -c=c2 --raid-level=1 --number-disks=2`

CLI Tools Device-Naming Convention

The following table lists device names are used with the CLI Tools commands. The character identifier represents all of the nodes that make up the device.

Identifier	Description
c	The controller, followed by a unique logical ID.
r	The RAID Volume (logical disk), followed by a logical ID name of the volume or disk.
d	The disk, followed by the physical disk logical ID name.
x	The expander, followed by the unique expander logical ID name.
j	The chassis, followed by the unique chassis logical ID name.
sp_bios	A system service processor. Note - Use this device identifier with Oracle Hardware Management Pack 2.3.5 and earlier.
sp	A system service processor. Note - Use this device identifier with Oracle Hardware Management Pack 2.3.6 and later.

All integers used to represent the device are 0 based. Disks are represented by logical ID names assigned by the tool at initialization. The disks are sorted by expander and slot ID to create unique numerical identifiers.

The following are examples of device names:

- c1 – Controller 1
- c1d2 – Disk with a logical ID 2 on controller 1
- c2r1 – RAID 1 on controller 2

Multiple devices can be listed together in a comma-separated list, for example: *device1,device2,device3*.

The following example shows a `raidconfig` command for creating a RAID volume with three disks:

```
raidconfig create --disks c1d2,c1d4,c1d5 --level 1
```

The following example shows an implementation of the disk-naming scheme.

ID	Brand	Model	Chassis	Slot	Type	Media	Size (GB)	Firmware
c1d0	SEAGATE	ST373455SSUN72G	0	0	sas	HDD	73	0791
c1d1	SEAGATE	ST35000N	0	1	sata	HDD	500	3AZQ
c1d2	SEAGATE	ST373455SSUN72G	0	2	sas	HDD	73	0B92
c1d3	SEAGATE	ST373455SSUN72G	0	3	sas	HDD	73	0B92
c1d4	SEAGATE	ST35000N	0	4	sata	HDD	500	3AZQ
c1d5	SEAGATE	ST35000N	0	5	sata	HDD	500	3AZQ
c1d6	SEAGATE	ST35000N	0	6	sata	HDD	500	3AZQ
c1d7	SEAGATE	ST373455SSUN72G	0	7	sas	HDD	73	0B92
c1d8	SEAGATE	ST373455SSUN72G	0	8	sas	HDD	73	0B92
c1d9	SEAGATE	ST373455SSUN72G	0	9	sas	HDD	73	0B92

c1d10	SEAGATE	ST35000N	0	10	sata	HDD	500	3AZQ
c1d11	SEAGATE	ST373455SSUN72G	0	11	sas	HDD	73	0B92
c1d12	SEAGATE	ST373455SSUN72G	0	12	sas	HDD	73	0B92
c1d13	SEAGATE	ST373455SSUN72G	0	13	sas	HDD	73	0B92
c1d14	SEAGATE	ST373455SSUN72G	0	14	sas	HDD	73	0B92
c1d15	SEAGATE	ST373455SSUN72G	0	15	sas	HDD	73	0B92
c1d16	SEAGATE	ST373455SSUN72G	0	16	sas	HDD	73	0B92
c1d17	SEAGATE	ST373455SSUN72G	0	17	sas	HDD	73	0B92
c1d18	SEAGATE	ST373455SSUN72G	0	18	sas	HDD	73	0B92
c1d19	SEAGATE	ST373455SSUN72G	0	19	sas	HDD	73	0B92
c1d20	SEAGATE	ST35000N	0	20	sata	HDD	500	3AZQ
c1d21	SEAGATE	ST35000N	0	21	sata	HDD	500	3AZQ
c1d22	SEAGATE	ST35000N	0	22	sata	HDD	500	3AZQ
c1d23	SEAGATE	ST35000N	0	23	sata	HDD	500	3AZQ
c1d24	SEAGATE	ST373455SSUN72G	1	0	sas	HDD	73	0791
c1d25	SEAGATE	ST35000N	1	1	sata	HDD	500	3AZQ
c1d26	SEAGATE	ST373455SSUN72G	1	3	sas	HDD	73	0791
c1d27	SEAGATE	ST35000N	1	4	sata	HDD	500	3AZQ
c1d28	SEAGATE	ST373455SSUN72G	1	5	sas	HDD	73	0791
c1d29	SEAGATE	ST35000N	1	6	sata	HDD	500	3AZQ
c1d30	SEAGATE	ST373455SSUN72G	1	7	sas	HDD	73	0791
c1d31	SEAGATE	ST373455SSUN72G	1	8	sas	HDD	73	0791
c1d32	SEAGATE	ST373455SSUN72G	1	9	sas	HDD	73	0791
c1d33	SEAGATE	ST373455SSUN72G	1	10	sas	HDD	73	0791
c1d34	SEAGATE	ST373455SSUN72G	1	11	sas	HDD	73	0791
c1d35	SEAGATE	ST35000N	1	12	sata	HDD	500	3AZQ
c1d36	SEAGATE	ST373455SSUN72G	1	13	sas	HDD	73	0791
c1d37	SEAGATE	ST373455SSUN72G	1	14	sas	HDD	73	0791
c1d38	SEAGATE	ST35000N	1	15	sata	HDD	500	3AZQ
c1d39	SEAGATE	ST373455SSUN72G	1	16	sas	HDD	73	0791
c1d40	SEAGATE	ST373455SSUN72G	1	17	sas	HDD	73	0791
c1d41	SEAGATE	ST35000N	1	18	sata	HDD	500	3AZQ
c1d42	SEAGATE	ST35000N	1	19	sata	HDD	500	3AZQ
c1d43	SEAGATE	ST35000N	1	20	sata	HDD	500	3AZQ
c1d44	SEAGATE	ST35000N	1	21	sata	HDD	500	3AZQ
c1d45	SEAGATE	ST35000N	1	22	sata	HDD	500	3AZQ
c1d46	SEAGATE	ST35000N	1	23	sata	HDD	500	3AZQ

Using biosconfig to Update the BIOS

biosconfig configures the BIOS CMOS settings, host boot order, and some service processor settings.

Note - The biosconfig tool is used to configure system BIOS (also called "legacy BIOS") on supported Oracle x86 servers. Servers that support UEFI BIOS must use the ubiosconfig tool. See [“Using ubiosconfig to Update the UEFI BIOS” on page 169](#).

For a list of the tools and the systems that support them, refer to:

<http://www.oracle.com/goto/ohmp>

biosconfig allows you to manipulate BIOS configurations from the OS command line. The configuration files and command-line interfaces are compatible with the Oracle Solaris, Windows, and Linux OSes.

The following table shows the information covered in this section.

Description	Links
Learn about the biosconfig command	“biosconfig Command Overview” on page 23
Display information about biosconfig	“Viewing biosconfig Command Options and Version Information” on page 38
Configure device boot order	“Configuring the Device Boot Order” on page 40
Configure the BIOS CMOS	“Configuring the BIOS CMOS” on page 44
Learn about extraneous command output	“Commands That Produce Unrelated, Innocuous, Extra Output” on page 50

biosconfig Command Overview

This section covers the following information:

- [“biosconfig Requirements” on page 24](#)

- [“biosconfig Device Terminology” on page 24](#)
- [“Editing XML Files” on page 25](#)
- [“biosconfig Command Syntax” on page 26](#)

biosconfig Requirements

- You must run biosconfig as root (Linux, Oracle Solaris OS) or Administrator (Windows) because it needs to use drivers that are in read- and write-protected physical address space.
- Close all other applications and quiesce your system before running biosconfig.
- Linux versions of biosconfig depend on access to /dev/nvram to guarantee serialized access to the CMOS.

Red Hat Enterprise Linux 4 distributions do not include the device by default. Red Hat Enterprise Linux 5 and SUSE Linux Enterprise Server distributions do include the device by default.

To use /dev/nvram, the driver needs to be compiled into the kernel (or loaded as a module), and /dev/nvram must exist (root can create it using `mknod /dev/nvram c 10 144`).

- The Sun System Management driver is required for biosconfig to run on Windows systems. For information on biosconfig for Windows, see: [“biosconfig for Windows” on page 27](#).

biosconfig Device Terminology

The following notes explain how biosconfig describes devices:

- Floppy refers to whatever the BIOS considers a removable device.
For example, this could be a USB flash drive.
- A USB flash drive bigger than 512 MB is referred to as a disk.
- A USB/CD-ROM is classified as a CD and not a removable device.
- PXE means a bootable network device.
For example, this might be an Ethernet controller or an InfiniBand interface that has boot support in its expansion ROM.

Device Name Examples

The device name examples listed in the following table are used in XML file output in this chapter.

Output Text	Description of Hardware
SATA:3M-MRVLRD 200254-01SUN24G 0801	Flash mini-DIMM SATA (which is disk-like)
USB:Port1:Memorex DVD+-RAM 510L	USB DVD drive (which is CD-like)
USB:Port0:SanDisk Cruzer Contour	1 GB USB flash drive (which is disk-like)
IB:Slot2.F0:PXE:MLNX HCA IB 1.9.972	InfiniBand PXE (which is network-like)
PXE:IBA GE Slot 00C8 v1324	On-board GigEthernet NIC (which is a network interface)

Editing XML Files

biosconfig enables you to configure settings across multiple similar servers using a common XML configuration file. However, if the configuration that is being modified includes a peripheral or component that is not on both systems, then you need to customize the XML file. The BIOS firmware of systems you are exporting from or importing to does not have to be at the same version.

Note - The XML tag definitions are determined by the current system BIOS. These values can vary by system type and it is not recommended that you use the XML file to update the BIOS configuration across different system types.

The biosconfig command can be used to get current configuration settings or set configuration settings. When used to get configuration settings, biosconfig generates XML output showing the configuration. When used to set configuration settings, biosconfig reads XML input describing the configuration settings.



Caution - Do not use biosconfig to change BIOS settings that are not visible in the normal BIOS setup menu.

To use biosconfig, you must have a working knowledge of XML file editing. The process of editing the BIOS includes using biosconfig to do the following tasks:

1. To obtain the BIOS configuration settings in XML, type:

```
biosconfig -get_option filename.xml
```

If an XML file name is specified with the get command, the BIOS configuration is saved to the XML file. If an XML file is not specified, the output is written to the terminal.

2. Review the XML file and modify it, as required.

You can modify the XML files in a editor of your choice, such as vi.

3. To implement the changes, type:

biosconfig -set_option filename.xml

You can use the same XML file to modify multiple systems of the same type.

biosconfig Command Syntax

The biosconfig command uses the following syntax:

biosconfig [-v] option [filename.xml]

When a command fails, it returns one of the failure codes listed in [“biosconfig Error Codes” on page 180](#).

The following table lists the available biosconfig options and their descriptions.

Option	Description
-get_version	Get version of this tool.
-get_boot_order	Get the boot devices list.
-set_boot_order	Set the boot devices list.
-set_boot_override	Set the first boot device for the next boot.
-get_bios_settings	Get setup configuration from BIOS.
-set_bios_settings	Get setup configuration to BIOS ROM.
-get_CMOS_dump	Get 256 bytes CMOS of set up data from BIOS.
-set_CMOS_dump	Set 256 bytes of CMOS set up data to BIOS.
-v	Verbose mode. On some operations, this might provide additional information regarding operational status. Verbose mode is only valid if an XML input or output filename is provided.

The following table lists examples of how the -get and -set command options affect input and output.

Command	Description
# biosconfig -get_version	Outputs to screen.
# biosconfig -get_version filename.xml	Outputs to filename.xml.
# biosconfig -get_version > filename.xml	Outputs to filename.xml.
# biosconfig -get_version some-command	Pipes the output to another command.

Command	Description
# biosconfig -set_bios_settings	Takes input from standard in.
# biosconfig -set_bios_settings <i>filename.xml</i>	Takes input from <i>filename.xml</i> .
# biosconfig -set_bios_settings < <i>filename.xml</i>	Takes input from <i>filename.xml</i> .

Note - In the output examples in this chapter, all white space outside the XML elements, such as indentation, is optional. For example, see the output in [“Make a Persistent Change to Boot Order”](#) on page 42.

biosconfig for Oracle Solaris OS

The BIOS configuration tool for Oracle Solaris OS (`biosconfig`) is a utility that runs on the host system and configures the host's BIOS CMOS settings, host boot order, and some service processor settings.

Oracle Solaris OS `biosconfig` consists of an Oracle Solaris OS `biosdrv` driver and the `biosconfig` application.

biosconfig for Windows

With `biosconfig` version 2.2.1 and above for Microsoft Windows, `biosconfig.exe` is run only in its installation directory so it can access its low-level management driver. The Sun System Management driver is included as part of the Hardware Management Pack download.

The Sun System Management driver is required in order to run `biosconfig` on Windows Server 2008 SP2 64-bit or Windows Server 2008 R2 systems. This driver is not required for Windows 2008 32-bit, or later versions of Windows.

The Sun System Management driver is not needed for other CLI Tools. Uninstall the driver to free system resources if `biosconfig` is not going to be used. When `biosconfig` is not installed, the driver must be uninstalled manually.

Note - On some systems, when using the Sun System Management Driver, `biosconfig` might take several minutes to complete some operations.

This section covers the following procedures:

- [“Install the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit” on page 28](#)
- [“Uninstall the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit” on page 35](#)

▼ Install the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit


1. In an Administrator terminal window (`cmd.exe`), run the Hardware Wizard executable file, `hdwiz.exe`.




2. Read the Welcome screen and click Next.



3. To install the hardware device manually, select **Install the hardware that I manually select from a list.**




4. Click Have Disk.




5. Choose the driver. There are two common paths for the Sun System Management Driver.

- **Navigate to the path where you extracted Hardware Management Pack.**
Open the SOFTWARE/drivers directory and navigate to the appropriate architecture (32 or 64 bit) and click OK.
- **Navigate to the path where you installed biosconfig.**
The location of the driver depends on which version of Oracle Hardware Management Pack you have.
 - *For version 2.2.7 or later:* The driver is located in the 2008_x64 directory.
 - *For version 2.2.6 and earlier:* The 2008_R2_x64 directory is for Windows Server 2008 R2 64-bit, and the 2008_SP2_x64 directory is for Windows Server 2008 SP2 64-bit.


For example:



6. Select the Sun System Manager Device Driver, and click Next.



7. Click Next to start installing.



8. When the installation is complete, click Finish.




▼ Uninstall the biosconfig Sun System Management Driver on Windows 2008 R2 and Windows 2008 64-bit


1. Open the Windows Control Panel and select Hardware.



2. In the hardware window, select Device Manager.



3. Right click on the Sun System Management Device Driver and select Uninstall.



4. Check Delete the driver software for this device and click OK.



The driver is removed from the system.

Viewing biosconfig Command Options and Version Information

This section covers the following information:

- [“View biosconfig Command Options” on page 38](#)
- [“View biosconfig Version Information” on page 39](#)

▼ View biosconfig Command Options

- To view the help output, execute the biosconfig command without arguments.

Type:

biosconfig

For example:

```
# biosconfig
Copyright (C) SUN Microsystems 2009.
BIOSconfig Utility Version 2.2.5
Build Date: Jan 11 2010
Build Time: 01:22:05
```

```
BIOSconfig Specification Version 2.4
```

```
Usage: biosconfig [-v] option [filename]
Example: biosconfig -get_version output.xml
```

```
[-v] Verbose on. Only valid if a xml input/output filename is provided
[Filename] Name of the XML output (or input) file for get (or set)
command (optional).
get commands will output to the console if the filename
is not provided
set commands will get input from the console if the filename
is not provided
```

Available options (Required):

```
-get_version Get version of this tool
-get_boot_order Get the BOOT Devices list
-set_boot_order Set the BOOT Devices list
-get_bios_settings Get setup configuration from BIOS
-set_bios_settings Set setup configuration to BIOS ROM
-get_CMOS_dump Get 256 bytes CMOS setup data from BIOS
-set_CMOS_dump Set 256 bytes of CMOS setup data to BIOS
```

▼ View biosconfig Version Information

1. To view version information, type:

```
biosconfig -get_version filename.xml
```

For example:

```
# biosconfig -get_version ver.xml
```

```
Copyright (C) SUN Microsystems 2009.
BIOSconfig Utility Version 2.1
Build Date: Jul 16 2009
Build Time: 15:55:12
```

```
BIOSconfig Specification Version 2.4
```

```
Success
```

2. View the created *filename.xml* file.

The following is an example of the version information in an XML file.

```
<?xml version="1.0" encoding="UTF-8"?>
<BIOSCONFIG>
  <BIOSCONFIG_VERSION>2.1</BIOSCONFIG_VERSION>
  <SPEC_VERSION>2.4</SPEC_VERSION>
  <SP_NETWORK_CONFIG>
    <DISCOVERY></DISCOVERY>
    <IP></IP>
    <NETMASK></NETMASK>
    <GATEWAY></GATEWAY>
  </SP_NETWORK_CONFIG>
  <PASSWORD_CONFIG>
    <PASSWORD></PASSWORD>
  </PASSWORD_CONFIG>
  <BOOT_ORDER_OVERRIDE>
    <HELP_STRING>FIRST=Choose one of: pxe, cdrom, disk,
floppy, bios, none</HELP_STRING>
    <FIRST></FIRST>
    <HELP_STRING>CLEAR_CMOS=Choose Yes, No or leave it
empty, em....</HELP_STRING>
    <CLEAR_CMOS></CLEAR_CMOS>
  </BOOT_ORDER_OVERRIDE>
  <BOOT_DEVICE_PRIORITY>
    <B0>
      <DEVICE_NAME></DEVICE_NAME>
      <PCI-B-D-F></PCI-B-D-F>
```

```
</B0>  
</BOOT_DEVICE_PRIORITY>  
</BIOSCONFIG>
```

Configuring the Device Boot Order

During BIOS power-on self-test (POST), BIOS scans the hardware and accumulates a list of bootable devices. That list is then presented as a boot list, which is the ordered list of bootable devices.

`biosconfig` enables you to configure the first device to boot at the next reboot or to configure the entire boot order. `biosconfig` does this by reading the boot-related tables that the BIOS stores in NVRAM and then manipulating the contents of CMOS where the boot order is stored.

This section covers the following information:

- [“Methods for Changing the Boot List” on page 40](#)
- [“Set the First Boot Device for the Next Boot” on page 41](#)
- [“Make a Persistent Change to Boot Order” on page 42](#)
- [“Change Boot Order Based on the PCI Bus, Device, or Function” on page 43](#)

Methods for Changing the Boot List

The boot list can be changed in any of the following ways:

- Change the order in BIOS setup utility.
- Reorder the categories using the IPMI bootflags that the SP offers to the compatible BIOS during POST. The default priority order for categories is CD/DVD, disk, removable, and network.
- Change the boot order using `biosconfig`. This manipulates the contents of CMOS and the BIOS boot block structures stored in NVRAM, which is a dedicated part of the BIOS ROM.

This section contains instructions for changing the boot order using `biosconfig`.

Note - This boot list changes dynamically when devices such as disk drives, USB devices, and PCIe cards are installed and removed. The boot list also changes when javaConsole floppy and CD redirection is started and stopped.

▼ Set the First Boot Device for the Next Boot

This procedure shows how to set the first boot device for the next boot only. To change the boot device for successive boots, see [“Make a Persistent Change to Boot Order” on page 42](#).

Here is an example of using the `-set_boot_override` command that specifies the first boot device as the PXE server on only the next boot:

1. **To create an XML file containing the current boot order of your system, type:**

```
biosconfig -get_boot_order filename.xml
```

2. **Edit XML text so that the device that you want to boot first is between the <FIRST> tags.**

In this example, the PXE device is the first boot device.

The following is an example of the resulting XML file.

```
<?xml version="1.0" encoding="UTF-8"?>
<BIOSCONFIG>
  <BIOSCONFIG_VERSION>2.1</BIOSCONFIG_VERSION>
  <SPEC_VERSION>2.4</SPEC_VERSION>
  <SP_NETWORK_CONFIG>
    <DISCOVERY></DISCOVERY>
    <IP></IP>
    <NETMASK></NETMASK>
    <GATEWAY></GATEWAY>
  </SP_NETWORK_CONFIG>
  <PASSWORD_CONFIG>
    <PASSWORD></PASSWORD>
  </PASSWORD_CONFIG>
  <BOOT_ORDER_OVERRIDE>
    <HELP_STRING>FIRST=Choose one of: pxe, cdrom, disk,
floppy, bios, none</HELP_STRING>
    <FIRST>pxe</FIRST>
    <HELP_STRING>CLEAR_CMOS=Choose Yes, No or leave it
empty, .....</HELP_STRING>
    <CLEAR_CMOS></CLEAR_CMOS>
  </BOOT_ORDER_OVERRIDE>
  <BOOT_DEVICE_PRIORITY>
  <Boot_Device_01>
    <DEVICE_NAME>USB:Port1:Memorex DVD+-RAM 510L v1</DEVICE_NAME>
  </Boot_Device_01>
  <Boot_Device_02>
    <DEVICE_NAME>SATA:3M-MRVLRD 200254-01SUN24G 0801</DEVICE_NAME>
  </Boot_Device_02>
  <Boot_Device_03>
```

```
        <DEVICE_NAME>USB:Port0:SanDisk Cruzer Contour</DEVICE_NAME>
    </Boot_Device_03>
    <Boot_Device_04>
        <DEVICE_NAME>IB:Slot2.F0:PXE:MLNX HCA IB 1.9.972 (PCI 07:00.
    </DEVICE_NAME>
        <PCI-B-D-F>07,00,00</PCI-B-D-F>
    </Boot_Device_04>
    <Boot_Device_05>
        <DEVICE_NAME>PXE:IBA GE Slot 00C8 v1324</DEVICE_NAME>
        <PCI-B-D-F>00,19,00</PCI-B-D-F>
    </Boot_Device_05>
    </BOOT_DEVICE_PRIORITY>
</BIOSCONFIG>
```

3. To set the boot order, type:

```
biosconfig -set_boot_override filename.xml
```

▼ Make a Persistent Change to Boot Order

To make a persistent change to the boot order, modify the order of devices between the `BOOT_DEVICE_PRIORITY` tags of the XML file.

The following example shows an XML file from a Sun Blade X6275 server module (which has a built-in bootable InfiniBand interface) set to optimal defaults with a 1-GByte USB flash, a USB CD, and a dual Gig-Ethernet Express Module plugged in.

1. To create an XML file containing the current boot order of your system, type:

```
biosconfig -get_boot_order filename.xml
```

The following is an example of the output of the XML file:

```
<?xml version="1.0" encoding="UTF-8"?>
<BIOSCONFIG>
  <BIOSCONFIG_VERSION>2.1</BIOSCONFIG_VERSION>
  <SPEC_VERSION>2.4</SPEC_VERSION>
  <SP_NETWORK_CONFIG>
    <DISCOVERY></DISCOVERY>
    <IP></IP>
    <NETMASK></NETMASK>
    <GATEWAY></GATEWAY>
  </SP_NETWORK_CONFIG>
  <PASSWORD_CONFIG>
    <PASSWORD></PASSWORD>
  </PASSWORD_CONFIG>
```

```

<BOOT_ORDER_OVERRIDE>
  <HELP_STRING>FIRST=Choose one of: pxe, cdrom, disk,
floppy, bios, none</HELP_STRING>
  <FIRST></FIRST>
  <HELP_STRING>CLEAR_CMOS=Choose Yes, No or leave it
empty, .....</HELP_STRING>
  <CLEAR_CMOS></CLEAR_CMOS>
</BOOT_ORDER_OVERRIDE>
<BOOT_DEVICE_PRIORITY>
<Boot_Device_01>
  <DEVICE_NAME>USB:Port1:Memorex DVD+-RAM 510L v1</DEVICE_NAME>
</Boot_Device_01>
<Boot_Device_02>
  <DEVICE_NAME>SATA:3M-MRVLRD 200254-01SUN24G 0801</DEVICE_NAME>
</Boot_Device_02>
<Boot_Device_03>
  <DEVICE_NAME>USB:Port0:SanDisk Cruzer Contour</DEVICE_NAME>
</Boot_Device_03>
<Boot_Device_04>
  <DEVICE_NAME>IB:Slot2.F0:PXE:MLNX HCA IB 1.9.972 (PCI 07:00.
</DEVICE_NAME>
  <PCI-B-D-F>07,00,00</PCI-B-D-F>
</Boot_Device_04>
<Boot_Device_05>
  <DEVICE_NAME>PXE:IBA GE Slot 00C8 v1324</DEVICE_NAME>
  <PCI-B-D-F>00,19,00</PCI-B-D-F>
</Boot_Device_05>
</BOOT_DEVICE_PRIORITY>
</BIOSCONFIG>

```

2. **Edit the device names displayed between the <DEVICE_NAME> tags so that the devices are listed in the desired boot order.**
3. **To set the boot order, type:**

```
biosconfig -set_boot_order filename.xml
```

▼ Change Boot Order Based on the PCI Bus, Device, or Function

The `biosconfig` command can alter the boot order based on the PCI bus, device, or function if the boot order list contains that information.

1. **To create an XML file containing the current boot order of your system, type:**

```
biosconfig -get_boot_order filename.xml
```

2. Edit the devices listed between the <PCI-B-D-F> tags so that they are in the desired order.

For example:

```
<BOOT_DEVICE_PRIORITY>
<Boot_Device_01>
  <DEVICE_NAME>PXE:IBA GE Slot 00C8 v1324</DEVICE_NAME>
  <PCI-B-D-F>00,19,00</PCI-B-D-F>
</Boot_Device_01>
<Boot_Device_02>
  <DEVICE_NAME>IB:Slot2.F0:PXE:MLNX HCA IB 1.9.972 (PCI 07:00.</DEVICE_NAME>
  <PCI-B-D-F>07,00,00</PCI-B-D-F>
</Boot_Device_02>
<Boot_Device_03>
  <DEVICE_NAME>USB:Port1:Memorex DVD+-RAM 510L v1</DEVICE_NAME>
</Boot_Device_03>
<Boot_Device_04>
  <DEVICE_NAME>USB:Port0:SanDisk Cruzer Contour</DEVICE_NAME>
</Boot_Device_04>
<Boot_Device_05>
  <DEVICE_NAME>SATA:3M-MRVLRD 200254-01SUN24G 0801</DEVICE_NAME>
</Boot_Device_05>
</BOOT_DEVICE_PRIORITY>
```

3. To set the boot order, type:

```
biosconfig -set_boot_order filename.xml
```

Configuring the BIOS CMOS

The BIOS configuration information is stored in the CMOS memory in the host's chipset. You can use `biosconfig` to modify these settings with a program on the host OS. Alternatively, you can configure many of the CMOS settings through the BIOS setup interface at BIOS POST.

`biosconfig` configures the BIOS CMOS settings using two methods:

- Copying and using a golden (known reliable) image
- Controlling each setting individually

This section covers the following information:

- [“Capture the BIOS CMOS Golden Image” on page 45](#)

- [“Apply the BIOS CMOS Golden Image” on page 46](#)
- [“Configuring Individual CMOS Settings” on page 47](#)

▼ Capture the BIOS CMOS Golden Image

The BIOS configuration consists of the contents of the CMOS and the boot tables in the NVRAM. The command `biosconfig -get_cmos_dump` captures the 256 bytes of CMOS, but it does not gather the boot table information from NVRAM. So this command might not capture the boot-order information, unless the bootable I/O configurations for the source and destination machines are the same.

1. **To generate a golden (known reliable) CMOS image, use the BIOS Setup Utility to configure the BIOS settings.**
2. **To capture the 256 bytes of CMOS containing the configuration information, type:**

```
biosconfig -get_cmos_dump filename.xml
```

The following display shows an example of the output.

```
Copyright (C) SUN Microsystems 2009.
BIOSconfig Utility Version 2.1
Build Date: Jul 16 2009
Build Time: 15:55:12
BIOSconfig Specification Version 2.4
Success
```

The following example shows an XML file containing the CMOS configuration information:

```
<BIOSCONFIG>
  <BIOSCONFIG_VERSION>2.1</BIOSCONFIG_VERSION>
  <SPEC_VERSION>2.4</SPEC_VERSION>
  <SP_NETWORK_CONFIG>
    <DISCOVERY></DISCOVERY>
    <IP></IP>
    <NETMASK></NETMASK>
    <GATEWAY></GATEWAY>
  </SP_NETWORK_CONFIG>
  <PASSWORD_CONFIG>
    <PASSWORD></PASSWORD>
  </PASSWORD_CONFIG>
  <BOOT_ORDER_OVERRIDE>
    <HELP_STRING>FIRST=Choose one of: pxe, cdrom, disk, floppy,
bios, none</HELP_STRING>
```

```

    <FIRST></FIRST>
    <HELP_STRING>CLEAR_CMOS=Choose Yes, No or leave it empty,
</HELP_STRING>
    <CLEAR_CMOS></CLEAR_CMOS>
</BOOT_ORDER_OVERRIDE>
<BOOT_DEVICE_PRIORITY>
    <B0>
        <DEVICE_NAME></DEVICE_NAME>
        <PCI-B-D-F></PCI-B-D-F>
    </B0>
</BOOT_DEVICE_PRIORITY>
<CMOS_DUMP>
<OFFSET_00>00.00.00.00.00.00.00.00.00.00.00.00.00.00.00.</OFFSET_00>
<OFFSET_10>00.30.00.30.0E.80.02.FF.FF.00.00.00.00.00.00.</OFFSET_10>
<OFFSET_20>00.00.00.00.00.00.00.00.00.30.47.47.47.47.04.3A.</OFFSET_20>
<OFFSET_30>FF.FF.20.85.90.F7.07.00.00.03.00.17.00.00.1F.3A.</OFFSET_30>
<OFFSET_40>00.00.00.00.00.00.00.00.00.00.00.00.00.00.00.</OFFSET_40>
<OFFSET_50>00.00.FF.00.13.00.00.01.80.30.30.30.30.00.00.</OFFSET_50>
<OFFSET_60>EF.40.41.42.43.44.45.46.47.08.09.0A.18.00.00.0B.</OFFSET_60>
<OFFSET_70>00.03.0C.0D.0E.0F.10.11.00.00.00.00.12.13.14.15.</OFFSET_70>
<OFFSET_80>11.24.26.06.46.14.00.16.02.00.F8.23.C8.17.20.07.</OFFSET_80>
<OFFSET_90>18.20.19.1A.1B.1C.1D.9E.DF.9E.DE.21.02.03.04.05.</OFFSET_90>
<OFFSET_A0>06.07.08.09.EA.2B.0B.0B.0B.4B.00.01.0F.00.0C.00.</OFFSET_A0>
<OFFSET_B0>00.00.00.00.10.32.54.76.10.32.54.76.14.00.00.00.</OFFSET_B0>
<OFFSET_C0>00.46.BC.00.00.00.00.00.80.C0.10.42.F9.FF.FF.</OFFSET_C0>
<OFFSET_D0>83.00.80.9C.DE.1F.40.02.FA.52.55.E0.F1.F3.E7.FF.</OFFSET_D0>
<OFFSET_E0>7C.00.01.04.00.00.05.04.03.04.00.02.07.02.17.00.</OFFSET_E0>
<OFFSET_F0>17.03.01.05.08.01.03.04.00.03.00.09.01.00.05.00.</OFFSET_F0>
</CMOS_DUMP>
</BIOSCONFIG>

```

Note - The data between the <CMOS_DUMP> element tags contains raw CMOS data.

▼ Apply the BIOS CMOS Golden Image

You can apply the golden image to identical hardware by copying the golden image from your source system to a destination system with the same BIOS revision, as shown using `set_cmos_dump`.

1. **Copy the `filename.xml` image from your source system to a destination system.**
2. **To apply the golden image to the destination system, type:**

```
biosconfig -set_cmos_dump filename.xml
```

Copyright (C) SUN Microsystems 2009.
BIOSconfig Utility Version 2.1
Build Date: Jul 16 2009
Build Time: 15:55:12

BIOSconfig Specification Version 2.4

Processing Input BIOS Data...

Success

Configuring Individual CMOS Settings

biosconfig provides two commands to manage individual CMOS settings:

- `biosconfig -get_bios_settings`
Gets CMOS settings from the platform.
- `biosconfig -set_bios_settings`
Sets CMOS settings on the platform.

To use these commands:

1. Use `-get_bios_settings filename.xml` to generate an XML file that describes the current settings.
2. Edit that XML file to change the settings.
3. Use `set_bios_settings filename.xml` to apply the settings to CMOS.

You can provide a subset of the XML file to include only the settings that you want to change with the `-get_bios_settings` command. The XML file must be valid, so you must remove entire option sets from the XML file.

Note - Values for the settings vary depending on your server type. biosconfig reads the host's BIOS image and the platform's CMOS to find the setup questions (the strings displayed in BIOS setup), the optimal default values, the current settings, and the permitted settings. The XML file structure matches the menu hierarchy in BIOS setup.

The names in the output XML file match the names in the setup menus; the only difference is that the spaces are replaced with underscores (_). For example, the Quick Boot entry in the Boot Settings Configuration submenu in the Boot menu of BIOS setup is specified like this:

```
<BIOSCONFIG>
```

```
<SETUP_CONFIG>
<Boot>
<Boot_Settings_Configuration>
<Quick_Boot>
```

Static and Dynamic CMOS Settings

There are two types of CMOS settings: static and dynamic. Static settings are human readable and dynamic settings are numerical. The following settings are determined at runtime by the BIOS:

- The value in CMOS
- The behavior determined by that value
- The BIOS setup strings displayed

▼ Configure a Static CMOS Setting

The following procedure describes how to set static CMOS settings. The XML samples shown are subsets of the output XML file.

1. To get the CMOS settings, type:

```
biosconfig -get_bios_settings filename.xml
```

2. View the XML file.

For example:

```
<BIOSCONFIG>
  <SETUP_CONFIG>
    <Boot>
      <Boot_Settings_Configuration>
        <Quick_Boot>
          <HELP_STRING>Allows BIOS to skip certain...
        </HELP_STRING>
        <DEFAULT_OPTION>Enabled</DEFAULT_OPTION>
        <SELECTED_OPTION>Enabled</SELECTED_OPTION>
        <OPTION-0>Disabled</OPTION-0>
        <OPTION-1>Enabled</OPTION-1>
      </Quick_Boot>
      <Onboard_IB_gPXE_boot_first >
        <HELP_STRING>Set Onboard Infiniband gPXE ....
      </HELP_STRING>
      <DEFAULT_OPTION>Disabled</DEFAULT_OPTION>
```

```

    <SELECTED_OPTION>Disabled</DEFAULT_OPTION>
    <OPTION-0>Disabled</OPTION-0>
    <OPTION-1>Enabled</OPTION-2>
    </Onboard_IB_gPXE_boot_first_>
    </Boot_Settings_Configuration>
    </Boot>
  </SETUP_CONFIG>
</BIOSCONFIG>

```

3. Modify the value in the <SELECTED_OPTION> tags, as needed.

The options listed below the <SELECTED_OPTION> tags display the available values.

For example, the options for the Quick Boot setting are Disabled and Enabled

4. To set the static CMOS values, type:

```
biosconfig -set_bios_settings filename.xml
```

▼ Configure a Dynamic Setting

`biosconfig` cannot retrieve the strings and the mapping between the values in CMOS. This behavior is BIOS dependent; the ability to retrieve this information depends on the BIOS revision and the platform type.

To configure or export dynamic settings, you need to discover the setting that you wish to use by following these steps:

1. **Enter the BIOS Setup utility.**
2. **Configure the settings manually and save the configuration.**
3. **To examine the resulting XML output to find the value that the BIOS is using for the setting you wish to specify, type:**

```
biosconfig -get_bios_settings filename.xml
```

This is an example of a dynamic CMOS setting as displayed in the XML file:

```

<BIOSCONFIG>
  <SETUP_CONFIG>
    <Boot>
      <Option_ROM_Enable>
      <NET0_Option_ROM_>
      <HELP_STRING>This Option enables execut...
      </HELP_STRING>
      <DEFAULT_OPTION> 0000 </DEFAULT_OPTION>
    </Boot>
  </SETUP_CONFIG>
</BIOSCONFIG>

```

```
<SELECTED_OPTION> 0000 </SELECTED_OPTION>
<OPTION_RANGE> 0000 - 0001 </OPTION_RANGE>
<OPTION-0>Not Available</OPTION-0>
</NET0_Option_ROM_>
</Option_ROM_Enable>
</Boot>
</SETUP_CONFIG>
</BIOSCONFIG>
```

In the preceding code, there are no string-to-value mappings offered by the biosconfig output.

4. To set the BIOS configuration, type:

```
biosconfig -set_bios_settings filename.xml
```

Use this XML file to configure dynamic CMOS settings on machines of the same model.

Commands That Produce Unrelated, Innocuous, Extra Output

The following is a known issue with biosconfig.

Some commands have extraneous output in the XML file. For example, the following is the extra output from -get_cmos_dump.

```
<SP_NETWORK_CONFIG>
  <DISCOVERY></DISCOVERY>
  <IP></IP>
  <NETMASK></NETMASK>
  <GATEWAY></GATEWAY>
</SP_NETWORK_CONFIG>
<PASSWORD_CONFIG>
  <PASSWORD></PASSWORD>
</PASSWORD_CONFIG>
<BOOT_ORDER_OVERRIDE>
  <HELP_STRING>FIRST=Choose one of: pxe, cdrom, disk,
  floppy, bios, none</HELP_STRING>
  <FIRST></FIRST>
  <HELP_STRING>CLEAR_CMOS=Choose Yes, No or leave it
  empty, empty means No</HELP_STRING>
  <CLEAR_CMOS></CLEAR_CMOS>
</BOOT_ORDER_OVERRIDE>
<BOOT_DEVICE_PRIORITY>
  <B0>
  <DEVICE_NAME></DEVICE_NAME>
```

```
<PCI-B-D-F></PCI-B-D-F>  
</B0>  
</BOOT_DEVICE_PRIORITY>
```


Using `firmware-check` to Confirm Minimum Required Firmware

Introduced in Oracle Hardware Management Pack 2.3.6, the `firmware-check` command verifies the firmware version of the current host system to determine if the latest minimum required version is installed. If the current host version is older than the minimum required version, a message is displayed using `stdout` or logged to `syslog`. Firmware checked by `firmware-check` includes system level firmware and Oracle ILOM. Running the minimum required version of firmware ensures optimal performance, security, and stability of the system.

The following table shows the information covered in this section.

Description	Links
Learn about the <code>fwupdate</code> command	“<code>firmware-check</code> Command Overview” on page 53
Display component information	“Checking System Firmware Information” on page 55

See Also:

[“Using `fwupdate` to Update Firmware” on page 57](#)

`firmware-check` Command Overview

This section covers the following information:

- [“`firmware-check` Features” on page 54](#)
- [“`firmware-check` Command Prerequisites” on page 54](#)
- [“`firmware-check` Command Syntax” on page 54](#)

firmware-check Features

When installed, `firmware-check` by default runs in the background at OS boot to check the installed system firmware against metadata. If the installed version of system firmware is older than the required minimum version, a message is logged to syslog. The `firmware-check` command can also be run manually at the command line or used in a script with the results being displayed and/or logged to syslog.

When run, `firmware-check` does the following:

- If the version is at or above the minimum level, no reporting is done.
- If the version is older than the minimum level, an error is reported.

firmware-check Command Prerequisites

- `firmware-check` is not supported for use with systems that have a version of Oracle ILOM older than 3.0.2.
- `firmware-check` can only be run on domains that have direct access to ILOM/sysfw versions, such as DOM0 and Control Domains. It cannot be run in non-global or Kernel zones, or in virtual environments. Communication occurs through KCS.
- For information on supported operating systems and platforms, see the *Release Notes*.

firmware-check Command Syntax

The `firmware-check` command uses the following syntax:

`firmware-check options`

When a command fails, it returns one of the failure codes listed in [“firmware-check Error Codes” on page 181](#).

The options listed in the following table apply to all CLI Tools commands, including `firmware-check`.

Short Option	Long Option	Description
-?	--help	Displays help information.

Short Option	Long Option	Description
-v	--version	Displays the tool version.

`firmware-check` supports the following command-specific options.

Short Option	Long Option	Description
-a	--age	Displays the installed metadata expiration date. The metadata determines if the installed firmware meets the latest minimum required version provided by Oracle. <code>firmware-check</code> checks if the metadata is out of date. When it is out of date, a message appears prompting you to download an update. This option cannot be combined with other options.
-q	--quiet	Run in quiet mode. No text is output to stdout or stderr.
-r	--readfw	Displays the current host sysfw/ILOM version. This option cannot be combined with other options.
-s	--syslog	Reports errors to syslog.

Checking System Firmware Information

This section covers the following information:

- [“Manually Check System Firmware” on page 55](#)
- [“List Current System Firmware” on page 56](#)
- [“Perform a Silent Check and Log the Results” on page 56](#)

▼ Manually Check System Firmware

The installation default is to check the system firmware during boot. You can also confirm system firmware is at the minimum version required by Oracle by manually running the command.

- **To check the system firmware to ensure it meets minimum requirements, type:**
`firmware-check`

This command checks the current firmware version against installed metadata. If the firmware needs to be updated, an error displays to stdout. If not, nothing is displayed.

▼ List Current System Firmware

- To list the current system firmware information, type:

```
firmware-check -r
```

This command will display the current host firmware version.

Output for a SPARC system looks similar to:

```
# firmware-check -r
Current host sysfw/ILOM version string: Sun System Firmware 8.3.11
2015/06/04 07:29
```

Output for an x86 system looks similar to:

```
# firmware-check -r
Current host sysfw/ILOM version string: 3.2.4.28.b
```

▼ Perform a Silent Check and Log the Results

Manually perform a silent firmware check and log the results.

- To perform a silent check of system firmware and log the results, type:

```
firmware-check -s -q
```

This command will perform a quiet version check and log any errors found in syslog.

Using fwupdate to Update Firmware

fwupdate is a utility that enables you to update, query, and validate the firmware of an Oracle server. This includes system firmware and the Oracle Integrated Lights Out Manager (ILOM), and device firmware such as network adapters, storage adapters, SAS expanders and various types of disk drives.

The following table shows the information covered in this section.

Description	Links
Learn about the fwupdate command	“fwupdate Command Overview” on page 57
Display component information	“Listing Component Firmware Information” on page 61
Check system firmware for minimum required version	“Checking System Firmware” on page 70
Update component firmware	“Updating Component Firmware” on page 71
Reset a device	“Reset a Device After a Firmware Update” on page 86
View execution summary information	“Execution Summary” on page 88

fwupdate Command Overview

This section covers the following information:

- [“fwupdate Features” on page 58](#)
- [“fwupdate Command Prerequisites” on page 58](#)
- [“Downloading Firmware Patches” on page 59](#)
- [“fwupdate and Service Processor Access” on page 59](#)
- [“fwupdate Command Syntax” on page 60](#)

fwupdate Features

fwupdate enables you to update firmware for the following components:

- System firmware and the Oracle ILOM service processor. System firmware includes BIOS for x86, and OBP, Hypervisor, NYX, POST, etc. for SPARC
- HBA and embedded storage controllers, SAS1, SAS2 and SAS3
- Disk drives (spinning media and flash drives)
- LSI SAS expander devices, SAS1, SAS2 and SAS3
- Emulex and QLogic Fiber Channel controllers

Note - Updating Emulex and QLogic Fiber Channel controller firmware using fwupdate requires the Emulex and QLogic vendor tools. If these packages are not already installed, install them as described in the *Oracle Hardware Management Pack Installation Guide*.

- Mellanox InfiniBand controllers
- Intel LOM (LAN on Motherboard)
- Intel Network Interface Cards (NICs)

You can use fwupdate to do the following:

- List firmware information for devices in a server
- Check that the system's firmware is at the minimum required version for supported features and security
- Ensure firmware file compatibility
- Update device firmware using an automated XML metadata file
- Update firmware manually using a raw firmware file
- Manually reset updated devices, if required

fwupdate Command Prerequisites

The following prerequisites must be met before using the fwupdate command:

- You must have root permission to run fwupdate commands on Unix-based platforms, or administrator permission for Windows platforms.
- Before using the fwupdate command to update device firmware, you must quiesce the device.



Caution - System hang or data loss. Before updating device firmware, make sure that the device is quiesced.

- When updating the firmware on a hard drive, the following prerequisites must be met:
 - Make sure that the operating system is not accessing the disk (for example, the system boot disk).
 - Make sure that an application is not accessing the disk (for example, a database application).
 - If hardware RAID is being used on the system, make sure that the RAID controller is not accessing the disk (for example, if it is rebuilding an array or is in a degraded state). You can use `raidconfig` to check the state of the arrays.
 - For Oracle Solaris systems, after hot-plugging a device, run the `devfsadm -C` command to re-enumerate all of the system device nodes before running the `fwupdate` command.
- Updating Emulex and QLogic Fiber Channel controller firmware using `fwupdate` requires the Emulex and QLogic vendor tools provided with Oracle Hardware Management Pack. If they are not installed, you need to install them, refer to the *Oracle Hardware Management Pack Installation Guide*.

Downloading Firmware Patches

Download firmware patches from <https://support.oracle.com>.

Search for the product that you want to update and download the latest firmware package available for that product.

fwupdate and Service Processor Access

When updating system firmware including the service processor (SP), `fwupdate` can be used over a local Host-to-ILOM interconnect or a remote Ethernet network connection. When using local update, `fwupdate` uses the fastest local interface available. If a Host-to-ILOM connection is available this fast connection is used, otherwise the slower KCS interface is used. See “[Host-to-ILOM Interconnect](#)” on page 17.

When issuing a `fwupdate` command that accesses the service processor, login credentials are not required when using the local Host-to-ILOM interconnect, but they are required for a remote Ethernet network connection.

Note - For systems with an Oracle ILOM version earlier than 3.2.4, to use a LAN interface (either the Host-to-ILOM interconnect or Ethernet network connection) you must manually include credentials using the -H and -U options for commands that access a service processor. If credentials are not provided the commands will default to the slower local KCS interface to access the local service processor.

The credential options listed in the following table are supported for `fwupdate` when accessing a service processor over a network connection.

Short Option	Long Options	Description
-H	--remote-hostname	This option is followed by the host name or IP address of the remote service processor.
-U	--remote-username	This option is followed by the user name with root access used to log in to the remote service processor.

When using these options to access an SP connection, you must use both options together.

Note - The password required by the network connection can be piped in on stdin for scripting use.

fwupdate Command Syntax

The `fwupdate` command uses the following syntax:

fwupdate *subcommand target options*

If you use the `--help` or `--version` options, the `fwupdate` command does not require subcommands; otherwise a subcommand is mandatory.

When a command fails, it returns one of the failure codes listed in [“fwupdate Error Codes” on page 181](#).

`fwupdate` supports the subcommands listed in the following table.

Subcommand	Description
<code>list</code>	Provides firmware information about a device or a file. For targets and options specific to the <code>list</code> subcommand, see “Listing Component Firmware Information” on page 61 .

Subcommand	Description
check	Check system firmware to see if it is at the minimum required version. For targets specific to the check subcommand, see “Checking System Firmware” on page 70 . Note - This feature is available with Oracle Hardware Management Pack 2.3.6 and later. For more information, see the <i>Release Notes</i> .
update	Updates one or more system components based on command-line directives. Devices can be updated automatically using metadata information contained in an XML file (recommended), or updated manually using a firmware image file. For targets and options specific to the update subcommand, see “Updating Component Firmware” on page 71 .
reset	Resets the specified device if the device supports a reset. Perform a reset on a device after a manual mode firmware update (if required). In some cases where the metadata used in an automatic mode firmware update does not automatically reset a device that requires one, this subcommand can be used. For targets and options specific to the reset subcommand, see “Reset a Device After a Firmware Update” on page 86 .

The options listed in the following table apply to all Oracle Hardware Management Pack CLI Tools commands, including `fwupdate`.

Short Option	Long Option	Description
-?	--help	Displays help information.
-V	--version	Displays the tool version.

Listing Component Firmware Information

This section covers the following information:

- [“list Subcommand Overview” on page 61](#)
- [“List All Component Firmware Information” on page 64](#)
- [“List Specific Component Firmware Information” on page 68](#)

list Subcommand Overview

The `list` subcommand does the following:

- Displays the version of firmware for all components
- Tells you whether the target device can be updated with the XML metadata file
- Saves the configuration information to a specified XML file

This information can be used to check the state of a device before executing a firmware update and can be used to verify that a firmware update has been successful. The device naming convention used for target devices is shared with other Oracle Hardware Management CLI Tools.

The format for using the `list` subcommand is:

```
fwupdate list target options
```

The supported targets for the `list` subcommand are listed in the following table.

Target	Description
<code>all</code>	All supported component types, such as disks, expanders, controllers, bridge devices, and system firmware (including Oracle ILOM) that can be updated using an XML metadata file included with a firmware package.
<code>disk</code>	Supported hard disk drives and solid state disk drives.
<code>expander</code>	Supported SAS expanders.
<code>controller</code>	Supported controllers, such as storage and networking.
<code>bridge</code>	Supported embedded SAS-to-SATA bridge devices (used on some older systems).
<code>sp_bios</code>	System firmware on x86 or SPARC, including BIOS/OBP and Oracle ILOM. Note - This target has been deprecated for SPARC and is replaced by the <code>sysfw</code> target.
<code>sysfw</code>	System firmware on SPARC, including OBP and Oracle ILOM.
<code>supported-targets</code>	List supported <code>fwupdate</code> component types that can be automatically updated using an XML metadata file. The firmware for these components can be updated individually or all at the same time using an XML metadata file included with a firmware package.
<code>supported-images</code>	List supported <code>fwupdate</code> component image types that can be manually updated. The firmware images of these components are individually updated by applying a firmware package image file.
<code>error-codes</code>	List all of the <code>fwupdate</code> return codes.

The `list` options are listed in the following table.

Short Option	Long Option	Description
<code>-n</code>	<code>--device_name</code>	Allows a mandatory parameter to designate a single device to list. The <code>--device_name</code> option is the common-mapped device name. For more information, see “CLI Tools Device-Naming Convention” on page 20 .
<code>-v</code>	<code>--verbose</code>	Displays detailed information about each component listed. Verbose is off by default.
<code>-x</code>	<code>--xml=filename.xml</code>	Uses the provided XML metadata file to determine which components are supported.

Short Option	Long Option	Description
-o	--output_xml= <i>filename.xml</i>	Prints the configuration information in XML format to the given file.

The following information is displayed with the `fwupdate list all` command. Items marked with an asterisk (*) are displayed in verbose listing.

- SP (SPARC) or SP + BIOS (x86)
 - ID
 - Product Name
 - ILOM Version
 - BIOS/OBP Version
 - XML Support
- Controllers
 - ID
 - Type
 - Manufacturer
 - Mode
 - Product Name
 - Firmware (F/W) Version
 - BIOS version
 - EFI Version
 - FCODE Version
 - Package Version
 - NVDATA Version
 - XML Support
 - NODE ID*
 - Part Number*
 - PCI Address*
 - PCI Vendor ID*
 - WWN*
- Disk
 - ID
 - Manufacturer
 - Model
 - Chassis
 - Slot

- Type
- Media
- Size
- Firmware (FW) Version
- XML Support
- NODE ID*
- WWN*
- Expander
 - ID
 - Chassis
 - Slot
 - Manufacturer
 - Model
 - Expander Name
 - Firmware (F/W) Version
 - XML Support
 - NODE ID*
 - Product Revision*
 - WWN*
- Bridge
 - ID
 - Chassis
 - Slot
 - Manufacturer
 - Model
 - Firmware (F/W) Version
 - Att FW Version
 - XML Support
 - NODE ID*
 - WWN*

▼ List All Component Firmware Information

- To list all component firmware information on the system, type:

```
fwupdate list all -v
```

The following is sample output from this command:

Note - The output for the c1 controller shows the NVMe controller type and the c2 and c3 controllers show NIC controller type, which are supported in Oracle Hardware Management Pack 2.3.1 and later.

```
=====
SP + BIOS
```

```
=====
ID: sp_bios
   Product Name: SUN SERVER X4-4
   ILOM Version: v3.2.2.10 r86071
   BIOS/OBP Version: 24010200
   XML Support: N/A
```

```
=====
CONTROLLER
```

```
=====
ID: c0
   Node ID: mpt2sas:01:00.0
   Type: SAS
   Manufacturer: LSI Logic
   Model: 0x0072
   Product Name: SGX-SAS6-INT-Z
   FW Version: 11.05.02.00
   BIOS Version: 07.21.04.00
   EFI Version: 07.18.02.11
   PCI Address: 01:00.0
   PCI Vendor ID: 0x1000
   WWN: 0x500605b00452c5f0
   Serial Number: 500605b00452c5f0
   NVDATA Version: 10.03.00.26
   XML Support: N/A
   NAC Name: /SYS/MB/PCI2/SAS2
```

```
DISKS
```

```
=====
```

```
ID: c0d0
   Manufacturer: HGST
   Model: H101212SESUN1.2T
   Slot: 0
   Node ID: PDS:5000cca01d04e311
   Type: sas
```

List All Component Firmware Information

Media: HDD
Size (GB): 1200
Serial Number: 001304D2P9VD KZG2P9VD
FW Version: A447
XML Support: N/A
NAC Name: /SYS/HDD0

ID: c0d1
Manufacturer: HGST
Model: H101212SESUN1.2T
Slot: 1
Node ID: PDS:5000cca01d049199
Type: sas
Media: HDD
Size (GB): 1200
Serial Number: 001304D2HWND KZG2HWND
FW Version: A447
XML Support: N/A
NAC Name: /SYS/HDD1

=====
CONTROLLER
=====

ID: c1
Node ID: nvme:81:00.00
Type: NVMe
Manufacturer: Intel
Model: 0x0953
Product Name: INTEL SSDPEDME016T4S
FW Version: 8DV1RA02
PCI Address: 81:00.0
PCI Vendor ID: 0x8086
Serial Number: CVMD4166002J1P6DGN
XML Support: N/A
NAC Name: /SYS/MB/PCI6/NVMe4

DISKS
=====

ID: c1d0
Manufacturer: INTEL
Model: SSDPEDME016T4S
Node ID: PDD:/dev/nvme0n1
Media: NVME
Size (GB): 200
Serial Number: CVMD4166002J1P6DGN
XML Support: N/A

=====
CONTROLLER
=====

ID: c2
Node ID: Generic WWN:00:10:E0:3B:F8:AC
Type: NET
Manufacturer: Intel
Model: 0x1528
Product Name: Intel(R) Ethernet Controller X540-AT2
EFI Version:
FCODE Version:
Package Version: 800004BE
PXE Version:
CLP Version:
FCOE Version:
ISCSI Version:
PCI Address: a0:00.0
PCI Vendor ID: 0x8086
Sequence Number: 0
XML Support: N/A
NAC Name: /SYS/MB/NET0

=====
CONTROLLER
=====

ID: c3
Node ID: Generic WWN:00:10:E0:3B:F8:AE
Type: NET
Manufacturer: Intel
Model: 0x1528
Product Name: Intel(R) Ethernet Controller X540-AT2
EFI Version:
FCODE Version:
Package Version: 800004BF
PXE Version:
CLP Version:
FCOE Version:
ISCSI Version:
PCI Address: b0:00.0
PCI Vendor ID: 0x8086
Sequence Number: 1
XML Support: N/A
NAC Name: /SYS/MB/NET2

▼ List Specific Component Firmware Information

- To list component firmware information, type:

fwupdate list target options

The following are some examples of the output for `fwupdate list` commands:

fwupdate list disk -v

```
=====
CONTROLLER
=====
ID: c0
Node ID: mptir2:40:00.0
Type: SAS
Manufacturer: LSI Logic
Model: 0x0072
Product Name: SGX-SAS6-REM-Z
FW Version: 11.05.02.00
BIOS Version: 07.21.04.00
EFI Version: 07.18.02.13
FCODE Version: 01.00.60.00
PCI Address: 40:00.0
PCI Vendor ID: 0x1000
WWN: 0x500605b005243000
NVDATA Version: 10.03.00.26 (default) 10.03.00.27 (persistent)
XML Support: N/A

DISKS
=====
ID: c0d0
Manufacturer: HITACHI
Model: H106030SDSUN300G
Slot: 2
Node ID: PDS:5000cca02515b089
Type: sas
Media: HDD
Size (GB): 300
FW Version: A2B0
XML Support: N/A

ID: c0d1
Manufacturer: HITACHI
Model: H106030SDSUN300G
Slot: 3
Node ID: PDS:5000cca025143f79
```

Type: sas
 Media: HDD
 Size (GB): 300
 FW Version: A2B0
 XML Support: N/A

fwupdate list sp_bios -x metadata_3.1.2.10.b.xml

SP + BIOS

```
=====
ID          Product Name      ILOM Version      BIOS/OBP Version  XML Support
-----
sp_bios    SUN FIRE X4170 M3  v3.1.2.10.a r75921  17030100      Yes
```

fwupdate list controller -n c0 -v

CONTROLLER

```
=====
ID: c0
Node ID: mptmega:41:00.0
Type: SAS
Manufacturer: LSI Logic
Model: 0x0079
Product Name: LSI MegaRAID SAS 9261-8i
FW Version: 2.130.353-1803
BIOS Version: 3.24.00
EFI Version: 4.12.05.00
FCODE Version:
PCI Address: 41:00.0
PCI Vendor ID: 0x1000
XML Support: N/A
```

fwupdate list disk -n c2d0

DISK

```
=====
ID      Manufacturer  Model              Chassis Slot  Type  Media  Size (GB)  FW
Version XML Support
-----
c2d0   ATA           3E128-TS2-550B01  -             -    sata  SSD       100      TI35
      N/A
```

fwupdate list disk -n c2d0 -v

DISK

```
=====
ID: c2d0
Manufacturer: ATA
Model: 3E128-TS2-550B01
```

```
Node ID: PDD:/dev/sg3
Type: sata
Media: SSD
Size (GB): 100
FW Version: TI35
XML Support: N/A
```

```
fwupdate list expander -n c1x0
```

```
EXPANDER
=====
ID      Chassis Slot Manufacturer Model    Expander Name  FW Version  XML Support
-----
c1x0    0        -    ORACLE    DE2-24P  Primary      0010       N/A
```

```
fwupdate list expander -n c1x0 -v
```

```
EXPANDER
=====
ID: c1x0
Chassis: 0
Manufacturer: ORACLE
Model: DE2-24P
Expander Name: Primary
FW Version: 0010
Product Revision: 0010
Node ID: EC:mpt2sas:30:00.0:5080020001431f3e
XML Support: N/A
```

Checking System Firmware

The following topics are covered in this section.

- [“check Subcommand Overview” on page 70](#)
- [“Check System Firmware Information” on page 71](#)

check Subcommand Overview

The check subcommand checks the current host system firmware to determine if the latest minimum required version is installed. If the current version is older than the minimum required version, a message is displayed.

Running the minimum required firmware version ensures optimal performance, security, and stability of the system.

Note - This feature is available with Oracle Hardware Management Pack 2.3.6 and later. For more information, see the *Release Notes*.

The following command syntax is used for the check subcommand:

```
fwupdate check target
```

The supported targets for the check subcommand are listed in the following table.

Target	Description
sp_bios	System firmware on x86 (BIOS) or SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM. Note - This target has been deprecated for SPARC and is replaced by the sysfw target.
sysfw	System firmware on SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM.

▼ Check System Firmware Information

- **To check to see if system firmware meets minimum requirements stability and security:**

For a SPARC system, type: **fwupdate check sysfw**

For an x86 system, type: **fwupdate check sp_bios**

The following is sample output from this command:

```
# fwupdate check sysfw
ERROR: The installed System Firmware or ILOM version
is not the latest available. You must update it to
obtain the latest security and other fixes.
```

If you are required to update your system firmware, download the latest patch. See [“Downloading Firmware Patches” on page 59](#).

Updating Component Firmware

The following topics are covered in this section.

- [“update Subcommand Overview” on page 72](#)
- [“Updating Component Firmware With a Metadata File \(Automatic Mode\)” on page 72](#)
- [“Updating Component Firmware Without a Metadata File \(Manual Mode\)” on page 80](#)

update Subcommand Overview

The update subcommand is used with `fwupdate` to update system and device firmware. The update subcommand supports two methods for updating system and device firmware:

- **Automatic mode** uses information contained in an XML metadata file that is packaged with the platform firmware download to update device firmware. This metadata contains information about the components that can be updated with the included firmware file. In addition, the metadata contains commands for any host resets or power cycles required by the update. See the release notes included with the firmware for more details. This is the most accurate and the recommended firmware update method to use.

Check the download package and its release notes to determine whether or not an XML metadata file is available, or simply look in the download package for a metadata XML file. The platform product notes might also contain important update information specific to the device you are updating.
- **Manual mode** allows you to update the firmware of a single device directly using a firmware file. This firmware update method should only be used if there is no XML metadata file available for the device that you want to update. In addition, any required device reset or power cycle not performed automatically after the update must be performed manually. Check the release notes included with the firmware for more details.

Each mode has its own supported command syntax and set of targets and options.

Note - Some systems require special processes to update system firmware. Always consult the release notes included with the firmware patch download for any special instructions that supersede instructions listed here.

Updating Component Firmware With a Metadata File (Automatic Mode)

`fwupdate update automatic mode` updates the specified target component(s) using platform-specific firmware update metadata information. This information is contained in a metadata

XML file that is part of the platform firmware download package. The metadata method ensures only supported platform components get updated and also performs any device/host resets or host power cycles required. This is the most accurate method to use to update firmware in a system.

The following command syntax is used for the `update` subcommand when using automatic mode:

```
fwupdate update target options -x metadata.xml
```

Examples of command usage are listed below the supported target and options tables.

When used in automatic mode, the `update` subcommand supports the following component type targets:

Target	Description
all	All supported targets, such as disks, expanders, controllers, bridge devices, and system firmware (including Oracle ILOM).
disk	Supported hard disk drives and solid state disk drives.
expander	Supported SAS expanders.
controller	Supported controllers, such as storage and networking.
bridge	Supported embedded SAS-to-SATA bridge devices (used on some older systems).
sp_bios	System firmware on x86 (BIOS) or SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM. Note - This target has been deprecated for SPARC and is replaced by the <code>sysfw</code> target.
sysfw	System firmware on SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM.

When used in automatic mode, `update` subcommand supports the following options:

Short Option	Long Option	Descriptions
-n	--device_name	Precedes name of the device to update. The name is the mapped name, which you can retrieve by using the <code>fwupdate list all</code> command. This option is not required when used with a metadata XML file. For information about device names, see “CLI Tools Device-Naming Convention” on page 20 .
-d	--dry-run	Optional. Checks all input, executes an available dry-run check command on the firmware and component, but makes no permanent changes.
-x	--xml=metadata.xml	If the firmware package contains a metadata XML file, this command provides the path to <code>metadata.xml</code> .
-o	--output=filename	Logs all actions in the specified file.

Short Option	Long Option	Descriptions
-p	--priority= <i>value</i>	Starts processing input metadata from an XML file at a given priority level, skipping all lower levels.
-q	--quiet	Uses silent, non-interactive mode. Suppresses user prompts and informational message output and only returns error codes during the update. Useful for scripting.
n/a	--silent-reboot	Enables a host reboot (or power cycle) after the firmware update with no prompt to the user. Reboot happens automatically. Note - This option is supported for all x86 systems. This option is also supported with newer SPARC systems that support Live Firmware Update and utilize metadata that includes a power cycle (refer to your SPARC firmware release notes to see if your system supports Live Firmware Update).
n/a	--silent-no-reboot	Prevents a host reboot after a firmware update. The user is not prompted to initiate a host reboot and no reboot takes place. If this option is used, the host will need to be manually rebooted later to complete the firmware update. Note - This option is supported for all x86 systems. This option is also supported with newer SPARC systems that support Live Firmware Update and utilize metadata that includes a power cycle (refer to your SPARC firmware release notes to see if your system supports Live Firmware Update).

Usage examples:

- To update the firmware of all devices supported in the metadata file, type:

```
fwupdate update all -x metadata.xml
```

For example, if you are updating NVMe device firmware and there are three NVMe devices installed in the system, specifying `fwupdate update all` with an NVMe metadata file will update all three NVMe devices. This is the recommended and safest method for updating devices.

- To update system firmware (including Oracle ILOM) in quiet (non-interactive) mode but delay any host reboot or power cycle:

For a SPARC system, type: **fwupdate update sysfw -q -x metadata.xml --silent-no-reboot**

For an x86 system, type: **fwupdate update sp_bios -q -x metadata.xml --silent-no-reboot**

This updates the platform system firmware as specified in the metadata without prompts or messages. If the metadata includes a host reboot or power cycle, the Oracle ILOM service processor is restarted after the update, but the host system is not restarted. The system firmware update on the host (which includes updates to BIOS for x86, or OBP, Hypervisor, NYX, POST, etc. for SPARC) will be completed at the next power cycle for SPARC or reboot for x86.

Note - The `--silent-no-reboot` and `--silent-reboot` options are not supported on SPARC systems that do not support the Live Firmware Update feature. For systems that support Live Firmware Update, these options are supported if the metadata includes a power cycle. Check the release notes included with your SPARC firmware download package to see if this feature is supported.

- To update all disks supported in the metadata file, type:

```
fwupdate update disk -x metadata.xml
```

This updates all disks in the system whose target device types are specified in the metadata file.

- To update a specific disk supported in the metadata file, type:

```
fwupdate update disk -x metadata.xml -n c0d1
```

This updates only disk `c0d1`, and only if the `c0d1` disk drive type is specified in the metadata file.

See also

- [“Update System Firmware Using Automatic Mode” on page 75](#)
- [“Update Device Firmware Using Automatic Mode” on page 78](#)

▼ Update System Firmware Using Automatic Mode

System firmware is generally a bundled package that includes firmware for the Oracle ILOM service processor and either BIOS for x86 systems, or OBP, Hypervisor, NYX, POST, etc. for SPARC systems.

- Before You Begin**
- To update system firmware using the fastest possible local option, ensure the Host-to-ILOM Interconnect is correctly configured to communicate with the target Oracle ILOM service processor ([“Configuring the Host-to-ILOM Interconnect” on page 109](#)). For systems that do not support updates over the Host-to-ILOM interconnect, the remote option utilizing a network connection to the service processor can be used.
 - Download the firmware update from <https://support.oracle.com>.
The download should include a metadata file and firmware file for the target system.
 - Make sure that the firmware is compatible with the target system. Some updates require a minimum version of firmware from which to perform the update. For some systems, special update processes might be described in the release notes that supersede instructions listed here. Read all documentation and release notes included with the firmware before proceeding.

1. To display information about system firmware, choose the local or remote option:

- **Local** – To list information about the local system firmware, enter one of the following commands:

For x86 systems: `fwupdate list sp_bios`

For SPARC systems: `fwupdate list sysfw`

- **Remote** – To list information about system firmware using a network connection, enter one of the following commands:

For x86 systems: `fwupdate list sp_bios -H sp_ip -U username`

For SPARC systems: `fwupdate list sysfw -H sp_ip -U username`

where `sp_ip` is the IP address of the service processor and `username` is the user name with Admin (a) role account privileges for logging in to the Oracle ILOM service processor.

Enter the Oracle ILOM password when prompted.

Output related to the target is displayed. For example the output from this command is similar to:

```
=====
SP + BIOS
=====
ID      Product Name          ILOM Version      BIOS/OBP Version  XML Support
-----
sp      ORACLE SERVER X6-2     v3.2.4.0 r64525    07060223         N/A
```

2. To update the system firmware, choose the local or remote option:

- **Local** – To update the local system firmware, enter one of the following commands:

- For any system: `fwupdate update all -x metadata.xml`

- For x86 systems: `fwupdate update sp_bios -x metadata.xml`

- For SPARC systems: `fwupdate update sysfw -x metadata.xml`

where `metadata.xml` is the path to the metadata file. For scripting purposes, you can add the `-q` option to perform the update without user interaction.

Note - For x86 systems, you can add either the `--silent-reboot` or `--silent-no-reboot` option after the XML metadata file option to either automatically reboot or not automatically reboot the server after the firmware update.

For SPARC systems, these options can only be used if the system supports the Live Firmware Update feature and only if the metadata includes a power cycle. Check the release notes included with your SPARC firmware download package to see if this feature is supported.

■ **Remote – To update system firmware using a network connection, enter one of the following commands:**

- For any system: `fwupdate update all -x metadata.xml -H sp_ip -U username`
- For x86 systems: `fwupdate update sp_bios -x metadata.xml -H sp_ip -U username`
- For SPARC systems: `fwupdate update sysfw -x metadata.xml -H sp_ip -U username`

where `metadata.xml` is the path to the metadata file.

Note - For x86 systems, you can add either the `--silent-reboot` or `--silent-no-reboot` option after the XML metadata file option to either automatically reboot or not automatically reboot the server after the firmware update.

For SPARC systems, these options can only be used if the system supports the Live Firmware Update feature and only if the metadata includes a power cycle. Check the release notes included with your SPARC firmware download package to see if this feature is supported.

Note - If you are using a version Oracle Hardware Management Pack earlier than 2.3.3, you must manually restart the remote system after the update.

3. **Follow any prompts, as required, to complete the update process.**
 4. **If you opted not to automatically restart the server after the update, you must plan time to restart the server to utilize the new system firmware.**
-

Note - Unless otherwise specified in the firmware release notes, a reboot is required for an x86 system; a power cycle is required for a SPARC system.

5. **To confirm the new system firmware after the server has restarted, enter one of the following commands:**

For x86 systems: `fwupdate list sp_bios`

For SPARC systems: `fwupdate list sysfw`

See Also [“Updating Component Firmware With a Metadata File \(Automatic Mode\)”](#) on page 72

▼ Update Device Firmware Using Automatic Mode

Device firmware includes storage and network controllers, disks, SAS expanders and SAS-to-SATA bridge devices.

- Before You Begin**
- Download the firmware update from <https://support.oracle.com>.
The download should include a metadata file and firmware file for the target device.
 - Make sure that the firmware is compatible with the target device; read all documentation and release notes included with the firmware before proceeding.
 - Quiesce the device (stop all activity) before performing the update.

1. To display information about component firmware, do one of the following:

- **To list information about all components, type:**

```
fwupdate list all
```

- **To list information about a specific device (such as a disk), type:**

```
fwupdate list disk
```

Output related to the target is displayed. For example the output from this command is similar to:

```
=====
CONTROLLER
=====
ID      Type  Manufacturer  Model  Product Name  FW Version
BIOS Version  EFI Version  FCODE Version  Package Version  NVDATA Version
XML Support
-----
-----
c0      SAS   LSI Logic    0x0072  SGX-SAS6-INT-Z  11.05.03.00
07.21.09.00  07.22.05.00  01.00.62.00  -                10.03.00.28
N/A

DISKS
=====
ID      Manufacturer  Model  Chassis  Slot  Type  Media
Size(GiB) FW Version XML Support
-----
-----
c0d0    HITACHI      H109090SESUN900G  -      0     sas   HDD
```

838	A72A	N/A					
c0d1	HITACHI		H109060SESUN600G	-	1	sas	HDD
559	A72A	N/A					
c0d2	HITACHI		H109060SESUN600G	-	2	sas	HDD
559	A72A	N/A					
c0d3	HITACHI		H109030SESUN300G	-	3	sas	HDD
279	A72A	N/A					
c0d4	HITACHI		H109060SESUN600G	-	4	sas	HDD
559	A72A	N/A					
c0d5	HITACHI		H109060SESUN600G	-	5	sas	HDD
559	A72A	N/A					
c0d6	HITACHI		H109060SESUN600G	-	6	sas	HDD
559	A72A	N/A					
c0d7	HITACHI		H109060SESUN600G	-	7	sas	HDD
559	A72A	N/A					

2. To update the device firmware, choose one of the following options:

■ Update all devices supported in the metadata, type:

```
fwupdate update all -x metadata.xml
```

where *metadata.xml* is the path to the metadata file. This updates all components in the system whose device types are specified in the metadata file.

■ Update specific devices supported in the metadata, type:

```
fwupdate update disk -x metadata.xml
```

where *metadata.xml* is the path to the metadata file. This updates all disks in the system whose device types are specified in the metadata file.

■ Update a single device supported in the metadata, type:

```
fwupdate update disk -x metadata.xml -n c0d1
```

where *metadata.xml* is the path to the metadata file. This updates only disk *c0d1*, and only if its disk drive type is specified in the metadata file.

3. Follow any prompts, as required, to complete the update process.

4. To confirm the new firmware, enter one of the following commands:

■ To list information about all components, type:

```
fwupdate list all
```

■ To list information about a specific device, type:

fwupdate list disk

See Also [“Updating Component Firmware With a Metadata File \(Automatic Mode\)” on page 72](#)

Updating Component Firmware Without a Metadata File (Manual Mode)

`fwupdate update` manual mode updates a single device using a firmware file that is part of the platform firmware download package. This method can be used if your firmware download package does not include a metadata file. Only one component and its supported firmware file can be specified per execution of this command.

Note - You cannot update storage device firmware on the Flash Accelerator F40 PCIe Card directly. The Flash Accelerator F40 PCIe Card storage device firmware is updated when the general firmware package is applied to the PCIe card. An error is generated if you try to apply an update directly to the Flash Accelerator F40 PCIe Card storage devices.

The following command syntax is used for the update subcommand when using manual mode:

```
fwupdate update target options -n devicename -f filename
```

For manual mode, only one target device can be specified per `fwupdate` execution. Every target device that needs to be updated must be run as a separate `fwupdate` command.

Examples of command usage are listed below the supported target and options tables.

When used in manual mode, the update subcommand supports the following component type targets:

Target	Description
<code>expander-firmware</code>	Supported SAS expander.
<code>expander-manufacturing-image</code>	Supported SAS expander manufacturing image.
<code>disk-firmware</code>	Supported disk drive firmware.
<code>sas-bridge-firmware</code>	Supported SAS-to-SATA bridge device (used on some older systems).
<code>sas-controller-firmware</code>	Supported SAS controller firmware.
<code>sas-controller-bios</code>	Supported SAS controller BIOS code.
<code>sas-controller-efi</code>	Supported SAS controller EFI firmware.
<code>sas-controller-fcode</code>	Supported SAS controller fcode.
<code>ib-controller-firmware</code>	Supported InfiniBand adapter firmware.

Target	Description
fc-controller-firmware	Supported fibre channel adapter firmware.
nic-controller-firmware	Supported Ethernet network interface controller firmware. <i>This target was introduced in Hardware Management Pack 2.3.1.</i> Note - This target is used to update add-in PCIe network adapters or onboard (also called LOM or LAN-on-motherboard) controller firmware. Currently, this feature is not available for all Intel-based Ethernet controllers or all operating systems. Refer to the Support Matrix for details at: http://www.oracle.com/goto/ohmp .
nvme-controller-firmware	Supported NVMe device firmware. <i>This target was introduced in Hardware Management Pack 2.3.1.</i>
sp-bios-firmware	System firmware on x86 (BIOS) or SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM. Note - This target has been deprecated for SPARC and is replaced by the sysfw-firmware target.
sysfw-firmware	System firmware on SPARC (OBP, Hypervisor, NYX, POST, etc.), including Oracle ILOM. <i>This target was introduced in Hardware Management Pack 2.3.6.</i>

When used in manual mode, update subcommand supports the following options:

Short Option	Long Option	Descriptions
-n	--device_name	Name of the device to update. The name is the mapped name, which you can retrieve by using the <code>fwupdate list all</code> command. This option is mandatory for manual mode updates. For information about device names, see “CLI Tools Device-Naming Convention” on page 20.
-f	--filename= <i>filename</i>	A mandatory option, with a mandatory parameter, designating the name of the firmware image file that is to be applied.
-r	--reset	Reset the component after the update has finished.
-d	--dry-run	Optional. Checks all input, executes an available dry-run check command on the firmware and component, but makes no permanent changes.
-o	--output= <i>filename</i>	Log all actions in the specified file.
-q	--quiet	Uses silent, non-interactive mode. Suppresses user prompts and informational message output and only returns error codes during the update. Useful for scripting.

Usage examples:

- To update system firmware (including Oracle ILOM):
For a SPARC system, type: `fwupdate update sysfw-firmware -n devicename -f firmware-package-file.pkg`

For an x86 system, type: **fwupdate update sys-bios-firmware -n devicename -f firmware-package-file.pkg**

Where *devicename* is the device ID for the service processor (can be derived from the `fwupdate list all` command) and *firmware-package-file* is the name of the firmware file. This updates the platform system firmware, including Oracle ILOM. A host reboot (x86) or powercycle (SPARC) will need to be performed manually.

Note - For SPARC systems without the Live Firmware Update feature, the host power cycle (or power off) will be handled by Oracle ILOM.

- To update a specific disk using an image file, type:
fwupdate update disk-firmware -n c1d1 -f diskfirmware.fw
This updates only disk c1d1.

See also

- [“Update System Firmware Using Manual Mode” on page 82](#)
- [“Update Device Firmware Using Manual Mode” on page 85](#)

▼ Update System Firmware Using Manual Mode

System firmware is generally a bundled package that includes firmware for the Oracle ILOM service processor and either BIOS for x86 systems, or OBP, Hypervisor, NYX, POST etc. for SPARC systems. This method can be used if your firmware download package does not include a metadata file. Only one component and its supported firmware file can be specified per execution of this command when using manual mode.

- Before You Begin**
- To update system firmware using the fastest possible local option, ensure the Host-to-ILOM Interconnect is correctly configured to communicate with the target Oracle ILOM service processor ([“Configuring the Host-to-ILOM Interconnect” on page 109](#)). For systems that do not support updates over the Host-to-ILOM interconnect, the remote option utilizing a network connection to the service processor can be used.
 - Download the firmware update from <https://support.oracle.com>.
 - Make sure that the firmware is compatible with the target system, read all documentation and release notes included with the firmware before proceeding. For some systems, special update processes might be described in the release notes that supersede instructions listed here.

1. **To display information about system firmware, choose the local or remote option:**

- **Local** – To list information about the local system firmware, enter one of the following commands:

For x86 systems: `fwupdate list sp_bios`

For SPARC systems: `fwupdate list sysfw`

- **Remote** – To list information about system firmware using a network connection, enter one of the following commands:

For x86 systems: `fwupdate list sp_bios -H sp_ip -U username`

For SPARC systems: `fwupdate list sysfw -H sp_ip -U username`

where `sp_ip` is the IP address of the service processor and `username` is the user name with Admin (a) role account privileges for logging in to the Oracle ILOM service processor.

Enter the Oracle ILOM password when prompted.

Output related to the target is displayed. For example the output from this command is similar to:

```
=====
SP + BIOS
=====
ID      Product Name          ILOM Version    BIOS/OBP Version XML Support
-----
sp      ORACLE SERVER X6-2     v3.2.4.0 r64525  07060223         N/A
```

2. To update the system firmware, choose the local or remote option:

- **Local** – To update the local system firmware, enter one of the following commands:

- For x86 systems: `fwupdate update sys-bios-firmware -n devicename -f firmware-package-file.pkg`

- For SPARC systems: `fwupdate update sysfw-firmware -n devicename -f firmware-package-file.pkg`

Where `devicename` is the device ID for the service processor (derived in step 1) and `firmware-package-file` is the name of the firmware file. For scripting purposes, you can add the `-q` option to perform the update without user interaction.

This updates the platform system firmware, including Oracle ILOM. A host reboot (x86) or powercycle (SPARC) will need to be performed manually.

Note - For SPARC systems without the Live Firmware Update feature, the host power cycle (or power off) will be handled by Oracle ILOM.

■ **Remote – To update system firmware using a network connection, enter one of the following commands:**

- For x86 systems: `fwupdate update sys-bios-firmware -n devicename -f firmware-package-file.pkg -H sp_ip -U username`
- For SPARC systems: `fwupdate update sysfw-firmware -n devicename -f firmware-package-file.pkg -H sp_ip -U username`

Where *devicename* is the device ID for the service processor (derived in step 1) and *firmware-package-file* is the name of the firmware file. This updates the platform system firmware, including Oracle ILOM. A host reboot (x86) or powercycle (SPARC) will need to be performed manually.

Note - For SPARC systems without the Live Firmware Update feature, the host power cycle (or power off) will be handled by Oracle ILOM.

Note - If you are using a version Oracle Hardware Management Pack earlier than 2.3.3, you must manually restart the remote system after the update.

3. **Follow any prompts, as required, to complete the update process.**
4. **Unless Oracle ILOM has performed a host power cycle (or power off) during the update process, restart the server to utilize the new system firmware after the update.**

Note - Unless otherwise specified in the firmware release notes, a reboot is required for an x86 system; a power cycle is required for a SPARC system with the Live Firmware Update feature.

5. **To confirm the new system firmware after the server has restarted, enter one of the following commands:**

For x86 systems: `fwupdate list sp_bios`

For SPARC systems: `fwupdate list sysfw`

See Also [“Updating Component Firmware Without a Metadata File \(Manual Mode\)” on page 80](#)

▼ Update Device Firmware Using Manual Mode

Device firmware includes storage and network controllers, disks, SAS expanders and SAS-to-SATA bridge devices.

- Before You Begin**
- Download the firmware update from <https://support.oracle.com>.
 - Make sure that the firmware is compatible with the target device; read all documentation and release notes included with the firmware before proceeding.
 - Quiesce the device (stop all activity) before performing the update.

1. To display information about component firmware, do one of the following:

- **To list information about all components, type:**

```
fwupdate list all
```

- **To list information about a specific device (such as a disk), type:**

```
fwupdate list disk
```

Output related to the target is displayed. For example the output from this command is similar to:

```
=====
CONTROLLER
=====
ID      Type  Manufacturer  Model      Product Name      FW Version
BIOS Version  EFI Version  FCODE Version  Package Version  NVDATA Version
XML Support
-----
-----
c0d0    SAS   LSI Logic     0x0072     SGX-SAS6-INT-Z    11.05.03.00
07.21.09.00  07.22.05.00  01.00.62.00   -                10.03.00.28
N/A

DISKS
=====
ID      Manufacturer  Model      Chassis  Slot  Type  Media
Size(GiB)  FW Version  XML Support
-----
-----
c0d0    HITACHI      H109090SESUN900G  -        0     sas   HDD
838     A72A        N/A
c0d1    HITACHI      H109060SESUN600G  -        1     sas   HDD
559     A72A        N/A
c0d2    HITACHI      H109060SESUN600G  -        2     sas   HDD
```

559	A72A	N/A					
c0d3	HITACHI	H109030SESUN300G	-	3	sas	HDD	
279	A72A	N/A					
c0d4	HITACHI	H109060SESUN600G	-	4	sas	HDD	
559	A72A	N/A					
c0d5	HITACHI	H109060SESUN600G	-	5	sas	HDD	
559	A72A	N/A					
c0d6	HITACHI	H109060SESUN600G	-	6	sas	HDD	
559	A72A	N/A					
c0d7	HITACHI	H109060SESUN600G	-	7	sas	HDD	
559	A72A	N/A					

2. To update the device firmware, type:

```
fwupdate update disk-firmware -n c0d1 -f diskfirmware.fw
```

Where *diskfirmware.fw* is the path to the firmware file. This updates only disk *c0d1*.

Note - If required, and the device supports a reset, add the *-r* option to reset the device after the update. Refer to the release notes for the firmware for details.

3. Follow any prompts, as required, to complete the update process.

4. Reset the device, if required, after the update.

Refer to the release notes that came with the firmware to see if a reset is necessary.

5. To confirm the new firmware, enter one of the following commands:

- **To list information about all components, type:**

```
fwupdate list all
```

- **To list information about a specific component, type:**

```
fwupdate list disk
```

- See Also
- [“Updating Component Firmware Without a Metadata File \(Manual Mode\)” on page 80](#)
 - [“Reset a Device After a Firmware Update” on page 86](#)

▼ Reset a Device After a Firmware Update

After firmware for a device has been updated, the device might need to be reset. This requirement is different with each device; the reset functionality might be part of the update

procedure or a separate function. To determine if your device requires a reset after a firmware update, consult the release notes included with your firmware.

- **To reset a device, type:**

```
fwupdate reset target -n devicename
```

The reset subcommand supports the following targets:

Target	Description
expander	Supported SAS expanders.
controller	Supported controllers, such as storage and networking.
sp_bios	The Oracle ILOM service processor on an x86 system. Note - This target has been deprecated for SPARC and is replaced by the sysfw target.
sysfw	The Oracle ILOM service processor on a SPARC system.

Options for the reset subcommand are listed in the following table.

Short Option	Long Option	Description
-n	--device_name	Required option followed by a mandatory parameter which designates a single device. Where the device name is the common-mapped device name shown when using the <code>fwupdate list all</code> command. For information about device names, see “CLI Tools Device-Naming Convention” on page 20 .

Usage examples:

- To reset the Oracle ILOM service processor:

For a SPARC system, type: `fwupdate reset sysfw -n devicename`

For an x86 system, type: `fwupdate reset sp_bios -n devicename`

Where *devicename* is the device ID of the service processor as derived from the `fwupdate list all` command. This command only resets the service processor. It does not reset the host.

- To reset a specific controller, type:

```
fwupdate reset controller -n c2
```

This command resets the controller identified as c2 when using the `fwupdate list all` command.

Execution Summary

After the `fwupdate` tool is used to update firmware, an execution summary provides information on whether or not the update was successful. This information is also written to the log file.

The following examples show the possible execution summary messages:

- Message printed after a successful dry-run/check function:
Check firmware successful for device: *device_name*
- The update was successful, but no firmware version information is available for this component:
Upgrade of firmware for *device_name* succeeded. Version information was not available.
Consult your product release notes for information on how to verify the update.
- Update was successful:
Upgrade of *device_name* from *old_fw* to *new_fw* succeeded.
- The version number of the software did not change after a successful update:
Upgrade of *device_name* from *old_fw* succeeded, but is not yet active.
This might mean that the server needs to be reset, or that other instructions need to be followed. Consult your product release notes for instructions on how to update the version number.
- Update failed:
Upgrade of *device_name* failed: *error_message*

The variables in the previous output represent the following:

- *device_name* is the logical name of the device that is being updated.
- *old_fw* is the old firmware version.
- *new_fw* is the new firmware version.
- *error_message* is the error message that explains why the firmware update did not succeed.

Using `hwmgmtcli` to Display Hardware Information

`hwmgmtcli` displays hardware configuration information and the status of your Oracle servers.

Note - There are some limitations to using `hwmgmtcli` tool for SPARC M5-32 and M6-32 servers. Refer to the *Release Notes* for more information.

The following table shows that information covered in this section.

Description	Links
Learn about the <code>hwmgmtcli</code> command.	“hwmgmtcli Command Syntax” on page 89
Display subsystem information.	“List Subsystem Information” on page 91
Display open problems with the system.	“View Open Problems” on page 91
Export subsystem information.	“Export Subsystem Information” on page 92

`hwmgmtcli` Command Syntax

The `hwmgmtcli` commands use the following command syntax:

`hwmgmtcli subcommand subsystem [option]`

The options listed in the following table apply to all CLI Tools commands, including `hwmgmtcli`.

Short Option	Long Option	Description
-?	--help	Help—Displays help information.
-V	--version	Version—Displays the tool version.

If you use the `--help` or `--version` options, the `hwmgmtcli` command does not require subcommands, otherwise one or more subcommands are mandatory.

`hwmgmtcli` supports the subcommands shown in the following table.

Subcommand	Function
<code>list subsystem</code>	Show details of one or all subsystems.
<code>export all</code>	Export details of all subsystems to an XML file.

You can choose to show all available information or you can choose a subsystem. The available subsystems are listed in the following table.

Subsystem	Description
<code>all</code>	Show all subsystems available. For the <code>export</code> subcommand, this is the only supported subsystem.
<code>server</code>	Show details of server subsystem.
<code>cooling</code>	Show details of cooling subsystem.
<code>processor</code>	Show details of processor subsystem.
<code>memory</code>	Show details of memory subsystem.
<code>power</code>	Show details of power subsystem.
<code>storage</code>	Show details of storage subsystem.
<code>network</code>	Show details of network subsystem.
<code>firmware</code>	Show details of firmware subsystem.
<code>device</code>	Show details of the device subsystem.
<code>bios</code>	Show details of BIOS subsystem.
<code>iomodule</code>	Show details of IO module subsystem.
<code>open_problems</code>	Show all SP diagnosed open problems (ILOM 3.1 or newer).
<code>dcu</code>	Show details of dcu subsystem (only available on multi-domained systems).

The `list subsystem` subcommand supports the option listed in the following table.

Short Option	Long Option	Description
<code>-d</code>	<code>--details</code>	Show all of the properties and components for the subsystem in detail.

The option listed in the following table is supported for the `export all` subcommand.

Short Option	Long Option	Description
-f	--filename	Export the subsystem information to <i>filename.xml</i> .

▼ List Subsystem Information

The `list` subcommand displays the current hardware configuration and status information of a server and its subsystems.

- **To list subsystem information, type:**

```
hwmgmtcli list subsystem
```

where *subsystem* is one of the subsystems listed in “[hwmgmtcli Command Syntax](#)” on page 89.

The current subsystem information is listed.

▼ View Open Problems

The `open_problems` subsystem displays information about logged system events.

- **To view open server problems, type:**

```
hwmgmtcli list open_problems
```

The following display shows sample output from this command:

```
=== open_problems report ===
Open Problem 1
Problem time       : Thu Feb 14 22:38:19 2013
Problem subsystem  : System
Problem location   : /SYS (Host System)
Problem description : The top cover of server was opened while AC
input was still applied to the power supplies. (Probability: 100, UUID:
8bb87e70-d210-632b-d553-fc1450105bc4, Part Number: 31112054+1+1, Serial
Number: 1242FML0UV, Reference Document: http://support.oracle.com/msg/SPX86-8003-8C).
Open Problem 2
Problem time       : Fri Feb 15 10:37:48 2013
Problem subsystem  : Storage
Problem location   : /SYS/DBP0/HDD2
Problem description : The disk temperature has exceeded the critical
limit. (Probability: 100, UUID: N/A, Part Number: H106030SDSUN300G, Serial
Number: 001234NTR1KD          PWGTR1KD, Reference Document: N/A)
```

▼ Export Subsystem Information

The following procedure describes how to use the `export all` subcommand to save the current hardware configuration and status information of a server and its subsystems to a file.

Note - The only subsystem available for the `export` subcommand is `all`.

- **To export subsystem information, type:**

```
hwmgmtcli export all --filename filename.xml
```

where *filename* is the file to which you want to export the current system or subsystem information.

The current information is exported to the specified *filename.xml* file.

Using `ilomconfig` to Configure Oracle ILOM

`ilomconfig` allows you to configure Oracle ILOM service processors from the host OS without having to connect to the management network. You can target `ilomconfig` changes to either the local or a remote Oracle ILOM service processor.

`ilomconfig` also functions as an *XML builder* by either exporting the configuration of an Oracle ILOM service processor to an existing XML file, or creating a new XML file. These XML files can then be used for subsequent restore operations on compatible Oracle ILOM service processors.

You can also use `ilomconfig` to configure a Host-to-ILOM Interconnect on platforms that support this configuration. For more information on Host-to-ILOM Interconnect, see [“Host-to-ILOM Interconnect” on page 17](#).

Note - There are some limitations to using `ilomconfig` tool for SPARC M5-32 and M6-32 servers. Refer to the *Release Notes* for more information.

The following table shows the information covered in this section.

Description	Links
Learn about the <code>ilomconfig</code> command	“<code>ilomconfig</code> Command Overview” on page 94
Import or Export XML configurations	“Importing and Exporting XML Configurations” on page 97
View system and SP information	“Listing System and SP Information” on page 101
Modify Oracle ILOM configurations	“Modifying Oracle ILOM Configurations” on page 104
Configure the Host-to-ILOM Interconnect	“Configuring the Host-to-ILOM Interconnect” on page 109
Manage the HMP Watchdog Agent	“Managing ILOM and Host Watchdog” on page 113

ilomconfig Command Overview

This section covers the following information:

- [“ilomconfig Features” on page 94](#)
- [“Restoring and Modifying Oracle ILOM XML Configuration Files” on page 94](#)
- [“ilomconfig Command Syntax” on page 95](#)

ilomconfig Features

The `ilomconfig` commands can be directed at a local or remote Oracle ILOM service processor, or an XML configuration file. This file can then be used as a golden image to make changes to multiple Oracle ILOM service processors. You can either export the configuration of an Oracle ILOM service processor or create a new XML configuration file.

`ilomconfig` provides the following functions:

- Back up and restore from an Oracle ILOM XML file
- Modify the XML file using sub-commands
- Configure the network connection, including DHCP and sideband
- List and configure identification information, including hostname, contact, location, and description
- List and configure DNS
- List and configure clock including time zone
- List and configure user management
- List and configure SNMP community

Restoring and Modifying Oracle ILOM XML Configuration Files

Starting with Hardware Management Pack 2.1, `ilomconfig` can generate a backup of an Oracle ILOM service processor's configuration to an XML file with the `export config` command. The `create` or `modify` subcommands can be used to create or modify XML files.

By default, `ilomconfig` commands are executed on the local Oracle ILOM service processor. When you use the `--xmlfile=config.xml` option, the `ilomconfig` commands operate on the specified XML file.

The `ilomconfig` subcommands can modify already existing settings in the XML file or create new settings.

Note - Ensure that when you create a new setting in an XML file, your target Oracle ILOM service processor supports the setting.

Oracle ILOM settings can be restored from an XML file starting with Oracle ILOM 3.0.12. Oracle ILOM settings that can be restored include:

- SSH private keys
- User SSH keys
- SSL cert
- COD license
- LDAP and AD certificates
- Platform binary data (currently limited to SPARC LDOMS config)
- User passwords
- SNMP users
- LDAP/LDAPSSL/RADIUS passwords
- Servicetag passphrase

ilomconfig Command Syntax

The `ilomconfig` commands must be run in administrator mode.

`ilomconfig subcommand type [option]`

When a command fails, it returns one of several failure codes listed in [“ilomconfig Error Codes” on page 183](#).

Options

The following table lists the options available to all CLI Tools commands, including `ilomconfig`.

Short Option	Long Option	Description
-?	--help	Displays help information.
-V	--version	Displays the tool version.

Short Option	Long Option	Description
-q	--quiet	Suppresses informational message output and returns only error codes.
-y	--yes	Confirms operation. Does not prompt user for confirmation on the operation when running.

When accessing a service processor, `ilomconfig` can be used over a local Host-to-ILOM interconnect or a remote Ethernet network connection. When issuing an `ilomconfig` command that accesses the service processor, credentials are not required when using the Host-to-ILOM interconnect, but they are required for a remote Ethernet network connection.

Note - For systems with an Oracle ILOM version earlier than 3.2.4, to use a LAN interface (either the local Host-to-ILOM interconnect or remote Ethernet network connection) you must manually include credentials using the `-H` and `-U` options for commands that access a service processor. If credentials are not provided the commands will default to the slower local KCS interface to access the local service processor.

The options listed in the following table are supported for `ilomconfig` over a network connection.

Short Option	Long Options	Description
-H	--remote-hostname	This option is followed by the host name or IP address of the remote service processor.
-U	--remote-username	This option is followed by the user name with root access used to log in to the remote service processor.

Use these options to make changes to a service processor using a remote network connection, rather than a local Host-to-ILOM connection. When using these options to access a service processor, you must use both options together. For example:

```
ilomconfig list system-summary --remote-hostname=sp_ip --remote-username=username
```

where *sp_ip* is the host name or IP address (in `xx.xx.xx.xx` format) of the target system's SP, and *username* is the user name with login access rights to perform the operation.

Note - The `enable/disable interconnect` and `create/delete credential` subcommands can not be used on remote service processors.

You are then prompted for the Oracle ILOM user password.

Note - The password required by the remote user name can be piped in on stdin for scripting use.

The option listed in the following table applies to using `ilomconfig` with a local Oracle ILOM XML configuration file.

Option	Description
<code>--xmlfile</code>	This option is followed by the path to the file you want to modify.

Note - If the `--xmlfile` option is specified, the changes are only made to the XML file. If the XML file option is omitted, the changes are made directly to the Oracle ILOM. The XML file cannot be manually edited by a user, it can only be changed by using `ilomconfig`.

Subcommands

The available `ilomconfig` subcommands are listed in the following table.

Subcommand	Description
<code>list</code>	Show Oracle ILOM settings, users, SNMP communities, and system summary.
<code>create</code>	Create users and SNMP communities.
<code>delete</code>	Delete users and SNMP communities.
<code>modify</code>	Modify Oracle ILOM settings.
<code>import</code>	Restore Oracle ILOM settings from an XML file.
<code>export</code>	Backup Oracle ILOM settings to an XML file.
<code>reset</code>	Reset Oracle ILOM to factory defaults.
<code>enable</code>	Enable Host-to-ILOM interconnect.
<code>disable</code>	Disable Host-to-ILOM interconnect.

Importing and Exporting XML Configurations

This section covers the following information:

- [“Export an XML Configuration” on page 98](#)
- [“Import an XML Configuration” on page 99](#)

▼ Export an XML Configuration

To export an entire configuration to an XML file, use the `ilomconfig export config` command.

Note - Exit or close all active ILOM login sessions before proceeding. The `ilomconfig export file` command enables exports of the current Oracle ILOM configuration. Before an export operation can be executed, all active open sessions must be closed. There must be no active ILOM sessions logged in to `/SP/console` during the export operation.

- **Do one of the following:**

- **To export an XML configuration using a passphrase, choose one of the following commands:**

- **To get a prompt asking whether you want to enter a passphrase:**

```
ilomconfig export config --xmlfile=filename.xml
```

where *filename.xml* represents the file to which you are exporting the ILOM configuration.

For example:

```
# ilomconfig export config --xmlfile=config.xml
Do you want to enter a passphrase to back up sensitive data? [y/n]? y
Enter passphrase: *****
Wrote backup of ILOM configuration to 'config.xml'.
```

- **To set up a passphrase to be used with an automated script, provide a passphrase or a file containing the passphrase as follows:**

```
echo passphrase | ilomconfig export config --xmlfile=filename.xml
```

where *passphrase* is the passphrase that you want to use.

or

```
cat file_with_passphrase | ilomconfig export config --xmlfile=filename.xml
```

where *file_with_passphrase* is the file containing the passphrase.

For example:

```
# echo passphrase | ilomconfig export config --xmlfile=config.xml
Enter passphrase: *****
Wrote backup of ILOM configuration to 'config.xml'.
```

The passphrase is automatically passed through the command line.

- **To export an XML configuration without using a passphrase:**

```
ilomconfig export config --xmlfile=filename.xml -y
```

where *filename.xml* represents the file to which you are exporting the ILOM configuration.

For example:

```
# ilomconfig export config --xmlfile=config.xml -y
Wrote backup of ILOM configuration to 'config.xml'.
```

This option exports the ILOM configuration without using a passphrase.

▼ Import an XML Configuration

To import an XML configuration file to configure Oracle ILOM, use the `ilomconfig import config` command. You can also use this command to restore the system configuration by importing a known reliable XML file.

Note - Exit or close all active ILOM login sessions before proceeding. The `ilomconfig import file` command imports the current Oracle ILOM configuration. Before an import operation can be executed, all active open sessions must be closed. There must be no active ILOM sessions logged in to `/SP/console` during the import operation.

- **Do one of the following:**

- **To import an XML configuration using a passphrase, choose one of the following commands.**

- **To get a prompt asking whether you want to enter a passphrase, type:**

```
ilomconfig import config --xmlfile=filename.xml
```

where *filename.xml* represents the file from which you are importing the ILOM configuration.

For example:

```
# ilomconfig import config --xmlfile=config.xml
Are you sure you want to import the settings from the XML file to ILOM? [y/n]? y
```

```

Do you want to enter a passphrase to restore sensitive data? [y/n]? y
Enter passphrase: *****
Preparing to restore XML file to ILOM...
Done preparing to restore XML file ILOM.
Restoring configuration (allow several minutes).....
.....Done.

```

- **To set up a passphrase to be used with an automated script, provide a passphrase or a file containing the passphrase as follows:**

```
echo passphrase | ilomconfig import config --xmlfile=filename.xml
```

where *passphrase* is passphrase that you want to use.

or

```
cat file_with_passphrase | ilomconfig import config --xmlfile=filename.xml
```

where *file_with_passphrase* is the file containing the passphrase.

For example:

```

# echo passphrase | ilomconfig import config --xmlfile=config.xml
Enter passphrase: *****
Preparing to restore XML file to ILOM...
Done preparing to restore XML file ILOM.
Restoring configuration (allow several minutes).....
.....Done.

```

The passphrase is automatically passed in through the command line.

- **To import an XML configuration without using a passphrase, type:**

```
ilomconfig import config --xmlfile=filename.xml -y
```

where *filename.xml* represents the file from which you are importing the ILOM configuration.

For example:

```

# ilomconfig import config --xmlfile=config.xml -y
Preparing to restore XML file to ILOM...
Done preparing to restore XML file ILOM.
Restoring configuration (allow several minutes).....
.....Done.

```

This option imports the ILOM configuration without using a passphrase.

Listing System and SP Information

This section covers the following information:

- “List System Summary Information” on page 101
- “List Users” on page 102
- “List an SNMP Community” on page 102
- “List IPv4 Network Settings” on page 102
- “List IPv6 Network Settings” on page 103
- “List Service Processor Identification Information” on page 103
- “List DNS Information” on page 103
- “List Clock Information” on page 104

▼ List System Summary Information

Use the `ilomconfig list` sub command to list system summary information including the product name, part number, serial number, Oracle ILOM host name, and Oracle ILOM version information. Use the `ilomconfig list system-summary` command to lists the same information as the Summary tab in the Oracle ILOM web interface.

- **Choose one of these procedures depending on where the system summary details are:**
 - **To view the system summary of the local Oracle ILOM service processor, type:**
- **To view the system summary information from a remote Oracle ILOM service processor, type:**

```
ilomconfig list system-summary
```

```
ilomconfig list system-summary --remote-hostname=sp_ip --remote-username=username
```

where *sp_ip* is the IP address of the remote server's service processor and *username* the valid user account with privileges to view system summary information.

For example:

```
ilomconfig list system-summary --remote-hostname=192.0.2.10 --remote-username=root
```

Oracle ILOM prompts for the root account password.

▼ List Users

To list one or all users, use the `ilomconfig list user username` command. If *username* is specified then only that user is listed. If *username* is blank, then all users are listed.

When you specify an XML file name, the command is run on information available in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list users, type:**

```
ilomconfig list user [username] [--xmlfile=filename.xml]
```

where *username* is the user to list and *filename.xml* is the name of the service processor configuration XML file.

▼ List an SNMP Community

To list one or all SNMP communities, use the `ilomconfig snmp-community` command. When you specify an XML file name, the command lists SNMP communities defined in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list SNMP communities, type:**

```
ilomconfig list snmp-community [communityname] [--xmlfile=filename.xml]
```

where *communityname* is the name of the SNMP community you are interested in and *filename.xml* is the name of the service processor configuration XML file.

▼ List IPv4 Network Settings

To list IPv4 network settings, use the `ilomconfig list network` command. This command lists IP address, netmask, gateway, DHCP settings, sideband, and MAC. When you specify an XML file name, this command lists IPv4 network settings defined in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list IPv4 network settings, type:**

```
ilomconfig list network [--xmlfile=filename.xml]
```

▼ List IPv6 Network Settings

To list IPv6 network settings, use the `ilomconfig list network-ipv6` command. This command lists IP address, gateway, autoconfig, link local IP address, dynamic IP address and interface state. When you specify an XML file name, this command lists IPv6 network settings defined in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list IPv6 network settings, type:**

```
ilomconfig list network-ipv6 [--xmlfile=filename.xml]
```

▼ List Service Processor Identification Information

To list identification information for the service processor, use the `ilomconfig list identification` command. This command lists service processor host name, system contact, system location, and system description, which is equivalent to the Identification tab on web interface. When you specify an XML file name, the command lists identification information defined in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list service processor identification information, type:**

```
ilomconfig list identification [--xmlfile=filename.xml]
```

▼ List DNS Information

To list DNS information, use the `ilomconfig list dns` command. If you specify an XML file name, the command lists DNS information defined in the exported service processor configuration XML file rather than querying Oracle ILOM itself.

- **To list DNS information, type:**

```
ilomconfig list dns [--xmlfile=filename.xml]
```

▼ List Clock Information

To list clock information, use the `ilomconfig list clock` command. When you specify an XML file name, the command lists clock information defined in the exported service processor configuration XML file rather than querying Oracle ILOM.

- **To list clock information, type:**

```
ilomconfig list clock [--xmlfile=filename.xml]
```

Modifying Oracle ILOM Configurations

This section covers the following information:

- [“Restore Oracle ILOM to Defaults” on page 104](#)
- [“Create a User” on page 105](#)
- [“Delete a User” on page 105](#)
- [“Modify a User Password or Role” on page 105](#)
- [“Create an SNMP Community” on page 106](#)
- [“Modify IPv4 Network Settings” on page 106](#)
- [“Modify IPv6 Network Settings” on page 107](#)
- [“Modify Identification Information” on page 108](#)
- [“Modify DNS Information” on page 108](#)
- [“Modify Clock Information” on page 109](#)

▼ Restore Oracle ILOM to Defaults

To restore the Oracle ILOM configuration to the factory defaults, use the `ilomconfig reset config` command. Use the `-y` option to bypass the yes or no confirmation prompt. This results in the reboot of the Oracle ILOM.

- **To restore Oracle ILOM to defaults, type:**

```
ilomconfig reset config [-y]
```

▼ Create a User

To create a user, use the `ilomconfig create user` command. The `-y` option prevents the yes/no confirmation prompt. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

1. **To create a user, type:**

```
ilomconfig create user username [-y][--role=role] [--xmlfile=filename.xml]
```

where *username* is the user to modify, `-role` is the role of the Oracle ILOM user and *filename.xml* is the name of the exported service processor configuration XML file to modify.

2. **At the prompt, enter the password for the user.**

▼ Delete a User

To delete a user, use the `ilomconfig delete user` command. The `-y` option prevents the yes or no confirmation prompt. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To delete a user, type:**

```
ilomconfig delete user username [-y] [--xmlfile=filename.xml]
```

where *username* is the user to delete and *filename.xml* is the name of the exported service processor configuration XML file to modify.

▼ Modify a User Password or Role

To modify a user password or role, use the `ilomconfig modify user` command. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To modify a user password or role, type:**

```
ilomconfig modify user username [-p] [--role=role] [--xmlfile=filename.xml]
```

where *username* is the user to modify, -p prompts for the user's password, -role is the role of the Oracle ILOM user and *filename.xml* is the name of the exported service processor configuration XML file to modify.

▼ Create an SNMP Community

To create an SNMP community, use the `ilomconfig create snmp-community` command. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To create an SNMP community, type:**

```
ilomconfig create snmp-community communityname [--permission=ro|rw] [--xmlfile=filename.xml]
```

where *communityname* is the SNMP community you are creating, --permission is either read-only or read-write (*ro|rw*), and *filename.xml* is the name of the exported service processor configuration XML file to modify.

▼ Modify IPv4 Network Settings

To modify IPv4 settings, use the `ilomconfig modify network` command. This command modifies IP address, netmask, gateway, DHCP settings, and sideband. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To modify IPv4 network settings, type:**

```
ilomconfig modify network [--ipdiscovery=static|dhcp] [--ipaddress=ipaddress] [--netmask=netmask] [--gateway=gateway] [--state=enabled|disabled] [--mgmtport=port] [--xmlfile=filename.xml]
```

Option	Description	Example
--ipdiscovery	Network discovery mechanism. Can be either static or DHCP.	static or dhcp

Option	Description	Example
--ipaddress	Oracle ILOM IP address	192.0.2.10
--netmask	Netmask address	255.255.255.0
--gateway	Gateway address	192.0.2.248
--state	Oracle ILOM management port state	enabled or disabled
--mgmtport	Oracle ILOM management port path	/SYS/SP/NET0 or SYS/MB/SP/NETMGMT
--xmlfile	Modify specified XML file rather than local Oracle ILOM service processor. Must be followed by = and the pathname to the file.	file.xml

▼ Modify IPv6 Network Settings

To modify IPv6 settings, use the `ilomconfig modify network-ipv6` command. This command lists IP address, netmask, gateway, DHCP settings, and sideband. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

● To modify IPv6 network settings, type:

```
ilomconfig modify network-ipv6 [--static-ipaddress=IPv6_address] [--autoconfig=disabled|stateless|dhcpv6_stateful|dhcpv6_stateless] [--state=enabled|disabled] [--xmlfile=filename.xml]
```

Option	Description	Example
--static-ipaddress	Oracle ILOM IPv6 static address.	2001:0db0:0000:82a1:0000:0000:1234:abcd
--autoconfig	Oracle ILOM IPv6 autoconfiguration state.	When using Oracle ILOM 3.0.12.x: disabled, stateless_only When using Oracle ILOM 3.0.14.x: disabled, stateless, dhcpv6_stateful, dhcpv6_stateless
--state	Oracle ILOM IPv6 administrative state.	enabled or disabled
--xmlfile	Modify specified XML file rather than local Oracle ILOM service processor. Must be followed by = and the pathname to the file.	file.txt

▼ Modify Identification Information

To modify identification information, use the `ilomconfig modify identification` command. This command modifies the host name, system contact, system location, and system description. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To modify identification information, type:**

```
ilomconfig modify identification [--hostname=hostname] [--system-contact=system_contact]
-[-system-location=system_location] [--system-identifier=system_identifier] [--
xmlfile=filename.xml]
```

Option	Description	Example
--hostname	Oracle ILOM host name.	service-processor. domain.com
--system-contact	Oracle ILOM system contact field.	user
--system-location	Oracle ILOM system location field.	west
--system-identifier	Oracle ILOM system identifier field.	x4800
--xmlfile	Modify specified XML file rather than local Oracle ILOM service processor. Must be followed by = and the pathname to the file.	file.xml

▼ Modify DNS Information

To modify DNS information, use the `ilomconfig modify dns` command. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To modify DNS information, type:**

```
ilomconfig modify dns [--nameservers=nameserverlist] [--autodns=enabled|disabled] [--
retries=retries] [--searchpath=searchpathlist] [--timeout=timeout] [--xmlfile=filename.xml]
```

Option	Description	Example
--nameservers	List of DNS nameserver IP addresses for Oracle ILOM separated by commas.	10.168.1.10

Option	Description	Example
--auto-dns	Oracle ILOM Auto-DNS state.	enabled or disabled
--searchpath	List of search suffixes in preferred order and separated by commas.	
--retries	Number of retry attempts for DNS.	Integer between 0 and 5.
--timeout	Number of seconds to wait for a DNS response. This can be used with up to six search suffixes, each separated by a comma.	2
--xmlfile	Modify specified XML file rather than local Oracle ILOM service processor. Must be followed by = and the pathname to the file.	file.xml

▼ Modify Clock Information

To modify clock information, use the `ilomconfig modify clock` command. When you specify an XML file name, the command modifies information defined in the exported service processor configuration XML file rather than modifying Oracle ILOM.

- **To modify clock information, type:**

```
ilomconfig modify clock [--datetime=datetime] [--timezone=timezone] [--usentp=enabled|disabled [-ntp-server1=ntpserver1] [--ntp-server2=ntpserver2] [--xmlfile=filename.xml]
```

Option	Description	Example
--datetime	Oracle ILOM date in <i>MMDDhhmmYYYY</i> format or <i>MMDDhhmmYYYY.ss</i> format.	032514272010
--timezone	Oracle ILOM clock time zone, such as GMT.	enabled or disabled
--usentp	Oracle ILOM NTP client state.	enabled or disabled
--ntp-server1	Oracle ILOM NTP server 1 IP address.	<i>aaa.bbb.ccc.ddd</i>
--ntp-server2	Oracle ILOM NTP server 2 IP address.	<i>aaa.bbb.ccc.ddd</i>
--xmlfile	Modify specified XML file rather than local Oracle ILOM service processor. Must be followed by = and the pathname to the file.	file.xml

Configuring the Host-to-ILOM Interconnect

The Host-to-ILOM Interconnect enables you to communicate locally with Oracle ILOM from the host operating system (OS) without the use of a network management connection (NET MGT) to the server. For more information, see [“Host-to-ILOM Interconnect” on page 17](#).

This section covers the following information:

- [“Providing Host Credentials to the Service Processor” on page 110](#)
- [“Enable the Host-to-ILOM Interconnect” on page 110](#)
- [“Disable the Host-to-ILOM Interconnect” on page 111](#)
- [“Modify the Host-to-ILOM Interconnect” on page 111](#)
- [“List the Host-to-ILOM Interconnect Settings” on page 112](#)
- [“Verify the Host-to-ILOM Interconnect Settings” on page 112](#)
- [“Set Up a Credential Cache on the Host” on page 112](#)
- [“Delete a Credential Cache on the Host” on page 113](#)

Providing Host Credentials to the Service Processor

Accessing a service processor over a remote network connection requires that you either provide credentials manually or set up a host credentials cache using `ilomconfig`.

Note - As of Oracle Hardware Management Pack 2.3.3, you can no longer create a local host credential cache for `ilomconfig`. Refer to the *Release Notes* for more information.

- For information on setting credentials using `ilomconfig`, see [“Set Up a Credential Cache on the Host” on page 112](#).
- To provide credentials manually, provide the Oracle ILOM login credentials when running a command over a network. For example:

```
# fwupdate update sp_bios -x metadata.xml --remote-username=root --remote-  
hostname=169.254.182.76  
  
# ubiosconfig list status -U root -H 169.254.182.76
```

▼ Enable the Host-to-ILOM Interconnect

Note - It is recommended that you use this command without any options and let the command choose the settings. You can override the defaults with different IP and netmask addresses, but this is for advanced users only.

- **To enable the Host-to-ILOM Interconnect, type:**

```
ilomconfig enable interconnect [--ipaddress=ipaddress] [--netmask=netmask] [--hostipaddress=hostipaddress]
```

Option	Description	Example
--ipaddress	Oracle ILOM IP address. This address must be in the format: 169.254.x.x	169.254.175.72
--netmask	Oracle ILOM netmask.	255.255.255.0
--hostipaddress	Host IP address. This address must be in the format: 169.254.x.x	169.254.175.73

▼ Disable the Host-to-ILOM Interconnect

To disable the Host-to-ILOM Interconnect, use the `ilomconfig disable interconnect` command.

- To disable the Host-to-ILOM interconnect, type:

```
ilomconfig disable interconnect
```

▼ Modify the Host-to-ILOM Interconnect

To modify the Host-to-ILOM Interconnect between the host and Oracle ILOM, use the `ilomconfig modify interconnect` command. This works only when the interconnect is enabled. At least one option must be specified.

- To modify the Host-to-ILOM Interconnect, type:

```
ilomconfig modify interconnect [--ipaddress=ipaddress] [--netmask=netmask] [--hostipaddress=hostipaddress]
```

Option	Description	Example
--ipaddress	Oracle ILOM IP address. This address must be in the format: 169.254.x.x	169.254.175.72
--netmask	Oracle ILOM netmask.	255.255.255.0
--hostipaddress	Host IP address. This address must be in the format: 169.254.x.x	169.254.175.72

▼ List the Host-to-ILOM Interconnect Settings

To list the interconnect state and IP settings on both the Oracle ILOM and host side of the interconnect, use `ilomconfig list interconnect`.

- To list the Host-to-ILOM interconnect settings, type:

```
ilomconfig list interconnect
```

▼ Verify the Host-to-ILOM Interconnect Settings

To verify if the Host-to-ILOM Interconnect is up and running do the following:

1. To verify the Host-to-ILOM interconnect settings, type:

```
ilomconfig list interconnect
```

The following is example output for this command.

```
Interconnect
=====
State: enabled
Type: USB Ethernet
SP Interconnect IP Address: 169.254.182.76
Host Interconnect IP Address: 169.254.182.77
Interconnect Netmask: 255.255.255.0
SP Interconnect MAC Address: 02:21:28:57:47:16
Host Interconnect MAC Address: 02:21:28:57:47:17
```

2. Make sure that you can ping the SP Interconnect IP Address. For example:

```
ping 169.254.182.76
```

▼ Set Up a Credential Cache on the Host

As of Oracle Hardware Management Pack 2.3.3, this feature has been disabled. Refer to the Release Notes for more information.

The host local credential cache contains the username and password required to access Oracle ILOM via the local Host-to-ILOM Interconnect.

The username and password for the credential cache must match the username and password for the account being used on the Oracle ILOM service processor (for example as shown by `ilomconfig list user`).

Note - The credentials provided must have root privileges.

- **To set up a credential cache on the host, type:**
`ilomconfig create credential --username=username`
where *username* is a valid user account name used to log in to Oracle ILOM.

▼ Delete a Credential Cache on the Host

To remove an existing host local credential cache, for example when you have changed the username used to access Oracle ILOM via the Host-to-ILOM Interconnect, delete the host local credential cache.

- **To delete a credential cache on the host, type:**
`ilomconfig delete credential --username=username`
where *username* is a valid user account name used to log in to Oracle ILOM.

Managing ILOM and Host Watchdog

Starting with Oracle Hardware Management Pack 2.3, Oracle ILOM and host watchdog tools are available for systems running a Linux OS. The following sections describe the tools and how to use them:

- [“HMP Watchdog Overview” on page 113](#)
- [“ILOM Watchdog `ilomconfig` Commands” on page 117](#)
- [“Host Watchdog `ilomconfig` Commands” on page 119](#)
- [“Troubleshooting ILOM Watchdog and Host Watchdog States” on page 121](#)

HMP Watchdog Overview

This section provides a brief overview of the HMP Watchdog Agent and the associated ILOM watchdog and host watchdog services.

The following information is covered in this section:

- [“HMP Watchdog Agent Overview” on page 114](#)
- [“ILOM Watchdog Overview” on page 115](#)
- [“Host Watchdog Overview” on page 116](#)

HMP Watchdog Agent Overview

The HMP Watchdog Agent is an optional Oracle Hardware Management Pack component that you can install using the Oracle Hardware Management Pack installer. For information on how to install this component, refer to the *Oracle Hardware Management Pack Installation Guide*.

Note the following important information regarding the HMP Watchdog Agent:

- Your system must meet the following requirements to run the HMP Watchdog Agent:
 - A Linux operating system installed
 - Oracle Hardware Management Pack 2.3 or later installed
 - Oracle ILOM 3.2.2 or later on the SP
- The agent is not started by default. It must be started after it is installed.
- The agent is not started automatically after host reset (even if it was started before reset). It must be restarted after the host is reset.
- The host or ILOM watchdog configuration is preserved after the host is reset.

The HMP Watchdog Agent provides two services:

- **ILOM watchdog:** If enabled, the ILOM watchdog periodically queries for Oracle ILOM's health. If Oracle ILOM becomes unresponsive, the host performs the specified timer action, which is either Warning or Reset. For more information, see [“ILOM Watchdog Overview” on page 115](#).
- **Host watchdog:** If enabled, the host watchdog watches over the host's health. If the host becomes unresponsive, Oracle ILOM performs the specified timer action, which is one of the following: Warning, Reset, Power Off, or Power Cycle. For more information, see [“Host Watchdog Overview” on page 116](#).

This document covers how to configure the HMP Watchdog Agent services using the `ilomconfig` CLI command.

Information on configuring the HMP Watchdog Agent manually is available at [“Configuring the HMP Watchdog Agent” in Oracle Server Management Agents User's Guide](#).

ILOM Watchdog Overview

The ILOM watchdog enables the host to perform user-settable predefined actions when the host notices that Oracle ILOM has stopped responding.

You can control ILOM watchdog's parameters from the `ilomconfig` command, or by editing the HMP Watchdog Agent's configuration file.

See [“ILOM Watchdog Parameters” on page 115](#) for more information on the ILOM watchdog parameters that can be modified.

When ILOM watchdog determines that Oracle ILOM has stopped responding and therefore performs the timer action, it logs an appropriate message into the HMP watchdog log file, and the host's system log at `/var/log/messages`.

Note - Using the `ilomconfig` command is the preferred method for controlling ILOM watchdog.

ILOM Watchdog Parameters

The ILOM watchdog parameters can be set by the user in one of the following ways:

- Preferred method: Use the `ilomconfig modify ilomwatchdog` command with the `ilomwatchdog` target to change the parameters. See [“ILOM Watchdog `ilomconfig` Commands” on page 117](#).
- Manually edit the configuration file. See [“Manually Edit the Configuration File” in *Oracle Server Management Agents User's Guide*](#).

The following table lists the ILOM watchdog parameters.

Parameter Name	Parameter in Configuration File	Description	Possible Values	Default value
Query Time Interval	<code>ilom_watchdog_query_time_interval</code>	The periodic time interval, in seconds, at which the host will send a query to Oracle ILOM. If Oracle ILOM does not respond, then this indicates that Oracle ILOM is unresponsive, and the host performs the Timer Action.	Positive integer up to 214748364	60 seconds

Parameter Name	Parameter in Configuration File	Description	Possible Values	Default value
Timer Action	<code>ilom_watchdog_timer_action</code>	The action which the host performs when it notices that Oracle ILOM is unresponsive.	Warning Reset	Warning
Number of Consecutive SP Resets	<code>ilom_watchdog_number_sp_reset</code>	If the value of Timer Action is Reset, this parameter tells the host the number of times the host resets the SP until it gives up.	Positive integer up to 20	2
Admin State	<code>ilom_watchdog_admin_state</code>	The state which the user (Admin) sets the ILOM watchdog.	Enable Disable	Disable

Host Watchdog Overview

Host watchdog gives Oracle ILOM the ability to perform user-settable predefined actions when Oracle ILOM notices that the host has stopped responding.

You can control the host watchdog parameters using the `ilomconfig` command, or by editing the HMP Watchdog Agent's configuration file.

Note - Using `ilomconfig` command is the preferred method for controlling the host watchdog.

Host watchdog is built on top of standard IPMI watchdog timer functionality. The HMP Watchdog Agent interacts with the IPMI watchdog timer as follows:

- When the host watchdog is enabled by the user, it first checks to see if IPMI watchdog timer is already started. If the IPMI watchdog timer is started, host watchdog issues a log message, indicating that watchdog timer is already started and host watchdog remains in the Disable state.
This addresses the case where someone has already set the IPMI watchdog timer.
- While the host watchdog is enabled, it periodically resets the IPMI watchdog timer to the configuration values of host watchdog.
This addresses the case where someone changes the configuration outside of HMP Watchdog Agent.
- The host watchdog periodically resets the IPMI watchdog timer. When the OS hangs, and therefore the IPMI watchdog timer is not reset before the timer expires, Oracle ILOM performs the action specified by the Timer Action parameter.

See [“Host Watchdog Parameters” on page 117](#) for more information on the host watchdog parameters that can be modified.

Host Watchdog Parameters

The following host watchdog parameters can be set by the user in one of the following ways:

- Preferred method: Use the `ilomconfig modify hostwatchdog` command to change the parameters. See [“Host Watchdog `ilomconfig` Commands” on page 119](#).
- Manually edit the configuration file. See [“Manually Edit the Configuration File” in *Oracle Server Management Agents User’s Guide*](#).

Property Name	Parameter in Configuration File	Description	Possible values	Default value
Timer Action	<code>host_watchdog_timer_action</code>	The action Oracle ILOM takes when the host become unresponsive.	Warning Reset PowerOff PowerCycle	Warning
Timer Value	<code>host_watchdog_timer_value</code>	The periodic time interval, in seconds, at which Oracle ILOM performs the Timer Action if the host is unresponsive.	Positive integer with a maximum of 6553	300
Admin State	<code>host_watchdog_admin_state</code>	The state in which the user (Admin) sets the host watchdog.	Enable Disable	Disable
Reset Period	<code>host_watchdog_reset_period</code>	The periodic time interval, in seconds, at which the host informs Oracle ILOM that the host is alive. This value has to be less than that of Timer Interval.	Positive integer that is less than the value of the Timer Value	60

ILOM Watchdog `ilomconfig` Commands

The following procedures describe how to use the `ilomconfig` command with an `ilomwatchdog` target to view and configure Oracle ILOM watchdog parameters. Options specific to each command are listed with the command. For general CLI tool options, see [“`ilomconfig` Command Syntax” on page 95](#).

- [“List Current ILOM Watchdog Settings” on page 118](#)
- [“Enable ILOM Watchdog” on page 118](#)
- [“Disable ILOM Watchdog” on page 118](#)

- [“Modify Current ILOM Watchdog Settings” on page 118](#)
- [“Reset ILOM Watchdog Parameters to Factory Defaults” on page 119](#)

▼ List Current ILOM Watchdog Settings

- To list the current ILOM watchdog settings, type:

```
ilomconfig list ilomwatchdog
```

The following is an example of the output of this command:

```
Query time interval: 60 seconds
Timer Action: Warning
Number of consecutive SP resets: 2
Admin state : Disable
Current state: Disable
```

▼ Enable ILOM Watchdog

- To enable ILOM watchdog, type:

```
ilomconfig enable ilomwatchdog
```

This sets the `ilom_watchdog_admin_state` parameter to Enable.

▼ Disable ILOM Watchdog

- To disable ILOM watchdog, type:

```
ilomconfig disable ilomwatchdog
```

This sets the `ilom_watchdog_admin_state` parameter to Disable.

▼ Modify Current ILOM Watchdog Settings

- To modify current ILOM watchdog settings, type:

```
ilomconfig modify ilomwatchdog --option
```

You can change more than one parameter with the same command.

The following options are available for this command.

Option	Possible values	Description
<code>--timer-action=action</code>	Warning Reset	This sets the <code>ilom_watchdog_timer_action</code> parameter, which determines the action the ILOM watchdog takes when Oracle ILOM is not responsive.
<code>--number-sp-reset=numsreset</code>	Positive integer up to 20	This sets the <code>ilom_watchdog_number_sp_reset</code> parameter, which determines the number of times the SP can be reset consecutively.
<code>--query-interval=queryinterval</code>	Positive integer up to 2147483647	This sets the <code>ilom_watchdog_query_time_interval</code> parameter, which determines the number of seconds between querying for Oracle ILOM's health.

▼ Reset ILOM Watchdog Parameters to Factory Defaults

- To reset ILOM watchdog configuration to factory defaults, type:

```
ilomconfig reset ilomwatchdog-config
```

See “[ILOM Watchdog Parameters](#)” on page 115 for information on defaults for ILOM watchdog parameters.

Host Watchdog `ilomconfig` Commands

The following procedures describe how to use the `ilomconfig` command with a `hostwatchdog` target to view information about host watchdog and modify the watchdog configuration parameters. Options specific to each command are listed with the command. For general CLI tool options, see “[ilomconfig Command Syntax](#)” on page 95.

- “[List Current Host Watchdog Settings](#)” on page 119
- “[Enable Host Watchdog](#)” on page 120
- “[Disable Host Watchdog](#)” on page 120
- “[Modify Current Host Watchdog Settings](#)” on page 120
- “[Reset Host Watchdog Parameters to Factory Defaults](#)” on page 121

▼ List Current Host Watchdog Settings

- To list `hostwatchdog` settings, type:

```
ilomconfig list hostwatchdog
```

The following is an example of the output of this command:

```

Timer Action: Warning
Timer Value: 300 seconds
Remaining timer value: 300 seconds
Reset period: 60 seconds
Admin state : Disable
Current state: Disable
    
```

See [“Host Watchdog Parameters” on page 117](#) for more information on the parameters.

▼ Enable Host Watchdog

- To enable the host watchdog, type:

```
ilomconfig enable hostwatchdog
```

This sets the `host_watchdog_admin_state` parameter to Enable.

▼ Disable Host Watchdog

- To disable the host watchdog, type:

```
ilomconfig disable hostwatchdog
```

This sets the `host_watchdog_admin_state` parameter to Disable.

▼ Modify Current Host Watchdog Settings

- To modify current host watchdog settings, type:

```
ilomconfig modify hostwatchdog --option
```

You can change more than one parameter with the same command.

The following options are available for this command.

Option	Possible Values	Description
<code>--timer-action=<i>action</i></code>	Warning Reset PowerOff PowerCycle	This sets the <code>host_watchdog_timer_action</code> parameter, which determines the action the host watchdog takes when the timer value expires.
<code>--timer-value=<i>timervalue</i></code>	Positive integer up to 6553	This sets the <code>host_watchdog_timer_value</code> parameter, which determines the

Option	Possible Values	Description
<code>--reset-period=queryinterval</code>	Positive integer that is less than the value of timer-value parameter	number of seconds before the timer expires. This sets the <code>host_watchdog_reset_period</code> parameter, which determines the number of seconds before resetting the timer value.

▼ Reset Host Watchdog Parameters to Factory Defaults

- To reset host watchdog configuration to factory defaults, type:

```
ilomconfig reset hostwatchdog-config
```

See “[Host Watchdog Parameters](#)” on page 117 for information on defaults for host watch dog parameters.

Troubleshooting ILOM Watchdog and Host Watchdog States

A list of error codes for the `ilomconfig` commands using `ilomwatchdog` and `hostwatchdog` targets are in “[ilomconfig Error Codes](#)” on page 183.

This section describes errors that might occur when the state of the daemon is not what is normally expected by the user.

Start and Stop Errors

The errors shown in the following table appear when the HMP Watchdog Agent has not been started or has stopped. You might see these messages when you run any `ilomconfig` commands with the `hostwatchdog` or `ilomwatchdog` targets.

Error Message	Cause	Solution
ERROR: HMP watchdog agent is not started.	HMP Watchdog Agent has not started.	Run the following command to start HMP watchdog: <code>service hmp_watchdogd start</code>
ERROR: HMP watchdog agent is stopped.	HMP Watchdog Agent has been stopped by SIGSTOP.	Send a SIGCONT to the HMP Watchdog Agent's process ID as follows:

Error Message	Cause	Solution
	<p>Note - It is dangerous to suspend the operation of the HMP Watchdog Agent by sending it the SIGSTOP signal.</p> <p>It is possible that host watchdog is already enabled, and if the HMP Watchdog Agent is suspended long enough such that host watchdog is not able to reset the IPMI watchdog timer, the IPMI watchdog timer can expire, and Oracle ILOM performs the timer action which can reset the host.</p>	<ol style="list-style-type: none"> 1. Get the HMP Watchdog Agent's process ID from the <code>/var/run/sun-ssm-hmp-watchdogd.pid</code> file. 2. Run the following command: <code>kill -CONT PID</code> where <i>PID</i> is the process ID that you identified in Step 1.

Errors Related to ILOM Watchdog State

The errors shown in the following table occur when the ILOM watchdog Admin state (which is set by the user) is different from the Current state . The error message is shown, followed by the reason for the message, and a solution to the problem. In these cases, `ilomconfig list` displays a string indicating the error condition.

Error Message	Problem	Solution
Oracle ILOM does not support health query. Need to have ILOM 3.2.2 or greater.	Oracle ILOM watchdog requires Oracle ILOM 3.2.2 or later to support a health query by IPMI. If you have an earlier version of Oracle ILOM, ILOM watchdog cannot be enabled.	<p>Do one of the following:</p> <ul style="list-style-type: none"> ■ Disable ILOM watchdog with the following command: <code>ilomconfig disable ilomwatchdog</code> ■ Update Oracle ILOM to a later version. After updating Oracle ILOM, run the following command to reload the watchdog: <code>/etc/init.d/hmp_watchdogd reload</code> or <code>service hmp_watchdogd reload</code>
IPMI command failed connection. Check IPMI driver.	<p>ILOM watchdog uses IPMI to communicate with Oracle ILOM.</p> <p>If there is problem with IPMI on the host so that it is unable to communicate with Oracle ILOM, and the ILOM watchdog is currently</p>	<p>Troubleshoot the IPMI driver on the host.</p> <p>Once the IPMI problem is resolved, the ILOM watchdog detects it during the time of query interval (default is 60 seconds) after the IPMI problem</p>

Error Message	Problem	Solution
SP is not running Oracle ILOM.	<p>in Enable state, the ILOM watchdog automatically notices this and changes to Inactive state.</p> <p>ILOM watchdog is enabled, but the SP is not running Oracle ILOM.</p> <p>If ILOM watchdog is currently in Enable state, the ILOM watchdog automatically notices this and changes to Inactive state.</p>	<p>is resolved, and changes to Enable state.</p> <p>Reboot the SP.</p> <p>When ILOM watchdog is in inactive state, once the SP is successfully rebooted, and ILOM watchdog successfully sends a health query to Oracle ILOM, it automatically changes to Enable state.</p>
SP is not running Oracle ILOM or Host-to-ILOM Interconnect is not enabled.	<p>On a platform with Emulex Pilot 3 BMC, and ILOM watchdog enabled, either the SP is not running Oracle ILOM or Host-to-ILOM Interconnect is not enabled.</p> <p>If ILOM watchdog is currently in Enable state, the ILOM watchdog automatically notices this and changes to Inactive state.</p>	<p>Make sure Host-to-ILOM Interconnect is enabled, if so, make sure that the SP is running Oracle ILOM.</p> <p>When ILOM watchdog is in inactive state, once the Host-to-ILOM interconnect is enabled, the SP is successfully running Oracle ILOM, and the ILOM watchdog successfully sends a health query to Oracle ILOM, it will automatically change to Enable state.</p>
Unknown failure in ILOM watchdog.	ILOM watchdog is enabled but encounters some unexpected errors	Report the failure to Oracle.

Errors Related to Host Watchdog State

The errors shown in the following table occur when the host watchdog state is affected by the state of the IPMI watchdog timer. The error message is shown, followed by the reason for the message, and a solution to the problem.

Error Message	Host Watchdog State	Problem	Solution
IPMI watchdog timer is enabled outside of Hardware Management Pack.	<p>Admin state : Disable</p> <p>Current state: Enable</p>	<p>The host watchdog has been disabled by the user, but the IPMI watchdog timer is enabled outside of Hardware Management Pack.</p> <p>While in this state (Admin state is Disable and Current State is Enable) if you enable host watchdog, host watchdog will remain in Disable state.</p>	<p>In order to enable hostwatchdog, IPMI watchdog timer needs to be turned off with the following command:</p> <pre>#ipmitool mc watchdog off</pre>
IPMI watchdog timer is enabled	Admin state : Enable	First, the Admin state is Enable and the user uses ipmitool to disable	After the duration of the reset period (default is 60 seconds), the host

Reset Host Watchdog Parameters to Factory Defaults

Error Message	Host Watchdog State	Problem	Solution
outside of Hardware Management Pack.	Current state: Enable	the IPMI watchdog timer, then the user uses ipmitool to enable IPMI watchdog timer.	watchdog automatically corrects the situation.
IPMI watchdog timer is disabled outside of Hardware Management Pack.	Admin state : Enable Current state: Disable	The IPMI watchdog timer is disabled outside of Hardware Management Pack while the host watchdog is in Enabled state.	After the reset period (default is 60 seconds), the host watchdog corrects this and re-enable the timer.
Need to have Oracle ILOM 3.2.2 or greater.	Varies	Oracle ILOM must be version 3.2.2 or greater to run host watchdog.	Do one of the following: <ul style="list-style-type: none"> ■ Disable host watchdog with this command: <pre>ilomconfig disable host watchdog</pre> ■ Upgrade Oracle ILOM to 3.2.3. or greater, then run one of the following commands: <pre>/etc/init.d/hmp_watchdog reload</pre> or <pre>service hmp_watchdog reload</pre>
IPMI command failed connection. Check IPMI driver.	Varies	Failure sending IPMI request to SP.	Check the IPMI driver on the host side.
IPMI watchdog command failed.	Varies	IPMI watchdog command got to the SP, but encountered failure.	Make sure the IPMI stack is working properly on Oracle ILOM.
Can not determine Oracle ILOM version.	Varies	Host watchdog is unable to determine the Oracle ILOM version.	Issue some IPMI commands to the SP to see if the IPMI commands work on the SP.

Using `ipmitool` for Windows

This section describes `ipmitool` and how to install `ipmitool` on systems running the Windows operating system.

Before beginning the procedures in this section, you must complete the following procedures:

1. Install the Microsoft Windows Server 2003 or Windows Server 2008 operating system.
2. Download `Windows.zip` and extract `InstallPack_x_x_x.exe`
3. Run `InstallPack_x_x_x.exe` to install supplemental software on the server

This section covers the following topics:

Description	Links
Learn about <code>ipmitool</code> .	“ipmitool Overview” on page 125
Learn about Sun IPMI System Management Driver 2.1.	“Sun IPMI System Management Driver 2.1” on page 126
Configure boot order.	“Configuring Boot Order Using ipmitool” on page 126

`ipmitool` Overview

The Oracle Hardware Management Pack IPMI configuration CLI tool (`ipmitool`), is a utility that reads the sensor data repository (SDR) and displays the following information:

- Sensor values
- System event log (SEL)
- Field-replaceable unit (FRU) information
- Inventory information

`ipmitool` also gets and sets LAN configuration parameters, and performs chassis power control operations through the server’s service processor.

`ipmitool` is supplemental software that you can install using the server's Tools and Drivers CD or using the `Installpack_x_x_x.exe` executable file, where the `_x_x_x` number identifies the version of the package (for example, `InstallPack_1_1_4.zip`).

For information about using `ipmitool` with the server management agents, see [“Generating SNMP Traps” in *Oracle Server Management Agents User's Guide*](#).

Sun IPMI System Management Driver 2.1

The Sun IPMI System Management Driver 2.1 allows communication between the Microsoft Windows host operating system and the ILOM service processor over an internal Keyboard Controller Style (KCS) interface. This driver is required for Microsoft Windows Server 2003 SP2 and earlier.

For later OS versions (including Microsoft Windows Server 2003 R2) the Microsoft-provided IPMI driver included in their Hardware Management Module provides the same functionality.

This driver must be installed before installing `ipmitool`. Refer to [“Installing the Sun IPMI System Management Driver 2.1” in *Oracle Hardware Management Pack Installation Guide*](#) for information on installing the driver.

Configuring Boot Order Using `ipmitool`

On some platforms, `ipmitool` offers an alternative to using `biosconfig` to make persistent changes to the boot order. This interface can specify which is the highest-priority category of boot device. This operation is equivalent to entering BIOS setup and moving an entire category of devices to the top of the boot list (for example, moving all disks to boot before CD-ROMs).

The following `ipmitool` raw commands work like the `ipmitool chassis bootdev` commands. During BIOS POST, the BIOS asks the SP for boot flags. The raw commands have an extra bit set (the persistent bit), which causes the BIOS to reorder the boot list and save that order in CMOS. These `ipmitool` commands can also be issued through the host SP Keyboard Controller Style (KCS) interface if you have the IPMI drivers installed on a host Linux system.

Use one of the following commands, depending on which device you want to boot first:

- To boot from PXE first:

```
ipmitool -H ... -U root -P ... raw 0x0 0x8 0x5 0xC0 0x4 0x0 0x0
```

The BIOS boot order changes so that PXE attempts to boot first. Sun Blade X6275 has both IB and Gigabit Ethernet interfaces, and this moves both to the top of the boot list with the InfiniBand PXE first followed by GE if IB fails over. The BIOS setup reflects the change in the boot order.

- To boot from CD/DVD first:

```
ipmitool -H ... -U root -P ... raw 0x0 0x8 0x5 0xC0 0x14 0x0 0x0
```

The BIOS boot order changes so that any CD/DVD attempts to boot first. On Sun Blade X6275 this could be a USB external CD/DVD-ROM drive or a JavaConsole-redirectioned CD. The BIOS setup reflects the change in the boot order.

- To boot from floppy or any removable media:

```
ipmitool -H ... -U root -P ... raw 0x0 0x8 0x5 0xC0 0x3C 0x0 0x0
```

The BIOS boot order changes so that any floppy or removable media (such as USB flash) attempts to boot first. On Sun Blade X6275 this could be a USB flash drive or a JavaConsole-redirectioned floppy. The BIOS setup reflects the change in the boot order.

- To boot from the hard drive:

```
ipmitool -H ... -U root -P ... raw 0x0 0x8 0x5 0xC0 0x8 0x0 0x0
```

The BIOS boot order changes so that the hard drive attempts to boot first. Sun Blade X6275 has a flash mini-DIMM SATA that boots first. The BIOS setup reflects the change in the boot order.

Using nvmeadm to Configure an NVM Express Device

The `nvmeadm` utility collects and modifies the NVMe device configuration. This utility supports NVMe add-in PCIe cards and NVMe SSDs beginning with the Oracle Flash Accelerator F160 PCIe Card and the 1.6 TB SSD. For a list of supported controllers and servers, see the support matrix at: <http://www.oracle.com/goto/ohmp>.

The following information is covered in this section:

Description	Links
Learn about the <code>nvmeadm</code> command	“nvmeadm Command Overview” on page 129
Display controller information	“List NVMe Controllers” on page 131
Display information about controller namespaces	“List NVMe Namespaces” on page 132
Display information about supported controller LBA (Logical Block Address) formats	“List the Supported LBA Format” on page 133
List or generate controller log pages	“List NVMe Controller Log Pages ” on page 134
Display the features of an NVMe controller	“List NVMe Features of the Controller” on page 135
Format controller namespaces	“Format All Namespaces on the Controller” on page 135
Erase controller namespaces	“Erase All Namespaces” on page 136
Export NVMe disk configuration to a file	“Export an SSD Disk Configuration” on page 136
Import NVMe disk configuration from a file	“Import an SSD Disk Configuration” on page 137

nvmeadm Command Overview

The `nvmeadm` commands use the following syntax:

```
nvmeadm subcommand [option] [controller_name]
```

Note - If a controller name is not specified for a command, the required information for all controllers is returned.

When a command fails, it returns one of several failure codes listed in [“nvmeadm Error Codes” on page 184](#).

The nvmeadm command supports the subcommands listed in the following table.

Subcommand	Function
list	Lists information for the specified controller.
namespace	Lists information for the namespaces of the specified controller.
getlog	Lists NVMe log pages of the controller. There are three log pages: SMART/Health, Error code information, and vendor-specific log information.
getfeature	Lists NVMe features of the controller.
format	Low-level formats specified namespaces, which changes the LBA (Logical Block Address) and metadata size for the controller. All data is destroyed after a low level format. Note - Stop all IO to the NVMe device before attempting to format it. This is not necessary if you are simply obtaining format details using the format -l or --list option.
erase	Erases the NVMe namespace media for the controller. Note - Stop all IO to the NVMe device before attempting this action.
export	Exports the SSD configuration to a file. This file should not be edited or modified.
import	Imports block size and metadata size configuration from a file. Note - Stop all IO to the NVMe device before attempting this action.

The nvmeadm command supports the options shown in the following table.

Short Option	Long Option	Subcommands Used With	Description
-?	--help	All	Displays usage information.
-V	n/a	All	Displays version information.
-a	--all	format	Selects all namespaces on the controller.
		erase	
-b	--blocksize	format	Specifies the LBA data size of a namespace on the controller. This option requires an argument for blocksize. Supported block sizes depend on the controller (see “List the Supported LBA Format” on page 133).
-e	--error	getlog	Retrieves the extended error information.
-f	--format	format	Formats the NVM namespace media on the controller to the logical block size and metadata size specified by -b, -m, -a and -n options.

Short Option	Long Option	Subcommands Used With	Description
-f	--filename	export, import	Writes the data to or reads the data from the specified file name.
-h	--health	getlog	Retrieves the SMART/health information of the controller. The information is over the life of the controller and is retained across power cycles.
-l	--list	format	Lists the LBA formats supported by the controller. Each LBA format contains LBA size and metadata size.
-m	--metadatasize	format	Specifies the metadata size of a namespace on the controller. This option requires an argument for metadata size. Supported metadata sizes depend on the supported block sizes (see “List the Supported LBA Format” on page 133).
-n	--namespace	format, namespace, erase	Selects the namespace on the controller.
-s	--vendor_specific	list, getlog	Retrieves the vendor-specific information of the specified controller. This option is used with the list and getlog subcommands. <ul style="list-style-type: none"> ■ When used with list, this option displays vendor information about the controller. ■ When used with getlog, this option generates nlog and eventlog files for Intel NVMe devices, and generates crash dump and memory dump files for Samsung NVMe devices. This option requires an argument that specifies the directory to which the log pages will be saved.
-v	--verbose	list, namespace	Displays detailed information of a controller or device/namespace, based on the invoked subcommand.

▼ List NVMe Controllers

- To list NVMe controllers in the system, do one of the following:
 - To list all NVMe controllers on the host, type:

```
nvmeadm list
```

```
SUNW-NVME-1
```
 - To list all NVMe controllers with details, type:

```
nvmeadm list -v
```

```
SUNW-NVME-1
  PCI Vendor ID:          1111
  Serial Number:         1111111111
  Model Number:          1111111111111
  Firmware Revision:     1.1.1
  Number of Namespaces:  1
```

- To list details for a specific controller, type:

```
nvmeadm list -v controller_name
```

For example:

```
nvmeadm list -v SUNW-NVME-1
```

```
SUNW-NVME-1
  PCI Vendor ID:          1111
  Serial Number:         1111111111
  Model Number:          1111111111111
  Firmware Revision:     1.1.1
  Number of Namespaces:  1
```

- To list vendor-specific details for a specific controller, type:

```
nvmeadm list -s controller_name
```

For example:

```
nvmeadm list -s SUNW-NVME-1
```

```
SUNW-NVME-1
  PCI Vendor ID:          0x8086
  PCI Device ID:          0x0953
  PCI Subsystem Vendor ID: 0x108e
  PCI Subsystem ID:       0x370b
  Oracle Part Number:     7090698
  Oracle Model Number:    IFDPC5EA3ORC1.6T
```

▼ List NVMe Namespaces

- To list an NVMe namespace, type:

```
nvmeadm namespace [-n] [namespace] [-v] [controller_name]
```

For example:

- To list namespaces on all NVMe controllers:

```
nvmeadm namespace
```

```
SUNW-NVME-1
  Namespace: 1
```

- For details on namespace 1 on controller SUNW-NVME-1:

```
nvmeadm namespace -n 1 -v SUNW-NVME-1
```

```
SUNW-NVME-1
  Namespace: 1
  Block Size:          512
  Capacity:            786146787328
  Metadata Size:      0
  Block Device Name:   /dev/rdisk/c5t0d0s2
```

▼ List the Supported LBA Format

- To list the supported LBA formats on an NVMe controller, type:

```
nvmeadm format -l [controller_name]
```

For example:

```
nvmeadm format -l SUNW-NVME-1
```

```
SUNW-NVME-1
  LBA Format: 1
    Block Size:          512
    Metadata Size:      0
  LBA Format: 2
    Block Size:          512
    Metadata Size:      8
  LBA Format: 3
    Block Size:          512
    Metadata Size:     16
  LBA Format: 4
    Block Size:         4096
    Metadata Size:      0
  LBA Format: 5
    Block Size:         4096
    Metadata Size:      8
  LBA Format: 6
    Block Size:         4096
    Metadata Size:     64
```

▼ List NVMe Controller Log Pages

There are three NVMe controller log pages as follows:

- **SMART/health information** is gathered over the life of the controller and is retained across power cycles. It includes critical warnings about the controller and device status, such as temperature threshold, available spare, device life status, and various I/O statistics used for calculating I/O performance.
- **Error information** is extended error information for commands. A number, which designates the error ID, must be specified with this command.
- **Vendor Log information** is the vendor-specific NVMe log implementation. Use this log when working with Oracle Service to troubleshoot errors.

- **Do one of the following:**

- **To list SMART/health information, type:**

```
nvmeadm getlog -h [controller_name]
```

The following is an example for the `nvmeadm getlog -h` command:

```
nvmeadm getlog -h SUNW-NVME-1
```

```
SUNW-NVME-1
```

```
SMART/Health Information:
```

```
  Critical Warning: 0
  Temperature: 300 Kelvin
  Available Spare: 100 percent
  Available Spare Threshold: 10 percent
  Percentage Used: 0 percent
  Data Unit Read: 0x746da4 of 512k bytes.
  Data Unit Written: 0x2d0 of 512k bytes.
  Number of Host Read Commands: 0xaeacba
  Number of Host Write Commands: 0x27
  Controller Busy Time in Minutes: 0x0
  Number of Power Cycle: 0x10d
  Number of Power On Hours: 0x3c8
  Number of Unsafe Shutdown: 0xfa
  Number of Media Errors: 0x0
  Number of Error Info Log Entries: 0x0
```

- **To list error information, type:**

```
nvmeadm getlog -e error_id [controller_name]
```

- **To save vendor log information to a file, type:**

```
nvmeadm getlog -s directory [controller_name]
```

For example, for a controller named SUNW-NVME-1:

```
nvmeadm getlog -s /logs SUNW-NVME-1
```

- For a Samsung controller, the files `crashdump_SUNW-NVME-1` and `memorydump_SUNW-NVME-1` are generated and placed under `/logs`.
- For an Intel controller, the files `eventlog_SUNW-NVME-1` and `nlog_SUNW-NVME-1` are generated and placed under `/logs`.

▼ List NVMe Features of the Controller

- To list NVMe features of the controller, type:

```
nvmeadm getfeature [controller_name]
```

For example:

```
nvmeadm getfeature SUNW-NVME-1
```

```
SUNW-NVME-1
  Command Arbitration:
    Arbitration Burst: 0
    Low Priority Weight: 0
    Medium Priority Weight: 0
    High Priority Weight: 0
  Power State: 0
  Temperature Threshold: 358 Kelvin
  Time Limited Error Recovery: 0 of 100 milliseconds
  Number of I/O submission queues allocated: 30
  Number of I/O completion queues allocated: 30
  Interrupt Coalescing Aggregation Time: 0 of 100 micro seconds
  Interrupt Coalescing Configuration:
    Interrupt Vector: 0
    Coalescing Disable: NO
  Write Atomicity Required: YES
```

▼ Format All Namespaces on the Controller

The controller does not support the format of a single namespace. Use the `-a` option to confirm the format of all namespaces. For supported metadata and block size information, see [“List the Supported LBA Format” on page 133](#).



Caution - All data is destroyed after a low-level format.

Before You Begin Stop all IO to the NVMe device before attempting format it.

- **To format all namespaces on a controller, type:**

```
nvmeadm format -f -a -m metadata_size -b block_size controller_name
```

For example:

```
nvmeadm format -f -a -m 0 -b 4096 SUNW-NVME-1
```

▼ Erase All Namespaces

The controller does not support the erase of a single namespace. Use the -a option to confirm the erase of all namespaces.



Caution - All data will be destroyed after an erase.

Before You Begin Stop all IO to the NVMe device before attempting this action.

- **To erase all namespaces, type:**

```
nvmeadm erase -a controller_name
```

For example:

```
nvmeadm erase -a SUNW-NVME-1
```

▼ Export an SSD Disk Configuration

- **To export an SSD disk configuration to a file, type:**

```
nvmeadm export -f filename.xml controller_name
```

For example:

```
nvmeadm export -f format.xml SUNW-NVME-1
```

Note - The exported XML file should not be edited or modified.

▼ Import an SSD Disk Configuration

Only block size and metadata size information can be imported.

Before You Begin Stop all IO to the NVMe device before attempting this action.

- **To import an SSD disk configuration from a file, type:**

```
nvmeadm import -f filename.xml controller_name
```

For example:

```
nvmeadm import -f format.xml SUNW-NVME-2
```


Using `raidconfig` to Configure RAID

`raidconfig` uses a general-purpose cross-OS storage management library to configure RAID volumes using an XML file.

The following table shows the information covered in this section.

Description	Links
Learn about the <code>raidconfig</code> command.	“<code>raidconfig</code> Command Overview” on page 139
Display controller, RAID, and disk information	“Listing Controller, RAID and Disk Information” on page 142
Create or delete RAID volumes	“Creating and Deleting RAID Volumes” on page 148
Modify a RAID or controller configuration	“Modifying a RAID Volume or Controller” on page 153
Start or stop a disk or RAID task	“Starting or Stopping a Task on a Disk or RAID” on page 158
Restore and clear a RAID controller configuration	“Restoring or Clearing a RAID Controller Configuration” on page 160
Export or import a RAID volume configuration	“Exporting or Importing a RAID Volume Configuration” on page 162
Create a RAID volume with partial disks	“Creating RAID Volumes With Partial Disks” on page 163

`raidconfig` Command Overview

This section covers the following information:

- [“`raidconfig` Features” on page 140](#)
- [“`raidconfig` Requirements” on page 140](#)
- [“`raidconfig` Command Syntax” on page 141](#)

raidconfig Features

raidconfig allows you to explore, monitor, and configure storage resources connected to the system.

Note - To use raidconfig on storage in a system, the controller that the storage is connected to must support RAID. For a list of supported controllers, see the support matrix at: <http://www.oracle.com/goto/ohmp>.

raidconfig provides the following functions:

- Shows, creates, deletes, and modifies RAID volumes.
- Facilitates scripting by using command-line options.
- Configures many similar and dissimilar platforms in a data center.
- Displays the current RAID configuration and writes it to an XML file so it can be edited and used to configure the same or a different platform.
- Represents a logical disk in a portable manner.
For example, using a unique enumeration per controller, instead of a SAS address, facilitates moving the XML file to other platforms.
- Provides a super-set of all configuration options provided by the Adaptec and LSI CLI commands.
- Uses capability checking for particular adapters based on data retrieved from the API.
- Creates nested RAID volumes depending on the controller.

raidconfig Requirements

Before running raidconfig, note the following requirements:



Caution - raidconfig can scan your controllers and connected disks and list disks that are either already in a RAID volume, or available to be included in a RAID volume. However, raidconfig cannot tell if an available disk has data on it, or if a disk is otherwise used as either a boot disk or logical disk for an application.

Before using raidconfig to create volumes (which will overwrite any existing data), use operating system tools to take an inventory of attached disks, their enumeration, and whether they contain data that you want to preserve.

- Root permissions are required to run `raidconfig` commands on Unix-based platforms.
- On Oracle Solaris, `raidconfig` is not compatible with the `raidctl` CLI tool. `raidconfig` supports SAS2 and SAS3, but the `raidctl` tool does not.
- For servers running Oracle Solaris, after hot-plugging any device, run the `devfsadm -C` command to reenumerate all of the system device nodes before running the `raidconfig` command.

raidconfig Command Syntax

The `raidconfig` commands use the following command syntax:

```
raidconfig subcommand target|task -option(s)
```

When a command fails, it returns one of several failure codes listed in [“raidconfig Error Codes” on page 184](#).

The options shown in the following table apply to all CLI Tools commands including `raidconfig`.

Short Option	Long Option	Description
-?	--help	Displays help information.
-v	--version	Displays the tool version.
-q	--quiet	Suppresses informational message output and only returns error codes.
-y	--yes	Confirms operation. Does not prompt user for confirmation on the operation when running.

The `raidconfig` command requires subcommands unless used with the `--help` or `--version` options.

The following table lists the `raidconfig` subcommands.

Subcommand	Function
<code>list</code>	Lists information on controllers, RAID volumes and disks, including disks not in a RAID volume. Specific devices can be selected for display.
<code>create</code>	Creates a RAID volume.
<code>delete</code>	Deletes a RAID volume.

Subcommand	Function
add	Adds a specified disk or spare.
remove	Removes a specified disk or spare.
modify	Modifies a RAID volume or a disk.
start	Starts a maintenance task.
stop	Stops a maintenance task.
restore	Finds the RAID configuration saved on a disk and restores it.
clear	Clears the RAID configuration saved on the disks of a defined controller.
export	Generates an XML file from a RAID configuration.
import	Reads in a RAID configuration from an XML file and creates RAID volumes and spares.

Whenever devices (controllers, RAID volumes, and disks) are used with commands, they must be uniquely identified. For information on how to do so, see the device-naming scheme at [“CLI Tools Device-Naming Convention” on page 20](#).

Device naming is shared with other CLI Tools based on the storage library.

Listing Controller, RAID and Disk Information

This section covers the following information:

- [“list Subcommand Overview” on page 142](#)
- [“Display a Brief Listing of All Devices” on page 145](#)
- [“Display a Brief Listing of a Device” on page 146](#)
- [“Display a Detailed Listing of a Device” on page 147](#)

list Subcommand Overview

The `list` subcommand displays controller, RAID volume, and disk data. The device targets for the `raidconfig list` are listed in the following table.

Target	Description
all	Shows details on all controllers, physical disks, and RAID volumes.
controller	Shows details on all controllers.

Target	Description
disk	Shows the physical disks.
raid	Shows all RAID details.

The `raidconfig list` command supports options listed in the following table.

Short Option	Long Option	Description
-c	--controller	Shows details about a particular controller. This option is followed by the controller ID string.
-r	--raid	Shows details about a particular RAID volume. This option is followed by the RAID ID string.
-d	--disks	Shows details about particular disk(s). This option is followed by a comma-separated list of the disk ID strings.
-v	--verbose	Lists all fields. By default, a brief listing shows only a subset of the fields.

The following data is displayed. Items marked with an asterisk (*) show a brief listing; all other items show a verbose listing.

Controllers:

- Node ID
- Manufacturer*
- Model*
- Part number
- Firmware(F/W) version*
- Serial Number
- RAID Volumes*
- Disks*
- Disks in use by another controller
- PCI address
- PCI vendor ID
- PCI device ID
- PCI subvendor ID
- PCI subdevice ID
- Battery backup status
- Maximum RAID volumes
- Maximum disks per RAID volume

- Supported RAID levels
- Maximum dedicated spares
- Maximum global spares
- Stripe size minimum
- Stripe size maximum
- Disable Auto Rebuild

Disks:

- ID*
- Chassis ID*
- Slot ID*
- Node ID
- Mapped to host OS (true/false)
- Device
- Disabled (true/false)
- In use by another controller
- RAID ID*
- Status*
- Type*
- Media*
- Manufacturer
- Model
- Size
- Serial number
- NAC name
- Spare state (global, dedicated, or N/A)*
- Current task
- Stoppable tasks
- Startable tasks
- Task state
- Task completion percent

RAID volumes:

- Logical ID (0-based)*
- Node ID

- Device name*
- Name (user assigned)*
- Status*
- RAID level*
- Number of disks*
- Capacity*
- Mounted
- Stripe size
- Leg size
- Read cache
- Write cache
- Current task
- Task state
- Task completion percent
- Stoppable tasks
- Startable tasks
- BIOS Boot Target

▼ Display a Brief Listing of All Devices

- To display a brief listing of all available controllers, RAID volumes, disks in use, and available disks, type:

```
raidconfig list all
```

The following shows sample output from this command.

```
CONTROLLER c0
=====
Manufacturer  Model      F/W Version  RAID Volumes  Disks
-----
Adaptec       0x0285     5.2-0        4              8

RAID Volumes
=====
ID      Name           Device      Status      Num Disks  Level  Size (GB)
-----
c0r0    0919XF5017-0  /dev/sda   OK          1          Simple 146
c0r1    raid1         /dev/sdb   OK          2          0      293
c0r2    raid2         /dev/sdc   OK          3          10     146
```

```
c0r3  noname          /dev/sdd  OK          2          0          293
```

DISKS In Use

```
=====
```

ID	Chassis	Slot	RAID ID	Status	Type	Media	Spare	Size (GB)
c0d0	0	0	c0r0	OK	sas	HDD	-	146
c0d1	0	1	c0r2	OK	sas	HDD	-	146
c0d2	0	2	c0r3	OK	sas	HDD	-	146
c0d3	0	3	c0r3	OK	sas	HDD	-	146
c0d4	0	4	c0r2	OK	sas	HDD	-	146
c0d5	0	5	c0r2	-	sas	HDD	Dedicated	146
c0d6	0	6	c0r1	OK	sas	HDD	-	146
c0d7	0	7	c0r1	OK	sas	HDD	-	146

The following table lists the possible RAID statuses that can be displayed with the `raidconfig list all` command.

Status	Meaning
OK	The status of the RAID volume is OK.
DEGRADED	The RAID volume has been degraded.
FAILED	The RAID volume has failed.
MISSING	The controller is reporting that it has a RAID volume is configured but the actual configuration settings aren't available. This status is rare.

The following table lists the possible disk statuses that can be displayed with the `raidconfig list all` command.

Status	Meaning
OK	The status of the disk is OK.
OFFLINE	The disk is offline.
FAILED	The disk has failed.
MISSING	The disk has been removed from a RAID.
INIT	The disk has been initialized.
SPARE	The disk is a spare.

▼ Display a Brief Listing of a Device

- To display a brief listing of a device, type:

```
raidconfig list subcommand option device
```

For example:

```
raidconfig list disk -d c0d0
```

```
DISKS Available
```

```
=====
```

ID	Chassis	Slot	RAID ID	Status	Type	Media	Spare	Size (GiB)
c0d0	0	0	-	-	sas	HDD	-	279

▼ Display a Detailed Listing of a Device

- To show a detailed listing of a device, type:

```
raidconfig list device option devicename -v
```

For example for a disk:

```
raidconfig list disk -d=c0d0 -v
```

```
Disk c0d0
```

```
=====
```

```
ID: c0d0
```

```
Chassis: 0
```

```
Slot: 0
```

```
Node ID: PDS:5000cca0257dbac1
```

```
Mapped to Host OS: true
```

```
Device: 5000CCA0257DBAC0
```

```
Disabled: false
```

```
Type: sas
```

```
Media: HDD
```

```
Manufacturer: HITACHI
```

```
Model: H106030SDSUN300G
```

```
Size (GiB): 279
```

```
Serial Number: 001214N74K2B PQJ74K2B
```

```
NAC Name: /SYS/SASBP/HDD0
```

```
Current Task: none
```

For example for a controller:

```
raidconfig list controller -v
```

```
CONTROLLER c0
```

```
=====
```

```
Node ID: mptir2:50:00.0
```

```
Manufacturer: LSI Logic
```

Model: SG-SAS6-INT-Z
F/W Version: 11.05.03.00
Serial Number: 500605b005468020
RAID Volumes: 1
Disks: 8
PCI Address: 50:00.0
PCI Vendor ID: 0x1000
PCI Device ID: 0x0072
PCI Subvendor ID: 0x1000
PCI Subdevice ID: 0x3050
Battery Backup Status: Not installed
Max RAID Volumes: 2
Max Disks per RAID Volume: 256
Supported RAID Levels: 0, 1, 10
Max Dedicated Spares: 0
Max Global Spares: 2
Stripe Size Min (KB): 64
Stripe Size Max (KB): 64

The following table lists the possible Battery Backup statuses that can be displayed with the `raidconfig list controller` command.

Status	Meaning
Not Installed	The battery backup option is not installed.
OK	The status of the battery backup is OK.
Charging	The battery backup is charging.
Discharging	The battery backup is discharging.
Low voltage	There is low voltage to the HBA on-board memory and the battery backup has become its primary source of power.
High temperature	The battery backup is overheating. This can cause the battery to stop charging and reduce its life expectancy.
Failed	The battery backup has failed and might need to be replaced.
Missing	The battery backup hardware is missing, malfunctioning, unplugged or fully discharged.

Creating and Deleting RAID Volumes

This section covers the following information:

- [“Create a RAID Volume” on page 149](#)
- [“Delete a RAID Volume” on page 150](#)

▼ Create a RAID Volume

Before You Begin Before using `raidconfig` to create volumes (which will overwrite any existing data on selected disks), use operating system tools to take an inventory of attached disks, their enumeration, and whether they contain data that you want to preserve. Be careful not to overwrite your OS boot disk or other logical disks used by applications.

- **To create a RAID volume, type:**

```
raidconfig create raid options -d disks
```

For example, to create a RAID 0 volume with a stripe size of 128 Kb and read-ahead caching enabled on controller 1, type the following command:

```
raidconfig create raid --stripe-size=128 --read-cache=enabled -d c1d0,c1d1
```

The `create raid` subcommand must take the `-d` option in addition to one or more of the options shown in the following table.

Short Option	Long Option	Description
-d	--disks	Specifies a list of disks with a comma separating the disk ID numbers.
N/A	--level	Specifies the RAID level of the volume e.g. 0, 1, 1E, 5, 10, 50, 60 etc. The levels supported for a particular controller can be seen in the controller 'Supported RAID Levels' field from the list command. If this option is not supplied, a level of '0' is used.
N/A	--name	Assigns the user-defined name that identifies the RAID volume. This name can be set to an empty string ("").
N/A	--read-cache	Read cache can be one of the following: disabled – Disables RAID read caching enabled – Enables RAID read ahead caching enabled_adaptive – Enables RAID read adaptive caching Note - Only supported with the Sun Storage 6 Gb SAS RAID PCIe HBA, Internal (SGX-SAS6-R-INT-Z, SG-SAS6-R-INT-Z) and Oracle Storage 12 Gb SAS RAID PCIe HBA, Internal (7110116, 7110117).
N/A	--stripe-size	Specifies the stripe size, in kilobytes, of the RAID volume to be created. If this option is not supplied, the controller uses a default size.
N/A	--subarrays	For nested RAID levels (10, 50), specifies the size of the RAID components in number of physical disks.
N/A	--subdisk-size	See “Creating RAID Volumes With Partial Disks” on page 163.
N/A	--write-cache	Write cache can be one of the following: disabled – Disables RAID write caching.

Short Option	Long Option	Description
		enabled – Enables RAID write caching.
		enabled_protect – Enables caching only if the battery is available. Note - Only supported with the Sun Storage 6 Gb SAS RAID PCIe HBA, Internal (SGX-SAS6-R-INT-Z, SG-SAS6-R-INT-Z) and Oracle Storage 12 Gb SAS RAID PCIe HBA, Internal (7110116, 7110117).

The maximum capacity of the RAID volume is not configurable. You can create RAID from partial disks if the HBA or controller support it, and all the disks are of the same size.

▼ Delete a RAID Volume

● To delete a RAID volume, type:

```
raidconfig delete raid option
```

For example:

- To delete RAID volume 1 created on controller 1, type:

```
raidconfig delete raid -r c1r1
```

- To delete all RAID volumes, type:

```
raidconfig delete raid --all
```

The `delete raid` requires one of the options shown in the following table.

Short Option	Long Option	Description
-r	--raid	Deletes the volume listed by ID number.
N/A	--all	Deletes all RAID volumes on all controllers. <code>raidconfig</code> queries the storage management library to determine if the RAID disks have been mounted. If so, it generates a warning message to the user and queries the user to delete the RAID volume.

Adding and Removing Disks and RAID Volumes

This section covers the following information:

- [“Add a Disk to a RAID Configuration” on page 151](#)

- [“Remove a Disk from a RAID Volume” on page 151](#)
- [“Add Spare Disks” on page 152](#)
- [“Remove a Spare Disk or a RAID Volume” on page 153](#)

▼ Add a Disk to a RAID Configuration

The `add disk` subcommand adds a specified disk to a RAID configuration.

Only certain RAID levels, such as RAID 5 or 6, allow disks to be added to their configuration when in a non-degraded (healthy) state. Only RAID levels that support redundancy allow disks to be added.

- **To add a specific disk to a RAID volume, type:**

```
raidconfig add disk -d disk -r raidvolume
```

For example:

```
raidconfig add disk -d c0d2 -r c0r1
```

Note - If you list the disk's properties after adding a disk, the RAID ID is not updated to reflect that it has been added to a RAID volume until the add process is complete.

The `add disk` subcommand requires the options shown in the following table.

Short Option	Long Option	Description
-d	--disks	Specifies the list of disks that you want to add to the RAID volume.
-r	--raid	Specifies the RAID volume ID number to which you want to add the disk.

▼ Remove a Disk from a RAID Volume

The `remove disk` subcommand removes a disk from a RAID volume. Only RAID levels that support redundancy allow for disks to be removed.

- **To remove a specific disk from a RAID volume, type:**

```
raidconfig remove disk -d disk -r raidvolume
```

For example:

```
raidconfig remove disk -d c0d0 -r c0r1
```

This subcommand requires the options shown in the following table.

Short Option	Long Option	Description
-d	--disks	Specifies the disk that you want to remove from the RAID volume.
-r	--raid	Specifies the RAID volume ID from which you want to remove the disk.

▼ Add Spare Disks

The `add spare` subcommand adds global or dedicated spare disks.

1. **To create two global spares using the specified disks, type:**

```
raidconfig add spare -d disk,disk
```

For example:

```
raidconfig add spare -d c1d0,c1d1
```

2. **To create two dedicated spares on a RAID volume using the specified disks, type:**

```
raidconfig add spare -d disk,disk -r raidvolume
```

For example:

```
raidconfig add spare -d c1d0,c1d1 -r c1r0
```

The `add spare` subcommand requires one of the options shown in the following table.

Short Option	Long Option	Description
-d	--disks	This <i>mandatory option</i> specifies a list of disk ID numbers, separated by commas. If the <code>-r</code> option is not used, the disks are added as global spares.
-r	--raid	Only used when working with dedicated spares. If a RAID Volume ID is specified, the spares should be added as dedicated spares for this RAID Volume. Note that some controllers do not support dedicated spares and the command might fail.

▼ Remove a Spare Disk or a RAID Volume

The `remove spare` subcommand removes disks global spares or as dedicated spares on a RAID volume.

- **Do one of the following:**

- **To remove two disks as global spares, type:**

```
raidconfig remove spare -d disk,disk
```

For example:

```
raidconfig remove spare -d c1d0,c1d1
```

- **To remove two disks as dedicated spares on a RAID volume, type:**

```
raidconfig remove spare -d disk,disk -r raidvolume
```

For example:

```
raidconfig remove spare -d c1d0,c1d1 -r c1r0
```

This subcommand requires the options shown in the following table.

Short Option	Long Option	Description
-d	--disks	Specifies disks to remove. Disk ID numbers are separated by commas. If the -r option is not defined, the disks are removed as global spares.
-r	--raid	If a RAID volume ID is specified, the disks should be removed as dedicated spares from this RAID volume.

Modifying a RAID Volume or Controller

This section covers the following information:

- [“Modify a RAID Volume” on page 154](#)
- [“Modify a Controller” on page 155](#)
- [“Modify the BIOS Boot Target” on page 155](#)
- [“Disable Auto Rebuild” on page 156](#)
- [“Modify a RAID Volume Name” on page 156](#)
- [“Enable or Disable JBOD Mode” on page 156](#)

▼ Modify a RAID Volume

The `modify raid` subcommand modifies the attributes of a RAID volume.

- **To modify a RAID volume, type:**

```
raidconfig modify raid -r raidvolume option
```

For example:

```
raidconfig modify raid -r c0r0 --write-cache=disabled
```

The `modify raid` subcommand requires the option shown in the following table.

Short Option	Long Option	Description
-r	--raid	Specifies the RAID volume to modify. This is required for the <code>modify raid</code> subcommand.

The following table lists additional options for the `modify raid` subcommand.

Option	Description
--name	Specifies the user-defined name to identify the RAID volume. Can be set to an empty string ("").
--read-cache	Write cache can be one of the following: disabled – Disables RAID read caching enabled – Enables RAID read caching enabled_adaptive – Enables RAID read adaptive caching
--write-cache	Write cache can be one of the following: disabled – Disables RAID write caching. enabled – Enables RAID write caching. enabled_protect – Enables caching only if the battery is available.
--bios-boot-target=true	Sets the boot target. When this option is set to true for a specific RAID volume, that RAID volume becomes the BIOS boot target.

▼ Modify a Controller

The `modify controller` command modifies certain controller attributes.

- **To modify a controller, type:**

```
raidconfig modify controller -c controller option
```

For example:

```
raidconfig modify controller -c c1 --disable-auto-rebuild=true
```

The `modify controller` subcommand requires the option shown in the following table.

Short Option	Long Option	Description
-c	--controller	Specifies the controller to modify. This is required for the <code>modify controller</code> subcommand.

The following table lists an additional option for the `modify controller` subcommand.

Option	Description
--disable-auto-rebuild=true false	Disables auto rebuild. When this option is set to true for a specific controller, auto rebuild will be disabled. If the option is set to false, a hot spare can automatically replace a faulty disk, in which case a long running background task is started.

Note - Not all controllers support modifications of `--disable-auto-rebuild`.

▼ Modify the BIOS Boot Target

The RAID volume with ID 0 is the default boot target. If you want to change the boot target, use the `--bios-boot-target` option.

- **To change the bios boot target, type:**

```
raidconfig modify raid -r raidvolume --bios-boot-target=true
```

For example:

```
raidconfig modify raid -r c0r0 --bios-boot-target=true
```

▼ Disable Auto Rebuild

When a hotspare disk replaces a faulty disk, it will start autobuilding the volume to use the hotspare disk if auto rebuild is enabled. If you do not want to start the long-running background task automatically, you can disable this feature.

- **To disable auto rebuild, type:**

```
raidconfig modify controller -c controller id --disable-auto-rebuild=true
```

For example:

```
raidconfig modify controller -c c0 --disable-auto-rebuild=true
```

▼ Modify a RAID Volume Name

To modify the user-specified name of a RAID volume:

- **To change the user-specified name of a RAID volume, type:**

```
raidconfig modify raid -r raidvolume --name name
```

For example:

```
raidconfig modify raid -r c0r0 --name engineering
```

▼ Enable or Disable JBOD Mode

For a system with an Oracle Storage 12 Gb SAS RAID PCIe HBA, Internal (7110116, 7110117) installed, you have the option to enable JBOD mode so that the underlying operating system can have the access to a disk directly without creating a RAID volume first. If JBOD mode is not enabled, the underlying operating system is not able to see the disk until the disk is included in a RAID volume.

You can enable JBOD mode on either a disk or controller. If you enable JBOD mode on the controller, all the disks on that controller will be in JBOD mode. Disk JBOD mode cannot be enabled until its controller has JBOD mode enabled.

Note - Do not disable JBOD mode on a controller if one of its disks in JBOD mode has the OS installed on it. Also, do not disable JBOD mode on an individual disk if that disk has the OS installed on it.

1. To enable or disable JBOD mode on a controller, type:

```
raidconfig modify controller -c controller --jbod enabled|disabled
```

When you enable JBOD mode on the controller, all the disks on that controller will be in JBOD mode. Disks can then have JBOD mode enabled or disabled individually. If you disable JBOD mode on a controller, any disks in JBOD mode will have JBOD mode disabled.

2. To enable or disable JBOD mode on a disk, type:

```
raidconfig modify disk -d disk --jbod enabled|disabled
```

The following example shows output for JBOD mode enabled on c0, then disabled on just disk 7.

```
CONTROLLER c0
=====
Manufacturer  Model                      F/W Version  RAID Volumes  Disks
-----
LSI Logic     MegaRAID 9361-8i          4.220.20-3050  1              8

RAID Volumes
=====
ID   Name      Device           Status  Num Disks  Level  Size (GiB)
-----
c0r1 OEL       /dev/sda         OK      1           0      465

DISKS In Use
=====
ID   Chassis  Slot  RAID ID  Status  Type  Media  Spare  Size (GiB)
-----
c0d0  0        0     c0r1    OK      sata  HDD    -      465

DISKS Available
=====
ID   Chassis  Slot  RAID ID  Status  Type  Media  Spare  Size (GiB)
-----
c0d1  0        1     -        JBOD   sas   HDD    -      137
c0d2  0        2     -        JBOD   sas   HDD    -      137
c0d3  0        3     -        JBOD   sas   HDD    -      137
c0d4  0        4     -        JBOD   sas   HDD    -      137
c0d5  0        5     -        JBOD   sas   HDD    -      137
c0d6  0        6     -        JBOD   sata  HDD    -      466
```

c0d7 0 7 - OK sata HDD - 466

Starting or Stopping a Task on a Disk or RAID

The `start task` and `stop task` subcommands control the execution of maintenance tasks on a disk or RAID volume.

- [“Executing Tasks on a Disk or RAID Volume” on page 158](#)
- [“Start or Stop a Task on a Disk or RAID Volume” on page 159](#)

Executing Tasks on a Disk or RAID Volume

There are a variety of tasks that can be run on a RAID volume and its disks using the `start task` or `stop task` subcommands.

The available background tasks are shown in the following table.

Task	Description
<code>verify</code>	Checks the validity of the RAID volume redundant data.
<code>init</code>	Initializes the RAID volume to write out the initial parity values. The initialization goes over the entire volume and initializes the parity data.
<code>copy</code>	Copies and moves an online physical disk onto a hotspare or unconfigured good drive. The copy is performed while the volume is online. Once completed, the destination disk is added to the logical volume configuration while the original source disk is removed from it.
<code>rebuild</code>	Regenerates the data of a single physical disk that is part of a logical volume with data redundancy. The physical disk is reconstructed from another physical disk and/or parity disks. A disk rebuild typically occurs after a disk replacement or repair.
<code>clear</code>	Clears a physical disk by writing zeroes over the entire disk.

Note - Not all devices support all tasks. To check the tasks a device supports, use the `list` subcommand and check the output under `Startable tasks`. If this field is blank, the device does not support any tasks.

The `start task` and `stop task` subcommands accept the options shown in the following table.

Short Option	Long Option	Description
-t	--task	Specifies the type of task to execute. Possible options are <code>verify</code> , <code>init</code> , <code>rebuild</code> , <code>clear</code> , or <code>copy</code> .
-d	--disk	Specifies the disk to execute the task on. Required by the <code>rebuild</code> and <code>clear</code> tasks.
-r	--raid	Specifies the RAID volume to execute the task on. Required by the <code>verify</code> and <code>init</code> tasks.
n/a	--src-disk	Specifies the source disk to use in a <code>copy</code> task.
n/a	--dst-disk	Specifies the destination disk to use in <code>copy</code> task.

▼ Start or Stop a Task on a Disk or RAID Volume

The `start task` and `stop task` subcommands control the execution of maintenance tasks on a disk or RAID volume. For more information on available tasks and options, see [“Executing Tasks on a Disk or RAID Volume” on page 158](#).

● To start or stop a task on a disk or RAID volume, type:

```
raidconfig start task -t taskname [-d|-r]
```

or

```
raidconfig stop task -t taskname [-d|-r]
```

The following are command examples for the `start task` and `stop task` subcommands:

- A RAID ID must be provided for the `verify` check (`verify`) and initialization task (`init`).
 - To start the `verify` task on a specified RAID volume, type:


```
raidconfig start task -t verify -r=raidvolume
```

 For example:


```
raidconfig start task -t verify -r=c0r1
```
 - To stop the `init` task on a specified RAID volume, type:


```
raidconfig stop task -t init -r=raidvolume
```

 For example:


```
raidconfig stop task -t init -r=c0r1
```
- A disk must be provided for the `rebuild` and `clear` tasks.
 - To start the `rebuild` task on a specified disk, type:


```
raidconfig start task -t rebuild -d=disk
```

 For example:

```
raidconfig start task -t rebuild -d=c0d1
```

Note - This can only be run on a disk that is part of a RAID volume.

- To start the `clear` task on a specified disk, type:

```
raidconfig start task -t clear -d=disk
```

For example:

```
raidconfig start task -t clear -d=c0d1
```

Note - This can only be run on a disk that is not part of a RAID volume.

- Source and destination disks must be provided for the copy task.

To start the copy task from one disk to another, type:

```
raidconfig start -task -t copy --src-disk=source_disk --dst-disk=destination_disk
```

For example:

```
raidconfig start -task -t copy --src-disk=c0d2 --dst-disk=c0d3
```

Note - The source disk must be in a RAID volume. The destination disk cannot be in a RAID volume.

Restoring or Clearing a RAID Controller Configuration

This section covers the following information:

- [“Check to See If a Controller Configuration Exists” on page 160](#)
- [“Restore a RAID Controller Configuration” on page 161](#)
- [“Clear a RAID Controller Configuration” on page 161](#)

▼ Check to See If a Controller Configuration Exists

1. To determine if an old configuration exists on the disks, view the controller's verbose properties. Type:

```
raidconfig list controller -v
```

The controller's properties are listed.

2. **View the property Disks In Use by Another Controller.**
 - a. **If the Disks In Use by Another Controller property is set to True, then an old configuration exists. This can be either restored or cleared.**
 - b. **If the Disks In Use by Another Controller property is set to False, then an old configuration does not exist.**

Note - If an old configuration does not exist and you attempt to run the `restore config` or `clear config` subcommands, `raidconfig` displays an error.

▼ Restore a RAID Controller Configuration

The `restore config` subcommand finds a RAID configuration stored on disks and restores this configuration to the destination controller.

- **To restore a RAID configuration saved on disks to a defined controller, type:**

```
raidconfig restore config -c=controller_id
```

where *controller_id* is the controller the RAID configuration is restored to.

The `restore config` subcommand requires the options shown in the following table.

Short Option	Long Option	Description
-c	--controller	Specifies the controller ID.

▼ Clear a RAID Controller Configuration

The `clear config` subcommand finds a RAID configuration stored on disks and removes the configuration.

- **To clear a RAID configuration saved on disks, type:**

```
raidconfig clear config -c=controller_id
```

where *controller_id* is the controller the RAID configuration is cleared from.

The `clear config` subcommand requires the options shown in the following table.

Short Option	Long Option	Description
-c	--controller	Specifies the controller ID.

Exporting or Importing a RAID Volume Configuration

This section covers the following information:

- [“Export a RAID Volume Configuration” on page 162](#)
- [“Import a RAID Volume Configuration” on page 163](#)

▼ Export a RAID Volume Configuration

The `export` subcommand writes XML-formatted configuration or inventory data to a file. Inventory data is a snapshot of all the fields for the controllers, RAID volumes, and disks. Configuration data contains only attributes that can be set and imported onto another system to configure that system's RAID volumes in the same manner.

The `export` subcommand requires a file name as a modifier. If a file by that name exists, the tool prompts to overwrite the file (unless the `-y` option is used). If the hyphen (-) is given for the filename, then the XML-formatted configuration is written to the screen.

- **To export the inventory or a configuration and write it to a file, do one of the following:**

- **To export the inventory data and write it to a file, type:**

```
raidconfig export inventory filename.xml
```

- **To export a configuration and write it to a file, type:**

```
raidconfig export config filename.xml
```

This subcommand requires at least one of the types shown in the following table.

Option	Description
inventory	Exports and writes all controller, RAID volume, and physical disk information to an XML file.
config	Exports and writes only configuration fields that can be imported to another system to an XML file.

▼ Import a RAID Volume Configuration

The `import` subcommand reads an XML-formatted configuration file and configures RAID volumes based on the file. If the creation of a specific RAID volume fails, the error is logged and the next RAID volume in the file is created.

The `import` subcommand requires the `config` type and a file name for the XML file.

Note - You cannot import a configuration into a system if the configuration includes disks that are already defined in a RAID volume or as a spares.

- **To configure the RAID volumes according to a configuration file, type:**

```
raidconfig import config filename.xml
```

Creating RAID Volumes With Partial Disks

The `--subdisk-size` option is available for the `raidconfig create` command to define the size of RAID volumes. This option is used to define the size of the partial disks to be used in a RAID volume.

This section covers the following information:

- [“Guidelines for Using the RAID Volume Size Option” on page 164](#)
- [“Partial Disk Properties in XML File ” on page 165](#)
- [“Create a RAID Volume with Partial Disks” on page 165](#)
- [“Adding or Removing a Partial Disk” on page 166](#)

Guidelines for Using the RAID Volume Size Option

Keep the following guidelines in mind when using the RAID volume `--subdisk-size`:

- The total sizes for the RAID volumes designated in the `--subdisk-size` option cannot exceed the available size for any of the disks. The total size can be less than or equal to the disk size, but it cannot be larger.
- You cannot create a RAID volume using a partial disk on a disk that is configured as part of a RAID volume. Once a disk has been included in a RAID volume, the disk is marked as "In Use" and cannot be used to create another RAID volume, even if just a part of the disk is used.

For example, the following sequence of commands is not allowed:

```
# raidconfig create raid --disk=c0d0,c0d2 --subdisk-size=50

# raidconfig create raid --disk=c0d0,c0d2 --subdisk-size=100
```

The second command results in an error.

- When creating multiple RAID volumes at the same time using the `--subdisk-size` option, all of the RAID volumes are configured with the same name if the `--name` option is used. If this occurs, you can rename the volumes using the `raidconfig modify` command.
- You can delete a RAID volume on a partial disk, but if the partial disk is used in another RAID volume, the disk will be marked as "In Use". You will not be able to create another RAID volume using that disk.

Disk Display

The `list all` subcommand indicates that a disk is part of more than one RAID volume. A row is added for each disk/raid combination under the `DISKS In Use` list.

The `Size` column shows the size of the subdisk used to create the RAID volume.

The following is an example of the `Disks In Use` output:

```
DISKS In Use
=====
ID      Chassis  Slot  RAID ID  Status  Type  Media  Spare  Size (GiB)
-----
```

c0d0	0	17	c0r0	OK	sas	HDD	-	50
c0d0	0	17	c0r1	OK	sas	HDD	-	100
c0d0	0	17	c0r2	OK	sas	HDD	-	200
c0d2	0	18	c0r0	OK	sas	HDD	-	50
c0d2	0	18	c0r1	OK	sas	HDD	-	100
c0d2	0	18	c0r2	OK	sas	HDD	-	200

Partial Disk Properties in XML File

If a RAID volume was created using partial disks, `raidconfig` stores the size of the sub-disk in the XML output generated by the `export` command. An example of a disk property is shown below:

```
<disk>
<chassis_id>0</chassis_id>
<slot_id>1</slot_id>
<subdisk_size>100</subdisk_size>
</disk>
```

▼ Create a RAID Volume with Partial Disks

Use the `--subdisk-size` option with the `raidconfig create` to create a RAID volume with partial disks:

- **To create a RAID volume with partial disks, type:**

```
raidconfig create raid --disk=disks --subdisk-size=sizes
```

For example, the following command creates three RAID volumes with subdisks within disks `c0d0` and `c0d2` sized at 50, 75, and 100 GB:

```
raidconfig create raid --disk=c0d0,c0d1 --subdisk-size=50,75,100
```

Create RAID level 0 volumes using disk sizes 50, 75, 100 from the following disk(s):

```
Disk c0d0 (controller 0 slot 0)
Disk c0d1 (controller 0 slot 1) [y/n]? y
RAID created successfully
```

If the `--subdisk-size` option is not used, the `raidconfig create` command creates a single RAID volume from the defined disks.

Adding or Removing a Partial Disk

The add and remove subcommands are supported for partial disks. If a disk contains multiple RAID volumes, they can be added and removed. For information on using the `raidconfig` add and remove commands, see [“Adding and Removing Disks and RAID Volumes” on page 150](#).

Note - When the disk supports multiple RAID volumes, only use the first RAID volume in the add and remove commands.

An example of removing a disk is shown below:

```
raidconfig remove disk -r=c0r4 -d=c0d0
```

```
Removing the following disk(s) from RAID c0r4:
Disk c0d0 (controller 0 slot 0) [y/n]? y
Successfully removed disk from RAID
```

```
raidconfig list all
```

```
CONTROLLER c0
```

```
=====
```

Manufacturer	Model	F/W Version	RAID Volumes	Disks
LSI Logic	0x0079	2.130.353-1803	6	7

```
RAID Volumes
```

```
=====
```

ID	Name	Device	Status	Num Disks	Level	Size (GiB)
c0r0	0	c3t0d0p0	OK	1	0	558
c0r1		c3t1d0p0	OK	1	0	278
c0r2		c3t2d0p0	OK	1	0	136
c0r3		c3t3d0p0	OK	1	0	70
c0r4		c3t4d0p0	DEGRADED	2	1	50
c0r5		c3t5d0p0	DEGRADED	2	1	100

```
DISKS In Use
```

```
=====
```

ID	Chassis	Slot	RAID ID	Status	Type	Media Spare	Size (GiB)
c0d1	0	1	c0r4	OK	sas	HDD	50
c0d1	0	1	c0r5	OK	sas	HDD	100
c0d3	0	3	c0r0	OK	sas	HDD	558
c0d4	0	4	c0r1	OK	sas	HDD	278
c0d5	0	6	c0r3	OK	sas	HDD	70
c0d6	0	7	c0r2	OK	sas	HDD	136

DISKS Available

```
=====
```

ID	Chassis	Slot	RAID ID	Status	Type	Media	Spare	Size (GiB)
c0d0	0	0	-	OK	sas	HDD	-	279
c0d2	0	2	-	OK	sas	HDD	-	279

The following is an example of adding a disk:

```
raidconfig add disk -r=c0r4 -d=c0d2
```

```
Adding the following disk(s) to RAID c0r4:
Disk c0d2 (controller 0 slot 2) [y/n]? y
Successfully added disk to RAID
```

```
raidconfig list all
```

CONTROLLER c0

```
=====
```

Manufacturer	Model	F/W Version	RAID Volumes	Disks
LSI Logic	0x0079	2.130.353-1803	6	7

RAID Volumes

```
=====
```

ID	Name	Device	Status	Num Disks	Level	Size (GiB)
c0r0	0	c3t0d0p0	OK	1	0	558
c0r1		c3t1d0p0	OK	1	0	278
c0r2		c3t2d0p0	OK	1	0	136
c0r3		c3t3d0p0	OK	1	0	70
c0r4		c3t4d0p0	DEGRADED	2	1	50
c0r5		c3t5d0p0	DEGRADED	2	1	100

DISKS In Use

```
=====
```

ID	Chassis	Slot	RAID ID	Status	Type	Media	Spare	Size (GiB)
c0d1	0	1	c0r4	OK	sas	HDD	-	50
c0d1	0	1	c0r5	OK	sas	HDD	-	100
c0d2	0	2	c0r4	INIT	sas	HDD	-	50
c0d2	0	2	c0r5	INIT	sas	HDD	-	100
c0d3	0	3	c0r0	OK	sas	HDD	-	558
c0d4	0	4	c0r1	OK	sas	HDD	-	278
c0d5	0	6	c0r3	OK	sas	HDD	-	70
c0d6	0	7	c0r2	OK	sas	HDD	-	136

DISKS Available

Create a RAID Volume with Partial Disks

```
=====
ID      Chassis  Slot  RAID ID  Status  Type  Media Spare  Size (GiB)
-----
c0d0    0        0     -        OK      sas   HDD   -        279
```

Using ubiosconfig to Update the UEFI BIOS

ubiosconfig provides a CLI tool for configuring BIOS on Oracle x86 servers that support UEFI BIOS. For other x86 systems, use the biosconfig tool. See [“Using biosconfig to Update the BIOS” on page 23](#).

ubiosconfig enables you to save server UEFI BIOS settings to an XML file, then load the settings from the XML file to configure UEFI BIOS settings on another server. For more information on UEFI BIOS, see your server documentation.

For information on the systems supported for each tool, refer to the support matrix at:

<http://www.oracle.com/goto/ohmp>

The following table shows the information covered in this section.

Description	Links
Overview of the ubiosconfig command syntax	“ubiosconfig Command Syntax” on page 169
Export UEFI settings	“Export UEFI Settings to an XML File” on page 171
Import UEFI BIOS settings	“Import UEFI BIOS Settings to a Server” on page 172
Display changes to UEFI BIOS settings	“Display Information on Changes to UEFI BIOS Settings” on page 172
Cancel pending UEFI BIOS settings	“Cancel Pending Changes to UEFI BIOS Settings” on page 173
Reset the UEFI BIOS settings	“Reset the UEFI BIOS Settings to Factory Default” on page 173

ubiosconfig Command Syntax

The ubiosconfig commands use the following command syntax:

```
ubiosconfig subcommand type [option]
```

If you use the `--help` or `--version` options, the `ubiosconfig` command does not require subcommands; otherwise one or more subcommands are mandatory.

When a command fails, it returns one of several failure codes listed in [“ubiosconfig Error Codes” on page 186](#).

The options listed in the following table apply to all CLI Tools commands including `ubiosconfig`.

Short Option	Long Option	Description
-?	--help	Displays help information.
-V	--version	Displays the tool version.

When accessing a service processor, `ubiosconfig` can be used over a local Host-to-ILOM interconnect or a remote Ethernet network connection. When issuing a `ubiosconfig` command that accesses the service processor, credentials are not required when using the Host-to-ILOM interconnect, but they are required for an Ethernet network connection.

Note - For systems with an Oracle ILOM version earlier than 3.2.4, to use a LAN interface (either the Host-to-ILOM interconnect or Ethernet network connection) you must manually include credentials using the `-H` and `-U` options for commands that access a service processor. If credentials are not provided the commands will default to the slower local KCS interface to access the local Oracle ILOM service processor.

The options listed in the following table are supported for `ubiosconfig` over a network connection.

Short Option	Long Options	Description
-H	--remote_hostname	This option is followed by the host name or IP address of the remote service processor.
-U	--remote_username	This option is followed by the user name with root access used to log in to the remote service processor.

For example:

```
ubiosconfig export all --remote_hostname=address --remote_username=username
```

where *address* is the remote host name or IP address (in `xx.xx.xx.xx` format) of the target server's service processor, and *username* is the user name with login access rights to perform the operation.

You are prompted for the password for this user name when accessing the remote Oracle ILOM service processor.

`ubiosconfig` supports the subcommands listed in the following table.

Subcommand	Function
<code>import</code>	Import a configuration XML file that will be applied to the server's UEFI BIOS at next boot.
<code>export</code>	Export the server's UEFI BIOS configuration to a local XML file.
<code>cancel</code>	Cancel pending UEFI BIOS configuration changes.
<code>list</code>	List status information regarding pending UEFI BIOS import or export operations.
<code>reset</code>	Reset the server's UEFI BIOS configuration to factory default at next boot.

▼ Export UEFI Settings to an XML File

The `export` subcommand exports a server's UEFI BIOS settings to an XML file.

- **To export UEFI BIOS settings to an XML file, type:**

```
ubiosconfig export type -x filename.xml option
```

where *type* is the supported type described below, *filename* is the optional path, and *option* is one of the options described below.

The supported type for `export` is listed in the following table.

Type	Description
<code>all</code>	Export all current server UEFI BIOS settings.

The supported options for `export` are listed in the following table.

Short Option	Long Option	Description
<code>-x</code>	<code>--xml_file</code>	The path to the XML file. Without this option, settings are displayed on the screen.
<code>-f</code>	<code>--force</code>	Ignore safeguards, and export BIOS XML file regardless of current system state.

Note - There is no guarantee of accuracy in the data when using the `--force` option.

▼ Import UEFI BIOS Settings to a Server

The `import` subcommand imports UEFI BIOS settings stored in an XML file to the server at next boot.

- **To import UEFI BIOS settings stored in an XML file, type:**

```
ubiosconfig import type -x filename.xml option
```

where *type* is one of the options described below, *filename* is the path to the XML file you want to import settings from and *option* is one of the options described below.

The supported types of import are listed in the following table.

Type	Description
all	Import all options from the XML file to the server's BIOS at next boot.
boot	Import only boot options from the XML file to the server's BIOS at next boot.
config	Import only configuration options from the XML file to the server's BIOS at next boot.

The possible option for the import is listed in the following table.

Short Option	Long Option	Description
-f	--force	Ignore safeguards, and import BIOS XML file regardless of current system state. Potentially dangerous and not recommended.

Note - There is no guarantee of accuracy in the data when using the `--force` option.

▼ Display Information on Changes to UEFI BIOS Settings

The `list` subcommand in conjunction with `type status` displays information about pending changes to UEFI BIOS settings at the next server boot.

- **To display information on UEFI BIOS setting changes, type:**

```
ubiosconfig list status
```

▼ Cancel Pending Changes to UEFI BIOS Settings

The `cancel` subcommand in conjunction with `type config` cancels any pending changes to UEFI BIOS settings.

- To cancel pending changes to UEFI BIOS settings, type:

```
ubiosconfig cancel config
```

▼ Reset the UEFI BIOS Settings to Factory Default

The `reset` subcommand resets the UEFI BIOS settings to factory defaults at the next server boot.

- To reset the UEFI BIOS settings to factory default, type:

```
ubiosconfig reset type
```

where *type* is one of the supported types listed in the following table.

Type	Description
<code>config</code>	Reset the server's UEFI BIOS to factory defaults at next power cycle. Any pending UEFI BIOS changes from <code>ubiosconfig</code> are added to the factory defaults.
<code>cancel</code>	Cancel any pending reset change to the server's UEFI BIOS settings.

Using `zoningcli` to Configure Zoning for the SPARC T3-1 Server

`zoningcli` provides a CLI tool for configuring zoning on Oracle SPARC T3-1 servers with the following qualifications:

- Runs Oracle Solaris OS.
- Has a 16-disk backplane (SAS-2 expander).
- If your Oracle SPARC T3-1 server is using the two on-board hard disk controllers, the 16-disk backplane *must* be zoned.
- If the server is using the SGX-SAS6-R-INT-Z SAS2 internal PCIe RAID HBA, the 16 disk backplane must *not* be zoned.

`zoningcli` can split zoning into two separate zones:

- Zone A (group 10) has the first 8 disks (PHY 0 - 7) and the first controller (PHY 20 -23)
- Zone B (group 11) has the last 8 disks (PHY 8 - 15) and the second controller (PHY 16-19)

Before attempting to change the server's zoning state, read the product notes pertaining to the 16 disk backplane.

You must have root permission to run `zoningcli`.

This section covers the topics shown in the following table.

Description	Links
Learn about the <code>zoningcli</code> command.	“zoningcli Command Overview” on page 176
Check the current zoning information.	“List Zoning Information” on page 176
Enable or disable zoning.	“ Enable and Disable Zoning” on page 177
Set up the expander in a pre-defined zoning configuration.	“Configure Zoning” on page 177

zoningcli Command Overview

The zoningcli commands use the following command syntax:

zoningcli *subcommand*

You must have root permission to run the zoningcli command.

The options listed in the following table apply to all CLI Tools commands, including zoningcli.

Short Option	Long Option	Description
-?	--help	Help—Displays help information.
-V	--version	Version—Displays the tool version.

If you use the --help or --version options, the zoningcli command does not require subcommands, otherwise one or more subcommands are mandatory.

zoningcli supports the subcommands listed in the following table.

Command	Function
enable	Enable the zoning.
disable	Disable the zoning.
list	Show the current zoning information.
config	Set up the expander in a pre-defined zoning configuration.

▼ List Zoning Information

The following procedure describes how to use the list subcommand to check the current zoning information. This enables you to see if zoning is currently enabled or disabled.

- **To list zoning information, type:**

zoningcli list expander

The current zoning information is listed.

▼ Enable and Disable Zoning

The following procedure describes how to use the `enable zoning` and `disable zoning` subcommands to control zoning. Zoning is set up by default.

1. **To enable zoning, type:**
`zoningcli enable zoning`
2. **To disable zoning, type the following command:**
`zoningcli disable zoning`

▼ Configure Zoning

Use the `config` subcommand to set up the expander in a pre-defined zoning configuration.

- **To set up the expander in a pre-defined zoning configuration, type:**
`zoningcli config zoning`

CLI Tools Error Codes

The following table shows the information covered in this section.

Description	Links
View error codes common to all CLI tools	“Common Error Codes” on page 179
View error codes for <code>biosconfig</code>	“biosconfig Error Codes” on page 180
View error codes for <code>firmware-check</code>	“firmware-check Error Codes” on page 181
View error codes for <code>fwupdate</code>	“fwupdate Error Codes” on page 181
View error codes for <code>hwmgmtcli</code>	“hwmgmtcli Error Codes” on page 182
View error codes for <code>ilomconfig</code>	“ilomconfig Error Codes” on page 183
View error codes for <code>nvmeadm</code>	“nvmeadm Error Codes” on page 184
View error codes for <code>raidconfig</code>	“raidconfig Error Codes” on page 184
View error codes for <code>ubiosconfig</code>	“ubiosconfig Error Codes” on page 186
View error codes for <code>zoningcli</code>	“zoningcli Error Codes” on page 187

Common Error Codes

The following table lists the common command error codes. Each error code has a string associated with it. The error code is printed to the log file and to the `stdout` file.

Code Number	Error Description
0	OK.
1	Invalid option.
2	Invalid subcommand.
3	Subcommand not supported.
4	Invalid device format.
5	Cannot create XML file.

Code Number	Error Description
6	Cannot read XML file.
7	Cannot retrieve application data.
8	Internal error.
9	Insufficient memory.
10	Invalid boolean argument.
11	Option not supported.
12	Storage library initialization failure.
13	Entered name is too long.
14	Invalid name after subcommand.
15	XML filename required.
16	Invalid argument.
17	Failure writing XML file.
18	Device is busy, command cannot be completed.
19	User terminated by pressing ctrl-c.
20	Insufficient privilege to execute command.
21	One or more arguments are missing.
22	Unsupported XML file. Please see errors.
23	XML parse failure.
24	Cannot find XML file.
25	XML file contains no records.
26	The current directory is not writeable.
27	Invalid type.
28	The prerequisite criteria fails priority requirement.
29	Prerequisite criteria causes forever loop.
30	IPMI timeout. Wait a few sections and try again.
31	Installation issues detected.
32	Platform not supported.
33	Oracle ILOM version not supported.
34	Command cannot be run in virtual environment.
35	Unlink file failure.
92	Interface already exists.

biosconfig Error Codes

The following table lists the biosconfig errors and the actions to take when they occur.

Error Number (s)	Description
Error 64	Execute biosconfig as root. Note - Do not run more than one instance of biosconfig at the same time. There are no locks in place (for any OS) to allow for multiple simultaneous accesses.

firmware-check Error Codes

The following table lists the `firmware-check` error codes.

Code Number	Error Description
34	Command cannot be run in virtual environment.
40	XML metadata read access error.
41	XML metadata version error.
42	Firmware is older than minimum required version.
43	XML metadata is not complete.
45	Firmware checking is not supported on systems with ILOM versions older than 3.0.2.

fwupdate Error Codes

The following table lists the `fwupdate` command error codes.

You can also list the error codes using the `fwupdate list error-codes` command. See [“list Subcommand Overview” on page 61](#) for more information.

Code Number	Error Description
200	Invalid device type.
201	Invalid device target type.
202	Invalid device ID, please run <code>fwupdate list all</code> to verify id.
203	Reset of component failed.
204	Firmware check failed for component.
205	Firmware download failed for component.
206	Specified component and specified image type do not match.
207	Must specify an image file name when doing an update.

Code Number	Error Description
208	Could not read specified image file.
209	Reset of this component type is not supported.
210	Specified component type does not match devices type.
211	Must specify device to update.
212	Update canceled by user.
213	Firmware version information not available. Reset necessary to activate new firmware.
214	Version verification failed.
215	Final version is being reported the same as the starting version. Update may have succeeded, please check update documentation.
216	Missing or corrupt firmware file referenced by firmware metadata file.
217	Metadata file invalid or corrupt.
218	Metadata error. Prerequisite and priority settings conflict.
219	Power control option is not supported for pre-application.
220	Power control option is not supported for post-application.
221	Power Control option is not supported.
222	Requested component not available.
223	Can't verify version information, no XML provided.
224	Metadata does not include support for this host.
225	Could not identify host type.
226	A valid subcommand required.
227	Invalid option entered.
228	Must specify device to reset.
229	Cannot open file to write XML output.
230	Metadata XML file is required.
231	Invalid priority level entered.
232	Cannot read firmware metadata XML file.
233	Missing required command argument.

hwmgmtcli Error Codes

The following table lists the hwmgmtcli command error codes.

Code Number	Error Description
242	Initialize HDL library failure.
243	HDL library command failure.

ilomconfig Error Codes

The following table lists the ilomconfig error codes.

Code Number	Error Description
50	Cannot connect to BMC interface.
51	Missing -username option.
52	Missing -password option.
53	User already exists.
54	Missing -communityname option.
55	Specified community already exists.
56	User does not exist.
57	Community name does not exist.
58	Delete failed.
59	Failures occurred during restore.
60	Must specify option to modify.
61	No such property.
62	Invalid user name length.
63	Invalid role value.
64	Invalid permission value.
65	Invalid password length.
66	Invalid IP discovery value.
67	Invalid IP state value.
68	Invalid IP address.
69	Invalid auto DNS value.
70	Invalid Use NTP value.
71	Product serial number does not match current system.
72	Oracle ILOM error occurred.
73	Cannot modify interconnect when disabled (use enable command).
74	ILOM not reachable over internal LAN.
75	Credential Failure.
76	Cannot manage interconnect when hostmanaged is set to false.
77	Could not connect to remote SP by LAN with supplied credentials.
78	Specified Command can not be used with a remote connection.
79	Oracle ILOM version does not support LAN over USB.
80	ILOM Interconnect required for fault forwarding.

Code Number	Error Description
81	SNMP timeout occurred while setting up fault forwarding.
82	Failed to configure ILOM SNMP correctly.
83	Service Processor has conflicting configuration. Refer to release notes for resolution.

nvmeadm Error Codes

The following table lists the nvmeadm error codes.

Code Number	Error Description
190	Invalid namespace.
191	Invalid controller.
192	Invalid block size and/or metadata size.
193	Command failed on one or more device(s).
194	Invalid directory name.
195	Operation canceled.

raidconfig Error Codes

Errors might be returned if you attempt to configure the RAID entry for an unsupported parameter. For example, if the RAID controller does not support the configured RAID level, the CLI displays a user-friendly error string identifying the misconfiguration and returns a matching error code.

The following table lists the error codes and strings specific to this tool.

Code Number	Error Description
100	No controllers available.
101	Controller does not support RAID.
102	No physical disks associated with controller.
103	Invalid controller.
104	Invalid disk.
105	Invalid RAID volume.
106	RAID level not supported by controller.

Code Number	Error Description
107	Default RAID level not supported.
108	A defined disk is in use.
109	Number of disks exceeds allowed number for this level.
110	Failure retrieving internal data.
111	Number of disks requested exceeds the number of available disks.
112	Cannot define both actual and requested number of disks.
113	Option not supported by controller.
114	Invalid stripe size for controller.
115	Invalid number of subarrays.
116	Cannot retrieve RAID data.
118	RAID creation failure.
119	RAID deletion failure.
120	Disk defined multiple times.
121	Disks must be in the same controller.
122	The maximum number of RAID Volumes has been created.
123	Invalid RAID configuration.
124	The RAID Volume is in use.
125	Incomplete RAID configuration.
126	Failure writing internal data.
127	Command requires disks to be entered.
128	Disk is not a dedicated spare.
129	Disk is not a global spare.
130	Controller does not support dedicated spares.
131	Controller does not support global spares.
132	Command requires disks or RAID volume to be entered.
133	A defined disk is not in a RAID volume.
134	Cannot set both read and write cache in same command.
135	Import could not create RAID volumes or spares - disks may be in use.
136	Subarrays option is required for this RAID level.
137	Incomplete command, no options have been supplied.
138	Number of disks requested exceeds the number of available disks with the same capacity.
139	RAID configuration does not have enough disks for the requested RAID level.
140	RAID configuration has too many disks for the requested RAID level.
141	Disk detected as in use by another controller. Use raidconfig restore or clear command.
142	The number of spares exceeds the maximum allowed by controller.
143	This command does not support the number-disks option.
144	Task type is invalid.

Code Number	Error Description
145	Task type must be defined.
146	Task type is only valid for disks.
147	Task type is only valid for RAID Volumes.
148	For this task, disk must not be in use.
149	For this task, disk must be in a RAID Volume.
150	Command currently cannot be executed.
151	The source disk must be in a RAID Volume.
152	The destination disk must not be in a RAID Volume.
153	The source and destination cannot be the same disk.
154	The source and destination are not the same size.
155	No foreign configuration detected for controller.
156	Unable to add disk to RAID Volume.
157	Task cannot be started, make sure task is listed in Startable Tasks.
158	Task cannot be stopped, make sure task is listed in Stoppable Tasks.
159	Invalid command, filename must come before options.
160	All disks must be the same size.
161	Command is not valid for this RAID level.
162	Subdisk sizes must be less than disk capacity.
163	Could not restore controller configuration.
164	The maximum number of subdisks is 16.
165	Invalid configuration, make sure spare is same size as disks in RAID Volume.
166	Disk mode is set to JBOD. Disable JBOD mode then try again.
167	Disk is in use by RAID controller. Remove from RAID configuration then try again.

ubiosconfig Error Codes

The following table lists the ubiosconfig errors.

Code Number	Error Description
50	Cannot connect to IPMI bmc device.
84, 85	Cannot update BIOS, update in progress.
86	Invalid configuration file provided.
87	Invalid boot configuration provided.
88	Invalid boot and configuration provided.
89	Failed to update BIOS.

Code Number	Error Description
90	BIOS partially updated.
91	BIOS out of sync.

zoningcli Error Codes

The following table lists the zoningcli command error codes.

Code Number	Error Description
250	Storage management library failure.
251	Zoning CLI SMP command failure.
252	Zoning CLI running on a not supported platform.
253	The expander does not have zoning support.

Index

A

automatic mode
 fwupdate
 update subcommand, 72

B

biosconfig, 23
 boot order
 next boot, 41
 overview, 40
 persistent, 42
 CMOS configuration, 44, 48
 dynamic setting, 49
 individual settings, 47
 static setting, 48
 CMOS golden image
 applying, 46
 capturing, 45
 device terminology, 24
 error codes, 180
 extraneous output, 50
 options, 26
 Oracle Solaris OS, 27
 overview, 23
 requirements, 24
 system management driver
 installing, 28, 35
 view commands, 38
 view version, 39
 Windows, 27
 XML files, 25
boot order

biosconfig
 device, 43
 function, 43
 next boot, 41
 PCI bus, 43
 persistent, 42
 configuring
 ipmitool, 126
 methods for changing, 40
boot target
 modify using raidconfig, 155

C

clock information
 listing, 104
 modifying, 109
CMOS
 applying golden image, 46
 capturing golden image, 45
 configuring dynamic setting, 49
 configuring individual settings, 47
 configuring static setting, 48
command syntax
 CLI tools common, 19

D

device naming
 CLI tools common, 20
disk
 adding, 151
 removing, 151

DNS information

- listing, 103
 - modifying, 108
- documentation links, 11

driver

- Windows 2003 SP1, 126

E

error codes

- biosconfig, 180
 - common, 179
 - firmware-check, 181
 - fwupdate, 181
 - hwmgmtcli, 182
 - ilomconfig, 183
 - nvmeadm, 184
 - raidconfig, 184
 - ubiosconfig, 186
 - zoningcli, 187
- exporting inventory data, 162

F

feedback, 11

firmware-check, 53

- command syntax, 54
- error codes, 181
- features, 54
- manually check firmware, 55
- prerequisites, 54

fwupdate, 57

automatic mode

- Oracle ILOM update, 75
- service processor update, 75
- system firmware update, 75

check subcommand, 70

- checking system firmware, 71
- overview, 70

command overview, 60

- description of automatic and manual modes, 72

error codes, 181

execution summary, 88

list subcommand, 61

- listing all components, 64
- listing specific components, 68
- overview, 61

network update, 59

Oracle ILOM update, 80

overview, 57

service processor update, 80

update subcommand

- automatic mode, 72
- single device mode, 80

H

Host-to-ILOM Interconnect

credential cache

- delete, 113
 - set up, 112
- disabling, 111

enabling, 17, 110

listing settings, 112

modifying, 111

hwmgmtcli, 89

command overview, 89

error codes, 182

exporting subsystem information, 92

listing subsystem information, 91

viewing open problems, 91

I

ilomconfig, 93

command usage, 95

creating a user, 105

creating SNMP community, 106

deleting a user, 105

error codes, 183

exporting XML configuration, 98

features, 94

importing XML configuration, 99

- IPv4 network settings
 - listing, 102
 - modifying, 106
 - IPv6 network settings
 - listing, 103
 - modifying, 107
 - listing clock information, 104
 - listing DNS information, 103
 - listing SNMP community, 102
 - listing SP information, 103
 - listing system summary information, 101
 - listing users, 102
 - modifying clock information, 109
 - modifying DNS information, 108
 - modifying identification information, 108
 - modifying Oracle ILOM XML files, 94
 - modifying user password, 105
 - modifying user role, 105
 - overview, 94
 - restoring Oracle ILOM defaults, 104
 - restoring Oracle ILOM XML files, 94
- ipmitool
- requirements, 125
- ipmitool driver
- installing for Windows 2003 SP1, 126
- IPv4
- listing network settings, 102
 - modifying network settings, 106
- IPv6
- listing network settings, 103
 - modifying network settings, 107
- L**
- listing system summary
 - ilomconfig, 101
 - local interconnect *See* Host-to-ILOM Interconnect
- M**
- manual mode
 - fwupdate
 - update subcommand, 80
- N**
- network settings
 - listing IPv4, 102
 - listing IPv6, 103
 - modifying IPv4, 106
 - modifying IPv6, 107
 - nvmeadm, 129
 - error codes, 184
- O**
- Oracle ILOM defaults
 - restoring, 104
 - Oracle ILOM ID information
 - modifying, 108
 - Oracle ILOM user
 - creating, 105
 - deleting, 105
 - Oracle ILOM user password
 - modifying, 105
 - Oracle ILOM user role
 - modifying, 105
 - Oracle ILOM users
 - listing, 102
 - Oracle ILOM XML configuration files
 - modifying, 94
 - restoring, 94
 - Oracle Solaris OS
 - biosconfig, 27
 - overview
 - CLI tools, 15
- P**
- partial disks
 - adding to RAID volume, 166
 - creating RAID volumes, 163
 - disk display, 164
 - exporting RAID configuration, 165

- guidelines for creating RAID, 164
- removing from RAID volume, 166

R

RAID controller configuration

- clearing, 161
- restoring, 161

RAID volume

- configuring from a file, 163
- creating, 149
- creating with partial disks, 163
- deleting, 150
- exporting with partial disks, 165
- name modify, 156

raidconfig, 139

- adding a disk, 151
- adding a spare, 152
- adding partial disks, 166
- auto rebuild disable, 156
- battery backup status, 148
- checking controller configuration, 160
- clearing RAID controller configuration , 161
- command overview, 141
- configuring RAID volumes from a file, 163
- create raid volume, 149
- creating RAID volumes with partial disks, 163
- delete raid volume, 150
- error codes, 184
- export inventory data, 162
- export subcommand, 162
- list subcommand, 142
- modify boot target, 155
- overview, 139
- RAID volume name modify, 156
- removing a disk, 151
- removing a spare, 153
- removing partial disks, 166
- requirements, 140
- restoring RAID controller configuration , 161
- size option
 - disk display, 164
 - guidelines, 163, 164

- start task subcommand, 158
- restore Oracle ILOM defaults
 - using XML configuration, 104

S

SNMP community

- creating, 106
- listing, 102

SP information

- listing, 103

spare disk

- adding, 152
- removing, 153

system management driver

- installing, 28, 35

U

ubiosconfig, 169

- cancel subcommand, 173
- command overview, 169
- error codes, 186
- export subcommand, 171
- import subcommand, 172
- list subcommand, 172
- reset subcommand, 173

W

Windows, 125

- biosconfig, 27

X

XML configuration

- exporting from Oracle ILOM, 98
- importing to Oracle ILOM, 99

Z

- zoningcli, 175

command overview, 176
disable zoning subcommand, 177
enable zoning subcommand, 177
error codes, 187
list expander subcommand, 176

