Gateway Documentation - Clearing Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.3.0.0

[April] [2014]

Table Of Contents

1. BACKGROUND 1
2. FCUBSCGService 2
2.1. AuthorizeClearingReject 2
2.1.1. CGRejection-Auth-Req-Full-MSG.xsd 2
2.1.2. CGRejection-Auth-Req-IO-MSG.xsd 15
2.1.3. CGRejection-Auth-Res-Full-MSG.xsd 21
2.1.4. CGRejection-Auth-Res-PK-MSG.xsd 35
2.2. CreateClearingReject 45
2.2.1. CGRejection-Create-Req-Full-MSG.xsd 45
2.2.2. CGRejection-Create-Req-IO-MSG.xsd 58
2.2.3. CGRejection-Create-Res-Full-MSG.xsd 66
2.2.4. CGRejection-Create-Res-PK-MSG.xsd 80
2.3. QueryClearingReject 90
2.3.1. CGRejection-Query-Req-MSG.xsd 90
2.3.2. CGRejection-Query-Res-Full-MSG.xsd 97
2.4. AuthorizeStopPayment 111
2.4.1. CGStopPayment-Auth-Req-Full-MSG.xsd 111
2.4.2. CGStopPayment-Auth-Req-MSG.xsd 123
2.4.3. CGStopPayment-Auth-Res-Full-MSG.xsd 129
2.4.4. CGStopPayment-Auth-Res-PK-MSG.xsd 142
2.5. CreateStopPayment 151
2.5.1. CGStopPayment-Create-Req-Full-MSG.xsd 151
2.5.2. CGStopPayment-Create-Req-MSG.xsd 163
2.5.3. CGStopPayment-Create-Res-Full-MSG.xsd 172
2.5.4. CGStopPayment-Create-Res-PK-MSG.xsd 185
2.6. QueryStopPayment 196
2.6.1. CGStopPayment-Query-Req-MSG.xsd 196
2.6.2. CGStopPayment-Query-Res-Full-MSG.xsd 203
2.7. AuthorizeTransaction 216
2.7.1. CGTransaction-Auth-Req-Full-MSG.xsd 216
2.7.2. CGTransaction-Auth-Req-MSG.xsd 276
2.7.3. CGTransaction-Auth-Res-Full-MSG.xsd 283
2.7.4. CGTransaction-Auth-Res-PK-MSG.xsd 345
2.8. CreateTransaction 354
2.8.1. CGTransaction-Create-Req-Full-MSG.xsd 354
2.8.2. CGTransaction-Create-Req-MSG.xsd 414
2.8.3. CGTransaction-Create-Res-Full-MSG.xsd 460
2.8.4. CGTransaction-Create-Res-PK-MSG.xsd 522
2.9. QueryTransaction 571
2.9.1. CGTransaction-Query-Req-MSG.xsd 571
2.9.2. CGTransaction-Query-Res-Full-MSG.xsd 578
2.10. ReverseTransaction 640
2.10.1. CGTransaction-Reverse-Req-Full-MSG.xsd 640
2.10.2. CGTransaction-Reverse-Req-MSG.xsd 700
2.10.3. CGTransaction-Reverse-Res-Full-MSG.xsd 707
2.10.4. CGTransaction-Reverse-Res-PK-MSG.xsd 769
2.11. QueryCcyClgHoliday 778
2.11.1. ST-QueryCcyClgHoliday-Req-IO-MSG.xsd 778
2.11.2. ST-QueryCcyClgHoliday-Res-Full-MSG.xsd 785

ORACLE

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSCGService of Branch-Module

2.FCUBSCGService

Clearing ServiceClearing Service

2.1.AuthorizeClearingReject

Authorize Cleading Reject

2.1.1.CGRejection-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*

INSTRAMT
INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.1.2.CGRejection-Auth-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details-IO*
    - *XREF*
    - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Clearing Reject Details IO Type

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

2.1.3.CGRejection-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the rejected clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description	
Name	INSTRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.4.CGRejection-Auth-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Reject-Details-IO*
      - *SCODE*
      - *XREF*
      - *TXNBRN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *ROUTINGNO*
      - *REASONCODE*
      - *REJECTREASON*
    - *Clearing-Reject-Details-PK*
      - *XREF*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the rejected clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Clearing Reject Details IO Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Clearing-Reject-Details-PK

Attribute	Description
Name	Clearing-Reject-Details-PK
Datatype	
Description	Clearing Reject Details PK Type

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Error Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.CreateClearingReject

Create Clearing Reject

2.2.1.CGRejection-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*

TXNDATE

VALDATE

LATECLG

ENDPOINT

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Creation Of Clearing Reject Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description

Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	**Description**
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	**Description**
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	**Description**
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3 pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description

Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	**Description**
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	

Attributes		
	Attribute	**Description**
	minOccurs	0
Restrictions		
	Restrictions	**Description**
	enumeration	A,U

TOP

ONCEAUTH

Attribute	**Description**	
Name	ONCEAUTH	
Datatype	String	
Description		
Attributes		
	Attribute	**Description**
	minOccurs	0
Restrictions		
	Restrictions	**Description**
	enumeration	Y,N

TOP

2.2.2.CGRejection-Create-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details-IO*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE

Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description

Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Creation Of Clearing Reject Details IO Type

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z_0-9]*

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.2.3.CGRejection-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for rejection of the updated clearing contract

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Creation Of Clearing Reject Details

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

ORACLE

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.CGRejection-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Clearing-Reject-Details-IO*
      - *SCODE*
      - *XREF*
      - *TXNBRN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *ROUTINGNO*
      - *REASONCODE*
      - *REJECTREASON*
    - *Clearing-Reject-Details-PK*
      - *XREF*
      - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for rejection of the updated clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	Creation Of Clearing Reject IO Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Clearing-Reject-Details-PK

Attribute	Description
Name	Clearing-Reject-Details-PK
Datatype	
Description	Creation Of Clearing Reject PK Type

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.QueryClearingReject

Query Clearing Reject

2.3.1.CGRejection-Query-Req-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Clearing-Reject-Details-IO
XREF
FCCREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

Clearing-Reject-Details-IO

Attribute	Description
Name	Clearing-Reject-Details-IO
Datatype	
Description	

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z0-9]{16}

TOP

2.3.2.CGRejection-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Clearing-Reject-Details*
    - *SCODE*
    - *XREF*
    - *TXNBRN*
    - *REMACCOUNT*
    - *INSTRNO*
    - *ROUTINGNO*
    - *REASONCODE*
    - *REJECTREASON*
    - *FCCREF*
    - *STATUS*
    - *BENACCOUNT*
    - *INSTRCCY*
    - *INSTRAMT*
    - *INSTRDATE*
    - *CHEQUEISSUEDATE*
    - *TXNDATE*
    - *VALDATE*
    - *LATECLG*

ENDPOINT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for the Query of cheque rejection

TOP

Clearing-Reject-Details

Attribute	Description
Name	Clearing-Reject-Details
Datatype	
Description	Query Of Clearing Reject Details Type

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

REASONCODE

Attribute	Description
Name	REASONCODE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 3 pattern / [a-zA-Z0-9]*

TOP

REJECTREASON

Attribute	Description
Name	REJECTREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENACCOUNT

Attribute	Description	
Name	BENACCOUNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

INSTRCCY

Attribute	Description	
Name	INSTRCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Warning Response Details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.AuthorizeStopPayment

Authorisation of Stop Payment

2.4.1.CGStopPayment-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the request message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the Clearing Authorisation of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description	
Name	STOPPAYNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description	
Name	STOPPAYTYPE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STARTCHKNO

Attribute	Description	
Name	STARTCHKNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENDCHKNO

Attribute	Description	
Name	ENDCHKNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description	
Name	CONF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	**Description**	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MODNO

Attribute	**Description**	
Name	MODNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	10

TOP

RECORDSTAT

Attribute	**Description**	
Name	RECORDSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	O,C

TOP

AUTHSTAT

Attribute	**Description**	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

2.4.2.CGStopPayment-Auth-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *XREF*
    - *STOPPAYNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the Clearing Authorisation of Stop Payment IO Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STOPPAYNO

Attribute	Description	
Name	STOPPAYNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9]*

TOP

2.4.3.CGStopPayment-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Authorisation of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 20; pattern = [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16; pattern = [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.4.4.CGStopPayment-Auth-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stop-Payment-Details-IO*
      - *XREF*
      - *STOPPAYNO*
    - *Stop-Payment-Details-PK*
      - *XREF*
      - *STOPPAYNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for authorisation of the Stop Payment

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	

Description	Includes the Authorisation of Stop Payment IO Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STOPPAYNO

Attribute	Description	
Name	STOPPAYNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9]*

TOP

Stop-Payment-Details-PK

Attribute	Description
Name	Stop-Payment-Details-PK
Datatype	
Description	Includes the Authorisation of Stop Payment Primary Key Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STOPPAYNO

Attribute	Description	
Name	STOPPAYNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	16
	pattern	[a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.CreateStopPayment

Input of Stop Payment

2.5.1.CGStopPayment-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the Clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 10

TOP

RECORDSTAT

Attribute	**Description**
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / O,C

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *REM*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description	
Name	ACC	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description	
Name	STOPPAYTYPE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

STARTCHKNO

Attribute	Description

Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

2.5.3.CGStopPayment-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for Stop Payment clearing contract

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Input of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

ORACLE

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.4.CGStopPayment-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Stop-Payment-Details-IO*
      - *SCODE*
      - *XREF*
      - *BRN*
      - *ACC*
      - *STOPPAYTYPE*
      - *STARTCHKNO*
      - *ENDCHKNO*
      - *AMT*
      - *EFFDT*
      - *EXPDT*
      - *REM*
    - *Stop-Payment-Details-PK*
      - *XREF*
      - *STOPPAYNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for Stop Payment of the updated clearing contract

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the Clearing Input of Stop Payment IO Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	**Description**
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

STARTCHKNO

Attribute	**Description**
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENDCHKNO

Attribute	**Description**
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

REM

Attribute	Description	
Name	REM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Stop-Payment-Details-PK

Attribute	Description
Name	Stop-Payment-Details-PK
Datatype	
Description	Includes the Clearing Input of Stop Payment Primary Key Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	

ORACLE

Restrictions	**Restrictions** / **Description** maxLength / 16 pattern / [a-zA-Z0-9]*

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.QueryStopPayment

Query of Stop Payment

2.6.1.CGStopPayment-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details-IO*
    - *XREF*
    - *STOPPAYNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the request message format for the Query of Stop Payment

TOP

Stop-Payment-Details-IO

Attribute	Description
Name	Stop-Payment-Details-IO
Datatype	
Description	Includes the clearing Query of Stop Payment Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	16
	pattern	[a-zA-Z0-9]*

TOP

2.6.2.CGStopPayment-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Stop-Payment-Details*
    - *SCODE*
    - *XREF*
    - *BRN*
    - *ACC*
    - *STOPPAYNO*
    - *STOPPAYTYPE*
    - *STARTCHKNO*
    - *ENDCHKNO*
    - *AMT*
    - *EFFDT*
    - *EXPDT*
    - *CONF*
    - *REM*
    - *CCY*
    - *ACCTITLE*
    - *MAKERID*
    - *MAKERSTAMP*
    - *CHECKERID*

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the response message format for the Query of Stop Payment

TOP

Stop-Payment-Details

Attribute	Description
Name	Stop-Payment-Details
Datatype	
Description	Includes the clearing Query of Stop Payment Details.

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRN

Attribute	Description	
Name	BRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 20; pattern = [a-zA-Z0-9]*

TOP

STOPPAYNO

Attribute	Description
Name	STOPPAYNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16; pattern = [a-zA-Z0-9]*

TOP

STOPPAYTYPE

Attribute	Description
Name	STOPPAYTYPE
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 1

TOP

STARTCHKNO

Attribute	Description
Name	STARTCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

ENDCHKNO

Attribute	Description
Name	ENDCHKNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 16

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

TOP

CONF

Attribute	Description
Name	CONF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REM

Attribute	Description
Name	REM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[A-Z]{3}

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Error Warning Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.7.AuthorizeTransaction

Authorisation of Clearing Transaction

2.7.1.CGTransaction-Auth-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM

ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

- *TXNMIS9*
- *TXNMIS10*
- *FUNDMIS1LBL1*
- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description

Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	**Description**
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	**Description**
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCCY

Attribute	**Description**
Name	ACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCCYAMT

Attribute	**Description**
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description	
Name	ROUTBNKCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description	
Name	ROUTBRNCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description	
Name	ROUTSECTCOD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description
Name	INSTRNO2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description
Name	CC_HOLDER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

REMBANK

Attribute	Description
Name	REMBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description	
Name	BENBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description	
Name	BENCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description	
Name	DENMCCY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT1

Attribute	Description	
Name	DENMAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACTAMT

Attribute	**Description**
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description	Specifies The MIS Group.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12
	minLength	1

TOP

REL_REF

Attribute	Description	
Name	REL_REF	
Datatype	String	
Description	Specifies The Related Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

REL_ACC

Attribute	Description	
Name	REL_ACC	
Datatype	String	
Description	Specifies The Related Account.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16
	minLength	1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.

Attributes	Attribute	Description
	minOccurs	0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 5 minInclusive / 0 totalDigits / 15

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked

Attributes	Attribute	Description
	minOccurs	0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8

Attribute	Description

Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	**Description**
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	**Description**
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	**Description**
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	**Description**
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

ORACLE

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

ORACLE

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.7.2.CGTransaction-Auth-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *Clearing-Details*
      - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

2.7.3.CGTransaction-Auth-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT

DENMCCY1

DENMAMT1

DENMCCY2

DENMAMT2

XRATE

DIRECTION

REMDET1

REMDET2

REMDET3

BENDET1

BENDET2

BENDET3

DIN

DINDATE

CUSTDATE

MODULE

MODREFNO

REJREASON

CUSTID

ACCTITLE

CUSTNAME

REMARKS

ACTAMT

MAKERID

MAKERSTAMP

CHECKERID

CHECKERSTAMP

MODNO

RECORDSTAT

AUTHSTAT

ONCEAUTH

STATUS

Mis-Details

BRANCH

CUSTNO

MISGRP

REL_REF

REL_ACC

MISHD

POOLCD

REFRT

REFRTTYPE

REFXRT

CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*

TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Authorized

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information related to Authorisation of Clearing Transaction.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	**Description**
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	Restrictions: fractionDigits = 3; totalDigits = 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENTRYNO

Attribute	Description	
Name	ENTRYNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description	
Name	REGCC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SPLCHQ

Attribute	Description	
Name	SPLCHQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TXNBRN

Attribute	Description	
Name	TXNBRN	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description
Name	INSTRNO2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

LCYCHGAMT

Attribute	Description
Name	LCYCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

CHGCCYLCYXRT

Attribute	Description
Name	CHGCCYLCYXRT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 12 Restrictions: totalDigits — Description: 24

TOP

LCYCHGAMT1

Attribute	Description
Name	LCYCHGAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

CHGCCYLCYXRT1

Attribute	Description
Name	CHGCCYLCYXRT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT2

Attribute	Description
Name	LCYCHGAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT2

Attribute	Description
Name	CHGCCYLCYXRT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT3

Attribute	Description
Name	LCYCHGAMT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT3

Attribute	Description
Name	CHGCCYLCYXRT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT4

Attribute	Description
Name	LCYCHGAMT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT4

Attribute	Description
Name	CHGCCYLCYXRT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

ACYTOTCHGAMT

Attribute	Description
Name	ACYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT2

Attribute	Description
Name	DENMAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description

Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	**Description**
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	**Description**
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	**Description**
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; pattern / [A-Z]*

TOP

MODREFNO

Attribute	**Description**
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	**Description**
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; minInclusive / 0; totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	**Description**
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
    - *Transaction-Details-PK*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Authorized

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Authorisation of Clearing Transaction Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information regarding Authorisation of Clearing Transaction primary key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.CreateTransaction

Input of Clearing Transaction

2.8.1.CGTransaction-Create-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM

ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT
DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Created

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description

Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

ERRCODE

Attribute	Description	
Name	ERRCODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

LCYCHGAMT

Attribute	**Description**
Name	LCYCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCYLCYXRT

Attribute	**Description**
Name	CHGCCYLCYXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 12 totalDigits / 24

TOP

LCYCHGAMT1

Attribute	**Description**
Name	LCYCHGAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

CHGCCYLCYXRT1

Attribute	**Description**
Name	CHGCCYLCYXRT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description
Name	CC_HOLDER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

REMBANK

Attribute	Description
Name	REMBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description	
Name	BENBRANCH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description	
Name	BENCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description	
Name	ROUTBNKNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description	
Name	DENMCCY1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: length, Description: 3 Restrictions: pattern, Description: [A-Z]{3}

TOP

DENMAMT2

Attribute	Description
Name	DENMAMT2
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: fractionDigits, Description: 3 Restrictions: totalDigits, Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACTAMT

Attribute	**Description**
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.

Attributes	Attribute	Description
	minOccurs	0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked

Attributes	Attribute	Description
	minOccurs	0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8

Attribute	Description

Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	**Description**
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	**Description**
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

Charge-Details

Attribute	Description	
Name	Charge-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	Indicated the Charge Component Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

ORACLE

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

ORACLE

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.8.2.CGTransaction-Create-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*
      - *VALDATE*
      - *LATECLG*
      - *ROUTINGNO*
      - *SERIALNO*
      - *ENTRYNO*

- *REGCC*
- *SPLCHQ*
- *TXNBRN*
- *BENACCOUNT*
- *TXNCCY*
- *CR_CARD_NO*
- *CC_HOLDER_NAME*
- *ENDPOINT*
- *ACCCY*
- *ACCCYAMT*
- *BENCUSTID*
- *DIRECTION*
- *REMBRANCH*
- *REMDET1*
- *REMDET2*
- *REMDET3*
- *BENDET1*
- *BENDET2*
- *BENDET3*
- *DIN*
- *DINDATE*
- *CUSTDATE*
- *REMARKS*
- *XRATE*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*
- *MISGRPTXN*
- *REFRTCD*
- *REFRTSPRD*
- *FUNDMIS1*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*

FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9

FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Retail Teller Transaction that has to be Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 pattern / [a-zA-Z_0-9]*

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

CR_CARD_NO

Attribute	Description
Name	CR_CARD_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

ENDPOINT

Attribute	Description	
Name	ENDPOINT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET2

Attribute	Description	
Name	REMDET2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REMDET3

Attribute	Description	
Name	REMDET3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET1

Attribute	Description	
Name	BENDET1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET2

Attribute	Description	
Name	BENDET2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	**Description**
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	**Description**
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

CHGAMT

Attribute	**Description**
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description** minOccurs / 0 nillable / true
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

ORACLE

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.8.3.CGTransaction-Create-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT

- *DENMCCY1*
- *DENMAMT1*
- *DENMCCY2*
- *DENMAMT2*
- *XRATE*
- *DIRECTION*
- *REMDET1*
- *REMDET2*
- *REMDET3*
- *BENDET1*
- *BENDET2*
- *BENDET3*
- *DIN*
- *DINDATE*
- *CUSTDATE*
- *MODULE*
- *MODREFNO*
- *REJREASON*
- *CUSTID*
- *ACCTITLE*
- *CUSTNAME*
- *REMARKS*
- *ACTAMT*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *MODNO*
- *RECORDSTAT*
- *AUTHSTAT*
- *ONCEAUTH*
- *STATUS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*
- *REFRTTYPE*
- *REFXRT*
- *CALCMETH*

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*

TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

ORACLE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Created

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	**Description**
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	Restrictions: fractionDigits = 3; totalDigits = 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

ORACLE

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description	
Name	REMCUST	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

ACCBRN

Attribute	Description	
Name	ACCBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description	
Name	INSTRNO2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LCYCHGAMT

Attribute	Description
Name	LCYCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT

Attribute	Description
Name	CHGCCYLCYXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT1

Attribute	Description
Name	LCYCHGAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT1

Attribute	Description
Name	CHGCCYLCYXRT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT2

Attribute	Description
Name	LCYCHGAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT2

Attribute	Description
Name	CHGCCYLCYXRT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT3

Attribute	Description
Name	LCYCHGAMT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT3

Attribute	Description
Name	CHGCCYLCYXRT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT4

Attribute	Description
Name	LCYCHGAMT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT4

Attribute	Description
Name	CHGCCYLCYXRT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

ACYTOTCHGAMT

Attribute	Description
Name	ACYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT2

Attribute	Description
Name	DENMAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description

Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

ORACLE

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Mis-Details

Attribute	**Description**
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; minInclusive / 0; totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.CGTransaction-Create-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *SCODE*
      - *CONSOLIDATED*
      - *Clearing-Details*
        - *PRODUCT*
        - *REMACCOUNT*
        - *INSTRNO*
        - *INSTRCCY*
        - *INSTRAMT*
        - *INSTRTYPE*
        - *INSTRDATE*
        - *CHEQUEISSUEDATE*
        - *TXNDATE*
        - *VALDATE*
        - *LATECLG*
        - *ROUTINGNO*
        - *SERIALNO*

ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
CR_CARD_NO
CC_HOLDER_NAME
ENDPOINT
ACCCY
ACCCYAMT
BENCUSTID
DIRECTION
REMBRANCH
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
DINDATE
CUSTDATE
REMARKS
XRATE

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4

FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8

FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10

Udf-Details

FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE

Charge-Details

CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD
TXNCODE
NETTINGIND
CHGGL
TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE

Transaction-Details-PK

XREF

Clearing-Details

FCCREF

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for Input Only information relating to the Retail Teller Transaction that has to be Queried

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction IO Details.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

CONSOLIDATED

Attribute	Description	
Name	CONSOLIDATED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 4 pattern / [a-zA-Z0-9]{4}

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

CR_CARD_NO

Attribute	Description
Name	CR_CARD_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

CC_HOLDER_NAME

Attribute	Description
Name	CC_HOLDER_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

ACCCY

Attribute	Description	
Name	ACCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

ACCCYAMT

Attribute	Description	
Name	ACCCYAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

BENCUSTID

Attribute	Description	
Name	BENCUSTID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

DIRECTION

Attribute	Description	
Name	DIRECTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	I,O

TOP

REMBRANCH

Attribute	Description
Name	REMBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 15 minInclusive / 0 totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked

Attributes	Attribute	Description
	minOccurs	0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 5 Restrictions: minInclusive — Description: 0 Restrictions: totalDigits — Description: 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS6

Attribute	Description

Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	**Description**
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	**Description**
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	**Description**
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	**Description**
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	Description
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE

Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	**Description**
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	**Description**
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 minLength / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGCOMP

Attribute	**Description**
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGAMT

Attribute	Description
Name	CHGAMT
Datatype	Number
Description	Indicates the amount charged.
Attributes	**Attribute** / **Description**: minOccurs / 0; nillable / true
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 12 Restrictions: totalDigits — Description: 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information Regarding Input of Clearing Transaction Primary Key Details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS error Response Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String

Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.9.QueryTransaction

Query of Clearing Transaction

2.9.1.CGTransaction-Query-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *Clearing-Details*
      - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes information relating to the Clearing Transaction that has to be Queried.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details

Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

2.9.2.CGTransaction-Query-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT

DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*

TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Full Response information relating to the Clearing Transaction that has been successfully Queried

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the Full Response information relating to the Clearing Transaction that has been successfully Queried.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	**Description**
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	Restrictions: fractionDigits = 3; totalDigits = 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 0 totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description
Name	INSTRNO2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LCYCHGAMT

Attribute	Description
Name	LCYCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT

Attribute	Description
Name	CHGCCYLCYXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT1

Attribute	Description
Name	LCYCHGAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT1

Attribute	Description
Name	CHGCCYLCYXRT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT2

Attribute	Description
Name	LCYCHGAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT2

Attribute	Description
Name	CHGCCYLCYXRT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT3

Attribute	Description
Name	LCYCHGAMT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT3

Attribute	Description
Name	CHGCCYLCYXRT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT4

Attribute	Description
Name	LCYCHGAMT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT4

Attribute	Description
Name	CHGCCYLCYXRT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

ACYTOTCHGAMT

Attribute	Description
Name	ACYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTBRNNAM

Attribute	Description	
Name	ROUTBRNNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description	
Name	ROUTSECTDISC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LCYTOTCHGAMT

Attribute	Description	
Name	LCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

TCYTOTCHGAMT

Attribute	Description	
Name	TCYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT2

Attribute	Description
Name	DENMAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description

Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CUSTID

Attribute	Description
Name	CUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9 pattern / [a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description
Name	ACCTITLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	**Description**
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; minInclusive / 0; totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

ORACLE

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

ORACLE

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.ReverseTransaction

Reversal of Clearing Transaction

2.10.1.CGTransaction-Reverse-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*

INSTRDATE
CHEQUEISSUEDATE
TXNDATE
VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM

- *ROUTSECTDISC*
- *LCYTOTCHGAMT*
- *TCYTOTCHGAMT*
- *DENMCCY1*
- *DENMAMT1*
- *DENMCCY2*
- *DENMAMT2*
- *XRATE*
- *DIRECTION*
- *REMDET1*
- *REMDET2*
- *REMDET3*
- *BENDET1*
- *BENDET2*
- *BENDET3*
- *DIN*
- *DINDATE*
- *CUSTDATE*
- *MODULE*
- *MODREFNO*
- *REJREASON*
- *CUSTID*
- *ACCTITLE*
- *CUSTNAME*
- *REMARKS*
- *ACTAMT*
- *MAKERID*
- *MAKERSTAMP*
- *CHECKERID*
- *CHECKERSTAMP*
- *MODNO*
- *RECORDSTAT*
- *AUTHSTAT*
- *ONCEAUTH*
- *STATUS*

Mis-Details

- *BRANCH*
- *CUSTNO*
- *MISGRP*
- *REL_REF*
- *REL_ACC*
- *MISHD*
- *POOLCD*
- *REFRT*

REFRTTYPE
REFXRT
CALCMETH
MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8

TXNMIS9
TXNMIS10
FUNDMIS1LBL1
FUNDMIS2LBL2
FUNDMIS3LBL3
FUNDMIS4LBL4
FUNDMIS5LBL5
FUNDMIS6LBL6
FUNDMIS7LBL7
FUNDMIS8LBL8
FUNDMIS9LBL9
FUNDMIS10LBL10
COMPMIS1LBL1
COMPMIS2LBL2
COMPMIS3LBL3
COMPMIS4LBL4
COMPMIS5LBL5
COMPMIS6LBL6
COMPMIS7LBL7
COMPMIS8LBL8
COMPMIS9LBL9
COMPMIS10LBL10
TXNMIS1LBL1
TXNMIS2LBL2
TXNMIS3LBL3
TXNMIS4LBL4
TXNMIS5LBL5
TXNMIS6LBL6
TXNMIS7LBL7
TXNMIS8LBL8
TXNMIS9LBL9
TXNMIS10LBL10
Udf-Details
FUNCTIONID
FIELD_NAME
DATATYPE
FIELD_VALUE
VAL_TYPE
Charge-Details
CHGCOMP
WAIVER
CHGAMT
CHGCCY
MISHEAD

TXNCODE

NETTINGIND

CHGGL

TYPE

LCYCHG

XRATE

TCYCHG

TCYXRATE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	

Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description	
Name	XREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SCODE

Attribute	Description	
Name	SCODE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	**Description**
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clearing-Details

Attribute	**Description**
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	**Description**
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	**Description**
Name	FCCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	Description
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	Description
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	Description
Name	INSTRCCY
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

INSTRAMT

Attribute	Description

Name	INSTRAMT
Datatype	Number
Description	
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description
Name	VALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATECLG

Attribute	Description
Name	LATECLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ROUTINGNO

Attribute	Description
Name	ROUTINGNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 27

TOP

SERIALNO

Attribute	Description
Name	SERIALNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	0
	totalDigits	9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20
	pattern	[a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description
Name	INSTRNO2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

LCYCHGAMT

Attribute	Description	
Name	LCYCHGAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT

Attribute	Description	
Name	CHGCCYLCYXRT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT1

Attribute	Description	
Name	LCYCHGAMT1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT1

Attribute	Description	
Name	CHGCCYLCYXRT1	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT2

Attribute	Description	
Name	LCYCHGAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT2

Attribute	Description	
Name	CHGCCYLCYXRT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT3

Attribute	Description	
Name	LCYCHGAMT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT3

Attribute	Description	
Name	CHGCCYLCYXRT3	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

LCYCHGAMT4

Attribute	Description	
Name	LCYCHGAMT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCYLCYXRT4

Attribute	Description	
Name	CHGCCYLCYXRT4	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

ACYTOTCHGAMT

Attribute	Description	
Name	ACYTOTCHGAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description	
Name	BENBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT1

Attribute	Description	
Name	DENMAMT1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

DENMCCY2

Attribute	Description	
Name	DENMCCY2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

DENMAMT2

Attribute	Description	
Name	DENMAMT2	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

XRATE

Attribute	Description	
Name	XRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	fractionDigits	12
	totalDigits	24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description
Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

REJREASON

Attribute	Description
Name	REJREASON
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACTAMT

Attribute	**Description**
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** fractionDigits / 3 totalDigits / 22

TOP

MAKERID

Attribute	**Description**
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / O,C

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	Description
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	Description
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16; minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.

Attributes	Attribute	Description
	minOccurs	0

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description	Specifies The Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

REFRT

Attribute	Description	
Name	REFRT	
Datatype	Number	
Description	Indicates the Refinancing Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	15
	minInclusive	0
	totalDigits	26

TOP

REFRTTYPE

Attribute	Description	
Name	REFRTTYPE	
Datatype	String	
Description	Indicates the Refinancing Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REFXRT

Attribute	Description	
Name	REFXRT	
Datatype	String	
Description	Indicates Refinancing Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	fractionDigits	5
	minInclusive	0
	totalDigits	15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked

Attributes	Attribute	Description
	minOccurs	0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS8

Attribute	Description

Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10

Attribute	**Description**
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD1

Attribute	**Description**
Name	COSTCOD1
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	Description
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD3

Attribute	Description
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD4

Attribute	Description
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12; minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4

Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 Restrictions: minLength — Description: 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS3LBL3

Attribute	Description
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	minLength	1

TOP

COMPMIS4LBL4

Attribute	Description
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS5LBL5

Attribute	Description
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS6LBL6

Attribute	Description
Name	COMPMIS6LBL6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description

Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	**Description**
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	**Description**
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	**Description**
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	Description
Name	TXNMIS8LBL8
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	**Description**
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

TOP

Charge-Details

Attribute	Description	
Name	Charge-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CHGCOMP

Attribute	Description	
Name	CHGCOMP	
Datatype	String	
Description	Indicated the Charge Component Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates that charge is waived off.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

ORACLE

TOP

CHGCCY

Attribute	Description
Name	CHGCCY
Datatype	String
Description	Indicates the currency of the charged amount.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	Indicates the MIS head for charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNCODE

Attribute	Description
Name	TXNCODE
Datatype	String
Description	Indicates the transacton code for charge
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

2.10.2.CGTransaction-Reverse-Req-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *Clearing-Details*
      - *FCCREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

2.10.3.CGTransaction-Reverse-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transaction-Details*
    - *XREF*
    - *SCODE*
    - *STATUS*
    - *BATCHTOTAMT*
    - *CONSOLIDATED*
    - *Clearing-Details*
      - *PRODUCT*
      - *FCCREF*
      - *ESN*
      - *REMACCOUNT*
      - *INSTRNO*
      - *INSTRCCY*
      - *INSTRAMT*
      - *INSTRTYPE*
      - *BENROUTINGNO*
      - *INSTRDATE*
      - *CHEQUEISSUEDATE*
      - *TXNDATE*

VALDATE
LATECLG
ROUTINGNO
SERIALNO
ENTRYNO
REGCC
SPLCHQ
TXNBRN
BENACCOUNT
TXNCCY
ENDPOINT
ACCCY
ACCCYAMT
ROUTBNKCOD
ROUTBRNCOD
ROUTSECTCOD
BENCUSTID
REMCUST
ACCBRN
INSTRNO2
ERRCODE
LCYCHGAMT
CHGCCYLCYXRT
LCYCHGAMT1
CHGCCYLCYXRT1
LCYCHGAMT2
CHGCCYLCYXRT2
LCYCHGAMT3
CHGCCYLCYXRT3
LCYCHGAMT4
CHGCCYLCYXRT4
ACYTOTCHGAMT
CR_CARD_NO
CC_HOLDER_NAME
REMBANK
REMBRANCH
BENBANK
BENBRANCH
BENCCY
ROUTBNKNAM
ROUTBRNNAM
ROUTSECTDISC
LCYTOTCHGAMT
TCYTOTCHGAMT

DENMCCY1
DENMAMT1
DENMCCY2
DENMAMT2
XRATE
DIRECTION
REMDET1
REMDET2
REMDET3
BENDET1
BENDET2
BENDET3
DIN
DINDATE
CUSTDATE
MODULE
MODREFNO
REJREASON
CUSTID
ACCTITLE
CUSTNAME
REMARKS
ACTAMT
MAKERID
MAKERSTAMP
CHECKERID
CHECKERSTAMP
MODNO
RECORDSTAT
AUTHSTAT
ONCEAUTH
STATUS

Mis-Details

BRANCH
CUSTNO
MISGRP
REL_REF
REL_ACC
MISHD
POOLCD
REFRT
REFRTTYPE
REFXRT
CALCMETH

MISGRPTXN
REFRTCD
REFRTSPRD
FUNDMIS1
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
FUNDMIS10
MISGRPCOMP
COMPMIS1
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
COMPMIS10
COSTCOD1
COSTCOD2
COSTCOD3
COSTCOD4
COSTCOD5
LINKGRP
CCY
RTFLAG
PROCFLG
TXNMIS1
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
TXNMIS10
FUNDMIS1LBL1

- *FUNDMIS2LBL2*
- *FUNDMIS3LBL3*
- *FUNDMIS4LBL4*
- *FUNDMIS5LBL5*
- *FUNDMIS6LBL6*
- *FUNDMIS7LBL7*
- *FUNDMIS8LBL8*
- *FUNDMIS9LBL9*
- *FUNDMIS10LBL10*
- *COMPMIS1LBL1*
- *COMPMIS2LBL2*
- *COMPMIS3LBL3*
- *COMPMIS4LBL4*
- *COMPMIS5LBL5*
- *COMPMIS6LBL6*
- *COMPMIS7LBL7*
- *COMPMIS8LBL8*
- *COMPMIS9LBL9*
- *COMPMIS10LBL10*
- *TXNMIS1LBL1*
- *TXNMIS2LBL2*
- *TXNMIS3LBL3*
- *TXNMIS4LBL4*
- *TXNMIS5LBL5*
- *TXNMIS6LBL6*
- *TXNMIS7LBL7*
- *TXNMIS8LBL8*
- *TXNMIS9LBL9*
- *TXNMIS10LBL10*

Udf-Details

- *FUNCTIONID*
- *FIELD_NAME*
- *DATATYPE*
- *FIELD_VALUE*
- *VAL_TYPE*

Charge-Details

- *CHGCOMP*
- *WAIVER*
- *CHGAMT*
- *CHGCCY*
- *MISHEAD*
- *TXNCODE*
- *NETTINGIND*
- *CHGGL*

TYPE
LCYCHG
XRATE
TCYCHG
TCYXRATE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for information relating to the Clearing Transaction that has to be Reversed

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SCODE

Attribute	Description
Name	SCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BATCHTOTAMT

Attribute	Description
Name	BATCHTOTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CONSOLIDATED

Attribute	Description
Name	CONSOLIDATED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

PRODUCT

Attribute	Description
Name	PRODUCT
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 4; pattern / [a-zA-Z0-9]{4}

TOP

FCCREF

Attribute	Description
Name	FCCREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 10

TOP

REMACCOUNT

Attribute	**Description**
Name	REMACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20; pattern / [a-zA-Z0-9]*

TOP

INSTRNO

Attribute	**Description**
Name	INSTRNO
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

INSTRCCY

Attribute	**Description**
Name	INSTRCCY
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[A-Z]{3}

TOP

INSTRAMT

Attribute	Description
Name	INSTRAMT
Datatype	Number
Description	
Restrictions	Restrictions: fractionDigits = 3; totalDigits = 22

TOP

INSTRTYPE

Attribute	Description
Name	INSTRTYPE
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [A-Z]{3}

TOP

BENROUTINGNO

Attribute	Description
Name	BENROUTINGNO
Datatype	String
Description	
Restrictions	Restrictions: maxLength = 27

TOP

INSTRDATE

Attribute	Description
Name	INSTRDATE
Datatype	Date
Description	

TOP

CHEQUEISSUEDATE

Attribute	Description
Name	CHEQUEISSUEDATE
Datatype	Date
Description	

TOP

TXNDATE

Attribute	Description
Name	TXNDATE
Datatype	Date
Description	

TOP

VALDATE

Attribute	Description	
Name	VALDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATECLG

Attribute	Description	
Name	LATECLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ROUTINGNO

Attribute	Description	
Name	ROUTINGNO	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	27

TOP

SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ENTRYNO

Attribute	Description
Name	ENTRYNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 0; totalDigits / 9

TOP

REGCC

Attribute	Description
Name	REGCC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SPLCHQ

Attribute	Description
Name	SPLCHQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TXNBRN

Attribute	Description
Name	TXNBRN
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENACCOUNT

Attribute	Description
Name	BENACCOUNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20 pattern / [a-zA-Z0-9]*

TOP

TXNCCY

Attribute	Description
Name	TXNCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ENDPOINT

Attribute	Description
Name	ENDPOINT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ACCCY

Attribute	Description
Name	ACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** length / 3 pattern / [A-Z]{3}

TOP

ACCCYAMT

Attribute	Description
Name	ACCCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

ROUTBNKCOD

Attribute	Description
Name	ROUTBNKCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTBRNCOD

Attribute	Description
Name	ROUTBRNCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

ROUTSECTCOD

Attribute	Description
Name	ROUTSECTCOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z_0-9]*

TOP

BENCUSTID

Attribute	Description
Name	BENCUSTID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

REMCUST

Attribute	Description
Name	REMCUST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

INSTRNO2

Attribute	Description
Name	INSTRNO2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ERRCODE

Attribute	Description
Name	ERRCODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

LCYCHGAMT

Attribute	Description
Name	LCYCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT

Attribute	Description
Name	CHGCCYLCYXRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT1

Attribute	Description
Name	LCYCHGAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT1

Attribute	Description
Name	CHGCCYLCYXRT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT2

Attribute	Description
Name	LCYCHGAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT2

Attribute	Description
Name	CHGCCYLCYXRT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT3

Attribute	Description
Name	LCYCHGAMT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT3

Attribute	Description
Name	CHGCCYLCYXRT3
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

LCYCHGAMT4

Attribute	Description
Name	LCYCHGAMT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CHGCCYLCYXRT4

Attribute	Description
Name	CHGCCYLCYXRT4
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

ACYTOTCHGAMT

Attribute	Description
Name	ACYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

CR_CARD_NO

Attribute	Description	
Name	CR_CARD_NO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

CC_HOLDER_NAME

Attribute	Description	
Name	CC_HOLDER_NAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

REMBANK

Attribute	Description	
Name	REMBANK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

REMBRANCH

Attribute	Description	
Name	REMBRANCH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

BENBANK

Attribute	Description
Name	BENBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; pattern / [a-zA-Z0-9]*

TOP

BENBRANCH

Attribute	Description
Name	BENBRANCH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

BENCCY

Attribute	Description
Name	BENCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

ROUTBNKNAM

Attribute	Description
Name	ROUTBNKNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTBRNNAM

Attribute	Description
Name	ROUTBRNNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ROUTSECTDISC

Attribute	Description
Name	ROUTSECTDISC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LCYTOTCHGAMT

Attribute	Description
Name	LCYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYTOTCHGAMT

Attribute	Description
Name	TCYTOTCHGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY1

Attribute	Description
Name	DENMCCY1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT1

Attribute	Description
Name	DENMAMT1
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

DENMCCY2

Attribute	Description
Name	DENMCCY2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [A-Z]{3}

TOP

DENMAMT2

Attribute	Description
Name	DENMAMT2
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

DIRECTION

Attribute	Description
Name	DIRECTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,O

TOP

REMDET1

Attribute	Description
Name	REMDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET2

Attribute	Description
Name	REMDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REMDET3

Attribute	Description
Name	REMDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET1

Attribute	Description
Name	BENDET1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET2

Attribute	Description
Name	BENDET2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BENDET3

Attribute	Description
Name	BENDET3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DIN

Attribute	Description

Name	DIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DINDATE

Attribute	Description
Name	DINDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTDATE

Attribute	Description
Name	CUSTDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2 pattern / [A-Z]*

TOP

MODREFNO

Attribute	Description
Name	MODREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

ORACLE

TOP

REJREASON

Attribute	Description	
Name	REJREASON	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CUSTID

Attribute	Description	
Name	CUSTID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9
	pattern	[a-zA-Z0-9]*

TOP

ACCTITLE

Attribute	Description	
Name	ACCTITLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACTAMT

Attribute	Description
Name	ACTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

MAKERID

Attribute	Description
Name	MAKERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CHECKERID

Attribute	Description
Name	CHECKERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 0 Restrictions: totalDigits — Description: 10

TOP

RECORDSTAT

Attribute	Description
Name	RECORDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: O,C

TOP

AUTHSTAT

Attribute	Description

Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,U

TOP

ONCEAUTH

Attribute	**Description**
Name	ONCEAUTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Mis-Details

Attribute	**Description**
Name	Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

ORACLE

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	Indicates The Customer Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Specifies The MIS Group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

REL_REF

Attribute	Description
Name	REL_REF
Datatype	String
Description	Specifies The Related Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

REL_ACC

Attribute	Description
Name	REL_ACC
Datatype	String
Description	Specifies The Related Account.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16 minLength / 1

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates The MIS Head.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Specifies The Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

REFRT

Attribute	Description
Name	REFRT
Datatype	Number
Description	Indicates the Refinancing Rate
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 15; minInclusive / 0; totalDigits / 26

TOP

REFRTTYPE

Attribute	Description
Name	REFRTTYPE
Datatype	String
Description	Indicates the Refinancing Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REFXRT

Attribute	Description
Name	REFXRT
Datatype	String
Description	Indicates Refinancing Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	Number
Description	Indicates The Interest Calculation Method 1 : 30(Euro)/360 : 1 2 : 30(US)/360 : 2 3 : Actual/360 : 3 4 : 30(Euro)/365 : 4 5 : 30(US)/365 : 5 6 : Actual/365 :6
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	Indicates the Transaction MIS Group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRTCD

Attribute	Description
Name	REFRTCD
Datatype	String
Description	Indicates the Refinancing Rate Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

REFRTSPRD

Attribute	Description
Name	REFRTSPRD
Datatype	Number
Description	Indicates the spread for the Refinance Rate Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 5; minInclusive / 0; totalDigits / 15

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9; minLength / 1

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description**: minOccurs / 0

ORACLE

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 9 Restrictions: minLength; Description: 1

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String

Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	Indicates the Fund type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	Indicates the Composite MIS group to which the transaction is linked
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9
	minLength	1

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked.
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength, minLength; Description: 9, 1

TOP

COSTCOD1

Attribute	Description
Name	COSTCOD1
Datatype	String

Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD2

Attribute	**Description**
Name	COSTCOD2
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD3

Attribute	**Description**
Name	COSTCOD3
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD4

Attribute	**Description**
Name	COSTCOD4
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COSTCOD5

Attribute	Description
Name	COSTCOD5
Datatype	String
Description	Indicates the transaction type of Cost Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

LINKGRP

Attribute	Description
Name	LINKGRP
Datatype	String
Description	Indicates Link to Group
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12 minLength / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates The Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

RTFLAG

Attribute	Description
Name	RTFLAG
Datatype	String
Description	Indicates the refinancing rate that should be used for the transaction
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PROCFLG

Attribute	Description
Name	PROCFLG
Datatype	String
Description	Indicates ProcflgType R-Related Reference Number A-Related Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9 minLength — 1

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS1LBL1

Attribute	Description
Name	FUNDMIS1LBL1
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS2LBL2

Attribute	Description
Name	FUNDMIS2LBL2
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS3LBL3

Attribute	Description
Name	FUNDMIS3LBL3
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS4LBL4

Attribute	Description
Name	FUNDMIS4LBL4
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS5LBL5

Attribute	Description
Name	FUNDMIS5LBL5
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS6LBL6

Attribute	Description
Name	FUNDMIS6LBL6
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS7LBL7

Attribute	Description
Name	FUNDMIS7LBL7
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS8LBL8

Attribute	Description
Name	FUNDMIS8LBL8
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS9LBL9

Attribute	Description
Name	FUNDMIS9LBL9
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

FUNDMIS10LBL10

Attribute	Description
Name	FUNDMIS10LBL10
Datatype	String
Description	Indicates the Fund to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS1LBL1

Attribute	Description
Name	COMPMIS1LBL1
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS2LBL2

Attribute	Description
Name	COMPMIS2LBL2
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS3LBL3

Attribute	**Description**
Name	COMPMIS3LBL3
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS4LBL4

Attribute	**Description**
Name	COMPMIS4LBL4
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS5LBL5

Attribute	**Description**
Name	COMPMIS5LBL5
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS6LBL6

Attribute	**Description**
Name	COMPMIS6LBL6
Datatype	String

Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS7LBL7

Attribute	Description
Name	COMPMIS7LBL7
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS8LBL8

Attribute	Description
Name	COMPMIS8LBL8
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS9LBL9

Attribute	Description
Name	COMPMIS9LBL9
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

COMPMIS10LBL10

Attribute	Description
Name	COMPMIS10LBL10
Datatype	String
Description	Indicates the composite type of MIS Code defined for the group to which the transaction is linked .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS1LBL1

Attribute	Description
Name	TXNMIS1LBL1
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS2LBL2

Attribute	Description
Name	TXNMIS2LBL2
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS3LBL3

Attribute	Description
Name	TXNMIS3LBL3
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS4LBL4

Attribute	Description
Name	TXNMIS4LBL4
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS5LBL5

Attribute	Description
Name	TXNMIS5LBL5
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS6LBL6

Attribute	Description
Name	TXNMIS6LBL6
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS7LBL7

Attribute	Description
Name	TXNMIS7LBL7
Datatype	String

Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS8LBL8

Attribute	**Description**
Name	TXNMIS8LBL8
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS9LBL9

Attribute	**Description**
Name	TXNMIS9LBL9
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

TXNMIS10LBL10

Attribute	**Description**
Name	TXNMIS10LBL10
Datatype	String
Description	Indicates the transaction type of MIS Code defined for the group to which the transaction is linked.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9 minLength / 1

TOP

Udf-Details

Attribute	Description
Name	Udf-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2; minLength / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CHGCOMP

Attribute	Description
Name	CHGCOMP
Datatype	String
Description	Indicated the Charge Component Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates that charge is waived off.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

CHGAMT

Attribute	Description	
Name	CHGAMT	
Datatype	Number	
Description	Indicates the amount charged.	
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	fractionDigits	3
	totalDigits	22

TOP

CHGCCY

Attribute	Description	
Name	CHGCCY	
Datatype	String	
Description	Indicates the currency of the charged amount.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description	Indicates the MIS head for charge.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNCODE

Attribute	Description	
Name	TXNCODE	
Datatype	String	
Description	Indicates the transacton code for charge	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETTINGIND

Attribute	Description
Name	NETTINGIND
Datatype	String
Description	Indicates whether charge need to be netted or not.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

CHGGL

Attribute	Description
Name	CHGGL
Datatype	String
Description	Indicates th GL associated with charge.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TYPE

Attribute	Description
Name	TYPE
Datatype	String
Description	Indicates the type of charge. F - Fixed, P - Percentage, I - Interest
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LCYCHG

Attribute	Description
Name	LCYCHG
Datatype	Number
Description	Indicates the chage in local currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: fractionDigits — Description: 3 Restrictions: totalDigits — Description: 22

TOP

XRATE

Attribute	Description
Name	XRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 12; totalDigits / 24

TOP

TCYCHG

Attribute	Description
Name	TCYCHG
Datatype	Number
Description	Indicate the charge in transaction currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

TCYXRATE

Attribute	Description
Name	TCYXRATE
Datatype	Number
Description	Indicates the exchange rate for transaction currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: fractionDigits / 3; totalDigits / 22

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Includes the FCUBS Error Response Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transaction-Details*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
    - *Transaction-Details-PK*
      - *XREF*
      - *Clearing-Details*
        - *FCCREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD gives the message format for Input Only information relating to the Clearing Transaction that has to be Reversed

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transaction-Details

Attribute	Description
Name	Transaction-Details
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description
Name	FCCREF
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z0-9]{16}

TOP

Transaction-Details-PK

Attribute	Description
Name	Transaction-Details-PK
Datatype	
Description	Includes the information relating to the Clearing Transaction that has to be Reversed with the primary key details.

TOP

XREF

Attribute	Description
Name	XREF
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	20

TOP

Clearing-Details

Attribute	Description
Name	Clearing-Details
Datatype	
Description	

TOP

FCCREF

Attribute	Description	
Name	FCCREF	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z0-9]{16}

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes the FCUBS Error Response.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description

Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Includes the FCUBS Warning Response.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.QueryCcyClgHoliday

Query Currency cleading Holing

2.11.1.ST-QueryCcyClgHoliday-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CCY_Holiday_Details-IO*
    - *CCCY*
    - *YR*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	

TOP

CCY_Holiday_Details-IO

Attribute	Description
Name	CCY_Holiday_Details-IO
Datatype	
Description	

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description	Indicates Clearing Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

YR

Attribute	Description
Name	YR

Datatype	Number
Description	Indicates Year

TOP

2.11.2.ST-QueryCcyClgHoliday-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *CCY_Holiday_Details*
      - *CCCY*
      - *YR*
    - *CCY_Holiday_Details-Full*
      - *YR*
      - *WKLY_HOL*
      - *CCCY*
      - *MAKERID*
      - *MAKERDTSTAMP*
      - *CHECKERID*
      - *CHECKERDTSTAMP*
      - *MODNO*
      - *AUTHSTAT*
      - *RECSTAT*
      - *ONCEAUTH*
      - *CCY_Holiday_List*
        - *ccy1*
        - *yer*

mont

hol_lst

UDFDETAILS

FUNCTIONID

FIELD_NAME

DATATYPE

FIELD_VALUE

VAL_TYPE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

CCY_Holiday_Details

Attribute	Description
Name	CCY_Holiday_Details
Datatype	
Description	Query Of Clearing Currency Holiday Details

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description	Indicates Clearing Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

CCY_Holiday_Details-Full

Attribute	Description
Name	CCY_Holiday_Details-Full
Datatype	
Description	Query Of Clearing Currency Holiday Details Full Type

TOP

YR

Attribute	Description
Name	YR
Datatype	Number
Description	Indicates Year

TOP

WKLY_HOL

Attribute	Description	
Name	WKLY_HOL	
Datatype	String	
Description	Indicates Weekly Holiday	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7

TOP

CCCY

Attribute	Description	
Name	CCCY	
Datatype	String	
Description	Indicates Clearing Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Specifies the User Id who has created\last modified the record.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Time when the User has created\last modified the record.

ORACLE

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHECKERID

Attribute	**Description**
Name	CHECKERID
Datatype	String
Description	Indicates the User Id who has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERDTSTAMP

Attribute	**Description**
Name	CHECKERDTSTAMP
Datatype	String
Description	Indicates the Date and Time, when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	Indicates Modification number i.e. the number of times the record has been modified.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the record is Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

CCY_Holiday_List

Attribute	Description	
Name	CCY_Holiday_List	
Datatype		
Description	Currency Holiday List	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ccy1

Attribute	Description	
Name	ccy1	
Datatype	String	
Description	Indicates Currency Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

yer

Attribute	Description
Name	yer
Datatype	Number
Description	Indicates Year
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

mont

Attribute	Description
Name	mont
Datatype	Number
Description	Indicates Month
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

hol_lst

Attribute	Description
Name	hol_lst
Datatype	String
Description	Indicates Holiday List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 31

TOP

UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	
Description	UDF Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

FIELD_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.
Restrictions	**Restrictions** / **Description**: maxLength 105; minLength 1

TOP

DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 15

TOP

FIELD_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String
Description	Indicates the User Defined Field Value.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 255; minLength 0

TOP

VAL_TYPE

Attribute	Description
Name	VAL_TYPE
Datatype	String
Description	Indicates Value type.
Attributes	**Attribute** / **Description**: minOccurs 0
Restrictions	**Restrictions** / **Description**: maxLength 2; minLength 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	Error Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	Warning Response Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Instruments Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.