Gateway Documentation - Islamic Letters of Credit Service

Oracle FLEXCUBE Universal Banking

Release FCUBS_12.0.3.0.0

[April] [2014]

ORACLE
FINANCIAL SERVICES

ORACLE

Table Of Contents

1. BACKGROUND 1
2. FCUBSLIService 2
2.1. ReverseLIPayment 2
2.1.1. LI-ReverseLIPayment-Res-Full-MSG.xsd 2
2.1.2. LI-ReverseLIPayment-Res-PK-MSG.xsd 82
2.1.3. LI-ReverseLIPayment-Req-Full-MSG.xsd 91
2.1.4. LI-ReverseLIPayment-Req-IO-MSG.xsd 170
2.2. RolloverContract 176
2.2.1. LI-RolloverContract-Req-Full-MSG.xsd 176
2.2.2. LI-RolloverContract-Req-IO-MSG.xsd 354
2.2.3. LI-RolloverContract-Res-Full-MSG.xsd 373
2.2.4. LI-RolloverContract-Res-PK-MSG.xsd 553
2.3. DeleteAmendConfirm 574
2.3.1. LI-DeleteAmendConfirm-Res-Full-MSG.xsd 574
2.3.2. LI-DeleteAmendConfirm-Res-PK-MSG.xsd 603
2.3.3. LI-DeleteAmendConfirm-Req-Full-MSG.xsd 612
2.3.4. LI-DeleteAmendConfirm-Req-IO-MSG.xsd 639
2.4. DeleteContract 645
2.4.1. LI-DeleteContract-Req-Full-MSG.xsd 645
2.4.2. LI-DeleteContract-Req-IO-MSG.xsd 823
2.4.3. LI-DeleteContract-Res-Full-MSG.xsd 829
2.4.4. LI-DeleteContract-Res-PK-MSG.xsd 1009
2.5. DeleteGuaranteeClaim 1018
2.5.1. LI-DeleteGuaranteeClaim-Req-Full-MSG.xsd 1018
2.5.2. LI-DeleteGuaranteeClaim-Req-IO-MSG.xsd 1083
2.5.3. LI-DeleteGuaranteeClaim-Res-Full-MSG.xsd 1090
2.5.4. LI-DeleteGuaranteeClaim-Res-PK-MSG.xsd 1157
2.6. DeleteLIPayment 1166
2.6.1. LI-DeleteLIPayment-Req-Full-MSG.xsd 1166
2.6.2. LI-DeleteLIPayment-Req-IO-MSG.xsd 1245
2.6.3. LI-DeleteLIPayment-Res-Full-MSG.xsd 1251
2.6.4. LI-DeleteLIPayment-Res-PK-MSG.xsd 1331
2.7. DeleteLITransfer 1340
2.7.1. LI-DeleteLITransfer-Req-Full-MSG.xsd 1340
2.7.2. LI-DeleteLITransfer-Req-IO-MSG.xsd 1415
2.7.3. LI-DeleteLITransfer-Res-Full-MSG.xsd 1421
2.7.4. LI-DeleteLITransfer-Res-PK-MSG.xsd 1498
2.8. DeleteProduct 1507
2.8.1. LI-DeleteProduct-Req-Full-MSG.xsd 1507
2.8.2. LI-DeleteProduct-Req-IO-MSG.xsd 1576
2.8.3. LI-DeleteProduct-Res-Full-MSG.xsd 1582
2.8.4. LI-DeleteProduct-Res-PK-MSG.xsd 1652
2.9. ModifyAmendConfirm 1661
2.9.1. LI-ModifyAmendConfirm-Req-Full-MSG.xsd 1661
2.9.2. LI-ModifyAmendConfirm-Req-IO-MSG.xsd 1688
2.9.3. LI-ModifyAmendConfirm-Res-Full-MSG.xsd 1706
2.9.4. LI-ModifyAmendConfirm-Res-PK-MSG.xsd 1735
2.10. ModifyContract 1755
2.10.1. LI-ModifyContract-Req-Full-MSG.xsd 1755
2.10.2. LI-ModifyContract-Req-IO-MSG.xsd 1933
2.10.3. LI-ModifyContract-Res-Full-MSG.xsd 2063
2.10.4. LI-ModifyContract-Res-PK-MSG.xsd 2243
2.11. ModifyGuaranteeClaim 2375
2.11.1. LI-ModifyGuaranteeClaim-Req-Full-MSG.xsd 2375

ORACLE

2.11.2. LI-ModifyGuaranteeClaim-Req-IO-MSG.xsd *2440*
2.11.3. LI-ModifyGuaranteeClaim-Res-Full-MSG.xsd *2477*
2.11.4. LI-ModifyGuaranteeClaim-Res-PK-MSG.xsd *2544*
2.12. ModifyLITransfer **2583**
2.12.1. LI-ModifyLITransfer-Req-Full-MSG.xsd *2583*
2.12.2. LI-ModifyLITransfer-Req-IO-MSG.xsd *2658*
2.12.3. LI-ModifyLITransfer-Res-Full-MSG.xsd *2706*
2.12.4. LI-ModifyLITransfer-Res-PK-MSG.xsd *2783*
2.13. ModifyProduct **2833**
2.13.1. LI-ModifyProduct-Req-Full-MSG.xsd *2833*
2.13.2. LI-ModifyProduct-Req-IO-MSG.xsd *2902*
2.13.3. LI-ModifyProduct-Res-Full-MSG.xsd *2955*
2.13.4. LI-ModifyProduct-Res-PK-MSG.xsd *3025*
2.14. QueryAmendConfirm **3080**
2.14.1. LI-QueryAmendConfirm-Req-IO-MSG.xsd *3080*
2.14.2. LI-QueryAmendConfirm-Res-Full-MSG.xsd *3086*
2.15. QueryContract **3115**
2.15.1. LI-QueryContract-Req-IO-MSG.xsd *3115*
2.15.2. LI-QueryContract-Res-Full-MSG.xsd *3122*
2.16. QueryGuaranteeClaim **3303**
2.16.1. LI-QueryGuaranteeClaim-Req-IO-MSG.xsd *3303*
2.16.2. LI-QueryGuaranteeClaim-Res-Full-MSG.xsd *3310*
2.17. QueryLIPayment **3378**
2.17.1. LI-QueryLIPayment-Req-IO-MSG.xsd *3378*
2.17.2. LI-QueryLIPayment-Res-Full-MSG.xsd *3384*
2.18. QueryLITransfer **3465**
2.18.1. LI-QueryLITransfer-Req-IO-MSG.xsd *3465*
2.18.2. LI-QueryLITransfer-Res-Full-MSG.xsd *3471*
2.19. QueryProduct **3549**
2.19.1. LI-QueryProduct-Req-IO-MSG.xsd *3549*
2.19.2. LI-QueryProduct-Res-Full-MSG.xsd *3555*
2.20. ReopenContract **3626**
2.20.1. LI-ReopenContract-Req-Full-MSG.xsd *3626*
2.20.2. LI-ReopenContract-Req-IO-MSG.xsd *3804*
2.20.3. LI-ReopenContract-Res-Full-MSG.xsd *3821*
2.20.4. LI-ReopenContract-Res-PK-MSG.xsd *4001*
2.21. ReverseContract **4020**
2.21.1. LI-ReverseContract-Req-Full-MSG.xsd *4020*
2.21.2. LI-ReverseContract-Req-IO-MSG.xsd *4198*
2.21.3. LI-ReverseContract-Res-Full-MSG.xsd *4205*
2.21.4. LI-ReverseContract-Res-PK-MSG.xsd *4385*
2.22. AuthorizeAmendConfirm **4394**
2.22.1. LI-AuthorizeAmendConfirm-Req-Full-MSG.xsd *4394*
2.22.2. LI-AuthorizeAmendConfirm-Req-IO-MSG.xsd *4421*
2.22.3. LI-AuthorizeAmendConfirm-Res-Full-MSG.xsd *4427*
2.22.4. LI-AuthorizeAmendConfirm-Res-PK-MSG.xsd *4456*
2.23. AuthorizeContract **4465**
2.23.1. LI-AuthorizeContract-Req-Full-MSG.xsd *4465*
2.23.2. LI-AuthorizeContract-Req-IO-MSG.xsd *4643*
2.23.3. LI-AuthorizeContract-Res-Full-MSG.xsd *4650*
2.23.4. LI-AuthorizeContract-Res-PK-MSG.xsd *4830*
2.24. AuthorizeGuaranteeClaim **4839**
2.24.1. LI-AuthorizeGuaranteeClaim-Req-Full-MSG.xsd *4839*
2.24.2. LI-AuthorizeGuaranteeClaim-Req-IO-MSG.xsd *4904*
2.24.3. LI-AuthorizeGuaranteeClaim-Res-Full-MSG.xsd *4911*
2.24.4. LI-AuthorizeGuaranteeClaim-Res-PK-MSG.xsd *4978*
2.25. AuthorizeLIPayment **4987**

2.25.1. LI-AuthorizeLIPayment-Req-Full-MSG.xsd *4987*
2.25.2. LI-AuthorizeLIPayment-Req-IO-MSG.xsd *5066*
2.25.3. LI-AuthorizeLIPayment-Res-Full-MSG.xsd *5072*
2.25.4. LI-AuthorizeLIPayment-Res-PK-MSG.xsd *5152*
2.26. AuthorizeLITransfer **5161**
2.26.1. LI-AuthorizeLITransfer-Req-Full-MSG.xsd *5161*
2.26.2. LI-AuthorizeLITransfer-Req-IO-MSG.xsd *5236*
2.26.3. LI-AuthorizeLITransfer-Res-Full-MSG.xsd *5242*
2.26.4. LI-AuthorizeLITransfer-Res-PK-MSG.xsd *5319*
2.27. AuthorizeProduct **5328**
2.27.1. LI-AuthorizeProduct-Req-Full-MSG.xsd *5328*
2.27.2. LI-AuthorizeProduct-Req-IO-MSG.xsd *5397*
2.27.3. LI-AuthorizeProduct-Res-Full-MSG.xsd *5404*
2.27.4. LI-AuthorizeProduct-Res-PK-MSG.xsd *5474*
2.28. CloseAmendConfirm **5483**
2.28.1. LI-CloseAmendConfirm-Req-Full-MSG.xsd *5483*
2.28.2. LI-CloseAmendConfirm-Req-IO-MSG.xsd *5510*
2.28.3. LI-CloseAmendConfirm-Res-Full-MSG.xsd *5518*
2.28.4. LI-CloseAmendConfirm-Res-PK-MSG.xsd *5547*
2.29. CloseContract **5558**
2.29.1. LI-CloseContract-Req-Full-MSG.xsd *5558*
2.29.2. LI-CloseContract-Req-IO-MSG.xsd *5736*
2.29.3. LI-CloseContract-Res-Full-MSG.xsd *5753*
2.29.4. LI-CloseContract-Res-PK-MSG.xsd *5933*
2.30. ConfirmAmendConfirm **5952**
2.30.1. LI-ConfirmAmendConfirm-Req-Full-MSG.xsd *5952*
2.30.2. LI-ConfirmAmendConfirm-Req-IO-MSG.xsd *5979*
2.30.3. LI-ConfirmAmendConfirm-Res-Full-MSG.xsd *5987*
2.30.4. LI-ConfirmAmendConfirm-Res-PK-MSG.xsd *6016*
2.31. CreateAmendConfirm **6027**
2.31.1. LI-CreateAmendConfirm-Req-Full-MSG.xsd *6027*
2.31.2. LI-CreateAmendConfirm-Req-IO-MSG.xsd *6054*
2.31.3. LI-CreateAmendConfirm-Res-Full-MSG.xsd *6074*
2.31.4. LI-CreateAmendConfirm-Res-PK-MSG.xsd *6103*
2.32. CreateContract **6125**
2.32.1. LI-CreateContract-Req-Full-MSG.xsd *6125*
2.32.2. LI-CreateContract-Req-IO-MSG.xsd *6303*
2.32.3. LI-CreateContract-Res-Full-MSG.xsd *6442*
2.32.4. LI-CreateContract-Res-PK-MSG.xsd *6622*
2.33. CreateGuaranteeClaim **6763**
2.33.1. LI-CreateGuaranteeClaim-Req-Full-MSG.xsd *6763*
2.33.2. LI-CreateGuaranteeClaim-Req-IO-MSG.xsd *6828*
2.33.3. LI-CreateGuaranteeClaim-Res-Full-MSG.xsd *6880*
2.33.4. LI-CreateGuaranteeClaim-Res-PK-MSG.xsd *6947*
2.34. CreateLIPayment **7001**
2.34.1. LI-CreateLIPayment-Req-Full-MSG.xsd *7001*
2.34.2. LI-CreateLIPayment-Req-IO-MSG.xsd *7080*
2.34.3. LI-CreateLIPayment-Res-Full-MSG.xsd *7142*
2.34.4. LI-CreateLIPayment-Res-PK-MSG.xsd *7222*
2.35. CreateLITransfer **7286**
2.35.1. LI-CreateLITransfer-Req-Full-MSG.xsd *7286*
2.35.2. LI-CreateLITransfer-Req-IO-MSG.xsd *7361*
2.35.3. LI-CreateLITransfer-Res-Full-MSG.xsd *7424*
2.35.4. LI-CreateLITransfer-Res-PK-MSG.xsd *7501*
2.36. CreateProduct **7567**
2.36.1. LI-CreateProduct-Req-Full-MSG.xsd *7567*
2.36.2. LI-CreateProduct-Req-IO-MSG.xsd *7636*
2.36.3. LI-CreateProduct-Res-Full-MSG.xsd *7692*

2.36.4. LI-CreateProduct-Res-PK-MSG.xsd 7762

1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data.The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.
The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

1. Inbound application integration – used when any external system needs to add, modify or query information within FLEXCUBE UBS
2. Outbound application integration– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS
The following sections provide detailed XSD documentation of all operations available in FCUBSLIService of LI-Module

2.FCUBSLIService

Islamic Letters of Credit ServiceIslamic Letters of Credit Service

2.1.ReverseLIPayment

Reverse Islamic LC Payment

2.1.1.LI-ReverseLIPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*

- *AUTHSTAT*
- *Liq-Details*
  - *COMP*
  - *AMTDUE*
  - *PREPAYCOMM*
  - *COMPCCY*
  - *DUEDATE*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4

ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5

- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*

COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9

FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	**Description**	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTAMT

Attribute	Description	
Name	CONTAMT	
Datatype	Number	
Description	Contract Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	**Description**
Name	COMPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**

Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	**Description**
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	**Description**
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	**Description**
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	**Description**
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	Description	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	Description	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS7

Attribute	Description	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS8

Attribute	Description	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	**Description**
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	**Description**
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	**Description**
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	**Description**
Name	FUNMIS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.1.2.LI-ReverseLIPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.1.3.LI-ReverseLIPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*
      - *AMTDUE*
      - *PREPAYCOMM*
      - *COMPCCY*

- *DUEDATE*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date

Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	**Description**
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	**Description**
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS4

Attribute	Description	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	Description	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	Description	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS7

Attribute	Description	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS1

Attribute	Description	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS2

Attribute	Description	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.1.4.LI-ReverseLIPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.2.RolloverContract

Rollover Islamic LC Contract

2.2.1.LI-RolloverContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

- *BENINSTCOVR2*
- *BENINSTCOVR3*
- *BENINSTCOVR4*
- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

Split-Detail

SPTSEQNO

SPTAMTTAG

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	**Description**	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	**Description**	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	**Description**	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	**Description**	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description	
Name	FFTINSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

FFTINSDESC

Attribute	Description	
Name	FFTINSDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	Description
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	**Description**	
Name	STOPDT	
Datatype	Date	
Description	Indicates Stop Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRRQRD

Attribute	**Description**	
Name	ACCRRQRD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CALCMETH

Attribute	**Description**	
Name	CALCMETH	
Datatype	String	
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,N,S

TOP

PARTY

Attribute	**Description**
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	**Description**	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	**Description**	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs; Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	**Description**
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	**Description**
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	**Description**
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	**Description**
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

2.2.2.LI-RolloverContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *Fft-Details*
      - *FFTINSCD*
      - *FFTINSDESC*
      - *SINGLEFFT*
    - *Shipment-Details*
      - *LATSHIPDT*
      - *SHPPERD*
      - *SHPMNTDET*
    - *Commission*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*

CONREFNO

LATEVNSEQNO

Collateral-details

CONREFNO

LATEVNSEQNO

Taxes

CONREFNO

LATEVNSEQNO

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

USEREFNO

Attribute	Description	
Name	USEREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description	
Name	FFTINSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 395

TOP

SHPMNTDET

Attribute	**Description**
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 400

TOP

Commission

Attribute	**Description**
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength, Description: 105 Restrictions: minLength, Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255 Restrictions: minLength, Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

KEY_ID

Attribute	Description	
Name	KEY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNCTION_ID

Attribute	Description	
Name	FUNCTION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.2.3.LI-RolloverContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Brok-Master
CONREFNO
CONTRACTCCY
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
BRKAMTCONCCY
LIQSTATUS
Master
Doc-Upload
DCREFNO
DOC_CATEGORY
DOC_TYPE
REMARKS
Ui-Columns
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description	
Name	TRAKLMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 215

TOP

ACCFORISB

Attribute	**Description**
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSBDT

Attribute	**Description**
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDNO

Attribute	**Description**
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STOPDT1

Attribute	**Description**
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	**Description**
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	**Description**
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LICEXPDT

Attribute	Description	
Name	LICEXPDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SETTLTYP

Attribute	Description	
Name	SETTLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,N

TOP

SETTLMTH

Attribute	Description	
Name	SETTLMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	**Description**
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	**Description**
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	**Description**
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	**Description**
Name	FEECLMADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTIALCLOS

Attribute	**Description**
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TEMPLATEID

Attribute	**Description**
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COLLATLOANALLOWED

Attribute	**Description**
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

MEDIUM

Attribute	Description	
Name	MEDIUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description	
Name	DOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

REFERENCE

Attribute	Description	
Name	REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCCPY

Attribute	Description	
Name	DOCCPY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	**Description**
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	Description	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSUCOMPCD

Attribute	Description	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSUCO

Attribute	Description	
Name	INSUCO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RNDRAT

Attribute	Description	
Name	RNDRAT	
Datatype	Number	
Description	Indicates Rounding Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

APPRATE

Attribute	Description	
Name	APPRATE	
Datatype	String	
Description	Indicates Apply Rate Current : C Next : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,N

TOP

ACQRDAMT

Attribute	Description	
Name	ACQRDAMT	
Datatype	Number	
Description	Indicates Acquired Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs / Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs / Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	**Description**
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS2

Attribute	**Description**
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.2.4.LI-RolloverContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *Fft-Details*
        - *FFTINSCD*
        - *FFTINSDESC*
        - *SINGLEFFT*
      - *Shipment-Details*
        - *LATSHIPDT*
        - *SHPPERD*
        - *SHPMNTDET*
      - *Commission*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Charges*

LATEVNSEQNO

CONREFNO

Settlements

CONREFNO

LATEVNSEQNO

Collateral-details

CONREFNO

LATEVNSEQNO

Taxes

CONREFNO

LATEVNSEQNO

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description	
Name	USEREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description	
Name	FFTINSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

FFTINSDESC

Attribute	Description	
Name	FFTINSDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: Description minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 16

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEY_ID

Attribute	Description
Name	KEY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNCTION_ID

Attribute	**Description**
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.3.DeleteAmendConfirm

Delete Islamic LC Amendment Confirmation

2.3.1.LI-DeleteAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

AMNDSEQNO
ISSDT
EXPDT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*

COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CONAMT

Attribute	Description	
Name	CONAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

INDECAMT

Attribute	Description	
Name	INDECAMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

ADDAMT

Attribute	Description	
Name	ADDAMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	65

TOP

PORTDIS

Attribute	Description	
Name	PORTDIS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	65

TOP

POSTOL

Attribute	Description	
Name	POSTOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

NEGTOL

Attribute	Description	
Name	NEGTOL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMDSTAT

Attribute	Description	
Name	AMDSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADDRESS_1

Attribute	**Description**
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_2

Attribute	**Description**
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_3

Attribute	**Description**
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_4

Attribute	**Description**
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

PARTY_NAME

Attribute	Description	
Name	PARTY_NAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description

Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	**Description**
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	**Description**
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTREIN

Attribute	Description	
Name	AMTREIN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UNIT_OF_MEASUREMENT

Attribute	**Description**
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	**Description**
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSDESC

Attribute	**Description**
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7000

TOP

AMTQ_UT

Attribute	**Description**
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	**Description**
Name	AMTQ_RE

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.3.2.LI-DeleteAmendConfirm-Res-PK-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
CHOICE
Amend-Details-PK
CONTREFNO
Amend-Details-IO
CONTREFNO
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.3.3.LI-DeleteAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

CLSRDT

Attribute	**Description**
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

COUNTRYCD

Attribute	Description

Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	**Description**
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	**Description**
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description

Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description

Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	**Description**
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength, Description: 105 Restrictions: minLength, Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255 Restrictions: minLength, Description: 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

UNIT_OF_MEASUREMENT

Attribute	**Description**
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	**Description**

Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	**Description**
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	**Description**
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	**Description**
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	**Description**
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	**Description**

Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	**Description**
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.3.4.LI-DeleteAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.4.DeleteContract

Delete Islamic LC Contract

2.4.1.LI-DeleteContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

- *BENINSTCOVR2*
- *BENINSTCOVR3*
- *BENINSTCOVR4*
- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

Taxes

Tax

CONREFNO

SCHEME

WAIVER

Tax-Details

RULE

BASISAMNTAG

COMPUEVNT

WAIVER

Rule-Details

VALUEDT

COMPUTATIONDT

CCY

AMT

ESN

Linkages

CONREFNO

LATEVNSEQNO

Linkage-Details

LINKEDTOCCY

LINKEDAMT

EXRATE

CONVLINKEDAMT

LINKEDTOREF

LINKAGETYP

Ui-Fields

ACCOUNT

DEPOSIT

UNCOVAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *ESN*
  - *CNTRPARTY*
  - *PRD*
  - *CCY*
  - *TENOR*
  - *UNITS*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *BRIDGL*
  - *CYSTALTYP*
  - *COLLLIQDAMT*
  - *LIQDLCCHGCOMM*
  - *MATDT*
  - *LOANAMT*
  - *BILLOS*
  - *CONTRACT_CURRENCY*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	**Description**	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	**Description**	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	**Description**	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	**Description**	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	**Description**	
Name	STOPDT	
Datatype	Date	
Description	Indicates Stop Date	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ACCRRQRD

Attribute	**Description**	
Name	ACCRRQRD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CALCMETH

Attribute	**Description**	
Name	CALCMETH	
Datatype	String	
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,N,S

TOP

PARTY

Attribute	**Description**
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STARTDT

Attribute	**Description**
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDATE

Attribute	**Description**
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FOLLWRUL

Attribute	**Description**
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDPER

Attribute	**Description**
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**	
Name	SPTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTAMTTAG

Attribute	**Description**	
Name	SPTAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SPTAMT

Attribute	**Description**	
Name	SPTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTACBRN

Attribute	**Description**	
Name	SPTACBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPTACCCY

Attribute	**Description**

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

2.4.2.LI-DeleteContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.4.3.LI-DeleteContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

- *UDEID*
- *RTCD*
- *USAGE*
- *INTBASIS*
- *SPLAMT*
- *INTRT*
- *INTSPRD*
- *UDEDESC*

Extsys-Ws-Master

- *Extsys-Ws-Details*
  - *EXTWSRESP*
  - *USERREMARKS*

Brok-Master

- *CONREFNO*
- *CONTRACTCCY*
- *BROKPERCENT*
- *BROKAMT*
- *Brok-Detail*
  - *BROKNAME*
  - *BROKER*
  - *BRKACC*
  - *BRKACCCCY*
  - *BRKPERCENT*
  - *BRKAMTACCCCY*
  - *EXRATE*
  - *ORGEXRATE*
  - *NEGRATE*
  - *NEGREFNO*
  - *REMARKS*
  - *BRKAMTCONCCY*
  - *LIQSTATUS*

Master

- *Doc-Upload*
  - *DCREFNO*
  - *DOC_CATEGORY*
  - *DOC_TYPE*
  - *REMARKS*
- *Ui-Columns*

Lic-Master

- *License-Utils-Detail*
  - *IMPLICNO*
  - *GOODSCD*
  - *QTYUTIL*
  - *AMTUTIL*

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description	
Name	TRAKLMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description	
Name	ACCFORISB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ISSBDT

Attribute	Description	
Name	ISSBDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMNDNO

Attribute	Description	
Name	AMNDNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STOPDT1

Attribute	Description	
Name	STOPDT1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description	
Name	REINTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

CUMMULATIVE

Attribute	Description	
Name	CUMMULATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,N

TOP

UNITS

Attribute	Description	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	**Description**
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	**Description**
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	**Description**
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	**Description**
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	**Description**
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description	
Name	FEECLMADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

COLLATLOANALLOWED

Attribute	Description	
Name	COLLATLOANALLOWED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

USERDEFSTAT

Attribute	**Description**
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BENCONFREQD

Attribute	**Description**
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREADVICEDT

Attribute	**Description**
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Details

ORACLE

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Goods-Details

Attribute	**Description**
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	**Description**	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSUCOMPCD

Attribute	**Description**	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSUCO

Attribute	**Description**	
Name	INSUCO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN1

Attribute	**Description**
Name	ADDRSLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN2

Attribute	**Description**
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN3

Attribute	**Description**
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN4

Attribute	**Description**
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	Description
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	**Description**
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	**Description**
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	**Description**
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	**Description**
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.5.DeleteGuaranteeClaim

DeleteGuaranteeClaim

2.5.1.LI-DeleteGuaranteeClaim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*

BENEFNAME

BENADDR

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

TXNSTAT

AUTHSTAT

LATEVNSEQNO

LATVERNO

BRANCH_CONT

Advices

- *MSGTYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*

RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2

BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*

ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description	
Name	CLAIM_SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLAIMDT

Attribute	Description	
Name	CLAIMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLAIMAMT

Attribute	Description	
Name	CLAIMAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

REMRKS

Attribute	Description	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description

Name	MSGTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	

Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	**Description**
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	**Description**
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	**Description**
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	**Description**
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD4

Attribute	Description	
Name	INSTRCD4	
Datatype	String	
Description	Indicates Instruction Code 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ITIMEIND1

Attribute	Description	
Name	ITIMEIND1	
Datatype	String	
Description	Indicates Time Indicator 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	**Description**
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	**Description**
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.5.2.LI-DeleteGuaranteeClaim-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-IO*
    - *CONREFNO*
    - *CLAIM_SEQNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

2.5.3.LI-DeleteGuaranteeClaim-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*
    - *BENEFNAME*
    - *BENADDR*
    - *MAKER*

- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *LATEVNSEQNO*
- *LATVERNO*
- *BRANCH_CONT*
- *Advices*
  - *MSGTYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHGREQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*

INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

ISSDT

Attribute	Description	
Name	ISSDT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Ffts

Attribute	Description

Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	**Description**
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	**Description**
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	**Description**
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	**Description**
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	**Description**
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	**Description**
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	Attribute	Description
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	**Description**
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	**Description**
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BASISAMNTAG

Attribute	Description	
Name	BASISAMNTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	Description	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs; Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs; Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.5.4.LI-DeleteGuaranteeClaim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Guarantee-Claim-PK*
      - *CONREFNO*
      - *CLAIM_SEQNO*
    - *Guarantee-Claim-IO*
      - *CONREFNO*
      - *CLAIM_SEQNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Guarantee-Claim-PK

Attribute	Description
Name	Guarantee-Claim-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.6.DeleteLIPayment

Delete Islamic LC Payment

2.6.1.LI-DeleteLIPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*

- *AMTDUE*
- *PREPAYCOMM*
- *COMPCCY*
- *DUEDATE*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*

REPRES2

REPRES3

REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description	This Node indicates the MIS details for the customer account	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	**Description**	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	**Description**	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	**Description**	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	**Description**	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.6.2.LI-DeleteLIPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.6.3.LI-DeleteLIPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*
      - *AMTDUE*
      - *PREPAYCOMM*
      - *COMPCCY*

- *DUEDATE*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs, Description: 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	Attribute: minOccurs, Description: 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT

Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

Liq-Details

Attribute	**Description**
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	**Description**
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	Description	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	Description	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS7

Attribute	Description	
Name	TRANMIS7	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS8

Attribute	Description	
Name	TRANMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	**Description**
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	**Description**
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	**Description**
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	**Description**
Name	FUNMIS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS5

Attribute	Description	
Name	FUNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS6

Attribute	Description	
Name	FUNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS7

Attribute	Description	
Name	FUNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.7.DeleteLITransfer

Deletion of Islamic Letters of Credit Transfer

2.7.1.LI-DeleteLITransfer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*

- *GOODSCD*
- *GOODSDESC*
- *PREADVDESC*
- *CONREFSHIP*
- *SLNOSHIP*
- *FROM*
- *TO*
- *PARTIALSHIP*
- *TRANSSHIP*
- *SHIPDETAILS*
- *SHIPMARKS*
- *SHIPPERIOD*
- *PORTDISCHG*
- *PORTLOAD*
- *CONREFLOG*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *POSTOL*
- *NEGTOL*
- *Parties-Details*
  - *CONREFPARTY*
  - *SLNOPARTY*
  - *PARTYTP*
  - *PARTYID*
  - *PARTYNAME*
  - *ADDRS1*
  - *ADDRS2*
  - *ADDRS3*
  - *ADDRS4*
  - *LANG*
  - *CNTY*
  - *PARTYDESCM*
- *Document-Details*
  - *CONREFDOC*
  - *SLNODOC*
  - *DOCCD*
  - *DOCTP*
  - *DOCDESCR*
  - *ORIGINALRQD*
  - *NOCOPIES*

- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*
  - *SLNOCLAUSE*
  - *CLAUSECOD*
  - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Limits1*
- *Advices*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *MODULE*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHG_REQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3

- *BENINSTCOVR4*
- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOREF

Attribute	Description	
Name	TOREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURAVL

Attribute	**Description**
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFGOOD

Attribute	**Description**
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOGOOD

Attribute	**Description**
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description	
Name	SHIPDETAILS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description	
Name	SHIPMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	Description	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	Description	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTP

Attribute	Description

Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	**Description**
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	Description	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAUSECOD

Attribute	Description

Name	CLAUSECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSDESC

Attribute	**Description**
Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	**Description**
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description	
Name	MSG_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	60

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODULE

Attribute	Description

Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 48

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	Description	
Name	SINGLEFFT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs; Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	**Description**
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.7.2.LI-DeleteLITransfer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-IO*
    - *FRMREF*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.7.3.LI-DeleteLITransfer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*

CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*
- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*

- *SLNOCLAUSE*
- *CLAUSECOD*
- *CLAUSDESC*

Transfer-Limits

- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*
- *SLNO*

Limits1

Advices

- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *MODULE*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHG_REQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*

- CHRGCCY
- CHRGAMT
- DISACCRAPPL
- WAIVER
- LIQDIND
- Charge-Liquidation
  - ESN
  - COMPNT
  - CHRGCCY
  - CHRGAMT
  - LIQDSTAT
- Settlements
  - CONREFNO
  - Contract-Settlement
    - IBANACNO
    - CUSTSPREAD
    - SPREADDEFN
    - COMPNT
    - TAGCCY
    - ACCBRN
    - ACC
    - ACCCCY
    - EXRATE
    - NETIND
    - ERICCY
    - ERIAMT
    - GENMSG
    - RATECD
    - CLEARNW
    - COVERBY
    - RTGSPMNT
    - BANKPRIOR
    - RTGSNW
    - PAYBY
    - TRANSTYP
    - INSTYP
    - INSNO
    - CHGDET
    - PAYMNTDET1
    - PAYMNTDET2
    - PAYMNTDET3
    - PAYMNTDET4
    - SNDTRRCVINFO1
    - SNDTRRCVINFO2

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURAVL

Attribute	Description
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	Description
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	Description
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	Description
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description

Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	**Description**
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 48

TOP

FFTINSDESC

Attribute	Description

Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	**Description**
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

ORACLE

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	**Description**	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST4

Attribute	**Description**	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	**Description**	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	**Description**	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	**Description**
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	**Description**
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	**Description**
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	**Description**
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	**Description**
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	**Description**
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	**Description**	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	**Description**	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	**Description**	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transfer-PK*
      - *FRMREF*
    - *Transfer-IO*
      - *FRMREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transfer-PK

Attribute	Description
Name	Transfer-PK
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.8.DeleteProduct

Deletion of LI Product

2.8.1.LI-DeleteProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*

LMTSTNRCALCTYP
REKYREQ
REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL

STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details
- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*

NOOFORIGINALS
ORGNALREQ
Clause-Details
CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-GI-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD

- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*

- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *CAPTLIZE*
    - *DISCACCRAPLB*
    - *PROPREQD*
    - *DISCNTBASIS*

DFTRULE

COMPNT

EVNTFRASSC

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYAMNT

Attribute	**Description**
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCY

Attribute	**Description**
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCUSTM

Attribute	**Description**
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDAT

Attribute	**Description**
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

EXPIRNOTREQFLG

Attribute	Description	
Name	EXPIRNOTREQFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXPIRNOTDYS

Attribute	Description	
Name	EXPIRNOTDYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLSURNTFLG

Attribute	Description	
Name	CLSURNTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

CLSURNTRQFLD

Attribute	Description	
Name	CLSURNTRQFLD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGCLAIM

Attribute	**Description**
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVABYLOAN

Attribute	**Description**
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	**Description**
Name	LOANBRIDGEGL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Commission-Details

Attribute	**Description**
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	**Description**
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	**Description**
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RULEIDENTIFICAT

Attribute	**Description**
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description

Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	Description
Name	EVNTDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COLLLCCOM

Attribute	**Description**
Name	COLLLCCOM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Preferences

Attribute	**Description**
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COMMCALCBASIS

Attribute	**Description**
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ccy-Details

Attribute	**Description**

Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	**Description**
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	**Description**
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	**Description**
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** enumeration / I,V,T,O,

TOP

DOCSHRTDESC

Attribute	**Description**
Name	DOCSHRTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

NOOFCOPIES

Attribute	**Description**
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

ORGNALREQ

Attribute	**Description**
Name	ORGNALREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTEXTDESC

Attribute	Description	
Name	FFTTEXTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ADVCD

Attribute	Description	
Name	ADVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SINGLFFT

Attribute	Description	
Name	SINGLFFT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Tracer-Details

Attribute	Description	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	**Description**
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Status-Details

Attribute	**Description**
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUSSEQ

Attribute	**Description**
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	**Description**
Name	STPACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	**Description**
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCNTROLE

Attribute	**Description**
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	**Description**
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Control-Prod-Stat

Attribute	**Description**
Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	**Description**
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	**Description**
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	Attribute	Description
	minOccurs	0

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description	Indicates charges required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Role-To-Head-Mapping

Attribute	Description	
Name	Role-To-Head-Mapping	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String

Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	**Description**
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	**Description**
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

ORACLE

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	**Description**
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	**Description**
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	**Description**
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Customers

Attribute	Description

Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	**Description**
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE

Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	**Description**
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	**Description**
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	**Description**
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.8.2.LI-DeleteProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

2.8.3.LI-DeleteProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*

REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
LC_TYPE

MAXIMUM

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Commission-Details

- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details

- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*
- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*

CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-Gl-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD

EVENTDESC

Accounting-Entries

ACCRLCD

AMTTAG

DRCRINDICTR

TRNCD

NETINDICTR

MISHD

REVALPRGL

REVALLSGL

REVALRTCD

REVALTXNCD

HOLTREAT

REVALREQD

RATE_TYPE_INDICATOR

Advices

MSGTYP

DESC

GENTIME

SUPRS

PRIOR

CHGREQD

Role-To-Head-Mapping

CLASCD

CLASDESC

Mapping-Details

ACCTRL

ROLDESC

ACCTHD

GLDESC

Branch-Ccy-Restrictions

CCYLST

BRNLST

CLASCD

CLASDESC

Branch-List

BRNDISALOW

BRNNAME

Ccy-List

BGTDLCCY

CCYNAME

Prod-Cust-Restrictions

CATGLIS

CLASCD

- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*
  - *DISCACCRAPLB*
  - *PROPREQD*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*
  - *EVNTFRASSC*

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	**Description**
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	**Description**
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	**Description**
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	**Description**
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYP

Attribute	**Description**
Name	PRDTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	**Description**
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	**Description**
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	**Description**
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	**Description**
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	**Description**
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	**Description**
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	**Description**
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	**Description**
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATCD

Attribute	**Description**
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	**Description**
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	**Description**
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	**Description**
Name	EVNTDESCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLLLCCOM

Attribute	Description
Name	COLLLCCOM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Currency-Preferences

Attribute	Description
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description	
Name	DOCSHRTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFCOPIES

Attribute	Description	
Name	NOOFCOPIES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

ORGNALREQ

Attribute	Description	
Name	ORGNALREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTEXTDESC

Attribute	Description
Name	FFTTEXTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description	
Name	TRCERCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

REQIRED

Attribute	Description	
Name	REQIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOFTRCERS

Attribute	Description	
Name	NOFTRCERS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: W,E,

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	**Description**
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	**Description**
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	**Description**
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Control-Prod-Stat

Attribute	Description

Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	Attribute: minOccurs, Description: 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String

Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description

Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	**Description**
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	**Description**
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	**Description**
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	**Description**
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.8.4.LI-DeleteProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.ModifyAmendConfirm

Modify Islamic LC Amendment Confirmation

2.9.1.LI-ModifyAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

AMNDSEQNO
ISSDT
EXPDT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*

COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description	
Name	AMTQ_UT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTQ_RE

Attribute	Description	
Name	AMTQ_RE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.9.2.LI-ModifyAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *EXPDT*
    - *SUBSYSSTAT*
    - *Party-Details*

VERNO

AMNDSEQNO

CUSTREFNO

CUSTREFDT

Fft-Details

CONREFFNO

VERNO

AMNDSEQNO

CODE

DESC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

ESN

EVENTCD

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

AMTQ_UT

AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONAMT

Attribute	Description
Name	CONAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTREFNO

Attribute	Description

Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFFNO

Attribute	**Description**
Name	CONREFFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY

Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

License-Utils-Detail

Attribute	Description	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	**Description**
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.9.3.LI-ModifyAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*

EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONAMT

Attribute	**Description**
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	**Description**
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	**Description**
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	**Description**
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDSTAT

Attribute	**Description**
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,U,R

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description

Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.9.4.LI-ModifyAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-PK*
      - *CONTREFNO*
    - *Amend-Details-IO*
      - *CONTREFNO*
      - *CONAMT*
      - *INDECAMT*
      - *ADDAMT*
      - *FROMPLACE*
      - *TOPLACE*
      - *LATSHIPDT*
      - *SHIPPER*
      - *PORTLOAD*
      - *PORTDIS*
      - *POSTOL*
      - *NEGTOL*
      - *AMDSTAT*
      - *VERNO*
      - *AMNDSEQNO*

EXPDT
SUBSYSSTAT
Party-Details
VERNO
AMNDSEQNO
CUSTREFNO
CUSTREFDT
Fft-Details
CONREFFNO
VERNO
AMNDSEQNO
CODE
DESC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
ESN
EVENTCD
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
AMTQ_UT
AMTQ_RE
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONAMT

Attribute	Description	
Name	CONAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 500

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFFNO

Attribute	Description
Name	CONREFFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description

Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Collateral-details

Attribute	**Description**
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs, Description: 1

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	Indicates Event Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	**Description**
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.ModifyContract

Modify Islamic LC Contract

2.10.1.LI-ModifyContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

TELEPHNO
FAXNUMBER
OPNPLCYFLG
POLICYUTLAMT
CVRDT
INSURANCEAMT
TELEXADDR
WAREHOUSEADDR
DRAFTAMT
DRAFTPCT
Draft-Details
AMTNAM
AMT
Control
Transdet
FROMLCREF
TOLCREF
SLNO
ESN
TRANSAMT
TRANSDT
NEWEXPDT
NEWLATSHIPMENTDT
Contract-Limits
AMOUNTTAG
CUSTNO
LINKAGE_TYPE
LINKAGEPERC
PARTYTYP
LIMITAMT
JVPARENT
SLNO
LINKEDREFNO
LIABILITY_NUMBER
Fundmaster
FUNDID
Insurance
INSUCO
INSUPOLCYNO
INSURANCEAMT
LCYAMT
Dfrrd-Intcomp
CONREFNUM
ESN

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *ESN*
  - *CNTRPARTY*
  - *PRD*
  - *CCY*
  - *TENOR*
  - *UNITS*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *BRIDGL*
  - *CYSTALTYP*
  - *COLLLIQDAMT*
  - *LIQDLCCHGCOMM*
  - *MATDT*
  - *LOANAMT*
  - *BILLOS*
  - *CONTRACT_CURRENCY*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	Description	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	Description	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	Description	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	Description	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	**Description**
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	**Description**
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	**Description**
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	**Description**
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	**Description**
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	100

TOP

DRAFTAMT

Attribute	Description	
Name	DRAFTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRAFTPCT

Attribute	Description	
Name	DRAFTPCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Draft-Details

Attribute	Description	
Name	Draft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	Description	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

PICKESN

Attribute	**Description**
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

EVENT

Attribute	**Description**
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STARTDT

Attribute	**Description**
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDATE

Attribute	**Description**
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FOLLWRUL

Attribute	**Description**
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDPER

Attribute	**Description**
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

ORACLE

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

2.10.2.LI-ModifyContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *BOOKDT*
    - *LATEVNSEQNO*
    - *BRANCH*
    - *MODUCD*
    - *USRDEFSTAT*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LINECID*

LMTTRTENOTYP
SUBSYSSTAT
ESN
REIMTYP
CHRGFRMBEN
ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
EVENTCD
DEALSRC
EXTREFNUM
STOPDT1
CONTREFNO
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
STOPDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CUSTNAME
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH

PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
CONSTAT
AUTHSTATS
AVAILESN
BACKTOBACK
ACKNREVCD
ACKDT
AMNDCHK
CALLINGFNID
URRPREF
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
UCNFAMT
STATUSCNTRLCD
USERDEFSTAT
CON_REF_NUM
Party-Details
PRTYTYP

- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *CONREFNO*
  - *ESN*
  - *VERNO*
  - *PRTYTYP*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *ESN*
- *Fft-Details*
  - *CONREFNO*
  - *ESN*
  - *FFTINSCD*
  - *FFTINSDESC*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *ESN*

- *Clause-Details*
  - *CONREFNO*
  - *ESN*
  - *DOCCD*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Shipment-Details*
  - *CONREFNO*
  - *ESN*
  - *FROMPALCE*
  - *TOPLACE*
  - *PARTIALSHPMNT*
  - *TRANSSHPMNT*
  - *LATSHIPDT*
  - *SHPPERD*
  - *SHPMNTDET*
  - *SHPMNTMARK*
  - *PORTDISCHARGE*
  - *PORTLOADING*
  - *SHPDAYS*
  - *PARSHIPDET*
  - *TRASHIPDET*
- *Goods-Details*
  - *CONREFNO*
  - *GOODDESC*
  - *GOODCD*
  - *REFPREADV*
  - *VERNO*
  - *EVENTCD*
- *Tracer-Details*
  - *CONREFNO*
  - *ESN*
  - *TRACERCD*
  - *TRACERDESC*
  - *TRACERPRTY*
  - *REQRD*
  - *MAXTRACER*
  - *SENTTODATE*
  - *STRTDYS*
  - *LASTTRACDT*
  - *MEDIUM*
  - *FREQ*
  - *TEMPLATE_ID*
- *Drafts*

- *CONREFNO*
- *ESN*
- *DRFTSLNO*
- *DRFTTNR*
- *Draft-Details*

Transdet

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Commission

- *CONREFNO*
- *LATEVNSEQNO*
- *Commission-Details*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *ACCRCCY*
  - *RATTYP*

Charges

- *LATEVNSEQNO*
- *CONREFNO*

- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *Settlement-Detail*
    - *INSTRCD1*
    - *INSTRCD2*
    - *INSTRCD3*
    - *INSTRCD4*

- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*

SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
ESN
EVENTCD
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
CONREFNO
LATEVNSEQNO
Tax
SCHEME
WAIVER
Tax-Details
BASISAMNTAG
COMPUEVNT
WAIVER
ESN
Rule-Details
COMPUTATIONDT
CCY
AMT
ESN
EFFECTIVEDT
STAT
BASISAMT
BASISAMTCCY
Linkages
CONREFNO
LATEVNSEQNO

- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *CONREFNO*
  - *VERNO*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFXRATE*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*
  - *MISGRPCOMP*
  - *MISGRPTXN*
  - *COMPMIS1*

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Lctbs-Lccbclnk-Master
CONTRACT_REF_NO
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
LOANACC
Bcpref
CONREFNO
LATEVNSEQNO
EXCHRT
RTTYP
MATDT
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC

- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTRT*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *KEYID*
- *Brok-Master*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BCREFNO*
    - *EVENTSEQNO*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *SQNO*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *KEY_ID*
  - *FUNCTION_ID*
  - *Doc-Upload*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
- *Lic-Master*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *License-Utils-Detail*
    - *AMTQ_UT*
    - *AMTQ_RE*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description

Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	**Description**
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	**Description**
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	**Description**
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

BOOKDT

Attribute	Description
Name	BOOKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODUCD

Attribute	Description
Name	MODUCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

USRDEFSTAT

Attribute	Description
Name	USRDEFSTAT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TRAKLMT

Attribute	**Description**
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTYTYP

Attribute	**Description**
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLIN

Attribute	**Description**
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

LINECID

Attribute	**Description**
Name	LINECID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: L,D

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 500

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

DEALSRC

Attribute	Description
Name	DEALSRC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

EXTREFNUM

Attribute	Description
Name	EXTREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPDT

Attribute	Description
Name	EXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	**Description**
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

SETTLTYP

Attribute	Description	
Name	SETTLTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,S,N

TOP

SETTLMTH

Attribute	Description	
Name	SETTLMTH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description	
Name	CREDITAVLWITH	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	143

TOP

PAYMNTDT

Attribute	Description	
Name	PAYMNTDT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description	
Name	TRANSBLE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

MAYCONFIRM

Attribute	Description	
Name	MAYCONFIRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REMARK

Attribute	Description	
Name	REMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

RELLCREF

Attribute	Description	
Name	RELLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

CONSTAT

Attribute	Description
Name	CONSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

AVAILESN

Attribute	Description
Name	AVAILESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CALLINGFNID

Attribute	Description
Name	CALLINGFNID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

UNDEREXPDT

Attribute	Description	
Name	UNDEREXPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

UNDRTKNAMT

Attribute	Description	
Name	UNDRTKNAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CON_REF_NUM

Attribute	Description
Name	CON_REF_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PARTYCIFID

Attribute	Description

Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

CUSTADDLIN4

Attribute	Description	
Name	CUSTADDLIN4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDATE

Attribute	Description	
Name	CUSTREFDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTYTYP

Attribute	**Description**
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

MEDTYP

Attribute	**Description**
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	**Description**
Name	MEDADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ESN

Attribute	Description

Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Clause-Details

Attribute	**Description**
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	**Description**
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	**Description**
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	**Description**
Name	PORTDISCHARGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Tracer-Details

Attribute	Description	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRACERCD

Attribute	Description	
Name	TRACERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	**Description**
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	**Description**
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKAGE_TYPE

Attribute	Description	
Name	LINKAGE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description	
Name	LINKAGEPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYTYP

Attribute	Description	
Name	PARTYTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Commission

Attribute	Description	
Name	Commission	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description	Includes Commission details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CCY

Attribute	Description

Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	**Description**
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	**Description**
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String

Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRCCY

Attribute	Description
Name	ACCRCCY
Datatype	String
Description	Indicates Acquired Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	Indicates Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String

Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	Attribute: minOccurs — Description: 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

ORACLE

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD

Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	Description	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	Description	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	Description	
Name	RCVRCUSTNAME4	
Datatype	String	
Description	Indicates Receiver Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description

Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	**Description**
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**

Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO6

Attribute	Description	
Name	SNDRRCVRINFO6	
Datatype	String	
Description	Indicates Sender Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	Description	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	**Description**
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	**Description**
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	Attribute: minOccurs — Description: 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	

Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT

Datatype	Date
Description	Indicates Effective Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STAT

Attribute	**Description**
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BASISAMT

Attribute	**Description**
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTCCY

Attribute	**Description**
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Linkages

Attribute	**Description**
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

Misdetails

Attribute	Description	
Name	Misdetails	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description

Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	**Description**
Name	REFXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description

Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS3

Attribute	**Description**	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS4

Attribute	**Description**	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS5

Attribute	**Description**	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS6

Attribute	**Description**	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS8

Attribute	Description	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS9

Attribute	Description	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPCOMP

Attribute	Description	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS2

Attribute	Description	
Name	FUNDMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS3

Attribute	Description	
Name	FUNDMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS4

Attribute	Description	
Name	FUNDMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS5

Attribute	Description	
Name	FUNDMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXCHRT

Attribute	Description

Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	**Description**
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATDT

Attribute	**Description**
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECDPREF

Attribute	**Description**
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	**Description**
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String

Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

Bcprefdet

Attribute	**Description**
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	**Description**
Name	RTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

KEYID

Attribute	Description
Name	KEYID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	**Description**
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKPERCENT

Attribute	**Description**
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

BROKER

Attribute	Description	
Name	BROKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

BRKACC

Attribute	Description	
Name	BRKACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

BRKACCCCY

Attribute	Description	
Name	BRKACCCCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

SQNO

Attribute	Description
Name	SQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

KEY_ID

Attribute	Description
Name	KEY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNCTION_ID

Attribute	Description
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOC_TYPE

Attribute	Description

Name	DOC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.10.3.LI-ModifyContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

POLICYUTLAMT
CVRDT
INSURANCEAMT
TELEXADDR
WAREHOUSEADDR
DRAFTAMT
DRAFTPCT
Draft-Details
AMTNAM
AMT
Control
Transdet
FROMLCREF
TOLCREF
SLNO
ESN
TRANSAMT
TRANSDT
NEWEXPDT
NEWLATSHIPMENTDT
Contract-Limits
AMOUNTTAG
CUSTNO
LINKAGE_TYPE
LINKAGEPERC
PARTYTYP
LIMITAMT
JVPARENT
SLNO
LINKEDREFNO
LIABILITY_NUMBER
Fundmaster
FUNDID
Insurance
INSUCO
INSUPOLCYNO
INSURANCEAMT
LCYAMT
Dfrrd-Intcomp
CONREFNUM
ESN
COMP
CCY
DUEDATE

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

Taxes

Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID

RTCD

USAGE

INTBASIS

SPLAMT

INTRT

INTSPRD

UDEDESC

Extsys-Ws-Master

Extsys-Ws-Details

EXTWSRESP

USERREMARKS

Brok-Master

CONREFNO

CONTRACTCCY

BROKPERCENT

BROKAMT

Brok-Detail

BROKNAME

BROKER

BRKACC

BRKACCCCY

BRKPERCENT

BRKAMTACCCCY

EXRATE

ORGEXRATE

NEGRATE

NEGREFNO

REMARKS

BRKAMTCONCCY

LIQSTATUS

Master

Doc-Upload

DCREFNO

DOC_CATEGORY

DOC_TYPE

REMARKS

Ui-Columns

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 215

TOP

ACCFORISB

Attribute	**Description**
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSBDT

Attribute	**Description**
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDNO

Attribute	**Description**
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STOPDT1

Attribute	**Description**
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTCCY

Attribute	**Description**
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CIFID

Attribute	**Description**
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description	
Name	REINTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

CUMMULATIVE

Attribute	Description	
Name	CUMMULATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,N

TOP

UNITS

Attribute	Description	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	**Description**	
Name	CHKR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHKDTTIME

Attribute	**Description**	
Name	CHKDTTIME	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTATS

Attribute	**Description**	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description	
Name	FEECLMADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COLLATLOANALLOWED

Attribute	Description	
Name	COLLATLOANALLOWED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description	
Name	DOCDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

REFERENCE

Attribute	Description	
Name	REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

DOCCPY

Attribute	Description	
Name	DOCCPY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	**Description**	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSUCOMPCD

Attribute	**Description**	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSUCO

Attribute	**Description**	
Name	INSUCO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN1

Attribute	**Description**
Name	ADDRSLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN2

Attribute	**Description**
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN3

Attribute	**Description**
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN4

Attribute	**Description**
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Control

Attribute	Description	
Name	Control	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Transdet

Attribute	Description	
Name	Transdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FROMLCREF

Attribute	Description	
Name	FROMLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RNDRAT

Attribute	Description	
Name	RNDRAT	
Datatype	Number	
Description	Indicates Rounding Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

APPRATE

Attribute	Description	
Name	APPRATE	
Datatype	String	
Description	Indicates Apply Rate Current : C Next : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,N

TOP

ACQRDAMT

Attribute	Description	
Name	ACQRDAMT	
Datatype	Number	
Description	Indicates Acquired Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs; Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	**Description**	
Name	BRIDGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CYSTALTYP

Attribute	**Description**	
Name	CYSTALTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COLLLIQDAMT

Attribute	**Description**	
Name	COLLLIQDAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDLCCHGCOMM

Attribute	**Description**	
Name	LIQDLCCHGCOMM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.10.4.LI-ModifyContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *LATVERNO*
      - *PRDCD*
      - *OPERCD*
      - *PRDDESC*
      - *PRDTP*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *SOURCE*
      - *BOOKDT*
      - *LATEVNSEQNO*
      - *BRANCH*
      - *MODUCD*
      - *USRDEFSTAT*
      - *TRAKLMT*

PRTYTYP
CRDLIN
LINECID
LMTTRTENOTYP
SUBSYSSTAT
ESN
REIMTYP
CHRGFRMBEN
ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
EVENTCD
DEALSRC
EXTREFNUM
STOPDT1
CONTREFNO
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
STOPDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CUSTNAME
CUSTREFDT
CUSTREFNO
LICEXPDT

SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
CONREFNOLOG
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
CONSTAT
AUTHSTATS
AVAILESN
BACKTOBACK
ACKNREVCD
ACKDT
AMNDCHK
CALLINGFNID
URRPREF
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
UCNFAMT
STATUSCNTRLCD
USERDEFSTAT

- *CON_REF_NUM*
- *Party-Details*
  - *PRTYTYP*
  - *PARTYDESC*
  - *PARTYCIFID*
  - *CUSTNAME*
  - *CUSTADDLIN1*
  - *CUSTADDLIN2*
  - *CUSTADDLIN3*
  - *CUSTADDLIN4*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDATE*
  - *LANGCD*
  - *TEMPLATE_ID*
  - *Party-Other-Addresses*
    - *CONREFNO*
    - *ESN*
    - *VERNO*
    - *PRTYTYP*
    - *MEDTYP*
    - *MEDADDR*
    - *ACCNO*
- *Advice-Details*
  - *MSGTYP*
  - *PRTY*
  - *PRTYID*
  - *PRTYNAME*
  - *MEDIUM*
  - *PRIORITY*
  - *SUPRESS*
  - *CHGREQD*
  - *ESN*
  - *Fft-Details*
    - *CONREFNO*
    - *ESN*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Documents-Details*
  - *DOCCD*
  - *DOCTYP*
  - *DOCDESC*
  - *REFERENCE*
  - *DOCCPY*

- *NOOFORIGINALS*
- *DOCORIGINAL*
- *ESN*
- *Clause-Details*
  - *CONREFNO*
  - *ESN*
  - *DOCCD*
  - *CLAUSECD*
  - *CLAUSEDESC*
- *Shipment-Details*
- *CONREFNO*
- *ESN*
- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*
- *Goods-Details*
- *CONREFNO*
- *GOODDESC*
- *GOODCD*
- *REFPREADV*
- *VERNO*
- *EVENTCD*
- *Tracer-Details*
- *CONREFNO*
- *ESN*
- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*

- *FREQ*
- *TEMPLATE_ID*

Drafts

- *CONREFNO*
- *ESN*
- *DRFTSLNO*
- *DRFTTNR*
- *Draft-Details*

Transdet

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Commission

- *CONREFNO*
- *LATEVNSEQNO*
- *Commission-Details*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *ACCRCCY*
  - *RATTYP*

- *Charges*
  - *LATEVNSEQNO*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *Settlement-Detail*
      - *INSTRCD1*

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1

- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Collateral-details

- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *ESN*
  - *EVENTCD*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*
  - *EXRATE*
  - *COLLTDESC*
  - *ADJSTSIGN*
  - *ADJSTAMT*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *ESN*
    - *Rule-Details*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*
      - *EFFECTIVEDT*
      - *STAT*
      - *BASISAMT*
      - *BASISAMTCCY*

- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *CONREFNO*
    - *VERNO*
    - *LINKEDTOREF*
    - *LINKAGETYP*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFXRATE*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*
  - *TXNMIS3*
  - *TXNMIS4*
  - *TXNMIS5*
  - *TXNMIS6*
  - *TXNMIS7*
  - *TXNMIS8*
  - *TXNMIS9*

MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
Txnmisdetails
Compmisdetails
Fundmisdetails
Lctbs-Lccbclnk-Master
CONTRACT_REF_NO
Split-Master
CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
LOANACC
Bcpref
CONREFNO
LATEVNSEQNO
EXCHRT
RTTYP
MATDT
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN

- *DRPRODAC*
- *CRACCBRN*
- *CRPRODAC*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTRT*
  - *UDEDESC*

Extsys-Ws-Master

- *KEYID*

Brok-Master

- *CONREFNO*
- *LATEVNSEQNO*
- *BROKPERCENT*
- *BROKAMT*
- *Brok-Detail*
  - *BROKNAME*
  - *BCREFNO*
  - *EVENTSEQNO*
  - *BROKER*
  - *BRKACC*
  - *BRKACCCCY*
  - *BRKPERCENT*
  - *BRKAMTACCCCY*
  - *EXRATE*
  - *ORGEXRATE*
  - *NEGRATE*
  - *NEGREFNO*
  - *REMARKS*
  - *SQNO*
  - *BRKAMTCONCCY*
  - *LIQSTATUS*

Master

- *KEY_ID*
- *FUNCTION_ID*
- *Doc-Upload*
  - *DOC_CATEGORY*
  - *DOC_TYPE*
  - *REMARKS*

Lic-Master

- *CONREFNO*
- *LATEVNSEQNO*
- *License-Utils-Detail*

AMTQ_UT

AMTQ_RE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	**Description**
Name	OPERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	**Description**
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTP

Attribute	**Description**
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	**Description**	
Name	USEREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EXTREFNO

Attribute	**Description**	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SOURCE

Attribute	**Description**	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

BOOKDT

Attribute	**Description**	
Name	BOOKDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODUCD

Attribute	Description
Name	MODUCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2

TOP

USRDEFSTAT

Attribute	Description
Name	USRDEFSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LINECID

Attribute	Description
Name	LINECID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / L,D

TOP

SUBSYSSTAT

Attribute	**Description**
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 500

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REIMTYP

Attribute	**Description**
Name	REIMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

CHRGFRMBEN

Attribute	**Description**
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DEALSRC

Attribute	Description
Name	DEALSRC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

EXTREFNUM

Attribute	Description
Name	EXTREFNUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 29

TOP

CLOSDT

Attribute	**Description**
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STOPDT

Attribute	**Description**
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GUARNTYP

Attribute	**Description**
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSREQ

Attribute	**Description**
Name	ISSREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

LICEXPDT

Attribute	**Description**
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SETTLTYP

Attribute	**Description**
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONREFNOLOG

Attribute	Description
Name	CONREFNOLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

CONSTAT

Attribute	**Description**
Name	CONSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTATS

Attribute	**Description**
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

AVAILESN

Attribute	**Description**
Name	AVAILESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BACKTOBACK

Attribute	**Description**
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALLINGFNID

Attribute	Description
Name	CALLINGFNID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UCNFAMT

Attribute	**Description**
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUSCNTRLCD

Attribute	**Description**
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	**Description**
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CON_REF_NUM

Attribute	**Description**
Name	CON_REF_NUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDATE

Attribute	Description	
Name	CUSTREFDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANGCD

Attribute	Description	
Name	LANGCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	Description

Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	**Description**
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DOCCD

Attribute	Description	
Name	DOCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSECD

Attribute	Description	
Name	CLAUSECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSEDESC

Attribute	Description	
Name	CLAUSEDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Shipment-Details

Attribute	Description	
Name	Shipment-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EVENTCD

Attribute	**Description**
Name	EVENTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	**Description**
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	**Description**
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	**Description**
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	**Description**
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Draft-Details

Attribute	Description	
Name	Draft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Transdet

Attribute	Description	
Name	Transdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Contract-Limits

Attribute	Description	
Name	Contract-Limits	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMOUNTTAG

Attribute	Description	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	**Description**
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	Attribute: minOccurs — Description: 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	Attribute: minOccurs — Description: 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number

Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRCCY

Attribute	Description
Name	ACCRCCY
Datatype	String
Description	Indicates Acquired Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	Indicates Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

ORACLE

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs / Description: 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	Attribute: minOccurs / Description: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	Attribute	Description
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description

Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4

Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

EVENTCD

Attribute	Description
Name	EVENTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT

Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Collateral Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	**Description**
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	**Description**

Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	**Description**
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	**Description**
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHEME

Attribute	**Description**

Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	**Description**
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	**Description**
Name	COMPUEVNT
Datatype	String
Description	Indicates Event

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	**Description**
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	**Description**
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	Attribute: minOccurs — Description: 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number

Description	Indicates Converted Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	**Description**
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFXRATE

Attribute	Description
Name	REFXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD2

Attribute	Description	
Name	COSTCD2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD3

Attribute	Description	
Name	COSTCD3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS5

Attribute	Description	
Name	COMPMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Bcpref

Attribute	Description

Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXCHRT

Attribute	**Description**
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTTYP

Attribute	**Description**
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

DRACCBRN

Attribute	Description	
Name	DRACCBRN	
Datatype	String	
Description	Indicates Debit Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

DRPRODAC

Attribute	Description	
Name	DRPRODAC	
Datatype	String	
Description	It indicates Debit Product Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

CRACCBRN

Attribute	Description	
Name	CRACCBRN	
Datatype	String	
Description	Indicates Credit Branch	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRPRODAC

Attribute	Description	
Name	CRPRODAC	
Datatype	String	
Description	Indicates Credit Product Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTRT

Attribute	Description

Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	**Description**
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	**Description**
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	**Description**
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	**Description**
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

EVENTSEQNO

Attribute	Description
Name	EVENTSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRKPERCENT

Attribute	**Description**
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKAMTACCCCY

Attribute	**Description**
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SQNO

Attribute	Description
Name	SQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEY_ID

Attribute	Description
Name	KEY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNCTION_ID

Attribute	Description
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8

TOP

Doc-Upload

Attribute	Description	
Name	Doc-Upload	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DOC_CATEGORY

Attribute	Description	
Name	DOC_CATEGORY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DOC_TYPE

Attribute	Description	
Name	DOC_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.ModifyGuaranteeClaim

ModifyGuaranteeClaim

2.11.1.LI-ModifyGuaranteeClaim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*

BENEFNAME

BENADDR

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

TXNSTAT

AUTHSTAT

LATEVNSEQNO

LATVERNO

BRANCH_CONT

Advices

- *MSGTYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*

RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2

BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*

ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
CONREFNO
Charge-Association

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description

Name	MSGTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	

Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	Attribute: minOccurs — Description: 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	**Description**
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs, Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

2.11.2.LI-ModifyGuaranteeClaim-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-IO*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
      - *Contract-Settlement*
        - *IBANACNO*
        - *CUSTSPREAD*
        - *SPREADDEFN*
        - *COMPNT*
        - *TAGCCY*
        - *ACCBRN*
        - *ACC*
        - *ACCCCY*
        - *EXRATE*
        - *NETIND*
        - *ERICCY*
        - *ERIAMT*

- *GENMSG*
- *RATECD*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *CONTREFNO*
  - *ESN*
  - *COMPNT*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *AMTTAG*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*

- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *SCHEME*

WAIVER

Tax-Details

BASISAMNTAG

COMPUEVNT

WAIVER

ESN

Rule-Details

COMPUTATIONDT

CCY

AMT

ESN

EFFECTIVEDT

STAT

BASISAMT

BASISAMTCCY

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description	
Name	CLAIM_SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	Attribute	Description
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description

Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description	
Name	SNDRCUSTNAME3	
Datatype	String	
Description	Indicates Sender Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	Description	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4

Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	**Description**
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	**Description**
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	**Description**
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	**Description**
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	Attribute: minOccurs — Description: 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BASISAMT

Attribute	Description
Name	BASISAMT

Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTCCY

Attribute	**Description**
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

2.11.3.LI-ModifyGuaranteeClaim-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*
    - *BENEFNAME*
    - *BENADDR*
    - *MAKER*

- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *LATEVNSEQNO*
- *LATVERNO*
- *BRANCH_CONT*
- *Advices*
  - *MSGTYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHGREQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4

SNDTRRCVINFO1

SNDTRRCVINFO2

SNDTRRCVINFO3

SNDTRRCVINFO4

SNDTRRCVINFO5

COVREQRD

RECVCVR

RECEIVER

REIMINST1

REIMINST2

REIMINST3

REIMINST4

RCVRCORRS1

RCVRCORRS2

RCVRCORRS3

RCVRCORRS4

INTERMEDIARY1

INTERMEDIARY2

INTERMEDIARY3

INTERMEDIARY4

ACCWITHINST1

ACCWITHINST2

ACCWITHINST3

ACCWITHINST4

ORDINST1

ORDINST2

ORDINST3

ORDINST4

ORDCUST1

ORDCUST2

ORDCUST3

ORDCUST4

BENINST1

BENINST2

BENINST3

BENINST4

ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

ISSDT

Attribute	Description	
Name	ISSDT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: enumeration / Description: Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs / Description: 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Ffts

Attribute	Description

Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	**Description**	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	**Description**	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	**Description**
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	Attribute	Description
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	**Description**
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	**Description**
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BASISAMNTAG

Attribute	Description	
Name	BASISAMNTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	Description	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs; Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs; Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.11.4.LI-ModifyGuaranteeClaim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Guarantee-Claim-PK*
      - *CONREFNO*
      - *CLAIM_SEQNO*
    - *Guarantee-Claim-IO*
      - *CONREFNO*
      - *CLAIM_SEQNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
        - *Contract-Settlement*
          - *IBANACNO*
          - *CUSTSPREAD*
          - *SPREADDEFN*
          - *COMPNT*
          - *TAGCCY*
          - *ACCBRN*
          - *ACC*
          - *ACCCCY*

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *CONTREFNO*
- *ESN*
- *COMPNT*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *AMTTAG*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*

- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Taxes

CONREFNO

LATEVNSEQNO

Tax

SCHEME

WAIVER

Tax-Details

BASISAMNTAG

COMPUEVNT

WAIVER

ESN

Rule-Details

COMPUTATIONDT

CCY

AMT

ESN

EFFECTIVEDT

STAT

BASISAMT

BASISAMTCCY

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Guarantee-Claim-PK

Attribute	Description
Name	Guarantee-Claim-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACC

Attribute	Description
Name	ACC

Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	Attribute: minOccurs — Description: 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

BASISAMNTAG

Attribute	**Description**
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	**Description**
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFECTIVEDT

Attribute	Description
Name	EFFECTIVEDT
Datatype	Date
Description	Indicates Effective Date
Attributes	Attribute: minOccurs — Description: 0

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates Status
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BASISAMT

Attribute	Description
Name	BASISAMT

Datatype	Number
Description	Indicates Basis Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	Indicates Basis Amount Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.ModifyLITransfer

Modification of Islamic Letters of Credit Transfer

2.12.1.LI-ModifyLITransfer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*

GOODSCD
GOODSDESC
PREADVDESC
CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*

- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*
  - *SLNOCLAUSE*
  - *CLAUSECOD*
  - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Limits1*
- *Advices*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *MODULE*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHG_REQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3

BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOREF

Attribute	Description	
Name	TOREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTREFNO

Attribute	**Description**	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CURAVL

Attribute	**Description**	
Name	CURAVL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFGOOD

Attribute	**Description**	
Name	CONREFGOOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNOGOOD

Attribute	**Description**	
Name	SLNOGOOD	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description	
Name	SHIPDETAILS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description	
Name	SHIPMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	Description	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	Description	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTP

Attribute	Description

Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	**Description**
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	**Description**	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LANG

Attribute	**Description**	
Name	LANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTY

Attribute	**Description**	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAUSECOD

Attribute	Description

Name	CLAUSECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSDESC

Attribute	**Description**
Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	**Description**
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description	
Name	MSG_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	60

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODULE

Attribute	Description

Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 48

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs; Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	**Description**
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	**Description**
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	**Description**
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY5

Attribute	**Description**
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	Description	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

2.12.2.LI-ModifyLITransfer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-IO*
    - *FRMREF*
    - *ESN*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *TOLCUSERREF*
    - *SUBSYSSTAT*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*
    - *CONREFSHIP*
    - *SLNOSHIP*
    - *FROM*
    - *TO*
    - *PARTIALSHIP*

TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *CNTY*

Document-Details
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *NOCOPIES*
- *NOORIGINAL*

Transfer-Limits
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*
- *SLNO*

Advices
- *CONTRACT_REF_NO*
- *EVENT_SEQ_NO*
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHG_REQD*
- *Ffts*

- *Charges*
  - *LATEVNSEQNO*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *Settlement-Detail*
      - *INSTRCD1*

INSTRCD2
INSTRCD3
INSTRCD4
ITIMEIND1
ITIMEIND2
ITIMEIND3
INSTRCD5
CONTREFNO
ESN
COMPNT
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5

Lcl_Clearing

AMTTAG
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSAMT

Attribute	Description	
Name	TRANSAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SUBSYSSTAT

Attribute	Description
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

CONREFSHIP

Attribute	Description	
Name	CONREFSHIP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNOSHIP

Attribute	Description	
Name	SLNOSHIP	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FROM

Attribute	Description	
Name	FROM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

TO

Attribute	Description	
Name	TO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	**Description**
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTP

Attribute	**Description**
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

SLNODOC

Attribute	Description
Name	SLNODOC

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

NOCOPIES

Attribute	Description
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CONTRACT_REF_NO

Attribute	Description	
Name	CONTRACT_REF_NO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	64

TOP

EVENT_SEQ_NO

Attribute	Description

Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String

Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details

Attributes	Attribute	Description
	minOccurs	0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description

Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4

Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

2.12.3.LI-ModifyLITransfer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*

CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*
- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*

- *SLNOCLAUSE*
- *CLAUSECOD*
- *CLAUSDESC*

Transfer-Limits

- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*
- *SLNO*

Limits1

Advices

- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *MODULE*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHG_REQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURAVL

Attribute	Description
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESCM

Attribute	**Description**
Name	PARTYDESCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Document-Details

Attribute	**Description**
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	**Description**
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNODOC

Attribute	**Description**
Name	SLNODOC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	Description
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	Description
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	Description
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description

Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	**Description**
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 48

TOP

FFTINSDESC

Attribute	Description

Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	**Description**
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

ORACLE

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	**Description**
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	**Description**
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	**Description**	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	**Description**	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	**Description**	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	**Description**	
Name	FREETXT2	
Datatype	String	
Description	Indicates Free Text 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.12.4.LI-ModifyLITransfer-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transfer-PK*
      - *FRMREF*
    - *Transfer-IO*
      - *FRMREF*
      - *ESN*
      - *TRANSAMT*
      - *TRANSDT*
      - *NEWEXPDT*
      - *NEWLATESTSHIPDT*
      - *TOLCUSERREF*
      - *SUBSYSSTAT*
      - *CONREFGOOD*
      - *SLNOGOOD*
      - *GOODSCD*
      - *GOODSDESC*
      - *PREADVDESC*
      - *CONREFSHIP*
      - *SLNOSHIP*

- *FROM*
- *TO*
- *PARTIALSHIP*
- *TRANSSHIP*
- *SHIPDETAILS*
- *SHIPMARKS*
- *SHIPPERIOD*
- *PORTDISCHG*
- *PORTLOAD*
- *TXNSTAT*
- *AUTHSTAT*
- *POSTOL*
- *NEGTOL*
- *Parties-Details*
  - *PARTYTP*
  - *PARTYID*
  - *PARTYNAME*
  - *CNTY*
- *Document-Details*
  - *SLNODOC*
  - *DOCCD*
  - *DOCTP*
  - *NOCOPIES*
  - *NOORIGINAL*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Advices*
  - *CONTRACT_REF_NO*
  - *EVENT_SEQ_NO*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*

- *PRTYNAME*
- *CHG_REQD*
- *Ffts*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*

- *RATECD*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *CONTREFNO*
  - *ESN*
  - *COMPNT*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *AMTTAG*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*

NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transfer-PK

Attribute	Description
Name	Transfer-PK
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSAMT

Attribute	Description	
Name	TRANSAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TRANSDT

Attribute	Description	
Name	TRANSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWEXPDT

Attribute	Description

Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	**Description**
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOLCUSERREF

Attribute	**Description**
Name	TOLCUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SUBSYSSTAT

Attribute	**Description**
Name	SUBSYSSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

CONREFGOOD

Attribute	**Description**
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOSHIP

Attribute	**Description**
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	**Description**
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	**Description**
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	**Description**
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	**Description**
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

EVENT_SEQ_NO

Attribute	Description
Name	EVENT_SEQ_NO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MSG_TYPE

Attribute	Description

Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	60

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	44

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	600

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description

Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description

Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1

Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer

Attributes	Attribute	Description
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description

Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	**Description**
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC

Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE

Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.ModifyProduct

Modification of LI Product

2.13.1.LI-ModifyProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*

LMTSTNRCALCTYP
REKYREQ
REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL

STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details
- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*

- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*
  - *CLAUSECD*
  - *DESC*

Fft-Details

- *FFTCD*
- *FFTTEXTDESC*
- *ADVCD*
- *SINGLFFT*

Tracer-Details

- *TRCERCD*
- *DESC*
- *REQIRED*
- *NOFTRCERS*
- *STRTDAYS*
- *FREQNCY*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *TAXRUL*
  - *TAXCMPNT*
  - *BASISCMPNT*
  - *COMPTATIONEVNT*
  - *TYP*

Status-Details

- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *AUTOFRWD*
- *AUTOREVERSE*
- *COMPLETEACCRUALS*
- *TRANSACTIONCD*
- *STATUS*
- *DERVTNRUL*
- *Status-GI-Details*
  - *ACCROLEDESC*
  - *ACCGLDESC*
  - *ACCNTROLE*
  - *TRNSFERGL*

Control-Prod-Stat

Product-Events

- *CLASCD*

- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*

- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *CAPTLIZE*
    - *DISCACCRAPLB*
    - *PROPREQD*
    - *DISCNTBASIS*

DFTRULE

COMPNT

EVNTFRASSC

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description	
Name	REKYAMNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYCCY

Attribute	Description	
Name	REKYCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYCUSTM

Attribute	Description	
Name	REKYCUSTM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYVALDAT

Attribute	Description	
Name	REKYVALDAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGCLAIM

Attribute	**Description**
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVABYLOAN

Attribute	**Description**
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	**Description**
Name	LOANBRIDGEGL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description

Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	Description
Name	EVNTDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

COMMCALCBASIS

Attribute	Description	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Ccy-Details

Attribute	Description

Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	**Description**
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	**Description**
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	**Description**
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description
Name	DOCSHRTDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTEXTDESC

Attribute	Description	
Name	FFTTEXTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ADVCD

Attribute	Description	
Name	ADVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SINGLFFT

Attribute	Description	
Name	SINGLFFT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Tracer-Details

Attribute	Description	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	**Description**
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Status-Details

Attribute	**Description**
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUSSEQ

Attribute	**Description**
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	**Description**
Name	STPACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description	
Name	REVERSEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	Description	
Name	AUTOFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOREVERSE

Attribute	Description	
Name	AUTOREVERSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPLETEACCRUALS

Attribute	Description	
Name	COMPLETEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Control-Prod-Stat

Attribute	Description
Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	**Description**
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	**Description**
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	Attribute	Description
	minOccurs	0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String

Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	**Description**
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	**Description**
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

ORACLE

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	**Description**
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	**Description**
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	**Description**
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Customers

Attribute	Description

Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	**Description**
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE

Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	**Description**
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	**Description**
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	**Description**
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

2.13.2.LI-ModifyProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*
    - *REKYCCY*
    - *REKYCUSTM*
    - *REKYVALDAT*
    - *REKYMATDATE*

REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
MAXIMUM
MAKER
MAKERSTAMP
Commission-Details
COMPNENT

- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *ACQRCCY*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *ACQREQD*
- *Currency-Preferences*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details

- *NOOFCOPIES*
- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*

Fft-Details

- *ADVCD*
- *SINGLFFT*

Tracer-Details

- *REQIRED*
- *NOFTRCERS*
- *STRTDAYS*
- *FREQNCY*

Tax-Scheme

- *SCHME*
- *Tax-Details*

Status-Details

- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *AUTOFRWD*
- *AUTOREVERSE*
- *COMPLETEACCRUALS*
- *TRANSACTIONCD*

- *STATUS*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCROLEDESC*
  - *ACCGLDESC*
  - *PRD*
  - *STATUS*
  - *ACCNTROLE*
  - *TRNSFERGL*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
  - *Advices*
    - *MSGTYP*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*
- *Mapping-Details*
  - *ACCTRL*
  - *ACCTHD*
  - *STAT*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*
- *Branch-List*
  - *BRNDISALOW*
- *Ccy-List*

BGTDLCCY

SOLDCCY

Prod-Cust-Restrictions

CATGLIS

CLASCD

Cust-Categories

CATGDSAW

Customers

CSTID

ALWD

Product-Fields

Field-Details

FLDNUM

FLDNAME

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

Product-Charges

Charge-Details

SETTCCY

DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DFTRULE

COMPNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	**Description**	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	**Description**	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	**Description**	
Name	PRDRMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	**Description**	
Name	PRDSTRTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

INCOTRM

Attribute	**Description**	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

TOLRNCEPOSTV

Attribute	**Description**	
Name	TOLRNCEPOSTV	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOLRNCENEGTV

Attribute	**Description**	
Name	TOLRNCENEGTV	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCOLLEMETHD

Attribute	**Description**	
Name	COMMCOLLEMETHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RLENARATIV

Attribute	Description	
Name	RLENARATIV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RTCODEPRFERD

Attribute	Description	
Name	RTCODEPRFERD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B

TOP

URRPREF

Attribute	Description	
Name	URRPREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description	
Name	PARCONALLOW	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

RULEIDENTIFICAT

Attribute	Description
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

ACQRCCY

Attribute	Description
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SETTLMNTCCY

Attribute	Description

Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	**Description**
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQREQD

Attribute	**Description**
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Preferences

Attribute	**Description**
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMMCALCBASIS

Attribute	**Description**
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></table>

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 1

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

STPACCRUALS

Attribute	Description	
Name	STPACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	Description	
Name	REVERSEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	Description	
Name	AUTOFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOREVERSE

Attribute	Description	
Name	AUTOREVERSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ACCNTROLE

Attribute	**Description**
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	**Description**
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG

Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	**Description**
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVALREQD

Attribute	**Description**
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Advices

Attribute	**Description**
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

Mapping-Details

Attribute	Description	
Name	Mapping-Details	
Datatype		
Description	Includes Mapping details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ACCTRL

Attribute	Description	
Name	ACCTRL	
Datatype	String	
Description	Indicates accounting role.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ACCTHD

Attribute	Description	
Name	ACCTHD	
Datatype	String	
Description	Indicates account head	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STAT

Attribute	Description	
Name	STAT	
Datatype	String	
Description	Indicates the status	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List

Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String

Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	**Description**
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISTYP

Attribute	Description
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String

Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	**Description**
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	**Description**
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	**Description**
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	**Description**

Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

2.13.3.LI-ModifyProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*

REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
LC_TYPE

MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
COMPNENT
COMPNENTDESC
RULEIDENTIFICAT
EVNT
BASISAMNTTYP
BASISAMNTCATG
SETTLMNTCCY
CHNGDRGAMNDMNT
STPAPPLICTION
RATTYP
RATCDUSGE
SHWNINCNTRTMAINSCR
RATCD
ACQREQD
RULEDESC
EVNTDESCR
COLLLCCOM
Currency-Preferences
CCY
COMMCALCBASIS
Ccy-Details
CCY
DEFRAT
MINRATE
MAXRAT
MINSPRD
MAXSPRD
Document-Details
DOCMNTCD
DOCMNTTYP
DOCSHRTDESC
NOOFCOPIES
NOOFORIGINALS
ORGNALREQ
Clause-Details

CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-Gl-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD

- *EVENTDESC*
- *Accounting-Entries*
  - *ACCRLCD*
  - *AMTTAG*
  - *DRCRINDICTR*
  - *TRNCD*
  - *NETINDICTR*
  - *MISHD*
  - *REVALPRGL*
  - *REVALLSGL*
  - *REVALRTCD*
  - *REVALTXNCD*
  - *HOLTREAT*
  - *REVALREQD*
  - *RATE_TYPE_INDICATOR*
- *Advices*
  - *MSGTYP*
  - *DESC*
  - *GENTIME*
  - *SUPRS*
  - *PRIOR*
  - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*
- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*

- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*
  - *DISCACCRAPLB*
  - *PROPREQD*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*
  - *EVNTFRASSC*

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	**Description**
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	**Description**
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	**Description**
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	**Description**
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYP

Attribute	**Description**
Name	PRDTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	**Description**
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description	
Name	MAXRTVARI	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CALQTDDYS

Attribute	Description	
Name	CALQTDDYS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

NUMOFDYS

Attribute	Description	
Name	NUMOFDYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LIFOFIFOCOMM

Attribute	Description	
Name	LIFOFIFOCOMM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	**Description**
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	**Description**
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	**Description**
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	**Description**
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	**Description**
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	**Description**
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	**Description**
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATCD

Attribute	**Description**
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	**Description**
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	**Description**
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	**Description**
Name	EVNTDESCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLLLCCOM

Attribute	**Description**	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	**Description**	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COMMCALCBASIS

Attribute	**Description**	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description	
Name	DOCSHRTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFCOPIES

Attribute	Description	
Name	NOOFCOPIES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

ORGNALREQ

Attribute	Description	
Name	ORGNALREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTEXTDESC

Attribute	Description
Name	FFTTEXTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description	
Name	TRCERCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

REQIRED

Attribute	Description	
Name	REQIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOFTRCERS

Attribute	Description	
Name	NOFTRCERS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: W,E,

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	Description	
Name	REVERSEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	Description	
Name	AUTOFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOREVERSE

Attribute	Description	
Name	AUTOREVERSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPLETEACCRUALS

Attribute	Description	
Name	COMPLETEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Control-Prod-Stat

Attribute	Description

Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	Attribute: minOccurs, Description: 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String

Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CATGLIS

Attribute	Description

Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	**Description**
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	**Description**
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	**Description**	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOC

Attribute	**Description**
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	**Description**
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	**Description**
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.13.4.LI-ModifyProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *STNDRDTNR*
      - *MINTENR*
      - *MAXTENR*
      - *CSHCOLLATRL*
      - *LMTSTNRCALCTYP*
      - *REKYREQ*
      - *REKYAMNT*
      - *REKYCCY*

REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
MAXIMUM
MAKER

- *MAKERSTAMP*
- *Commission-Details*
  - *COMPNENT*
  - *RULEIDENTIFICAT*
  - *EVNT*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *ACQRCCY*
  - *SETTLMNTCCY*
  - *CHNGDRGAMNDMNT*
  - *STPAPPLICTION*
  - *RATTYP*
  - *RATCDUSGE*
  - *SHWNINCNTRTMAINSCR*
  - *ACQREQD*
  - *Currency-Preferences*
    - *COMMCALCBASIS*
  - *Ccy-Details*
    - *DEFRAT*
    - *MINRATE*
    - *MAXRAT*
    - *MINSPRD*
    - *MAXSPRD*
- *Document-Details*
  - *NOOFCOPIES*
  - *NOOFORIGINALS*
  - *ORGNALREQ*
  - *Clause-Details*
- *Fft-Details*
  - *ADVCD*
  - *SINGLFFT*
- *Tracer-Details*
  - *REQIRED*
  - *NOFTRCERS*
  - *STRTDAYS*
  - *FREQNCY*
- *Tax-Scheme*
  - *SCHME*
  - *Tax-Details*
- *Status-Details*
  - *STATUSSEQ*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *AUTOFRWD*

- *AUTOREVERSE*
- *COMPLETEACCRUALS*
- *TRANSACTIONCD*
- *STATUS*
- *DERVTNRUL*
- *Status-Gl-Details*
  - *ACCROLEDESC*
  - *ACCGLDESC*
  - *PRD*
  - *STATUS*
  - *ACCNTROLE*
  - *TRNSFERGL*

Product-Events

- *CLASCD*
- *Event-Details*
  - *EVNTCD*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
  - *Advices*
    - *MSGTYP*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*
- *Mapping-Details*
  - *ACCTRL*
  - *ACCTHD*
  - *STAT*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*

Branch-List

BRNDISALOW

Ccy-List

BGTDLCCY

SOLDCCY

Prod-Cust-Restrictions

CATGLIS

CLASCD

Cust-Categories

CATGDSAW

Customers

CSTID

ALWD

Product-Fields

Field-Details

FLDNUM

FLDNAME

Product-Mis-Details

MISGRP

POOLCD

CSTCD1

CSTCD2

CSTCD4

CSTCD5

Default-Mis-Codes

MISTYP

MISCLS

MISCD

KYID

Product-Charges

Charge-Details

SETTCCY

DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DFTRULE

COMPNT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDSLG

Attribute	**Description**
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	**Description**
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	**Description**
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	**Description**
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	**Description**
Name	PRDGRP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	**Description**
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	**Description**
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	**Description**
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	**Description**
Name	LMTSTNRCALCTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	**Description**
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYAMNT

Attribute	**Description**
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	**Description**
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	**Description**
Name	REKYCUSTM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	**Description**
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E,

TOP

INCLDTODAT

Attribute	**Description**
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRFREQ

Attribute	**Description**
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	**Description**
Name	ACRMNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	**Description**
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRTVARI

Attribute	**Description**
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CALQTDDYS

Attribute	**Description**
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	**Description**
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

RULEIDENTIFICAT

Attribute	Description
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description

Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	**Description**
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

ACQRCCY

Attribute	**Description**
Name	ACQRCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

SETTLMNTCCY

Attribute	**Description**
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	**Description**
Name	CHNGDRGAMNDMNT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPAPPLICTION

Attribute	**Description**	
Name	STPAPPLICTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATTYP

Attribute	**Description**	
Name	RATTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	X,F,S,

TOP

RATCDUSGE

Attribute	**Description**	
Name	RATCDUSGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**	
Name	SHWNINCNTRTMAINSCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Preferences

Attribute	Description
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

DEFRAT

Attribute	Description
Name	DEFRAT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

NOOFCOPIES

Attribute	Description	
Name	NOOFCOPIES	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	5

TOP

ORGNALREQ

Attribute	Description	
Name	ORGNALREQ	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description	
Name	Clause-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 1

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOFTRCERS

Attribute	**Description**
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDAYS

Attribute	**Description**
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREQNCY

Attribute	**Description**
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax-Scheme

Attribute	**Description**
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	**Description**
Name	SCHME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

Tax-Details

Attribute	Description	
Name	Tax-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

Status-Details

Attribute	Description	
Name	Status-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	1

TOP

STATUSSEQ

Attribute	Description	
Name	STATUSSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STPACCRUALS

Attribute	Description	
Name	STPACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	20

TOP

ACCGLDESC

Attribute	Description	
Name	ACCGLDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	255

TOP

PRD

Attribute	Description	
Name	PRD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

TOP

ACCNTROLE

Attribute	Description	
Name	ACCNTROLE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	**Description**
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number

Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	**Description**
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	**Description**
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates currency list

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List.
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String

Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number

Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description

Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	**Description**
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	**Description**
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.14.QueryAmendConfirm

Query of Amendment Confirmation

2.14.1.LI-QueryAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.14.2.LI-QueryAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-IO*
      - *CONTREFNO*
    - *Amend-Details-Full*
      - *CONTREFNO*
      - *CCY*
      - *CONAMT*
      - *INDECAMT*
      - *ADDAMT*
      - *FROMPLACE*
      - *TOPLACE*
      - *LATSHIPDT*
      - *SHIPPER*
      - *PORTLOAD*
      - *PORTDIS*
      - *POSTOL*
      - *NEGTOL*
      - *AMDSTAT*
      - *VERNO*

- *AMNDSEQNO*
- *ISSDT*
- *EXPDT*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *CLSRDT*
- *Party-Details*
  - *PARTYTYPE*
  - *CIFID*
  - *CUSTNAME*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDT*
  - *PARTYDESC*
  - *ADDRESS_1*
  - *ADDRESS_2*
  - *ADDRESS_3*
  - *ADDRESS_4*
  - *LANGUAGE*
  - *ISSUER1*
  - *Party-Other-Addrs*
    - *MEDIUM_TYPE*
    - *MEDIUM_ADDRESS*
    - *ACCOUNT_NO_1*
- *Advices-Details*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PARTY_TYPE*
  - *MEDIUM*
  - *PARTY_ID*
  - *PARTY_NAME*
  - *CHG_REQD*
  - *Fft-Details*
    - *CODE*
    - *DESC*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: pattern; Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 128 Restrictions: pattern; Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 0
Restrictions	Restrictions: Description
	maxLength: 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	**Description**
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	**Description**
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	**Description**
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	Description	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

QTYREIN

Attribute	Description

Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.15.QueryContract

Query Islamic LC Contract

2.15.1.LI-QueryContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTREFNO

Attribute	**Description**
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.15.2.LI-QueryContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
    - *Contract-Details-Full*
      - *LATVERNO*
      - *PRDCD*
      - *OPERCD*
      - *PRDDESC*
      - *PRDTP*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *SOURCE*
      - *TRAKLMT*
      - *PRTYTYP*
      - *CRDLIN*
      - *LMTTRTENOTYP*

REIMTYP
CHRGFRMBEN
ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE

REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID

- *Party-Details*
  - *PRTYTYP*
  - *PARTYDESC*
  - *PARTYCIFID*
  - *CUSTNAME*
  - *CUSTADDLIN1*
  - *CUSTADDLIN2*
  - *CUSTADDLIN3*
  - *CUSTADDLIN4*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDATE*
  - *LANGCD*
  - *ISSBANK*
  - *TEMPLATE_ID*
  - *Party-Other-Addresses*
    - *MEDTYP*
    - *MEDADDR*
    - *ACCNO*
- *Advice-Details*
  - *MSGTYP*
  - *PRTY*
  - *PRTYID*
  - *PRTYNAME*
  - *MEDIUM*
  - *PRIORITY*
  - *SUPRESS*
  - *CHGREQD*
  - *Fft-Details*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Documents-Details*
  - *DOCCD*
  - *DOCTYP*
  - *DOCDESC*
  - *REFERENCE*
  - *DOCCPY*
  - *NOOFORIGINALS*
  - *DOCORIGINAL*
  - *Clause-Details*
    - *CLAUSECD*
    - *CLAUSEDESC*
- *Shipment-Details*

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*

- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*

- *ACCRREQD*
- *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*

CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3

ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

- *COLLTDESC*
- *ADJSTSIGN*
- *ADJSTAMT*

Taxes

- *Tax*
  - *CONREFNO*
  - *SCHEME*
  - *WAIVER*
  - *Tax-Details*
    - *RULE*
    - *BASISAMNTAG*
    - *COMPUEVNT*
    - *WAIVER*
    - *Rule-Details*
      - *VALUEDT*
      - *COMPUTATIONDT*
      - *CCY*
      - *AMT*
      - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*

POOLCD
REFINANCE_RATE
REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN

- *TRANMIS1*
- *TRANMIS2*
- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*

- *BASISAMTCCY*
- *BASISAMT*
- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*

Bcpref

- *CONREFNO*
- *LATEVNSEQNO*
- *BCREFNO*
- *ESN*
- *CNTRPARTY*
- *PRD*
- *CCY*
- *TENOR*
- *UNITS*
- *CRDLINE*
- *RTCD*
- *EXCHRT*
- *RTTYP*
- *MATACC*
- *BRIDGL*
- *CYSTALTYP*
- *COLLLIQDAMT*
- *LIQDLCCHGCOMM*
- *MATDT*
- *LOANAMT*
- *BILLOS*
- *CONTRACT_CURRENCY*
- *RATECDPREF*
- *MAXRATVAR*
- *MINRTVAR*
- *PMNTMD*
- *DRACCBRN*
- *DRPRODAC*

- *CRACCBRN*
- *CRPRODAC*
- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME

Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONTAMT

Attribute	**Description**
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXCONTAMT

Attribute	**Description**
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIABTOL

Attribute	**Description**
Name	LIABTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	Description
Name	TENOR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	**Description**
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	**Description**
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	**Description**
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	**Description**
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	**Description**
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	**Description**
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	**Description**
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDATE

Attribute	Description	
Name	CUSTREFDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANGCD

Attribute	Description	
Name	LANGCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description

Name	MEDADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	**Description**
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	**Description**	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINKEDREFNO

Attribute	**Description**	
Name	LINKEDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LIABILITY_NUMBER

Attribute	**Description**	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Fundmaster

Attribute	**Description**	
Name	Fundmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	**Description**
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	**Description**
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	**Description**
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	**Description**
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.16.QueryGuaranteeClaim

QueryGuaranteeClaim

2.16.1.LI-QueryGuaranteeClaim-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Guarantee-Claim-IO
CONREFNO
CLAIM_SEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.16.2.LI-QueryGuaranteeClaim-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Guarantee-Claim-IO*
      - *CONREFNO*
      - *CLAIM_SEQNO*
    - *Guarantee-Claim-Full*
      - *CONREFNO*
      - *CLAIM_SEQNO*
      - *CLAIMDT*
      - *CLAIMAMT*
      - *REMRKS*
      - *TEMPLATEID*
      - *ISSDT*
      - *EXPDATE*
      - *ACC_CCY*
      - *AMNT*
      - *OS_GUARAMT*
      - *CPTY_NAME*
      - *ADDR*
      - *CPTYTYP*

COUNT_PARTYREF
BENEFNAME
BENADDR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
LATEVNSEQNO
LATVERNO
BRANCH_CONT
Advices
- *MSGTYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1

BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2

ENVCONT3

ENVCONT4

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Charges

CONREFNO

Charge-Association

COMPNT

CREATESN

RULE

WAIVER

DISACCRAPPL

ACCRREQD

DESC

Charge-Application

CREATESN

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

COMPNT

CHRGCCY

CHRGAMT

LIQDSTAT

Taxes

Tax

CONREFNO

SCHEME

WAIVER

Tax-Details

RULE

BASISAMNTAG

COMPUEVNT

WAIVER

Rule-Details

VALUEDT

COMPUTATIONDT

CCY

AMT

ESN

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description	
Name	CLAIM_SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	**Description**
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	**Description**
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	**Description**
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BENEFNAME

Attribute	**Description**
Name	BENEFNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BENADDR

Attribute	**Description**
Name	BENADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description

Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	**Description**	
Name	COVREQRD	
Datatype	String	
Description	Indicates Cover Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

RECVCVR

Attribute	**Description**	
Name	RECVCVR	
Datatype	String	
Description	Indicates Receiver of Cover	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RECEIVER

Attribute	**Description**	
Name	RECEIVER	
Datatype	String	
Description	Indicates Receiver	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

REIMINST1

Attribute	**Description**	
Name	REIMINST1	
Datatype	String	
Description	Indicates Reimburse Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	**Description**
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	**Description**
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	**Description**
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	**Description**
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	**Description**
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	**Description**
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**	
Name	REGREP2	
Datatype	String	
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN

Attributes	Attribute	Description
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TGCCY

Attribute	Description	
Name	TGCCY	
Datatype	String	
Description	Indicates Tag Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

TGAMT

Attribute	Description	
Name	TGAMT	
Datatype	Number	
Description	Indicates Tag Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

SCHEME

Attribute	Description
Name	SCHEME

Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	**Description**
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	**Description**	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Rule-Details

Attribute	**Description**	
Name	Rule-Details	
Datatype		
Description	Includes Rule details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

VALUEDT

Attribute	**Description**	
Name	VALUEDT	
Datatype	Date	
Description	Indicates Value Date	
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.17.QueryLIPayment

Query of LIPayment

2.17.1.LI-QueryLIPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.17.2.LI-QueryLIPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-IO*
      - *CONREFNO*
    - *Payment-Details-Full*
      - *CONTCCY*
      - *CONREFNO*
      - *CONTAMT*
      - *CUSTNAME*
      - *VALDT*
      - *TOTPAID*
      - *PAYMNTREM*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *Liq-Details*
        - *COMP*

- *AMTDUE*
- *PREPAYCOMM*
- *COMPCCY*
- *DUEDATE*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description

Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	**Description**
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	**Description**
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	**Description**
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	**Description**
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	**Description**
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number

Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements

Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description

Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3

Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	**Description**
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST1

Attribute	**Description**
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST2

Attribute	**Description**
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST3

Attribute	**Description**
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4

Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5

Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,P

TOP

Settlement-Detail

Attribute	Description	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	Description	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description	
Name	INSTRCD3	
Datatype	String	
Description	Indicates Instruction Code 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	**Description**	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	**Description**	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	**Description**	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS2

Attribute	**Description**	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.18.QueryLITransfer

Query of Islamic Letters of Credit Transfer

2.18.1.LI-QueryLITransfer-Req-IO-MSG.xsd

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Transfer-IO
FRMREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	**Description**	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.18.2.LI-QueryLITransfer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transfer-IO*
      - *FRMREF*
    - *Transfer-Full*
      - *FRMREF*
      - *LATEVNSEQNO*
      - *LATVERNO*
      - *TOREF*
      - *SLNO*
      - *TRANSAMT*
      - *TRANSDT*
      - *NEWEXPDT*
      - *NEWLATESTSHIPDT*
      - *PERDPRESENTATION*
      - *TOLCUSERREF*
      - *CONTREFNO*
      - *CURAVL*
      - *CONREFGOOD*
      - *SLNOGOOD*

GOODSCD
GOODSDESC
PREADVDESC
CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*

- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*
  - *SLNOCLAUSE*
  - *CLAUSECOD*
  - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Limits1*
- *Advices*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *MODULE*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHG_REQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

COMPNT

CHRGCCY

CHRGAMT

LIQDSTAT

Settlements

CONREFNO

Contract-Settlement

IBANACNO

CUSTSPREAD

SPREADDEFN

COMPNT

TAGCCY

ACCBRN

ACC

ACCCCY

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

CLEARNW

COVERBY

RTGSPMNT

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3

BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CURAVL

Attribute	Description
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description	
Name	SHIPMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	Description	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	Description	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	Description	
Name	PORTLOAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Parties-Details

Attribute	Description	
Name	Parties-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFPARTY

Attribute	Description	
Name	CONREFPARTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNOPARTY

Attribute	Description	
Name	SLNOPARTY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYTP

Attribute	Description	
Name	PARTYTP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

PARTYID

Attribute	Description

Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	**Description**
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

Document-Details

Attribute	Description	
Name	Document-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFDOC

Attribute	Description	
Name	CONREFDOC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNODOC

Attribute	Description	
Name	SLNODOC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DOCCD

Attribute	Description	
Name	DOCCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DOCTP

Attribute	Description

Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	**Description**
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	5

TOP

Clause-Deatils

Attribute	Description	
Name	Clause-Deatils	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CONREFCLAUSE

Attribute	Description	
Name	CONREFCLAUSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNOCLAUSE

Attribute	Description	
Name	SLNOCLAUSE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLAUSECOD

Attribute	Description	
Name	CLAUSECOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CLAUSDESC

Attribute	Description

Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	**Description**
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	**Description**
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 600

TOP

CHG_REQD

Attribute	Description

Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	**Description**
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 48

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description

Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread

Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3

Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	**Description**
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	**Description**
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4

Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	**Description**	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	**Description**	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	**Description**
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	**Description**
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15

Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String

Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT2

Attribute	Description	
Name	ENVCONT2	
Datatype	String	
Description	Indicates Envelope Contents 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT3

Attribute	Description	
Name	ENVCONT3	
Datatype	String	
Description	Indicates Envelope Contents 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD

Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRCUSTNAME4

Attribute	**Description**	
Name	SNDRCUSTNAME4	
Datatype	String	
Description	Indicates Sender Customer Name 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME1

Attribute	**Description**	
Name	RCVRCUSTNAME1	
Datatype	String	
Description	Indicates Receiver Customer Name 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	**Description**	
Name	RCVRCUSTNAME2	
Datatype	String	
Description	Indicates Receiver Customer Name 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME3

Attribute	**Description**	
Name	RCVRCUSTNAME3	
Datatype	String	
Description	Indicates Receiver Customer Name 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

RCVRACC

Attribute	Description	
Name	RCVRACC	
Datatype	String	
Description	Indicates Receiver Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.19.QueryProduct

Query of LI Product

2.19.1.LI-QueryProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

TOP

2.19.2.LI-QueryProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-IO*
      - *PRDCD*
    - *Product-Details-Full*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *PRDTYP*
      - *REVLVNG*
      - *PRDGRPDESC*
      - *PRDTYPDESC*
      - *STNDRDTNR*
      - *MINTENR*
      - *MAXTENR*
      - *CSHCOLLATRL*

LMTSTNRCALCTYP
REKYREQ
REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL

STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details
- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*

- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*
  - *CLAUSECD*
  - *DESC*

Fft-Details

- *FFTCD*
- *FFTTEXTDESC*
- *ADVCD*
- *SINGLFFT*

Tracer-Details

- *TRCERCD*
- *DESC*
- *REQIRED*
- *NOFTRCERS*
- *STRTDAYS*
- *FREQNCY*

Tax-Scheme

- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *TAXRUL*
  - *TAXCMPNT*
  - *BASISCMPNT*
  - *COMPTATIONEVNT*
  - *TYP*

Status-Details

- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *AUTOFRWD*
- *AUTOREVERSE*
- *COMPLETEACCRUALS*
- *TRANSACTIONCD*
- *STATUS*
- *DERVTNRUL*
- *Status-GI-Details*
  - *ACCROLEDESC*
  - *ACCGLDESC*
  - *ACCNTROLE*
  - *TRNSFERGL*

Control-Prod-Stat

Product-Events

- *CLASCD*

- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*

- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *CAPTLIZE*
    - *DISCACCRAPLB*
    - *PROPREQD*
    - *DISCNTBASIS*

DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTENR

Attribute	**Description**
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXTENR

Attribute	**Description**
Name	MAXTENR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	**Description**
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	**Description**
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	**Description**
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYAMNT

Attribute	**Description**
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / A,R,

TOP

COMMCALMETHD

Attribute	**Description**
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	**Description**
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMMPROCFLG

Attribute	**Description**
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	**Description**
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWPRPY

Attribute	**Description**
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	**Description**
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

NRMLRTVARI

Attribute	**Description**
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

MAXRTVARI

Attribute	**Description**
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CALQTDDYS

Attribute	**Description**
Name	CALQTDDYS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	**Description**
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	**Description**
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	**Description**
Name	EXPIRNOTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	**Description**
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COLLBRIDGEGL

Attribute	**Description**
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STATCNFLG

Attribute	**Description**
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LC_TYPE

Attribute	**Description**
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RULEIDENTIFICAT

Attribute	Description
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description

Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	**Description**
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	**Description**
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	**Description**
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

ACQREQD

Attribute	Description	
Name	ACQREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RULEDESC

Attribute	Description	
Name	RULEDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

EVNTDESCR

Attribute	Description	
Name	EVNTDESCR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Document-Details

Attribute	Description	
Name	Document-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DOCMNTCD

Attribute	Description	
Name	DOCMNTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DOCMNTTYP

Attribute	Description	
Name	DOCMNTTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description	
Name	DOCSHRTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTEXTDESC

Attribute	Description
Name	FFTTEXTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description

Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

REQIRED

Attribute	**Description**
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	**Description**
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	**Description**
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	**Description**
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	W,E,

TOP

Status-Details

Attribute	Description	
Name	Status-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

STATUSSEQ

Attribute	Description	
Name	STATUSSEQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

STPACCRUALS

Attribute	Description	
Name	STPACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REVERSEACCRUALS

Attribute	Description	
Name	REVERSEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	Description

Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREVERSE

Attribute	**Description**
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	**Description**
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	**Description**
Name	STATUS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Control-Prod-Stat

Attribute	Description
Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	**Description**
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	Description

Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	**Description**
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B,S,

TOP

Advices

Attribute	**Description**
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST

Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BRNDISALOW

Attribute	Description	
Name	BRNDISALOW	
Datatype	String	
Description	Indicates Branch Disalowed	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

BRNNAME

Attribute	Description	
Name	BRNNAME	
Datatype	String	
Description	Indicates Branch Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYNAME

Attribute	Description
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories

Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number

Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description

Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT

Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	**Description**
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	**Description**
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	**Description**
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.ReopenContract

Reopen Islamic LC Contract

2.20.1.LI-ReopenContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

PARTYDESC
PARTYCIFID
CUSTNAME
CUSTADDLIN1
CUSTADDLIN2
CUSTADDLIN3
CUSTADDLIN4
COUNTRYCD
CUSTREFNO
CUSTREFDATE
LANGCD
ISSBANK
TEMPLATE_ID
Party-Other-Addresses
MEDTYP
MEDADDR
ACCNO
Advice-Details
MSGTYP
PRTY
PRTYID
PRTYNAME
MEDIUM
PRIORITY
SUPRESS
CHGREQD
Fft-Details
FFTINSCD
FFTINSDESC
SINGLEFFT
Documents-Details
DOCCD
DOCTYP
DOCDESC
REFERENCE
DOCCPY
NOOFORIGINALS
DOCORIGINAL
Clause-Details
CLAUSECD
CLAUSEDESC
Shipment-Details
FROMPALCE
TOPLACE

PARTIALSHPMNT
TRANSSHPMNT
LATSHIPDT
SHPPERD
SHPMNTDET
SHPMNTMARK
PORTDISCHARGE
PORTLOADING
SHPDAYS
PARSHIPDET
TRASHIPDET
Goods-Details
GOODDESC
GOODCD
REFPREADV
Tracer-Details
TRACERCD
TRACERDESC
TRACERPRTY
REQRD
MAXTRACER
SENTTODATE
STRTDYS
LASTTRACDT
MEDIUM
FREQ
TEMPLATE_ID
Drafts
DRFTSLNO
DRFTTNR
PCTAMT
CRDAYSFRM
DRAWEE
ADDRS1
ADDRS2
ADDRS3
INSUCOMPCD
INSUCO
ADDRSLN1
ADDRSLN2
ADDRSLN3
ADDRSLN4
INSUEXPDT
INSUPOLCYNO

- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

Charge-Application

CREATESN

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

COMPNT

CHRGCCY

CHRGAMT

LIQDSTAT

Settlements

CONREFNO

Contract-Settlement

IBANACNO

CUSTSPREAD

SPREADDEFN

COMPNT

TAGCCY

ACCBRN

ACC

ACCCCY

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

CLEARNW

COVERBY

RTGSPMNT

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

Split-Detail

SPTSEQNO

SPTAMTTAG

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SOURCE

Attribute	**Description**
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	**Description**
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTYTYP

Attribute	**Description**
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLIN

Attribute	**Description**
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description	
Name	LMTTRTENOTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,D

TOP

REIMTYP

Attribute	Description	
Name	REIMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

CHRGFRMBEN

Attribute	Description	
Name	CHRGFRMBEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	210

TOP

ADDAMTCOVERD

Attribute	Description	
Name	ADDAMTCOVERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	Description	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	Description	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	Description	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	Description	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	100

TOP

DRAFTAMT

Attribute	Description	
Name	DRAFTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRAFTPCT

Attribute	Description	
Name	DRAFTPCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Draft-Details

Attribute	Description	
Name	Draft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	Description	
Name	AMTNAM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs; Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	**Description**	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	**Description**	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	**Description**	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	**Description**	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

2.20.2.LI-ReopenContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *Commission*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Collateral-details*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Taxes*
      - *CONREFNO*
      - *LATEVNSEQNO*

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EXTREFNO

Attribute	**Description**	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Commission

Attribute	**Description**	
Name	Commission	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	**Description**	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

KEY_ID

Attribute	Description	
Name	KEY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNCTION_ID

Attribute	Description	
Name	FUNCTION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.20.3.LI-ReopenContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

Taxes

Tax

CONREFNO

SCHEME

WAIVER

Tax-Details

RULE

BASISAMNTAG

COMPUEVNT

WAIVER

Rule-Details

VALUEDT

COMPUTATIONDT

CCY

AMT

ESN

Linkages

CONREFNO

LATEVNSEQNO

Linkage-Details

LINKEDTOCCY

LINKEDAMT

EXRATE

CONVLINKEDAMT

LINKEDTOREF

LINKAGETYP

Ui-Fields

ACCOUNT

DEPOSIT

UNCOVAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
Lctbs-Lccbclnk-Master
CONTRACT_REF_NO
Lctbs-Lccbclnk-Master-Child
BCREFNO
BCCY
BILL_AMT
OURLCREF
Split-Master
CONREFNO
Split-Master
BASISAMTTAG
BASISAMTCCY
BASISAMT
Split-Detail
SPTSEQNO
SPTAMTTAG

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Brok-Master
CONREFNO
CONTRACTCCY
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
BRKAMTCONCCY
LIQSTATUS
Master
Doc-Upload
DCREFNO
DOC_CATEGORY
DOC_TYPE
REMARKS
Ui-Columns
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description	
Name	TRAKLMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description	
Name	ACCFORISB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ISSBDT

Attribute	Description	
Name	ISSBDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMNDNO

Attribute	Description	
Name	AMNDNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STOPDT1

Attribute	Description	
Name	STOPDT1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	**Description**	
Name	EXPDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXPPLACE

Attribute	**Description**	
Name	EXPPLACE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	29

TOP

CLOSDT

Attribute	**Description**	
Name	CLOSDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GUARNTYP

Attribute	**Description**	
Name	GUARNTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CIFID

Attribute	**Description**
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LICEXPDT

Attribute	Description	
Name	LICEXPDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SETTLTYP

Attribute	Description	
Name	SETTLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,N

TOP

SETTLMTH

Attribute	Description	
Name	SETTLMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description	
Name	FEECLMADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COLLATLOANALLOWED

Attribute	Description	
Name	COLLATLOANALLOWED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

MEDIUM

Attribute	Description	
Name	MEDIUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

ORACLE

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	**Description**	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS3

Attribute	**Description**	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSUCOMPCD

Attribute	**Description**	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSUCO

Attribute	**Description**	
Name	INSUCO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Control

Attribute	Description	
Name	Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Transdet

Attribute	Description	
Name	Transdet	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FROMLCREF

Attribute	Description	
Name	FROMLCREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEWLATSHIPMENTDT

Attribute	**Description**	
Name	NEWLATSHIPMENTDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Limits

Attribute	**Description**	
Name	Contract-Limits	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMOUNTTAG

Attribute	**Description**	
Name	AMOUNTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**	
Name	CUSTNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Fundmaster

Attribute	Description
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RNDRAT

Attribute	Description	
Name	RNDRAT	
Datatype	Number	
Description	Indicates Rounding Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

APPRATE

Attribute	Description	
Name	APPRATE	
Datatype	String	
Description	Indicates Apply Rate Current : C Next : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,N

TOP

ACQRDAMT

Attribute	Description	
Name	ACQRDAMT	
Datatype	Number	
Description	Indicates Acquired Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs / Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs / Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	Attribute: minOccurs — Description: 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	Attribute: minOccurs — Description: 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	**Description**
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	**Description**
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	**Description**
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	**Description**

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.20.4.LI-ReopenContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *Commission*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Collateral-details*
        - *CONREFNO*
        - *LATEVNSEQNO*

Taxes

CONREFNO

LATEVNSEQNO

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: Description minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 16

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

Brok-Master

Attribute	Description	
Name	Brok-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Master

Attribute	Description	
Name	Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

KEY_ID

Attribute	Description
Name	KEY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNCTION_ID

Attribute	**Description**
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.21.ReverseContract

Reverse Islamic LC Contract

2.21.1.LI-ReverseContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

PARTYDESC
PARTYCIFID
CUSTNAME
CUSTADDLIN1
CUSTADDLIN2
CUSTADDLIN3
CUSTADDLIN4
COUNTRYCD
CUSTREFNO
CUSTREFDATE
LANGCD
ISSBANK
TEMPLATE_ID
Party-Other-Addresses
MEDTYP
MEDADDR
ACCNO
Advice-Details
MSGTYP
PRTY
PRTYID
PRTYNAME
MEDIUM
PRIORITY
SUPRESS
CHGREQD
Fft-Details
FFTINSCD
FFTINSDESC
SINGLEFFT
Documents-Details
DOCCD
DOCTYP
DOCDESC
REFERENCE
DOCCPY
NOOFORIGINALS
DOCORIGINAL
Clause-Details
CLAUSECD
CLAUSEDESC
Shipment-Details
FROMPALCE
TOPLACE

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

TELEPHNO
FAXNUMBER
OPNPLCYFLG
POLICYUTLAMT
CVRDT
INSURANCEAMT
TELEXADDR
WAREHOUSEADDR
DRAFTAMT
DRAFTPCT
Draft-Details
AMTNAM
AMT
Control
Transdet
FROMLCREF
TOLCREF
SLNO
ESN
TRANSAMT
TRANSDT
NEWEXPDT
NEWLATSHIPMENTDT
Contract-Limits
AMOUNTTAG
CUSTNO
LINKAGE_TYPE
LINKAGEPERC
PARTYTYP
LIMITAMT
JVPARENT
SLNO
LINKEDREFNO
LIABILITY_NUMBER
Fundmaster
FUNDID
Insurance
INSUCO
INSUPOLCYNO
INSURANCEAMT
LCYAMT
Dfrrd-Intcomp
CONREFNUM
ESN

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

Split-Detail

SPTSEQNO

SPTAMTTAG

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SOURCE

Attribute	**Description**
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	**Description**
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTYTYP

Attribute	**Description**
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLIN

Attribute	**Description**
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	**Description**	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	**Description**	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	**Description**	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	**Description**	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	**Description**	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	**Description**	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	**Description**	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	**Description**
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	**Description**
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	**Description**
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	**Description**
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description	
Name	FUNDMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS10

Attribute	Description	
Name	FUNDMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTREFNO

Attribute	**Description**
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

2.21.3.LI-ReverseContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

CONREFNO

SCHEME

WAIVER

Tax-Details

RULE

BASISAMNTAG

COMPUEVNT

WAIVER

Rule-Details

VALUEDT

COMPUTATIONDT

CCY

AMT

ESN

Linkages

CONREFNO

LATEVNSEQNO

Linkage-Details

LINKEDTOCCY

LINKEDAMT

EXRATE

CONVLINKEDAMT

LINKEDTOREF

LINKAGETYP

Ui-Fields

ACCOUNT

DEPOSIT

UNCOVAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Brok-Master
CONREFNO
CONTRACTCCY
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
BRKAMTCONCCY
LIQSTATUS
Master
Doc-Upload
DCREFNO
DOC_CATEGORY
DOC_TYPE
REMARKS
Ui-Columns
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL

QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length — Description: 3 Restrictions: pattern — Description: [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description	
Name	ACCFORISB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ISSBDT

Attribute	Description	
Name	ISSBDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMNDNO

Attribute	Description	
Name	AMNDNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STOPDT1

Attribute	Description	
Name	STOPDT1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

LICEXPDT

Attribute	Description	
Name	LICEXPDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SETTLTYP

Attribute	Description	
Name	SETTLTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,S,N

TOP

SETTLMTH

Attribute	Description	
Name	SETTLMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description	
Name	REINTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

CUMMULATIVE

Attribute	Description	
Name	CUMMULATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,N

TOP

UNITS

Attribute	Description	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHKR

Attribute	**Description**
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHKDTTIME

Attribute	**Description**
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	**Description**
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	**Description**
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	**Description**
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	**Description**
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	**Description**
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	**Description**
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description	
Name	FEECLMADV	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

COLLATLOANALLOWED

Attribute	Description	
Name	COLLATLOANALLOWED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

USERDEFSTAT

Attribute	**Description**
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BENCONFREQD

Attribute	**Description**
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PREADVICEDT

Attribute	**Description**
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 150

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDRS2

Attribute	Description	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

INSUCOMPCD

Attribute	Description	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

INSUCO

Attribute	Description	
Name	INSUCO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	maxOccurs: unbounded minOccurs: 0

TOP

FROMLCREF

Attribute	Description
Name	FROMLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RNDRAT

Attribute	Description	
Name	RNDRAT	
Datatype	Number	
Description	Indicates Rounding Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

APPRATE

Attribute	Description	
Name	APPRATE	
Datatype	String	
Description	Indicates Apply Rate Current : C Next : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,N

TOP

ACQRDAMT

Attribute	Description	
Name	ACQRDAMT	
Datatype	Number	
Description	Indicates Acquired Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.22.AuthorizeAmendConfirm

Authorize Islamic LC Amendment Confirmation

2.22.1.LI-AuthorizeAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

- *AMNDSEQNO*
- *ISSDT*
- *EXPDT*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *CLSRDT*
- *Party-Details*
  - *PARTYTYPE*
  - *CIFID*
  - *CUSTNAME*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDT*
  - *PARTYDESC*
  - *ADDRESS_1*
  - *ADDRESS_2*
  - *ADDRESS_3*
  - *ADDRESS_4*
  - *LANGUAGE*
  - *ISSUER1*
  - *Party-Other-Addrs*
    - *MEDIUM_TYPE*
    - *MEDIUM_ADDRESS*
    - *ACCOUNT_NO_1*
- *Advices-Details*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PARTY_TYPE*
  - *MEDIUM*
  - *PARTY_ID*
  - *PARTY_NAME*
  - *CHG_REQD*
  - *Fft-Details*
    - *CODE*
    - *DESC*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*

COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description	
Name	AMTQ_UT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTQ_RE

Attribute	Description	
Name	AMTQ_RE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.22.2.LI-AuthorizeAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable, Description: true
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: pattern, Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.22.3.LI-AuthorizeAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *CLSRDT*
- *Party-Details*
  - *PARTYTYPE*
  - *CIFID*
  - *CUSTNAME*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDT*
  - *PARTYDESC*
  - *ADDRESS_1*
  - *ADDRESS_2*
  - *ADDRESS_3*
  - *ADDRESS_4*
  - *LANGUAGE*
  - *ISSUER1*
  - *Party-Other-Addrs*
    - *MEDIUM_TYPE*
    - *MEDIUM_ADDRESS*
    - *ACCOUNT_NO_1*
- *Advices-Details*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PARTY_TYPE*
  - *MEDIUM*
  - *PARTY_ID*
  - *PARTY_NAME*
  - *CHG_REQD*
  - *Fft-Details*
    - *CODE*
    - *DESC*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONAMT

Attribute	**Description**
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	**Description**
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	**Description**
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	**Description**
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	**Description**
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description

Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

License-Utils-Detail

Attribute	Description	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	Description	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-PK*
      - *CONTREFNO*
    - *Amend-Details-IO*
      - *CONTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.23.AuthorizeContract

Authorize Islamic LC Contract

2.23.1.LI-AuthorizeContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

PARTYDESC
PARTYCIFID
CUSTNAME
CUSTADDLIN1
CUSTADDLIN2
CUSTADDLIN3
CUSTADDLIN4
COUNTRYCD
CUSTREFNO
CUSTREFDATE
LANGCD
ISSBANK
TEMPLATE_ID
Party-Other-Addresses
MEDTYP
MEDADDR
ACCNO
Advice-Details
MSGTYP
PRTY
PRTYID
PRTYNAME
MEDIUM
PRIORITY
SUPRESS
CHGREQD
Fft-Details
FFTINSCD
FFTINSDESC
SINGLEFFT
Documents-Details
DOCCD
DOCTYP
DOCDESC
REFERENCE
DOCCPY
NOOFORIGINALS
DOCORIGINAL
Clause-Details
CLAUSECD
CLAUSEDESC
Shipment-Details
FROMPALCE
TOPLACE

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *ESN*
  - *CNTRPARTY*
  - *PRD*
  - *CCY*
  - *TENOR*
  - *UNITS*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *BRIDGL*
  - *CYSTALTYP*
  - *COLLLIQDAMT*
  - *LIQDLCCHGCOMM*
  - *MATDT*
  - *LOANAMT*
  - *BILLOS*
  - *CONTRACT_CURRENCY*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	Description	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	Description	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	Description	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	Description	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CIFID

Attribute	**Description**
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description	
Name	FFTINSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

FFTINSDESC

Attribute	Description	
Name	FFTINSDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs — Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	Attribute	Description
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	Attribute: minOccurs — Description: 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	**Description**
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	**Description**
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	**Description**
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	**Description**
Name	COMMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Contract-Details-IO
CONREFNO
USEREFNO
EXTREFNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

EXTREFNO

Attribute	**Description**	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.23.3.LI-AuthorizeContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Brok-Master
CONREFNO
CONTRACTCCY
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
BRKAMTCONCCY
LIQSTATUS
Master
Doc-Upload
DCREFNO
DOC_CATEGORY
DOC_TYPE
REMARKS
Ui-Columns
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description	
Name	REINTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

CUMMULATIVE

Attribute	Description	
Name	CUMMULATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	C,N

TOP

UNITS

Attribute	Description	
Name	UNITS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,M

TOP

FREQ

Attribute	Description	
Name	FREQ	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSUCOMPCD

Attribute	**Description**
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSUCO

Attribute	**Description**
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Control

Attribute	Description	
Name	Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Transdet

Attribute	Description	
Name	Transdet	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FROMLCREF

Attribute	Description	
Name	FROMLCREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Fundmaster

Attribute	Description
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	Attribute: minOccurs — Description: 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs / Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs / Description: 1
Restrictions	Restrictions: maxLength / Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs / Description: 0
Restrictions	Restrictions: maxLength / Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs / Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs; Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description	
Name	SPTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTAMTTAG

Attribute	Description	
Name	SPTAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SPTAMT

Attribute	Description	
Name	SPTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTACBRN

Attribute	Description	
Name	SPTACBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

BRIDGL

Attribute	**Description**
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CYSTALTYP

Attribute	**Description**
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COLLLIQDAMT

Attribute	**Description**
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	**Description**
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.24.AuthorizeGuaranteeClaim

AuthorizeGuaranteeClaim

2.24.1.LI-AuthorizeGuaranteeClaim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*

BENEFNAME
BENADDR
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
LATEVNSEQNO
LATVERNO
BRANCH_CONT
Advices
- *MSGTYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*

Settlements
- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*

RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2

BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*

- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description	
Name	CLAIM_SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLAIMDT

Attribute	Description	
Name	CLAIMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLAIMAMT

Attribute	Description	
Name	CLAIMAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

REMRKS

Attribute	Description	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	**Description**
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	**Description**
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	**Description**
Name	AMNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description

Name	MSGTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	

Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	**Description**
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	**Description**
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs, Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

2.24.2.LI-AuthorizeGuaranteeClaim-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-IO*
    - *CONREFNO*
    - *CLAIM_SEQNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

2.24.3.LI-AuthorizeGuaranteeClaim-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*
    - *BENEFNAME*
    - *BENADDR*
    - *MAKER*

- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *LATEVNSEQNO*
- *LATVERNO*
- *BRANCH_CONT*
- *Advices*
  - *MSGTYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHGREQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4

SNDTRRCVINFO1

SNDTRRCVINFO2

SNDTRRCVINFO3

SNDTRRCVINFO4

SNDTRRCVINFO5

COVREQRD

RECVCVR

RECEIVER

REIMINST1

REIMINST2

REIMINST3

REIMINST4

RCVRCORRS1

RCVRCORRS2

RCVRCORRS3

RCVRCORRS4

INTERMEDIARY1

INTERMEDIARY2

INTERMEDIARY3

INTERMEDIARY4

ACCWITHINST1

ACCWITHINST2

ACCWITHINST3

ACCWITHINST4

ORDINST1

ORDINST2

ORDINST3

ORDINST4

ORDCUST1

ORDCUST2

ORDCUST3

ORDCUST4

BENINST1

BENINST2

BENINST3

BENINST4

ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

ISSDT

Attribute	Description	
Name	ISSDT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

EXPDATE

Attribute	Description	
Name	EXPDATE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

ACC_CCY

Attribute	Description	
Name	ACC_CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

COUNT_PARTYREF

Attribute	**Description**
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BENEFNAME

Attribute	**Description**
Name	BENEFNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BENADDR

Attribute	**Description**
Name	BENADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYPE

Attribute	Description
Name	MSGTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Ffts

Attribute	Description

Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	**Description**
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	**Description**
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	**Description**
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	Attribute	Description
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	**Description**
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	**Description**
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BASISAMNTAG

Attribute	**Description**	
Name	BASISAMNTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	**Description**	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	**Description**	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Rule-Details

Attribute	**Description**
Name	Rule-Details
Datatype	
Description	Includes Rule details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs; Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs; Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Guarantee-Claim-PK*
      - *CONREFNO*
      - *CLAIM_SEQNO*
    - *Guarantee-Claim-IO*
      - *CONREFNO*
      - *CLAIM_SEQNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Guarantee-Claim-PK

Attribute	Description
Name	Guarantee-Claim-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.25.AuthorizeLIPayment

Authorize Islamic LC Payment

2.25.1.LI-AuthorizeLIPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*

- *AMTDUE*
- *PREPAYCOMM*
- *COMPCCY*
- *DUEDATE*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	**Description**
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	**Description**
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	**Description**
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	**Description**
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

NIPPAYER

Attribute	**Description**	
Name	NIPPAYER	
Datatype	Number	
Description	Indicates Nip Payer	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description	This Node indicates the MIS details for the customer account	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS7

Attribute	**Description**	
Name	TXNMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS8

Attribute	**Description**	
Name	TXNMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS9

Attribute	**Description**	
Name	TXNMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

MISGRPCOMP

Attribute	**Description**	
Name	MISGRPCOMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS7

Attribute	**Description**	
Name	COMMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS8

Attribute	**Description**	
Name	COMMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS9

Attribute	**Description**	
Name	COMMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS10

Attribute	**Description**	
Name	COMMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS1

Attribute	Description	
Name	FUNMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS2

Attribute	Description	
Name	FUNMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS3

Attribute	Description	
Name	FUNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS4

Attribute	Description	
Name	FUNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.25.2.LI-AuthorizeLIPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONREFNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.25.3.LI-AuthorizeLIPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*
      - *AMTDUE*
      - *PREPAYCOMM*
      - *COMPCCY*

- *DUEDATE*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

- *RCVRACC*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*

FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs — Description: 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	Attribute: minOccurs — Description: 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

Liq-Details

Attribute	**Description**
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	**Description**
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	Attribute	Description
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

ORACLE

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	Description	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	Description	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	**Description**
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	**Description**
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	**Description**
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	**Description**
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	**Description**
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	**Description**
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS8

Attribute	Description	
Name	FUNMIS8	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS9

Attribute	Description	
Name	FUNMIS9	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONREFNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.26.AuthorizeLITransfer

Authorization of Islamic Letters of Credit Transfer

2.26.1.LI-AuthorizeLITransfer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*

GOODSCD
GOODSDESC
PREADVDESC
CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*

- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*
  - *SLNOCLAUSE*
  - *CLAUSECOD*
  - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Limits1*
- *Advices*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *MODULE*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHG_REQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

COMPNT

CHRGCCY

CHRGAMT

LIQDSTAT

Settlements

CONREFNO

Contract-Settlement

IBANACNO

CUSTSPREAD

SPREADDEFN

COMPNT

TAGCCY

ACCBRN

ACC

ACCCCY

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

CLEARNW

COVERBY

RTGSPMNT

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3

BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TOREF

Attribute	Description	
Name	TOREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURAVL

Attribute	**Description**
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFGOOD

Attribute	**Description**
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOGOOD

Attribute	**Description**
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description	
Name	SHIPDETAILS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description	
Name	SHIPMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	Description	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	Description	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTP

Attribute	Description

Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	**Description**
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	Description	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAUSECOD

Attribute	Description

Name	CLAUSECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSDESC

Attribute	**Description**
Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	**Description**
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MODULE

Attribute	Description

Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 48

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs; Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	**Description**	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	Description	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

FCUBS_HEADER
SOURCE
UBSCOMP
MSGID
CORRELID
USERID
BRANCH
MODULEID
SERVICE
OPERATION
SOURCE_OPERATION
SOURCE_USERID
DESTINATION
MULTITRIPID
FUNCTIONID
ACTION
MSGSTAT
PASSWORD
ADDL
PARAM
NAME
VALUE
FCUBS_BODY
Transfer-IO
FRMREF

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

2.26.3.LI-AuthorizeLITransfer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*

CONREFSHIP
SLNOSHIP
FROM
TO
PARTIALSHIP
TRANSSHIP
SHIPDETAILS
SHIPMARKS
SHIPPERIOD
PORTDISCHG
PORTLOAD
CONREFLOG
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
POSTOL
NEGTOL
Parties-Details
- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details
- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*
- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*

- *SLNOCLAUSE*
- *CLAUSECOD*
- *CLAUSDESC*

Transfer-Limits

- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*
- *SLNO*

Limits1

Advices

- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *MODULE*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHG_REQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*

CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURAVL

Attribute	Description
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	Description
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	Description
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	Description
Name	NOCOPIES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description

Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	**Description**
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 48

TOP

FFTINSDESC

Attribute	Description

Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs, Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	**Description**
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	**Description**
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	**Description**
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	**Description**
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	**Description**
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	**Description**
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	**Description**
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	Description	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transfer-PK*
      - *FRMREF*
    - *Transfer-IO*
      - *FRMREF*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transfer-PK

Attribute	Description
Name	Transfer-PK
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.27.AuthorizeProduct

Authorization of LI Product

2.27.1.LI-AuthorizeProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*

LMTSTNRCALCTYP
REKYREQ
REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL

STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details
- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*

- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*
  - *CLAUSECD*
  - *DESC*
- *Fft-Details*
- *FFTCD*
- *FFTTEXTDESC*
- *ADVCD*
- *SINGLFFT*
- *Tracer-Details*
- *TRCERCD*
- *DESC*
- *REQIRED*
- *NOFTRCERS*
- *STRTDAYS*
- *FREQNCY*
- *Tax-Scheme*
- *SCHME*
- *SCHEMEDESC*
- *Tax-Details*
  - *TAXRUL*
  - *TAXCMPNT*
  - *BASISCMPNT*
  - *COMPTATIONEVNT*
  - *TYP*
- *Status-Details*
- *STATUSSEQ*
- *STPACCRUALS*
- *REVERSEACCRUALS*
- *AUTOFRWD*
- *AUTOREVERSE*
- *COMPLETEACCRUALS*
- *TRANSACTIONCD*
- *STATUS*
- *DERVTNRUL*
- *Status-GI-Details*
  - *ACCROLEDESC*
  - *ACCGLDESC*
  - *ACCNTROLE*
  - *TRNSFERGL*
- *Control-Prod-Stat*
- *Product-Events*
- *CLASCD*

- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*

- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *CAPTLIZE*
    - *DISCACCRAPLB*
    - *PROPREQD*
    - *DISCNTBASIS*

DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

REVLVNG

Attribute	**Description**
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYAMNT

Attribute	**Description**
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCCY

Attribute	**Description**
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYCUSTM

Attribute	**Description**
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYVALDAT

Attribute	**Description**
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGCLAIM

Attribute	**Description**
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ADVABYLOAN

Attribute	**Description**
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	**Description**
Name	LOANBRIDGEGL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Commission-Details

Attribute	**Description**
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	**Description**
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	**Description**
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RULEIDENTIFICAT

Attribute	**Description**
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description

Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	Description
Name	EVNTDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

COMMCALCBASIS

Attribute	Description	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Ccy-Details

Attribute	Description

Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	**Description**
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	**Description**
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	**Description**
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description
Name	DOCSHRTDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 1
Restrictions	**Restrictions** / **Description** maxLength: 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTEXTDESC

Attribute	**Description**	
Name	FFTTEXTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ADVCD

Attribute	**Description**	
Name	ADVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SINGLFFT

Attribute	**Description**	
Name	SINGLFFT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Tracer-Details

Attribute	**Description**	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	**Description**
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Status-Details

Attribute	**Description**
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUSSEQ

Attribute	**Description**
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	**Description**
Name	STPACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description	
Name	REVERSEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOFRWD

Attribute	Description	
Name	AUTOFRWD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AUTOREVERSE

Attribute	Description	
Name	AUTOREVERSE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COMPLETEACCRUALS

Attribute	Description	
Name	COMPLETEACCRUALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Control-Prod-Stat

Attribute	Description
Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	**Description**
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	**Description**
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	Attribute	Description
	minOccurs	0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String

Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	**Description**
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	**Description**
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	**Description**
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	**Description**
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	**Description**
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Customers

Attribute	Description

Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	**Description**
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CSTCD5

Attribute	**Description**
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	**Description**
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE

Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	**Description**
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	**Description**
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	**Description**
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	**Description**
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>Name</td><td>RULDESC</td></tr>
<tr><td>Datatype</td><td>String</td></tr>
<tr><td>Description</td><td>Indicates rule Description</td></tr>
<tr><td>Attributes</td><td>
<table>
<tr><th>Attribute</th><th>Description</th></tr>
<tr><td>minOccurs</td><td>0</td></tr>
</table>
</td></tr>
<tr><td>Restrictions</td><td>
<table>
<tr><th>Restrictions</th><th>Description</th></tr>
<tr><td>maxLength</td><td>255</td></tr>
</table>
</td></tr>
</table>

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *MODNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	4

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.27.3.LI-AuthorizeProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*

REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
LC_TYPE

MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
COMPNENT
COMPNENTDESC
RULEIDENTIFICAT
EVNT
BASISAMNTTYP
BASISAMNTCATG
SETTLMNTCCY
CHNGDRGAMNDMNT
STPAPPLICTION
RATTYP
RATCDUSGE
SHWNINCNTRTMAINSCR
RATCD
ACQREQD
RULEDESC
EVNTDESCR
COLLLCCOM
Currency-Preferences
CCY
COMMCALCBASIS
Ccy-Details
CCY
DEFRAT
MINRATE
MAXRAT
MINSPRD
MAXSPRD
Document-Details
DOCMNTCD
DOCMNTTYP
DOCSHRTDESC
NOOFCOPIES
NOOFORIGINALS
ORGNALREQ
Clause-Details

CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-Gl-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD

- *EVENTDESC*
- *Accounting-Entries*
  - *ACCRLCD*
  - *AMTTAG*
  - *DRCRINDICTR*
  - *TRNCD*
  - *NETINDICTR*
  - *MISHD*
  - *REVALPRGL*
  - *REVALLSGL*
  - *REVALRTCD*
  - *REVALTXNCD*
  - *HOLTREAT*
  - *REVALREQD*
  - *RATE_TYPE_INDICATOR*
- *Advices*
  - *MSGTYP*
  - *DESC*
  - *GENTIME*
  - *SUPRS*
  - *PRIOR*
  - *CHGREQD*

Role-To-Head-Mapping

- *CLASCD*
- *CLASDESC*
- *Mapping-Details*
  - *ACCTRL*
  - *ROLDESC*
  - *ACCTHD*
  - *GLDESC*

Branch-Ccy-Restrictions

- *CCYLST*
- *BRNLST*
- *CLASCD*
- *CLASDESC*
- *Branch-List*
  - *BRNDISALOW*
  - *BRNNAME*
- *Ccy-List*
  - *BGTDLCCY*
  - *CCYNAME*

Prod-Cust-Restrictions

- *CATGLIS*
- *CLASCD*

- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*
  - *DISCACCRAPLB*
  - *PROPREQD*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*
  - *EVNTFRASSC*

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDRMRKS

Attribute	**Description**
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

PRDSTRTDT

Attribute	**Description**
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDENDDT

Attribute	**Description**
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDGRP

Attribute	**Description**
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

PRDTYP

Attribute	**Description**
Name	PRDTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	**Description**
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	**Description**
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	**Description**
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	**Description**
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	**Description**
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	**Description**
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	**Description**
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	**Description**
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	**Description**
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANPRD

Attribute	**Description**
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

COLLBRIDGEGL

Attribute	**Description**
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STATCNFLG

Attribute	**Description**
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATCD

Attribute	**Description**
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	**Description**
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	**Description**
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	**Description**
Name	EVNTDESCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COMMCALCBASIS

Attribute	Description	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description	
Name	DOCSHRTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFCOPIES

Attribute	Description	
Name	NOOFCOPIES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

ORGNALREQ

Attribute	Description	
Name	ORGNALREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTTEXTDESC

Attribute	Description
Name	FFTTEXTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description	
Name	TRCERCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

REQIRED

Attribute	Description	
Name	REQIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOFTRCERS

Attribute	Description	
Name	NOFTRCERS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TAXRUL

Attribute	**Description**
Name	TAXRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

TAXCMPNT

Attribute	**Description**
Name	TAXCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISCMPNT

Attribute	**Description**
Name	BASISCMPNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: W,E,

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	**Description**
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	**Description**
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	**Description**
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Control-Prod-Stat

Attribute	Description

Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

HOLTREAT

Attribute	Description	
Name	HOLTREAT	
Datatype	String	
Description	Indicates holiday treatment.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REVALREQD

Attribute	Description	
Name	REVALREQD	
Datatype	String	
Description	Indicates reval Required	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description	
Name	RATE_TYPE_INDICATOR	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	M,B,S,

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description	Indicates Event Advices	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	Attribute: minOccurs, Description: 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String

Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CATGLIS

Attribute	Description

Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

Customers

Attribute	Description	
Name	Customers	
Datatype		
Description	Indicates Customers	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CSTID

Attribute	Description	
Name	CSTID	
Datatype	String	
Description	Indicates customer ID.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description	Indicates customer Name.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ALWD

Attribute	Description	
Name	ALWD	
Datatype	String	
Description	Indicates whether customer is allowed or not.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	**Description**
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	**Description**
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	Description
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	Description
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	Description
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

SETTCCY

Attribute	**Description**	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	**Description**	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	**Description**	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOC

Attribute	**Description**
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	**Description**
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	**Description**
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *MODNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*
    - *WARNING*
      - *WCODE*
      - *WDESC*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER

Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID

Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.28.CloseAmendConfirm

Close Islamic LC Amendment Confirmation

2.28.1.LI-CloseAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

AMNDSEQNO
ISSDT
EXPDT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*

COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description	
Name	ACCOUNT_NO_1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

Advices-Details

Attribute	Description	
Name	Advices-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description	
Name	MSG_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	**Description**
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

- FCUBS_HEADER
  - SOURCE
  - UBSCOMP
  - MSGID
  - CORRELID
  - USERID
  - BRANCH
  - MODULEID
  - SERVICE
  - OPERATION
  - SOURCE_OPERATION
  - SOURCE_USERID
  - DESTINATION
  - MULTITRIPID
  - FUNCTIONID
  - ACTION
  - MSGSTAT
  - PASSWORD
  - ADDL
    - PARAM
      - NAME
      - VALUE
- FCUBS_BODY
  - Amend-Details-IO
    - CONTREFNO
    - Collateral-details
      - CONREFNO
      - LATEVNSEQNO
    - TXNUDFDETAILS
      - FLDNAME
      - FLDVAL
    - Lic-Master
      - CONREFNO
      - LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.28.3.LI-CloseAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*
  - *COLLTCCY*
  - *COLLTPCT*
  - *COLLTAMT*

EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONAMT

Attribute	**Description**
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	**Description**
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	**Description**
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	**Description**
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	**Description**
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

COUNTRYCD

Attribute	**Description**	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	**Description**	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDT

Attribute	**Description**	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDESC

Attribute	**Description**	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description

Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

License-Utils-Detail

Attribute	Description	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	Description	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.28.4.LI-CloseAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-PK*
      - *CONTREFNO*
    - *Amend-Details-IO*
      - *CONTREFNO*
      - *Collateral-details*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
      - *Lic-Master*
        - *CONREFNO*
        - *LATEVNSEQNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Collateral-details

Attribute	Description	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.CloseContract

Close Islamic LC Contract

2.29.1.LI-CloseContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

PARTYDESC
PARTYCIFID
CUSTNAME
CUSTADDLIN1
CUSTADDLIN2
CUSTADDLIN3
CUSTADDLIN4
COUNTRYCD
CUSTREFNO
CUSTREFDATE
LANGCD
ISSBANK
TEMPLATE_ID
Party-Other-Addresses
MEDTYP
MEDADDR
ACCNO
Advice-Details
MSGTYP
PRTY
PRTYID
PRTYNAME
MEDIUM
PRIORITY
SUPRESS
CHGREQD
Fft-Details
FFTINSCD
FFTINSDESC
SINGLEFFT
Documents-Details
DOCCD
DOCTYP
DOCDESC
REFERENCE
DOCCPY
NOOFORIGINALS
DOCORIGINAL
Clause-Details
CLAUSECD
CLAUSEDESC
Shipment-Details
FROMPALCE
TOPLACE

PARTIALSHPMNT

TRANSSHPMNT

LATSHIPDT

SHPPERD

SHPMNTDET

SHPMNTMARK

PORTDISCHARGE

PORTLOADING

SHPDAYS

PARSHIPDET

TRASHIPDET

Goods-Details

GOODDESC

GOODCD

REFPREADV

Tracer-Details

TRACERCD

TRACERDESC

TRACERPRTY

REQRD

MAXTRACER

SENTTODATE

STRTDYS

LASTTRACDT

MEDIUM

FREQ

TEMPLATE_ID

Drafts

DRFTSLNO

DRFTTNR

PCTAMT

CRDAYSFRM

DRAWEE

ADDRS1

ADDRS2

ADDRS3

INSUCOMPCD

INSUCO

ADDRSLN1

ADDRSLN2

ADDRSLN3

ADDRSLN4

INSUEXPDT

INSUPOLCYNO

- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

Charge-Application

CREATESN

COMPNT

TGCCY

TGAMT

CHRGCCY

CHRGAMT

DISACCRAPPL

WAIVER

LIQDIND

Charge-Liquidation

ESN

COMPNT

CHRGCCY

CHRGAMT

LIQDSTAT

Settlements

CONREFNO

Contract-Settlement

IBANACNO

CUSTSPREAD

SPREADDEFN

COMPNT

TAGCCY

ACCBRN

ACC

ACCCCY

EXRATE

NETIND

ERICCY

ERIAMT

GENMSG

RATECD

CLEARNW

COVERBY

RTGSPMNT

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *ESN*
  - *CNTRPARTY*
  - *PRD*
  - *CCY*
  - *TENOR*
  - *UNITS*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *BRIDGL*
  - *CYSTALTYP*
  - *COLLLIQDAMT*
  - *LIQDLCCHGCOMM*
  - *MATDT*
  - *LOANAMT*
  - *BILLOS*
  - *CONTRACT_CURRENCY*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	Description	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	Description	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	Description	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	Description	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FROMLCREF

Attribute	**Description**
Name	FROMLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TOLCREF

Attribute	**Description**
Name	TOLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STARTDT

Attribute	**Description**
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDATE

Attribute	**Description**
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FOLLWRUL

Attribute	**Description**
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDPER

Attribute	**Description**
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CREATESN

Attribute	Description	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RULE

Attribute	Description	
Name	RULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	**Description**
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	**Description**
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**	
Name	SPTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTAMTTAG

Attribute	**Description**	
Name	SPTAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SPTAMT

Attribute	**Description**	
Name	SPTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTACBRN

Attribute	**Description**	
Name	SPTACBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPTACCCY

Attribute	**Description**

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	**Description**
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	**Description**
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	**Description**
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	**Description**
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

BRKAMTACCCCY

Attribute	Description	
Name	BRKAMTACCCCY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ORGEXRATE

Attribute	Description	
Name	ORGEXRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGRATE

Attribute	Description	
Name	NEGRATE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description
	maxOccurs: unbounded
	minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description
	minOccurs: 1
Restrictions	Restrictions: Description
	maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

2.29.2.LI-CloseContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *Commission*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
    - *Settlements*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Collateral-details*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *Taxes*
      - *CONREFNO*
      - *LATEVNSEQNO*

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTREFNO

Attribute	**Description**
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Commission

Attribute	**Description**
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description

Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master

Attribute	**Description**
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	**Description**
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Split-Master

Attribute	**Description**
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 200

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

KEY_ID

Attribute	Description	
Name	KEY_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNCTION_ID

Attribute	Description	
Name	FUNCTION_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

2.29.3.LI-CloseContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

UDEID
RTCD
USAGE
INTBASIS
SPLAMT
INTRT
INTSPRD
UDEDESC
Extsys-Ws-Master
Extsys-Ws-Details
EXTWSRESP
USERREMARKS
Brok-Master
CONREFNO
CONTRACTCCY
BROKPERCENT
BROKAMT
Brok-Detail
BROKNAME
BROKER
BRKACC
BRKACCCCY
BRKPERCENT
BRKAMTACCCCY
EXRATE
ORGEXRATE
NEGRATE
NEGREFNO
REMARKS
BRKAMTCONCCY
LIQSTATUS
Master
Doc-Upload
DCREFNO
DOC_CATEGORY
DOC_TYPE
REMARKS
Ui-Columns
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description	
Name	TRAKLMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description	
Name	ACCFORISB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ISSBDT

Attribute	Description	
Name	ISSBDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMNDNO

Attribute	Description	
Name	AMNDNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STOPDT1

Attribute	Description	
Name	STOPDT1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	**Description**
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	**Description**
Name	FEECLMADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PARTIALCLOS

Attribute	**Description**
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TEMPLATEID

Attribute	**Description**
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COLLATLOANALLOWED

Attribute	**Description**
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs: unbounded minOccurs: 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs: 0
Restrictions	**Restrictions** / **Description** maxLength: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FROMPALCE

Attribute	**Description**	
Name	FROMPALCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

TOPLACE

Attribute	**Description**	
Name	TOPLACE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PARTIALSHPMNT

Attribute	**Description**	
Name	PARTIALSHPMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TRANSSHPMNT

Attribute	**Description**	
Name	TRANSSHPMNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ADDRS3

Attribute	**Description**
Name	ADDRS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSUCOMPCD

Attribute	**Description**
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

INSUCO

Attribute	**Description**
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN1

Attribute	Description	
Name	ADDRSLN1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN2

Attribute	Description	
Name	ADDRSLN2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN3

Attribute	Description	
Name	ADDRSLN3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRSLN4

Attribute	Description	
Name	ADDRSLN4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FROMLCREF

Attribute	Description
Name	FROMLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Fundmaster

Attribute	Description
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	**Description**
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	**Description**
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	**Description**
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	**Description**
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	**Description**
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	**Description**
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD5

Attribute	**Description**
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

TXNMIS1

Attribute	**Description**
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	**Description**
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	**Description**
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	**Description**
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	**Description**
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes		
	Attribute	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	**Description**	
Name	SPTSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTAMTTAG

Attribute	**Description**	
Name	SPTAMTTAG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

SPTAMT

Attribute	**Description**	
Name	SPTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPTACBRN

Attribute	**Description**	
Name	SPTACBRN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

SPTACCCY

Attribute	**Description**

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.29.4.LI-CloseContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *Commission*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
      - *Settlements*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *Collateral-details*
        - *CONREFNO*
        - *LATEVNSEQNO*

Taxes

CONREFNO

LATEVNSEQNO

Linkages

CONREFNO

LATEVNSEQNO

TXNUDFDETAILS

FLDNAME

FLDVAL

Misdetails

CONREFNO

Lctbs-Lccbclnk-Master

CONTRACT_REF_NO

Split-Master

CONREFNO

LATEVNSEQNO

Bcpref

CONREFNO

LATEVNSEQNO

Extsys-Ws-Master

KEYID

Brok-Master

CONREFNO

LATEVNSEQNO

Master

KEY_ID

FUNCTION_ID

Lic-Master

CONREFNO

LATEVNSEQNO

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable = true
Restrictions	**Restrictions** / **Description**: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: Description maxLength: 105 minLength: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 255 minLength: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	Attribute: Description minOccurs: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 0
Restrictions	Restrictions: Description maxLength: 16

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	200

TOP

Brok-Master

Attribute	Description	
Name	Brok-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Master

Attribute	Description	
Name	Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

KEY_ID

Attribute	Description
Name	KEY_ID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNCTION_ID

Attribute	**Description**
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.30.ConfirmAmendConfirm

Confirmation of Amendment Confirmation

2.30.1.LI-ConfirmAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

AMNDSEQNO
ISSDT
EXPDT
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
- *PARTYTYPE*
- *CIFID*
- *CUSTNAME*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDT*
- *PARTYDESC*
- *ADDRESS_1*
- *ADDRESS_2*
- *ADDRESS_3*
- *ADDRESS_4*
- *LANGUAGE*
- *ISSUER1*
- *Party-Other-Addrs*
  - *MEDIUM_TYPE*
  - *MEDIUM_ADDRESS*
  - *ACCOUNT_NO_1*

Advices-Details
- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *PARTY_TYPE*
- *MEDIUM*
- *PARTY_ID*
- *PARTY_NAME*
- *CHG_REQD*
- *Fft-Details*
  - *CODE*
  - *DESC*

Collateral-details
- *CONREFNO*
- *LATEVNSEQNO*
- *Collateral*

COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHG_REQD

Attribute	**Description**
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CODE

Attribute	**Description**
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description	
Name	AMTQ_UT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AMTQ_RE

Attribute	Description	
Name	AMTQ_RE	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*
    - *Collateral-details*
      - *CONREFNO*
      - *LATEVNSEQNO*
    - *TXNUDFDETAILS*
      - *FLDNAME*
      - *FLDVAL*
    - *Lic-Master*
      - *CONREFNO*
      - *LATEVNSEQNO*

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	Restrictions: length = 3; pattern = [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs = 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable = true
Restrictions	Restrictions: pattern = [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Collateral-details

Attribute	Description	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TXNUDFDETAILS

Attribute	Description	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description

Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	**Description**
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

2.30.3.LI-ConfirmAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
TXNSTAT
AUTHSTAT
CLSRDT
Party-Details
PARTYTYPE
CIFID
CUSTNAME
COUNTRYCD
CUSTREFNO
CUSTREFDT
PARTYDESC
ADDRESS_1
ADDRESS_2
ADDRESS_3
ADDRESS_4
LANGUAGE
ISSUER1
Party-Other-Addrs
MEDIUM_TYPE
MEDIUM_ADDRESS
ACCOUNT_NO_1
Advices-Details
MSG_TYPE
SUPRESS
PRIORITY
PARTY_TYPE
MEDIUM
PARTY_ID
PARTY_NAME
CHG_REQD
Fft-Details
CODE
DESC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONAMT

Attribute	**Description**
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	**Description**
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	**Description**
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	**Description**
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	**Description**
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	**Description**
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	**Description**
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	**Description**

Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.30.4.LI-ConfirmAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-PK*
      - *CONTREFNO*
    - *Amend-Details-IO*
      - *CONTREFNO*
      - *Collateral-details*
        - *CONREFNO*
        - *LATEVNSEQNO*
      - *TXNUDFDETAILS*
        - *FLDNAME*
        - *FLDVAL*
      - *Lic-Master*
        - *CONREFNO*
        - *LATEVNSEQNO*
  - *FCUBS_ERROR_RESP*
    - *ERROR*
      - *ECODE*
      - *EDESC*
  - *FCUBS_WARNING_RESP*

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description

Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Collateral-details

Attribute	Description	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.31.CreateAmendConfirm

Create Islamic LC Amendment Confirmation

2.31.1.LI-CreateAmendConfirm-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*

- *AMNDSEQNO*
- *ISSDT*
- *EXPDT*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *CLSRDT*
- *Party-Details*
  - *PARTYTYPE*
  - *CIFID*
  - *CUSTNAME*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDT*
  - *PARTYDESC*
  - *ADDRESS_1*
  - *ADDRESS_2*
  - *ADDRESS_3*
  - *ADDRESS_4*
  - *LANGUAGE*
  - *ISSUER1*
  - *Party-Other-Addrs*
    - *MEDIUM_TYPE*
    - *MEDIUM_ADDRESS*
    - *ACCOUNT_NO_1*
- *Advices-Details*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PARTY_TYPE*
  - *MEDIUM*
  - *PARTY_ID*
  - *PARTY_NAME*
  - *CHG_REQD*
  - *Fft-Details*
    - *CODE*
    - *DESC*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONAMT

Attribute	Description
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INDECAMT

Attribute	Description
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	Description
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	Description
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_2

Attribute	**Description**
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_3

Attribute	**Description**
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRESS_4

Attribute	**Description**
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LANGUAGE

Attribute	**Description**
Name	LANGUAGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description

Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	**Description**
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	150

TOP

CHG_REQD

Attribute	Description	
Name	CHG_REQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CODE

Attribute	Description	
Name	CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number

Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.31.2.LI-CreateAmendConfirm-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-IO*
    - *CONTREFNO*
    - *CONAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *EXPDT*
    - *CLSRDT*
    - *Party-Details*
      - *CUSTREFNO*
      - *CUSTREFDT*
      - *Party-Other-Addrs*
        - *MEDIUM_TYPE*

MEDIUM_ADDRESS

ACCOUNT_NO_1

Advices-Details

MSG_TYPE

SUPRESS

PRIORITY

PARTY_TYPE

MEDIUM

PARTY_ID

PARTY_NAME

CHG_REQD

Fft-Details

DESC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

AMTQ_UT

AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONAMT

Attribute	**Description**	
Name	CONAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDAMT

Attribute	**Description**	
Name	ADDAMT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	140

TOP

FROMPLACE

Attribute	**Description**	
Name	FROMPLACE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

TOPLACE

Attribute	**Description**	
Name	TOPLACE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXPDT

Attribute	**Description**
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSRDT

Attribute	**Description**
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Details

Attribute	**Description**
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	Description
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHG_REQD

Attribute	**Description**
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Fft-Details

Attribute	**Description**
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	**Description**
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**

Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	**Description**
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	**Description**
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.31.3.LI-CreateAmendConfirm-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Amend-Details-Full*
    - *CONTREFNO*
    - *CCY*
    - *CONAMT*
    - *INDECAMT*
    - *ADDAMT*
    - *FROMPLACE*
    - *TOPLACE*
    - *LATSHIPDT*
    - *SHIPPER*
    - *PORTLOAD*
    - *PORTDIS*
    - *POSTOL*
    - *NEGTOL*
    - *AMDSTAT*
    - *VERNO*
    - *AMNDSEQNO*
    - *ISSDT*
    - *EXPDT*

- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *CLSRDT*
- *Party-Details*
  - *PARTYTYPE*
  - *CIFID*
  - *CUSTNAME*
  - *COUNTRYCD*
  - *CUSTREFNO*
  - *CUSTREFDT*
  - *PARTYDESC*
  - *ADDRESS_1*
  - *ADDRESS_2*
  - *ADDRESS_3*
  - *ADDRESS_4*
  - *LANGUAGE*
  - *ISSUER1*
  - *Party-Other-Addrs*
    - *MEDIUM_TYPE*
    - *MEDIUM_ADDRESS*
    - *ACCOUNT_NO_1*
- *Advices-Details*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PARTY_TYPE*
  - *MEDIUM*
  - *PARTY_ID*
  - *PARTY_NAME*
  - *CHG_REQD*
  - *Fft-Details*
    - *CODE*
    - *DESC*
- *Collateral-details*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Collateral*
    - *COLLTCCY*
    - *COLLTPCT*
    - *COLLTAMT*

EXRATE

COLLTDESC

ADJSTSIGN

ADJSTAMT

TXNUDFDETAILS

FLDNAME

FLDVAL

Lic-Master

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	Restrictions: enumeration — Description: FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	Restrictions: maxLength — Description: 12 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

BRANCH

Attribute	Description

Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Amend-Details-Full

Attribute	Description
Name	Amend-Details-Full
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	16

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONAMT

Attribute	**Description**
Name	CONAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INDECAMT

Attribute	**Description**
Name	INDECAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDAMT

Attribute	**Description**
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 140

TOP

FROMPLACE

Attribute	**Description**
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	**Description**
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMDSTAT

Attribute	**Description**
Name	AMDSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,C,U,R

TOP

VERNO

Attribute	**Description**
Name	VERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDSEQNO

Attribute	Description
Name	AMNDSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,S,A,H,V

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

CLSRDT

Attribute	Description
Name	CLSRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

PARTYTYPE

Attribute	Description
Name	PARTYTYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	150

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADDRESS_1

Attribute	Description
Name	ADDRESS_1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_2

Attribute	Description
Name	ADDRESS_2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_3

Attribute	Description
Name	ADDRESS_3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRESS_4

Attribute	Description
Name	ADDRESS_4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANGUAGE

Attribute	Description
Name	LANGUAGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ISSUER1

Attribute	Description
Name	ISSUER1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Party-Other-Addrs

Attribute	Description
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MEDIUM_TYPE

Attribute	Description
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

MEDIUM_ADDRESS

Attribute	Description
Name	MEDIUM_ADDRESS
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	**Description**
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	**Description**
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PARTY_ID

Attribute	Description
Name	PARTY_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

PARTY_NAME

Attribute	Description
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CODE

Attribute	Description
Name	CODE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTCCY

Attribute	Description

Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

TOP

Lic-Master

Attribute	Description	
Name	Lic-Master	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

License-Utils-Detail

Attribute	Description	
Name	License-Utils-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IMPLICNO

Attribute	Description	
Name	IMPLICNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC

Datatype	String
Description	

TOP

2.31.4.LI-CreateAmendConfirm-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Amend-Details-PK*
      - *CONTREFNO*
    - *Amend-Details-IO*
      - *CONTREFNO*
      - *CONAMT*
      - *ADDAMT*
      - *FROMPLACE*
      - *TOPLACE*
      - *LATSHIPDT*
      - *SHIPPER*
      - *PORTLOAD*
      - *PORTDIS*
      - *POSTOL*
      - *NEGTOL*
      - *EXPDT*
      - *CLSRDT*
      - *Party-Details*
        - *CUSTREFNO*

CUSTREFDT
Party-Other-Addrs
MEDIUM_TYPE
MEDIUM_ADDRESS
ACCOUNT_NO_1
Advices-Details
MSG_TYPE
SUPRESS
PRIORITY
PARTY_TYPE
MEDIUM
PARTY_ID
PARTY_NAME
CHG_REQD
Fft-Details
DESC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
TXNUDFDETAILS
FLDNAME
FLDVAL
Lic-Master
CONREFNO
LATEVNSEQNO
License-Utils-Detail
IMPLICNO
GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
AMTQ_UT
AMTQ_RE
FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Amend-Details-PK

Attribute	Description
Name	Amend-Details-PK
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Amend-Details-IO

Attribute	Description
Name	Amend-Details-IO
Datatype	
Description	

TOP

CONTREFNO

Attribute	Description	
Name	CONTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONAMT

Attribute	Description
Name	CONAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDAMT

Attribute	Description
Name	ADDAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 140

TOP

FROMPLACE

Attribute	Description
Name	FROMPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHIPPER

Attribute	Description
Name	SHIPPER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTDIS

Attribute	Description
Name	PORTDIS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPDT

Attribute	**Description**
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSRDT

Attribute	**Description**
Name	CLSRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Party-Details

Attribute	**Description**
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDT

Attribute	**Description**

Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Party-Other-Addrs

Attribute	**Description**
Name	Party-Other-Addrs
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MEDIUM_TYPE

Attribute	**Description**
Name	MEDIUM_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MEDIUM_ADDRESS

Attribute	**Description**
Name	MEDIUM_ADDRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCOUNT_NO_1

Attribute	**Description**
Name	ACCOUNT_NO_1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advices-Details

Attribute	Description
Name	Advices-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTY_TYPE

Attribute	Description
Name	PARTY_TYPE
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PARTY_ID

Attribute	**Description**
Name	PARTY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

PARTY_NAME

Attribute	**Description**
Name	PARTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CHG_REQD

Attribute	**Description**
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Collateral-details

Attribute	Description	
Name	Collateral-details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates Contract Reference Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description

Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	**Description**
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	**Description**
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	**Description**
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	**Description**
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	**Description**

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	**Description**
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	**Description**
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	**Description**
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description

Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	**Description**
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AMTQ_UT

Attribute	**Description**
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	**Description**

Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.CreateContract

Create Islamic LC Contract

2.32.1.LI-CreateContract-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*

ADDAMTCOVERD
PERDPRESENTATION
CHRGCCYISB
CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE

UNITS
FREQ
NEXTREINDT
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
PRTYTYP

PARTYDESC
PARTYCIFID
CUSTNAME
CUSTADDLIN1
CUSTADDLIN2
CUSTADDLIN3
CUSTADDLIN4
COUNTRYCD
CUSTREFNO
CUSTREFDATE
LANGCD
ISSBANK
TEMPLATE_ID
Party-Other-Addresses
MEDTYP
MEDADDR
ACCNO
Advice-Details
MSGTYP
PRTY
PRTYID
PRTYNAME
MEDIUM
PRIORITY
SUPRESS
CHGREQD
Fft-Details
FFTINSCD
FFTINSDESC
SINGLEFFT
Documents-Details
DOCCD
DOCTYP
DOCDESC
REFERENCE
DOCCPY
NOOFORIGINALS
DOCORIGINAL
Clause-Details
CLAUSECD
CLAUSEDESC
Shipment-Details
FROMPALCE
TOPLACE

- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*

TELEPHNO
FAXNUMBER
OPNPLCYFLG
POLICYUTLAMT
CVRDT
INSURANCEAMT
TELEXADDR
WAREHOUSEADDR
DRAFTAMT
DRAFTPCT
Draft-Details
AMTNAM
AMT
Control
Transdet
FROMLCREF
TOLCREF
SLNO
ESN
TRANSAMT
TRANSDT
NEWEXPDT
NEWLATSHIPMENTDT
Contract-Limits
AMOUNTTAG
CUSTNO
LINKAGE_TYPE
LINKAGEPERC
PARTYTYP
LIMITAMT
JVPARENT
SLNO
LINKEDREFNO
LIABILITY_NUMBER
Fundmaster
FUNDID
Insurance
INSUCO
INSUPOLCYNO
INSURANCEAMT
LCYAMT
Dfrrd-Intcomp
CONREFNUM
ESN

- *COMP*
- *CCY*
- *DUEDATE*
- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*

- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*

PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1

BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*

PMNTCD

ADDINFOSORBNET

SNDRCUSTNAME1

SNDRCUSTNAME2

SNDRCUSTNAME3

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

Collateral-details

CONREFNO

LATEVNSEQNO

Collateral

COLLTCCY

COLLTPCT

COLLTAMT

EXRATE

COLLTDESC

ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *Tax*
    - *CONREFNO*
    - *SCHEME*
    - *WAIVER*
    - *Tax-Details*
      - *RULE*
      - *BASISAMNTAG*
      - *COMPUEVNT*
      - *WAIVER*
      - *Rule-Details*
        - *VALUEDT*
        - *COMPUTATIONDT*
        - *CCY*
        - *AMT*
        - *ESN*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDTOCCY*
    - *LINKEDAMT*
    - *EXRATE*
    - *CONVLINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*

REFRATETYP
PROCALCMTH
REFSPREAD
REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2

- *TRANMIS3*
- *TRANMIS4*
- *TRANMIS5*
- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*

- *Split-Detail*
  - *SPTSEQNO*
  - *SPTAMTTAG*
  - *SPTAMT*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTEXCHRT*
  - *SPTPRTYID*
  - *SPTPERCENTAGE*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *ESN*
  - *CNTRPARTY*
  - *PRD*
  - *CCY*
  - *TENOR*
  - *UNITS*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *BRIDGL*
  - *CYSTALTYP*
  - *COLLLIQDAMT*
  - *LIQDLCCHGCOMM*
  - *MATDT*
  - *LOANAMT*
  - *BILLOS*
  - *CONTRACT_CURRENCY*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*

- *LOANVALDATE*
- *ORGEXCHRATE*
- *Bcprefdet*
  - *UDEID*
  - *RTCD*
  - *USAGE*
  - *INTBASIS*
  - *SPLAMT*
  - *INTRT*
  - *INTSPRD*
  - *UDEDESC*
- *Extsys-Ws-Master*
  - *Extsys-Ws-Details*
    - *EXTWSRESP*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *CONTRACTCCY*
  - *BROKPERCENT*
  - *BROKAMT*
  - *Brok-Detail*
    - *BROKNAME*
    - *BROKER*
    - *BRKACC*
    - *BRKACCCCY*
    - *BRKPERCENT*
    - *BRKAMTACCCCY*
    - *EXRATE*
    - *ORGEXRATE*
    - *NEGRATE*
    - *NEGREFNO*
    - *REMARKS*
    - *BRKAMTCONCCY*
    - *LIQSTATUS*
- *Master*
  - *Doc-Upload*
    - *DCREFNO*
    - *DOC_CATEGORY*
    - *DOC_TYPE*
    - *REMARKS*
  - *Ui-Columns*
- *Lic-Master*
  - *License-Utils-Detail*
    - *IMPLICNO*

GOODSCD
QTYUTIL
AMTUTIL
QTYREIN
AMTREIN
REMARKS
UNIT_OF_MEASUREMENT
LICENSE_AMOUNT
GOODSDESC
AMTQ_UT
AMTQ_RE
AVAILQTY_LICAMT
LIC_AMOUNT_UTILIZED
LIC_AMOUNT_REINS

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description	
Name	LATVERNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description	
Name	OPERCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

EXTREFNO

Attribute	Description

Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

LMTTRTENOTYP

Attribute	Description	
Name	LMTTRTENOTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,D

TOP

REIMTYP

Attribute	Description	
Name	REIMTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,O,C

TOP

CHRGFRMBEN

Attribute	Description	
Name	CHRGFRMBEN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	210

TOP

ADDAMTCOVERD

Attribute	Description	
Name	ADDAMTCOVERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMNDNO

Attribute	Description
Name	AMNDNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MAXLIABAMT

Attribute	Description

Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLTXT

Attribute	**Description**
Name	TOLTXT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,N,A

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EFFDT

Attribute	**Description**
Name	EFFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TENOR

Attribute	**Description**
Name	TENOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,I,R

TOP

INCOTRM

Attribute	**Description**	
Name	INCOTRM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INCODESC

Attribute	**Description**	
Name	INCODESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

APPRULE

Attribute	**Description**	
Name	APPRULE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RULENARRATIVE

Attribute	**Description**	
Name	RULENARRATIVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	35

TOP

CIFID

Attribute	Description	
Name	CIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTTYP

Attribute	Description	
Name	CUSTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

CUSTREFDT

Attribute	Description	
Name	CUSTREFDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CURRAVAIL

Attribute	**Description**
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OSLIAB

Attribute	**Description**
Name	OSLIAB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REMARK

Attribute	Description
Name	REMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

RELLCREF

Attribute	Description
Name	RELLCREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKDTTIME

Attribute	Description
Name	MAKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,U,A

TOP

BACKTOBACK

Attribute	Description
Name	BACKTOBACK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONFAMT

Attribute	Description
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	Description
Name	FEECLMADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

PARTIALCLOS

Attribute	Description
Name	PARTIALCLOS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COLLATLOANALLOWED

Attribute	Description
Name	COLLATLOANALLOWED
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT

Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

USERDEFSTAT

Attribute	Description
Name	USERDEFSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BENCONFREQD

Attribute	Description
Name	BENCONFREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PREADVICEDT

Attribute	Description
Name	PREADVICEDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESC

Attribute	Description	
Name	PARTYDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

PARTYCIFID

Attribute	Description	
Name	PARTYCIFID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

CUSTNAME

Attribute	Description	
Name	CUSTNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

CUSTADDLIN1

Attribute	Description
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	Description
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	Description
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	Description
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	Description
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATE_ID

Attribute	Description	
Name	TEMPLATE_ID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

Party-Other-Addresses

Attribute	Description	
Name	Party-Other-Addresses	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MEDTYP

Attribute	Description	
Name	MEDTYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

MEDADDR

Attribute	Description	
Name	MEDADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

ACCNO

Attribute	Description
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	Description
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

PRTYID

Attribute	Description

Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Documents-Details

Attribute	Description
Name	Documents-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

DOCTYP

Attribute	Description
Name	DOCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DOCCPY

Attribute	**Description**
Name	DOCCPY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

DOCORIGINAL

Attribute	**Description**
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

FROMPALCE

Attribute	Description

Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SHPPERD

Attribute	Description	
Name	SHPPERD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	395

TOP

SHPMNTDET

Attribute	Description	
Name	SHPMNTDET	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	400

TOP

SHPMNTMARK

Attribute	Description	
Name	SHPMNTMARK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

PORTDISCHARGE

Attribute	Description	
Name	PORTDISCHARGE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	**Description**
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	**Description**
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

REFPREADV

Attribute	**Description**
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs; Description: 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Control

Attribute	**Description**	
Name	Control	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Transdet

Attribute	**Description**	
Name	Transdet	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FROMLCREF

Attribute	**Description**	
Name	FROMLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TOLCREF

Attribute	**Description**	
Name	TOLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEWLATSHIPMENTDT

Attribute	Description

Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	**Description**
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	**Description**
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

SLNO

Attribute	Description
Name	SLNO

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	**Description**
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FUNDID

Attribute	**Description**
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	Description
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

PICKESN

Attribute	Description
Name	PICKESN
Datatype	Number
Description	Indicates Pickup Event Seq Number
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

EVENT

Attribute	Description
Name	EVENT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	Attribute: minOccurs, Description: 0

TOP

APPRATE

Attribute	Description
Name	APPRATE
Datatype	String
Description	Indicates Apply Rate Current : C Next : N
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: ,C,N

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	Attribute: minOccurs, Description: 0

TOP

EVNTDESC

Attribute	Description
Name	EVNTDESC
Datatype	String
Description	Indicates Event Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COMPDESC

Attribute	Description
Name	COMPDESC
Datatype	String
Description	Indicates Component Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Charge-Liquidation

Attribute	Description	
Name	Charge-Liquidation	
Datatype		
Description	Includes Charge Liquidation details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description	
Name	REIMINST5	
Datatype	String	
Description	Indicates Reimburse Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description	
Name	RCORRS15	
Datatype	String	
Description	Indicates Receiver Correspondent 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST5

Attribute	Description	
Name	ORDCUST5	
Datatype	String	
Description	Indicates Ordering Customer 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST5

Attribute	Description	
Name	ORDINST5	
Datatype	String	
Description	Indicates Ordering Institution 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	Restrictions: maxLength — Description: 105 Restrictions: minLength — Description: 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255 Restrictions: minLength — Description: 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	**Description**	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	**Description**	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	**Description**	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	**Description**	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

FUNMIS10

Attribute	Description	
Name	FUNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

Txnmisdetails

Attribute	Description	
Name	Txnmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Compmisdetails

Attribute	Description	
Name	Compmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Fundmisdetails

Attribute	Description	
Name	Fundmisdetails	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	Description
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	Description
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

QTYUTIL

Attribute	**Description**
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTUTIL

Attribute	**Description**
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

QTYREIN

Attribute	**Description**
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMTREIN

Attribute	**Description**
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description	
Name	UNIT_OF_MEASUREMENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

LICENSE_AMOUNT

Attribute	Description	
Name	LICENSE_AMOUNT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

GOODSDESC

Attribute	Description	
Name	GOODSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

2.32.2.LI-CreateContract-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-IO*
    - *PRDCD*
    - *OPERCD*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*
    - *CHRGMSTISB*
    - *CHRGFRMISB*
    - *ACCFORISB*
    - *ISSBDT*

STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
APPRULE
RULENARRATIVE
CIFID
CUSTTYP
CUSTREFDT
CUSTREFNO
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT

AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
TEMPLATEID
UNDEREXPDT
UNDRTKNAMT
CONPERCENT
USRLCREFERENCE
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*
- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*

- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUPOLCYNO*
- *LCYAMT*

Dfrrd-Intcomp

Commission

- *CONREFNO*
- *LATEVNSEQNO*

- *Commission-Details*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
- *Charges*
  - *LATEVNSEQNO*
  - *CONREFNO*
  - *Charge-Association*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*

EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2

ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN

- *ADJSTAMT*
- *Taxes*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Tax*
    - *WAIVER*
    - *Tax-Details*
      - *Rule-Details*
- *Linkages*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Linkage-Details*
    - *LINKEDAMT*
    - *LINKEDTOREF*
    - *LINKAGETYP*
  - *Ui-Fields*
    - *ACCOUNT*
    - *DEPOSIT*
    - *UNCOVAMT*
- *TXNUDFDETAILS*
  - *FLDNAME*
  - *FLDVAL*
- *Misdetails*
  - *CONREFNO*
  - *LATESN*
  - *MISGRP*
  - *RELACC*
  - *RELETED_REFERENCE*
  - *MISHEAD*
  - *RATEFLG*
  - *POOLCD*
  - *REFINANCE_RATE*
  - *REFRATETYP*
  - *PROCALCMTH*
  - *REFSPREAD*
  - *REFRATECD*
  - *COSTCD1*
  - *COSTCD2*
  - *COSTCD3*
  - *COSTCD4*
  - *COSTCD5*
  - *TXNMIS1*
  - *TXNMIS10*
  - *TXNMIS2*

- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *LATEVNSEQNO*
- *Split-Master*

- *Split-Detail*
  - *SPTAMTTAG*
  - *SPTACBRN*
  - *SPTACCCY*
  - *SPRACNO*
  - *SPTPRTYID*
  - *LOANACC*
  - *NEGORATE*
  - *NEGO_REF_NO*
- *Bcpref*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BCREFNO*
  - *PRD*
  - *CCY*
  - *CRDLINE*
  - *RTCD*
  - *EXCHRT*
  - *RTTYP*
  - *MATACC*
  - *LOANAMT*
  - *RATECDPREF*
  - *MAXRATVAR*
  - *MINRTVAR*
  - *PMNTMD*
  - *DRACCBRN*
  - *DRPRODAC*
  - *CRACCBRN*
  - *CRPRODAC*
  - *LOANVALDATE*
  - *Bcprefdet*
    - *UDEID*
    - *INTBASIS*
    - *SPLAMT*
    - *INTRT*
    - *UDEDESC*
- *Extsys-Ws-Master*
  - *KEYID*
  - *Extsys-Ws-Details*
    - *USERREMARKS*
- *Brok-Master*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *BROKPERCENT*

BROKAMT

Brok-Detail

BRKACC

BRKACCCCY

BRKPERCENT

EXRATE

REMARKS

BRKAMTCONCCY

Master

KEY_ID

FUNCTION_ID

Doc-Upload

DCREFNO

DOC_CATEGORY

DOC_TYPE

REMARKS

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

AMTQ_UT

AMTQ_RE

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

OPERCD

Attribute	Description
Name	OPERCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / ,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	Description
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	Description
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	Description
Name	STOPDT1
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CIFID

Attribute	Description
Name	CIFID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTTYP

Attribute	**Description**
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SETTLTYP

Attribute	**Description**
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,S,N

TOP

SETTLMTH

Attribute	Description	
Name	SETTLMTH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description	
Name	CREDITAVLWITH	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	143

TOP

PAYMNTDT

Attribute	Description	
Name	PAYMNTDT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	143

TOP

REVOLVE

Attribute	Description	
Name	REVOLVE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	**Description**
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	**Description**
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	**Description**
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

RELLCREF

Attribute	**Description**	
Name	RELLCREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TXNSTAT

Attribute	**Description**	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTATS

Attribute	**Description**	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

BACKTOBACK

Attribute	**Description**	
Name	BACKTOBACK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACKNREVCD

Attribute	Description
Name	ACKNREVCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

FEECLMADV

Attribute	**Description**
Name	FEECLMADV
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

STATUSCNTRLCD

Attribute	Description	
Name	STATUSCNTRLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description

Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRYCD

Attribute	Description	
Name	COUNTRYCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description	
Name	CUSTREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTREFDATE

Attribute	Description	
Name	CUSTREFDATE	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LANGCD

Attribute	Description	
Name	LANGCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description

Name	MEDADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description

Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCDESC

Attribute	**Description**
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

GOODDESC

Attribute	Description	
Name	GOODDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	6500

TOP

GOODCD

Attribute	Description	
Name	GOODCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

REFPREADV

Attribute	Description	
Name	REFPREADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Tracer-Details

Attribute	Description	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DRFTSLNO

Attribute	Description

Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

DRFTTNR

Attribute	**Description**
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PCTAMT

Attribute	**Description**
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	**Description**
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	**Description**
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

OPNPLCYFLG

Attribute	**Description**
Name	OPNPLCYFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

WAREHOUSEADDR

Attribute	Description	
Name	WAREHOUSEADDR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	100

TOP

DRAFTAMT

Attribute	Description	
Name	DRAFTAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DRAFTPCT

Attribute	Description	
Name	DRAFTPCT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Draft-Details

Attribute	Description	
Name	Draft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

AMTNAM

Attribute	Description

Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

AMT

Attribute	**Description**
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Control

Attribute	**Description**
Name	Control
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Transdet

Attribute	**Description**
Name	Transdet
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	**Description**
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description

Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

JVPARENT

Attribute	**Description**
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Fundmaster

Attribute	Description
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Commission

Attribute	**Description**
Name	Commission
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	Attribute: minOccurs, Description: 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number

Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	Description	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description	Indicates Latest Event Sequence Number	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Contract-Settlement

Attribute	Description	
Name	Contract-Settlement	
Datatype		
Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CUSTSPREAD

Attribute	Description

Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	**Description**
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	**Description**
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	**Description**
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description	
Name	SNDTRRCVINFO1	
Datatype	String	
Description	Indicates Sender To Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description	
Name	SNDTRRCVINFO2	
Datatype	String	
Description	Indicates Sender To Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO3

Attribute	Description	
Name	SNDTRRCVINFO3	
Datatype	String	
Description	Indicates Sender To Receiver Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO4

Attribute	Description	
Name	SNDTRRCVINFO4	
Datatype	String	
Description	Indicates Sender To Receiver Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3

Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4

Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail

Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: enumeration; Description: ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	Attribute: minOccurs — Description: 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields

Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	Description
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	Description
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	**Description**
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS10

Attribute	**Description**
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS2

Attribute	**Description**
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS3

Attribute	**Description**
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS4

Attribute	**Description**
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	

Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	

Attribute	Description
minOccurs	0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	
Restrictions	

Attribute	Description
minOccurs	0

Restrictions	Description
maxLength	16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	

Attribute	Description
maxOccurs	unbounded
minOccurs	0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	Attribute: minOccurs, Description: 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	Description
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	Description
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTPRTYID

Attribute	Description
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANACC

Attribute	**Description**
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NEGORATE

Attribute	**Description**
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGO_REF_NO

Attribute	**Description**
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Bcpref

Attribute	**Description**
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	**Description**
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	**Description**
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLINE

Attribute	Description	
Name	CRDLINE	
Datatype	String	
Description	Indicates Credit Line	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	11

TOP

RTCD

Attribute	Description	
Name	RTCD	
Datatype	String	
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

EXCHRT

Attribute	Description	
Name	EXCHRT	
Datatype	Number	
Description	Indicates Exchange Rate.	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RTTYP

Attribute	Description	
Name	RTTYP	
Datatype	String	
Description	Indicates the Rate Type	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	**Description**
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	**Description**
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

INTBASIS

Attribute	**Description**

Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

KEYID

Attribute	Description

Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Extsys-Ws-Details

Attribute	**Description**
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERREMARKS

Attribute	**Description**
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	**Description**
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

BRKACCCCY

Attribute	Description	
Name	BRKACCCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description	
Name	BRKPERCENT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

EXRATE

Attribute	Description	
Name	EXRATE	
Datatype	Number	
Description	Indicates Exchange Rate	
Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description	
Name	REMARKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Master

Attribute	**Description**
Name	Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEY_ID

Attribute	**Description**
Name	KEY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNCTION_ID

Attribute	**Description**
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Doc-Upload

Attribute	**Description**
Name	Doc-Upload
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 2000

TOP

Lic-Master

Attribute	Description

Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

License-Utils-Detail

Attribute	**Description**
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IMPLICNO

Attribute	**Description**
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

2.32.3.LI-CreateContract-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Contract-Details-Full*
    - *LATVERNO*
    - *PRDCD*
    - *OPERCD*
    - *PRDDESC*
    - *PRDTP*
    - *CONREFNO*
    - *USEREFNO*
    - *EXTREFNO*
    - *SOURCE*
    - *TRAKLMT*
    - *PRTYTYP*
    - *CRDLIN*
    - *LMTTRTENOTYP*
    - *REIMTYP*
    - *CHRGFRMBEN*
    - *ADDAMTCOVERD*
    - *PERDPRESENTATION*
    - *CHRGCCYISB*

CHRGMSTISB
CHRGFRMISB
ACCFORISB
ISSBDT
AMNDNO
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
MAXCONTAMT
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
INCODESC
APPRULE
RULENARRATIVE
CIFID
CUSTNAME
CUSTTYP
CUSTREFDT
CUSTREFNO
LICEXPDT
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
CURRAVAIL
OSLIAB
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
NEXTREINDT

ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
MAKER
MAKDTTIME
CHKR
CHKDTTIME
TXNSTAT
AUTHSTATS
BACKTOBACK
ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
PARTIALCLOS
TEMPLATEID
COLLATLOANALLOWED
UNDEREXPDT
UNDRTKNAMT
AVLDUNDRTKGAMT
CONPERCENT
USRLCREFERENCE
UCNFAMT
AVALCONFAMT
AVALUCNFAMT
USGTST
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYDESC*
- *PARTYCIFID*
- *CUSTNAME*

- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details

- *MSGTYP*
- *PRTY*
- *PRTYID*
- *PRTYNAME*
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Documents-Details

- *DOCCD*
- *DOCTYP*
- *DOCDESC*
- *REFERENCE*
- *DOCCPY*
- *NOOFORIGINALS*
- *DOCORIGINAL*
- *Clause-Details*
  - *CLAUSECD*
  - *CLAUSEDESC*

Shipment-Details

- *FROMPALCE*
- *TOPLACE*
- *PARTIALSHPMNT*
- *TRANSSHPMNT*
- *LATSHIPDT*

- *SHPPERD*
- *SHPMNTDET*
- *SHPMNTMARK*
- *PORTDISCHARGE*
- *PORTLOADING*
- *SHPDAYS*
- *PARSHIPDET*
- *TRASHIPDET*

Goods-Details

- *GOODDESC*
- *GOODCD*
- *REFPREADV*

Tracer-Details

- *TRACERCD*
- *TRACERDESC*
- *TRACERPRTY*
- *REQRD*
- *MAXTRACER*
- *SENTTODATE*
- *STRTDYS*
- *LASTTRACDT*
- *MEDIUM*
- *FREQ*
- *TEMPLATE_ID*

Drafts

- *DRFTSLNO*
- *DRFTTNR*
- *PCTAMT*
- *CRDAYSFRM*
- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*

- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *FROMLCREF*
- *TOLCREF*
- *SLNO*
- *ESN*
- *TRANSAMT*
- *TRANSDT*
- *NEWEXPDT*
- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUCO*
- *INSUPOLCYNO*
- *INSURANCEAMT*
- *LCYAMT*

Dfrrd-Intcomp

- *CONREFNUM*
- *ESN*
- *COMP*
- *CCY*
- *DUEDATE*

- *AMTDUE*
- *AMOUNTPAID*
- *STATUS*
- *LIQDDATE*

Commission

- *CONREFNO*
- *Commission-Details*
  - *COMPNT*
  - *PICKESN*
  - *EVENT*
  - *CCY*
  - *AMT*
  - *COLLPERD*
  - *RATEPER*
  - *WAIVER*
  - *RATE*
  - *PAYTYP*
  - *STOPDT*
  - *ACCRRQRD*
  - *CALCMETH*
  - *PARTY*
  - *STARTDT*
  - *GOODDATE*
  - *FOLLWRUL*
  - *RNDPER*
  - *RNDRAT*
  - *APPRATE*
  - *ACQRDAMT*
  - *COMMCALCBASIS*
  - *EVNTDESC*
  - *COMPDESC*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*

- *TGCCY*
- *TGAMT*
- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*

SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4

- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*

SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT
EXRATE
COLLTDESC
ADJSTSIGN
ADJSTAMT
Taxes
Tax

- *CONREFNO*
- *SCHEME*
- *WAIVER*
- *Tax-Details*
  - *RULE*
  - *BASISAMNTAG*
  - *COMPUEVNT*
  - *WAIVER*
  - *Rule-Details*
    - *VALUEDT*
    - *COMPUTATIONDT*
    - *CCY*
    - *AMT*
    - *ESN*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDTOCCY*
  - *LINKEDAMT*
  - *EXRATE*
  - *CONVLINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*

REFRATECD
COSTCD1
COSTCD2
COSTCD3
COSTCD4
COSTCD5
TXNMIS1
TXNMIS10
TXNMIS2
TXNMIS3
TXNMIS4
TXNMIS5
TXNMIS6
TXNMIS7
TXNMIS8
TXNMIS9
MISGRPCOMP
MISGRPTXN
COMPMIS1
COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5

- *TRANMIS6*
- *TRANMIS7*
- *TRANMIS8*
- *TRANMIS9*
- *TRANMIS10*
- *COMMIS1*
- *COMMIS2*
- *COMMIS3*
- *COMMIS4*
- *COMMIS5*
- *COMMIS6*
- *COMMIS7*
- *COMMIS8*
- *COMMIS9*
- *COMMIS10*
- *FUNMIS1*
- *FUNMIS2*
- *FUNMIS3*
- *FUNMIS4*
- *FUNMIS5*
- *FUNMIS6*
- *FUNMIS7*
- *FUNMIS8*
- *FUNMIS9*
- *FUNMIS10*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

- *CONREFNO*
- *Split-Master*
  - *BASISAMTTAG*
  - *BASISAMTCCY*
  - *BASISAMT*
  - *Split-Detail*
    - *SPTSEQNO*
    - *SPTAMTTAG*

SPTAMT

SPTACBRN

SPTACCCY

SPRACNO

SPTEXCHRT

SPTPRTYID

SPTPERCENTAGE

LOANACC

NEGORATE

NEGO_REF_NO

Bcpref

CONREFNO

LATEVNSEQNO

BCREFNO

ESN

CNTRPARTY

PRD

CCY

TENOR

UNITS

CRDLINE

RTCD

EXCHRT

RTTYP

MATACC

BRIDGL

CYSTALTYP

COLLLIQDAMT

LIQDLCCHGCOMM

MATDT

LOANAMT

BILLOS

CONTRACT_CURRENCY

RATECDPREF

MAXRATVAR

MINRTVAR

PMNTMD

DRACCBRN

DRPRODAC

CRACCBRN

CRPRODAC

LOANVALDATE

ORGEXCHRATE

Bcprefdet

- *UDEID*
- *RTCD*
- *USAGE*
- *INTBASIS*
- *SPLAMT*
- *INTRT*
- *INTSPRD*
- *UDEDESC*

Extsys-Ws-Master

- *Extsys-Ws-Details*
  - *EXTWSRESP*
  - *USERREMARKS*

Brok-Master

- *CONREFNO*
- *CONTRACTCCY*
- *BROKPERCENT*
- *BROKAMT*
- *Brok-Detail*
  - *BROKNAME*
  - *BROKER*
  - *BRKACC*
  - *BRKACCCCY*
  - *BRKPERCENT*
  - *BRKAMTACCCCY*
  - *EXRATE*
  - *ORGEXRATE*
  - *NEGRATE*
  - *NEGREFNO*
  - *REMARKS*
  - *BRKAMTCONCCY*
  - *LIQSTATUS*

Master

- *Doc-Upload*
  - *DCREFNO*
  - *DOC_CATEGORY*
  - *DOC_TYPE*
  - *REMARKS*
- *Ui-Columns*

Lic-Master

- *License-Utils-Detail*
  - *IMPLICNO*
  - *GOODSCD*
  - *QTYUTIL*
  - *AMTUTIL*

QTYREIN

AMTREIN

REMARKS

UNIT_OF_MEASUREMENT

LICENSE_AMOUNT

GOODSDESC

AMTQ_UT

AMTQ_RE

AVAILQTY_LICAMT

LIC_AMOUNT_UTILIZED

LIC_AMOUNT_REINS

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8 Restrictions: pattern — Description: [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Contract-Details-Full

Attribute	Description
Name	Contract-Details-Full
Datatype	
Description	

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	enumeration	,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDTP

Attribute	Description
Name	PRDTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,I,E,S,C,G,H,A,R

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

EXTREFNO

Attribute	Description	
Name	EXTREFNO	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

TRAKLMT

Attribute	Description	
Name	TRAKLMT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PRTYTYP

Attribute	Description	
Name	PRTYTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

PERDPRESENTATION

Attribute	**Description**
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 143

TOP

CHRGCCYISB

Attribute	**Description**
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGMSTISB

Attribute	**Description**
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGFRMISB

Attribute	**Description**
Name	CHRGFRMISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	215

TOP

ACCFORISB

Attribute	Description	
Name	ACCFORISB	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ISSBDT

Attribute	Description	
Name	ISSBDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMNDNO

Attribute	Description	
Name	AMNDNO	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STOPDT1

Attribute	Description	
Name	STOPDT1	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXCONTAMT

Attribute	Description
Name	MAXCONTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INCODESC

Attribute	Description
Name	INCODESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CUSTREFDT

Attribute	Description
Name	CUSTREFDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

LICEXPDT

Attribute	Description
Name	LICEXPDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SETTLTYP

Attribute	Description
Name	SETTLTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,S,N

TOP

SETTLMTH

Attribute	Description
Name	SETTLMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	Description
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PAYMNTDT

Attribute	Description
Name	PAYMNTDT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CURRAVAIL

Attribute	Description
Name	CURRAVAIL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

OSLIAB

Attribute	Description
Name	OSLIAB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REVOLVE

Attribute	Description
Name	REVOLVE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,T,V

TOP

REINTYP

Attribute	Description
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEXTREINDT

Attribute	Description
Name	NEXTREINDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	Description
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	Description
Name	MAYCONFIRM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKDTTIME

Attribute	**Description**
Name	MAKDTTIME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CHKR

Attribute	Description
Name	CHKR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHKDTTIME

Attribute	Description
Name	CHKDTTIME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description
Name	AUTHSTATS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / ,U,A

TOP

BACKTOBACK

Attribute	**Description**
Name	BACKTOBACK
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKNREVCD

Attribute	**Description**
Name	ACKNREVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACKDT

Attribute	**Description**
Name	ACKDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMDDT

Attribute	**Description**
Name	AMDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

AMNDCHK

Attribute	**Description**
Name	AMNDCHK

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	**Description**
Name	GUARREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

FEECLMADV

Attribute	Description	
Name	FEECLMADV	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PARTIALCLOS

Attribute	Description	
Name	PARTIALCLOS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

TEMPLATEID

Attribute	Description	
Name	TEMPLATEID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COLLATLOANALLOWED

Attribute	Description	
Name	COLLATLOANALLOWED	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVLDUNDRTKGAMT

Attribute	Description
Name	AVLDUNDRTKGAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

UCNFAMT

Attribute	Description
Name	UCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALCONFAMT

Attribute	Description
Name	AVALCONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AVALUCNFAMT

Attribute	Description
Name	AVALUCNFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

USGTST

Attribute	Description
Name	USGTST
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYDESC

Attribute	Description
Name	PARTYDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN1

Attribute	**Description**
Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTREFDATE

Attribute	**Description**
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LANGCD

Attribute	**Description**
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ACCNO

Attribute	**Description**
Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSGTYP

Attribute	**Description**
Name	MSGTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

MEDIUM

Attribute	Description	
Name	MEDIUM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCTYP

Attribute	**Description**
Name	DOCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,T,I,V,O

TOP

DOCDESC

Attribute	Description
Name	DOCDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

REFERENCE

Attribute	Description
Name	REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	Description
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	Description
Name	Shipment-Details
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FROMPALCE

Attribute	Description
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

TOPLACE

Attribute	Description
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	Description
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	Description
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	Description
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SHPPERD

Attribute	Description
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PORTLOADING

Attribute	**Description**
Name	PORTLOADING
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

SHPDAYS

Attribute	**Description**
Name	SHPDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARSHIPDET

Attribute	**Description**
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRASHIPDET

Attribute	**Description**
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

TRACERCD

Attribute	Description
Name	TRACERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

TRACERDESC

Attribute	Description
Name	TRACERDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REQRD

Attribute	Description
Name	REQRD
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MAXTRACER

Attribute	Description
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SENTTODATE

Attribute	Description
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STRTDYS

Attribute	Description
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LASTTRACDT

Attribute	Description
Name	LASTTRACDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

FREQ

Attribute	**Description**
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	**Description**
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	**Description**
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	**Description**
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS2

Attribute	Description	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSUCOMPCD

Attribute	Description	
Name	INSUCOMPCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

INSUCO

Attribute	Description	
Name	INSUCO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN1

Attribute	**Description**
Name	ADDRSLN1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN2

Attribute	**Description**
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN3

Attribute	**Description**
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ADDRSLN4

Attribute	**Description**
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

TELEPHNO

Attribute	Description
Name	TELEPHNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

FAXNUMBER

Attribute	Description
Name	FAXNUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

OPNPLCYFLG

Attribute	Description
Name	OPNPLCYFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

POLICYUTLAMT

Attribute	**Description**
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	**Description**
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	**Description**
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	**Description**
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1

Restrictions	Restrictions	Description
	maxLength	105

TOP

AMT

Attribute	Description	
Name	AMT	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Control

Attribute	Description	
Name	Control	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Transdet

Attribute	Description	
Name	Transdet	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FROMLCREF

Attribute	Description	
Name	FROMLCREF	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

TOLCREF

Attribute	Description
Name	TOLCREF
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSAMT

Attribute	**Description**
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TRANSDT

Attribute	**Description**
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWEXPDT

Attribute	**Description**
Name	NEWEXPDT
Datatype	Date

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	**Description**	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINKEDREFNO

Attribute	**Description**	
Name	LINKEDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LIABILITY_NUMBER

Attribute	**Description**	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

Fundmaster

Attribute	**Description**	
Name	Fundmaster	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LCYAMT

Attribute	**Description**
Name	LCYAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Dfrrd-Intcomp

Attribute	**Description**
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFNUM

Attribute	**Description**
Name	CONREFNUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMOUNTPAID

Attribute	Description
Name	AMOUNTPAID
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDDATE

Attribute	Description
Name	LIQDDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	Includes Commission details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

PICKESN

Attribute	Description	
Name	PICKESN	
Datatype	Number	
Description	Indicates Pickup Event Seq Number	
Attributes	Attribute	Description
	minOccurs	1

TOP

EVENT

Attribute	Description	
Name	EVENT	
Datatype	String	
Description	Indicates Event	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	Description
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PAYTYP

Attribute	Description
Name	PAYTYP
Datatype	String
Description	Indicates Payment Type ADVANCED : A Arrears : R
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,R

TOP

STOPDT

Attribute	Description
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	Description
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	Description
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number

Description	Indicates Rounding Period	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

RNDRAT

Attribute	Description	
Name	RNDRAT	
Datatype	Number	
Description	Indicates Rounding Rate	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

APPRATE

Attribute	Description	
Name	APPRATE	
Datatype	String	
Description	Indicates Apply Rate Current : C Next : N	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,C,N

TOP

ACQRDAMT

Attribute	Description	
Name	ACQRDAMT	
Datatype	Number	
Description	Indicates Acquired Amount	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9

Attributes	Attribute	Description
	minOccurs	0

TOP

EVNTDESC

Attribute	Description	
Name	EVNTDESC	
Datatype	String	
Description	Indicates Event Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COMPDESC

Attribute	Description	
Name	COMPDESC	
Datatype	String	
Description	Indicates Component Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description

Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description	
Name	FREETXT3	
Datatype	String	
Description	Indicates Free Text 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs; Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	

Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	Description
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

LINKEDTOCCY

Attribute	Description
Name	LINKEDTOCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

CONVLINKEDAMT

Attribute	Description
Name	CONVLINKEDAMT
Datatype	Number
Description	Indicates Converted Linked Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String

Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	**Description**
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	**Description**
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	**Description**
Name	ACCOUNT
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	**Description**
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS1

Attribute	Description
Name	TRANMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS2

Attribute	Description
Name	TRANMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS3

Attribute	Description
Name	TRANMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS9

Attribute	Description	
Name	TRANMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS10

Attribute	Description	
Name	TRANMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS1

Attribute	Description	
Name	COMMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

COMMIS2

Attribute	Description	
Name	COMMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS3

Attribute	Description	
Name	COMMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS4

Attribute	Description	
Name	COMMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS5

Attribute	Description	
Name	COMMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS6

Attribute	Description	
Name	COMMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS10

Attribute	**Description**
Name	FUNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

Txnmisdetails

Attribute	**Description**
Name	Txnmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Compmisdetails

Attribute	**Description**
Name	Compmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Fundmisdetails

Attribute	**Description**
Name	Fundmisdetails
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BASISAMTTAG

Attribute	Description
Name	BASISAMTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASISAMTCCY

Attribute	Description
Name	BASISAMTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BASISAMT

Attribute	Description
Name	BASISAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SPTSEQNO

Attribute	Description
Name	SPTSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

SPTAMT

Attribute	Description
Name	SPTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

SPTACCCY

Attribute	Description

Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SPTEXCHRT

Attribute	**Description**
Name	SPTEXCHRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SPTPERCENTAGE

Attribute	**Description**
Name	SPTPERCENTAGE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANACC

Attribute	Description
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CNTRPARTY

Attribute	Description
Name	CNTRPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,D,M

TOP

CRDLINE

Attribute	Description
Name	CRDLINE

Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

BRIDGL

Attribute	Description
Name	BRIDGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CYSTALTYP

Attribute	Description
Name	CYSTALTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COLLLIQDAMT

Attribute	Description
Name	COLLLIQDAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDLCCHGCOMM

Attribute	Description
Name	LIQDLCCHGCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

MATDT

Attribute	Description
Name	MATDT
Datatype	Date
Description	Indicates Maturity Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BILLOS

Attribute	Description
Name	BILLOS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTRACT_CURRENCY

Attribute	Description
Name	CONTRACT_CURRENCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC

Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

CRACCBRN

Attribute	**Description**
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRPRODAC

Attribute	**Description**
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LOANVALDATE

Attribute	**Description**
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ORGEXCHRATE

Attribute	**Description**
Name	ORGEXCHRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

USAGE

Attribute	Description
Name	USAGE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INTSPRD

Attribute	Description
Name	INTSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Extsys-Ws-Details

Attribute	Description
Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EXTWSRESP

Attribute	Description
Name	EXTWSRESP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

USERREMARKS

Attribute	Description
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	Description
Name	Brok-Master
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTRACTCCY

Attribute	Description
Name	CONTRACTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Brok-Detail

Attribute	Description

Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BROKNAME

Attribute	**Description**
Name	BROKNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

BROKER

Attribute	**Description**
Name	BROKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

BRKACC

Attribute	**Description**
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

BRKACCCCY

Attribute	**Description**
Name	BRKACCCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

BRKAMTACCCCY

Attribute	Description
Name	BRKAMTACCCCY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

ORGEXRATE

Attribute	Description
Name	ORGEXRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGRATE

Attribute	Description
Name	NEGRATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGREFNO

Attribute	Description
Name	NEGREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQSTATUS

Attribute	Description
Name	LIQSTATUS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Doc-Upload

Attribute	Description
Name	Doc-Upload
Datatype	
Description	
Attributes	Attribute: Description maxOccurs: unbounded minOccurs: 0

TOP

DCREFNO

Attribute	Description
Name	DCREFNO
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	Attribute: Description minOccurs: 1
Restrictions	Restrictions: Description maxLength: 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Ui-Columns

Attribute	Description
Name	Ui-Columns
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	Description
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	Description
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

GOODSCD

Attribute	Description	
Name	GOODSCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

TOP

QTYUTIL

Attribute	Description	
Name	QTYUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTUTIL

Attribute	Description	
Name	AMTUTIL	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

QTYREIN

Attribute	Description	
Name	QTYREIN	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

UNIT_OF_MEASUREMENT

Attribute	Description
Name	UNIT_OF_MEASUREMENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

LICENSE_AMOUNT

Attribute	Description
Name	LICENSE_AMOUNT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 7000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

AVAILQTY_LICAMT

Attribute	Description
Name	AVAILQTY_LICAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_UTILIZED

Attribute	Description
Name	LIC_AMOUNT_UTILIZED
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIC_AMOUNT_REINS

Attribute	Description
Name	LIC_AMOUNT_REINS
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	**Description**
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	**Description**
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.32.4.LI-CreateContract-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Contract-Details-PK*
      - *CONREFNO*
    - *Contract-Details-IO*
      - *PRDCD*
      - *OPERCD*
      - *CONREFNO*
      - *USEREFNO*
      - *EXTREFNO*
      - *TRAKLMT*
      - *PRTYTYP*
      - *CRDLIN*
      - *LMTTRTENOTYP*
      - *REIMTYP*
      - *CHRGFRMBEN*
      - *ADDAMTCOVERD*
      - *PERDPRESENTATION*
      - *CHRGCCYISB*
      - *CHRGMSTISB*

CHRGFRMISB
ACCFORISB
ISSBDT
STOPDT1
CONTCCY
CONTAMT
POSTOL
NEGTOL
LIABTOL
MAXLIABAMT
TOLTXT
ISSDT
EFFDT
TENOR
EXPDT
EXPPLACE
CLOSDT
GUARNTYP
ISSREQ
INCOTRM
APPRULE
RULENARRATIVE
CIFID
CUSTTYP
CUSTREFDT
CUSTREFNO
SETTLTYP
SETTLMTH
CREDITAVLWITH
PAYMNTDT
REVOLVE
REINTYP
CUMMULATIVE
UNITS
FREQ
ALLOWREPAY
CLOSTYP
TRANSBLE
MAYCONFIRM
REMARK
RELLCREF
TXNSTAT
AUTHSTATS
BACKTOBACK

ACKNREVCD
ACKDT
AMDDT
AMNDCHK
URRPREF
GUARREFNO
CONFAMT
PARCONALLOW
FEECLMADV
TEMPLATEID
UNDEREXPDT
UNDRTKNAMT
CONPERCENT
USRLCREFERENCE
STATUSCNTRLCD
USERDEFSTAT
BENCONFREQD
PREADVICEDT
FUNDID
Party-Details
- *PRTYTYP*
- *PARTYCIFID*
- *CUSTNAME*
- *CUSTADDLIN1*
- *CUSTADDLIN2*
- *CUSTADDLIN3*
- *CUSTADDLIN4*
- *COUNTRYCD*
- *CUSTREFNO*
- *CUSTREFDATE*
- *LANGCD*
- *ISSBANK*
- *TEMPLATE_ID*
- *Party-Other-Addresses*
  - *MEDTYP*
  - *MEDADDR*
  - *ACCNO*

Advice-Details
- *MEDIUM*
- *PRIORITY*
- *SUPRESS*
- *CHGREQD*
- *Fft-Details*
  - *FFTINSCD*

FFTINSDESC

SINGLEFFT

Documents-Details

DOCCD

DOCDESC

REFERENCE

DOCCPY

NOOFORIGINALS

DOCORIGINAL

Clause-Details

CLAUSECD

CLAUSEDESC

Shipment-Details

FROMPALCE

TOPLACE

PARTIALSHPMNT

TRANSSHPMNT

LATSHIPDT

SHPPERD

SHPMNTDET

SHPMNTMARK

PORTDISCHARGE

PORTLOADING

SHPDAYS

PARSHIPDET

TRASHIPDET

Goods-Details

GOODDESC

GOODCD

REFPREADV

Tracer-Details

TRACERPRTY

REQRD

MAXTRACER

SENTTODATE

STRTDYS

MEDIUM

FREQ

TEMPLATE_ID

Drafts

DRFTSLNO

DRFTTNR

PCTAMT

CRDAYSFRM

- *DRAWEE*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *INSUCOMPCD*
- *INSUCO*
- *ADDRSLN1*
- *ADDRSLN2*
- *ADDRSLN3*
- *ADDRSLN4*
- *INSUEXPDT*
- *INSUPOLCYNO*
- *TELEPHNO*
- *FAXNUMBER*
- *OPNPLCYFLG*
- *POLICYUTLAMT*
- *CVRDT*
- *INSURANCEAMT*
- *TELEXADDR*
- *WAREHOUSEADDR*
- *DRAFTAMT*
- *DRAFTPCT*
- *Draft-Details*
  - *AMTNAM*
  - *AMT*

Control

Transdet

- *NEWLATSHIPMENTDT*

Contract-Limits

- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *PARTYTYP*
- *JVPARENT*
- *SLNO*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*

Fundmaster

- *FUNDID*

Insurance

- *INSUPOLCYNO*
- *LCYAMT*

Dfrrd-Intcomp

- *Commission*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Commission-Details*
    - *CCY*
    - *AMT*
    - *COLLPERD*
    - *RATEPER*
    - *WAIVER*
    - *RATE*
    - *STOPDT*
    - *ACCRRQRD*
    - *CALCMETH*
    - *PARTY*
    - *STARTDT*
    - *GOODDATE*
    - *FOLLWRUL*
    - *RNDPER*
    - *RNDRAT*
    - *ACQRDAMT*
    - *COMMCALCBASIS*
- *Charges*
  - *LATEVNSEQNO*
  - *CONREFNO*
  - *Charge-Association*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *CUSTSPREAD*
    - *SPREADDEFN*

TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3

ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*

ITIMEIND3
INSTRCD5
BANKOPERCD
INSTRCD6
TRNSTYPCD
REGREP1
REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Collateral-details
CONREFNO
LATEVNSEQNO
Collateral
COLLTCCY
COLLTPCT
COLLTAMT

- *EXRATE*
- *COLLTDESC*
- *ADJSTSIGN*
- *ADJSTAMT*

Taxes

- *CONREFNO*
- *LATEVNSEQNO*
- *Tax*
  - *WAIVER*
  - *Tax-Details*
    - *Rule-Details*

Linkages

- *CONREFNO*
- *LATEVNSEQNO*
- *Linkage-Details*
  - *LINKEDAMT*
  - *LINKEDTOREF*
  - *LINKAGETYP*
- *Ui-Fields*
  - *ACCOUNT*
  - *DEPOSIT*
  - *UNCOVAMT*

TXNUDFDETAILS

- *FLDNAME*
- *FLDVAL*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*

- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*
- *COMPMIS4*
- *COMPMIS5*
- *COMPMIS6*
- *COMPMIS7*
- *COMPMIS8*
- *COMPMIS9*
- *FUNDMIS1*
- *FUNDMIS10*
- *FUNDMIS2*
- *FUNDMIS3*
- *FUNDMIS4*
- *FUNDMIS5*
- *FUNDMIS6*
- *FUNDMIS7*
- *FUNDMIS8*
- *FUNDMIS9*
- *MISGRPFUN*
- *Txnmisdetails*
- *Compmisdetails*
- *Fundmisdetails*

Lctbs-Lccbclnk-Master

- *CONTRACT_REF_NO*
- *Lctbs-Lccbclnk-Master-Child*
  - *BCREFNO*
  - *BCCY*
  - *BILL_AMT*
  - *OURLCREF*

Split-Master

CONREFNO
LATEVNSEQNO
Split-Master
Split-Detail
SPTAMTTAG
SPTACBRN
SPTACCCY
SPRACNO
SPTPRTYID
LOANACC
NEGORATE
NEGO_REF_NO
Bcpref
CONREFNO
LATEVNSEQNO
BCREFNO
PRD
CCY
CRDLINE
RTCD
EXCHRT
RTTYP
MATACC
LOANAMT
RATECDPREF
MAXRATVAR
MINRTVAR
PMNTMD
DRACCBRN
DRPRODAC
CRACCBRN
CRPRODAC
LOANVALDATE
Bcprefdet
UDEID
INTBASIS
SPLAMT
INTRT
UDEDESC
Extsys-Ws-Master
KEYID
Extsys-Ws-Details
USERREMARKS
Brok-Master

CONREFNO

LATEVNSEQNO

BROKPERCENT

BROKAMT

Brok-Detail

BRKACC

BRKACCCCY

BRKPERCENT

EXRATE

REMARKS

BRKAMTCONCCY

Master

KEY_ID

FUNCTION_ID

Doc-Upload

DCREFNO

DOC_CATEGORY

DOC_TYPE

REMARKS

Lic-Master

CONREFNO

LATEVNSEQNO

License-Utils-Detail

IMPLICNO

GOODSCD

QTYUTIL

AMTUTIL

QTYREIN

AMTREIN

REMARKS

AMTQ_UT

AMTQ_RE

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Contract-Details-PK

Attribute	Description
Name	Contract-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Details-IO

Attribute	Description
Name	Contract-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

OPERCD

Attribute	Description
Name	OPERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: enumeration / ,OPN,ONC,PAD,ADV,CNF,ANC,RMB

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

USEREFNO

Attribute	Description
Name	USEREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

EXTREFNO

Attribute	Description
Name	EXTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

TRAKLMT

Attribute	Description
Name	TRAKLMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CRDLIN

Attribute	Description
Name	CRDLIN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

LMTTRTENOTYP

Attribute	Description
Name	LMTTRTENOTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,D

TOP

REIMTYP

Attribute	Description
Name	REIMTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,O,C

TOP

CHRGFRMBEN

Attribute	Description
Name	CHRGFRMBEN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 210

TOP

ADDAMTCOVERD

Attribute	Description
Name	ADDAMTCOVERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 143

TOP

CHRGCCYISB

Attribute	Description
Name	CHRGCCYISB
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGMSTISB

Attribute	Description
Name	CHRGMSTISB
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGFRMISB

Attribute	Description
Name	CHRGFRMISB

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 215

TOP

ACCFORISB

Attribute	**Description**
Name	ACCFORISB
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ISSBDT

Attribute	**Description**
Name	ISSBDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STOPDT1

Attribute	**Description**
Name	STOPDT1
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONTCCY

Attribute	**Description**
Name	CONTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 1

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

LIABTOL

Attribute	Description
Name	LIABTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXLIABAMT

Attribute	Description
Name	MAXLIABAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

TOLTXT

Attribute	Description
Name	TOLTXT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,N,A

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

EFFDT

Attribute	Description
Name	EFFDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TENOR

Attribute	Description
Name	TENOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

EXPDT

Attribute	Description
Name	EXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

EXPPLACE

Attribute	Description
Name	EXPPLACE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 29

TOP

CLOSDT

Attribute	Description
Name	CLOSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GUARNTYP

Attribute	Description
Name	GUARNTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ISSREQ

Attribute	Description
Name	ISSREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,I,R

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

APPRULE

Attribute	Description
Name	APPRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RULENARRATIVE

Attribute	Description
Name	RULENARRATIVE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CIFID

Attribute	Description
Name	CIFID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 9

TOP

CUSTTYP

Attribute	Description
Name	CUSTTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CUSTREFDT

Attribute	**Description**
Name	CUSTREFDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTREFNO

Attribute	**Description**
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SETTLTYP

Attribute	**Description**
Name	SETTLTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,S,N

TOP

SETTLMTH

Attribute	**Description**
Name	SETTLMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / ,P,A,D,M,N

TOP

CREDITAVLWITH

Attribute	**Description**
Name	CREDITAVLWITH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

PAYMNTDT

Attribute	**Description**
Name	PAYMNTDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 143

TOP

REVOLVE

Attribute	**Description**
Name	REVOLVE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,T,V

TOP

REINTYP

Attribute	**Description**
Name	REINTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,M

TOP

CUMMULATIVE

Attribute	Description
Name	CUMMULATIVE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,N

TOP

UNITS

Attribute	Description
Name	UNITS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,D,M

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ALLOWREPAY

Attribute	Description
Name	ALLOWREPAY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLOSTYP

Attribute	Description
Name	CLOSTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

TRANSBLE

Attribute	**Description**
Name	TRANSBLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAYCONFIRM

Attribute	**Description**
Name	MAYCONFIRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REMARK

Attribute	**Description**
Name	REMARK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

RELLCREF

Attribute	**Description**
Name	RELLCREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTATS

Attribute	Description	
Name	AUTHSTATS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,U,A

TOP

BACKTOBACK

Attribute	Description	
Name	BACKTOBACK	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ACKNREVCD

Attribute	Description	
Name	ACKNREVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ACKDT

Attribute	Description
Name	ACKDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMDDT

Attribute	Description
Name	AMDDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

AMNDCHK

Attribute	Description
Name	AMNDCHK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

GUARREFNO

Attribute	Description
Name	GUARREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONFAMT

Attribute	**Description**
Name	CONFAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

FEECLMADV

Attribute	**Description**
Name	FEECLMADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATEID

Attribute	**Description**
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

UNDEREXPDT

Attribute	Description
Name	UNDEREXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

UNDRTKNAMT

Attribute	Description
Name	UNDRTKNAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONPERCENT

Attribute	Description
Name	CONPERCENT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

USRLCREFERENCE

Attribute	Description
Name	USRLCREFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

STATUSCNTRLCD

Attribute	Description
Name	STATUSCNTRLCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

USERDEFSTAT

Attribute	Description	
Name	USERDEFSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

BENCONFREQD

Attribute	Description	
Name	BENCONFREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PREADVICEDT

Attribute	Description	
Name	PREADVICEDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

FUNDID

Attribute	Description	
Name	FUNDID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Party-Details

Attribute	Description
Name	Party-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 1

TOP

PRTYTYP

Attribute	Description
Name	PRTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYCIFID

Attribute	Description
Name	PARTYCIFID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 150

TOP

CUSTADDLIN1

Attribute	Description

Name	CUSTADDLIN1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN2

Attribute	**Description**
Name	CUSTADDLIN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN3

Attribute	**Description**
Name	CUSTADDLIN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

CUSTADDLIN4

Attribute	**Description**
Name	CUSTADDLIN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRYCD

Attribute	**Description**
Name	COUNTRYCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CUSTREFNO

Attribute	Description
Name	CUSTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTREFDATE

Attribute	Description
Name	CUSTREFDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LANGCD

Attribute	Description
Name	LANGCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ISSBANK

Attribute	Description
Name	ISSBANK
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

Party-Other-Addresses

Attribute	Description
Name	Party-Other-Addresses
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDTYP

Attribute	Description
Name	MEDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

MEDADDR

Attribute	Description
Name	MEDADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

ACCNO

Attribute	Description

Name	ACCNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

Advice-Details

Attribute	**Description**
Name	Advice-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

SINGLEFFT

Attribute	Description

Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Documents-Details

Attribute	**Description**
Name	Documents-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCCD

Attribute	**Description**
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCDESC

Attribute	**Description**
Name	DOCDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

REFERENCE

Attribute	**Description**
Name	REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

DOCCPY

Attribute	Description
Name	DOCCPY
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

DOCORIGINAL

Attribute	Description
Name	DOCORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description

Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSEDESC

Attribute	**Description**
Name	CLAUSEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Shipment-Details

Attribute	**Description**
Name	Shipment-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROMPALCE

Attribute	**Description**
Name	FROMPALCE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TOPLACE

Attribute	**Description**
Name	TOPLACE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

PARTIALSHPMNT

Attribute	**Description**
Name	PARTIALSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSSHPMNT

Attribute	**Description**
Name	TRANSSHPMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LATSHIPDT

Attribute	**Description**
Name	LATSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SHPPERD

Attribute	**Description**
Name	SHPPERD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 395

TOP

SHPMNTDET

Attribute	Description
Name	SHPMNTDET
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 400

TOP

SHPMNTMARK

Attribute	Description
Name	SHPMNTMARK
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

PORTDISCHARGE

Attribute	Description
Name	PORTDISCHARGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTLOADING

Attribute	Description
Name	PORTLOADING
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

SHPDAYS

Attribute	Description
Name	SHPDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARSHIPDET

Attribute	Description
Name	PARSHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRASHIPDET

Attribute	Description
Name	TRASHIPDET
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

Goods-Details

Attribute	Description
Name	Goods-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODDESC

Attribute	Description
Name	GOODDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

GOODCD

Attribute	Description
Name	GOODCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

REFPREADV

Attribute	Description
Name	REFPREADV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRACERPRTY

Attribute	Description
Name	TRACERPRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REQRD

Attribute	Description

Name	REQRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

MAXTRACER

Attribute	**Description**
Name	MAXTRACER
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SENTTODATE

Attribute	**Description**
Name	SENTTODATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDYS

Attribute	**Description**
Name	STRTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

FREQ

Attribute	Description
Name	FREQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TEMPLATE_ID

Attribute	Description
Name	TEMPLATE_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

Drafts

Attribute	Description
Name	Drafts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DRFTSLNO

Attribute	Description
Name	DRFTSLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

DRFTTNR

Attribute	Description
Name	DRFTTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PCTAMT

Attribute	Description
Name	PCTAMT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P

TOP

CRDAYSFRM

Attribute	Description
Name	CRDAYSFRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 107

TOP

DRAWEE

Attribute	Description
Name	DRAWEE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSUCOMPCD

Attribute	Description
Name	INSUCOMPCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

INSUCO

Attribute	Description
Name	INSUCO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRSLN1

Attribute	Description
Name	ADDRSLN1

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN2

Attribute	Description
Name	ADDRSLN2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN3

Attribute	Description
Name	ADDRSLN3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRSLN4

Attribute	Description
Name	ADDRSLN4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INSUEXPDT

Attribute	Description
Name	INSUEXPDT
Datatype	Date
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

INSUPOLCYNO

Attribute	Description	
Name	INSUPOLCYNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

TELEPHNO

Attribute	Description	
Name	TELEPHNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

FAXNUMBER

Attribute	Description	
Name	FAXNUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

OPNPLCYFLG

Attribute	Description	
Name	OPNPLCYFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

POLICYUTLAMT

Attribute	Description
Name	POLICYUTLAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CVRDT

Attribute	Description
Name	CVRDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSURANCEAMT

Attribute	Description
Name	INSURANCEAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TELEXADDR

Attribute	Description
Name	TELEXADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

WAREHOUSEADDR

Attribute	Description
Name	WAREHOUSEADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

DRAFTAMT

Attribute	Description
Name	DRAFTAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DRAFTPCT

Attribute	Description
Name	DRAFTPCT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Draft-Details

Attribute	Description
Name	Draft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

AMTNAM

Attribute	Description
Name	AMTNAM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Control

Attribute	Description
Name	Control
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Transdet

Attribute	Description
Name	Transdet
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NEWLATSHIPMENTDT

Attribute	Description
Name	NEWLATSHIPMENTDT
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Contract-Limits

Attribute	Description
Name	Contract-Limits
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JVPARENT

Attribute	**Description**
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

SLNO

Attribute	**Description**
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	**Description**
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	**Description**
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Fundmaster

Attribute	Description
Name	Fundmaster
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FUNDID

Attribute	Description
Name	FUNDID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Insurance

Attribute	Description
Name	Insurance
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

INSUPOLCYNO

Attribute	Description
Name	INSUPOLCYNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LCYAMT

Attribute	Description
Name	LCYAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Dfrrd-Intcomp

Attribute	Description
Name	Dfrrd-Intcomp
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Commission

Attribute	Description
Name	Commission
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	

Description	Includes Commission details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COLLPERD

Attribute	Description
Name	COLLPERD
Datatype	Number
Description	Indicates Collection Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RATEPER

Attribute	Description
Name	RATEPER
Datatype	Number
Description	Indicates Rate Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER

Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATE

Attribute	**Description**
Name	RATE
Datatype	Number
Description	Indicates Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STOPDT

Attribute	**Description**
Name	STOPDT
Datatype	Date
Description	Indicates Stop Date
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCRRQRD

Attribute	**Description**
Name	ACCRRQRD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CALCMETH

Attribute	**Description**
Name	CALCMETH
Datatype	String
Description	Indicates Calculation Method Periodic : P Non Periodic : N Flat : S

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,P,N,S

TOP

PARTY

Attribute	Description
Name	PARTY
Datatype	String
Description	Indicates Party
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STARTDT

Attribute	Description
Name	STARTDT
Datatype	Date
Description	Indicates Start Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODDATE

Attribute	Description
Name	GOODDATE
Datatype	Date
Description	Indicates Good Until Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FOLLWRUL

Attribute	Description
Name	FOLLWRUL
Datatype	String
Description	Indicates Follow Rule Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RNDPER

Attribute	Description
Name	RNDPER
Datatype	Number
Description	Indicates Rounding Period
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RNDRAT

Attribute	Description
Name	RNDRAT
Datatype	Number
Description	Indicates Rounding Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACQRDAMT

Attribute	Description
Name	ACQRDAMT
Datatype	Number
Description	Indicates Acquired Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	Indicates Calculation Basis 30(EURO)/360 : 1 30(US)/360 : 2 Actual/360 : 3 30(EURO)/365 : 4 30(US)/365 : 5 6 : 6 7 : 7 8 : 8 Actual/Actual : 9
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**	
Name	INSTRCD6	
Datatype	String	
Description	Indicates Instruction Code 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	**Description**	
Name	TRNSTYPCD	
Datatype	String	
Description	Indicates Transaction Code of Time Indicators	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

REGREP1

Attribute	**Description**	
Name	REGREP1	
Datatype	String	
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Collateral-details

Attribute	Description
Name	Collateral-details
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

Collateral

Attribute	Description
Name	Collateral
Datatype	
Description	Includes Collateral details
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTCCY

Attribute	Description
Name	COLLTCCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

COLLTPCT

Attribute	Description
Name	COLLTPCT
Datatype	Number
Description	Indicates Percent
Attributes	Attribute: minOccurs — Description: 0

TOP

COLLTAMT

Attribute	Description
Name	COLLTAMT
Datatype	Number
Description	Indicates Collateral Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

COLLTDESC

Attribute	Description
Name	COLLTDESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADJSTSIGN

Attribute	Description
Name	ADJSTSIGN
Datatype	Number
Description	Indicates Adjustment Type Increase : 1 Decrease : -1
Attributes	Attribute: minOccurs — Description: 0

TOP

ADJSTAMT

Attribute	Description
Name	ADJSTAMT
Datatype	Number
Description	Indicates Adjustment Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	**Description**
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Linkages

Attribute	Description
Name	Linkages
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Linkage-Details

Attribute	Description
Name	Linkage-Details
Datatype	
Description	Includes Linkage details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

LINKEDAMT

Attribute	Description
Name	LINKEDAMT
Datatype	Number
Description	Indicates Linked Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDTOREF

Attribute	Description
Name	LINKEDTOREF
Datatype	String
Description	Indicates Linked To Reference Number/Account
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

LINKAGETYP

Attribute	Description
Name	LINKAGETYP
Datatype	String
Description	Indicates Linkage Type Account : A Deposit : D
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,D

TOP

Ui-Fields

Attribute	Description
Name	Ui-Fields
Datatype	
Description	Includes UI Fields details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACCOUNT

Attribute	Description
Name	ACCOUNT
Datatype	String

Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

DEPOSIT

Attribute	**Description**
Name	DEPOSIT
Datatype	String
Description	Indicates Deposit
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

UNCOVAMT

Attribute	**Description**
Name	UNCOVAMT
Datatype	String
Description	Indicates UnCovered Amount
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

TXNUDFDETAILS

Attribute	**Description**
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	**Description**
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

RELACC

Attribute	**Description**
Name	RELACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

RELETED_REFERENCE

Attribute	**Description**
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

MISHEAD

Attribute	**Description**
Name	MISHEAD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RATEFLG

Attribute	**Description**
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

Lctbs-Lccbclnk-Master

Attribute	Description
Name	Lctbs-Lccbclnk-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONTRACT_REF_NO

Attribute	Description
Name	CONTRACT_REF_NO
Datatype	String
Description	Indicates Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Lctbs-Lccbclnk-Master-Child

Attribute	Description
Name	Lctbs-Lccbclnk-Master-Child
Datatype	
Description	Master Child Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

BCCY

Attribute	Description
Name	BCCY
Datatype	String
Description	Indicates the Currency.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

BILL_AMT

Attribute	Description
Name	BILL_AMT
Datatype	Number
Description	Indicates the Bill Amount.
Attributes	Attribute: minOccurs — Description: 0

TOP

OURLCREF

Attribute	Description
Name	OURLCREF
Datatype	String
Description	Indicates our Letters of Credit Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

Split-Master

Attribute	Description
Name	Split-Master
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Split-Detail

Attribute	Description
Name	Split-Detail
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

SPTAMTTAG

Attribute	Description
Name	SPTAMTTAG
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 25

TOP

SPTACBRN

Attribute	Description
Name	SPTACBRN
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPTACCCY

Attribute	**Description**
Name	SPTACCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SPRACNO

Attribute	**Description**
Name	SPRACNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SPTPRTYID

Attribute	**Description**
Name	SPTPRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LOANACC

Attribute	**Description**
Name	LOANACC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NEGORATE

Attribute	Description
Name	NEGORATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEGO_REF_NO

Attribute	Description
Name	NEGO_REF_NO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Bcpref

Attribute	Description
Name	Bcpref
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BCREFNO

Attribute	Description
Name	BCREFNO
Datatype	String
Description	Indicates Bills and Collections Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

PRD

Attribute	Description
Name	PRD
Datatype	String
Description	Indicates Product Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CRDLINE

Attribute	Description
Name	CRDLINE
Datatype	String
Description	Indicates Credit Line
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	11

TOP

RTCD

Attribute	Description
Name	RTCD
Datatype	String
Description	Indicates Rate as of Booking :B Spot :S Value :V Dr Value :D Cr Value :C Inst. Date :I
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

EXCHRT

Attribute	Description
Name	EXCHRT
Datatype	Number
Description	Indicates Exchange Rate.
Attributes	Attribute: minOccurs — Description: 0

TOP

RTTYP

Attribute	Description
Name	RTTYP
Datatype	String
Description	Indicates the Rate Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 8

TOP

MATACC

Attribute	Description
Name	MATACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOANAMT

Attribute	Description
Name	LOANAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

RATECDPREF

Attribute	Description
Name	RATECDPREF
Datatype	String
Description	Indicates Rate Code Prefernce
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B

TOP

MAXRATVAR

Attribute	Description
Name	MAXRATVAR
Datatype	Number
Description	Indicates Maximum Rate Variance
Attributes	Attribute: minOccurs — Description: 0

TOP

MINRTVAR

Attribute	Description
Name	MINRTVAR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PMNTMD

Attribute	Description
Name	PMNTMD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

DRACCBRN

Attribute	Description
Name	DRACCBRN
Datatype	String
Description	Indicates Debit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DRPRODAC

Attribute	Description
Name	DRPRODAC
Datatype	String
Description	It indicates Debit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

CRACCBRN

Attribute	Description
Name	CRACCBRN
Datatype	String
Description	Indicates Credit Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CRPRODAC

Attribute	Description
Name	CRPRODAC
Datatype	String
Description	Indicates Credit Product Account
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

LOANVALDATE

Attribute	Description
Name	LOANVALDATE
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Bcprefdet

Attribute	Description
Name	Bcprefdet
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

UDEID

Attribute	Description
Name	UDEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

INTBASIS

Attribute	Description
Name	INTBASIS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SPLAMT

Attribute	Description
Name	SPLAMT
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INTRT

Attribute	Description
Name	INTRT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

UDEDESC

Attribute	Description
Name	UDEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Extsys-Ws-Master

Attribute	Description
Name	Extsys-Ws-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEYID

Attribute	Description
Name	KEYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 200

TOP

Extsys-Ws-Details

Attribute	Description

Name	Extsys-Ws-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

USERREMARKS

Attribute	**Description**
Name	USERREMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Brok-Master

Attribute	**Description**
Name	Brok-Master
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

BROKPERCENT

Attribute	Description
Name	BROKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BROKAMT

Attribute	Description
Name	BROKAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Brok-Detail

Attribute	Description
Name	Brok-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRKACC

Attribute	Description
Name	BRKACC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

BRKACCCCY

Attribute	Description
Name	BRKACCCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

BRKPERCENT

Attribute	Description
Name	BRKPERCENT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

BRKAMTCONCCY

Attribute	Description
Name	BRKAMTCONCCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Master

Attribute	Description
Name	Master

Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

KEY_ID

Attribute	**Description**
Name	KEY_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNCTION_ID

Attribute	**Description**
Name	FUNCTION_ID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

Doc-Upload

Attribute	**Description**
Name	Doc-Upload
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DCREFNO

Attribute	**Description**
Name	DCREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

DOC_CATEGORY

Attribute	Description
Name	DOC_CATEGORY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOC_TYPE

Attribute	Description
Name	DOC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Lic-Master

Attribute	Description
Name	Lic-Master
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

License-Utils-Detail

Attribute	**Description**
Name	License-Utils-Detail
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IMPLICNO

Attribute	**Description**
Name	IMPLICNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

GOODSCD

Attribute	**Description**
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

QTYUTIL

Attribute	Description
Name	QTYUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTUTIL

Attribute	Description
Name	AMTUTIL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

QTYREIN

Attribute	Description
Name	QTYREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTREIN

Attribute	Description
Name	AMTREIN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REMARKS

Attribute	Description
Name	REMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

AMTQ_UT

Attribute	Description
Name	AMTQ_UT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

AMTQ_RE

Attribute	Description
Name	AMTQ_RE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.CreateGuaranteeClaim

CreateGuaranteeClaim

2.33.1.LI-CreateGuaranteeClaim-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*

BENEFNAME

BENADDR

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

TXNSTAT

AUTHSTAT

LATEVNSEQNO

LATVERNO

BRANCH_CONT

Advices

- *MSGTYPE*
- *SUPRESS*
- *PRIORITY*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*

RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2

BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*

- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*

COMPNT
CREATESN
RULE
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description	
Name	CLAIM_SEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLAIMDT

Attribute	Description	
Name	CLAIMDT	
Datatype	Date	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

CLAIMAMT

Attribute	Description	
Name	CLAIMAMT	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1

TOP

REMRKS

Attribute	Description	
Name	REMRKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	Description
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	Description
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	Description
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYPE

Attribute	Description

Name	MSGTYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

SUPRESS

Attribute	**Description**
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRIORITY

Attribute	**Description**
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	15

TOP

PRTYID

Attribute	Description	
Name	PRTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	11

TOP

PRTYNAME

Attribute	Description	
Name	PRTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	

Description	Includes Contract Settlement details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String

Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description	
Name	PAYMNTDET1	
Datatype	String	
Description	Indicates Details Of Payment 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description	
Name	PAYMNTDET2	
Datatype	String	
Description	Indicates Details Of Payment 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET3

Attribute	Description	
Name	PAYMNTDET3	
Datatype	String	
Description	Indicates Details Of Payment 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET4

Attribute	Description	
Name	PAYMNTDET4	
Datatype	String	
Description	Indicates Details Of Payment 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	**Description**
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1

Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	**Description**
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	**Description**
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	**Description**
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	Attribute: minOccurs — Description: 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 14

TOP

PMNTTYP

Attribute	Description

Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description

Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

DECLARTION

Attribute	Description	
Name	DECLARTION	
Datatype	Number	
Description	Indicates Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association

Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

BASISAMNTAG

Attribute	Description
Name	BASISAMNTAG
Datatype	String
Description	Indicates Basis Component
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

COMPUEVNT

Attribute	Description
Name	COMPUEVNT
Datatype	String
Description	Indicates Event
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs, Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs, Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs, Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs, Description: 0

TOP

2.33.2.LI-CreateGuaranteeClaim-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-IO*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *BRANCH_CONT*
    - *Advices*
      - *SUPRESS*
      - *PRIORITY*

- *MEDIUM*
- *CHGREQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
- *Settlements*
- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*
  - *COVREQRD*
  - *RECVCVR*
  - *RECEIVER*
  - *REIMINST1*
  - *REIMINST4*

RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5

RCORRS15

ORDCUST5

ORDINST5

ULTBEN5

Settlement-Detail

- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*

REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Taxes
CONREFNO
LATEVNSEQNO
Tax
WAIVER
Tax-Details
Rule-Details

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

TEMPLATEID

Attribute	Description
Name	TEMPLATEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

MAKER

Attribute	Description
Name	MAKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	**Description**
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Ffts

Attribute	Description	
Name	Ffts	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTINSCD

Attribute	Description	
Name	FFTINSCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTINSDESC

Attribute	Description	
Name	FFTINSDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD

Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	**Description**
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	**Description**
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	**Description**
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	**Description**
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4

Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST2

Attribute	Description	
Name	ORDCUST2	
Datatype	String	
Description	Indicates Ordering Customer 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description	
Name	BENINST4	
Datatype	String	
Description	Indicates Beneficiary Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5

Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

POSACC

Attribute	**Description**	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

COUNTRCLGNW

Attribute	**Description**	
Name	COUNTRCLGNW	
Datatype	String	
Description	Indicates Clearing Network	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1

Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String

Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3

Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DISACCRAPPL

Attribute	Description	
Name	DISACCRAPPL	
Datatype	String	
Description	Indicates Consider as Discount Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number

Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	**Description**
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	**Description**
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	**Description**

Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

Rule-Details

Attribute	**Description**
Name	Rule-Details
Datatype	
Description	Includes Rule details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

2.33.3.LI-CreateGuaranteeClaim-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Guarantee-Claim-Full*
    - *CONREFNO*
    - *CLAIM_SEQNO*
    - *CLAIMDT*
    - *CLAIMAMT*
    - *REMRKS*
    - *TEMPLATEID*
    - *ISSDT*
    - *EXPDATE*
    - *ACC_CCY*
    - *AMNT*
    - *OS_GUARAMT*
    - *CPTY_NAME*
    - *ADDR*
    - *CPTYTYP*
    - *COUNT_PARTYREF*
    - *BENEFNAME*
    - *BENADDR*
    - *MAKER*

- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *LATEVNSEQNO*
- *LATVERNO*
- *BRANCH_CONT*
- *Advices*
  - *MSGTYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHGREQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4

SNDTRRCVINFO1

SNDTRRCVINFO2

SNDTRRCVINFO3

SNDTRRCVINFO4

SNDTRRCVINFO5

COVREQRD

RECVCVR

RECEIVER

REIMINST1

REIMINST2

REIMINST3

REIMINST4

RCVRCORRS1

RCVRCORRS2

RCVRCORRS3

RCVRCORRS4

INTERMEDIARY1

INTERMEDIARY2

INTERMEDIARY3

INTERMEDIARY4

ACCWITHINST1

ACCWITHINST2

ACCWITHINST3

ACCWITHINST4

ORDINST1

ORDINST2

ORDINST3

ORDINST4

ORDCUST1

ORDCUST2

ORDCUST3

ORDCUST4

BENINST1

BENINST2

BENINST3

BENINST4

ULTBEN1

ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *SNDRCUSTNAME1*
  - *SNDRCUSTNAME2*
  - *SNDRCUSTNAME3*
  - *SNDRCUSTNAME4*
  - *RCVRCUSTNAME1*
  - *RCVRCUSTNAME2*
  - *RCVRCUSTNAME3*
  - *RCVRCUSTNAME4*
  - *SNDRRCVRPART*
  - *ULTBANDCD*
  - *ADDLINFO1*
  - *ADDLINFO2*
  - *ADDLINFO3*
  - *ADDLINFO4*
  - *NIPPAYER*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*
  - *SNDRRCVRINFO4*
  - *SNDRRCVRINFO5*
  - *SNDRRCVRINFO6*
  - *DECLARTION*
  - *REPRES1*
  - *REPRES2*
  - *REPRES3*
  - *REPRES4*
  - *RCVRACC*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CREATESN
COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Taxes
Tax
CONREFNO
SCHEME
WAIVER
Tax-Details
RULE
BASISAMNTAG
COMPUEVNT
WAIVER
Rule-Details
VALUEDT
COMPUTATIONDT
CCY
AMT
ESN
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Guarantee-Claim-Full

Attribute	Description
Name	Guarantee-Claim-Full
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAIMDT

Attribute	Description
Name	CLAIMDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CLAIMAMT

Attribute	Description
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

REMRKS

Attribute	Description
Name	REMRKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

TEMPLATEID

Attribute	**Description**
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

ISSDT

Attribute	**Description**
Name	ISSDT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EXPDATE

Attribute	**Description**
Name	EXPDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACC_CCY

Attribute	**Description**
Name	ACC_CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

AMNT

Attribute	Description
Name	AMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

OS_GUARAMT

Attribute	Description
Name	OS_GUARAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CPTY_NAME

Attribute	Description
Name	CPTY_NAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ADDR

Attribute	Description
Name	ADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

CPTYTYP

Attribute	Description
Name	CPTYTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COUNT_PARTYREF

Attribute	Description
Name	COUNT_PARTYREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENEFNAME

Attribute	Description
Name	BENEFNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

BENADDR

Attribute	Description
Name	BENADDR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

MSGTYPE

Attribute	Description	
Name	MSGTYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PRTY

Attribute	Description	
Name	PRTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Ffts

Attribute	Description

Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String

Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1

Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	**Description**
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	**Description**
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	**Description**
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	**Description**
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description	
Name	ORDINST2	
Datatype	String	
Description	Indicates Ordering Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST3

Attribute	Description	
Name	ORDINST3	
Datatype	String	
Description	Indicates Ordering Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST4

Attribute	Description	
Name	ORDINST4	
Datatype	String	
Description	Indicates Ordering Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST1

Attribute	Description	
Name	ORDCUST1	
Datatype	String	
Description	Indicates Ordering Customer 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2

Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description	
Name	BENINSTCOVR3	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR4

Attribute	Description	
Name	BENINSTCOVR4	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR5

Attribute	Description	
Name	BENINSTCOVR5	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description	
Name	COUNTRPRYBIC	
Datatype	String	
Description	Indicates Counterparty Bank	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYACC

Attribute	Description	
Name	COUNTRPRYACC	
Datatype	String	
Description	Indicates Counterparty Account	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description	
Name	COUNTRPRYNAM	
Datatype	String	
Description	Indicates Counterparty Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

AGID

Attribute	Description	
Name	AGID	
Datatype	String	
Description	Indicates Agreement Identification	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

POSACC

Attribute	Description	
Name	POSACC	
Datatype	String	
Description	Indicates Post Accounting	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5

Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0

Restrictions	Restrictions	Description
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	**Description**
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	**Description**
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1

Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant

Attributes	Attribute	Description
	minOccurs	0

TOP

ULTBANDCD

Attribute	Description	
Name	ULTBANDCD	
Datatype	String	
Description	Indicates Ultimate Bank Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO2

Attribute	Description	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO3

Attribute	Description	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	Attribute: minOccurs — Description: 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String

Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application

Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

TGCCY

Attribute	**Description**
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	**Description**
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Tax Details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SCHEME

Attribute	**Description**
Name	SCHEME
Datatype	String
Description	Indicates Scheme
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Tax-Details

Attribute	**Description**
Name	Tax-Details
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

BASISAMNTAG

Attribute	Description	
Name	BASISAMNTAG	
Datatype	String	
Description	Indicates Basis Component	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPUEVNT

Attribute	Description	
Name	COMPUEVNT	
Datatype	String	
Description	Indicates Event	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

WAIVER

Attribute	Description	
Name	WAIVER	
Datatype	String	
Description	Indicates Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Rule-Details

Attribute	Description
Name	Rule-Details
Datatype	
Description	Includes Rule details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

VALUEDT

Attribute	Description
Name	VALUEDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs; Description: 1

TOP

COMPUTATIONDT

Attribute	Description
Name	COMPUTATIONDT
Datatype	Date
Description	Indicates Transaction Date
Attributes	Attribute: minOccurs; Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	Indicates Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

AMT

Attribute	Description
Name	AMT
Datatype	Number
Description	Indicates Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number

Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.33.4.LI-CreateGuaranteeClaim-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Guarantee-Claim-PK*
      - *CONREFNO*
      - *CLAIM_SEQNO*
    - *Guarantee-Claim-IO*
      - *CONREFNO*
      - *CLAIM_SEQNO*
      - *CLAIMDT*
      - *CLAIMAMT*
      - *REMRKS*
      - *TEMPLATEID*
      - *MAKER*
      - *MAKERSTAMP*
      - *CHECKER*
      - *CHECKERSTAMP*
      - *TXNSTAT*
      - *AUTHSTAT*
      - *LATEVNSEQNO*
      - *LATVERNO*

- *BRANCH_CONT*
- *Advices*
  - *SUPRESS*
  - *PRIORITY*
  - *MEDIUM*
  - *CHGREQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
- *Settlements*
  - *CONREFNO*
  - *LATEVNSEQNO*
  - *Contract-Settlement*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*
    - *CLEARNW*
    - *COVERBY*
    - *RTGSPMNT*
    - *BANKPRIOR*
    - *RTGSNW*
    - *PAYBY*
    - *TRANSTYP*
    - *INSTYP*
    - *INSNO*
    - *CHGDET*
    - *PAYMNTDET1*
    - *PAYMNTDET2*
    - *PAYMNTDET3*
    - *PAYMNTDET4*
    - *SNDTRRCVINFO1*
    - *SNDTRRCVINFO2*
    - *SNDTRRCVINFO3*
    - *SNDTRRCVINFO4*
    - *SNDTRRCVINFO5*
    - *COVREQRD*

RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6

ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *ULTBANDCD*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*

SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
Charges
LATEVNSEQNO
CONREFNO
Charge-Association
WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Taxes
CONREFNO
LATEVNSEQNO
Tax
WAIVER
Tax-Details
Rule-Details
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Guarantee-Claim-PK

Attribute	Description
Name	Guarantee-Claim-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

Guarantee-Claim-IO

Attribute	Description
Name	Guarantee-Claim-IO
Datatype	
Description	

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CLAIM_SEQNO

Attribute	Description
Name	CLAIM_SEQNO
Datatype	Number
Description	

TOP

CLAIMDT

Attribute	Description

Name	CLAIMDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

CLAIMAMT

Attribute	**Description**
Name	CLAIMAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 1

TOP

REMRKS

Attribute	**Description**
Name	REMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

TEMPLATEID

Attribute	**Description**
Name	TEMPLATEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

MAKER

Attribute	**Description**
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

BRANCH_CONT

Attribute	Description
Name	BRANCH_CONT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MEDIUM

Attribute	Description	
Name	MEDIUM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	Description

Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	**Description**
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	**Description**
Name	BANKPRIOR
Datatype	String

Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD

Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	**Description**
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1

Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	**Description**
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	**Description**
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	**Description**
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	**Description**
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	**Description**
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	**Description**
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	**Description**
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

POSACC

Attribute	Description
Name	POSACC

Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	**Description**
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	**Description**
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	**Description**
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Charges

Attribute	Description	
Name	Charges	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LATEVNSEQNO

Attribute	Description	
Name	LATEVNSEQNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

Charge-Association

Attribute	Description	
Name	Charge-Association	
Datatype		
Description	Includes Charge Association details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WAIVER

Attribute	Description

Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String

Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Taxes

Attribute	Description
Name	Taxes
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Tax

Attribute	Description
Name	Tax
Datatype	
Description	Includes Tax details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

Tax-Details

Attribute	Description	
Name	Tax-Details	
Datatype		
Description	Includes Tax details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

Rule-Details

Attribute	Description	
Name	Rule-Details	
Datatype		
Description	Includes Rule details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FCUBS_ERROR_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.CreateLIPayment

Create Islamic LC Payment

2.34.1.LI-CreateLIPayment-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*

- *AMTDUE*
- *PREPAYCOMM*
- *COMPCCY*
- *DUEDATE*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *COMPNT*
  - *CHRGCCY*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *Contract-Settlement*
  - *IBANACNO*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *COMPNT*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *ACCCCY*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*

ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3

ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*

- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing

- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*
- *SNDRCUSTNAME4*
- *RCVRCUSTNAME1*
- *RCVRCUSTNAME2*
- *RCVRCUSTNAME3*
- *RCVRCUSTNAME4*
- *SNDRRCVRPART*
- *ULTBANDCD*
- *ADDLINFO1*
- *ADDLINFO2*
- *ADDLINFO3*
- *ADDLINFO4*
- *NIPPAYER*
- *SUPPID*
- *PAYERID*
- *PMNTTYP*
- *NOOFDEC*
- *ADDID*
- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*

REPRES2

REPRES3

REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails

Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	Attribute	Description
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT

Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 7

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	Description
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	Description
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description

Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

ACCRREQD

Attribute	**Description**	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

DESC

Attribute	**Description**	
Name	DESC	
Datatype	String	
Description	Indicates Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

Charge-Application

Attribute	**Description**	
Name	Charge-Application	
Datatype		
Description	Includes Charge Application details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CREATESN

Attribute	**Description**	
Name	CREATESN	
Datatype	Number	
Description	Indicates Creation ESN	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT

Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

CHRGCCY

Attribute	Description	
Name	CHRGCCY	
Datatype	String	
Description	Indicates Charge Currency	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	**Description**
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST3

Attribute	Description	
Name	BENINST3	
Datatype	String	
Description	Indicates Beneficiary Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	**Description**
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	**Description**
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

PMNTCD

Attribute	Description	
Name	PMNTCD	
Datatype	String	
Description	Indicates Payment Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

ADDINFOSORBNET

Attribute	Description	
Name	ADDINFOSORBNET	
Datatype	String	
Description	Indicates Additional Information	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

TOP

SNDRCUSTNAME1

Attribute	Description	
Name	SNDRCUSTNAME1	
Datatype	String	
Description	Indicates Sender Customer Name 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME2

Attribute	Description	
Name	SNDRCUSTNAME2	
Datatype	String	
Description	Indicates Sender Customer Name 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

Misdetails

Attribute	**Description**	
Name	Misdetails	
Datatype		
Description	This Node indicates the MIS details for the customer account	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CONREFNO

Attribute	**Description**	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATESN

Attribute	**Description**	
Name	LATESN	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MISGRP

Attribute	**Description**	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

RELETED_REFERENCE

Attribute	Description
Name	RELETED_REFERENCE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MISHEAD

Attribute	Description
Name	MISHEAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS7

Attribute	**Description**
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS8

Attribute	**Description**
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TXNMIS9

Attribute	**Description**
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

MISGRPCOMP

Attribute	**Description**
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPTXN

Attribute	Description	
Name	MISGRPTXN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

COMPMIS1

Attribute	Description	
Name	COMPMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COMPMIS10

Attribute	Description	
Name	COMPMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description	
Name	COMPMIS2	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS2

Attribute	**Description**
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS3

Attribute	**Description**
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS4

Attribute	**Description**
Name	FUNDMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS5

Attribute	**Description**
Name	FUNDMIS5
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS6

Attribute	Description	
Name	FUNDMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS7

Attribute	Description	
Name	FUNDMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS8

Attribute	Description	
Name	FUNDMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS9

Attribute	Description	
Name	FUNDMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

MISGRPFUN

Attribute	Description	
Name	MISGRPFUN	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS1

Attribute	Description	
Name	TRANMIS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS2

Attribute	Description	
Name	TRANMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	30

TOP

TRANMIS4

Attribute	Description
Name	TRANMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS5

Attribute	Description
Name	TRANMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS6

Attribute	Description
Name	TRANMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS7

Attribute	Description
Name	TRANMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS8

Attribute	Description
Name	TRANMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS9

Attribute	Description
Name	TRANMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TRANMIS10

Attribute	Description
Name	TRANMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS7

Attribute	**Description**
Name	COMMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS8

Attribute	**Description**
Name	COMMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS9

Attribute	**Description**
Name	COMMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS10

Attribute	**Description**
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS4

Attribute	Description
Name	FUNMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS5

Attribute	Description
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS6

Attribute	Description
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS7

Attribute	Description
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.34.2.LI-CreateLIPayment-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-IO*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *AUTHSTAT*
    - *Liq-Details*
      - *PREPAYCOMM*
      - *DUEDATE*
    - *Charges*
      - *LATEVNSEQNO*
      - *CONREFNO*
      - *Charge-Association*
        - *WAIVER*
        - *DISACCRAPPL*
        - *ACCRREQD*

- *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*
  - *BANKPRIOR*
  - *RTGSNW*
  - *PAYBY*
  - *TRANSTYP*
  - *INSTYP*
  - *INSNO*
  - *CHGDET*
  - *PAYMNTDET1*
  - *PAYMNTDET2*
  - *PAYMNTDET3*
  - *PAYMNTDET4*
  - *SNDTRRCVINFO1*
  - *SNDTRRCVINFO2*
  - *SNDTRRCVINFO3*
  - *SNDTRRCVINFO4*
  - *SNDTRRCVINFO5*

COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW

- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *ULTBANDCD*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*
  - *SNDRRCVRINFO1*
  - *SNDRRCVRINFO2*
  - *SNDRRCVRINFO3*

- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*
- *COMPMIS10*
- *COMPMIS2*
- *COMPMIS3*

COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	nillable	true
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description

Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	**Description**
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONTCCY

Attribute	Description	
Name	CONTCCY	
Datatype	String	
Description	Indicates Contract Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT

Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description	Includes the Settlements Details.	
Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	Description	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	Description	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	Description	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	Attribute	Description
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	Attribute	Description
	minOccurs	0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD4

Attribute	Description	
Name	COSTCD4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description	
Name	COSTCD5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

TXNMIS1

Attribute	Description	
Name	TXNMIS1	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

TXNMIS10

Attribute	Description	
Name	TXNMIS10	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS2

Attribute	Description	
Name	TXNMIS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	Description
Name	COMPMIS6
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description
Name	COMPMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS8

Attribute	Description
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS9

Attribute	Description
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

2.34.3.LI-CreateLIPayment-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Payment-Details-Full*
    - *CONTCCY*
    - *CONREFNO*
    - *CONTAMT*
    - *CUSTNAME*
    - *VALDT*
    - *TOTPAID*
    - *PAYMNTREM*
    - *MAKER*
    - *MAKERSTAMP*
    - *CHECKER*
    - *CHECKERSTAMP*
    - *TXNSTAT*
    - *AUTHSTAT*
    - *Liq-Details*
      - *COMP*
      - *AMTDUE*
      - *PREPAYCOMM*
      - *COMPCCY*

- *DUEDATE*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*
    - *COMPNT*
    - *TGCCY*
    - *TGAMT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *DISACCRAPPL*
    - *WAIVER*
    - *LIQDIND*
  - *Charge-Liquidation*
    - *ESN*
    - *COMPNT*
    - *CHRGCCY*
    - *CHRGAMT*
    - *LIQDSTAT*
- *Settlements*
  - *CONREFNO*
  - *Contract-Settlement*
    - *IBANACNO*
    - *CUSTSPREAD*
    - *SPREADDEFN*
    - *COMPNT*
    - *TAGCCY*
    - *ACCBRN*
    - *ACC*
    - *ACCCCY*
    - *EXRATE*
    - *NETIND*
    - *ERICCY*
    - *ERIAMT*
    - *GENMSG*
    - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2

ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*

REGREP2
REGREP3
ENVCONT1
ENVCONT2
ENVCONT3
ENVCONT4
ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4

RCVRACC

Misdetails

CONREFNO

LATESN

MISGRP

RELACC

RELETED_REFERENCE

MISHEAD

RATEFLG

POOLCD

REFINANCE_RATE

REFRATETYP

PROCALCMTH

REFSPREAD

REFRATECD

COSTCD1

COSTCD2

COSTCD3

COSTCD4

COSTCD5

TXNMIS1

TXNMIS10

TXNMIS2

TXNMIS3

TXNMIS4

TXNMIS5

TXNMIS6

TXNMIS7

TXNMIS8

TXNMIS9

MISGRPCOMP

MISGRPTXN

COMPMIS1

COMPMIS10

COMPMIS2

COMPMIS3

COMPMIS4

COMPMIS5

COMPMIS6

COMPMIS7

COMPMIS8

COMPMIS9

FUNDMIS1

FUNDMIS10

FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
TRANMIS1
TRANMIS2
TRANMIS3
TRANMIS4
TRANMIS5
TRANMIS6
TRANMIS7
TRANMIS8
TRANMIS9
TRANMIS10
COMMIS1
COMMIS2
COMMIS3
COMMIS4
COMMIS5
COMMIS6
COMMIS7
COMMIS8
COMMIS9
COMMIS10
FUNMIS1
FUNMIS2
FUNMIS3
FUNMIS4
FUNMIS5
FUNMIS6
FUNMIS7
FUNMIS8
FUNMIS9
FUNMIS10
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	**Description**
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Payment-Details-Full

Attribute	Description
Name	Payment-Details-Full
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	Attribute: minOccurs — Description: 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	Attribute: minOccurs — Description: 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	The User Id who has created/last modified the record.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP

Datatype	String
Description	Indicates Date and Stamp when the User has created\last modified the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

CHECKER

Attribute	**Description**
Name	CHECKER
Datatype	String
Description	The User Id who has Authorized the creation\modificaiton of the record
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	Indicates Date and Stamp when the User has Authorized the creation\modification of the record.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 7

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	Indicates the Transaction Status O - Open C - Close
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / V,S,A,H,K

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT

Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / U,A

TOP

Liq-Details

Attribute	**Description**
Name	Liq-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMP

Attribute	**Description**
Name	COMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

AMTDUE

Attribute	**Description**
Name	AMTDUE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PREPAYCOMM

Attribute	**Description**
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPCCY

Attribute	Description
Name	COMPCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	Attribute: minOccurs — Description: 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

IBANACNO

Attribute	Description	
Name	IBANACNO	
Datatype	String	
Description	Indicates IBAN Account Number	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

CUSTSPREAD

Attribute	Description	
Name	CUSTSPREAD	
Datatype	Number	
Description	Indicates Customer Spread	
Attributes	Attribute	Description
	minOccurs	0

TOP

SPREADDEFN

Attribute	Description	
Name	SPREADDEFN	
Datatype	String	
Description	Indicates Spread Definition	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

COMPNT

Attribute	Description	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description

Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	**Description**
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	**Description**
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP

Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5

Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2

Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST3

Attribute	Description	
Name	ORDCUST3	
Datatype	String	
Description	Indicates Ordering Customer 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description	
Name	ORDCUST4	
Datatype	String	
Description	Indicates Ordering Customer 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST1

Attribute	Description	
Name	BENINST1	
Datatype	String	
Description	Indicates Beneficiary Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST2

Attribute	Description	
Name	BENINST2	
Datatype	String	
Description	Indicates Beneficiary Institution 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST3

Attribute	**Description**
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST4

Attribute	**Description**
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN1

Attribute	**Description**
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	**Description**
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC

Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYNAM

Attribute	**Description**
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	**Description**
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	**Description**
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	**Description**
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

SNDRTORECV6

Attribute	**Description**	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	**Description**	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	**Description**	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	**Description**	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	**Description**
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2

Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6

Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	**Description**
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	**Description**
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	**Description**
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	**Description**

Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4

Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

ADDLINFO1

Attribute	**Description**	
Name	ADDLINFO1	
Datatype	String	
Description	Indicates Additional Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	**Description**	
Name	ADDLINFO2	
Datatype	String	
Description	Indicates Additional Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO3

Attribute	**Description**	
Name	ADDLINFO3	
Datatype	String	
Description	Indicates Additional Information 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO4

Attribute	**Description**	
Name	ADDLINFO4	
Datatype	String	
Description	Indicates Additional Information 4	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String

Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	**Description**
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	**Description**
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	**Description**
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	**Description**
Name	SNDRRCVRINFO2
Datatype	String

Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	**Description**
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	**Description**
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	**Description**
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	**Description**
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MISGRP

Attribute	Description	
Name	MISGRP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

RELACC

Attribute	Description	
Name	RELACC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description
Name	RATEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,R

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REFINANCE_RATE

Attribute	Description
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATETYP

Attribute	Description
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	Description
Name	PROCALCMTH

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	Description
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REFRATECD

Attribute	Description
Name	REFRATECD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	Description
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	Description
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

COSTCD3

Attribute	Description
Name	COSTCD3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD4

Attribute	Description
Name	COSTCD4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS3

Attribute	Description
Name	TXNMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS4

Attribute	Description
Name	TXNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS5

Attribute	Description
Name	TXNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS6

Attribute	Description
Name	TXNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	Description
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	Description
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

COMPMIS6

Attribute	Description	
Name	COMPMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS7

Attribute	Description	
Name	COMPMIS7	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS8

Attribute	Description	
Name	COMPMIS8	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPMIS9

Attribute	Description	
Name	COMPMIS9	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

FUNDMIS1

Attribute	Description
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS10

Attribute	Description
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	**Description**
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	**Description**
Name	MISGRPFUN
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS1

Attribute	**Description**
Name	TRANMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TRANMIS2

Attribute	**Description**
Name	TRANMIS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS3

Attribute	Description	
Name	TRANMIS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS4

Attribute	Description	
Name	TRANMIS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS5

Attribute	Description	
Name	TRANMIS5	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

TRANMIS6

Attribute	Description	
Name	TRANMIS6	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS7

Attribute	**Description**
Name	TRANMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS8

Attribute	**Description**
Name	TRANMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS9

Attribute	**Description**
Name	TRANMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TRANMIS10

Attribute	**Description**
Name	TRANMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

COMMIS1

Attribute	Description
Name	COMMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS2

Attribute	Description
Name	COMMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS3

Attribute	Description
Name	COMMIS3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS4

Attribute	Description
Name	COMMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS5

Attribute	Description
Name	COMMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS6

Attribute	Description
Name	COMMIS6
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS7

Attribute	Description
Name	COMMIS7
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS8

Attribute	Description
Name	COMMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

COMMIS9

Attribute	Description
Name	COMMIS9

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

COMMIS10

Attribute	Description
Name	COMMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS1

Attribute	Description
Name	FUNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS2

Attribute	Description
Name	FUNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

FUNMIS3

Attribute	Description
Name	FUNMIS3
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS4

Attribute	**Description**
Name	FUNMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS5

Attribute	**Description**
Name	FUNMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS6

Attribute	**Description**
Name	FUNMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

FUNMIS7

Attribute	**Description**
Name	FUNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	30

TOP

FUNMIS8

Attribute	Description
Name	FUNMIS8
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS9

Attribute	Description
Name	FUNMIS9
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

FUNMIS10

Attribute	Description
Name	FUNMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.34.4.LI-CreateLIPayment-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Payment-Details-PK*
      - *CONREFNO*
    - *Payment-Details-IO*
      - *CONTCCY*
      - *CONREFNO*
      - *CONTAMT*
      - *CUSTNAME*
      - *VALDT*
      - *TOTPAID*
      - *PAYMNTREM*
      - *AUTHSTAT*
      - *Liq-Details*
        - *PREPAYCOMM*
        - *DUEDATE*
      - *Charges*
        - *LATEVNSEQNO*
        - *CONREFNO*
        - *Charge-Association*

WAIVER
DISACCRAPPL
ACCRREQD
DESC
Charge-Application
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
LATEVNSEQNO
Contract-Settlement
CUSTSPREAD
SPREADDEFN
TAGCCY
ACCBRN
ACC
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM

- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*
  - *ULTBANDCD*
  - *SUPPID*
  - *PAYERID*
  - *PMNTTYP*
  - *NOOFDEC*
  - *ADDID*

- *SNDRRCVRINFO1*
- *SNDRRCVRINFO2*
- *SNDRRCVRINFO3*
- *SNDRRCVRINFO4*
- *SNDRRCVRINFO5*
- *SNDRRCVRINFO6*
- *DECLARTION*
- *REPRES1*
- *REPRES2*
- *REPRES3*
- *REPRES4*
- *RCVRACC*

Misdetails

- *CONREFNO*
- *LATESN*
- *MISGRP*
- *RELACC*
- *RELETED_REFERENCE*
- *MISHEAD*
- *RATEFLG*
- *POOLCD*
- *REFINANCE_RATE*
- *REFRATETYP*
- *PROCALCMTH*
- *REFSPREAD*
- *REFRATECD*
- *COSTCD1*
- *COSTCD2*
- *COSTCD3*
- *COSTCD4*
- *COSTCD5*
- *TXNMIS1*
- *TXNMIS10*
- *TXNMIS2*
- *TXNMIS3*
- *TXNMIS4*
- *TXNMIS5*
- *TXNMIS6*
- *TXNMIS7*
- *TXNMIS8*
- *TXNMIS9*
- *MISGRPCOMP*
- *MISGRPTXN*
- *COMPMIS1*

COMPMIS10
COMPMIS2
COMPMIS3
COMPMIS4
COMPMIS5
COMPMIS6
COMPMIS7
COMPMIS8
COMPMIS9
FUNDMIS1
FUNDMIS10
FUNDMIS2
FUNDMIS3
FUNDMIS4
FUNDMIS5
FUNDMIS6
FUNDMIS7
FUNDMIS8
FUNDMIS9
MISGRPFUN
Txnmisdetails
Compmisdetails
Fundmisdetails
FCUBS_ERROR_RESP
ERROR
ECODE
EDESC
FCUBS_WARNING_RESP
WARNING
WCODE
WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description

Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Payment-Details-PK

Attribute	Description
Name	Payment-Details-PK
Datatype	
Description	

TOP

CONREFNO

Attribute	Description	
Name	CONREFNO	
Datatype	String	
Description	Indicates the Contract Reference Number.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Payment-Details-IO

Attribute	Description
Name	Payment-Details-IO
Datatype	
Description	

TOP

CONTCCY

Attribute	Description
Name	CONTCCY
Datatype	String
Description	Indicates Contract Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTAMT

Attribute	Description
Name	CONTAMT
Datatype	Number
Description	Contract Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CUSTNAME

Attribute	Description
Name	CUSTNAME
Datatype	String
Description	Indicates Customer Name

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

VALDT

Attribute	Description
Name	VALDT
Datatype	Date
Description	Indicates Value Date
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOTPAID

Attribute	Description
Name	TOTPAID
Datatype	Number
Description	Indicates Total Paid
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PAYMNTREM

Attribute	Description
Name	PAYMNTREM
Datatype	String
Description	Indicates Payment Remarks
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	Specifies whether the record is authorized or not
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / U,A

TOP

Liq-Details

Attribute	Description
Name	Liq-Details
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

PREPAYCOMM

Attribute	Description
Name	PREPAYCOMM
Datatype	Number
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

DUEDATE

Attribute	Description
Name	DUEDATE
Datatype	Date
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	Includes the Charges Details.
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String

Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number

Attributes	Attribute	Description
	minOccurs	0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	Includes the Settlements Details.
Attributes	Attribute: minOccurs — Description: 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO

Datatype	Number
Description	Indicates Latest Event Sequence Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

TAGCCY

Attribute	**Description**
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY

Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	**Description**	
Name	ULTBEN3	
Datatype	String	
Description	Indicates Ultimate Beneficiary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN4

Attribute	**Description**	
Name	ULTBEN4	
Datatype	String	
Description	Indicates Ultimate Beneficiary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR1

Attribute	**Description**	
Name	BENINSTCOVR1	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	**Description**	
Name	BENINSTCOVR2	
Datatype	String	
Description	Indicates Beneficiary Institution For Cover 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	**Description**
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR4

Attribute	**Description**
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR5

Attribute	**Description**
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COUNTRPRYBIC

Attribute	**Description**
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	**Description**	
Name	ULTBEN5	
Datatype	String	
Description	Indicates Ultimate Beneficiary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Settlement-Detail

Attribute	**Description**	
Name	Settlement-Detail	
Datatype		
Description	Includes Settlement details	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

INSTRCD1

Attribute	**Description**	
Name	INSTRCD1	
Datatype	String	
Description	Indicates Instruction Code 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD2

Attribute	**Description**	
Name	INSTRCD2	
Datatype	String	
Description	Indicates Instruction Code 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

Misdetails

Attribute	Description
Name	Misdetails
Datatype	
Description	This Node indicates the MIS details for the customer account
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates the Contract Reference Number.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATESN

Attribute	Description
Name	LATESN
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

RELACC

Attribute	Description
Name	RELACC
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

RELETED_REFERENCE

Attribute	Description	
Name	RELETED_REFERENCE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

MISHEAD

Attribute	Description	
Name	MISHEAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

RATEFLG

Attribute	Description	
Name	RATEFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,R

TOP

POOLCD

Attribute	Description	
Name	POOLCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REFINANCE_RATE

Attribute	**Description**
Name	REFINANCE_RATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATETYP

Attribute	**Description**
Name	REFRATETYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,X,F,P

TOP

PROCALCMTH

Attribute	**Description**
Name	PROCALCMTH
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,1,2,3,4,5,6,7,8,9

TOP

REFSPREAD

Attribute	**Description**
Name	REFSPREAD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

REFRATECD

Attribute	**Description**
Name	REFRATECD

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COSTCD1

Attribute	**Description**
Name	COSTCD1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD2

Attribute	**Description**
Name	COSTCD2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD3

Attribute	**Description**
Name	COSTCD3
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

COSTCD4

Attribute	**Description**
Name	COSTCD4
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

COSTCD5

Attribute	Description
Name	COSTCD5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

TXNMIS1

Attribute	Description
Name	TXNMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS10

Attribute	Description
Name	TXNMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS2

Attribute	Description
Name	TXNMIS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS3

Attribute	Description	
Name	TXNMIS3	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS4

Attribute	Description	
Name	TXNMIS4	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS5

Attribute	Description	
Name	TXNMIS5	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS6

Attribute	Description	
Name	TXNMIS6	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

TXNMIS7

Attribute	Description
Name	TXNMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS8

Attribute	Description
Name	TXNMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TXNMIS9

Attribute	Description
Name	TXNMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPCOMP

Attribute	Description
Name	MISGRPCOMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPTXN

Attribute	Description
Name	MISGRPTXN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

COMPMIS1

Attribute	Description
Name	COMPMIS1
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

COMPMIS10

Attribute	Description
Name	COMPMIS10
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS2

Attribute	Description
Name	COMPMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPMIS3

Attribute	Description
Name	COMPMIS3

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS4

Attribute	**Description**
Name	COMPMIS4
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS5

Attribute	**Description**
Name	COMPMIS5
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS6

Attribute	**Description**
Name	COMPMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

COMPMIS7

Attribute	**Description**
Name	COMPMIS7
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS8

Attribute	**Description**
Name	COMPMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPMIS9

Attribute	**Description**
Name	COMPMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS1

Attribute	**Description**
Name	FUNDMIS1
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

FUNDMIS10

Attribute	**Description**
Name	FUNDMIS10
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	10

TOP

FUNDMIS2

Attribute	Description
Name	FUNDMIS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS3

Attribute	Description
Name	FUNDMIS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS4

Attribute	Description
Name	FUNDMIS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS5

Attribute	Description
Name	FUNDMIS5
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

FUNDMIS6

Attribute	Description
Name	FUNDMIS6
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS7

Attribute	Description
Name	FUNDMIS7
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS8

Attribute	Description
Name	FUNDMIS8
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FUNDMIS9

Attribute	Description
Name	FUNDMIS9
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

MISGRPFUN

Attribute	Description
Name	MISGRPFUN
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 30

TOP

Txnmisdetails

Attribute	Description
Name	Txnmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

Compmisdetails

Attribute	Description
Name	Compmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

Fundmisdetails

Attribute	Description
Name	Fundmisdetails
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded Attribute: minOccurs; Description: 0

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	Attribute: maxOccurs; Description: unbounded

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.CreateLITransfer

Creation of Islamic Letters of Credit Transfer

2.35.1.LI-CreateLITransfer-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*

- *GOODSCD*
- *GOODSDESC*
- *PREADVDESC*
- *CONREFSHIP*
- *SLNOSHIP*
- *FROM*
- *TO*
- *PARTIALSHIP*
- *TRANSSHIP*
- *SHIPDETAILS*
- *SHIPMARKS*
- *SHIPPERIOD*
- *PORTDISCHG*
- *PORTLOAD*
- *CONREFLOG*
- *MAKER*
- *MAKERSTAMP*
- *CHECKER*
- *CHECKERSTAMP*
- *TXNSTAT*
- *AUTHSTAT*
- *POSTOL*
- *NEGTOL*
- *Parties-Details*
  - *CONREFPARTY*
  - *SLNOPARTY*
  - *PARTYTP*
  - *PARTYID*
  - *PARTYNAME*
  - *ADDRS1*
  - *ADDRS2*
  - *ADDRS3*
  - *ADDRS4*
  - *LANG*
  - *CNTY*
  - *PARTYDESCM*
- *Document-Details*
  - *CONREFDOC*
  - *SLNODOC*
  - *DOCCD*
  - *DOCTP*
  - *DOCDESCR*
  - *ORIGINALRQD*
  - *NOCOPIES*

- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*
  - *SLNOCLAUSE*
  - *CLAUSECOD*
  - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *LIMITAMT*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Limits1*
- *Advices*
  - *MSG_TYPE*
  - *SUPRESS*
  - *PRIORITY*
  - *MODULE*
  - *PRTY*
  - *MEDIUM*
  - *PRTYID*
  - *PRTYNAME*
  - *CHG_REQD*
  - *Ffts*
    - *FFTINSCD*
    - *FFTINSDESC*
    - *SINGLEFFT*
- *Charges*
  - *CONREFNO*
  - *Charge-Association*
    - *COMPNT*
    - *CREATESN*
    - *RULE*
    - *WAIVER*
    - *DISACCRAPPL*
    - *ACCRREQD*
    - *DESC*
  - *Charge-Application*
    - *CREATESN*

COMPNT
TGCCY
TGAMT
CHRGCCY
CHRGAMT
DISACCRAPPL
WAIVER
LIQDIND
Charge-Liquidation
ESN
COMPNT
CHRGCCY
CHRGAMT
LIQDSTAT
Settlements
CONREFNO
Contract-Settlement
IBANACNO
CUSTSPREAD
SPREADDEFN
COMPNT
TAGCCY
ACCBRN
ACC
ACCCCY
EXRATE
NETIND
ERICCY
ERIAMT
GENMSG
RATECD
CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3

PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3

- *BENINSTCOVR4*
- *BENINSTCOVR5*
- *COUNTRPRYBIC*
- *COUNTRPRYACC*
- *COUNTRPRYNAM*
- *AGID*
- *POSACC*
- *COUNTRCLGNW*
- *SNDRTORECV6*
- *ACCWITHINST5*
- *BENINST5*
- *INTERMEDIARY5*
- *REIMINST5*
- *RCORRS15*
- *ORDCUST5*
- *ORDINST5*
- *ULTBEN5*
- *DRCRIND*
- *Settlement-Detail*
  - *INSTRCD1*
  - *INSTRCD2*
  - *INSTRCD3*
  - *INSTRCD4*
  - *ITIMEIND1*
  - *ITIMEIND2*
  - *ITIMEIND3*
  - *INSTRCD5*
  - *BANKOPERCD*
  - *INSTRCD6*
  - *TRNSTYPCD*
  - *REGREP1*
  - *REGREP2*
  - *REGREP3*
  - *ENVCONT1*
  - *ENVCONT2*
  - *ENVCONT3*
  - *ENVCONT4*
  - *ENVCONT5*
- *Lcl_Clearing*
  - *FREETXT1*
  - *FREETXT2*
  - *FREETXT3*
  - *PMNTCD*
  - *ADDINFOSORBNET*

SNDRCUSTNAME1
SNDRCUSTNAME2
SNDRCUSTNAME3
SNDRCUSTNAME4
RCVRCUSTNAME1
RCVRCUSTNAME2
RCVRCUSTNAME3
RCVRCUSTNAME4
SNDRRCVRPART
ULTBANDCD
ADDLINFO1
ADDLINFO2
ADDLINFO3
ADDLINFO4
NIPPAYER
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description

Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	**Description**
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	**Description**
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	**Description**
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	**Description**
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 128 Restrictions: pattern — Description: [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>minOccurs</td><td>1</td></tr></table>

Restrictions	Restrictions	Description
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CURAVL

Attribute	Description
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description	
Name	SHIPDETAILS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description	
Name	SHIPMARKS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	Description	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	Description	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTP

Attribute	Description

Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	**Description**
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	**Description**
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	**Description**
Name	ADDRS2
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS3

Attribute	Description	
Name	ADDRS3	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ADDRS4

Attribute	Description	
Name	ADDRS4	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

LANG

Attribute	Description	
Name	LANG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

CNTY

Attribute	Description	
Name	CNTY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYDESCM

Attribute	Description
Name	PARTYDESCM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNODOC

Attribute	Description
Name	SLNODOC
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLAUSECOD

Attribute	Description

Name	CLAUSECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CLAUSDESC

Attribute	**Description**
Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

Transfer-Limits

Attribute	**Description**
Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LIMITAMT

Attribute	**Description**
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description	
Name	MSG_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	60

TOP

SUPRESS

Attribute	Description	
Name	SUPRESS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRIORITY

Attribute	Description	
Name	PRIORITY	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

MODULE

Attribute	Description

Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

PRTY

Attribute	**Description**
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 64

TOP

MEDIUM

Attribute	**Description**
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	**Description**
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	**Description**
Name	PRTYNAME
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 48

TOP

FFTINSDESC

Attribute	Description
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	Description
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	Description
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String

Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CREATESN

Attribute	**Description**
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

RULE

Attribute	**Description**
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	Attribute: minOccurs; Description: 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs; Description: 1
Restrictions	Restrictions: maxLength; Description: 10

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs; Description: 0

TOP

LIQDSTAT

Attribute	Description

Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

IBANACNO

Attribute	**Description**
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN

Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCCCY

Attribute	**Description**
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	**Description**
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description

Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	**Description**
Name	COVREQRD
Datatype	String

Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	**Description**
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	**Description**
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	**Description**
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST2

Attribute	**Description**
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST3

Attribute	Description	
Name	REIMINST3	
Datatype	String	
Description	Indicates Reimburse Institution 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST4

Attribute	Description	
Name	REIMINST4	
Datatype	String	
Description	Indicates Reimburse Institution 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS1

Attribute	Description	
Name	RCVRCORRS1	
Datatype	String	
Description	Indicates Receiver Correspondent 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RCVRCORRS2

Attribute	Description	
Name	RCVRCORRS2	
Datatype	String	
Description	Indicates Receiver Correspondent 2	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS3

Attribute	Description	
Name	RCVRCORRS3	
Datatype	String	
Description	Indicates Receiver Correspondent 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

RCVRCORRS4

Attribute	Description	
Name	RCVRCORRS4	
Datatype	String	
Description	Indicates Receiver Correspondent 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY1

Attribute	Description	
Name	INTERMEDIARY1	
Datatype	String	
Description	Indicates Intermediary 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3

Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM

Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	**Description**
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	**Description**
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	**Description**
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	**Description**
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3

Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD

Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT5

Attribute	Description

Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1000

TOP

Lcl_Clearing

Attribute	**Description**
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FREETXT1

Attribute	**Description**
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT2

Attribute	**Description**
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

FREETXT3

Attribute	**Description**
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

PMNTCD

Attribute	**Description**
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

ADDINFOSORBNET

Attribute	**Description**
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	**Description**
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	**Description**
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2
Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number

Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1

Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	34

TOP

TXNUDFDETAILS

Attribute	Description	
Name	TXNUDFDETAILS	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FLDNAME

Attribute	Description	
Name	FLDNAME	
Datatype	String	
Description	Indicates Field Name	
Restrictions	**Restrictions**	**Description**
	maxLength	105
	minLength	1

TOP

FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description	Indicates Field Value	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255
	minLength	0

TOP

2.35.2.LI-CreateLITransfer-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-IO*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TRANSAMT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*
    - *CONREFSHIP*
    - *FROM*
    - *TO*
    - *PARTIALSHIP*

- *TRANSSHIP*
- *SHIPDETAILS*
- *SHIPMARKS*
- *SHIPPERIOD*
- *PORTDISCHG*
- *PORTLOAD*
- *CONREFLOG*
- *TXNSTAT*
- *AUTHSTAT*
- *POSTOL*
- *NEGTOL*
- *Parties-Details*
  - *CONREFPARTY*
  - *SLNOPARTY*
  - *PARTYTP*
  - *PARTYID*
  - *PARTYNAME*
  - *ADDRS1*
  - *ADDRS2*
  - *LANG*
  - *CNTY*
- *Document-Details*
  - *CONREFDOC*
  - *DOCCD*
  - *DOCTP*
  - *DOCDESCR*
  - *ORIGINALRQD*
  - *NOCOPIES*
  - *NOORIGINAL*
  - *Clause-Deatils*
    - *CONREFCLAUSE*
    - *CLAUSECOD*
    - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*
  - *LIABILITY_NUMBER*
  - *SLNO*
- *Advices*

- *MSG_TYPE*
- *SUPRESS*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*
  - *CLEARNW*
  - *COVERBY*
  - *RTGSPMNT*

BANKPRIOR

RTGSNW

PAYBY

TRANSTYP

INSTYP

INSNO

CHGDET

PAYMNTDET1

PAYMNTDET2

PAYMNTDET3

PAYMNTDET4

SNDTRRCVINFO1

SNDTRRCVINFO2

SNDTRRCVINFO3

SNDTRRCVINFO4

SNDTRRCVINFO5

COVREQRD

RECVCVR

RECEIVER

REIMINST1

REIMINST4

RCVRCORRS1

RCVRCORRS2

RCVRCORRS3

RCVRCORRS4

INTERMEDIARY1

INTERMEDIARY2

INTERMEDIARY3

INTERMEDIARY4

ACCWITHINST1

ACCWITHINST2

ACCWITHINST3

ACCWITHINST4

ORDINST1

ORDINST2

ORDINST3

ORDINST4

ORDCUST1

ORDCUST2

ORDCUST3

ORDCUST4

BENINST1

BENINST2

BENINST3

BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*

ENVCONT5
Lcl_Clearing
FREETXT1
FREETXT2
FREETXT3
PMNTCD
ADDINFOSORBNET
ULTBANDCD
SUPPID
PAYERID
PMNTTYP
NOOFDEC
ADDID
SNDRRCVRINFO1
SNDRRCVRINFO2
SNDRRCVRINFO3
SNDRRCVRINFO4
SNDRRCVRINFO5
SNDRRCVRINFO6
DECLARTION
REPRES1
REPRES2
REPRES3
REPRES4
RCVRACC
TXNUDFDETAILS
FLDNAME
FLDVAL

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	

Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	Attribute: nillable — Description: true
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: pattern — Description: [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	**Description**
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description	
Name	FRMREF	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 30

TOP

TOLCUSERREF

Attribute	**Description**
Name	TOLCUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONREFGOOD

Attribute	**Description**
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOGOOD

Attribute	**Description**
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FROM

Attribute	Description
Name	FROM

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 65

TOP

CONREFLOG

Attribute	**Description**
Name	CONREFLOG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

POSTOL

Attribute	**Description**
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

PARTYID

Attribute	Description	
Name	PARTYID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

PARTYNAME

Attribute	Description	
Name	PARTYNAME	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	150

TOP

ADDRS1

Attribute	Description	
Name	ADDRS1	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ADDRS2

Attribute	Description	
Name	ADDRS2	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DOCCD

Attribute	Description

Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	**Description**
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description
Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description	
Name	SLNO	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Advices

Attribute	Description	
Name	Advices	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

MSG_TYPE

Attribute	Description	
Name	MSG_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 600

TOP

Ffts

Attribute	Description

Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	**Description**
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 48

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	Description
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL

Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	**Description**
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	**Description**
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount

Attributes	Attribute	Description
	minOccurs	0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

Charge-Liquidation

Attribute	Description
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

ESN

Attribute	Description	
Name	ESN	
Datatype	Number	
Description	Indicates Event Sequence Number	
Attributes	Attribute	Description
	minOccurs	0

TOP

CHRGAMT

Attribute	Description	
Name	CHRGAMT	
Datatype	Number	
Description	Indicates Charge Amount	
Attributes	Attribute	Description
	minOccurs	0

TOP

LIQDSTAT

Attribute	Description	
Name	LIQDSTAT	
Datatype	String	
Description	Indicates Liquidated	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

TOP

Settlements

Attribute	Description	
Name	Settlements	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String

Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CUSTSPREAD

Attribute	**Description**
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SPREADDEFN

Attribute	**Description**
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	Attribute: minOccurs — Description: 0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String

Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String

Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	**Description**
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	**Description**
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	**Description**
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**	
Name	INSTYP	
Datatype	String	
Description	Indicates Instrument Type	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

INSNO

Attribute	**Description**	
Name	INSNO	
Datatype	String	
Description	Indicates Instrument Number	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

CHGDET

Attribute	**Description**	
Name	CHGDET	
Datatype	String	
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	R,B,O

TOP

PAYMNTDET1

Attribute	**Description**
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description

Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2
Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1

Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5
Datatype	String
Description	Indicates Intermediary 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5

Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	Attribute: minOccurs; Description: 0
Restrictions	Restrictions: maxLength; Description: 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT4

Attribute	Description	
Name	ENVCONT4	
Datatype	String	
Description	Indicates Envelope Contents 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

ENVCONT5

Attribute	Description	
Name	ENVCONT5	
Datatype	String	
Description	Indicates Envelope Contents 5	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1000

TOP

Lcl_Clearing

Attribute	Description	
Name	Lcl_Clearing	
Datatype		
Description	Includes Local clearing details	
Attributes	Attribute	Description
	minOccurs	0

TOP

FREETXT1

Attribute	Description	
Name	FREETXT1	
Datatype	String	
Description	Indicates Free Text 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD

Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3

Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration

Attributes	Attribute	Description
	minOccurs	0

TOP

REPRES1

Attribute	Description	
Name	REPRES1	
Datatype	String	
Description	Indicates Repair Reason 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES2

Attribute	Description	
Name	REPRES2	
Datatype	String	
Description	Indicates Repair Reason 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES3

Attribute	Description	
Name	REPRES3	
Datatype	String	
Description	Indicates Repair Reason 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

REPRES4

Attribute	Description	
Name	REPRES4	
Datatype	String	
Description	Indicates Repair Reason 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

2.35.3.LI-CreateLITransfer-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Transfer-Full*
    - *FRMREF*
    - *LATEVNSEQNO*
    - *LATVERNO*
    - *TOREF*
    - *SLNO*
    - *TRANSAMT*
    - *TRANSDT*
    - *NEWEXPDT*
    - *NEWLATESTSHIPDT*
    - *PERDPRESENTATION*
    - *TOLCUSERREF*
    - *CONTREFNO*
    - *CURAVL*
    - *CONREFGOOD*
    - *SLNOGOOD*
    - *GOODSCD*
    - *GOODSDESC*
    - *PREADVDESC*

CONREFSHIP

SLNOSHIP

FROM

TO

PARTIALSHIP

TRANSSHIP

SHIPDETAILS

SHIPMARKS

SHIPPERIOD

PORTDISCHG

PORTLOAD

CONREFLOG

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

TXNSTAT

AUTHSTAT

POSTOL

NEGTOL

Parties-Details

- *CONREFPARTY*
- *SLNOPARTY*
- *PARTYTP*
- *PARTYID*
- *PARTYNAME*
- *ADDRS1*
- *ADDRS2*
- *ADDRS3*
- *ADDRS4*
- *LANG*
- *CNTY*
- *PARTYDESCM*

Document-Details

- *CONREFDOC*
- *SLNODOC*
- *DOCCD*
- *DOCTP*
- *DOCDESCR*
- *ORIGINALRQD*
- *NOCOPIES*
- *NOORIGINAL*
- *Clause-Deatils*
  - *CONREFCLAUSE*

- *SLNOCLAUSE*
- *CLAUSECOD*
- *CLAUSDESC*

Transfer-Limits

- *PARTYTYP*
- *LIMITAMT*
- *JVPARENT*
- *AMOUNTTAG*
- *CUSTNO*
- *LINKAGE_TYPE*
- *LINKAGEPERC*
- *LINKEDREFNO*
- *LIABILITY_NUMBER*
- *SLNO*

Limits1

Advices

- *MSG_TYPE*
- *SUPRESS*
- *PRIORITY*
- *MODULE*
- *PRTY*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *CHG_REQD*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *CONREFNO*
- *Charge-Association*
  - *COMPNT*
  - *CREATESN*
  - *RULE*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CREATESN*
  - *COMPNT*
  - *TGCCY*
  - *TGAMT*

- *CHRGCCY*
- *CHRGAMT*
- *DISACCRAPPL*
- *WAIVER*
- *LIQDIND*

Charge-Liquidation

- *ESN*
- *COMPNT*
- *CHRGCCY*
- *CHRGAMT*
- *LIQDSTAT*

Settlements

CONREFNO

Contract-Settlement

- *IBANACNO*
- *CUSTSPREAD*
- *SPREADDEFN*
- *COMPNT*
- *TAGCCY*
- *ACCBRN*
- *ACC*
- *ACCCCY*
- *EXRATE*
- *NETIND*
- *ERICCY*
- *ERIAMT*
- *GENMSG*
- *RATECD*
- *CLEARNW*
- *COVERBY*
- *RTGSPMNT*
- *BANKPRIOR*
- *RTGSNW*
- *PAYBY*
- *TRANSTYP*
- *INSTYP*
- *INSNO*
- *CHGDET*
- *PAYMNTDET1*
- *PAYMNTDET2*
- *PAYMNTDET3*
- *PAYMNTDET4*
- *SNDTRRCVINFO1*
- *SNDTRRCVINFO2*

SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST2
REIMINST3
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4
BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC

COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
DRCRIND
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*
- *ENVCONT2*
- *ENVCONT3*
- *ENVCONT4*
- *ENVCONT5*

Lcl_Clearing
- *FREETXT1*
- *FREETXT2*
- *FREETXT3*
- *PMNTCD*
- *ADDINFOSORBNET*
- *SNDRCUSTNAME1*
- *SNDRCUSTNAME2*
- *SNDRCUSTNAME3*

SNDRCUSTNAME4

RCVRCUSTNAME1

RCVRCUSTNAME2

RCVRCUSTNAME3

RCVRCUSTNAME4

SNDRRCVRPART

ULTBANDCD

ADDLINFO1

ADDLINFO2

ADDLINFO3

ADDLINFO4

NIPPAYER

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String

Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8 pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 128 pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Transfer-Full

Attribute	Description
Name	Transfer-Full
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOREF

Attribute	Description
Name	TOREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSDT

Attribute	Description
Name	TRANSDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CONTREFNO

Attribute	**Description**
Name	CONTREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CURAVL

Attribute	**Description**
Name	CURAVL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFGOOD

Attribute	**Description**
Name	CONREFGOOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOGOOD

Attribute	**Description**
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOSHIP

Attribute	Description
Name	SLNOSHIP
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

TO

Attribute	Description
Name	TO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	Description
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	Description
Name	TRANSSHIP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

SHIPDETAILS

Attribute	Description
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	Description
Name	SHIPMARKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPPERIOD

Attribute	Description
Name	SHIPPERIOD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 390

TOP

PORTDISCHG

Attribute	Description
Name	PORTDISCHG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	65

TOP

PORTLOAD

Attribute	Description
Name	PORTLOAD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

CONREFLOG

Attribute	Description
Name	CONREFLOG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CONREFPARTY

Attribute	Description
Name	CONREFPARTY
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 16

TOP

SLNOPARTY

Attribute	Description
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

PARTYTP

Attribute	Description
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYID

Attribute	Description
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS3

Attribute	Description
Name	ADDRS3
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ADDRS4

Attribute	Description
Name	ADDRS4
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

CNTY

Attribute	Description
Name	CNTY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

PARTYDESCM

Attribute	**Description**
Name	PARTYDESCM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Document-Details

Attribute	**Description**
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	**Description**
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNODOC

Attribute	**Description**
Name	SLNODOC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	Description
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6500

TOP

ORIGINALRQD

Attribute	Description
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOCOPIES

Attribute	Description
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NOORIGINAL

Attribute	Description
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SLNOCLAUSE

Attribute	Description
Name	SLNOCLAUSE
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

Transfer-Limits

Attribute	Description
Name	Transfer-Limits
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

PARTYTYP

Attribute	Description
Name	PARTYTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

LIMITAMT

Attribute	Description
Name	LIMITAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

JVPARENT

Attribute	Description
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	Description
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	Description
Name	CUSTNO
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

LINKAGE_TYPE

Attribute	Description

Name	LINKAGE_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F,P,C

TOP

LINKAGEPERC

Attribute	Description
Name	LINKAGEPERC
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LINKEDREFNO

Attribute	Description
Name	LINKEDREFNO
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

LIABILITY_NUMBER

Attribute	Description
Name	LIABILITY_NUMBER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Limits1

Attribute	Description
Name	Limits1
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

PRIORITY

Attribute	Description
Name	PRIORITY
Datatype	Number

Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MODULE

Attribute	Description
Name	MODULE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

PRTY

Attribute	Description
Name	PRTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 64

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 600

TOP

CHG_REQD

Attribute	Description
Name	CHG_REQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 48

TOP

FFTINSDESC

Attribute	Description

Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

RULE

Attribute	Description
Name	RULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	Description
Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CREATESN

Attribute	Description
Name	CREATESN
Datatype	Number
Description	Indicates Creation ESN
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TGCCY

Attribute	Description
Name	TGCCY
Datatype	String
Description	Indicates Tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

TGAMT

Attribute	Description
Name	TGAMT
Datatype	Number
Description	Indicates Tag Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CHRGCCY

Attribute	Description
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	Attribute: minOccurs — Description: 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

WAIVER

Attribute	Description
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

LIQDIND

Attribute	Description
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

COMPNT

Attribute	**Description**
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CHRGCCY

Attribute	**Description**
Name	CHRGCCY
Datatype	String
Description	Indicates Charge Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CHRGAMT

Attribute	**Description**

Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIQDSTAT

Attribute	**Description**
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

Settlements

Attribute	**Description**
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Contract-Settlement

Attribute	**Description**
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

IBANACNO

Attribute	Description
Name	IBANACNO
Datatype	String
Description	Indicates IBAN Account Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

TAGCCY

Attribute	Description
Name	TAGCCY

Datatype	String
Description	Indicates tag Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACCBRN

Attribute	Description
Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ACC

Attribute	Description
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCCCY

Attribute	Description
Name	ACCCCY
Datatype	String
Description	Indicates Account Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

EXRATE

Attribute	Description
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate

Attributes	Attribute	Description
	minOccurs	0

TOP

NETIND

Attribute	Description
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ERICCY

Attribute	Description
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,H,U,N

TOP

RTGSNW

Attribute	Description
Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String

Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	**Description**
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	**Description**
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CHGDET

Attribute	**Description**
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description

Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information_1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	**Description**
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information_2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	**Description**
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information_3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO4

Attribute	**Description**
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information_4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO5

Attribute	**Description**
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information_5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

REIMINST2

Attribute	Description
Name	REIMINST2
Datatype	String
Description	Indicates Reimburse Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST3

Attribute	Description
Name	REIMINST3
Datatype	String
Description	Indicates Reimburse Institution 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1
Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

INTERMEDIARY2

Attribute	Description
Name	INTERMEDIARY2
Datatype	String
Description	Indicates Intermediary 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY3

Attribute	Description
Name	INTERMEDIARY3
Datatype	String
Description	Indicates Intermediary 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY4

Attribute	Description
Name	INTERMEDIARY4
Datatype	String
Description	Indicates Intermediary 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST1

Attribute	Description
Name	ACCWITHINST1
Datatype	String
Description	Indicates Account with Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST2

Attribute	Description
Name	ACCWITHINST2

Datatype	String
Description	Indicates Account with Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST3

Attribute	Description
Name	ACCWITHINST3
Datatype	String
Description	Indicates Account with Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ACCWITHINST4

Attribute	Description
Name	ACCWITHINST4
Datatype	String
Description	Indicates Account with Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST1

Attribute	Description
Name	ORDINST1
Datatype	String
Description	Indicates Ordering Institution 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST2

Attribute	Description
Name	BENINST2
Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3

Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

SNDRTORECV6

Attribute	Description	
Name	SNDRTORECV6	
Datatype	String	
Description	Indicates Sender to Receiver Information 6	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST5

Attribute	Description	
Name	ACCWITHINST5	
Datatype	String	
Description	Indicates Account with Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

BENINST5

Attribute	Description	
Name	BENINST5	
Datatype	String	
Description	Indicates Beneficiary Institution 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY5

Attribute	Description	
Name	INTERMEDIARY5	
Datatype	String	
Description	Indicates Intermediary 5	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

DRCRIND

Attribute	Description
Name	DRCRIND
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / R,P

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2

Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD3

Attribute	**Description**
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

INSTRCD4

Attribute	**Description**
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND1

Attribute	**Description**
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

ITIMEIND2

Attribute	**Description**
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

ITIMEIND3

Attribute	**Description**	
Name	ITIMEIND3	
Datatype	String	
Description	Indicates Time Indicator 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

INSTRCD5

Attribute	**Description**	
Name	INSTRCD5	
Datatype	String	
Description	Indicates Time Indicator 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

BANKOPERCD

Attribute	**Description**	
Name	BANKOPERCD	
Datatype	String	
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	**Description**
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String

Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3
Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

SNDRCUSTNAME1

Attribute	Description
Name	SNDRCUSTNAME1
Datatype	String
Description	Indicates Sender Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME2

Attribute	Description
Name	SNDRCUSTNAME2
Datatype	String
Description	Indicates Sender Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME3

Attribute	Description
Name	SNDRCUSTNAME3
Datatype	String
Description	Indicates Sender Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRCUSTNAME4

Attribute	Description
Name	SNDRCUSTNAME4
Datatype	String
Description	Indicates Sender Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME1

Attribute	Description
Name	RCVRCUSTNAME1
Datatype	String
Description	Indicates Receiver Customer Name 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME2

Attribute	Description
Name	RCVRCUSTNAME2

Datatype	String
Description	Indicates Receiver Customer Name 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME3

Attribute	Description
Name	RCVRCUSTNAME3
Datatype	String
Description	Indicates Receiver Customer Name 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RCVRCUSTNAME4

Attribute	Description
Name	RCVRCUSTNAME4
Datatype	String
Description	Indicates Receiver Customer Name 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRPART

Attribute	Description
Name	SNDRRCVRPART
Datatype	Number
Description	Indicates Sender Receiver Participant
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	20

TOP

ADDLINFO1

Attribute	Description
Name	ADDLINFO1
Datatype	String
Description	Indicates Additional Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO2

Attribute	Description
Name	ADDLINFO2
Datatype	String
Description	Indicates Additional Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO3

Attribute	Description
Name	ADDLINFO3
Datatype	String
Description	Indicates Additional Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ADDLINFO4

Attribute	Description
Name	ADDLINFO4
Datatype	String
Description	Indicates Additional Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

NIPPAYER

Attribute	Description
Name	NIPPAYER
Datatype	Number
Description	Indicates Nip Payer
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String
Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description	
Name	NOOFDEC	
Datatype	Number	
Description	Indicates Number of Declaration	
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

ADDID

Attribute	Description	
Name	ADDID	
Datatype	String	
Description	Indicates Additional Identifier	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	32

TOP

SNDRRCVRINFO1

Attribute	Description	
Name	SNDRRCVRINFO1	
Datatype	String	
Description	Indicates Sender Receiver Information 1	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO2

Attribute	Description	
Name	SNDRRCVRINFO2	
Datatype	String	
Description	Indicates Sender Receiver Information 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4
Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description**: maxLength / 105; minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255; minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description

Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.35.4.LI-CreateLITransfer-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Transfer-PK*
      - *FRMREF*
    - *Transfer-IO*
      - *FRMREF*
      - *LATEVNSEQNO*
      - *LATVERNO*
      - *TRANSAMT*
      - *NEWEXPDT*
      - *NEWLATESTSHIPDT*
      - *PERDPRESENTATION*
      - *TOLCUSERREF*
      - *CONTREFNO*
      - *CONREFGOOD*
      - *SLNOGOOD*
      - *GOODSCD*
      - *GOODSDESC*
      - *PREADVDESC*
      - *CONREFSHIP*

- *FROM*
- *TO*
- *PARTIALSHIP*
- *TRANSSHIP*
- *SHIPDETAILS*
- *SHIPMARKS*
- *SHIPPERIOD*
- *PORTDISCHG*
- *PORTLOAD*
- *CONREFLOG*
- *TXNSTAT*
- *AUTHSTAT*
- *POSTOL*
- *NEGTOL*
- *Parties-Details*
  - *CONREFPARTY*
  - *SLNOPARTY*
  - *PARTYTP*
  - *PARTYID*
  - *PARTYNAME*
  - *ADDRS1*
  - *ADDRS2*
  - *LANG*
  - *CNTY*
- *Document-Details*
  - *CONREFDOC*
  - *DOCCD*
  - *DOCTP*
  - *DOCDESCR*
  - *ORIGINALRQD*
  - *NOCOPIES*
  - *NOORIGINAL*
  - *Clause-Deatils*
    - *CONREFCLAUSE*
    - *CLAUSECOD*
    - *CLAUSDESC*
- *Transfer-Limits*
  - *PARTYTYP*
  - *JVPARENT*
  - *AMOUNTTAG*
  - *CUSTNO*
  - *LINKAGE_TYPE*
  - *LINKAGEPERC*
  - *LINKEDREFNO*

- *LIABILITY_NUMBER*
- *SLNO*

Advices

- *MSG_TYPE*
- *SUPRESS*
- *MEDIUM*
- *PRTYID*
- *PRTYNAME*
- *Ffts*
  - *FFTINSCD*
  - *FFTINSDESC*
  - *SINGLEFFT*

Charges

- *LATEVNSEQNO*
- *CONREFNO*
- *Charge-Association*
  - *WAIVER*
  - *DISACCRAPPL*
  - *ACCRREQD*
  - *DESC*
- *Charge-Application*
  - *CHRGAMT*
  - *DISACCRAPPL*
  - *WAIVER*
  - *LIQDIND*
- *Charge-Liquidation*
  - *ESN*
  - *CHRGAMT*
  - *LIQDSTAT*

Settlements

- *CONREFNO*
- *LATEVNSEQNO*
- *Contract-Settlement*
  - *CUSTSPREAD*
  - *SPREADDEFN*
  - *TAGCCY*
  - *ACCBRN*
  - *ACC*
  - *EXRATE*
  - *NETIND*
  - *ERICCY*
  - *ERIAMT*
  - *GENMSG*
  - *RATECD*

CLEARNW
COVERBY
RTGSPMNT
BANKPRIOR
RTGSNW
PAYBY
TRANSTYP
INSTYP
INSNO
CHGDET
PAYMNTDET1
PAYMNTDET2
PAYMNTDET3
PAYMNTDET4
SNDTRRCVINFO1
SNDTRRCVINFO2
SNDTRRCVINFO3
SNDTRRCVINFO4
SNDTRRCVINFO5
COVREQRD
RECVCVR
RECEIVER
REIMINST1
REIMINST4
RCVRCORRS1
RCVRCORRS2
RCVRCORRS3
RCVRCORRS4
INTERMEDIARY1
INTERMEDIARY2
INTERMEDIARY3
INTERMEDIARY4
ACCWITHINST1
ACCWITHINST2
ACCWITHINST3
ACCWITHINST4
ORDINST1
ORDINST2
ORDINST3
ORDINST4
ORDCUST1
ORDCUST2
ORDCUST3
ORDCUST4

BENINST1
BENINST2
BENINST3
BENINST4
ULTBEN1
ULTBEN2
ULTBEN3
ULTBEN4
BENINSTCOVR1
BENINSTCOVR2
BENINSTCOVR3
BENINSTCOVR4
BENINSTCOVR5
COUNTRPRYBIC
COUNTRPRYACC
COUNTRPRYNAM
AGID
POSACC
COUNTRCLGNW
SNDRTORECV6
ACCWITHINST5
BENINST5
INTERMEDIARY5
REIMINST5
RCORRS15
ORDCUST5
ORDINST5
ULTBEN5
Settlement-Detail
- *INSTRCD1*
- *INSTRCD2*
- *INSTRCD3*
- *INSTRCD4*
- *ITIMEIND1*
- *ITIMEIND2*
- *ITIMEIND3*
- *INSTRCD5*
- *BANKOPERCD*
- *INSTRCD6*
- *TRNSTYPCD*
- *REGREP1*
- *REGREP2*
- *REGREP3*
- *ENVCONT1*

ENVCONT2

ENVCONT3

ENVCONT4

ENVCONT5

Lcl_Clearing

FREETXT1

FREETXT2

FREETXT3

PMNTCD

ADDINFOSORBNET

ULTBANDCD

SUPPID

PAYERID

PMNTTYP

NOOFDEC

ADDID

SNDRRCVRINFO1

SNDRRCVRINFO2

SNDRRCVRINFO3

SNDRRCVRINFO4

SNDRRCVRINFO5

SNDRRCVRINFO6

DECLARTION

REPRES1

REPRES2

REPRES3

REPRES4

RCVRACC

TXNUDFDETAILS

FLDNAME

FLDVAL

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	

Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length 3; pattern [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable true
Restrictions	**Restrictions** / **Description**: pattern [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	**Description**	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	**Description**	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	**Description**	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	**Description**
Name	ADDL
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	Attribute: maxOccurs = unbounded; minOccurs = 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Transfer-PK

Attribute	Description
Name	Transfer-PK
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

Transfer-IO

Attribute	Description
Name	Transfer-IO
Datatype	
Description	

TOP

FRMREF

Attribute	Description
Name	FRMREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LATVERNO

Attribute	Description
Name	LATVERNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TRANSAMT

Attribute	Description
Name	TRANSAMT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWEXPDT

Attribute	Description
Name	NEWEXPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

NEWLATESTSHIPDT

Attribute	Description
Name	NEWLATESTSHIPDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PERDPRESENTATION

Attribute	Description
Name	PERDPRESENTATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 30

TOP

TOLCUSERREF

Attribute	Description
Name	TOLCUSERREF
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	16

TOP

CONTREFNO

Attribute	Description
Name	CONTREFNO
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

CONREFGOOD

Attribute	Description
Name	CONREFGOOD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

SLNOGOOD

Attribute	Description
Name	SLNOGOOD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

GOODSCD

Attribute	Description
Name	GOODSCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

GOODSDESC

Attribute	Description
Name	GOODSDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6500

TOP

PREADVDESC

Attribute	Description
Name	PREADVDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

CONREFSHIP

Attribute	Description
Name	CONREFSHIP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 16

TOP

FROM

Attribute	Description
Name	FROM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 65

TOP

TO

Attribute	Description
Name	TO

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 65

TOP

PARTIALSHIP

Attribute	**Description**
Name	PARTIALSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSSHIP

Attribute	**Description**
Name	TRANSSHIP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

SHIPDETAILS

Attribute	**Description**
Name	SHIPDETAILS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

SHIPMARKS

Attribute	**Description**
Name	SHIPMARKS
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

SHIPPERIOD

Attribute	**Description**	
Name	SHIPPERIOD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	390

TOP

PORTDISCHG

Attribute	**Description**	
Name	PORTDISCHG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

PORTLOAD

Attribute	**Description**	
Name	PORTLOAD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	65

TOP

CONREFLOG

Attribute	**Description**	
Name	CONREFLOG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,K,V,S,A,H

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,A,U

TOP

POSTOL

Attribute	Description
Name	POSTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NEGTOL

Attribute	Description
Name	NEGTOL
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Parties-Details

Attribute	Description
Name	Parties-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFPARTY

Attribute	**Description**
Name	CONREFPARTY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

SLNOPARTY

Attribute	**Description**
Name	SLNOPARTY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

PARTYTP

Attribute	**Description**
Name	PARTYTP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

PARTYID

Attribute	**Description**
Name	PARTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

PARTYNAME

Attribute	Description
Name	PARTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 150

TOP

ADDRS1

Attribute	Description
Name	ADDRS1
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ADDRS2

Attribute	Description
Name	ADDRS2
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

LANG

Attribute	Description
Name	LANG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CNTY

Attribute	Description
Name	CNTY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CONREFDOC

Attribute	Description
Name	CONREFDOC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

DOCCD

Attribute	Description
Name	DOCCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCTP

Attribute	Description
Name	DOCTP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,T,I,V,O

TOP

DOCDESCR

Attribute	**Description**
Name	DOCDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 6500

TOP

ORIGINALRQD

Attribute	**Description**
Name	ORIGINALRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NOCOPIES

Attribute	**Description**
Name	NOCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOORIGINAL

Attribute	**Description**
Name	NOORIGINAL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

Clause-Deatils

Attribute	Description
Name	Clause-Deatils
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CONREFCLAUSE

Attribute	Description
Name	CONREFCLAUSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

CLAUSECOD

Attribute	Description
Name	CLAUSECOD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CLAUSDESC

Attribute	Description
Name	CLAUSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Transfer-Limits

Attribute	Description

Name	Transfer-Limits
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

PARTYTYP

Attribute	**Description**
Name	PARTYTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

JVPARENT

Attribute	**Description**
Name	JVPARENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

AMOUNTTAG

Attribute	**Description**
Name	AMOUNTTAG
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,LIAB_OS_AMT,CNF_LIAB_OS_AMT,UCNF_LIAB_OS_AMT,REIM_OS_UND_AMT,REIM_OS_NON_UND_AMT

TOP

CUSTNO

Attribute	**Description**
Name	CUSTNO
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LINKAGE_TYPE

Attribute	Description	
Name	LINKAGE_TYPE	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	L,F,P,C

TOP

LINKAGEPERC

Attribute	Description	
Name	LINKAGEPERC	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LINKEDREFNO

Attribute	Description	
Name	LINKEDREFNO	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	30

TOP

LIABILITY_NUMBER

Attribute	Description	
Name	LIABILITY_NUMBER	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

SLNO

Attribute	Description
Name	SLNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSG_TYPE

Attribute	Description
Name	MSG_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 60

TOP

SUPRESS

Attribute	Description
Name	SUPRESS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

MEDIUM

Attribute	Description
Name	MEDIUM
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 60

TOP

PRTYID

Attribute	Description
Name	PRTYID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 44

TOP

PRTYNAME

Attribute	Description
Name	PRTYNAME
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 600

TOP

Ffts

Attribute	Description
Name	Ffts
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTINSCD

Attribute	Description
Name	FFTINSCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 48

TOP

FFTINSDESC

Attribute	**Description**
Name	FFTINSDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

SINGLEFFT

Attribute	**Description**
Name	SINGLEFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Charges

Attribute	**Description**
Name	Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LATEVNSEQNO

Attribute	**Description**
Name	LATEVNSEQNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	**Description**
Name	CONREFNO

Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

Charge-Association

Attribute	**Description**
Name	Charge-Association
Datatype	
Description	Includes Charge Association details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DISACCRAPPL

Attribute	**Description**
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

ACCRREQD

Attribute	**Description**
Name	ACCRREQD
Datatype	String

Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	Indicates Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Charge-Application

Attribute	Description
Name	Charge-Application
Datatype	
Description	Includes Charge Application details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DISACCRAPPL

Attribute	Description
Name	DISACCRAPPL
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

WAIVER

Attribute	**Description**
Name	WAIVER
Datatype	String
Description	Indicates Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

LIQDIND

Attribute	**Description**
Name	LIQDIND
Datatype	String
Description	Indicates Liquidated Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Charge-Liquidation

Attribute	**Description**
Name	Charge-Liquidation
Datatype	
Description	Includes Charge Liquidation details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ESN

Attribute	**Description**
Name	ESN
Datatype	Number
Description	Indicates Event Sequence Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHRGAMT

Attribute	Description
Name	CHRGAMT
Datatype	Number
Description	Indicates Charge Amount
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

LIQDSTAT

Attribute	Description
Name	LIQDSTAT
Datatype	String
Description	Indicates Liquidated
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Settlements

Attribute	Description
Name	Settlements
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CONREFNO

Attribute	Description
Name	CONREFNO
Datatype	String
Description	Indicates Contract Reference Number
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

LATEVNSEQNO

Attribute	Description
Name	LATEVNSEQNO
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Contract-Settlement

Attribute	Description
Name	Contract-Settlement
Datatype	
Description	Includes Contract Settlement details
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

CUSTSPREAD

Attribute	Description
Name	CUSTSPREAD
Datatype	Number
Description	Indicates Customer Spread
Attributes	Attribute: minOccurs, Description: 0

TOP

SPREADDEFN

Attribute	Description
Name	SPREADDEFN
Datatype	String
Description	Indicates Spread Definition
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 1

TOP

TAGCCY

Attribute	Description
Name	TAGCCY
Datatype	String
Description	Indicates tag Currency
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 3

TOP

ACCBRN

Attribute	Description

Name	ACCBRN
Datatype	String
Description	Indicates Branch
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

ACC

Attribute	**Description**
Name	ACC
Datatype	String
Description	Indicates Account
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

EXRATE

Attribute	**Description**
Name	EXRATE
Datatype	Number
Description	Indicates Exchange Rate
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NETIND

Attribute	**Description**
Name	NETIND
Datatype	String
Description	Indicates Netting Indicator Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ERICCY

Attribute	**Description**
Name	ERICCY
Datatype	String
Description	Indicates ERI Currency

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

ERIAMT

Attribute	Description
Name	ERIAMT
Datatype	Number
Description	Indicates ERI Amount
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

GENMSG

Attribute	Description
Name	GENMSG
Datatype	String
Description	Indicates Generate Message Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATECD

Attribute	Description
Name	RATECD
Datatype	String
Description	Indicates Rate Code Mid Rate : M Buy : B Sell : S
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,M,B,S

TOP

CLEARNW

Attribute	Description
Name	CLEARNW
Datatype	String
Description	Indicates Network Code

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

COVERBY

Attribute	Description
Name	COVERBY
Datatype	String
Description	Indicates Cover By Clearing : C Message : M
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / C,M

TOP

RTGSPMNT

Attribute	Description
Name	RTGSPMNT
Datatype	String
Description	Indicates RTGS Payment Y for Yes; N for No
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

BANKPRIOR

Attribute	Description
Name	BANKPRIOR
Datatype	String
Description	Indicates Banking Priority Highly Urgent Payments : H Urgent Payment : U Normal Payment : N
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / ,H,U,N

TOP

RTGSNW

Attribute	Description

Name	RTGSNW
Datatype	String
Description	Indicates RTGS Network
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

PAYBY

Attribute	Description
Name	PAYBY
Datatype	String
Description	Indicates Payment By Message : M Instrument : I Clearing : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,I,C

TOP

TRANSTYP

Attribute	Description
Name	TRANSTYP
Datatype	String
Description	Indicates Transfer Type Bank Transfer : B Customer Transfer : C Bank Transfer for Own Account : O Direct Debit Advice : D MCK : M None : X
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / B,C,O,D,M,X

TOP

INSTYP

Attribute	Description
Name	INSTYP
Datatype	String
Description	Indicates Instrument Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

INSNO

Attribute	Description
Name	INSNO
Datatype	String
Description	Indicates Instrument Number
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

CHGDET

Attribute	Description
Name	CHGDET
Datatype	String
Description	Indicates Details Of Charge Remitter all Charges : R Beneficiary all Charges : B Remitter our Charges : O
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / R,B,O

TOP

PAYMNTDET1

Attribute	Description
Name	PAYMNTDET1
Datatype	String
Description	Indicates Details Of Payment 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET2

Attribute	Description
Name	PAYMNTDET2
Datatype	String
Description	Indicates Details Of Payment 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET3

Attribute	Description
Name	PAYMNTDET3
Datatype	String
Description	Indicates Details Of Payment 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PAYMNTDET4

Attribute	Description
Name	PAYMNTDET4
Datatype	String
Description	Indicates Details Of Payment 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO1

Attribute	Description
Name	SNDTRRCVINFO1
Datatype	String
Description	Indicates Sender To Receiver Information 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO2

Attribute	Description
Name	SNDTRRCVINFO2
Datatype	String
Description	Indicates Sender To Receiver Information 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

SNDTRRCVINFO3

Attribute	Description
Name	SNDTRRCVINFO3
Datatype	String
Description	Indicates Sender To Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO4

Attribute	Description
Name	SNDTRRCVINFO4
Datatype	String
Description	Indicates Sender To Receiver Information 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

SNDTRRCVINFO5

Attribute	Description
Name	SNDTRRCVINFO5
Datatype	String
Description	Indicates Sender To Receiver Information 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COVREQRD

Attribute	Description
Name	COVREQRD
Datatype	String
Description	Indicates Cover Required Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1

TOP

RECVCVR

Attribute	Description
Name	RECVCVR
Datatype	String
Description	Indicates Receiver of Cover
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

RECEIVER

Attribute	Description
Name	RECEIVER
Datatype	String
Description	Indicates Receiver
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 11

TOP

REIMINST1

Attribute	Description
Name	REIMINST1
Datatype	String
Description	Indicates Reimburse Institution 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

REIMINST4

Attribute	Description
Name	REIMINST4
Datatype	String
Description	Indicates Reimburse Institution 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

RCVRCORRS1

Attribute	Description
Name	RCVRCORRS1

Datatype	String
Description	Indicates Receiver Correspondent 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS2

Attribute	Description
Name	RCVRCORRS2
Datatype	String
Description	Indicates Receiver Correspondent 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS3

Attribute	Description
Name	RCVRCORRS3
Datatype	String
Description	Indicates Receiver Correspondent 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCVRCORRS4

Attribute	Description
Name	RCVRCORRS4
Datatype	String
Description	Indicates Receiver Correspondent 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

INTERMEDIARY1

Attribute	Description
Name	INTERMEDIARY1
Datatype	String
Description	Indicates Intermediary 1

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY2

Attribute	Description	
Name	INTERMEDIARY2	
Datatype	String	
Description	Indicates Intermediary 2	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY3

Attribute	Description	
Name	INTERMEDIARY3	
Datatype	String	
Description	Indicates Intermediary 3	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

INTERMEDIARY4

Attribute	Description	
Name	INTERMEDIARY4	
Datatype	String	
Description	Indicates Intermediary 4	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ACCWITHINST1

Attribute	Description	
Name	ACCWITHINST1	
Datatype	String	
Description	Indicates Account with Institution 1	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST2

Attribute	Description	
Name	ACCWITHINST2	
Datatype	String	
Description	Indicates Account with Institution 2	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST3

Attribute	Description	
Name	ACCWITHINST3	
Datatype	String	
Description	Indicates Account with Institution 3	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ACCWITHINST4

Attribute	Description	
Name	ACCWITHINST4	
Datatype	String	
Description	Indicates Account with Institution 4	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST1

Attribute	Description	
Name	ORDINST1	
Datatype	String	
Description	Indicates Ordering Institution 1	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

TOP

ORDINST2

Attribute	Description
Name	ORDINST2
Datatype	String
Description	Indicates Ordering Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST3

Attribute	Description
Name	ORDINST3
Datatype	String
Description	Indicates Ordering Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDINST4

Attribute	Description
Name	ORDINST4
Datatype	String
Description	Indicates Ordering Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST1

Attribute	Description
Name	ORDCUST1
Datatype	String
Description	Indicates Ordering Customer 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ORDCUST2

Attribute	Description
Name	ORDCUST2
Datatype	String
Description	Indicates Ordering Customer 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST3

Attribute	Description
Name	ORDCUST3
Datatype	String
Description	Indicates Ordering Customer 3
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST4

Attribute	Description
Name	ORDCUST4
Datatype	String
Description	Indicates Ordering Customer 4
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST1

Attribute	Description
Name	BENINST1
Datatype	String
Description	Indicates Beneficiary Institution 1
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

BENINST2

Attribute	Description
Name	BENINST2

Datatype	String
Description	Indicates Beneficiary Institution 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST3

Attribute	Description
Name	BENINST3
Datatype	String
Description	Indicates Beneficiary Institution 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINST4

Attribute	Description
Name	BENINST4
Datatype	String
Description	Indicates Beneficiary Institution 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN1

Attribute	Description
Name	ULTBEN1
Datatype	String
Description	Indicates Ultimate Beneficiary 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN2

Attribute	Description
Name	ULTBEN2
Datatype	String
Description	Indicates Ultimate Beneficiary 2

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN3

Attribute	Description
Name	ULTBEN3
Datatype	String
Description	Indicates Ultimate Beneficiary 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

ULTBEN4

Attribute	Description
Name	ULTBEN4
Datatype	String
Description	Indicates Ultimate Beneficiary 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR1

Attribute	Description
Name	BENINSTCOVR1
Datatype	String
Description	Indicates Beneficiary Institution For Cover 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

BENINSTCOVR2

Attribute	Description
Name	BENINSTCOVR2
Datatype	String
Description	Indicates Beneficiary Institution For Cover 2
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

BENINSTCOVR3

Attribute	Description
Name	BENINSTCOVR3
Datatype	String
Description	Indicates Beneficiary Institution For Cover 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR4

Attribute	Description
Name	BENINSTCOVR4
Datatype	String
Description	Indicates Beneficiary Institution For Cover 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINSTCOVR5

Attribute	Description
Name	BENINSTCOVR5
Datatype	String
Description	Indicates Beneficiary Institution For Cover 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

COUNTRPRYBIC

Attribute	Description
Name	COUNTRPRYBIC
Datatype	String
Description	Indicates Counterparty Bank
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

COUNTRPRYACC

Attribute	Description
Name	COUNTRPRYACC
Datatype	String
Description	Indicates Counterparty Account
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

COUNTRPRYNAM

Attribute	Description
Name	COUNTRPRYNAM
Datatype	String
Description	Indicates Counterparty Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

AGID

Attribute	Description
Name	AGID
Datatype	String
Description	Indicates Agreement Identification
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

POSACC

Attribute	Description
Name	POSACC
Datatype	String
Description	Indicates Post Accounting
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

COUNTRCLGNW

Attribute	Description
Name	COUNTRCLGNW
Datatype	String
Description	Indicates Clearing Network
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

SNDRTORECV6

Attribute	Description
Name	SNDRTORECV6
Datatype	String
Description	Indicates Sender to Receiver Information 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCWITHINST5

Attribute	Description
Name	ACCWITHINST5
Datatype	String
Description	Indicates Account with Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

BENINST5

Attribute	Description
Name	BENINST5
Datatype	String
Description	Indicates Beneficiary Institution 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

INTERMEDIARY5

Attribute	Description
Name	INTERMEDIARY5

Datatype	String
Description	Indicates Intermediary 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

REIMINST5

Attribute	Description
Name	REIMINST5
Datatype	String
Description	Indicates Reimburse Institution 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RCORRS15

Attribute	Description
Name	RCORRS15
Datatype	String
Description	Indicates Receiver Correspondent 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDCUST5

Attribute	Description
Name	ORDCUST5
Datatype	String
Description	Indicates Ordering Customer 5
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ORDINST5

Attribute	Description
Name	ORDINST5
Datatype	String
Description	Indicates Ordering Institution 5

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

ULTBEN5

Attribute	Description
Name	ULTBEN5
Datatype	String
Description	Indicates Ultimate Beneficiary 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Settlement-Detail

Attribute	Description
Name	Settlement-Detail
Datatype	
Description	Includes Settlement details
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

INSTRCD1

Attribute	Description
Name	INSTRCD1
Datatype	String
Description	Indicates Instruction Code 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD2

Attribute	Description
Name	INSTRCD2
Datatype	String
Description	Indicates Instruction Code 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD3

Attribute	Description
Name	INSTRCD3
Datatype	String
Description	Indicates Instruction Code 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

INSTRCD4

Attribute	Description
Name	INSTRCD4
Datatype	String
Description	Indicates Instruction Code 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND1

Attribute	Description
Name	ITIMEIND1
Datatype	String
Description	Indicates Time Indicator 1
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND2

Attribute	Description
Name	ITIMEIND2
Datatype	String
Description	Indicates Time Indicator 2
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

ITIMEIND3

Attribute	Description
Name	ITIMEIND3
Datatype	String
Description	Indicates Time Indicator 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

INSTRCD5

Attribute	Description
Name	INSTRCD5
Datatype	String
Description	Indicates Time Indicator 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

BANKOPERCD

Attribute	Description
Name	BANKOPERCD
Datatype	String
Description	Indicates Bank Operation Code CRED : CRED SPAY : SPAY SPRI : SPRI SSTD : SSTD
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,CRED,SPAY,SPRI,SSTD

TOP

INSTRCD6

Attribute	Description
Name	INSTRCD6
Datatype	String
Description	Indicates Instruction Code 6
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

TRNSTYPCD

Attribute	Description
Name	TRNSTYPCD
Datatype	String
Description	Indicates Transaction Code of Time Indicators
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

REGREP1

Attribute	Description
Name	REGREP1
Datatype	String
Description	Indicates Regulatory Report 1 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP2

Attribute	Description
Name	REGREP2
Datatype	String
Description	Indicates Regulatory Report 2 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,/BENEFRES/,/ORDERRES/

TOP

REGREP3

Attribute	Description
Name	REGREP3
Datatype	String
Description	Indicates Regulatory Report 3 /BENEFRES/ : /BENEFRES/ /ORDERRES/ : /ORDERRES/
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	,/BENEFRES/,/ORDERRES/

TOP

ENVCONT1

Attribute	Description
Name	ENVCONT1
Datatype	String
Description	Indicates Envelope Contents 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT2

Attribute	Description
Name	ENVCONT2
Datatype	String
Description	Indicates Envelope Contents 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT3

Attribute	Description
Name	ENVCONT3
Datatype	String
Description	Indicates Envelope Contents 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT4

Attribute	Description
Name	ENVCONT4
Datatype	String
Description	Indicates Envelope Contents 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 2000

TOP

ENVCONT5

Attribute	Description
Name	ENVCONT5
Datatype	String
Description	Indicates Envelope Contents 5
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 1000

TOP

Lcl_Clearing

Attribute	Description
Name	Lcl_Clearing
Datatype	
Description	Includes Local clearing details
Attributes	Attribute: minOccurs — Description: 0

TOP

FREETXT1

Attribute	Description
Name	FREETXT1
Datatype	String
Description	Indicates Free Text 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT2

Attribute	Description
Name	FREETXT2
Datatype	String
Description	Indicates Free Text 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

FREETXT3

Attribute	Description
Name	FREETXT3

Datatype	String
Description	Indicates Free Text 3
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

PMNTCD

Attribute	Description
Name	PMNTCD
Datatype	String
Description	Indicates Payment Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

ADDINFOSORBNET

Attribute	Description
Name	ADDINFOSORBNET
Datatype	String
Description	Indicates Additional Information
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 16

TOP

ULTBANDCD

Attribute	Description
Name	ULTBANDCD
Datatype	String
Description	Indicates Ultimate Bank Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

SUPPID

Attribute	Description
Name	SUPPID
Datatype	String

Description	Indicates Supplement Identification PESEL : P REGON : R 1 : 1 2 : 2
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,P,R,1,2

TOP

PAYERID

Attribute	Description
Name	PAYERID
Datatype	String
Description	Indicates Payer Identifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 14

TOP

PMNTTYP

Attribute	Description
Name	PMNTTYP
Datatype	String
Description	Indicates Payment Type D : D E : E K : K M : M S : S T : T U : U
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,D,E,K,M,S,T,U

TOP

NOOFDEC

Attribute	Description
Name	NOOFDEC
Datatype	Number
Description	Indicates Number of Declaration
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ADDID

Attribute	Description
Name	ADDID
Datatype	String
Description	Indicates Additional Identifier
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 32

TOP

SNDRRCVRINFO1

Attribute	Description
Name	SNDRRCVRINFO1
Datatype	String
Description	Indicates Sender Receiver Information 1
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO2

Attribute	Description
Name	SNDRRCVRINFO2
Datatype	String
Description	Indicates Sender Receiver Information 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO3

Attribute	Description
Name	SNDRRCVRINFO3
Datatype	String
Description	Indicates Sender Receiver Information 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

SNDRRCVRINFO4

Attribute	Description
Name	SNDRRCVRINFO4

Datatype	String
Description	Indicates Sender Receiver Information 4
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO5

Attribute	Description
Name	SNDRRCVRINFO5
Datatype	String
Description	Indicates Sender Receiver Information 5
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

SNDRRCVRINFO6

Attribute	Description
Name	SNDRRCVRINFO6
Datatype	String
Description	Indicates Sender Receiver Information 6
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

DECLARTION

Attribute	Description
Name	DECLARTION
Datatype	Number
Description	Indicates Declaration
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

REPRES1

Attribute	Description
Name	REPRES1
Datatype	String
Description	Indicates Repair Reason 1
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	35

TOP

REPRES2

Attribute	Description
Name	REPRES2
Datatype	String
Description	Indicates Repair Reason 2
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES3

Attribute	Description
Name	REPRES3
Datatype	String
Description	Indicates Repair Reason 3
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

REPRES4

Attribute	Description
Name	REPRES4
Datatype	String
Description	Indicates Repair Reason 4
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RCVRACC

Attribute	Description
Name	RCVRACC
Datatype	String
Description	Indicates Receiver Account
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 34

TOP

TXNUDFDETAILS

Attribute	Description
Name	TXNUDFDETAILS
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Restrictions	**Restrictions** / **Description** maxLength / 105 minLength / 1

TOP

FLDVAL

Attribute	Description
Name	FLDVAL
Datatype	String
Description	Indicates Field Value
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255 minLength / 0

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	

Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description

Name	WDESC
Datatype	String
Description	

TOP

2.36.CreateProduct

Creation of LI Product

2.36.1.LI-CreateProduct-Req-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*

LMTSTNRCALCTYP
REKYREQ
REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL

STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
MAKER
MAKERSTAMP
CHECKER
CHECKERSTAMP
MODNO
TXNSTAT
AUTHSTAT
Commission-Details
- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details
- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*

NOOFORIGINALS
ORGNALREQ
Clause-Details
CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-GI-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD

- *CLASDESC*
- *Event-Details*
  - *EVNTCD*
  - *EVENTDESC*
  - *Accounting-Entries*
    - *ACCRLCD*
    - *AMTTAG*
    - *DRCRINDICTR*
    - *TRNCD*
    - *NETINDICTR*
    - *MISHD*
    - *REVALPRGL*
    - *REVALLSGL*
    - *REVALRTCD*
    - *REVALTXNCD*
    - *HOLTREAT*
    - *REVALREQD*
    - *RATE_TYPE_INDICATOR*
  - *Advices*
    - *MSGTYP*
    - *DESC*
    - *GENTIME*
    - *SUPRS*
    - *PRIOR*
    - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*
  - *CLASDESC*
  - *Mapping-Details*
    - *ACCTRL*
    - *ROLDESC*
    - *ACCTHD*
    - *GLDESC*
- *Branch-Ccy-Restrictions*
  - *CCYLST*
  - *BRNLST*
  - *CLASCD*
  - *CLASDESC*
  - *Branch-List*
    - *BRNDISALOW*
    - *BRNNAME*
  - *Ccy-List*
    - *BGTDLCCY*
    - *CCYNAME*

- *Prod-Cust-Restrictions*
  - *CATGLIS*
  - *CLASCD*
  - *Cust-Categories*
    - *CATGDSAW*
    - *DESCRIPTION*
  - *Customers*
    - *CSTID*
    - *CUSTNAME*
    - *ALWD*
- *Product-Fields*
  - *Field-Details*
    - *FLDNUM*
    - *FLDNAME*
- *Product-Mis-Details*
  - *MISGRP*
  - *POOLCD*
  - *CSTCD1*
  - *CSTCD2*
  - *CSTCD4*
  - *CSTCD5*
  - *Default-Mis-Codes*
    - *MISCLS*
    - *MISCD*
- *Product-Charges*
  - *Charge-Details*
    - *CHGTYP*
    - *THRDPTYTY*
    - *DRCRTYPE*
    - *NTCNSINDI*
    - *NETCONSPLSMINS*
    - *SWIFTQLF*
    - *SETTCCY*
    - *DFTWAIV*
    - *ALWRULAMND*
    - *AMNDAFTRASSOC*
    - *ALWAMTAMND*
    - *AMNDAFTRAPPL*
    - *STPASOCIATN*
    - *ADVCHG*
    - *CAPTLIZE*
    - *DISCACCRAPLB*
    - *PROPREQD*
    - *DISCNTBASIS*

DFTRULE
COMPNT
EVNTFRASSC
EVNTFRAPPL
EVNTFRLIQ
BASISAMNTTAG
BASICAMTTGDESC
ACCRREQD
COMPNENTDESC
EVNTASSCTDESC
EVNTAPPLIDESC
EVNTLIQDDESC
RULDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: enumeration / FCUBS,FCIS

TOP

MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** maxLength / 12 pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description** length / 3 pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

SERVICE

Attribute	**Description**
Name	SERVICE

Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	**Description**
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** nillable / true
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	**Description**
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	**Description**
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

DESTINATION

Attribute	**Description**
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	8
	pattern	[A-Z_0-9]*

TOP

ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 128; pattern / [a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	Description
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	Description
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description	
Name	REKYAMNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYCCY

Attribute	Description	
Name	REKYCCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYCUSTM

Attribute	Description	
Name	REKYCUSTM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYVALDAT

Attribute	Description	
Name	REKYVALDAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / I,E,

TOP

INCLDTODAT

Attribute	**Description**
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ACRFREQ

Attribute	**Description**
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	**Description**
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

ACRDAY

Attribute	**Description**
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLSURDAYS

Attribute	**Description**
Name	CLSURDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

EXPIRNOTREQFLG

Attribute	Description	
Name	EXPIRNOTREQFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

EXPIRNOTDYS

Attribute	Description	
Name	EXPIRNOTDYS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLSURNTFLG

Attribute	Description	
Name	CLSURNTFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	B,A

TOP

CLSURNTRQFLD

Attribute	Description	
Name	CLSURNTRQFLD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGCLAIM

Attribute	**Description**
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVABYLOAN

Attribute	**Description**
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

LOANBRIDGEGL

Attribute	**Description**
Name	LOANBRIDGEGL
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD

Attribute	Description	
Name	LOANPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COLLBRIDGEGL

Attribute	Description	
Name	COLLBRIDGEGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STATCNFLG

Attribute	Description	
Name	STATCNFLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,M

TOP

MINIMUM

Attribute	Description	
Name	MINIMUM	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

CHECKER

Attribute	Description
Name	CHECKER

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

CHECKERSTAMP

Attribute	**Description**
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

MODNO

Attribute	**Description**
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

TXNSTAT

Attribute	**Description**
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

AUTHSTAT

Attribute	**Description**
Name	AUTHSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 1

TOP

Commission-Details

Attribute	**Description**
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

COMPNENT

Attribute	**Description**
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNENTDESC

Attribute	**Description**
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

RULEIDENTIFICAT

Attribute	**Description**
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description

Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	**Description**
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	Description
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	Description
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	Description
Name	EVNTDESCR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	Description	
Name	CCY	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

COMMCALCBASIS

Attribute	Description	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

Ccy-Details

Attribute	Description

Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	**Description**
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	**Description**
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	**Description**
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs, Description: unbounded Attribute: minOccurs, Description: 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 1
Restrictions	Restrictions: maxLength, Description: 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs, Description: 0

Restrictions	Restrictions	Description
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description
Name	DOCSHRTDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

FFTTEXTDESC

Attribute	Description	
Name	FFTTEXTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	2000

TOP

ADVCD

Attribute	Description	
Name	ADVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SINGLFFT

Attribute	Description	
Name	SINGLFFT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Tracer-Details

Attribute	Description	
Name	Tracer-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 2000

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

TYP

Attribute	**Description**
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / W,E,

TOP

Status-Details

Attribute	**Description**
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

STATUSSEQ

Attribute	**Description**
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

STPACCRUALS

Attribute	**Description**
Name	STPACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Control-Prod-Stat

Attribute	Description
Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String

Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

EVENTDESC

Attribute	**Description**
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	35

TOP

DRCRINDICTR

Attribute	Description	
Name	DRCRINDICTR	
Datatype	String	
Description	Indicates debit or credit.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	D,C

TOP

TRNCD

Attribute	Description	
Name	TRNCD	
Datatype	String	
Description	Indicates transaction code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

TOP

NETINDICTR

Attribute	Description	
Name	NETINDICTR	
Datatype	String	
Description	Indicates netting indicator.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

MISHD

Attribute	Description	
Name	MISHD	
Datatype	String	
Description	Indicates MIS head.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String

Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	**Description**
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	**Description**
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	**Description**
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Number
Description	Indicates priority.

Attributes	Attribute	Description
	minOccurs	0

TOP

CHGREQD

Attribute	Description	
Name	CHGREQD	
Datatype	String	
Description	Indicates charges required.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Role-To-Head-Mapping

Attribute	Description	
Name	Role-To-Head-Mapping	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

CLASCD

Attribute	Description	
Name	CLASCD	
Datatype	String	
Description	Indicates Class Code	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

CLASDESC

Attribute	Description	
Name	CLASDESC	
Datatype	String	
Description	Indicates Class Code Description	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String

Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	**Description**
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	**Description**
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	**Description**
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

ORACLE

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

BRNNAME

Attribute	Description
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Ccy-List

Attribute	Description

Name	Ccy-List
Datatype	
Description	Indicates Currency List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	**Description**
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

CCYNAME

Attribute	**Description**
Name	CCYNAME
Datatype	String
Description	Indicates Currency name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

Prod-Cust-Restrictions

Attribute	**Description**
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	**Description**
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Cust-Categories

Attribute	Description
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

CATGDSAW

Attribute	Description
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

DESCRIPTION

Attribute	Description
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Customers

Attribute	Description

Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	**Description**
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

POOLCD

Attribute	**Description**	
Name	POOLCD	
Datatype	String	
Description	Indicates Pool Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD1

Attribute	**Description**	
Name	CSTCD1	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD2

Attribute	**Description**	
Name	CSTCD2	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

CSTCD4

Attribute	**Description**	
Name	CSTCD4	
Datatype	String	
Description	Indicates Cost Code.	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	Description
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	Description
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	Description
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	Description
Name	DRCRTYPE

Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	**Description**
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	Description
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 3

TOP

DFTWAIV

Attribute	Description
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWRULAMND

Attribute	Description
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	Description
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	Description
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,O,

TOP

DFTRULE

Attribute	**Description**	
Name	DFTRULE	
Datatype	String	
Description	Indicates Rule	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	**Description**	
Name	COMPNT	
Datatype	String	
Description	Indicates Component	
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNTFRASSC

Attribute	**Description**	
Name	EVNTFRASSC	
Datatype	String	
Description	Indicates Event For Association	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

EVNTFRAPPL

Attribute	**Description**	
Name	EVNTFRAPPL	
Datatype	String	
Description	Indicates Event For Application	
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	4

TOP

EVNTFRLIQ

Attribute	Description	
Name	EVNTFRLIQ	
Datatype	String	
Description	Indicates Event For Liquidation	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

BASISAMNTTAG

Attribute	Description	
Name	BASISAMNTTAG	
Datatype	String	
Description	Indicates Basis Amount Tag	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

TOP

BASICAMTTGDESC

Attribute	Description	
Name	BASICAMTTGDESC	
Datatype	String	
Description	Indicates Basis Amount Description	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

TOP

ACCRREQD

Attribute	Description	
Name	ACCRREQD	
Datatype	String	
Description	Indicates Accrual Required Y for Yes; N for No	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String
Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

RULDESC

Attribute	Description
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

2.36.2.LI-CreateProduct-Req-IO-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-IO*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*
    - *REKYCCY*
    - *REKYCUSTM*

REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
LC_TYPE
MAXIMUM
Commission-Details

- *COMPNENT*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details

- *DOCMNTCD*
- *DOCMNTTYP*
- *NOOFCOPIES*
- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*
  - *CLAUSECD*

Fft-Details

- *FFTCD*
- *ADVCD*
- *SINGLFFT*

Tracer-Details

- *TRCERCD*
- *REQIRED*
- *NOFTRCERS*
- *STRTDAYS*
- *FREQNCY*

Tax-Scheme

- *SCHME*

- *Tax-Details*
  - *BASISCMPNT*
  - *COMPTATIONEVNT*
  - *TYP*
- *Status-Details*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *COMPLETEACCRUALS*
  - *TRANSACTIONCD*
  - *STATUS*
  - *DERVTNRUL*
  - *Status-Gl-Details*
    - *ACCROLEDESC*
    - *ACCGLDESC*
    - *ACCNTROLE*
    - *TRNSFERGL*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*
      - *REVALRTCD*
      - *REVALTXNCD*
      - *HOLTREAT*
      - *REVALREQD*
      - *RATE_TYPE_INDICATOR*
    - *Advices*
      - *MSGTYP*
      - *GENTIME*
      - *SUPRS*
      - *PRIOR*
      - *CHGREQD*
- *Role-To-Head-Mapping*
  - *CLASCD*

Mapping-Details
ACCTRL
ACCTHD
STAT
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Charges
Charge-Details
SETTCCY
DFTWAIV
ALWRULAMND
AMNDAFTRASSOC
ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DISCACCRAPLB

DISCNTBASIS

DFTRULE

COMPNT

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

CORRELID

Attribute	Description
Name	CORRELID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	Description
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	Description
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	Description
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description
Name	PASSWORD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description
Name	ADDL
Datatype	
Description	
Attributes	**Attribute** / **Description**
	minOccurs / 0

TOP

PARAM

Attribute	Description
Name	PARAM
Datatype	
Description	
Attributes	**Attribute** / **Description**
	maxOccurs / unbounded
	minOccurs / 0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description

Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	**Description**
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYMATDATE

Attribute	**Description**
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	**Description**
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INCOTRM

Attribute	**Description**
Name	INCOTRM
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

TOLRNCEPOSTV

Attribute	**Description**	
Name	TOLRNCEPOSTV	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

TOLRNCENEGTV

Attribute	**Description**	
Name	TOLRNCENEGTV	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

COMMCOLLEMETHD

Attribute	**Description**	
Name	COMMCOLLEMETHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,R,

TOP

COMMCALMETHD

Attribute	**Description**	
Name	COMMCALMETHD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	**Description**
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

CLSURNTDAYS

Attribute	**Description**
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	**Description**
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	**Description**
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

RTCODEPRFERD

Attribute	**Description**
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / M,B

TOP

URRPREF

Attribute	**Description**
Name	URRPREF
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	**Description**
Name	PARCONALLOW
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CHGCLAIM

Attribute	**Description**
Name	CHGCLAIM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVABYLOAN

Attribute	Description	
Name	ADVABYLOAN	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

LOANBRIDGEGL

Attribute	Description	
Name	LOANBRIDGEGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

LOANPRD

Attribute	Description	
Name	LOANPRD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

COLLBRIDGEGL

Attribute	Description	
Name	COLLBRIDGEGL	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

TOP

EVNT

Attribute	Description	
Name	EVNT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	4

TOP

BASISAMNTTYP

Attribute	Description	
Name	BASISAMNTTYP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATCD

Attribute	Description
Name	RATCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

ACQREQD

Attribute	Description
Name	ACQREQD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COLLLCCOM

Attribute	**Description**
Name	COLLLCCOM
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Currency-Preferences

Attribute	**Description**
Name	Currency-Preferences
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	**Description**
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

COMMCALCBASIS

Attribute	**Description**
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String

Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,V,T,O,

TOP

NOOFCOPIES

Attribute	**Description**
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	**Description**
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 5

TOP

ORGNALREQ

Attribute	**Description**
Name	ORGNALREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Clause-Details

Attribute	**Description**
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description	
Name	CLAUSECD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

Fft-Details

Attribute	Description	
Name	Fft-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

FFTCD

Attribute	Description	
Name	FFTCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	12

TOP

ADVCD

Attribute	Description	
Name	ADVCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	15

TOP

SINGLFFT

Attribute	Description

Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

Tracer-Details

Attribute	**Description**
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

TRCERCD

Attribute	**Description**
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

REQIRED

Attribute	**Description**
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	**Description**
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BASISCMPNT

Attribute	Description	
Name	BASISCMPNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	25

TOP

COMPTATIONEVNT

Attribute	Description	
Name	COMPTATIONEVNT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

TYP

Attribute	Description	
Name	TYP	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	W,E,

TOP

Status-Details

Attribute	Description	
Name	Status-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REVERSEACCRUALS

Attribute	Description
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOFRWD

Attribute	Description
Name	AUTOFRWD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

AUTOREVERSE

Attribute	Description
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMPLETEACCRUALS

Attribute	Description
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	9

TOP

Product-Events

Attribute	Description
Name	Product-Events
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

Event-Details

Attribute	Description
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 6

TOP

Accounting-Entries

Attribute	Description

Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	**Description**
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1

Restrictions	Restrictions	Description
	maxLength	3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MISHD

Attribute	Description
Name	MISHD
Datatype	String
Description	Indicates MIS head.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String

Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	**Description**
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	**Description**
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	**Description**
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

Branch-Ccy-Restrictions

Attribute	Description

Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Branch-List

Attribute	Description
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	Description
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Ccy-List

Attribute	Description
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description

Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CATGLIS

Attribute	**Description**
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	Description
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	Description
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	

Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5

Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

Default-Mis-Codes

Attribute	**Description**
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

MISTYP

Attribute	**Description**
Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

MISCLS

Attribute	**Description**
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 100

TOP

MISCD

Attribute	**Description**
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

KYID

Attribute	**Description**
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

SETTCCY

Attribute	**Description**
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	**Description**

Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	**Description**
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	**Description**
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	**Description**
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 10

TOP

2.36.3.LI-CreateProduct-Res-Full-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *Product-Details-Full*
    - *PRDCD*
    - *PRDDESC*
    - *PRDSLG*
    - *PRDRMRKS*
    - *PRDSTRTDT*
    - *PRDENDDT*
    - *PRDGRP*
    - *PRDTYP*
    - *REVLVNG*
    - *PRDGRPDESC*
    - *PRDTYPDESC*
    - *STNDRDTNR*
    - *MINTENR*
    - *MAXTENR*
    - *CSHCOLLATRL*
    - *LMTSTNRCALCTYP*
    - *REKYREQ*
    - *REKYAMNT*

REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM
LC_TYPE

MAXIMUM

MAKER

MAKERSTAMP

CHECKER

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

Commission-Details

- *COMPNENT*
- *COMPNENTDESC*
- *RULEIDENTIFICAT*
- *EVNT*
- *BASISAMNTTYP*
- *BASISAMNTCATG*
- *SETTLMNTCCY*
- *CHNGDRGAMNDMNT*
- *STPAPPLICTION*
- *RATTYP*
- *RATCDUSGE*
- *SHWNINCNTRTMAINSCR*
- *RATCD*
- *ACQREQD*
- *RULEDESC*
- *EVNTDESCR*
- *COLLLCCOM*
- *Currency-Preferences*
  - *CCY*
  - *COMMCALCBASIS*
- *Ccy-Details*
  - *CCY*
  - *DEFRAT*
  - *MINRATE*
  - *MAXRAT*
  - *MINSPRD*
  - *MAXSPRD*

Document-Details

- *DOCMNTCD*
- *DOCMNTTYP*
- *DOCSHRTDESC*
- *NOOFCOPIES*
- *NOOFORIGINALS*
- *ORGNALREQ*
- *Clause-Details*

CLAUSECD
DESC
Fft-Details
FFTCD
FFTTEXTDESC
ADVCD
SINGLFFT
Tracer-Details
TRCERCD
DESC
REQIRED
NOFTRCERS
STRTDAYS
FREQNCY
Tax-Scheme
SCHME
SCHEMEDESC
Tax-Details
TAXRUL
TAXCMPNT
BASISCMPNT
COMPTATIONEVNT
TYP
Status-Details
STATUSSEQ
STPACCRUALS
REVERSEACCRUALS
AUTOFRWD
AUTOREVERSE
COMPLETEACCRUALS
TRANSACTIONCD
STATUS
DERVTNRUL
Status-Gl-Details
ACCROLEDESC
ACCGLDESC
ACCNTROLE
TRNSFERGL
Control-Prod-Stat
Product-Events
CLASCD
CLASDESC
Event-Details
EVNTCD

EVENTDESC

Accounting-Entries

ACCRLCD

AMTTAG

DRCRINDICTR

TRNCD

NETINDICTR

MISHD

REVALPRGL

REVALLSGL

REVALRTCD

REVALTXNCD

HOLTREAT

REVALREQD

RATE_TYPE_INDICATOR

Advices

MSGTYP

DESC

GENTIME

SUPRS

PRIOR

CHGREQD

Role-To-Head-Mapping

CLASCD

CLASDESC

Mapping-Details

ACCTRL

ROLDESC

ACCTHD

GLDESC

Branch-Ccy-Restrictions

CCYLST

BRNLST

CLASCD

CLASDESC

Branch-List

BRNDISALOW

BRNNAME

Ccy-List

BGTDLCCY

CCYNAME

Prod-Cust-Restrictions

CATGLIS

CLASCD

- *Cust-Categories*
  - *CATGDSAW*
  - *DESCRIPTION*
- *Customers*
  - *CSTID*
  - *CUSTNAME*
  - *ALWD*

Product-Fields

- *Field-Details*
  - *FLDNUM*
  - *FLDNAME*

Product-Mis-Details

- *MISGRP*
- *POOLCD*
- *CSTCD1*
- *CSTCD2*
- *CSTCD4*
- *CSTCD5*
- *Default-Mis-Codes*
  - *MISCLS*
  - *MISCD*

Product-Charges

- *Charge-Details*
  - *CHGTYP*
  - *THRDPTYTY*
  - *DRCRTYPE*
  - *NTCNSINDI*
  - *NETCONSPLSMINS*
  - *SWIFTQLF*
  - *SETTCCY*
  - *DFTWAIV*
  - *ALWRULAMND*
  - *AMNDAFTRASSOC*
  - *ALWAMTAMND*
  - *AMNDAFTRAPPL*
  - *STPASOCIATN*
  - *ADVCHG*
  - *CAPTLIZE*
  - *DISCACCRAPLB*
  - *PROPREQD*
  - *DISCNTBASIS*
  - *DFTRULE*
  - *COMPNT*
  - *EVNTFRASSC*

EVNTFRAPPL

EVNTFRLIQ

BASISAMNTTAG

BASICAMTTGDESC

ACCRREQD

COMPNENTDESC

EVNTASSCTDESC

EVNTAPPLIDESC

EVNTLIQDDESC

RULDESC

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

TOP

Product-Details-Full

Attribute	Description
Name	Product-Details-Full
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description	
Name	PRDDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

PRDSLG

Attribute	Description	
Name	PRDSLG	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255

TOP

PRDRMRKS

Attribute	Description	
Name	PRDRMRKS	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

PRDSTRTDT

Attribute	Description	
Name	PRDSTRTDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PRDENDDT

Attribute	Description	
Name	PRDENDDT	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

PRDGRP

Attribute	Description	
Name	PRDGRP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	**Description**
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

PRDGRPDESC

Attribute	**Description**
Name	PRDGRPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

PRDTYPDESC

Attribute	**Description**
Name	PRDTYPDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 22

TOP

STNDRDTNR

Attribute	**Description**
Name	STNDRDTNR
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYAMNT

Attribute	Description
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	Description
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	Description
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	Description
Name	REKYVALDAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,E,

TOP

INCLDTODAT

Attribute	Description
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRFREQ

Attribute	Description
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	Description
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	Description
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

EXPIRNOTREQFLG

Attribute	**Description**
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

EXPIRNOTDYS

Attribute	**Description**
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURNTFLG

Attribute	**Description**
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / B,A

TOP

CLSURNTRQFLD

Attribute	**Description**
Name	CLSURNTRQFLD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	**Description**
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	**Description**
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	**Description**
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	**Description**
Name	MINIMUM
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

MAKER

Attribute	Description
Name	MAKER
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 12

TOP

MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 35

TOP

CHECKER

Attribute	Description
Name	CHECKER
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

MODNO

Attribute	Description
Name	MODNO
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TXNSTAT

Attribute	Description
Name	TXNSTAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

AUTHSTAT

Attribute	Description
Name	AUTHSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	1

TOP

Commission-Details

Attribute	Description	
Name	Commission-Details	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

COMPNENT

Attribute	Description	
Name	COMPNENT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNENTDESC

Attribute	Description	
Name	COMPNENTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

RULEIDENTIFICAT

Attribute	Description	
Name	RULEIDENTIFICAT	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description
Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	Description
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

STPAPPLICTION

Attribute	Description
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATTYP

Attribute	Description
Name	RATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: X,F,S,

TOP

RATCDUSGE

Attribute	Description
Name	RATCDUSGE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description
Name	SHWNINCNTRTMAINSCR

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATCD

Attribute	**Description**
Name	RATCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

ACQREQD

Attribute	**Description**
Name	ACQREQD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RULEDESC

Attribute	**Description**
Name	RULEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

EVNTDESCR

Attribute	**Description**
Name	EVNTDESCR
Datatype	String
Description	

Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	255

TOP

COLLLCCOM

Attribute	**Description**	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	**Description**	
Name	Currency-Preferences	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

CCY

Attribute	**Description**	
Name	CCY	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

COMMCALCBASIS

Attribute	**Description**	
Name	COMMCALCBASIS	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DEFRAT

Attribute	Description
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINRATE

Attribute	Description
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MAXRAT

Attribute	Description
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MINSPRD

Attribute	Description
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	Description
Name	MAXSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	I,V,T,O,

TOP

DOCSHRTDESC

Attribute	Description	
Name	DOCSHRTDESC	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

NOOFCOPIES

Attribute	Description	
Name	NOOFCOPIES	
Datatype	Number	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

NOOFORIGINALS

Attribute	Description	
Name	NOOFORIGINALS	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	5

TOP

ORGNALREQ

Attribute	Description	
Name	ORGNALREQ	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

Fft-Details

Attribute	Description
Name	Fft-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD

Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

FFTTEXTDESC

Attribute	Description
Name	FFTTEXTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	

Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

TRCERCD

Attribute	Description	
Name	TRCERCD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	15

TOP

DESC

Attribute	Description	
Name	DESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2000

TOP

REQIRED

Attribute	Description	
Name	REQIRED	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

NOFTRCERS

Attribute	Description	
Name	NOFTRCERS	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

SCHEMEDESC

Attribute	Description
Name	SCHEMEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	255

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

TAXRUL

Attribute	Description
Name	TAXRUL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

TAXCMPNT

Attribute	Description
Name	TAXCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

COMPTATIONEVNT

Attribute	Description
Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 4

TOP

TYP

Attribute	Description
Name	TYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: W,E,

TOP

Status-Details

Attribute	Description
Name	Status-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

STATUSSEQ

Attribute	Description
Name	STATUSSEQ
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

STPACCRUALS

Attribute	Description
Name	STPACCRUALS
Datatype	String
Description	

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	**Description**
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	**Description**
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	**Description**
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	Description
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4000

TOP

Status-GI-Details

Attribute	Description
Name	Status-GI-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

ACCGLDESC

Attribute	Description
Name	ACCGLDESC
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 255

TOP

ACCNTROLE

Attribute	Description
Name	ACCNTROLE
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 20

TOP

TRNSFERGL

Attribute	Description
Name	TRNSFERGL
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Control-Prod-Stat

Attribute	Description

Name	Control-Prod-Stat
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

EVNTCD

Attribute	Description
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

EVENTDESC

Attribute	Description
Name	EVENTDESC
Datatype	String
Description	Indicates the Event Description.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

Accounting-Entries

Attribute	Description
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCRLCD

Attribute	Description
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

AMTTAG

Attribute	Description

Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 35

TOP

DRCRINDICTR

Attribute	**Description**
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** enumeration / D,C

TOP

TRNCD

Attribute	**Description**
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

NETINDICTR

Attribute	**Description**
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

MISHD

Attribute	**Description**
Name	MISHD
Datatype	String
Description	Indicates MIS head.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

DESC

Attribute	Description
Name	DESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 2000

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	Attribute: minOccurs, Description: 0

TOP

CHGREQD

Attribute	Description
Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: enumeration, Description: Y,N

TOP

Role-To-Head-Mapping

Attribute	Description
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	Attribute: minOccurs, Description: 0

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	Attribute: minOccurs, Description: 0
Restrictions	Restrictions: maxLength, Description: 10

TOP

CLASDESC

Attribute	Description
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	Attribute: minOccurs, Description: 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Mapping-Details

Attribute	Description
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	Description
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ROLDESC

Attribute	Description
Name	ROLDESC
Datatype	String
Description	Indicates role description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

GLDESC

Attribute	Description
Name	GLDESC
Datatype	String
Description	Indicates GL description.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency Restrictions .
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST
Datatype	String
Description	Indicates Branch Restrictions
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD
Datatype	String

Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

CLASDESC

Attribute	**Description**
Name	CLASDESC
Datatype	String
Description	Indicates Class Code Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disalowed
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

BRNNAME

Attribute	**Description**
Name	BRNNAME
Datatype	String
Description	Indicates Branch Name
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	Restrictions	Description
	maxLength	105

TOP

Ccy-List

Attribute	Description	
Name	Ccy-List	
Datatype		
Description	Indicates Currency List Details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

TOP

BGTDLCCY

Attribute	Description	
Name	BGTDLCCY	
Datatype	String	
Description	Indicates Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

TOP

CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Indicates Currency name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255

TOP

Prod-Cust-Restrictions

Attribute	Description	
Name	Prod-Cust-Restrictions	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

TOP

CATGLIS

Attribute	Description

Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

DESCRIPTION

Attribute	**Description**
Name	DESCRIPTION
Datatype	String
Description	Indicates Customer Category Desription
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates customer ID.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

CUSTNAME

Attribute	**Description**
Name	CUSTNAME
Datatype	String
Description	Indicates customer Name.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

ALWD

Attribute	**Description**
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String

Description	Indicates MIS code.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

Product-Charges

Attribute	**Description**
Name	Product-Charges
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Charge-Details

Attribute	**Description**
Name	Charge-Details
Datatype	
Description	Includes Charge Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CHGTYP

Attribute	**Description**
Name	CHGTYP
Datatype	String
Description	Indicates Charge Type Counter Party : C Third Party : T Their Charges : E
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / C,T,E,

TOP

THRDPTYTY

Attribute	**Description**
Name	THRDPTYTY
Datatype	String
Description	Indicates Third Party Type
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 16

TOP

DRCRTYPE

Attribute	**Description**
Name	DRCRTYPE
Datatype	String
Description	Indicates Debit/Credit Debit : D Credit : C
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / D,C,

TOP

NTCNSINDI

Attribute	**Description**
Name	NTCNSINDI
Datatype	String
Description	Indicates Net Consideration Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

NETCONSPLSMINS

Attribute	**Description**
Name	NETCONSPLSMINS
Datatype	String
Description	Indicates Add/Subtract Add : A Subtract : S
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / A,S,

TOP

SWIFTQLF

Attribute	**Description**
Name	SWIFTQLF
Datatype	String
Description	Indicates Swift Qualifier

Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

SETTCCY

Attribute	**Description**
Name	SETTCCY
Datatype	String
Description	Indicates Settlement Currency
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

DFTWAIV

Attribute	**Description**
Name	DFTWAIV
Datatype	String
Description	Indicates Default Waiver Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWRULAMND

Attribute	**Description**
Name	ALWRULAMND
Datatype	String
Description	Indicates Allow Rule Amendment Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRASSOC

Attribute	**Description**
Name	AMNDAFTRASSOC
Datatype	String

Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description

Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

CAPTLIZE

Attribute	**Description**
Name	CAPTLIZE
Datatype	String
Description	Indicates Captilize Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	**Description**
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PROPREQD

Attribute	**Description**
Name	PROPREQD
Datatype	String
Description	Indicates Propagation Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

EVNTFRASSC

Attribute	Description
Name	EVNTFRASSC
Datatype	String
Description	Indicates Event For Association
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRAPPL

Attribute	Description
Name	EVNTFRAPPL
Datatype	String
Description	Indicates Event For Application
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

EVNTFRLIQ

Attribute	Description
Name	EVNTFRLIQ
Datatype	String
Description	Indicates Event For Liquidation
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 4

TOP

BASISAMNTTAG

Attribute	Description
Name	BASISAMNTTAG
Datatype	String
Description	Indicates Basis Amount Tag
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 25

TOP

BASICAMTTGDESC

Attribute	Description
Name	BASICAMTTGDESC
Datatype	String
Description	Indicates Basis Amount Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 50

TOP

ACCRREQD

Attribute	Description

Name	ACCRREQD
Datatype	String
Description	Indicates Accrual Required Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPNENTDESC

Attribute	Description
Name	COMPNENTDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 105

TOP

EVNTASSCTDESC

Attribute	Description
Name	EVNTASSCTDESC
Datatype	String
Description	Indicates Event Association Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTAPPLIDESC

Attribute	Description
Name	EVNTAPPLIDESC
Datatype	String
Description	Indicates Event Application Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

EVNTLIQDDESC

Attribute	Description
Name	EVNTLIQDDESC
Datatype	String

Description	Indicates Event Liquidation Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

RULDESC

Attribute	**Description**
Name	RULDESC
Datatype	String
Description	Indicates rule Description
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 255

TOP

FCUBS_ERROR_RESP

Attribute	**Description**
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ERROR

Attribute	**Description**
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded

TOP

ECODE

Attribute	**Description**
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	**Description**
Name	EDESC

Datatype	String
Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

2.36.4.LI-CreateProduct-Res-PK-MSG.xsd

- *FCUBS_HEADER*
  - *SOURCE*
  - *UBSCOMP*
  - *MSGID*
  - *CORRELID*
  - *USERID*
  - *BRANCH*
  - *MODULEID*
  - *SERVICE*
  - *OPERATION*
  - *SOURCE_OPERATION*
  - *SOURCE_USERID*
  - *DESTINATION*
  - *MULTITRIPID*
  - *FUNCTIONID*
  - *ACTION*
  - *MSGSTAT*
  - *PASSWORD*
  - *ADDL*
    - *PARAM*
      - *NAME*
      - *VALUE*
- *FCUBS_BODY*
  - *CHOICE*
    - *Product-Details-PK*
      - *PRDCD*
    - *Product-Details-IO*
      - *PRDCD*
      - *PRDDESC*
      - *PRDSLG*
      - *PRDRMRKS*
      - *PRDSTRTDT*
      - *PRDENDDT*
      - *PRDGRP*
      - *PRDTYP*
      - *REVLVNG*
      - *STNDRDTNR*
      - *MINTENR*
      - *MAXTENR*
      - *CSHCOLLATRL*
      - *LMTSTNRCALCTYP*
      - *REKYREQ*

REKYAMNT
REKYCCY
REKYCUSTM
REKYVALDAT
REKYMATDATE
REKYTOTLPAID
INCOTRM
TOLRNCEPOSTV
TOLRNCENEGTV
COMMCOLLEMETHD
COMMCALMETHD
RETRSPCEFLG
COMMPROCFLG
INCLDTODAT
ACRFREQ
ACRMNT
ACRDAY
CLSURDAYS
CONFRQD
ALWPRPY
EXCNGRATTYP
NRMLRTVARI
MAXRTVARI
CALQTDDYS
NUMOFDYS
LIFOFIFOCOMM
EXPIRNOTFLG
EXPIRNOTREQFLG
EXPIRNOTDYS
CLSURNTFLG
CLSURNTRQFLD
CLSURNTDAYS
APPLRULE
RLENARATIV
RTCODEPRFERD
URRPREF
PARCONALLOW
CHGCLAIM
ADVABYLOAN
LOANBRIDGEGL
LOANPRD
COLLBRIDGEGL
STATCNFLG
MINIMUM

- *LC_TYPE*
- *MAXIMUM*
- *Commission-Details*
  - *COMPNENT*
  - *RULEIDENTIFICAT*
  - *EVNT*
  - *BASISAMNTTYP*
  - *BASISAMNTCATG*
  - *SETTLMNTCCY*
  - *CHNGDRGAMNDMNT*
  - *STPAPPLICTION*
  - *RATTYP*
  - *RATCDUSGE*
  - *SHWNINCNTRTMAINSCR*
  - *RATCD*
  - *ACQREQD*
  - *COLLLCCOM*
  - *Currency-Preferences*
    - *CCY*
    - *COMMCALCBASIS*
  - *Ccy-Details*
    - *CCY*
    - *DEFRAT*
    - *MINRATE*
    - *MAXRAT*
    - *MINSPRD*
    - *MAXSPRD*
- *Document-Details*
  - *DOCMNTCD*
  - *DOCMNTTYP*
  - *NOOFCOPIES*
  - *NOOFORIGINALS*
  - *ORGNALREQ*
  - *Clause-Details*
    - *CLAUSECD*
- *Fft-Details*
  - *FFTCD*
  - *ADVCD*
  - *SINGLFFT*
- *Tracer-Details*
  - *TRCERCD*
  - *REQIRED*
  - *NOFTRCERS*
  - *STRTDAYS*

- *FREQNCY*
- *Tax-Scheme*
  - *SCHME*
  - *Tax-Details*
    - *BASISCMPNT*
    - *COMPTATIONEVNT*
    - *TYP*
- *Status-Details*
  - *STPACCRUALS*
  - *REVERSEACCRUALS*
  - *AUTOFRWD*
  - *AUTOREVERSE*
  - *COMPLETEACCRUALS*
  - *TRANSACTIONCD*
  - *STATUS*
  - *DERVTNRUL*
  - *Status-GI-Details*
    - *ACCROLEDESC*
    - *ACCGLDESC*
    - *ACCNTROLE*
    - *TRNSFERGL*
- *Product-Events*
  - *CLASCD*
  - *Event-Details*
    - *EVNTCD*
    - *Accounting-Entries*
      - *ACCRLCD*
      - *AMTTAG*
      - *DRCRINDICTR*
      - *TRNCD*
      - *NETINDICTR*
      - *MISHD*
      - *REVALPRGL*
      - *REVALLSGL*
      - *REVALRTCD*
      - *REVALTXNCD*
      - *HOLTREAT*
      - *REVALREQD*
      - *RATE_TYPE_INDICATOR*
    - *Advices*
      - *MSGTYP*
      - *GENTIME*
      - *SUPRS*
      - *PRIOR*

CHGREQD
Role-To-Head-Mapping
CLASCD
Mapping-Details
ACCTRL
ACCTHD
STAT
Branch-Ccy-Restrictions
CCYLST
BRNLST
CLASCD
Branch-List
BRNDISALOW
Ccy-List
BGTDLCCY
SOLDCCY
Prod-Cust-Restrictions
CATGLIS
CLASCD
Cust-Categories
CATGDSAW
Customers
CSTID
ALWD
Product-Fields
Field-Details
FLDNUM
FLDNAME
Product-Mis-Details
MISGRP
POOLCD
CSTCD1
CSTCD2
CSTCD4
CSTCD5
Default-Mis-Codes
MISTYP
MISCLS
MISCD
KYID
Product-Charges
Charge-Details
SETTCCY
DFTWAIV

ALWRULAMND

AMNDAFTRASSOC

ALWAMTAMND

AMNDAFTRAPPL

STPASOCIATN

ADVCHG

DISCACCRAPLB

DISCNTBASIS

DFTRULE

COMPNT

FCUBS_ERROR_RESP

ERROR

ECODE

EDESC

FCUBS_WARNING_RESP

WARNING

WCODE

WDESC

FCUBS_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

TOP

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	pattern	[a-zA-Z_0-9]*

TOP

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	**Restrictions**	**Description**
	enumeration	FCUBS,FCIS

TOP

MSGID

Attribute	Description

Name	MSGID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

CORRELID

Attribute	**Description**
Name	CORRELID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

USERID

Attribute	**Description**
Name	USERID
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: maxLength / 12; pattern / [A-Z_0-9]*

TOP

BRANCH

Attribute	**Description**
Name	BRANCH
Datatype	String
Description	
Restrictions	**Restrictions** / **Description**: length / 3; pattern / [a-zA-Z_0-9]{3}

TOP

MODULEID

Attribute	**Description**
Name	MODULEID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: nillable / true
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

SOURCE_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MULTITRIPID

Attribute	Description
Name	MULTITRIPID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8; pattern / [A-Z_0-9]*

TOP

ACTION

Attribute	Description
Name	ACTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: pattern / [a-zA-Z_0-9]*

TOP

MSGSTAT

Attribute	Description
Name	MSGSTAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	SUCCESS,WARNING,FAILURE

TOP

PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	128
	pattern	[a-zA-Z_0-9=+/]*

TOP

ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

TOP

PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

TOP

VALUE

Attribute	Description
Name	VALUE

Datatype	String
Description	

TOP

FCUBS_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

TOP

CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

TOP

Product-Details-PK

Attribute	Description
Name	Product-Details-PK
Datatype	
Description	

TOP

PRDCD

Attribute	Description	
Name	PRDCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

Product-Details-IO

Attribute	Description
Name	Product-Details-IO
Datatype	
Description	

TOP

PRDCD

Attribute	Description
Name	PRDCD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	1
Restrictions	**Restrictions**	**Description**
	maxLength	4

TOP

PRDDESC

Attribute	Description
Name	PRDDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 105

TOP

PRDSLG

Attribute	Description
Name	PRDSLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDRMRKS

Attribute	Description
Name	PRDRMRKS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

PRDSTRTDT

Attribute	Description
Name	PRDSTRTDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDENDDT

Attribute	Description
Name	PRDENDDT
Datatype	Date
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

PRDGRP

Attribute	Description
Name	PRDGRP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 6

TOP

PRDTYP

Attribute	Description
Name	PRDTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 1

TOP

REVLVNG

Attribute	Description
Name	REVLVNG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STNDRDTNR

Attribute	Description
Name	STNDRDTNR

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINTENR

Attribute	Description
Name	MINTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXTENR

Attribute	Description
Name	MAXTENR
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CSHCOLLATRL

Attribute	Description
Name	CSHCOLLATRL
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LMTSTNRCALCTYP

Attribute	Description
Name	LMTSTNRCALCTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / F,R

TOP

REKYREQ

Attribute	Description
Name	REKYREQ

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYAMNT

Attribute	**Description**
Name	REKYAMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCCY

Attribute	**Description**
Name	REKYCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYCUSTM

Attribute	**Description**
Name	REKYCUSTM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYVALDAT

Attribute	**Description**
Name	REKYVALDAT
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

REKYMATDATE

Attribute	Description
Name	REKYMATDATE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REKYTOTLPAID

Attribute	Description
Name	REKYTOTLPAID
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

INCOTRM

Attribute	Description
Name	INCOTRM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

TOLRNCEPOSTV

Attribute	Description
Name	TOLRNCEPOSTV
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

TOLRNCENEGTV

Attribute	Description
Name	TOLRNCENEGTV
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

COMMCOLLEMETHD

Attribute	Description
Name	COMMCOLLEMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: A,R,

TOP

COMMCALMETHD

Attribute	Description
Name	COMMCALMETHD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: P,N,

TOP

RETRSPCEFLG

Attribute	Description
Name	RETRSPCEFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

COMMPROCFLG

Attribute	Description
Name	COMMPROCFLG

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / I,E,

TOP

INCLDTODAT

Attribute	**Description**
Name	INCLDTODAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

ACRFREQ

Attribute	**Description**
Name	ACRFREQ
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,M,Q,H,A,

TOP

ACRMNT

Attribute	**Description**
Name	ACRMNT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

ACRDAY

Attribute	**Description**
Name	ACRDAY
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLSURDAYS

Attribute	Description
Name	CLSURDAYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CONFRQD

Attribute	Description
Name	CONFRQD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ALWPRPY

Attribute	Description
Name	ALWPRPY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXCNGRATTYP

Attribute	Description
Name	EXCNGRATTYP
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 9

TOP

NRMLRTVARI

Attribute	Description
Name	NRMLRTVARI

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

MAXRTVARI

Attribute	Description
Name	MAXRTVARI
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1

TOP

CALQTDDYS

Attribute	Description
Name	CALQTDDYS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NUMOFDYS

Attribute	Description
Name	NUMOFDYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LIFOFIFOCOMM

Attribute	Description
Name	LIFOFIFOCOMM
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / L,F

TOP

EXPIRNOTFLG

Attribute	Description
Name	EXPIRNOTFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: B,A

TOP

EXPIRNOTREQFLG

Attribute	Description
Name	EXPIRNOTREQFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

EXPIRNOTDYS

Attribute	Description
Name	EXPIRNOTDYS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

CLSURNTFLG

Attribute	Description
Name	CLSURNTFLG
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: B,A

TOP

CLSURNTRQFLD

Attribute	Description
Name	CLSURNTRQFLD
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

CLSURNTDAYS

Attribute	Description
Name	CLSURNTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

APPLRULE

Attribute	Description
Name	APPLRULE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RLENARATIV

Attribute	Description
Name	RLENARATIV
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 35

TOP

RTCODEPRFERD

Attribute	Description
Name	RTCODEPRFERD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B

TOP

URRPREF

Attribute	Description
Name	URRPREF
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: ,URR LATEST VERSION,NOTURR

TOP

PARCONALLOW

Attribute	Description
Name	PARCONALLOW
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

CHGCLAIM

Attribute	Description
Name	CHGCLAIM
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

ADVABYLOAN

Attribute	Description
Name	ADVABYLOAN
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

LOANBRIDGEGL

Attribute	Description
Name	LOANBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

LOANPRD

Attribute	Description
Name	LOANPRD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

COLLBRIDGEGL

Attribute	Description
Name	COLLBRIDGEGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STATCNFLG

Attribute	Description
Name	STATCNFLG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,M

TOP

MINIMUM

Attribute	Description
Name	MINIMUM

Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

LC_TYPE

Attribute	Description
Name	LC_TYPE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / S,U

TOP

MAXIMUM

Attribute	Description
Name	MAXIMUM
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Commission-Details

Attribute	Description
Name	Commission-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

COMPNENT

Attribute	Description
Name	COMPNENT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

RULEIDENTIFICAT

Attribute	Description
Name	RULEIDENTIFICAT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

EVNT

Attribute	Description
Name	EVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

BASISAMNTTYP

Attribute	Description
Name	BASISAMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 25

TOP

BASISAMNTCATG

Attribute	Description
Name	BASISAMNTCATG
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / N,O,D,X,

TOP

SETTLMNTCCY

Attribute	Description

Name	SETTLMNTCCY
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

CHNGDRGAMNDMNT

Attribute	**Description**
Name	CHNGDRGAMNDMNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

STPAPPLICTION

Attribute	**Description**
Name	STPAPPLICTION
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATTYP

Attribute	**Description**
Name	RATTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / X,F,S,

TOP

RATCDUSGE

Attribute	**Description**
Name	RATCDUSGE
Datatype	String
Description	

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	A,P,

TOP

SHWNINCNTRTMAINSCR

Attribute	Description	
Name	SHWNINCNTRTMAINSCR	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

RATCD

Attribute	Description	
Name	RATCD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

ACQREQD

Attribute	Description	
Name	ACQREQD	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

COLLLCCOM

Attribute	Description	
Name	COLLLCCOM	
Datatype	String	
Description		
Attributes	**Attribute**	**Description**
	minOccurs	0

Restrictions	Restrictions	Description
	enumeration	Y,N

TOP

Currency-Preferences

Attribute	Description
Name	Currency-Preferences
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCY

Attribute	Description
Name	CCY
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

COMMCALCBASIS

Attribute	Description
Name	COMMCALCBASIS
Datatype	Number
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

Ccy-Details

Attribute	Description
Name	Ccy-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CCY

Attribute	Description
Name	CCY

Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

DEFRAT

Attribute	**Description**
Name	DEFRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINRATE

Attribute	**Description**
Name	MINRATE
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXRAT

Attribute	**Description**
Name	MAXRAT
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MINSPRD

Attribute	**Description**
Name	MINSPRD
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MAXSPRD

Attribute	**Description**
Name	MAXSPRD

Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

Document-Details

Attribute	Description
Name	Document-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

DOCMNTCD

Attribute	Description
Name	DOCMNTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

DOCMNTTYP

Attribute	Description
Name	DOCMNTTYP
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,V,T,O,

TOP

NOOFCOPIES

Attribute	Description
Name	NOOFCOPIES
Datatype	Number
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

NOOFORIGINALS

Attribute	Description
Name	NOOFORIGINALS
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 5

TOP

ORGNALREQ

Attribute	Description
Name	ORGNALREQ
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

Clause-Details

Attribute	Description
Name	Clause-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

CLAUSECD

Attribute	Description
Name	CLAUSECD
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 12

TOP

Fft-Details

Attribute	Description
Name	Fft-Details

Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

FFTCD

Attribute	Description
Name	FFTCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 12

TOP

ADVCD

Attribute	Description
Name	ADVCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

SINGLFFT

Attribute	Description
Name	SINGLFFT
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Tracer-Details

Attribute	Description
Name	Tracer-Details
Datatype	
Description	
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

ORACLE

TOP

TRCERCD

Attribute	Description
Name	TRCERCD
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 15

TOP

REQIRED

Attribute	Description
Name	REQIRED
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

NOFTRCERS

Attribute	Description
Name	NOFTRCERS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

STRTDAYS

Attribute	Description
Name	STRTDAYS
Datatype	Number
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FREQNCY

Attribute	Description
Name	FREQNCY
Datatype	Number
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Tax-Scheme

Attribute	Description
Name	Tax-Scheme
Datatype	
Description	
Attributes	Attribute: minOccurs — Description: 0

TOP

SCHME

Attribute	Description
Name	SCHME
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 6

TOP

Tax-Details

Attribute	Description
Name	Tax-Details
Datatype	
Description	
Attributes	Attribute: maxOccurs — Description: unbounded Attribute: minOccurs — Description: 0

TOP

BASISCMPNT

Attribute	Description
Name	BASISCMPNT
Datatype	String
Description	
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: maxLength — Description: 25

TOP

COMPTATIONEVNT

Attribute	Description

Name	COMPTATIONEVNT
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

TYP

Attribute	**Description**
Name	TYP
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / W,E,

TOP

Status-Details

Attribute	**Description**
Name	Status-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

STPACCRUALS

Attribute	**Description**
Name	STPACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVERSEACCRUALS

Attribute	**Description**
Name	REVERSEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOFRWD

Attribute	**Description**
Name	AUTOFRWD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AUTOREVERSE

Attribute	**Description**
Name	AUTOREVERSE
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

COMPLETEACCRUALS

Attribute	**Description**
Name	COMPLETEACCRUALS
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

TRANSACTIONCD

Attribute	**Description**
Name	TRANSACTIONCD
Datatype	String
Description	
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 3

TOP

STATUS

Attribute	Description
Name	STATUS
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

DERVTNRUL

Attribute	Description
Name	DERVTNRUL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4000

TOP

Status-Gl-Details

Attribute	Description
Name	Status-Gl-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ACCROLEDESC

Attribute	Description
Name	ACCROLEDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

ACCGLDESC

Attribute	Description

Name	ACCGLDESC
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 255

TOP

ACCNTROLE

Attribute	**Description**
Name	ACCNTROLE
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 20

TOP

TRNSFERGL

Attribute	**Description**
Name	TRNSFERGL
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Product-Events

Attribute	**Description**
Name	Product-Events
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0

Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Event-Details

Attribute	**Description**
Name	Event-Details
Datatype	
Description	Indicates Event Details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

EVNTCD

Attribute	**Description**
Name	EVNTCD
Datatype	String
Description	Indicates the event code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 6

TOP

Accounting-Entries

Attribute	**Description**
Name	Accounting-Entries
Datatype	
Description	Accounting Entry Details for Events
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCRLCD

Attribute	**Description**
Name	ACCRLCD
Datatype	String
Description	Indicates the Role code.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

AMTTAG

Attribute	Description
Name	AMTTAG
Datatype	String
Description	Indicates amount tag.
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 35

TOP

DRCRINDICTR

Attribute	Description
Name	DRCRINDICTR
Datatype	String
Description	Indicates debit or credit.
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: enumeration — Description: D,C

TOP

TRNCD

Attribute	Description
Name	TRNCD
Datatype	String
Description	Indicates transaction code.
Attributes	Attribute: minOccurs — Description: 1
Restrictions	Restrictions: maxLength — Description: 3

TOP

NETINDICTR

Attribute	Description
Name	NETINDICTR
Datatype	String
Description	Indicates netting indicator.
Attributes	Attribute: minOccurs — Description: 0
Restrictions	Restrictions: enumeration — Description: Y,N

TOP

MISHD

Attribute	Description
Name	MISHD

Datatype	String
Description	Indicates MIS head.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALPRGL

Attribute	Description
Name	REVALPRGL
Datatype	String
Description	Indicates reval profit GL.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALLSGL

Attribute	Description
Name	REVALLSGL
Datatype	String
Description	Indicates reval loss GL
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

REVALRTCD

Attribute	Description
Name	REVALRTCD
Datatype	String
Description	Indicates reval rate code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 8

TOP

REVALTXNCD

Attribute	Description
Name	REVALTXNCD
Datatype	String
Description	Indicates reval transaction code.

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

HOLTREAT

Attribute	Description
Name	HOLTREAT
Datatype	String
Description	Indicates holiday treatment.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

REVALREQD

Attribute	Description
Name	REVALREQD
Datatype	String
Description	Indicates reval Required
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / Y,N

TOP

RATE_TYPE_INDICATOR

Attribute	Description
Name	RATE_TYPE_INDICATOR
Datatype	String
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / M,B,S,

TOP

Advices

Attribute	Description
Name	Advices
Datatype	
Description	Indicates Event Advices
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

ORACLE

TOP

MSGTYP

Attribute	Description
Name	MSGTYP
Datatype	String
Description	Indicates the message type.
Attributes	**Attribute** / **Description** minOccurs / 1
Restrictions	**Restrictions** / **Description** maxLength / 15

TOP

GENTIME

Attribute	Description
Name	GENTIME
Datatype	String
Description	Indicates generation time.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,A

TOP

SUPRS

Attribute	Description
Name	SUPRS
Datatype	String
Description	Indicates if any of the advices are not applicable to the contract,Then it can be suppressed.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

PRIOR

Attribute	Description
Name	PRIOR
Datatype	Number
Description	Indicates priority.
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CHGREQD

Attribute	Description

Name	CHGREQD
Datatype	String
Description	Indicates charges required.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

Role-To-Head-Mapping

Attribute	**Description**
Name	Role-To-Head-Mapping
Datatype	
Description	
Attributes	**Attribute** / **Description** minOccurs / 0

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Mapping-Details

Attribute	**Description**
Name	Mapping-Details
Datatype	
Description	Includes Mapping details
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

ACCTRL

Attribute	**Description**
Name	ACCTRL
Datatype	String
Description	Indicates accounting role.
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 20

TOP

ACCTHD

Attribute	Description
Name	ACCTHD
Datatype	String
Description	Indicates account head
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

STAT

Attribute	Description
Name	STAT
Datatype	String
Description	Indicates the status
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 4

TOP

Branch-Ccy-Restrictions

Attribute	Description
Name	Branch-Ccy-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CCYLST

Attribute	Description
Name	CCYLST
Datatype	String
Description	Indicates Currency List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

BRNLST

Attribute	Description
Name	BRNLST

Datatype	String
Description	Indicates Branch List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	**Description**
Name	CLASCD
Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

Branch-List

Attribute	**Description**
Name	Branch-List
Datatype	
Description	Indicates Branch List Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BRNDISALOW

Attribute	**Description**
Name	BRNDISALOW
Datatype	String
Description	Indicates Branch Disallowed
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Ccy-List

Attribute	**Description**
Name	Ccy-List
Datatype	
Description	Indicates Currency List
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

BGTDLCCY

Attribute	Description
Name	BGTDLCCY
Datatype	String
Description	Indicates Currency Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

SOLDCCY

Attribute	Description
Name	SOLDCCY
Datatype	String
Description	Indicates Sold Currency.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 3

TOP

Prod-Cust-Restrictions

Attribute	Description
Name	Prod-Cust-Restrictions
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

CATGLIS

Attribute	Description
Name	CATGLIS
Datatype	String
Description	Indicates Category List
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / D,A

TOP

CLASCD

Attribute	Description
Name	CLASCD

Datatype	String
Description	Indicates Class Code
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Cust-Categories

Attribute	**Description**
Name	Cust-Categories
Datatype	
Description	Indicates Customer Categories
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CATGDSAW

Attribute	**Description**
Name	CATGDSAW
Datatype	String
Description	Indicates code of customer category
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 10

TOP

Customers

Attribute	**Description**
Name	Customers
Datatype	
Description	Indicates Customers
Attributes	**Attribute** / **Description** maxOccurs / unbounded minOccurs / 0

TOP

CSTID

Attribute	**Description**
Name	CSTID
Datatype	String
Description	Indicates Customer ID
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** maxLength / 9

TOP

ALWD

Attribute	Description
Name	ALWD
Datatype	String
Description	Indicates whether customer is allowed or not.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: enumeration / A,D

TOP

Product-Fields

Attribute	Description
Name	Product-Fields
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

Field-Details

Attribute	Description
Name	Field-Details
Datatype	
Description	Indicates Field Details
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

FLDNUM

Attribute	Description
Name	FLDNUM
Datatype	Number
Description	Indicates Field Number
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

FLDNAME

Attribute	Description
Name	FLDNAME
Datatype	String
Description	Indicates Field Name

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	105

TOP

Product-Mis-Details

Attribute	Description
Name	Product-Mis-Details
Datatype	
Description	
Attributes	**Attribute** / **Description**: minOccurs / 0

TOP

MISGRP

Attribute	Description
Name	MISGRP
Datatype	String
Description	Indicates MIS group.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 12

TOP

POOLCD

Attribute	Description
Name	POOLCD
Datatype	String
Description	Indicates Pool Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD1

Attribute	Description
Name	CSTCD1
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD2

Attribute	Description
Name	CSTCD2
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD4

Attribute	Description
Name	CSTCD4
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

CSTCD5

Attribute	Description
Name	CSTCD5
Datatype	String
Description	Indicates Cost Code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 9

TOP

Default-Mis-Codes

Attribute	Description
Name	Default-Mis-Codes
Datatype	
Description	Indicates Default MIS Codes
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

MISTYP

Attribute	Description

Name	MISTYP
Datatype	String
Description	Indicates MIS type.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

MISCLS

Attribute	Description
Name	MISCLS
Datatype	String
Description	Indicates MIS class.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 100

TOP

MISCD

Attribute	Description
Name	MISCD
Datatype	String
Description	Indicates MIS code.
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

KYID

Attribute	Description
Name	KYID
Datatype	String
Description	Indicates Key ID
Attributes	**Attribute** / **Description**: minOccurs / 0
Restrictions	**Restrictions** / **Description**: maxLength / 50

TOP

Product-Charges

Attribute	Description
Name	Product-Charges
Datatype	
Description	

Attributes	Attribute	Description
	minOccurs	0

TOP

Charge-Details

Attribute	Description	
Name	Charge-Details	
Datatype		
Description	Includes Charge Details	
Attributes	**Attribute**	**Description**
	maxOccurs	unbounded
	minOccurs	0

TOP

SETTCCY

Attribute	Description	
Name	SETTCCY	
Datatype	String	
Description	Indicates Settlement Currency	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	3

TOP

DFTWAIV

Attribute	Description	
Name	DFTWAIV	
Datatype	String	
Description	Indicates Default Waiver Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

ALWRULAMND

Attribute	Description	
Name	ALWRULAMND	
Datatype	String	
Description	Indicates Allow Rule Amendment Y for Yes; N for No	
Attributes	**Attribute**	**Description**
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	enumeration	Y,N

TOP

AMNDAFTRASSOC

Attribute	Description
Name	AMNDAFTRASSOC
Datatype	String
Description	Indicates Amend After Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ALWAMTAMND

Attribute	Description
Name	ALWAMTAMND
Datatype	String
Description	Indicates Allow Amount Amendement Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

AMNDAFTRAPPL

Attribute	Description
Name	AMNDAFTRAPPL
Datatype	String
Description	Indicates Amend After Application Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

STPASOCIATN

Attribute	Description
Name	STPASOCIATN
Datatype	String
Description	Indicates Stop Association Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0

Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

ADVCHG

Attribute	Description
Name	ADVCHG
Datatype	String
Description	Indicates Advice Charge Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCACCRAPLB

Attribute	Description
Name	DISCACCRAPLB
Datatype	String
Description	Indicates Consider as Discount Y for Yes; N for No
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / Y,N

TOP

DISCNTBASIS

Attribute	Description
Name	DISCNTBASIS
Datatype	String
Description	Indicates Discount Basis Inflow : I Outflow : O
Attributes	**Attribute** / **Description** minOccurs / 0
Restrictions	**Restrictions** / **Description** enumeration / I,O,

TOP

DFTRULE

Attribute	Description
Name	DFTRULE
Datatype	String
Description	Indicates Rule

Attributes	Attribute	Description
	minOccurs	0
Restrictions	**Restrictions**	**Description**
	maxLength	10

TOP

COMPNT

Attribute	Description
Name	COMPNT
Datatype	String
Description	Indicates Component
Attributes	**Attribute** / **Description**: minOccurs / 1
Restrictions	**Restrictions** / **Description**: maxLength / 10

TOP

FCUBS_ERROR_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded; minOccurs / 0

TOP

ERROR

Attribute	Description
Name	ERROR
Datatype	
Description	
Attributes	**Attribute** / **Description**: maxOccurs / unbounded

TOP

ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

TOP

EDESC

Attribute	Description
Name	EDESC
Datatype	String

Description	

TOP

FCUBS_WARNING_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></table>

TOP

WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attributes	<table><tr><th>Attribute</th><th>Description</th></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></table>

TOP

WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

TOP

WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

TOP

Islamic Letters of Credit Service
[April] [2014]

Oracle Financial Services software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2013], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of
this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.