

Gateway Documentation - COCurrencyService  
Oracle FLEXCUBE Universal Banking  
Release FCELCM-UBS\_12.1.0.0.0  
[October][2015]



# Table Of Contents

---

<b>1. Background</b>	.....	<b>1</b>
<b>2. COCurrencyService</b>	.....	<b>2</b>
<b>  2.1.AuthorizeCurrency</b>	.....	<b>2</b>
2.1.1.CO-AuthorizeCurrency-Req-Full-MSG.xsd	.....	2
2.1.2.CO-AuthorizeCurrency-Req-IO-MSG.xsd	.....	16
2.1.3.CO-AuthorizeCurrency-Res-Full-MSG.xsd	.....	23
2.1.4.CO-AuthorizeCurrency-Res-PK-MSG.xsd	.....	39
<b>  2.2.CloseCurrency</b>	.....	<b>49</b>
2.2.1.CO-CloseCurrency-Req-Full-MSG.xsd	.....	49
2.2.2.CO-CloseCurrency-Req-IO-MSG.xsd	.....	63
2.2.3.CO-CloseCurrency-Res-Full-MSG.xsd	.....	70
2.2.4.CO-CloseCurrency-Res-PK-MSG.xsd	.....	86
<b>  2.3.CreateCurrency</b>	.....	<b>96</b>
2.3.1.CO>CreateCurrency-Req-Full-MSG.xsd	.....	96
2.3.2.CO>CreateCurrency-Req-IO-MSG.xsd	.....	110
2.3.3.CO>CreateCurrency-Res-Full-MSG.xsd	.....	122
2.3.4.CO>CreateCurrency-Res-PK-MSG.xsd	.....	138
<b>  2.4.DeleteCurrency</b>	.....	<b>152</b>
2.4.1.CO>DeleteCurrency-Req-Full-MSG.xsd	.....	152
2.4.2.CO>DeleteCurrency-Req-IO-MSG.xsd	.....	166
2.4.3.CO>DeleteCurrency-Res-Full-MSG.xsd	.....	173
2.4.4.CO>DeleteCurrency-Res-PK-MSG.xsd	.....	189
<b>  2.5.ModifyCurrency</b>	.....	<b>197</b>
2.5.1.CO>ModifyCurrency-Req-Full-MSG.xsd	.....	198
2.5.2.CO>ModifyCurrency-Req-IO-MSG.xsd	.....	212
2.5.3.CO>ModifyCurrency-Res-Full-MSG.xsd	.....	222
2.5.4.CO>ModifyCurrency-Res-PK-MSG.xsd	.....	238
<b>  2.6.QueryCurrency</b>	.....	<b>250</b>
2.6.1.CO>QueryCurrency-Req-IO-MSG.xsd	.....	250
2.6.2.CO>QueryCurrency-Res-Full-MSG.xsd	.....	257
<b>  2.7.ReopenCurrency</b>	.....	<b>273</b>
2.7.1.CO>ReopenCurrency-Req-Full-MSG.xsd	.....	273
2.7.2.CO>ReopenCurrency-Req-IO-MSG.xsd	.....	287
2.7.3.CO>ReopenCurrency-Res-Full-MSG.xsd	.....	295
2.7.4.CO>ReopenCurrency-Res-PK-MSG.xsd	.....	311

## **1. Background**

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

### **1. Inbound application integration :**

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

### **2. Outbound application integration :**

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in COCurrencyService of COMMON Module

## 2. COCurrencyService

### 2.1.AuthorizeCurrency

2.1.1.CO-AuthorizeCurrency-Req-Full-MSG.xsd

*AUTHORIZECURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*  
*ALTERNATE\_CURRENCY\_CODE*  
*EURO\_CONVERSION\_REQUIRED*  
*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*  
*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*

*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## **AUTHORIZECURRENCY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZECURRENCY_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELIID

<b>Attribute</b>	<b>Description</b>
Name	CORRELIID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELIID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeCurrency

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>	
	Name	MAKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	MAKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKERSTAMP
Datatype	string	
	Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105
minLength	1

## FLDVAL

ORACLE®

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

### 2.1.2.CO-AuthorizeCurrency-Req-IO-MSG.xsd

*AUTHORIZECURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-IO*

*CURRENCY\_CODE*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

## AUTHORIZECURRENCY\_IOPK\_REQ

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZECURRENCY_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*			
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td></tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td></tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>						
Name	SOURCE_USERID						
Datatype	string						
Description	This is the user id in the Source system who is performing the action.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## DESTINATION

<b>Attribute</b>	<b>Description</b>				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>
Name	FUNCTIONID
Datatype	string
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	
		pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

<b>Attribute</b>	<b>Description</b>				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizeCurrency

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	CURRENCY_CODE
Datatype	string
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CHECKER

Attribute	<b>Description</b>				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	<b>Description</b>				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	<b>Description</b>				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

### 2.1.3.CO-AuthorizeCurrency-Res-Full-MSG.xsd

*AUTHORIZECURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

**ORACLE®**

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
    *NAME*  
    *VALUE*  
*FCUBS\_BODY*  
    *Currency-Full*  
        *EURO\_TYPE\_CURRENCY*  
        *INDEX\_CURRENCY*  
        *INDEX\_BASE\_CURRENCY*  
        *CUTOFF\_HOUR*  
        *CUTOFF\_MINUTE*  
        *ALTERNATE\_CURRENCY\_CODE*  
        *EURO\_CONVERSION\_REQUIRED*  
        *CUTOFF\_DAYS*  
        *CURRENCY\_TYPE*  
        *CURRENCY\_CODE*  
        *CURRENCY\_NAME*  
        *COUNTRY*

*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*  
*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

## **AUTHORIZECURRENCY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZECURRENCY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message. 26

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<b>Restrictions</b>
	maxLength

<b>Restrictions</b>	<b>Description</b>
maxLength	12
pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>
Name	BRANCH
Datatype	string
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<b>Restrictions</b>
	length

<b>Restrictions</b>	<b>Description</b>
length	3
pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<b>Attribute</b>
	<b>Description</b>

<b>Attribute</b>	<b>Description</b>
minOccurs	0
nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	CHECKERSTAMP
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105
minLength	1

## FLDVAL

ORACLE®

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

<b>Attribute</b>	<b>Description</b>				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>				
maxOccurs	unbounded				

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_WARNING_RESP
Datatype	
Description	

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
<b>Attribute</b>		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

### 2.1.4.CO-AuthorizeCurrency-Res-PK-MSG.xsd

*AUTHORIZECURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

**ORACLE®**

*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Currency-PK*  
*CURRENCY\_CODE*  
*Currency-IO*  
*CURRENCY\_CODE*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*E CODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

#### **AUTHORIZECURRENCY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZECURRENCY_IOPK_RES
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELIID

<b>Attribute</b>	<b>Description</b>
Name	CORRELIID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELIID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

<b>Attribute</b>	<b>Description</b>
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	CURRENCY_CODE
Datatype	string
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CHECKER

Attribute	<b>Description</b>				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	<b>Description</b>				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	<b>Description</b>				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

## FCUBS\_ERROR\_RESP

Attribute	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

## 2.2.CloseCurrency

2.2.1.CO-CloseCurrency-Req-Full-MSG.xsd

*CLOSECURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

**ORACLE®**

*CUTOFF\_MINUTE*  
*ALTERNATE\_CURRENCY\_CODE*  
*EURO\_CONVERSION\_REQUIRED*  
*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*  
*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## **CLOSECURRENCY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CLOSECURRENCY_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CloseCurrency

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	MAKERSTAMP
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	35

## CHECKER

<b>Attribute</b>	<b>Description</b>
Name	CHECKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	CHECKERSTAMP
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105
minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

## 2.2.2.CO-CloseCurrency-Req-IO-MSG.xsd

*CLOSECURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

## *Currency-IO*

*CURRENCY\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

## **CLOSECURRENCY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CLOSECURRENCY_IOPK_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## **MSGID**

<b>Attribute</b>	<b>Description</b>
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID

Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*			
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td></tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td></tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>						
Name	SOURCE_USERID						
Datatype	string						
Description	This is the user id in the Source system who is performing the action.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## DESTINATION

<b>Attribute</b>	<b>Description</b>				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>
Name	FUNCTIONID
Datatype	string
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	
		pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

<b>Attribute</b>	<b>Description</b>				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CloseCurrency

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	CURRENCY_CODE
Datatype	string
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## MAKER

Attribute	<b>Attribute</b>	<b>Description</b>				
Name	MAKER					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

## MAKERSTAMP

Attribute	<b>Attribute</b>	<b>Description</b>				
Name	MAKERSTAMP					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

## MODNO

Attribute	<b>Attribute</b>	<b>Description</b>				
Name	MODNO					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4	
Restrictions	Description					
totalDigits	4					

## 2.2.3.CO-CloseCurrency-Res-Full-MSG.xsd

*CLOSECURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

**ORACLE®**

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*  
*INDEX\_CURRENCY*  
*INDEX\_BASE\_CURRENCY*  
*CUTOFF\_HOUR*  
*CUTOFF\_MINUTE*  
*ALTERNATE\_CURRENCY\_CODE*  
*EURO\_CONVERSION\_REQUIRED*  
*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*

*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*  
*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

## **CLOSECURRENCY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSECURRENCY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	MAKERSTAMP
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	35

## CHECKER

<b>Attribute</b>	<b>Description</b>
Name	CHECKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	CHECKERSTAMP
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105
minLength	1

## FLDVAL

ORACLE®

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

<b>Attribute</b>	<b>Description</b>				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>				
maxOccurs	unbounded				

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_WARNING_RESP
Datatype	
Description	

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
<b>Attribute</b>		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.2.4.CO-CloseCurrency-Res-PK-MSG.xsd

*CLOSECURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

**ORACLE®**

*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Currency-PK*  
*CURRENCY\_CODE*  
*Currency-IO*  
*CURRENCY\_CODE*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

## **CLOSECURRENCY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSECURRENCY_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<b>Restrictions</b>
	maxLength

<b>Restrictions</b>	<b>Description</b>
maxLength	12
pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>
Name	BRANCH
Datatype	string
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<b>Restrictions</b>
	length

<b>Restrictions</b>	<b>Description</b>
length	3
pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<b>Attribute</b>
	<b>Description</b>

<b>Attribute</b>	<b>Description</b>
minOccurs	0
nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

<b>Attribute</b>	<b>Description</b>
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	CURRENCY_CODE
Datatype	string
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## MAKER

Attribute	<b>Description</b>				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	<b>Description</b>				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>35</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	<b>Description</b>				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>4</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

## FCUBS\_ERROR\_RESP

Attribute	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

## 2.3.CreateCurrency

2.3.1.CO-CREATECURRENCY-Req-Full-MSG.xsd

*CREATECURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*  
*ALTERNATE\_CURRENCY\_CODE*  
*EURO\_CONVERSION\_REQUIRED*  
*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*  
*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## CREATECURRENCY\_FSFS\_REQ

Attribute	Description
Name	CREATECURRENCY_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<b>Restrictions</b>
	maxLength

<b>Restrictions</b>	<b>Description</b>
maxLength	12
pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>
Name	BRANCH
Datatype	string
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<b>Restrictions</b>
	length

<b>Restrictions</b>	<b>Description</b>
length	3
pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<b>Attribute</b>
	<b>Description</b>

<b>Attribute</b>	<b>Description</b>
minOccurs	0
nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateCurrency

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <td><b>Description</b></td> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
Attribute	
	<b>Attribute</b>
	<b>Description</b>
	minOccurs
	0
Restrictions	
	<b>Restrictions</b>
	<b>Description</b>
	maxLength
	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
Attribute	
	<b>Attribute</b>
	<b>Description</b>
	minOccurs
	0
Restrictions	
	<b>Restrictions</b>
	<b>Description</b>
	maxLength
	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
Attribute	
	<b>Attribute</b>
	<b>Description</b>
	minOccurs
	0
	maxOccurs
	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
Restrictions	
	<b>Restrictions</b>
	<b>Description</b>
	maxLength
	105
	minLength
	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

### 2.3.2.CO-Currency-Req-IO-MSG.xsd

*CREATECURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

### *Currency-IO*

*EURO\_TYPE\_CURRENCY*  
*INDEX\_CURRENCY*  
*INDEX\_BASE\_CURRENCY*  
*CUTOFF\_HOUR*  
*CUTOFF\_MINUTE*  
*ALTERNATE\_CURRENCY\_CODE*  
*EURO\_CONVERSION\_REQUIRED*  
*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*

### *Currency-Country*

*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## **CREATECURRENCY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CREATECURRENCY_IOPK_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateCurrency

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <td><b>Attribute</b></td> <td><b>Description</b></td> </tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <tr> <td><b>Restrictions</b></td> <td><b>Description</b></td> </tr> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <td><b>Attribute</b></td> <td><b>Description</b></td> </tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

## Currency-Country

<b>Attribute</b>	<b>Description</b>							
Name	Currency-Country							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	COUNTRY_CODE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>					
Name	COUNTRY_DESCRIPTION					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	105
<b>Restrictions</b>	<b>Description</b>					
maxLength	105					

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>						
Name	FLDNAM						
Datatype	string						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	105	minLength	1
<b>Restrictions</b>	<b>Description</b>						
maxLength	105						
minLength	1						

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

### 2.3.3.CO-Currency-Res-Full-MSG.xsd

*CREATECURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CREATECURRENCY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATECURRENCY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>

**ORACLE®**

Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description							
Name	MSGID							
Datatype	string							
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description	
Name	USERID	

Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description					
Name	EURO_TYPE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>		Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description					
enumeration	E,I,O,C					

## INDEX\_CURRENCY

Attribute	Description					
Name	INDEX_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		Restrictions	Description	enumeration	Y,N
Restrictions	Description					
enumeration	Y,N					

## INDEX\_BASE\_CURRENCY

Attribute	Description					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## EURO\_CONVERSION\_REQUIRED

Attribute	<b>Description</b>				
Name	EURO_CONVERSION_REQUIRED				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## CUTOFF\_DAYS

Attribute	Description				
Name	CUTOFF_DAYS				
Datatype	decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CURRENCY\_TYPE

Attribute	Description				
Name	CURRENCY_TYPE				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_NAME

Attribute	Description				
Name	CURRENCY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## COUNTRY

Attribute	Description
Name	COUNTRY

Datatype	string					
Description						
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## CURRENCY\_DECIMALS

Attribute	Description					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

Attribute	Description					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </table>	Restrictions	Description	enumeration	T,U,D,R,	
Restrictions	Description					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

Attribute	Description					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	MAKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
	Name	MODNO
Datatype	decimal	
	Description	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	4	

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_CODE	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0
Restrictions	Description						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## ERROR

<b>Attribute</b>	<b>Description</b>					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

2.3.4.CO-Currency-Res-PK-MSG.xsd

*CREATECURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

**ORACLE®**

*NAME*  
*VALUE*

*FCUBS\_BODY*

*Currency-PK*

*CURRENCY\_CODE*

*Currency-IO*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

**WARNING****WCODE****WDESC****CREATECURRENCY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATECURRENCY_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

**MSGID**

<b>Attribute</b>	<b>Description</b>
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*			
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td></tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td></tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

Attribute	Description							
Name	SOURCE_USERID							
Datatype	string							
Description	This is the user id in the Source system who is performing the action.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							

## DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	string					
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## MULTITRIPID

Attribute	Description					
Name	MULTITRIPID					
Datatype	string					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	
		pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

<b>Attribute</b>	<b>Description</b>				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

<b>Attribute</b>	<b>Description</b>
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	CURRENCY_CODE
Datatype	string
Description	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>E,I,O,C</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

Attribute	Description				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	Description				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	Description
-----------	-------------

Name	CUTOFF_HOUR	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CUTOFF\_MINUTE

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_MINUTE	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## ALTERNATE\_CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ALTERNATE_CURRENCY_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## EURO\_CONVERSION\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	EURO_CONVERSION_REQUIRED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>
Name	CUTOFF_DAYS
Datatype	decimal
Description	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	105

## COUNTRY

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_DECIMALS

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>T,U,D,R,</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	T,U,D,R,
<b>Restrictions</b>	<b>Description</b>					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## Currency-Country

<b>Attribute</b>	<b>Description</b>							
Name	Currency-Country							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	COUNTRY_CODE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

## COUNTRY\_DESCRIPTION

Attribute	Description					
Name	COUNTRY_DESCRIPTION					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105
Restrictions	Description					
maxLength	105					

## UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	string							
Description	Indicates Field Name							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description							
maxLength	105							
minLength	1							

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
Description	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Description	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Description	maxOccurs	unbounded

## WARNING

ORACLE®

<b>Attribute</b>	<b>Description</b>				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>				
maxOccurs	unbounded				

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.4.DeleteCurrency

2.4.1.CO-DeleteCurrency-Req-Full-MSG.xsd

*DELETECURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

**ORACLE®**

## *UDFDETAILS*

*FLDNAM*

*FLDVAL*

## **DELETECURRENCY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETECURRENCY_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## **MSGID**

<b>Attribute</b>	<b>Description</b>
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*			
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td></tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td></tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>						
Name	SOURCE_USERID						
Datatype	string						
Description	This is the user id in the Source system who is performing the action.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## DESTINATION

<b>Attribute</b>	<b>Description</b>				
Name	DESTINATION				
Datatype	string				
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>
Name	FUNCTIONID
Datatype	string
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	8	
		pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
		pattern
		[a-zA-Z_0-9=+/*]

<b>Attribute</b>	<b>Description</b>				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeleteCurrency

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

<b>Attribute</b>	<b>Description</b>
Name	EURO_TYPE_CURRENCY
Datatype	string
Description	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	E,I,O,C	

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	INDEX_CURRENCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N

## INDEX\_BASE\_CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	INDEX_BASE_CURRENCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CUTOFF\_HOUR

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_HOUR	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22

## CUTOFF\_MINUTE

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_MINUTE	
Datatype	decimal	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	22	

## ALTERNATE\_CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	ALTERNATE_CURRENCY_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## EURO\_CONVERSION\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	EURO_CONVERSION_REQUIRED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_DAYS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_CODE

Attribute	Description					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

## CURRENCY\_NAME

Attribute	Description					
Name	CURRENCY_NAME					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	105
Restrictions	Description					
maxLength	105					

## COUNTRY

Attribute	Description					
Name	COUNTRY					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	3
Restrictions	Description					
maxLength	3					

## CURRENCY\_DECIMALS

Attribute	Description					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

Attribute	Description	
-----------	-------------	--

Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>T,U,D,R,</td></tr> </tbody> </table>		Restrictions	Description	enumeration	T,U,D,R,
Restrictions	Description					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

Attribute	Description					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

## MAKER

Attribute	Description					
Name	MAKER					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>		Restrictions	Description	maxLength	12
Restrictions	Description					
maxLength	12					

## MAKERSTAMP

Attribute	Description					
Name	MAKERSTAMP					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

## CHECKER

Attribute	Description	

Name	CHECKER					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	
Restrictions	Description					
maxLength	12					

## CHECKERSTAMP

Attribute	Description					
Name	CHECKERSTAMP					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>	Restrictions	Description	maxLength	35	
Restrictions	Description					
maxLength	35					

## MODNO

Attribute	Description					
Name	MODNO					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>4</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	4	
Restrictions	Description					
totalDigits	4					

## TXNSTAT

Attribute	Description					
Name	TXNSTAT					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

## AUTHSTAT

Attribute	Description	

Name	AUTHSTAT					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	1	
Restrictions	Description					
maxLength	1					

## Currency-Country

Attribute	Description							
Name	Currency-Country							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## COUNTRY\_CODE

Attribute	Description					
Name	COUNTRY_CODE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## COUNTRY\_DESCRIPTION

Attribute	Description					
Name	COUNTRY_DESCRIPTION					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	
Restrictions	Description					
maxLength	105					

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>						
Name	FLDNAM						
Datatype	string						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	105	minLength	1
<b>Restrictions</b>	<b>Description</b>						
maxLength	105						
minLength	1						

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

### 2.4.2.CO-DeleteCurrency-Req-IO-MSG.xsd

*DELETECURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-IO*

*CURRENCY\_CODE*

## **DELETECURRENCY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETECURRENCY_IOPK_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteCurrency

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

2.4.3.CO-DeleteCurrency-Res-Full-MSG.xsd

*DELETECURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

*COUNTRY\_CODE*

**ORACLE®**

## *COUNTRY\_DESCRIPTION*

### *UDFDETAILS*

*FLDNAM*

*FLDVAL*

### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

### *FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **DELETECURRENCY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETECURRENCY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description					
Name	EURO_TYPE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>		Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description					
enumeration	E,I,O,C					

## INDEX\_CURRENCY

Attribute	Description					
Name	INDEX_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		Restrictions	Description	enumeration	Y,N
Restrictions	Description					
enumeration	Y,N					

## INDEX\_BASE\_CURRENCY

Attribute	Description					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## EURO\_CONVERSION\_REQUIRED

Attribute	<b>Description</b>				
Name	EURO_CONVERSION_REQUIRED				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_NAME					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	105
<b>Restrictions</b>	<b>Description</b>					
maxLength	105					

## COUNTRY

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY	

Datatype	string					
Description						
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## CURRENCY\_DECIMALS

Attribute	Description					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

Attribute	Description					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </table>	Restrictions	Description	enumeration	T,U,D,R,	
Restrictions	Description					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

Attribute	Description					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	MAKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
	Name	MODNO
Datatype	decimal	
	Description	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	4	

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_CODE	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0
Restrictions	Description						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## ERROR

<b>Attribute</b>	<b>Description</b>					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

2.4.4.CO-DeleteCurrency-Res-PK-MSG.xsd

*DELETECURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

**ORACLE®**

*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Currency-PK*  
*CURRENCY\_CODE*  
*Currency-IO*  
*CURRENCY\_CODE*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*E CODE*  
*E DESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*W CODE*  
*W DESC*

## **DELETECURRENCY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETECURRENCY_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>

Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description							
Name	MSGID							
Datatype	string							
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description	
Name	USERID	

Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

Attribute	Description
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	
Attribute	Description
	minOccurs
	0
	maxOccurs
	unbounded

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	
Attribute	Description
	maxOccurs
	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.5.ModifyCurrency

ORACLE®

## 2.5.1.CO-ModifyCurrency-Req-Full-MSG.xsd

*MODIFYCURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

ORACLE®

*CUTOFF\_DAYS*  
*CURRENCY\_TYPE*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*Currency-Country*

*COUNTRY\_CODE*  
*COUNTRY\_DESCRIPTION*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## **MODIFYCURRENCY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYCURRENCY_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>					
Name	OPERATION					
Datatype	string					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>					
pattern	[a-zA-Z_0-9]*					

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_OPERATION							
Datatype	string							
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_USERID							
Datatype	string							
Description	This is the user id in the Source system who is performing the action.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>					
Name	MSGSTAT					
Datatype	string					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	SUCCESS,WARNING,FAILURE
<b>Restrictions</b>	<b>Description</b>					
enumeration	SUCCESS,WARNING,FAILURE					

## PASSWORD

<b>Attribute</b>	<b>Description</b>							
Name	PASSWORD							
Datatype	string							
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
<b>Restrictions</b>	<b>Description</b>							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

## ADDL

<b>Attribute</b>	<b>Description</b>					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					

## PARAM

<b>Attribute</b>	<b>Description</b>							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifyCurrency

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>E,I,O,C</td></tr></tbody></table>	Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

Attribute	Description				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

ORACLE®

<b>Attribute</b>	<b>Description</b>					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CUTOFF\_HOUR

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_HOUR					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CUTOFF\_MINUTE

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_MINUTE					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## ALTERNATE\_CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	ALTERNATE_CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	10
<b>Restrictions</b>	<b>Description</b>					
maxLength	10					

## EURO\_CONVERSION\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	EURO_CONVERSION_REQUIRED	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_DAYS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## COUNTRY

<b>Attribute</b>	<b>Description</b>				
Name	COUNTRY				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_DECIMALS

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_DECIMALS				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CURRENCY\_ROUND\_RULE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_ROUND_RULE				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	T,U,D,R,
Restrictions	Description				
enumeration	T,U,D,R,				

## CURRENCY\_ROUND\_UNIT

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_ROUND_UNIT				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

<b>Attribute</b>	<b>Description</b>				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>4</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	totalDigits	4
<b>Restrictions</b>	<b>Description</b>				
totalDigits	4				

## TXNSTAT

<b>Attribute</b>	<b>Description</b>				
Name	TXNSTAT				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	1
<b>Restrictions</b>	<b>Description</b>				
maxLength	1				

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>				
Name	AUTHSTAT				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	1
<b>Restrictions</b>	<b>Description</b>				
maxLength	1				

## Currency-Country

<b>Attribute</b>	<b>Description</b>						
Name	Currency-Country						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE

Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>3</td></tr> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## COUNTRY\_DESCRIPTION

Attribute	Description					
Name	COUNTRY_DESCRIPTION					
Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105	
Restrictions	Description					
maxLength	105					

## UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	string							
Description	Indicates Field Name							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

## FLDVAL

Attribute	Description					
Name	FLDVAL					
Datatype	string					
Description	Indicates Field Value					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	
Restrictions	Description
maxLength	255
minLength	0

## 2.5.2.CO-ModifyCurrency-Req-IO-MSG.xsd

*MODIFYCURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-IO*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*EURO\_CONVERSION\_REQUIRED*

*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

#### **MODIFYCURRENCY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYCURRENCY_IOPK_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	<b>Description</b>							
Name	BRANCH							
Datatype	string							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

## MODULEID

Attribute	<b>Description</b>							
Name	MODULEID							
Datatype	string							
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							

## SERVICE

Attribute	<b>Description</b>					
Name	SERVICE					
Datatype	string					
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	nillable	true
Attribute	Description					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## OPERATION

Attribute	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifyCurrency

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## INDEX\_CURRENCY

Attribute	Description				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	Description				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## EURO\_CONVERSION\_REQUIRED

Attribute	Description				
Name	EURO_CONVERSION_REQUIRED				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>				
enumeration	Y,N				

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_NAME					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	105
<b>Restrictions</b>	<b>Description</b>					
maxLength	105					

## COUNTRY

<b>Attribute</b>	<b>Description</b>					
Name	COUNTRY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_DECIMALS

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

Attribute	Description					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>T,U,D,R,</td></tr></tbody></table>		Restrictions	Description	enumeration	T,U,D,R,
Restrictions	Description					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

Attribute	Description					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		Restrictions	Description	totalDigits	22
Restrictions	Description					
totalDigits	22					

## MAKER

Attribute	Description					
Name	MAKER					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>		Restrictions	Description	maxLength	12
Restrictions	Description					
maxLength	12					

## MAKERSTAMP

Attribute	Description					
Name	MAKERSTAMP					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>		Restrictions	Description	maxLength	35
Restrictions	Description					
maxLength	35					

<b>Attribute</b>	<b>Description</b>						
Name	UDFDETAILS						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## FLDNAM

<b>Attribute</b>	<b>Description</b>						
Name	FLDNAM						
Datatype	string						
Description	Indicates Field Name						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	105	minLength	1
<b>Restrictions</b>	<b>Description</b>						
maxLength	105						
minLength	1						

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

2.5.3.CO-ModifyCurrency-Res-Full-MSG.xsd

*MODIFYCURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

**ORACLE®**

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYCURRENCY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYCURRENCY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>					
Name	OPERATION					
Datatype	string					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>					
pattern	[a-zA-Z_0-9]*					

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_OPERATION							
Datatype	string							
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_USERID							
Datatype	string							
Description	This is the user id in the Source system who is performing the action.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>					
Name	MSGSTAT					
Datatype	string					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	SUCCESS,WARNING,FAILURE
<b>Restrictions</b>	<b>Description</b>					
enumeration	SUCCESS,WARNING,FAILURE					

## PASSWORD

<b>Attribute</b>	<b>Description</b>							
Name	PASSWORD							
Datatype	string							
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
<b>Restrictions</b>	<b>Description</b>							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

## ADDL

<b>Attribute</b>	<b>Description</b>					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					

## PARAM

<b>Attribute</b>	<b>Description</b>							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>E,I,O,C</td></tr></tbody></table>	Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

Attribute	Description				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

ORACLE®

<b>Attribute</b>	<b>Description</b>					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CUTOFF\_HOUR

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_HOUR					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CUTOFF\_MINUTE

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_MINUTE					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## ALTERNATE\_CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	ALTERNATE_CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	10
<b>Restrictions</b>	<b>Description</b>					
maxLength	10					

## EURO\_CONVERSION\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	EURO_CONVERSION_REQUIRED	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	Y,N	

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>	
Name	CUTOFF_DAYS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_CODE	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	
	maxLength	3

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	105
<b>Restrictions</b>	<b>Description</b>				
maxLength	105				

## COUNTRY

<b>Attribute</b>	<b>Description</b>				
Name	COUNTRY				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## CURRENCY\_DECIMALS

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_DECIMALS				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>				
totalDigits	22				

## CURRENCY\_ROUND\_RULE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_ROUND_RULE				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	T,U,D,R,
<b>Restrictions</b>	<b>Description</b>				
enumeration	T,U,D,R,				

## CURRENCY\_ROUND\_UNIT

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_ROUND_UNIT				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>				
totalDigits	22				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

<b>Attribute</b>	<b>Description</b>				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>4</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	totalDigits	4
<b>Restrictions</b>	<b>Description</b>				
totalDigits	4				

## TXNSTAT

<b>Attribute</b>	<b>Description</b>				
Name	TXNSTAT				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	1
<b>Restrictions</b>	<b>Description</b>				
maxLength	1				

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>				
Name	AUTHSTAT				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>1</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	1
<b>Restrictions</b>	<b>Description</b>				
maxLength	1				

## Currency-Country

<b>Attribute</b>	<b>Description</b>						
Name	Currency-Country						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE

Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>3</td></tr> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## COUNTRY\_DESCRIPTION

Attribute	Description					
Name	COUNTRY_DESCRIPTION					
Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> </table>	Restrictions	Description	maxLength	105	
Restrictions	Description					
maxLength	105					

## UDFDETAILS

Attribute	Description							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded	
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## FLDNAM

Attribute	Description							
Name	FLDNAM							
Datatype	string							
Description	Indicates Field Name							
Restrictions	<table border="1"> <tr> <th>Restrictions</th><th>Description</th></tr> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </table>	Restrictions	Description	maxLength	105	minLength	1	
Restrictions	Description							
maxLength	105							
minLength	1							

## FLDVAL

Attribute	Description					
Name	FLDVAL					
Datatype	string					
Description	Indicates Field Value					
Attribute	<table border="1"> <tr> <th>Attribute</th><th>Description</th></tr> <tr> <td>minOccurs</td><td>0</td></tr> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0
Restrictions	Description						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## ERROR

<b>Attribute</b>	<b>Description</b>					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

2.5.4.CO-ModifyCurrency-Res-PK-MSG.xsd

*MODIFYCURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

**ORACLE®**

*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Currency-PK*  
*CURRENCY\_CODE*  
*Currency-IO*  
*INDEX\_CURRENCY*  
*INDEX\_BASE\_CURRENCY*  
*EURO\_CONVERSION\_REQUIRED*  
*CURRENCY\_CODE*  
*CURRENCY\_NAME*  
*COUNTRY*  
*CURRENCY\_DECIMALS*  
*CURRENCY\_ROUND\_RULE*  
*CURRENCY\_ROUND\_UNIT*  
*MAKER*  
*MAKERSTAMP*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

## **MODIFYCURRENCY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYCURRENCY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

<b>Attribute</b>	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## DESTINATION

<b>Attribute</b>	<b>Description</b>				
Name	DESTINATION				
Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
<b>Attribute</b>	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
<b>Restrictions</b>	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
<b>Attribute</b>	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
<b>Restrictions</b>	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
<b>Attribute</b>	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
<b>Restrictions</b>	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>				
Name	MSGSTAT				
Datatype	string				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	SUCCESS,WARNING,FAILURE
<b>Restrictions</b>	<b>Description</b>				
enumeration	SUCCESS,WARNING,FAILURE				

## PASSWORD

<b>Attribute</b>	<b>Description</b>						
Name	PASSWORD						
Datatype	string						
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
<b>Restrictions</b>	<b>Description</b>						
maxLength	128						
pattern	[a-zA-Z_0-9=+/*]						

## ADDL

<b>Attribute</b>	<b>Description</b>				
Name	ADDL				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

## PARAM

ORACLE®

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

<b>Attribute</b>	<b>Description</b>
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## INDEX\_CURRENCY

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	INDEX_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N	
Restrictions	Description					
enumeration	Y,N					

## INDEX\_BASE\_CURRENCY

Attribute	Description					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## EURO\_CONVERSION\_REQUIRED

Attribute	Description					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N	
Restrictions	Description					
enumeration	Y,N					

## CURRENCY\_CODE

Attribute	Description					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## CURRENCY\_NAME

Attribute	Description	
Name	CURRENCY_NAME	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	105	

## COUNTRY

<b>Attribute</b>	<b>Description</b>					
Name	COUNTRY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_DECIMALS

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	T,U,D,R,
<b>Restrictions</b>	<b>Description</b>					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	<b>Description</b>
	maxLength
	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	MAKERSTAMP
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	<b>Description</b>
	maxLength
	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
	minOccurs
	0
	maxOccurs
	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>	Restrictions	Description	maxLength	105	minLength	1
Restrictions	Description						
maxLength	105						
minLength	1						

## FLDVAL

Attribute	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>255</td> </tr> <tr> <td>minLength</td> <td>0</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0
Restrictions	Description						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

Attribute	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

Attribute	<b>Description</b>				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

ORACLE®

<b>Attribute</b>	<b>Description</b>						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

<b>Attribute</b>	<b>Description</b>				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>				
maxOccurs	unbounded				

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.6.QueryCurrency

2.6.1.CO-QueryCurrency-Req-IO-MSG.xsd

*QUERYCURRENCY\_IOFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

**ORACLE®**

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-IO*

*CURRENCY\_CODE*

## **QUERYCURRENCY\_IOFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	QUERYCURRENCY_IOFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description							
Name	MSGID							
Datatype	string							
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryCurrency

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

2.6.2.CO-QueryCurrency-Res-Full-MSG.xsd

*QUERYCURRENCY\_IOFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-IO*

*CURRENCY\_CODE*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

**ORACLE®**

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **QUERYCURRENCY\_IOFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	QUERYCURRENCY_IOFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>		Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description					
enumeration	FCUBS,FCIS					

## MSGID

Attribute	Description							
Name	MSGID							
Datatype	string							
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	length	3	pattern	[a-zA-Z_0-9]{3}
<b>Restrictions</b>	<b>Description</b>						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description				
enumeration	E,I,O,C				

## INDEX\_CURRENCY

Attribute	Description				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## INDEX\_BASE\_CURRENCY

Attribute	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>10</td></tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## **EURO\_CONVERSION\_REQUIRED**

<b>Attribute</b>	<b>Description</b>					
Name	EURO_CONVERSION_REQUIRED					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>					
enumeration	Y,N					

## **CUTOFF\_DAYS**

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## **CURRENCY\_TYPE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_CODE**

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## **CURRENCY\_NAME**

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_NAME	

Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 105

## COUNTRY

Attribute	Description	
Name	COUNTRY	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
		maxLength 3

## CURRENCY\_DECIMALS

Attribute	Description	
Name	CURRENCY_DECIMALS	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		totalDigits 22

## CURRENCY\_ROUND\_RULE

Attribute	Description	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
		minOccurs 0
Restrictions	<b>Restrictions</b>	<b>Description</b>
		enumeration T,U,D,R,

## CURRENCY\_ROUND\_UNIT

Attribute	Description	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>
Name	MAKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	MAKERSTAMP
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	35

## CHECKER

<b>Attribute</b>	<b>Description</b>
Name	CHECKER
Datatype	string
Description	
Attribute	<b>Attribute</b>
	<b>Description</b>
Restrictions	minOccurs
	<b>Restrictions</b>
	maxLength
	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>
Name	CHECKERSTAMP
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_CODE
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>
Name	COUNTRY_DESCRIPTION
Datatype	string
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>
Name	UDFDETAILS
Datatype	
Description	
<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>
Name	FLDNAM
Datatype	string
Description	Indicates Field Name
<b>Restrictions</b>	
<b>Restrictions</b>	<b>Description</b>
maxLength	105
minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>						
Name	FLDVAL						
Datatype	string						
Description	Indicates Field Value						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
maxOccurs	unbounded						

## ERROR

<b>Attribute</b>	<b>Description</b>				
Name	ERROR				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>				
maxOccurs	unbounded				

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_WARNING_RESP
Datatype	
Description	

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
<b>Attribute</b>		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.7.ReopenCurrency

2.7.1.CO-ReopenCurrency-Req-Full-MSG.xsd

*REOPENCURRENCY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

**ORACLE®**

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## REOPENCURRENCY\_FSFS\_REQ

Attribute	Description
Name	REOPENCURRENCY_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description

ORACLE®

Name	MSGID							
Datatype	string							
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>length</td><td>3</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	string

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## SOURCE\_USERID

Attribute	Description							
Name	SOURCE_USERID							
Datatype	string							
Description	This is the user id in the Source system who is performing the action.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							

## DESTINATION

Attribute	Description					
Name	DESTINATION					
Datatype	string					
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description					
pattern	[a-zA-Z_0-9]*					

## MULTITRIPID

Attribute	Description					
Name	MULTITRIPID					
Datatype	string					
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>				
Name	MSGSTAT				
Datatype	string				
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	SUCCESS,WARNING,FAILURE
<b>Restrictions</b>	<b>Description</b>				
enumeration	SUCCESS,WARNING,FAILURE				

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD							
Datatype	string							
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0		
Attribute	Description							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>128</td></tr> <tr> <td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr> </tbody> </table>		Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
Restrictions	Description							
maxLength	128							
pattern	[a-zA-Z_0-9=+/*]							

## ADDL

Attribute	Description					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

## PARAM

Attribute	Description							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th><th>Description</th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of ReopenCurrency	

## Currency-Full

<b>Attribute</b>	<b>Description</b>
Name	Currency-Full
Datatype	
Description	

## **EURO\_TYPE\_CURRENCY**

<b>Attribute</b>	<b>Description</b>				
Name	EURO_TYPE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	E,I,O,C
<b>Restrictions</b>	<b>Description</b>				
enumeration	E,I,O,C				

## **INDEX\_CURRENCY**

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	Y,N
<b>Restrictions</b>	<b>Description</b>				
enumeration	Y,N				

## **INDEX\_BASE\_CURRENCY**

<b>Attribute</b>	<b>Description</b>				
Name	INDEX_BASE_CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## **CUTOFF\_HOUR**

<b>Attribute</b>	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>totalDigits</td><td>22</td></tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## EURO\_CONVERSION\_REQUIRED

Attribute	<b>Description</b>				
Name	EURO_CONVERSION_REQUIRED				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## CUTOFF\_DAYS

Attribute	<b>Description</b>				
Name	CUTOFF_DAYS				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CURRENCY\_TYPE

Attribute	Description				
Name	CURRENCY_TYPE				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_NAME

Attribute	Description				
Name	CURRENCY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

## COUNTRY

Attribute	Description				
Name	COUNTRY				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CURRENCY\_DECIMALS

Attribute	Description
Name	CURRENCY_DECIMALS
Datatype	decimal
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## CURRENCY\_ROUND\_RULE

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_ROUND_RULE	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	T,U,D,R,

## CURRENCY\_ROUND\_UNIT

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY_ROUND_UNIT	
Datatype	decimal	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
	Name	MODNO
Datatype	decimal	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
	Name	TXNSTAT
Datatype	string	
	Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_CODE	
Datatype	string	
Description		
Attribute		
Restrictions	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_DESCRIPTION	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	105	

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>							
Name	UDFDETAILS							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## FLDNAM

<b>Attribute</b>	<b>Description</b>							
Name	FLDNAM							
Datatype	string							
Description	Indicates Field Name							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>105</td></tr> <tr> <td>minLength</td><td>1</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	105	minLength	1
<b>Restrictions</b>	<b>Description</b>							
maxLength	105							
minLength	1							

## FLDVAL

<b>Attribute</b>	<b>Description</b>							
Name	FLDVAL							
Datatype	string							
Description	Indicates Field Value							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	255	minLength	0
<b>Restrictions</b>	<b>Description</b>							
maxLength	255							
minLength	0							

## 2.7.2.CO-ReopenCurrency-Req-IO-MSG.xsd

*REOPENCURRENCY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

**ORACLE®**

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Currency-IO*  
*CURRENCY\_CODE*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*

#### **REOPENCURRENCY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	REOPENCURRENCY_IOPK_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

<b>Attribute</b>	<b>Description</b>				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>nillable</td><td>true</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.
Restrictions	<b>Restrictions</b>
	maxLength

<b>Restrictions</b>	<b>Description</b>
maxLength	12
pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>
Name	BRANCH
Datatype	string
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.
Restrictions	<b>Restrictions</b>
	length

<b>Restrictions</b>	<b>Description</b>
length	3
pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.
Attribute	<b>Attribute</b>
	<b>Description</b>

<b>Attribute</b>	<b>Description</b>
minOccurs	0
nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string				
Description	This is the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0		
Attribute	Description						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>8</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

Attribute	Description
Name	ACTION
Datatype	string
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

<b>Attribute</b>	
<b>Attribute</b>	<b>Description</b>
minOccurs	0
maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenCurrency

## Currency-IO

<b>Attribute</b>	<b>Description</b>
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <tr> <td><b>Restrictions</b></td> <td><b>Description</b></td> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>				
maxLength	3				

## MAKER

<b>Attribute</b>	<b>Description</b>				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <td><b>Attribute</b></td> <td><b>Description</b></td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <tr> <td><b>Restrictions</b></td> <td><b>Description</b></td> </tr> <tr> <td>maxLength</td> <td>12</td> </tr> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	12
<b>Restrictions</b>	<b>Description</b>				
maxLength	12				

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
Restrictions	Description				
maxLength	35				

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	decimal				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>4</td></tr></tbody></table>	Restrictions	Description	totalDigits	4
Restrictions	Description				
totalDigits	4				

2.7.3.CO-ReopenCurrency-Res-Full-MSG.xsd

*REOPENCURRENCY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Currency-Full*

*EURO\_TYPE\_CURRENCY*

*INDEX\_CURRENCY*

*INDEX\_BASE\_CURRENCY*

*CUTOFF\_HOUR*

*CUTOFF\_MINUTE*

*ALTERNATE\_CURRENCY\_CODE*

*EURO\_CONVERSION\_REQUIRED*

*CUTOFF\_DAYS*

*CURRENCY\_TYPE*

*CURRENCY\_CODE*

*CURRENCY\_NAME*

*COUNTRY*

*CURRENCY\_DECIMALS*

*CURRENCY\_ROUND\_RULE*

*CURRENCY\_ROUND\_UNIT*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Currency-Country*

**ORACLE®**

*COUNTRY\_CODE*

*COUNTRY\_DESCRIPTION*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENCURRENCY\_FSFS\_RES

Attribute	Description
Name	REOPENCURRENCY_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>enumeration</td><td>FCUBS,FCIS</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	enumeration	FCUBS,FCIS
<b>Restrictions</b>	<b>Description</b>				
enumeration	FCUBS,FCIS				

## MSGID

<b>Attribute</b>	<b>Description</b>						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## CORRELID

<b>Attribute</b>	<b>Description</b>						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>						
pattern	[a-zA-Z_0-9]*						

## USERID

<b>Attribute</b>	<b>Description</b>
Name	USERID
Datatype	string
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>
Name	OPERATION
Datatype	string
Description	This is the operation of the service which is being invoked. This field is case-sensitive.

Attribute	<b>Attribute</b>		<b>Description</b>
	nillable	true	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>				
Name	MULTITRIPID				
Datatype	string				
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>						
Name	FUNCTIONID						
Datatype	string						
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>						
minOccurs	0						
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>8</td></tr> <tr> <td>pattern</td><td>[A-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	maxLength	8	pattern	[A-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>						
maxLength	8						
pattern	[A-Z_0-9]*						

## ACTION

<b>Attribute</b>	<b>Description</b>				
Name	ACTION				
Datatype	string				
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.				
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>	<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>
Name	MSGSTAT
Datatype	string
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Currency-Full

Attribute	Description
Name	Currency-Full
Datatype	
Description	

## EURO\_TYPE\_CURRENCY

Attribute	Description					
Name	EURO_TYPE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>E,I,O,C</td></tr> </tbody> </table>		Restrictions	Description	enumeration	E,I,O,C
Restrictions	Description					
enumeration	E,I,O,C					

## INDEX\_CURRENCY

Attribute	Description					
Name	INDEX_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td><td>Y,N</td></tr> </tbody> </table>		Restrictions	Description	enumeration	Y,N
Restrictions	Description					
enumeration	Y,N					

## INDEX\_BASE\_CURRENCY

Attribute	Description					
Name	INDEX_BASE_CURRENCY					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>3</td></tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## CUTOFF\_HOUR

Attribute	<b>Description</b>				
Name	CUTOFF_HOUR				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## CUTOFF\_MINUTE

Attribute	<b>Description</b>				
Name	CUTOFF_MINUTE				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## ALTERNATE\_CURRENCY\_CODE

Attribute	<b>Description</b>				
Name	ALTERNATE_CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## EURO\_CONVERSION\_REQUIRED

Attribute	<b>Description</b>				
Name	EURO_CONVERSION_REQUIRED				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>Y,N</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## CUTOFF\_DAYS

<b>Attribute</b>	<b>Description</b>					
Name	CUTOFF_DAYS					
Datatype	decimal					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	22
<b>Restrictions</b>	<b>Description</b>					
totalDigits	22					

## CURRENCY\_TYPE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_TYPE					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_CODE

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_CODE					
Datatype	string					
Description						
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	3
<b>Restrictions</b>	<b>Description</b>					
maxLength	3					

## CURRENCY\_NAME

<b>Attribute</b>	<b>Description</b>					
Name	CURRENCY_NAME					
Datatype	string					
Description						
Attribute	<table border="1"><thead><tr><th><b>Attribute</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>		<b>Restrictions</b>	<b>Description</b>	maxLength	105
<b>Restrictions</b>	<b>Description</b>					
maxLength	105					

## COUNTRY

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY	

Datatype	string					
Description						
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>maxLength</td> <td>3</td> </tr> </table>	Restrictions	Description	maxLength	3	
Restrictions	Description					
maxLength	3					

## CURRENCY\_DECIMALS

Attribute	Description					
Name	CURRENCY_DECIMALS					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## CURRENCY\_ROUND\_RULE

Attribute	Description					
Name	CURRENCY_ROUND_RULE					
Datatype	string					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>enumeration</td> <td>T,U,D,R,</td> </tr> </table>	Restrictions	Description	enumeration	T,U,D,R,	
Restrictions	Description					
enumeration	T,U,D,R,					

## CURRENCY\_ROUND\_UNIT

Attribute	Description					
Name	CURRENCY_ROUND_UNIT					
Datatype	decimal					
Description						
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>		Attribute	Description	minOccurs	0
Attribute	Description					
minOccurs	0					
Restrictions	<table border="1"> <tr> <th>Restrictions</th> <th>Description</th> </tr> <tr> <td>totalDigits</td> <td>22</td> </tr> </table>	Restrictions	Description	totalDigits	22	
Restrictions	Description					
totalDigits	22					

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	MAKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKER
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
	Name	CHECKERSTAMP
Datatype	string	
	Description	
Attribute		
	<b>Attribute</b>	<b>Description</b>
Restrictions	minOccurs	0
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
	Name	MODNO
Datatype	decimal	
	Description	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	4	

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	1

## Currency-Country

<b>Attribute</b>	<b>Description</b>	
Name	Currency-Country	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## COUNTRY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_CODE	
Datatype	string	
Description		

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	3	

## COUNTRY\_DESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	COUNTRY_DESCRIPTION	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	105

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>maxLength</td><td>255</td></tr> <tr> <td>minLength</td><td>0</td></tr> </tbody> </table>	Restrictions	Description	maxLength	255	minLength	0
Restrictions	Description						
maxLength	255						
minLength	0						

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## ERROR

<b>Attribute</b>	<b>Description</b>					
Name	ERROR					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	maxOccurs	unbounded
Attribute	Description					
maxOccurs	unbounded					

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_WARNING_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description							
minOccurs	0							
maxOccurs	unbounded							

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		

ORACLE®

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

2.7.4.CO-ReopenCurrency-Res-PK-MSG.xsd

*REOPENCURRENCY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

**ORACLE®**

<i>NAME</i>
<i>VALUE</i>
<i>FCUBS_BODY</i>
<i>Currency-PK</i>
<i>CURRENCY_CODE</i>
<i>Currency-IO</i>
<i>CURRENCY_CODE</i>
<i>MAKER</i>
<i>MAKERSTAMP</i>
<i>MODNO</i>
<i>FCUBS_ERROR_RESP</i>
<i>ERROR</i>
<i>E CODE</i>
<i>E DESC</i>
<i>FCUBS_WARNING_RESP</i>
<i>WARNING</i>
<i>W CODE</i>
<i>W DESC</i>

## REOPENCURRENCY\_IOPK\_RES

<b>Attribute</b>	<b>Description</b>
Name	REOPENCURRENCY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td></tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td></tr> <tr> <td>nillable</td> <td>true</td></tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th><th>Description</th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## USERID

<b>Attribute</b>	<b>Description</b>						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

<b>Attribute</b>	<b>Description</b>						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

<b>Attribute</b>	<b>Description</b>						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

<b>Attribute</b>	<b>Description</b>				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## OPERATION

<b>Attribute</b>	<b>Description</b>					
Name	OPERATION					
Datatype	string					
Description	This is the operation of the service which is being invoked. This field is case-sensitive.					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	nillable	true
<b>Attribute</b>	<b>Description</b>					
nillable	true					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>					
pattern	[a-zA-Z_0-9]*					

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_OPERATION							
Datatype	string							
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*		
<b>Restrictions</b>	<b>Description</b>							
pattern	[a-zA-Z_0-9]*							

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>							
Name	SOURCE_USERID							
Datatype	string							
Description	This is the user id in the Source system who is performing the action.							
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	nillable	true
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
nillable	true							

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	pattern	[a-zA-Z_0-9]*	

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th><th><b>Description</b></th></tr> </thead> <tbody> <tr> <td>pattern</td><td>[a-zA-Z_0-9]*</td></tr> </tbody> </table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

## MSGSTAT

<b>Attribute</b>	<b>Description</b>					
Name	MSGSTAT					
Datatype	string					
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".					
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>SUCCESS,WARNING,FAILURE</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	enumeration	SUCCESS,WARNING,FAILURE
<b>Restrictions</b>	<b>Description</b>					
enumeration	SUCCESS,WARNING,FAILURE					

## PASSWORD

<b>Attribute</b>	<b>Description</b>							
Name	PASSWORD							
Datatype	string							
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0		
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>128</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9+=/]*</td> </tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	128	pattern	[a-zA-Z_0-9+=/]*
<b>Restrictions</b>	<b>Description</b>							
maxLength	128							
pattern	[a-zA-Z_0-9+=/]*							

## ADDL

<b>Attribute</b>	<b>Description</b>					
Name	ADDL					
Datatype						
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					

## PARAM

<b>Attribute</b>	<b>Description</b>							
Name	PARAM							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Currency-PK

Attribute	Description
Name	Currency-PK
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## Currency-IO

Attribute	Description
Name	Currency-IO
Datatype	
Description	

## CURRENCY\_CODE

Attribute	Description				
Name	CURRENCY_CODE				
Datatype	string				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## MAKER

<b>Attribute</b>	<b>Description</b>					
Name	MAKER					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>12</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	12
<b>Restrictions</b>	<b>Description</b>					
maxLength	12					

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>					
Name	MAKERSTAMP					
Datatype	string					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>maxLength</td><td>35</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	maxLength	35
<b>Restrictions</b>	<b>Description</b>					
maxLength	35					

## MODNO

<b>Attribute</b>	<b>Description</b>					
Name	MODNO					
Datatype	decimal					
Description						
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0
<b>Attribute</b>	<b>Description</b>					
minOccurs	0					
Restrictions	<table border="1"> <thead> <tr> <th><b>Restrictions</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>totalDigits</td><td>4</td></tr> </tbody> </table>		<b>Restrictions</b>	<b>Description</b>	totalDigits	4
<b>Restrictions</b>	<b>Description</b>					
totalDigits	4					

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>							
Name	FCUBS_ERROR_RESP							
Datatype								
Description								
Attribute	<table border="1"> <thead> <tr> <th><b>Attribute</b></th> <th><b>Description</b></th> </tr> </thead> <tbody> <tr> <td>minOccurs</td><td>0</td></tr> <tr> <td>maxOccurs</td><td>unbounded</td></tr> </tbody> </table>		<b>Attribute</b>	<b>Description</b>	minOccurs	0	maxOccurs	unbounded
<b>Attribute</b>	<b>Description</b>							
minOccurs	0							
maxOccurs	unbounded							

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		

Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	
Attribute	
Attribute	Description
minOccurs	0
maxOccurs	unbounded

## WARNING

Attribute	Description
Name	WARNING
Datatype	
Description	
Attribute	
Attribute	Description
maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

Gateway Documentation - COCurrencyService  
[October] [2015]

Oracle Financial services Software Limited  
Oracle Park  
Off western Express Highway  
Goregaon(East)  
Mumbai,Maharashtra 400 063  
India

**Worldwide Inquiries:**

Phone: +91 22 6718 3000  
Fax:+91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.