

Gateway Documentation - ELAccountService  
Oracle FLEXCUBE Universal Banking  
Release FCELCM-UBS\_12.1.0.0.0  
[October][2015]



# Table Of Contents

---

<b>1. Background</b>	<b>1</b>
<b>2. ELAccountService</b>	<b>2</b>
<b>2.1. AuthorizeNettingDetails</b>	<b>2</b>
2.1.1. GE-AuthorizeNettingDetails-Req-Full-MSG.xsd	2
2.1.2. GE-AuthorizeNettingDetails-Req-IO-MSG.xsd	15
2.1.3. GE-AuthorizeNettingDetails-Res-Full-MSG.xsd	23
2.1.4. GE-AuthorizeNettingDetails-Res-PK-MSG.xsd	38
<b>2.2. CloseNettingDetails</b>	<b>48</b>
2.2.1. GE-CloseNettingDetails-Req-Full-MSG.xsd	48
2.2.2. GE-CloseNettingDetails-Req-IO-MSG.xsd	62
2.2.3. GE-CloseNettingDetails-Res-Full-MSG.xsd	70
2.2.4. GE-CloseNettingDetails-Res-PK-MSG.xsd	84
<b>2.3. CreateNettingDetails</b>	<b>94</b>
2.3.1. GE-CreateNettingDetails-Req-Full-MSG.xsd	94
2.3.2. GE-CreateNettingDetails-Req-IO-MSG.xsd	108
2.3.3. GE-CreateNettingDetails-Res-Full-MSG.xsd	119
2.3.4. GE-CreateNettingDetails-Res-PK-MSG.xsd	134
<b>2.4. DeleteNettingDetails</b>	<b>147</b>
2.4.1. GE-DeleteNettingDetails-Req-Full-MSG.xsd	147
2.4.2. GE-DeleteNettingDetails-Req-IO-MSG.xsd	160
2.4.3. GE-DeleteNettingDetails-Res-Full-MSG.xsd	167
2.4.4. GE-DeleteNettingDetails-Res-PK-MSG.xsd	182
<b>2.5. ModifyNettingDetails</b>	<b>192</b>
2.5.1. GE-ModifyNettingDetails-Req-Full-MSG.xsd	192
2.5.2. GE-ModifyNettingDetails-Req-IO-MSG.xsd	205
2.5.3. GE-ModifyNettingDetails-Res-Full-MSG.xsd	216
2.5.4. GE-ModifyNettingDetails-Res-PK-MSG.xsd	231
<b>2.6. QueryNettingDetails</b>	<b>244</b>
2.6.1. GE-QueryNettingDetails-Req-IO-MSG.xsd	244
2.6.2. GE-QueryNettingDetails-Res-Full-MSG.xsd	251
<b>2.7. ReopenNettingDetails</b>	<b>267</b>
2.7.1. GE-ReopenNettingDetails-Req-Full-MSG.xsd	267
2.7.2. GE-ReopenNettingDetails-Req-IO-MSG.xsd	280
2.7.3. GE-ReopenNettingDetails-Res-Full-MSG.xsd	288
2.7.4. GE-ReopenNettingDetails-Res-PK-MSG.xsd	303

# 1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

## 1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

## 2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in ELAccountService of EL Module

## 2. ELAccountService

### 2.1.AuthorizeNettingDetails

#### 2.1.1.GE-AuthorizeNettingDetails-Req-Full-MSG.xsd

*AUTHORIZENETTINGDETAILS\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

#### **AUTHORIZENETTINGDETAILS\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZENETTINGDETAILS_FSFS_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeNettingDetails

**Netting-Details-Full**

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**CUSTOMER\_NUMBER**

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

**CURRENCY**

Attribute	Description
Name	CURRENCY
Datatype	string

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.1.2.GE-AuthorizeNettingDetails-Req-IO-MSG.xsd

#### *AUTHORIZENETTINGDETAILS\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-IO*  
*REFERENCENO*  
*STATUS*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

#### AUTHORIZENETTINGDETAILS\_IOPK\_REQ

Attribute	Description
Name	AUTHORIZENETTINGDETAILS_IOPK_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of AuthorizeNettingDetails

## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.1.3.GE-AuthorizeNettingDetails-Res-Full-MSG.xsd

*AUTHORIZENETTINGDETAILS\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-Full*  
*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*CURRENCY*  
*AMOUNT*  
*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

#### **AUTHORIZENETTINGDETAILS\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZENETTINGDETAILS_FSFS_RES
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	



Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Netting-Details-Full

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## AMOUNT

Attribute	Description
-----------	-------------

Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

Attribute	Description	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

Attribute	Description	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

Attribute	Description	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

Attribute	Description	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

## SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.1.4. GE-AuthorizeNettingDetails-Res-PK-MSG.xsd

*AUTHORIZENETTINGDETAILS\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*



*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-PK*

*REFERENCENO*

*STATUS*

*Netting-Details-IO*

*REFERENCENO*

*STATUS*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**AUTHORIZENETTINGDETAILS\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZENETTINGDETAILS_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Netting-Details-PK

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-PK
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## CHECKERSTAMP

Attribute	Description
Name	CHECKERSTAMP
Datatype	string
Description	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.2.CloseNettingDetails

### 2.2.1.GE-CloseNettingDetails-Req-Full-MSG.xsd

*CLOSENETTINGDETAILS\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-Full*  
*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*CURRENCY*  
*AMOUNT*  
*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*

CHECKERSTAMP

MODNO

TXNSTAT

AUTHSTAT

UDFDETAILS

FLDNAM

FLDVAL

## CLOSENETTINGDETAILS\_FSFS\_REQ

Attribute	Description
Name	CLOSENETTINGDETAILS_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*
	<b>Description</b>	

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	

Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	

Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	<b>Description</b>	

## ADDL

<b>Attribute</b>		<b>Description</b>
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## PARAM

<b>Attribute</b>		<b>Description</b>
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## NAME

<b>Attribute</b>		<b>Description</b>
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>		<b>Description</b>
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>		<b>Description</b>
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Request of CloseNettingDetails	

## Netting-Details-Full

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## AMOUNT

Attribute	Description				
Name	AMOUNT				
Datatype	decimal				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## VALUE\_DATE

Attribute	Description				
Name	VALUE_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description				
Name	EXP_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## NETTING\_REQUIRED

Attribute	Description				
Name	NETTING_REQUIRED				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

*CLOSENETTINGDETAILS\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-IO*

*REFERENCENO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*MODNO*

**CLOSENETTINGDETAILS\_IOPK\_REQ**

Attribute	Description
-----------	-------------



Name	CLOSENETTINGDETAILS_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CloseNettingDetails

## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"> <tr> <th>Attribute</th> <th>Description</th> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

2.2.3.GE-CloseNettingDetails-Res-Full-MSG.xsd

*CLOSENETTINGDETAILS\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*



VALUE\_DATE  
 BOOKING\_DATE  
 EXP\_DATE  
 NETTING\_REQUIRED  
 SOURCE  
 USER\_REFNO  
 CONTRACT\_TYPE  
 LIAB\_NO  
 LINE\_CODE  
 SERIALNO  
 STATUS  
 MAKER  
 MAKERSTAMP  
 CHECKER  
 CHECKERSTAMP  
 MODNO  
 TXNSTAT  
 AUTHSTAT  
 UDFDETAILS  
     FLDNAM  
     FLDVAL  
 FCUBS\_ERROR\_RESP  
     ERROR  
     ECODE  
     EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
     WCODE  
     WDESC

**CLOSENETTINGDETAILS\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSENETTINGDETAILS_FSFS_RES

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

## BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	string							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Netting-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	20

## CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	3

## AMOUNT

Attribute	Description	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## VALUE\_DATE

Attribute	Description	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

## BOOKING\_DATE

Attribute	Description	
Name	BOOKING_DATE	
Datatype	String	
Description		



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

Attribute	Description	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

Attribute	Description	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

Attribute	Description	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.2.4.GE-CloseNettingDetails-Res-PK-MSG.xsd

*CLOSETTINGDETAILS\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-PK*  
*REFERENCENO*  
*STATUS*  
*Netting-Details-IO*  
*REFERENCENO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**CLOSENETTINGDETAILS\_IOPK\_RES**

Attribute	Description
Name	CLOSENETTINGDETAILS_IOPK_RES
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

**MSGID**

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about PK Response		

## Netting-Details-PK

Attribute		Description	
Name	Netting-Details-PK		
Datatype			
Description			

## REFERENCENO

Attribute		Description	
Name	REFERENCENO		
Datatype	string		
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## Netting-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.3.CreateNettingDetails

### 2.3.1.GE-CreateNettingDetails-Req-Full-MSG.xsd

[CREATENETTINGDETAILS\\_FSFS\\_REQ](#)



*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

**CREATENETTINGDETAILS\_FSFS\_REQ**

Attribute	Description
Name	CREATENETTINGDETAILS_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	Restrictions	Description
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description

Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateNettingDetails

## Netting-Details-Full

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.3.2.GE-CreateNettingDetails-Req-IO-MSG.xsd

#### *CREATENETTINGDETAILS\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-IO*  
*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*CURRENCY*  
*AMOUNT*  
*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

**CREATENETTINGDETAILS\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CREATENETTINGDETAILS_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.



Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>
Name	DESTINATION

Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of CreateNettingDetails

## Netting-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## CURRENCY

Attribute	Description	
Name	CURRENCY	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

Attribute	Description	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

Attribute	Description	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

Attribute	Description	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

Attribute	Description	
Name	EXP_DATE	
Datatype	String	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

### 2.3.3.GE-CreateNettingDetails-Res-Full-MSG.xsd

#### *CREATENETTINGDETAILS\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## CREATENETTINGDETAILS\_FSFS\_RES

Attribute	Description
Name	CREATENETTINGDETAILS_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	Attribute	Description
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	Attribute	Description
	minOccurs	0
	nillable	true

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]
	<b>Description</b>	

## ADDL

<b>Attribute</b>		<b>Description</b>
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

## PARAM

<b>Attribute</b>		<b>Description</b>
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## NAME

<b>Attribute</b>		<b>Description</b>
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>		<b>Description</b>
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>		<b>Description</b>
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

## Netting-Details-Full



Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## AMOUNT

Attribute	Description				
Name	AMOUNT				
Datatype	decimal				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>totalDigits</td> <td>22</td> </tr> </tbody> </table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## VALUE\_DATE

Attribute	Description				
Name	VALUE_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description				
Name	EXP_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## NETTING\_REQUIRED

Attribute	Description				
Name	NETTING_REQUIRED				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	maxOccurs	unbounded	

## ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

## EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

## FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

## WARNING

Attribute		Description	
Name	WARNING		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	maxOccurs	unbounded	

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.3.4.GE-CreateNettingDetails-Res-PK-MSG.xsd

*CREATENETTINGDETAILS\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-PK*



*REFERENCENO*

*STATUS*

*Netting-Details-IO*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**CREATENETTINGDETAILS\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATENETTINGDETAILS_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about PK Response	

## Netting-Details-PK

Attribute		Description	
Name		Netting-Details-PK	
Datatype			
Description			

## REFERENCENO

Attribute		Description	
Name		REFERENCENO	
Datatype		string	
Description			
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength		50

## STATUS

Attribute		Description	
Name		STATUS	
Datatype		string	
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

### Netting-Details-IO

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-IO
Datatype	
Description	

### REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

### AMOUNT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>		<b>Description</b>
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>		<b>Description</b>
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>		<b>Description</b>
Name	EXP_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>		<b>Description</b>
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	enumeration	Y,N

## USER\_REFNO

Attribute		Description	
Name	USER_REFNO		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

## CONTRACT\_TYPE

Attribute		Description	
Name	CONTRACT_TYPE		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

## LIAB\_NO

Attribute		Description	
Name	LIAB_NO		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	9	

## LINE\_CODE

Attribute		Description	
Name	LINE_CODE		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

## SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

## 2.4.DeleteNettingDetails

### 2.4.1.GE-DeleteNettingDetails-Req-Full-MSG.xsd

*DELETENETTINGDETAILS\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## DELETENETTINGDETAILS\_FSFS\_REQ

Attribute	Description
Name	DELETENETTINGDETAILS_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Request of DeleteNettingDetails	

## Netting-Details-Full

Attribute		Description	
Name		Netting-Details-Full	
Datatype			
Description			

## REFERENCENO

Attribute		Description	
Name		REFERENCENO	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description				
Name	EXP_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## NETTING\_REQUIRED

Attribute	Description				
Name	NETTING_REQUIRED				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## USER\_REFNO

Attribute	Description
Name	USER_REFNO
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

### LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.4.2.GE-DeleteNettingDetails-Req-IO-MSG.xsd

*DELETENETTINGDETAILS\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-IO*  
*REFERENCENO*  
*STATUS*

**DELETENETTINGDETAILS\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETENETTINGDETAILS_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteNettingDetails

**Netting-Details-IO**

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**STATUS**

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

*DELETENETTINGDETAILS\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
     *FLDNAM*  
     *FLDVAL*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

**DELETENETTINGDETAILS\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETENETTINGDETAILS_FSFS_RES
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation

Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Netting-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## AMOUNT

Attribute	Description				
Name	AMOUNT				
Datatype	decimal				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

## VALUE\_DATE

Attribute	Description				
Name	VALUE_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description
Name	EXP_DATE
Datatype	String
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

#### FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

#### WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

#### WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

#### WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

#### 2.4.4.GE-DeleteNettingDetails-Res-PK-MSG.xsd

*DELETENETTINGDETAILS\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*



*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
     *Netting-Details-PK*  
         *REFERENCENO*  
         *STATUS*  
     *Netting-Details-IO*  
         *REFERENCENO*  
         *STATUS*  
*FCUBS\_ERROR\_RESP*  
     *ERROR*  
         *ECODE*  
         *EDESC*  
*FCUBS\_WARNING\_RESP*  
     *WARNING*  
         *WCODE*  
         *WDESC*

**DELETENETTINGDETAILS\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	DELETENETTINGDETAILS_IOPK_RES

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description						
Name	USERID						
Datatype	string						
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description						
maxLength	12						
pattern	[A-Z_0-9]*						

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	string						
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description						
length	3						
pattern	[a-zA-Z_0-9]{3}						

## MODULEID

Attribute	Description
Name	MODULEID
Datatype	string
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Netting-Details-PK

Attribute	Description
Name	Netting-Details-PK
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## Netting-Details-IO

Attribute	Description	
Name	Netting-Details-IO	
Datatype		
Description		

## REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

## 2.5.ModifyNettingDetails

### 2.5.1.GE-ModifyNettingDetails-Req-Full-MSG.xsd

#### *MODIFYNETTINGDETAILS\_FSFS\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

##### *FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## **MODIFYNETTINGDETAILS\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYNETTINGDETAILS_FSFS_REQ
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "EXCLUDE"

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded



**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ModifyNettingDetails

**Netting-Details-Full**

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**CUSTOMER\_NUMBER**

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

**CURRENCY**

Attribute	Description
Name	CURRENCY
Datatype	string

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.5.2.GE-ModifyNettingDetails-Req-IO-MSG.xsd

#### *MODIFYNETTINGDETAILS\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-IO*  
*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*LIABILITY\_ID*  
*FACILITY\_ID*  
*AMOUNT*  
*VALUE\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

**MODIFYNETTINGDETAILS\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYNETTINGDETAILS_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE LIBS. In



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
pattern	[A-Z_0-9]*	

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ModifyNettingDetails

**Netting-Details-IO**

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**CUSTOMER\_NUMBER**

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

**LIABILITY\_ID**

Attribute	Description	
Name	LIABILITY_ID	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## FACILTY\_ID

Attribute	Description	
Name	FACILTY_ID	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## AMOUNT

Attribute	Description	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

Attribute	Description	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

Attribute	Description	
Name	EXP_DATE	
Datatype	String	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

### 2.5.3. GE-ModifyNettingDetails-Res-Full-MSG.xsd

#### *MODIFYNETTINGDETAILS\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

##### *FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*CURRENCY*  
*AMOUNT*  
*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*

WCODE

WDESC

## MODIFYNETTINGDETAILS\_FSFS\_RES

Attribute	Description
Name	MODIFYNETTINGDETAILS_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL



Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about Full Response		

## Netting-Details-Full

Attribute		Description	
Name	Netting-Details-Full		
Datatype			
Description			

## REFERENCENO

Attribute		Description	
Name	REFERENCENO		
Datatype	string		
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description				
Name	EXP_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## NETTING\_REQUIRED

Attribute	Description				
Name	NETTING_REQUIRED				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## USER\_REFNO

Attribute	Description
Name	USER_REFNO
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String



Description	
-------------	--

#### 2.5.4. GE-ModifyNettingDetails-Res-PK-MSG.xsd

### *MODIFYNETTINGDETAILS\_IOPK\_RES*

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Netting-Details-PK*

*REFERENCENO*

*STATUS*

*Netting-Details-IO*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*LIABILITY\_ID*

*FACILITY\_ID*

*AMOUNT*

*VALUE\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYNETTINGDETAILS\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYNETTINGDETAILS_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EL EXCLUDE UBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
pattern	[A-Z_0-9]*	

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

**Netting-Details-PK**

Attribute	Description
Name	Netting-Details-PK
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**STATUS**

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

**Netting-Details-IO**

Attribute	Description
Name	Netting-Details-IO
Datatype	



Description	
-------------	--

## REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

## CUSTOMER\_NUMBER

Attribute	Description	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	20

## LIABILITY\_ID

Attribute	Description	
Name	LIABILITY_ID	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

## FACILTY\_ID

Attribute	Description	
Name	FACILTY_ID	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
Restrictions	<b>Restrictions</b>	<b>Description</b>
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.6.QueryNettingDetails

### 2.6.1.GE-QueryNettingDetails-Req-IO-MSG.xsd

*QUERYNETTINGDETAILS\_IOFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-IO*

*REFERENCENO*

*STATUS*

## QUERYNETTINGDETAILS\_IOFS\_REQ

Attribute	Description
Name	QUERYNETTINGDETAILS_IOFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about IO Request of QueryNettingDetails		

## Netting-Details-IO

Attribute		Description	
Name	Netting-Details-IO		
Datatype			
Description			

## REFERENCENO

Attribute		Description	
Name	REFERENCENO		
Datatype	string		
Description			

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

### 2.6.2.GE-QueryNettingDetails-Res-Full-MSG.xsd

#### *QUERYNETTINGDETAILS\_IOFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-IO*

*REFERENCENO*

*STATUS*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*

*BOOKING\_DATE*

*EXP\_DATE*

*NETTING\_REQUIRED*

*SOURCE*

*USER\_REFNO*

*CONTRACT\_TYPE*

*LIAB\_NO*

*LINE\_CODE*

*SERIALNO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## QUERYNETTINGDETAILS\_IOFS\_RES

Attribute	Description
Name	QUERYNETTINGDETAILS_IOFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description	
Name	REFERENCENO	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

## Netting-Details-Full

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description
Name	REFERENCENO
Datatype	string
Description	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CUSTOMER\_NUMBER

<b>Attribute</b>	<b>Description</b>	
Name	CUSTOMER_NUMBER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## CURRENCY

<b>Attribute</b>	<b>Description</b>	
Name	CURRENCY	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

Attribute	Description				
Name	BOOKING_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## EXP\_DATE

Attribute	Description				
Name	EXP_DATE				
Datatype	String				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## NETTING\_REQUIRED

Attribute	Description				
Name	NETTING_REQUIRED				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>Y,N</td></tr></tbody></table>	Restrictions	Description	enumeration	Y,N
Restrictions	Description				
enumeration	Y,N				

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>20</td></tr></tbody></table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## USER\_REFNO

Attribute	Description
Name	USER_REFNO
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxOccurs	unbounded

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

Description	
-------------	--

## 2.7.ReopenNettingDetails

### 2.7.1.GE-ReopenNettingDetails-Req-Full-MSG.xsd

*REOPENNETTINGDETAILS\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-Full*

*REFERENCENO*

*CUSTOMER\_NUMBER*

*CURRENCY*

*AMOUNT*

*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

#### REOPENNETTINGDETAILS\_FSFS\_REQ

Attribute	Description
Name	REOPENNETTINGDETAILS_FSFS_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "EXCLUDE"

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of ReopenNettingDetails

**Netting-Details-Full**

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

**REFERENCENO**

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**CUSTOMER\_NUMBER**

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

**CURRENCY**

Attribute	Description
Name	CURRENCY
Datatype	string

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

## AMOUNT

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

## USER\_REFNO

<b>Attribute</b>	<b>Description</b>	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CONTRACT\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## LIAB\_NO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

## LINE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SERIALNO

<b>Attribute</b>	<b>Description</b>	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

## MAKER

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.7.2.GE-ReopenNettingDetails-Req-IO-MSG.xsd

#### *REOPENNETTINGDETAILS\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-IO*  
*REFERENCENO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*

## REOPENNETTINGDETAILS\_IOPK\_REQ

Attribute	Description
Name	REOPENNETTINGDETAILS_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	



Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenNettingDetails

## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

### 2.7.3.GE-ReopenNettingDetails-Res-Full-MSG.xsd

*REOPENNETTINGDETAILS\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Netting-Details-Full*  
*REFERENCENO*  
*CUSTOMER\_NUMBER*  
*CURRENCY*  
*AMOUNT*  
*VALUE\_DATE*  
*BOOKING\_DATE*  
*EXP\_DATE*  
*NETTING\_REQUIRED*  
*SOURCE*  
*USER\_REFNO*  
*CONTRACT\_TYPE*  
*LIAB\_NO*  
*LINE\_CODE*  
*SERIALNO*  
*STATUS*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENNETTINGDETAILS\_FSFS\_RES

Attribute	Description
Name	REOPENNETTINGDETAILS_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Netting-Details-Full

Attribute	Description
Name	Netting-Details-Full
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## CUSTOMER\_NUMBER

Attribute	Description				
Name	CUSTOMER_NUMBER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>20</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	20
Restrictions	Description				
maxLength	20				

## CURRENCY

Attribute	Description				
Name	CURRENCY				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
Restrictions	Description				
maxLength	3				

## AMOUNT

Attribute	Description
-----------	-------------

Name	AMOUNT	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

## VALUE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## BOOKING\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	BOOKING_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## EXP\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EXP_DATE	
Datatype	String	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## NETTING\_REQUIRED

<b>Attribute</b>	<b>Description</b>	
Name	NETTING_REQUIRED	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	Y,N

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	20

### USER\_REFNO

Attribute	Description	
Name	USER_REFNO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### CONTRACT\_TYPE

Attribute	Description	
Name	CONTRACT_TYPE	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### LIAB\_NO

Attribute	Description	
Name	LIAB_NO	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	9

### LINE\_CODE

Attribute	Description	
Name	LINE_CODE	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

## SERIALNO

Attribute	Description	
Name	SERIALNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	22

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	10

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING



Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.7.4.GE-ReopenNettingDetails-Res-PK-MSG.xsd

*REOPENNETTINGDETAILS\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Netting-Details-PK*

*REFERENCENO*

*STATUS*

*Netting-Details-IO*

*REFERENCENO*

*STATUS*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **REOPENNETTINGDETAILS\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	REOPENNETTINGDETAILS_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	

Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

## Netting-Details-PK

<b>Attribute</b>	<b>Description</b>
Name	Netting-Details-PK
Datatype	
Description	

## REFERENCENO

<b>Attribute</b>	<b>Description</b>	
Name	REFERENCENO	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10



## Netting-Details-IO

Attribute	Description
Name	Netting-Details-IO
Datatype	
Description	

## REFERENCENO

Attribute	Description				
Name	REFERENCENO				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## STATUS

Attribute	Description				
Name	STATUS				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

## MAKERSTAMP

Attribute	Description
Name	MAKERSTAMP
Datatype	string
Description	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	



## FINANCIAL SERVICES

Gateway Documentation - ELAccountService  
[October] [2015]

Oracle Financial services Software Limited  
Oracle Park  
Off western Express Highway  
Goregaon(East)  
Mumbai,Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax:+91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.