

Gateway Documentation - ELInsuranceCompanyService  
Oracle FLEXCUBE Universal Banking  
Release FCELCM-UBS\_12.1.0.0.0  
[October][2015]



# Table Of Contents

---

<b>1. Background</b>	<b>1</b>
<b>2. ELInsuranceCompanyService</b>	<b>2</b>
<b>2.1.AuthorizeInsuranceCompany</b>	<b>2</b>
2.1.1.GE-AuthorizeInsuranceCompany-Req-Full-MSG.xsd	2
2.1.2.GE-AuthorizeInsuranceCompany-Req-IO-MSG.xsd	13
2.1.3.GE-AuthorizeInsuranceCompany-Res-Full-MSG.xsd	20
2.1.4.GE-AuthorizeInsuranceCompany-Res-PK-MSG.xsd	33
<b>2.2.CloseInsuranceCompany</b>	<b>43</b>
2.2.1.GE-CloseInsuranceCompany-Req-Full-MSG.xsd	43
2.2.2.GE-CloseInsuranceCompany-Req-IO-MSG.xsd	54
2.2.3.GE-CloseInsuranceCompany-Res-Full-MSG.xsd	61
2.2.4.GE-CloseInsuranceCompany-Res-PK-MSG.xsd	74
<b>2.3.CreateInsuranceCompany</b>	<b>84</b>
2.3.1.GE-CreateInsuranceCompany-Req-Full-MSG.xsd	84
2.3.2.GE-CreateInsuranceCompany-Req-IO-MSG.xsd	95
2.3.3.GE-CreateInsuranceCompany-Res-Full-MSG.xsd	104
2.3.4.GE-CreateInsuranceCompany-Res-PK-MSG.xsd	116
<b>2.4.DeleteInsuranceCompany</b>	<b>127</b>
2.4.1.GE-DeleteInsuranceCompany-Req-Full-MSG.xsd	127
2.4.2.GE-DeleteInsuranceCompany-Req-IO-MSG.xsd	138
2.4.3.GE-DeleteInsuranceCompany-Res-Full-MSG.xsd	145
2.4.4.GE-DeleteInsuranceCompany-Res-PK-MSG.xsd	157
<b>2.5.ModifyInsuranceCompany</b>	<b>166</b>
2.5.1.GE-ModifyInsuranceCompany-Req-Full-MSG.xsd	166
2.5.2.GE-ModifyInsuranceCompany-Req-IO-MSG.xsd	177
2.5.3.GE-ModifyInsuranceCompany-Res-Full-MSG.xsd	187
2.5.4.GE-ModifyInsuranceCompany-Res-PK-MSG.xsd	199
<b>2.6.QueryInsuranceCompany</b>	<b>210</b>
2.6.1.GE-QueryInsuranceCompany-Req-IO-MSG.xsd	210
2.6.2.GE-QueryInsuranceCompany-Res-Full-MSG.xsd	217
<b>2.7.ReopenInsuranceCompany</b>	<b>230</b>
2.7.1.GE-ReopenInsuranceCompany-Req-Full-MSG.xsd	230
2.7.2.GE-ReopenInsuranceCompany-Req-IO-MSG.xsd	241
2.7.3.GE-ReopenInsuranceCompany-Res-Full-MSG.xsd	249
2.7.4.GE-ReopenInsuranceCompany-Res-PK-MSG.xsd	261

## 1. Background

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs. The integration needs supported by the Gateway can be broadly categorized from the perspective of Gateway as follows

### 1. Inbound application integration :

This is used when any external system needs to add, modify or query information within FLEXCUBE UBS

### 2. Outbound application integration :

This is used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in ELInsuranceCompanyService of EL Module

## 2. ELInsuranceCompanyService

### 2.1.AuthorizeInsuranceCompany

#### 2.1.1.GE-AuthorizeInsuranceCompany-Req-Full-MSG.xsd

*AUTHORIZEINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

#### **AUTHORIZEINSURANCECOMPANY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEINSURANCECOMPANY_FSFS_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID



Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of AuthorizeInsuranceCompany

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE2

Attribute	Description

Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

2.1.2.GE-AuthorizeInsuranceCompany-Req-IO-MSG.xsd

*AUTHORIZEINSURANCECOMPANY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

CHECKER

CHECKERSTAMP

MODNO

#### AUTHORIZEINSURANCECOMPANY\_IOPK\_REQ

Attribute	Description
Name	AUTHORIZEINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

#### MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
Attribute	Description				
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
Attribute	Description				
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*
	<b>Description</b>	

## ACTION

<b>Attribute</b>		
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## MSGSTAT

<b>Attribute</b>		
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE
	<b>Description</b>	

## PASSWORD

<b>Attribute</b>		
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	<b>Description</b>	

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about IO Request of AuthorizeInsuranceCompany	

## Insurance-Company-IO

Attribute		Description	
Name		Insurance-Company-IO	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

2.1.3.GE-AuthorizeInsuranceCompany-Res-Full-MSG.xsd

*AUTHORIZEINSURANCECOMPANY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-Full*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

#### **AUTHORIZEINSURANCECOMPANY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string



Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE2

Attribute	Description

Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

### 2.1.4. GE-AuthorizeInsuranceCompany-Res-PK-MSG.xsd

*AUTHORIZEINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-PK*

*INSURANCE\_COMPANY\_NAME*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **AUTHORIZEINSURANCECOMPANY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	AUTHORIZEINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

**Insurance-Company-PK**

Attribute	Description
Name	Insurance-Company-PK
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**Insurance-Company-IO**

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

**WCODE**

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

**WDESC**

Attribute	Description	
Name	WDESC	
Datatype	String	

Description	
-------------	--

## 2.2.CloseInsuranceCompany

### 2.2.1.GE-CloseInsuranceCompany-Req-Full-MSG.xsd

*CLOSEINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

#### **CLOSEINSURANCECOMPANY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEINSURANCECOMPANY_FSFS_REQ
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CloseInsuranceCompany

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE2

Attribute	Description

Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

2.2.2.GE-CloseInsuranceCompany-Req-IO-MSG.xsd

*CLOSEINSURANCECOMPANY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*



*MAKER*

*MAKERSTAMP*

*MODNO*

## CLOSEINSURANCECOMPANY\_IOPK\_REQ

Attribute	Description
Name	CLOSEINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	8
	pattern	[A-Z_0-9]*
	<b>Description</b>	

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	enumeration	SUCCESS,WARNING,FAILURE
	<b>Description</b>	

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*
	<b>Description</b>	

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about IO Request of CloseInsuranceCompany	

## Insurance-Company-IO

Attribute		Description	
Name		Insurance-Company-IO	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

2.2.3.GE-CloseInsuranceCompany-Res-Full-MSG.xsd

*CLOSEINSURANCECOMPANY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-Full*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*



*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

#### **CLOSEINSURANCECOMPANY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

#### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

#### **SOURCE**

<b>Attribute</b>	<b>Description</b>				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th><b>Restrictions</b></th><th><b>Description</b></th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	<b>Restrictions</b>	<b>Description</b>	pattern	[a-zA-Z_0-9]*
<b>Restrictions</b>	<b>Description</b>				
pattern	[a-zA-Z_0-9]*				

#### **UBSCOMP**

<b>Attribute</b>	<b>Description</b>
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE. <sup>64</sup>	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE2

Attribute	Description

Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	maxLength	1
	<b>Description</b>	

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	minOccurs	0
	maxOccurs	unbounded
	<b>Description</b>	

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	maxLength	105
	minLength	1
	<b>Description</b>	

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.2.4. GE-CloseInsuranceCompany-Res-PK-MSG.xsd

*CLOSEINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-PK*

*INSURANCE\_COMPANY\_NAME*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CLOSEINSURANCECOMPANY\_IOPK\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CLOSEINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
pattern	[A-Z_0-9]*	

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

**Insurance-Company-PK**

Attribute	Description
Name	Insurance-Company-PK
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**Insurance-Company-IO**

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String

## 2.3.CreateInsuranceCompany

### 2.3.1.GE-CreateInsuranceCompany-Req-Full-MSG.xsd

*CREATEINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

#### CREATEINSURANCECOMPANY\_FSFS\_REQ

Attribute	Description
Name	CREATEINSURANCECOMPANY_FSFS_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
pattern	[A-Z_0-9]*	

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of CreateInsuranceCompany

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## ADDRESS\_LINE2

Attribute	Description

Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	TXNSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

2.3.2.GE-CreateInsuranceCompany-Req-IO-MSG.xsd

*CREATEINSURANCECOMPANY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## CREATEINSURANCECOMPANY\_IOPK\_REQ

Attribute	Description
Name	CREATEINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## USERID

Attribute	Description	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*
	<b>Description</b>	

## BRANCH

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## SOURCE\_USERID

<b>Attribute</b>		<b>Description</b>
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>		<b>Description</b>
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*
	<b>Description</b>	

## MULTIRIPID

<b>Attribute</b>		<b>Description</b>
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	<b>Description</b>	

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of CreateInsuranceCompany	

## Insurance-Company-IO

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

### INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

### SHORT\_NAME

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

### ADDRESS\_LINE1

Attribute	Description				
Name	ADDRESS_LINE1				
Datatype	string				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

### ADDRESS\_LINE2

Attribute	Description				
Name	ADDRESS_LINE2				
Datatype	string				
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions					
	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				



### ADDRESS\_LINE3

Attribute	Description	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

### ADDRESS\_LINE4

Attribute	Description	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

### UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

### FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.3.3.GE-CreateInsuranceCompany-Res-Full-MSG.xsd

*CREATEINSURANCECOMPANY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **CREATEINSURANCECOMPANY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	CREATEINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	string	
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>
Name	DESTINATION

Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Insurance-Company-Full

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE1

Attribute		Description	
Name	ADDRESS_LINE1		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

### ADDRESS\_LINE2

Attribute		Description	
Name	ADDRESS_LINE2		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

### ADDRESS\_LINE3

Attribute		Description	
Name	ADDRESS_LINE3		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

### ADDRESS\_LINE4

Attribute		Description	
Name	ADDRESS_LINE4		
Datatype	string		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	maxLength	50	

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	

Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.3.4.GE-CreateInsuranceCompany-Res-PK-MSG.xsd

*CREATEINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-PK*  
*INSURANCE\_COMPANY\_NAME*  
*Insurance-Company-IO*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

Attribute	Description
Name	CREATEINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description			This XSD Gives Information about PK Response

## Insurance-Company-PK

Attribute		Description	
Name		Insurance-Company-PK	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### Insurance-Company-IO

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-IO
Datatype	
Description	

### INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>
Name	ADDRESS_LINE2
Datatype	string
Description	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP



Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.4.DeleteInsuranceCompany

### 2.4.1.GE-DeleteInsuranceCompany-Req-Full-MSG.xsd

*DELETEINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*  
*DESTINATION*  
*MULTIRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
     *PARAM*  
         *NAME*  
         *VALUE*  
*FCUBS\_BODY*  
     *Insurance-Company-Full*  
         *INSURANCE\_COMPANY\_NAME*  
         *SHORT\_NAME*  
         *ADDRESS\_LINE1*  
         *ADDRESS\_LINE2*  
         *ADDRESS\_LINE3*  
         *ADDRESS\_LINE4*  
         *MAKER*  
         *MAKERSTAMP*  
         *CHECKER*  
         *CHECKERSTAMP*  
         *MODNO*  
         *TXNSTAT*  
         *AUTHSTAT*  
         *UDFDETAILS*  
             *FLDNAM*  
             *FLDVAL*

**DELETEINSURANCECOMPANY\_FSFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	DELETEINSURANCECOMPANY_FSFS_REQ

Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description							
Name	CORRELID							
Datatype	string							
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>		Attribute	Description	minOccurs	0	nillable	true
Attribute	Description							
minOccurs	0							
nillable	true							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description							
pattern	[a-zA-Z_0-9]*							

## USERID

Attribute	Description							
Name	USERID							
Datatype	string							
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> <tr> <td>pattern</td> <td>[A-Z_0-9]*</td> </tr> </tbody> </table>		Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
Restrictions	Description							
maxLength	12							
pattern	[A-Z_0-9]*							

## BRANCH

Attribute	Description							
Name	BRANCH							
Datatype	string							
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.							
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>length</td> <td>3</td> </tr> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]{3}</td> </tr> </tbody> </table>		Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
Restrictions	Description							
length	3							
pattern	[a-zA-Z_0-9]{3}							

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>
Name	ADDL

Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

## PARAM

<b>Attribute</b>	<b>Description</b>						
Name	PARAM						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request of DeletelnsuranceCompany

## Insurance-Company-Full

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

## SHORT\_NAME



Attribute	Description	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

#### ADDRESS\_LINE1

Attribute	Description	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

#### ADDRESS\_LINE2

Attribute	Description	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

#### ADDRESS\_LINE3

Attribute	Description	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

#### ADDRESS\_LINE4

Attribute	Description	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	50

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## CHECKER

Attribute	Description	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	12

## CHECKERSTAMP

Attribute	Description	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	totalDigits	4

## TXNSTAT

Attribute	Description	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	1

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

### 2.4.2.GE-DeleteInsuranceCompany-Req-IO-MSG.xsd

#### *DELETEINSURANCECOMPANY\_IOPK\_REQ*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

#### DELETEINSURANCECOMPANY\_IOPK\_REQ

Attribute	Description
Name	DELETEINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

#### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

#### UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	string						
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## USERID

Attribute	Description
Name	USERID
Datatype	string

Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
	<b>Restrictions</b>	<b>Description</b>
Restrictions	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID



Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of DeleteInsuranceCompany

## Insurance-Company-IO

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

### 2.4.3. GE-DeleteInsuranceCompany-Res-Full-MSG.xsd

#### *DELETEINSURANCECOMPANY\_FSFS\_RES*

##### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

WCODE

WDESC

### DELETEINSURANCECOMPANY\_FSFS\_RES

Attribute	Description
Name	DELETEINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

### SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

### UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

### MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
Attribute	Description				
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
Attribute	Description				
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Response	

## Insurance-Company-Full

Attribute		Description	
Name		Insurance-Company-Full	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

*DELETEINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-PK*

*INSURANCE\_COMPANY\_NAME*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*



WARNING

WCODE

WDESC

## DELETEINSURANCECOMPANY\_IOPK\_RES

Attribute	Description
Name	DELETEINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name	ADDL		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	

## PARAM

Attribute		Description	
Name	PARAM		
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs	0	
	maxOccurs	unbounded	

## NAME

Attribute		Description	
Name	NAME		
Datatype	String		
Description			

## VALUE

Attribute		Description	
Name	VALUE		
Datatype	String		
Description			

## FCUBS\_BODY

Attribute		Description	
Name	FCUBS_BODY		
Datatype			
Description	This XSD Gives Information about PK Response		

## Insurance-Company-PK

Attribute		Description	
Name	Insurance-Company-PK		
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name	INSURANCE_COMPANY_NAME		
Datatype	string		
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### Insurance-Company-IO

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-IO
Datatype	
Description	

### INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

### ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

### ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

### EDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.5.ModifyInsuranceCompany

### 2.5.1.GE-ModifyInsuranceCompany-Req-Full-MSG.xsd

*MODIFYINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*



*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-Full*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*  
*FLDVAL*

## MODIFYINSURANCECOMPANY\_FSFS\_REQ

Attribute	Description
Name	MODIFYINSURANCECOMPANY_FSFS_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULEID						
Datatype	string						
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	nillable	true
Attribute	Description				
nillable	true				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Request of ModifyInsuranceCompany	

## Insurance-Company-Full

Attribute		Description	
Name		Insurance-Company-Full	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

#### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

#### CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.5.2.GE-ModifyInsuranceCompany-Req-IO-MSG.xsd

*MODIFYINSURANCECOMPANY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**MODIFYINSURANCECOMPANY\_IOPK\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string

Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	string				
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	string				
Description	This is the operation of the service which is being invoked. This field is case-sensitive.				
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	nillable	true
	Attribute	Description			
nillable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	string						
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nillable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

## SOURCE\_USERID

Attribute	Description
Name	SOURCE_USERID
Datatype	string
Description	This is the user id in the Source system who is performing the action.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTIRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION



Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
	maxOccurs	unbounded

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IO Request of ModifyInsuranceCompany	

## Insurance-Company-IO

Attribute	Description	
Name	Insurance-Company-IO	
Datatype		
Description		

## INSURANCE\_COMPANY\_NAME

Attribute	Description	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	
	<b>Description</b>	
	minOccurs	0
Restrictions	<b>Restrictions</b>	
	<b>Description</b>	
	maxLength	50

## ADDRESS\_LINE1

Attribute	Description	
Name	ADDRESS_LINE1	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

2.5.3.GE-ModifyInsuranceCompany-Res-Full-MSG.xsd

*MODIFYINSURANCECOMPANY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## **MODIFYINSURANCECOMPANY\_FSFS\_RES**

<b>Attribute</b>	<b>Description</b>
Name	MODIFYINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

## **SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "EXCLUDE"

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

**Insurance-Company-Full**

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**SHORT\_NAME**

Attribute	Description				
Name	SHORT_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**ADDRESS\_LINE1**

Attribute	Description
Name	ADDRESS_LINE1
Datatype	string

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	

Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	

Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

## FCUBS\_WARNING\_RESP



Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attribute	Attribute	Description
	maxOccurs	unbounded

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

### 2.5.4.GE-ModifyInsuranceCompany-Res-PK-MSG.xsd

*MODIFYINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-PK*

*INSURANCE\_COMPANY\_NAME*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## MODIFYINSURANCECOMPANY\_IOPK\_RES

Attribute	Description
Name	MODIFYINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		Attribute	Description
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about PK Response	

## Insurance-Company-PK

Attribute		Description	
Name		Insurance-Company-PK	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### Insurance-Company-IO

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-IO
Datatype	
Description	

### INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

#### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

#### UDFDETAILS

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.6.QueryInsuranceCompany

### 2.6.1.GE-QueryInsuranceCompany-Req-IO-MSG.xsd

*QUERYINSURANCECOMPANY\_IOFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-IO*  
*INSURANCE\_COMPANY\_NAME*

**QUERYINSURANCECOMPANY\_IOFS\_REQ**

<b>Attribute</b>	<b>Description</b>
Name	QUERYINSURANCECOMPANY_IOFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

<b>Attribute</b>	<b>Description</b>
Name	SOURCE

Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	string
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>
Name	SERVICE
Datatype	string
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	



Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of QueryInsuranceCompany

## Insurance-Company-IO

<b>Attribute</b>	<b>Description</b>
Name	Insurance-Company-IO
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### 2.6.2.GE-QueryInsuranceCompany-Res-Full-MSG.xsd

*QUERYINSURANCECOMPANY\_IOFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-IO*  
*INSURANCE\_COMPANY\_NAME*  
*Insurance-Company-Full*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## QUERYINSURANCECOMPANY\_IOFS\_RES

Attribute	Description
Name	QUERYINSURANCECOMPANY_IOFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	string

Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID



Attribute	Description	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	

Description	
-------------	--

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

## Insurance-Company-IO

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## Insurance-Company-Full

Attribute	Description
Name	Insurance-Company-Full
Datatype	
Description	

## INSURANCE\_COMPANY\_NAME

Attribute	Description	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SHORT\_NAME

Attribute	Description	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	255
	minLength	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	Attribute	Description
	minOccurs	0
	maxOccurs	unbounded

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attribute		
	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attribute							
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	maxOccurs	unbounded
Attribute	Description						
minOccurs	0						
maxOccurs	unbounded						

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attribute					
	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

## 2.7.ReopenInsuranceCompany

### 2.7.1.GE-ReopenInsuranceCompany-Req-Full-MSG.xsd

*REOPENINSURANCECOMPANY\_FSFS\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*



*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*Insurance-Company-Full*  
*INSURANCE\_COMPANY\_NAME*  
*SHORT\_NAME*  
*ADDRESS\_LINE1*  
*ADDRESS\_LINE2*  
*ADDRESS\_LINE3*  
*ADDRESS\_LINE4*  
*MAKER*  
*MAKERSTAMP*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*TXNSTAT*  
*AUTHSTAT*  
*UDFDETAILS*  
*FLDNAM*

**REOPENINSURANCECOMPANY\_FSFS\_REQ**

Attribute	Description
Name	REOPENINSURANCECOMPANY_FSFS_REQ
Datatype	
Description	

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

**MSGID**

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute	Attribute		Description
	minOccurs		0
	maxOccurs		unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Request of ReopenInsuranceCompany	

## Insurance-Company-Full

Attribute		Description	
Name		Insurance-Company-Full	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

#### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

#### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

#### CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

### 2.7.2.GE-ReopenInsuranceCompany-Req-IO-MSG.xsd

*REOPENINSURANCECOMPANY\_IOPK\_REQ*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*MAKER*

*MAKERSTAMP*

*MODNO*

## REOPENINSURANCECOMPANY\_IOPK\_REQ

Attribute	Description
Name	REOPENINSURANCECOMPANY_IOPK_REQ
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	string
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within EXCLUDE IIBS. In

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	string	
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	string	
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	

Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request of ReopenInsuranceCompany

**Insurance-Company-IO**

Attribute	Description
Name	Insurance-Company-IO
Datatype	
Description	

**INSURANCE\_COMPANY\_NAME**

Attribute	Description				
Name	INSURANCE_COMPANY_NAME				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>50</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

**MAKER**

Attribute	Description				
Name	MAKER				
Datatype	string				
Description					
Attribute	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>12</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

**MAKERSTAMP**

Attribute	Description	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	decimal	
Description		
Attribute	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	4

### 2.7.3.GE-ReopenInsuranceCompany-Res-Full-MSG.xsd

*REOPENINSURANCECOMPANY\_FSFS\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-Full*

*INSURANCE\_COMPANY\_NAME*

*SHORT\_NAME*

*ADDRESS\_LINE1*

*ADDRESS\_LINE2*

*ADDRESS\_LINE3*

*ADDRESS\_LINE4*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENINSURANCECOMPANY\_FSFS\_RES

Attribute	Description
Name	REOPENINSURANCECOMPANY_FSFS_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	string						
Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.						
Attribute	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
pattern	[A-Z_0-9]*	

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	length	3
pattern	[a-zA-Z_0-9]{3}	

## MODULEID

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	



Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	string	
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

## ADDL

Attribute		Description	
Name		ADDL	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0

## PARAM

Attribute		Description	
Name		PARAM	
Datatype			
Description			
Attribute			
		<b>Attribute</b>	<b>Description</b>
		minOccurs	0
		maxOccurs	unbounded

## NAME

Attribute		Description	
Name		NAME	
Datatype		String	
Description			

## VALUE

Attribute		Description	
Name		VALUE	
Datatype		String	
Description			

## FCUBS\_BODY

Attribute		Description	
Name		FCUBS_BODY	
Datatype			
Description		This XSD Gives Information about Full Response	

## Insurance-Company-Full

Attribute		Description	
Name		Insurance-Company-Full	
Datatype			
Description			

## INSURANCE\_COMPANY\_NAME

Attribute		Description	
Name		INSURANCE_COMPANY_NAME	
Datatype		string	
Description			

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## SHORT\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	SHORT_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE1

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE1	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE2

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE2	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE3

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE3	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## ADDRESS\_LINE4

<b>Attribute</b>	<b>Description</b>	
Name	ADDRESS_LINE4	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	decimal	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	totalDigits	4

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	string	
Description	Indicates Field Name	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	string	
Description	Indicates Field Value	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## ERROR

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ERROR	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

*REOPENINSURANCECOMPANY\_IOPK\_RES*

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Insurance-Company-PK*

*INSURANCE\_COMPANY\_NAME*

*Insurance-Company-IO*

*INSURANCE\_COMPANY\_NAME*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*



*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

## REOPENINSURANCECOMPANY\_IOPK\_RES

Attribute	Description
Name	REOPENINSURANCECOMPANY_IOPK_RES
Datatype	
Description	

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	string				
Description	This is the code for the system which has sourced this message. For request messages, this field has to contain the source code for the partner system as maintained within FLEXCUBE UBS. In case of response messages this field will contain "FLEXCUBE".				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	string				
Description	This is the component of FLEXCUBE for which this message is meant. Gateway supports both FLEXCUBE UBS and FLEXCUBE Investor Services. If the message is for FLEXCUBE UBS then this field should contain "FCUBS" and "FCIS" if meant for FLEXCUBE Investor Services. This field is case-sensitive.				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

## MSGID

Attribute	Description
Name	MSGID
Datatype	string

Description	This is the "unique" message ID for this message. In inbound messages, if this field is present then Gateway would perform technical duplicate recognition using this field. For all messages going out from Gateway, Gateway will populate a unique message ID in this field.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	string	
Description	This is the correlation ID for the message. Gateway supports 2 correlation patterns, namely "Message ID to Correlation ID" (M2C) and "Correlation ID to Correlation ID" (C2C). While using asynchronous means of communication (like a JMS queue), the partner system can correlate the response received from Gateway to the request message sent by it using this field. If the correlation pattern is M2C then this field will contain the MSGID of the request message. If the correlation pattern is C2C then this field will contain the CORRELID of the request message.	
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
nillable	true	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	string	
Description	This is the user id which will be used within FLEXCUBE to record the transaction. This needs to be a valid user id as maintained within FLEXCUBE.	
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
pattern	[A-Z_0-9]*	

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	string	
Description	This is the Branch of FLEXCUBE where the transaction would be recorded. This needs to be a valid Branch code as maintained in FLEXCUBE.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	string	
Description	This field is applicable only if messages are being sent to FCIS using Gateway. This is the module id of FCIS where the transaction will be recorded.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	string	
Description	This field should contain the code of the Service of FLEXCUBE which is being requested. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	string	
Description	This is the operation of the service which is being invoked. This field is case-sensitive.	
Attribute	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	string	
Description	This is the code for the operation being invoked in the Source system. The code of Source Operation being sent needs to be maintained as a valid Source Operation for the Source within FLEXCUBE.	

Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	string	
Description	This is the user id in the Source system who is performing the action.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	string	
Description	This the system for which this message is destined. In case of request messages to FLEXCUBE, it should be "FLEXCUBE". In case of response, the SOURCE from the request message is reproduced here.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	string	
Description	In response messages, this is the ID sent by FLEXCUBE in case any overrides are encountered. In request messages, the source system is expected to reproduce the MULTITRIPID from the earlier received response if the source system accepts the overrides.	
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	string	
Description	This is the function in FLEXCUBE which is being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	string	
Description	This is the action on the function being invoked. For integration scenarios this need not be sent. This is used by FLEXCUBE native user interface.	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	string	
Description	In response messages, FLEXCUBE will indicate the status of the request in this field. The various values are "SUCCESS", "WARNING" and "FAILURE".	
Attribute		
	Attribute	Description
	minOccurs	0
Restrictions		
	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	string	
Description		
Attribute		
	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attribute	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PK Response	

## Insurance-Company-PK

<b>Attribute</b>	<b>Description</b>	
Name	Insurance-Company-PK	
Datatype		
Description		

## INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
------------------	--------------------	--

Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### Insurance-Company-IO

<b>Attribute</b>	<b>Description</b>	
Name	Insurance-Company-IO	
Datatype		
Description		

### INSURANCE\_COMPANY\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	INSURANCE_COMPANY_NAME	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

### MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

### MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	string	
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions		
	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

Attribute		Description	
Name	MODNO		
Datatype	decimal		
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
Restrictions	<b>Restrictions</b>		<b>Description</b>
	totalDigits	4	

### FCUBS\_ERROR\_RESP

Attribute		Description	
Name	FCUBS_ERROR_RESP		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	minOccurs	0	
	maxOccurs	unbounded	

### ERROR

Attribute		Description	
Name	ERROR		
Datatype			
Description			
Attribute	<b>Attribute</b>		<b>Description</b>
	maxOccurs	unbounded	

### ECODE

Attribute		Description	
Name	ECODE		
Datatype	String		
Description			

### EDESC

Attribute		Description	
Name	EDESC		
Datatype	String		
Description			

### FCUBS\_WARNING\_RESP

Attribute		Description	
Name	FCUBS_WARNING_RESP		
Datatype			
Description			



Attribute		
	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	maxOccurs	unbounded

**WARNING**

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attribute		
	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

**WCODE**

<b>Attribute</b>	<b>Description</b>	
Name	WCODE	
Datatype	String	
Description		

**WDESC**

<b>Attribute</b>	<b>Description</b>	
Name	WDESC	
Datatype	String	
Description		



## FINANCIAL SERVICES

Gateway Documentation - ELInsuranceCompanyService  
[October] [2015]

Oracle Financial services Software Limited  
Oracle Park  
Off western Express Highway  
Goregaon(East)  
Mumbai,Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax:+91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2013], [2015], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.